





IBM Software Group

Add Your Own Tools to IBM WebSphere Development Studio Client for iSeries: Eclipse Plug-in Development

iSeries Application Development Team: IBM Toronto

 WebSphere software



Add your own tools: Eclipse Plug-in Development

© 2003 IBM Corporation

This presentation explains how to extend IBM WebSphere Development Studio Client for iSeries to add your tools.

Agenda

- Brief Introduction to Eclipse
- WebSphere Studio Workbench
- Extending the Workbench
 - Writing Eclipse plug-ins
 - HelloWorld plug-in example
- WebSphere Development Studio Client
 - iSeries Tools in the Workbench
 - Extending Development Studio Client
- Summary



IBM Software Group

What is Eclipse?


WebSphere. software



Add your own tools: Eclipse Plug-in Development

© 2003 IBM Corporation

What is Eclipse?



- Eclipse is an empty slate:
 - Except for the Java tools it supplies
 - Use it to build AD products
 - By writing "plug-ins" that offer tools for particular programming needs
 - Plug-ins "snap into" Eclipse seamless
 - Eclipse + useful plug-ins = product
 - Common base for all new IBM AD products
 - Common base for many new 3rd party products
- Eclipse is an opportunity
 - To build and sell plug-ins for all eclipse users
 - All users of Eclipse and Eclipse-based products

So what is Eclipse? With the exception of the built-in Java tools, Eclipse itself is not that interesting. It only gets interesting when you add to it some plug-ins (for example, tools) that do something interesting.

An Eclipse-based product is Eclipse plus a number of interesting plug-ins. IBM is building numerous such Eclipse-based products, including as we have seen Site Developer and Development Studio Client. Further, because Eclipse is free and business partners are free to include it in their products, there will be many other Eclipse-based products from other companies too, including Rational and TogetherSoft.

For business partners or software developers who write and sell application development tools, Eclipse is a fantastic opportunity. By writing plug-ins for Eclipse, those plug-ins can be sold to any developer using any product based on Eclipse or even just the raw Eclipse as downloaded from www.eclipse.org. This opportunity is not lost on iSeries tool vendors, who are all looking at offering Eclipse plug-ins for their tools. This will result in a rich offering of third party plug-ins for developers to choose from, all of which extend their core Development Studio Client development environment. One community, one core development platform, many IBM and 3rd party tools. This is community and excitement!

Eclipse Open Source Organization

- ★ An open source community chartered to manage the evolution of an open application development integration platform
- ★ Managed by an independent, multi-vendor organization
- ★ Technology licensed via the Common Public License
- ★ Based on Java with initial support for Linux & Windows
- ★ Broad Industry Support



An Open,
Extensible Tools
Integration Platform

IBM
Technology
Contribution



www.eclipse.org

Eclipse was developed by IBM and donated to the open source community. That donation is estimated to be worth \$40 million. Anyone can download Eclipse for free, including the source code, from www.eclipse.org. Eclipse has generated extraordinary excitement in the development community and the tools community. It is written in Java, and can be extended by tools that are also written in Java. These tools are known as plug-ins. Out of the box, Eclipse offers an integrated development environment (IDE) that has built-in support for teams and projects and a robust and revolutionary user interface framework. It also has tools built-in to create Eclipse plug-ins. Further, there are extensive and very powerful tools built-in for developing Java applications with Eclipse. So, if all you want is the world's best Java toolset, then all you need is Eclipse. You can't beat the price!





Eclipse Workbench

A 'Portal-like' Tool Integration Platform

A personalized, extensible development platform organized via developer

"Perspectives"



Some of the common services Eclipse supplies include: the Java integrated development environment (IDE), project management, debug, plug-in frameworks, desktop and help frameworks, and resource managers.



Eclipse – Broad Industry Support

Over 135 companies have been involved in the Eclipse project, including these industry leaders ...

- Altoweb
- Bowstreet
- BrowserSoft
- CommerceQuest
- Computer Assoc.
- Compuware
- Crystal Decisions
- Embarcadero
- Holosofx
- Instantiations
- LegacyJ
- Macromedia
- Merant
- Neuvis
- QSSL
- Rational
- Red Hat
- Serena
- Sitraka
- Skyva
- TeleLogic
- TogetherSoft
- Versant
- Versata
- Aldon
- MKS
- Softlanding
- Lansa
- ASC



www.Eclipse.org

"This has long been a dream of developers, and now IBM is providing the integration framework to make it possible."
 Arun Gupta, CTO, Neuvis Software

"The goal of Eclipse to provide a seamless interface where developers can leverage tools from multiple vendors is a great idea and is something that will add value to our customers. Eclipse is a great way to make it easy for iSeries customers to integrate WebSphere and leading development tools like LANSAS".

Bill Benjamin
 Vice President, Business Development
 LANSAS Inc.

Not a complete list!!

•MKS Comp

IBM is not alone with Eclipse. The open-source consortium that oversees contributions made to it include a number of large companies, and that list is growing. Note that MKS is an iSeries tool vendor. See www.eclipse.org for the latest list.



IBM Software Group

What is WebSphere Studio Workbench?

WebSphere. software



Add your own tools: Eclipse Plug-in Development


© 2003 IBM Corporation

WebSphere Studio Workbench

- Basis of all next-gen IBM AD products. Eg:
 - WebSphere Studio Site Developer
 - WebSphere Studio Application Developer
 - WebSphere Studio Integration Edition
- Available to IBM Business Partners
 - Via IBM PartnerWorld for Developers
 - ✓ To build/test plugins
 - ✓ To create products

Each product is a different "configuration" of WebSphere Studio

► Refers to product family




Here you see that Development Studio Client is based on WebSphere Studio Site Developer, while Development Studio Client Advanced is based on WebSphere Studio Application Developer.

The Workbench is based on the open-source Eclipse technology about to be discussed. It is not for sale, but is the basis of all IBM WebSphere Studio products, and is available to business partners.

Site Developer is IBM's entry level offering based on eclipse, and it is for building dynamic Web sites out of non-EJB Java. Application Developer extends Site Developer and adds support for EJBs. Application Developer-Integration Edition extends Application Developer and adds support for JCA Connectors and for Workflow. Enterprise Developer extends Application Developer-Integration Edition and adds support for S/390 and Enterprise Generation Language (EGL), the follow-on to VisualAge Generator.

WebSphere Studio Workbench (WSWB)

A fundamental change in AD Tooling paradigm




Challenges

- ▶ Difficulty of integration
- ▶ Different Semantics, UI etc
- ▶ Different repositories
- ▶ Not best-of-breed Tool Services
- ▶ Difficult to manage
- ▶ Slow to Market


Benefits

- ▶ Easier integration
- ▶ Single view/mgmt
- ▶ Common look and feel
- ▶ Best-of-breed Tool Services
- ▶ Tool builder focus on tool functions
- ▶ Fast to Market



New WebSphere Studio Site Developer


- ★ For professional developers of dynamic Web applications & sites
- ★ Delivers integrated support for open Web standards, including Java, JSP, XML, Rich Media & Web services tools






New WebSphere Studio Application Developer

- ★ For professional developers of Java & J2EE applications, requiring integrated Web, JSP, XML & Web services support
- ★ Advanced tools for code generation, performance tuning & quality
- ★ Includes a highly integrated WebSphere Application Server test environment and deployment automation tools



New WebSphere Studio Integration Edition

- ★ For developers & integrators of advanced J2EE & Web services
- ★ RAD tools for visual application modeling, composition & adaptability (e.g., business rules)
- ★ Advanced EAI tools for generating adapters & dynamic microflows including integration of remote host assets






IBM Software Group

Eclipse Technology and Terminology

WebSphere. software



Add your own tools: Eclipse Plug-in Development

© 2003 IBM Corporation

Workbench




- Perspectives
 - Contain views and editors
 - Are named and have default layout of the views/editors
 - Are targeted towards a specific type of development, i.e. Java, XML, Help, Debug, WebFacing, ...
- Editors
 - That open, edit, save and close files
 - Can contribute to the Workbench menu bar and tool bar
- Views
 - That display information
 - Can have their own toolbars
 - Updates saved automatically
- Miscellaneous
 - Actions, Menus, Toolbars, Wizards, Properties, Preferences

Workspace

- Workspace is the term given to refer to all development resources currently accessible in the Workbench
- Eclipse Resource Workspace
 - Resources = Projects + Folders + Files
 - Projects map to a folder in local file system
 - Projects contain folders and files
 - Folders contain folders and files
 - Projects are typed
 - Resources are versioned as they change
 - User can compare and restore versions
 - Resources can have properties
 - Properties are displayed in the properties view



Workbench Overview



The screenshot shows the Eclipse IDE interface with several callouts pointing to specific features:

- Global tool bar and menu bar:** Points to the top navigation bar containing menus like 'Navigate', 'Search', 'Project', 'Run', 'XML', 'Window', and 'Help', along with a toolbar of icons.
- Open perspectives:** Points to the vertical toolbar on the left side of the workbench, which contains icons for different development perspectives.
- Pull down menu for a view:** Points to a dropdown arrow in the Package Explorer view.
- Resources:** Points to the Package Explorer view on the left, showing a project tree with folders like 'TradeTutorial' and 'WHOLESALE Database'.
- Editor:** Points to the main central area where the XML file 'PurchaseOrder.xml' is being edited.
- Local tool bar for a view:** Points to a toolbar located at the bottom right of the Package Explorer view.
- Views:** Points to the 'Tasks' and 'Properties' tabs at the bottom of the IDE.

The Editor view displays the following XML content:

```

<purchaseOrder orderDate="2001-01-01" xmlns:po="http://www.ibm.com" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="http://www.ibm.com PurchaseOrder.xsd">
  <shipTo>
    <country>US</country>
    <name>Alice Smith</name>
    <street>125 Maple Street</street>
    <city>Mill Valley</city>
    <state>CA</state>
    <zip>90952</zip>
  </shipTo>
  <billTo>
    <name>Hurry, my</name>
    <items>
      <item>
        <partNum>872-AA</partNum>
        <productName>Lawnmower</productName>
      </item>
    </items>
  </billTo>
  <po:comment>
    <item>
      <productName>
    </item>
  </po:comment>
</purchaseOrder>

```

The Properties view at the bottom shows the following table:



| Property | Value |
|---------------|---|
| editable | true |
| last modified | 20/05/03 6:34 PM |
| name | PurchaseOrder.xml |
| path | /XMLEditProject/PurchaseOrder/PurchaseOrder.xml |
| size | 1081 |

The Eclipse workbench has four open perspectives. You can see them lined up on the left frame of the workbench. The current active perspective is the one whose icon is indented, which in this case is the Java perspective. To open a new perspective, you use Window->Open Perspective giving you the Select Perspective dialog that you saw previously. This particular perspective has a Package Explorer view which drives the Editor and the Outline view.




Using Eclipse

Start by opening a perspective based on the type of development they are working on.





Then create new resources (projects, files and folders) using the "New" wizards

Work with your resources using the Navigator view. The Navigator view shows all resources. Often it is easier to use a local view which filters out projects that are not related. For example the "Packages view" shows only Java projects.



Eclipse Team Support

- Users create and work with **projects**
 - Contain **folders** and **files**
 - Which are versioned as they change
 - Are “typed” and have type-unique tooling 
 - Are **synchronized** between local workspace and team repository



Central to the Eclipse integrated development environment is support for projects. Projects are simply a grouping of folders and files.

Plug-ins have types, such as Java or Web or XML. Tools that plug into Eclipse can define their own new project types. Tools that plug into Eclipse work against resources (folders or files) within projects. They can be scoped to projects of a particular type, if appropriate.

All projects, regardless of type, have common behavior and support. This includes the ability for a team to share a project by using an Eclipse-supporting software change management (SCM) product such as Concurrent Version System (CVS) or Rational Clearcase. This SCM acts as a central repository for one or more projects. Each team member can easily keep their local copy of any project "in synch" with the central repository copy. CVS is a free open-source SCM. It runs on Linux, UNIX and Windows. It comes on the Linux distribution CDs for iSeries Linux LPAR.

All IBM SCM vendors for iSeries are enabling, or have enabled, their products to Eclipse.



IBM Software Group

Developing Eclipse Plug-ins

WebSphere. software



Add your own tools: Eclipse Plug-in Development

© 2003 IBM Corporation

Plug-in Development

- You add functions to the Workbench by developing plug-ins
- Plug-ins
 - Highest level of organization / structure for adding functionality to the Workbench
 - WebFacing plug-in
 - Remote Systems Explorer plug-in
 - Web Tooling plug-in
 - iSeries extensions to Web Tooling plug-in
 - ...
 - A collection of files which implement your desired function
 - Plugin installed by copying your files to a subdirectory of <root>/plugins
 - There are built in tools for installing new plug-ins
 - Described by the plugin.xml file
 - Eclipse will look for this file in all subdirectories of <root>/plugins
 - Describes what function(s) your plug-in is adding to the Workbench

Anatomy of a Plug-in

- Files typically found in a plug-in

| | |
|---|---------------------------------------|
| <root>/plugins/com.ibm.example/ plugin.xml | - describes the plug-in |
| plugin.properties | - translatable strings for plugin.xml |
| example.jar | - Java code for the plug-in |
| example.properties | - translatable strings |
| HelpContexts.xml | - structure for F1 help |
| doc.properties | - translatable strings for help |
| doc/ *.html | - plug-in documentation |
| nl/ en_US/ ... | - NL versions of .properties files |
| icons/ ... | - graphics files for your plug-in |



Example Anatomy of a Plug-in

The screenshot displays a Windows Explorer window titled "D:\WDS\series\eclipse\plugins\com.ibm.etools.iseries.core_5.0.1". The address bar is circled in red. The left pane shows a tree view of folders, with "com.ibm.etools.iseries.core_5.0.1" selected. The right pane shows the contents of this folder, including "plugin.properties" and "plugin.xml", which are circled in red. The status bar at the bottom shows "39 object(s) (Disk free space: 417 MB)" and "10.5 MB".

23 | Add you own tools | Eclipse Plug-in Development | © 2003 IBM Corporation

Plugin.xml File


- An XML file that describes:
 - Prerequisite plug-ins
 - Jar files shipped with your plug-in
 - Extension points implemented by your plug-in
 - Declares new extension points added by your plug-in
- Required for every plug-in
- Special plugin.xml editor included in the Eclipse plug-in development environment

Extension Points

- Allow you to add functions to the workbench
 - Declared in the plugin.xml file
 - Associated Java code is shipped in JAR files
 - First you need to find the extension point for the new function you want to add
 - Workbench extension points are documented in the online help
 - Includes the XML DTD for the extension point and example XML code



Extension Points





Example Extension Points

Help - WebSphere Development Studio Client Advanced Edition for iSeries

Search: [Advanced Search](#)

Contents [Home](#) **Tool developer information**

- [-] Tool developer information
 - [-] Extending the platform
 - [-] Programmer's Guide
 - [-] Reference
 - [-] API Reference
 - [-] Extension Points Reference
 - [-] Platform Runtime
 - [-] Workspace
 - [-] Workbench
 - [-] Team
 - [-] Debug
 - [-] Help
 - [-] Other
 - [-] Other Reference Information
 - [-] Examples Guide
 - [-] Questions Index
 - [-] Extending the Java tools
 - [-] Plug-in Development Environment
 - [-] Help System Example
 - [-] GEF Developer's Guide
 - [-] Draw2D Developer's Guide

Workbench

- [org.eclipse.ui.acceleratorConfigurations](#)
- [org.eclipse.ui.acceleratorScopes](#)
- [org.eclipse.ui.acceleratorSets](#)
- [org.eclipse.ui.actionDefinitions](#)
- [org.eclipse.ui.actionSetPartAssociations](#)
- [org.eclipse.ui.actionSets](#)
- [org.eclipse.ui.decorators](#)
- [org.eclipse.ui.dropActions](#)
- [org.eclipse.ui.editorActions](#)
- [org.eclipse.ui.editors](#)
- [org.eclipse.ui.elementFactories](#)
- [org.eclipse.ui.exportWizards](#)
- [org.eclipse.ui.importWizards](#)
- [org.eclipse.ui.markerHelp](#)
- [org.eclipse.ui.markerResolution](#)
- [org.eclipse.ui.newWizards](#)
- [org.eclipse.ui.perspectiveExtensions](#)
- [org.eclipse.ui.perspectives](#)
- [org.eclipse.ui.popupMenus](#)
- [org.eclipse.ui.preferencePages](#)
- [org.eclipse.ui.projectNatureImages](#)
- [org.eclipse.ui.propertyPages](#)
- [org.eclipse.ui.resourceFilters](#)
- [org.eclipse.ui.startup](#)
- [org.eclipse.ui.viewActions](#)
- [org.eclipse.ui.views](#)
- [org.eclipse.ui.workingSets](#)

Team


- [org.eclipse.team.core.fileTypes](#)

Documentation for Workbench extension points is available in the online help under **Tool Developer Information**

Add your own popup menus to the Workbench



Extension Point Documentation



Export Wizards

Identifier: org.eclipse.ui.exportWizards

Description: This extension point is used to register export wizard wizards appear as choices within the "Export Dialog", and are used from the workbench.

Wizards may optionally specify a description subelement whose body text about the wizard.

Configuration Markup:

```
<!ELEMENT wizard (description? selection*)>
<!ATTLIST wizard
  id CDATA #REQUIRED
  name CDATA #REQUIRED
  class CDATA #REQUIRED
  icon CDATA #IMPLIED
>
<!ELEMENT description (#PCDATA)>
```

- **id** - a unique name that will be used to identify this wizard.
- **name** - a translatable name that will be used in the dialog box to represent the wizard.
- **class** - a fully qualified name of the class that implements

DTD description for the XML to declare the extension point in your plugin.xml file

Actual XML examples are shown farther down the page!

Hello World Plug-in Example

- Create a new plug-in project
- Examine the Plug-in Development perspective
- Add a menu and menu item to the main menu
- Supply an action for the menu item that displays a message box

Now lets walk through an example



Creating a new Plug-in Project

New
Select
Create a Plug-in Project

- Component Test
- Data
- EJB
- Series
- J2EE
- Java
- Plug-in Development**
 - Remote File Transfer
 - Server
 - Simple
 - Symptom Database
 - Web
 - WebFacing
 - Web Services
 - XML
 - Examples

New Plug-in Project

Plug-in Project Name
Select the name of the new plug-in project (e.g. 'com.example.xyz'). By default, this name will also be used for the plug-in ID.

Project name:

Project contents:
 Use default

Directory:

Use the "New" wizard to create a new Plug-in project

By convention your plug-ins should start with the reverse of your Internet domain name. For example: com.ibm...



Creating a New Plug-in Project

New Plug-in Project
Plug-in Project Structure
 Define essential plug-in structure settings

Plug-in Id:

Java builder output:

Plug-in runtime library:

Source folder:

< Back Next > Finish Cancel

New Plug-in Project
Plug-in Code Generators
 Select the wizard that will generate the initial plug-in code

Create a blank plug-in project

Create a plug-in project using a code generation wizard

Available code generation wizards

- Custom plug-in wizard
- Default Plug-In Structure
- Hello, World!
- Plug-in with a multi-page editor
- Plug-in with an editor
- Plug-in with a popup menu
- Plug-in with a property page
- Plug-in with a view
- Plug-in with perspective extensions

This wizard creates standard plug-in directory structure and adds the following:

- **Action set.** This template creates a simple action set that adds **Sample Menu** to the menu bar and a button to the tool bar. Both the menu item in the new menu and the button invoke the same **Sample Action**. Its role is to open a simple message dialog with a message of your choice.

Extensions Used

- org.eclipse.ui.actionSet

< Back Next > Finish Cancel



Creating a New Plug-in Project

New Hello World plug-in project

Simple Plug-in Content
Enter the required data to generate initial plug-in files

Plug-in name: MyPlugin Plug-in
 Version: 1.0.0
 Provider Name: EXAMPLE
 Class Name: com.example.MyPlugin.MyPluginPlugin
 Generate code for the class

Plug-in code generation options
 Add default instance access
 Add support for resource bundles
 Add access to the workspace

< Back Next > Finish Cancel

New Hello World plug-in project

Sample Action Set
This template will generate a sample action set extension with a menu, a menu item and a tool bar button.

Java Package Name: com.example.MyPlugin.actions
 Action Class Name: SampleAction
 Message Box Text: Hello, Eclipse world
 Add the action set to the resource perspective

< Back Next > Finish Cancel



Plug-in Development Environment

Plugin project

Plug-in development perspective

plugin.xml Editor


Implementation of the actionSets extension point to provide the popup menu

Customized editor pages to help you define extensions, runtime jar files, dependencies, ...

Defining the Extension


Use the “Extensions” page of the plug-in editor to define your implementation of an extension point

Or use the source tab to manually enter the XML (ouch)!



Plug-in Build Path

Right click on the PDE project and select properties to get this dialog



ECLIPSE_HOME is a variable that points to the directory where Eclipse (the workbench) is installed.

.jar files required for the plug-in to build (SWT, JFace, ...)

Action Class (Invoked by the Popup Menu)

actionSet extension point requires the class to implement the IWorkbenchWindowActionDelegate interface

```

public class SampleAction implements IWorkbenchWindowActionDelegate {
    private IWorkbenchWindow window;


    /**
     * The constructor.
     * Our sample action implements workbench action delegate. The action proxy will be created by the
     * workbench and shown in the UI. When the user tries to use the action, this delegate will be
     * created and execution will be delegated to it.
     * See Also:
     */
    /**
     * The action has been activated. The argument of the
     * method represents the 'real' action sitting
     * in the workbench UI.
     * See IWorkbenchWindowActionDelegate#run
     */
    public void run(IAction action) {
        MessageDialog.openInformation(
            window.getShell(),
            "MyPlugin Plug-in",
            "Hello, Eclipse world");
    }
}
    
```

JFace MessageDialog class

run method(...) is invoked when the popup menu is selected

| Description | Resource | In Folder | Location |
|---|-----------------|------------------------------|----------|
| Broken Link - strutsEGL.UpdateAccoun... | struts-confi... | TradeTutorial/Web Content... | line 40 |
| Broken Link - /wfprof/services/ReportS... | eservices.css | WebFacing Project/Web Co... | line 21 |

Testing Your Plug-in




The screenshot shows the Eclipse IDE interface. The Package Explorer on the left displays a project named 'com.example.MyPlugin' with sub-packages 'src' and 'test'. The 'Run As' menu is open, showing options: '1 Java Application', '2 Remote Java Application, in iSeries view', '3 Java Application in iSeries Server', '4 Unit Test', '5 Run-time Workbench', and '6 Java Bean / Applet'. The 'Run-time Workbench' option is highlighted. The Properties view on the right shows details for the selected plug-in, including Plug-in Id, Plug-in Name, Version, Provider Name, and Class. The Outline view on the far right shows the project's dependency tree.

1. Select any plug-in project
2. Use the Run As -> Run-time Workbench menu item to launch a new instance of the Workbench with your plug-in(s) loaded.

- ▶ Use Debug-> Run-time Workbench to debug your plug-in
- ▶ Set breakpoints in the Java source editor before or after launching the debugger




It Works!



Brand new copy of the Workbench running with your plug-in

User Interface

- User Interface for plug-ins should be done using SWT and JFace
 - Provides the best integration with the Workbench
- SWT is a new Java widget toolkit
 - Different than AWT and Swing
- JFace is a UI Framework built on top of SWT for creating wizards, editors, views, dialogs, preference pages,



User Interface

- SWT
 - Fast
 - Native operating system look and feel
 - Provides all the common UI widgets
 - Button, Label, Menu, MenuItem, ProgressBar, ...
- JFace
 - UI frameworks built on top of SWT
 - Provide a higher level of abstraction so you can focus on your added function, not UI details
 - Provide a common look and feel across all Workbench tools
 - Wizards, ..., preference pages all look and act the same
 - Provides base set of classes you can extend to add your specific function

User Interface - JFace

- Text Framework
 - Framework for providing source (text) editors
 - Provides support for
 - Content assist, syntax highlighting, formatting, ...
- Viewer Framework
 - Different types of views into a data model
 - TreeViewer, CheckboxTreeViewer, TableViewer, ...
- Contribution Framework
 - Framework for adding actions to the workbench toolbar and menubar
- Dialog Framework
 - Framework for creating dialogs that interact with the user
 - Example classes:
 - PreferenceDialog, PropertyDialog, WizardDialog, ...
 - Also provides pages for using inside the dialogs
 - PreferencePage, PropertyPage, WizardPage, ...



IBM Software Group

Other Things to Consider

WebSphere. software



Add your own tools: Eclipse Plug-in Development

© 2003 IBM Corporation


HELP!!! – Lots of ways to provide help

- **Tooltip help**
 - Also known as "fly-over help"
 - Tooltip is shown when user hovers the mouse pointer over a menu item, button, entry field, ...
 - Use the `setToolTipText(String text)` method on a widget
- **F1 key help**
 - Context sensitive help
 - Typically used to provide a short description of the current task when the user presses F1 in a view, dialog, wizard, entry field
 - Set context ids using `WorkbenchHelp.setHelp(...)`
 - Eclipse then looks up the context id in HelpContexts.xml
- **Full blown online help**
 - You can provide complete online documentation integrated into the *Help* perspective
 - This is full topic on its own

Team Extension Points

- Version / Configuration Management
 - Allows source management providers to plug into the workbench
 - Can be used with by any project in the Workspace without any additional work
 - Java projects, Web projects, iSeries projects, ...

Open source CVS implementation of the VCM APIs is provided as a reference implementation





IBM Software Group

What about the iSeries?

WebSphere. software



Add your own tools: Eclipse Plug-in Development

© 2003 IBM Corporation



WebSphere Development Studio V5

| | |
|-------|----------------------|
| RPG | COBOL |
| C/C++ | PDM, SEU SDA, RLU |

V5R1 or V5R2
5722-WDS
No-cost V4 Upgrade 5903

Unlimited Licenses

| | | | | | |
|---------|-----------|---------------|-------------|------------|------------------|
| iSeries | iSeries | iSeries | iSeries | Web Facing | iSeries Projects |
| Java | Debug | Struts Web | Web Service | | RSE |
| Trace | Profiling | DB | XML | App Server | |

+CODE
+VisualAge RPG

WebSphere Development Studio Client V5

There is now only one application development product sold by IBM, for iSeries, as of V4R5. This is WebSphere Development Studio (Development Studio), which includes all four host compilers, all traditional tools (ADTS = PDM+SEU+SDA+RLU+DFU+AFP+CGU), and unlimited licenses of the workstation-based toolset named WebSphere Development Studio Client (formerly WebSphere Development Tools).

If you are an existing customer who has a subscription, you can upgrade to Development Studio free of charge. Without a Software Subscription, there is an upgrade fee. New licenses of Development Studio are priced very competitive compared to the combined prices of all constituent products. As of V5R1, there is no way to purchase the compilers or tools individually. So if you have RPG at V5R1 or higher, you must have Development Studio and hence are entitled to Development Studio Client.

For consultants who do not have an iSeries of their own, but still wish to have the client tools, Development Studio Client is also made available as a passport advantage product so it can be purchased "off the shelf" from IBM Direct.

Development Studio has been a huge success, with over 80,000 licenses sold. Just as every development machine used to have PDM and SEU, every development machine will now have all the modern Application Development tools from IBM. This ubiquity is especially important for business partners who build and sell software. These Business Partners are now free to build software using any of the technologies or tools in Development Studio, and can assume their customers will have the tools required to tailor everything from RPG to Java and Web user interfaces. This effectively raises the lowest common denominator to a level unparalleled by any other operating system.

RPG and COBOL Tools

- **Remote Systems Explorer**



- For random drill-down or filtered access to remote:
 - Library, objects and members in QSYS
 - IFS Folders and Files
 - Linux (including LPAR), Unix and Windows Folders and Files
 - Local Folders and Files
- For remote command execution of
 - QSYS Commands
 - QShell Commands
 - Linux, Unix and Windows Commands
- For exploration of Jobs in QSYS

- **iSeries Projects and Navigator**

- For structured, project-based development
- Local team-sharable project
- Holds source files and source members and save files
- Push action to copy local files to associated library


Remote System Explorer Perspective

- **Manages connections to remote systems**
 - Where you create and manage connection information
 - Connections subsequently used in all iSeries tools
 - Start by using the New Connection wizard
 - Connection appears in tree view
 - Expand it to see "subsystem" -> functional groupings



iSeries Connection Properties

- Use Properties of iSeries
Commands to set:
 - Library list information
 - Current library
 - Initial command to call
 - Environment variables
- All information is applied at connect time



iSeries Connection Subsystems

- Expand a connection in the to see subsystems:
 - **iSeries Objects**
 - **iSeries Commands**
 - **iSeries Jobs**
 - **IFS Files**

iSeries Objects

Like WRKXXXPDM. For drilling down on libraries, objects, mbrs
Right click offers wealth of actions like create, rename, delete...
Can edit source members using built-in LPEX or classic CODE
Can create User Defined Actions just like in PDM

iSeries Commands

For creating command sets containing one or more CL commands
Right click and select Run to remote run commands
Results are logged in Command console

iSeries Jobs

For seeing jobs, filtered by number, user ID or status
Right click to do common actions on jobs, such as end or hold

IFS Files

For drilling down on IFS folders and files
Right click offers wealth of actions like create, rename, delete...
Can edit source members using built-in LPEX or classic CODE



- Expand a filter to see objects resulting from resolution of filter
- Drill down through libraries, and source files to get to members
- Right click on libraries, objects and members to get actions

Built-in Remote Systems LPEX Editor

Various iSeries specific views for showing additional information.
iSeries Error List shows compile / verify errors

Remote System Explorer - WebSphere Development Studio Client Advanced Edition for iSeries

File Edit Source Compile Navigate Search Project Run Window Help

Remote Systems

Global Definitions

Files

ORDENTD :
ITEM : DISK
DSTRCT : D
CSTMTR : DI
STOCK : DI
STRCD
ORDERS : C
ORDLIN : D

Data Structures

Constants

Indicators

Fields

Main Procedure

Subroutines

*INZSR
ADDORDER
ADDORDHD
ADDORDLIN

Row 117 Column 1 Replace

```

011700 *
011800 *
011900 CSR RqsCust BEGSR
02000 *
02100 *
021200 * Display the prompt for a customer
02200 C WRITE FKEY
02300 C EXPMT PROMPT
02400 *
02500 *
02600 * Clear error indicators
02700 C EXSR ClrError
02800 *
02900 * Process the user's request ...
03000 C *IN03 CASEQ *ON
03100 C *IN04 CASEQ *ON
03200 C *IN12 CASEQ *ON
03300 C CAS
03400 C ENDCS
03500 *
    
```

Verify program action completed with informational

iSeries Error List - <S105VM2M>WFLAB29/QRPGLESRC(ORDENTR)

| ID | Message | S... | L... | Location | Conne... |
|-----------|---------------------------------------|------|------|----------------|----------|
| i RNF7031 | The name or indicator CUSTLNAME... | 0 | 72 | WFLAB29/QRP... | S105V... |
| i RNF7031 | The name or indicator IDATA is not... | 0 | 5 | WFLAB29/QRP... | S105V... |
| i RNF7031 | The name or indicator PARTPRICE i... | 0 | 83 | WFLAB29/QRP... | S105V... |
| i RNF7150 | Record STRCD in file STOCK contai... | 0 | 31 | WFLAB29/QRP... | S105V... |
| i RNF7086 | RPG handles blocking for file ORDE... | 0 | 32 | WFLAB29/QRP... | S105V... |

Remote Systems Team

Tasks | iSeries Comman... | iSeries Listings | iSeries Error List | Remote Comma... | Spooled Files | Properties | iSeries Job Log

WFLAB29/QRPGLESRC(ORDENTR) MBRTYPE(RPGLD) - Parts Order Entry - data.entrv

RSE: Filters and Filter Pools

- Expand a subsystem to see "filters"
 - Like WRKXXXPDM generic name filters but
 - Are named and saved
 - There are some predefined
 - Such as Library List to see *LIBL libraries in iSeries Objects
 - Such as popular commands in iSeries Commands
 - To create your own, right click on subsystem object
 - Each filter can contain multiple filter strings
 - So you can list all libraries that start with A *and* B
- Eventually, you'll have too many filters
 - Time to turn on "Show Filter Pools" via preferences
 - Expanding subsystems will then first show filter pools
 - Filters are grouped into named pools
 - By default they are added to the single default filter pool
 - You can create your own filter pools
 - Then add filters to it
 - Expand a filter pool to see just the filters in it


iSeries Objects Subsystem Filters

- **Library List filter**
 - Displays library list
 - Provides popup actions for working with the library list
- **Library filters**
 - Specify simple, generic or special library names
 - Lists all matching libraries, when expanded
- **Object filters**
 - Specify simple or generic object names, library-qualified
 - Library name can be simple, generic or special
 - Specify simple or generic object types and attributes
 - Can specify one or more type:attribute pairs (OR operation)
 - Lists all objects that meet criteria, when expanded
- **Member filters**
 - Specify simple or generic member names, lib/file-qualified
 - Library name and file name can be simple or generic
 - Specify simple or generic member types
 - Can specify one or more member types (OR operation)
 - Lists all members that meet criteria, when expanded

Remote Systems LPEX Editor


- Remote Systems LPEX Editor
 - Re-write of CODE Editor for Eclipse
- What it has today:
 - All base support from CODE Editor, such as:
 - Alt+L/C/M/D/U/S/J to select/copy/move/delete/unselect/split/join
 - Select streams, lines, blocks and rectangles (Edit menu)
 - Command-line for directly entering editor commands
 - Keystroke recording for repetitive tasks
 - Compare utility
 - Rich search, find and replace
 - Bookmarks and quick marks
 - Ctrl+L to locate a line
 - Line-number prefix area
 - File->Get File to import a file
 - Filter Selection to only show lines containing selected text
 - Plus!
 - Outline view support for ILE RPG and COBOL
 - Content assist for ILE RPG

Underlying Model of the RSE



Profiles enable team support and effective grouping

iSeries Projects Perspective



Create iSeries Project **Create Source File** **Create Source Mbr**

iSeries Project

Source Physical File

Source Members


iSeries Project navigator: expand project to work with local source

Remote Systems view for convenience

56 Add you own tools | Eclipse Plug-in Development © 2003 IBM Corporation

Here we see the iSeries Projects perspective, which you can explicitly open. The primary view is the iSeries Navigator that allows exploration of all existing iSeries Projects. There are wizards launchable from the toolbar for creating a new iSeries Project, or creating source physical files and source members within an existing project. The iSeries Projects perspective includes a full copy of the Remote Systems Explorer, as a view, for your convenience. This allows you to easily work with the contents of the associated library while simultaneously working with the local copies of the source within the project.

New iSeries Project Wizard



Give your project a name

Choose connection from RSE list

Identify Associated Library: this is the target library for pushes and builds

Here we see the rest of the iSeries Project wizard. First, give the project a name. Any name you want! Then select or create a connection (from the RSE!) that identifies the iSeries with which this project is associated. Also select the library on that iSeries where the contents of this project will be pushed to. Also, specify a CL command to call for the "Build" action. If you don't have such a CL command, enter a dummy value or leave it blank.

iSeries Project Wizard

Build style controls how the iSeries project is built on the remote system

New

iSeries Project Properties
Select and configure the active build style for this project.

Active build style:
CL Program
Command
*NONE

Configure...

This build style will upload CL programs specified in the configuration, compile them, and then run them to build this project. The compile commands can be automatically generated.

Provided by IBM plugin "iSeries Tooling - Styles Plugin" version 5.0.0

< Back Next > Finish Cancel

CL Program Build Style Configuration

Enter the project's source file that contains the COMPILE.CCLE and BIND.CCLE members that will be uploaded to build this project.

Build Source File:
QCLSRC

Automatically generate COMPILE.CCLE prior to each build
 Automatically push all changed members prior to build

OK Cancel

Specify Build Style and style configuration parameters for iSeries Project

more information on next slide ...

Command Build Style Configuration

Enter the command to be executed to build this project.

Build Command:
|

Automatically push all changed members prior to build

OK Cancel

Here we see the rest of the iSeries Project wizard. First, give the project a name. Any name you want! Then select or create a connection (from the RSE!) that identifies the iSeries with which this project is associated. Also select the library on that iSeries where the contents of this project will be pushed to. Also, specify a CL command to call for the "Build" action. If you don't have such a CL command, enter a dummy value or leave it blank.

iSeries Projects Build Styles

- **Build Styles**
 - Specify how to build the iSeries project on the remote system
 - Three IBM-supplied build styles
 - CL Program**
 - Automatically generates COMPILE.CLLE and BIND.CLLE
 - Adds compile command for each source file in project
 - Uses last compile command from RSE for specified source type
i.e. CRTBNDRPG versus CRTRPGMOD
 - At build time these two members are pushed to iSeries, compiled and run
 - Command**
 - You specify single command to run build
 - Good if you have an existing build script
 - *NONE**
 - No build support
- **ISVs can plug-in additional build styles**
 - To work with their existing iSeries systems

Here we see the wizard for creating a new iSeries source physical file. Within the project, this is actually a folder. When the project is pushed to its associated library, this result in a CRTSRCPF command being run to create a file with the attributes specified in this wizard.

Project "Bleedthrough"

The screenshot displays the WebSphere Development Studio Client for iSeries interface. The 'iSeries Project Navigator' on the left shows a project named 'WHOLESALE' containing several files and members. A context menu is open over the project, listing various actions such as 'New', 'Go Into', 'Copy', 'Delete', and 'Show Remote Objects'. A callout box with the text 'Currently showing only local resources' points to the 'Show Remote Objects' menu item. The main editor window shows a table with columns for 'Row', 'Column', and 'Replace', containing data for various fields like 'DName', 'Dquant', 'Dpart', 'Ds', 'DR', 'Dprice', 'open', 'Eval', 'callp', and 'DSPLY'. The 'Properties' window at the bottom right shows details for the selected project, including its name 'WHOLESALE' and path '/WHOLESALE'.

Here we see an iSeries project in the iSeries Navigator, within the iSeries Projects perspective, that has a number of local files and members. Right-clicking on the project or anything in the project, gives a popup menu with the all-important "Show Remote Objects" menu item....

Local and Remote Objects

iSeries Project navigator:

- ▶ local files and members
 - Use Push popup menu action to copy from project to library
 - Use Build to build project
 - Use Team->Sync to copy to/from team repository
- ▶ remote objects, files and mbrs
 - Use Add to Project to copy from library to project

(Remote) =>

- ▶ only exists in associated library

(Local/Remote) =>

- ▶ exists locally and in associated lib

(Local/Remote) =>

- ▶ conflict between local and remote

otherwise =>

- ▶ only exists locally


Once "Show Remote Objects" is enabled (it is a toggle) all the objects in the associated library for this project are shown in the iSeries Navigator.

This navigator is called a "bleed through" view because it lists both local files/members and remote objects, files and members. However, if a file or member exists both locally and remotely, it is not shown twice. Rather, it is only shown once, and its icon and bracketed text identify it as existing in both places.

The icons and text enable you to see at a glance which files/members exist only locally, only remotely, or both locally and remotely. In the latter case, the color of the icon indicates if the two are in synch or not. If not, it is an indication you need to "push" your local source to the associated library to get it in synch.

iSeries Projects Remote Build

- **Submit Build**
 - Submits build of iSeries project on remote system
 - Adds build job to iSeries Build Job Status view



The screenshot shows the "iSeries Build Job Status" dialog box. It contains a table with columns for Date/Time Submitted, Job, Project, and Status. A context menu is open over the second row, showing options: Cancel, Retrieve Errors, and Remove. A refresh interval of 10 seconds is indicated at the bottom of the dialog.

| Date/Time Submitted | Job | Project | Status |
|----------------------|----------------------|-------------|----------|
| 30-Mar-03 9:29:02 PM | 923621/YANTZI/YANTZI | WH01 P5A1 F | Finished |
| 30-Mar-03 9:30:08 PM | 923623/YANTZI/YANTZI | | Queued |

Callouts in the image:

- Job where build is running**: Points to the Job column in the table.
- Status of the build**: Points to the Status column in the table.
- Refresh interval determines how frequently status is updated**: Points to the "Refresh Interval: 10 seconds" text at the bottom of the dialog.
- Retrieve errors from build to the iSeries Error List**: Points to the "Retrieve Errors" option in the context menu.

Once "Show Remote Objects" is enabled (it is a toggle) all the objects in the associated library for this project are shown in the iSeries Navigator.

This navigator is called a "bleed through" view because it lists both local files/members and remote objects, files and members. However, if a file or member exists both locally and remotely, it is not shown twice. Rather, it is only shown once, and its icon and bracketed text identify it as existing in both places.


The icons and text enable you to see at a glance which files/members exist only locally, only remotely, or both locally and remotely. In the latter case, the color of the icon indicates if the two are in synch or not. If not, it is an indication you need to "push" your local source to the associated library to get it in synch.



IBM Software Group

Remote System Explorer Extension Points

WebSphere. software



Add your own tools: Eclipse Plug-in Development

© 2003 IBM Corporation

Additional documentation on the following extension points can be found in:

C:\WDSC\iseries\eclipse\plugins\com.ibm.etools.systems.core_5.0.0\plugin.xml

Benefits of Building On Top of the RSE

- What does the RSE offer you?

- Extension points for remote objects**

- Popup menus
 - Property pages

- Extend the remote system framework**

- Add a new subsystem
 - Add a new system type
 - iSeries, Linux, Unix, Windows and Local are pre-supplied

- Java APIs for accessing remote systems**

- Native
 - Retrieve lists of libraries, objects, members and jobs based on filters
 - Retrieve properties for a library, object, member or job
 - Prompt and run commands
 - Run applications in batch or interactive
 - IFS / Windows / Linux / Unix
 - Retrieve lists of directories / files
 - Run remote commands

Adding a New RSE System Type

- **Extension point**

com.ibm.etools.systems.core.systemtype

- **Adds a new system type to the Remote Systems Framework**

The new system type will appear in the new connection wizard

No Java code required!

You can then add new subsystems for this type

```
<extension point="com.ibm.etools.systems.core.systemtype">
  <type name="Windows"
    iconlive="icons/windowsLive.gif">
    icon="icons/windows.gif">
  </type>
</extension>
```

**icon changes
when system
is connected
or
disconnected**

Adding New Subsystems

- **Extension point**

com.ibm.etools.systems.core.subsystemfactory

A SubSystemFactory creates instances of a specific type of subsystem

- **Adds a new subsystem**

New subsystem will appear under connections of specified type

```
<extension point="com.ibm.etools.systems.core.subsystemfactory">
```

```
<factory
  systemtypes="iSeries"
  name="Files"
  icon="icons/filesubsys.gif"
  iconlive="icons/filesubsyslive.gif"
  id="com.acme.etools.mypkg.myfactory"
  class="com.acme.etools.mypkg.MyClass"
  category="files"
  vendor="acme">
```

```
</extension point>
```

Class must implement the
**com.ibm.etools.systems.subsystems.SubSystem
Factory
interface**

Adding Property Pages for Remote Objects

- **Extension point**

com.ibm.etools.systems.core.propertyPages

- **Add property pages for remote objects**

Property pages will appear in the properties dialog when user selects "Properties..." from the popup menu for a remote object

```
<extension point="com.ibm.etools.systems.core.propertyPages">
  <page class="com.acme.myPropertyPage"
    id="com.acme.mypropertypage"
    name="Remote File Info"
    icon="icons/myProperties.gif"
    subsystemfactoryid="ibm.filesLocal"
    typecategoryfilter="files"
    typefilter="file"
    subtypefilter="java"
    namefilter="*.java">
  </page>
</extension>
```

- Filters are subsystem specific
- Each remote object can have a type, subtype and subtype
- For example
 - Type: *PGM
 - Subtype: RPGLE
- Can also filter by name

Adding Popup Menu Actions for Remote Objects

- **Extension point**

`com.ibm.etools.systems.core.popupMenus`

- **Add action for remote objects**

New action will appear in the popup menu of remote objects in the Remote Systems view

Example 

Adding Popup Menu Actions for Remote Objects

```
<extension point="com.ibm.etools.systems.core.popupMenu">
  <objectContribution
    id="com.acme.displayfile.actions"
    subsystemfactoryid="ibm.files400"
    typecategoryfilter="OBJECT*"
    typefilter=""FILE"
    subtypefilter="DSPF"
    namefilter=""*>
    <menu id="com.acme.displayfile.menu"
      label="My Display File Actions">
      <separator name="group1"/>
    </menu>
    <action id="com.acme.action1"
      label="My first action"
      class="com.acme.actions.Action1"
      menubarPath="com.acme.displayfile.menu/group1"
      enablesFor="1">
    </action>
    <action id="com.acme.action2"
      label="My second action"
      class="com.acme.actions.Action2"
      menubarPath="com.acme.displayfile.menu/group1"
      enablesFor="+">
    </action>
  </objectContribution>
</extension>
```

Same as property pages

Adds the menu item


Your actions



IBM Software Group

Examples from Business Partners

WebSphere. software



Add your own tools: Eclipse Plug-in Development


© 2003 IBM Corporation



SoftLanding Systems, Inc.

Free Spooled File Plug-in for WDS, includes:

- Spooled files subsystem
- Spool files filtering
- Spooled files table view
- Perform remote actions on spooled files



www.softlanding.com



SoftLanding Systems, Inc.

New
Spooled File Filter
 Create a new filter to list spooled files

User: *
 Output queue: *
 Library: *
 User data: *
 Form type: *

< Back Next > Finish Cancel

Define your own filters for showing spooled files

Your spooled files

| File | Device or Queue | User Data | Status | Total Pages | Current P... | User | Job | Job Number | File Num |
|-----------|-----------------|-----------|--------|-------------|--------------|--------|------------|------------|----------|
| ORDENTR | QGPL/QPRINT | | *READY | 33 | 0 | YANTZI | QPADEV0... | 917371 | 1 |
| OFFLINE1A | QGPL/QPRINT | | *READY | 3 | 0 | YANTZI | QPADEV0... | 917406 | 1 |
| OFFLINE1A | QGPL/QPRINT | | *READY | 3 | 0 | YANTZI | QPADEV0... | 917406 | 2 |
| OFFLINE1A | QGPL/QPRINT | | *READY | 3 | 0 | YANTZI | QPADEV0... | 917406 | 3 |
| OFFLINE1A | QGPL/QPRINT | | *READY | 3 | 0 | | | | |
| OFFLINE1A | QGPL/QPRINT | | *READY | 3 | 0 | | | | |
| OFFLINE1A | QGPL/QPRINT | | *READY | 3 | 0 | | | | |
| OFFLINE1A | QGPL/QPRINT | | *READY | 3 | 0 | | | | |


Spooled files view shows details about each spool file and provides right click popup menu actions



IBM Software Group

Plug-in Development Summary

WebSphere. software



Add your own tools: Eclipse Plug-in Development

© 2003 IBM Corporation

Summary

- Eclipse and the WebSphere Studio Workbench provide:
 - An integrated development environment**
 - Extendable platform**
 - You can focus on your function without worrying about:
 - Resource management
 - Help system
 - Rich set of base classes for quickly developing UI
- WDSi provides:
 - iSeries tooling plugged into Eclipse
 - Remote Systems Framework
 - With extension points so you can add functionality to the RSE



Additional Resources

- Eclipse
www.eclipse.org
- WebSphere Development Studio Client
<http://www.ibm.com/software/awdtools/series/>
- IBM's developerWorks
www.ibm.com/developer





Disclaimer

- **Acknowledgement:**

This presentation is a collaborative effort of the IBM Toronto AS/400 Application Development presentation team, including work done by:

Phil Coulthard, George Farr, Claus Weiss, Don Yantzi, John Steinbacher, David Slater, Alison Butteril, Linda Cole

- **Disclaimer:**

The information contained in this document has not been submitted to any formal IBM test and is distributed on an as is basis without any warranty either express or implied. The use of this information or the implementation of any of these techniques is a customer responsibility and depends on the customers' ability to evaluate and integrate them into the customers' operational environment. While each item may have been reviewed by IBM for accuracy in a specific situation, there is no guarantee that the same or similar results will result elsewhere. Customers attempting to adapt these techniques to their own environment do so at their own risk.

- **Reproduction:**

The base presentation is the property of IBM Corporation. Permission must be obtained PRIOR to making copies of this material for any reason.



IBM Software Group

Add your own tools to IBM WebSphere Development Studio Client for iSeries: Eclipse Plug-in Development

WebSphere. software



Add your own tools: Eclipse Plug-in Development

© 2003 IBM Corporation