

450155



| IBM Software Group Toronto Laboratory

RPG and COBOL Tools in WDS: RSE Advanced
Agenda key: 56MM

| Claus Weiss (weiss@ca.ibm.com)
IBM Toronto Lab

| Thursday, April 27, 2006 |

© 2004, 2006 IBM Corporation

IBM Software group, Toronto Laboratory **IBM**

WebSphere Development Studio

Current 5722-WDS customers with software subscription for V5R3, to upgrade to WDS V6.0 use feature #: 2656
Available after GA

RPG

COBOL

C/C++

PDM
SEU
SDA
RLU

Upgrade from WDS 6.0 to 6.0.1 using Rational Product updater

Unlimited Licenses

New WDS Lite
Technology preview

iSeries	iSeries	iSeries	iSeries	Web Facing WDHT support	iSeries Projects	+CODE +VisualAge RPG	
Java™	Debug	Struts Web	Web Service	RSE			
JSF	EGL Java generation	Trace	Profiling	DB	XML	App Server	HATS Toolkit

www.ibm.com/software/awdtools/iseries

WebSphere Development Studio Client V6.0.1 based on RWD V6

2
WDS | RSE advanced |
© 2004, 2006 IBM Corporation

There is now only one application development product sold by IBM, for iSeries, as of V4R5. This is WebSphere Development Studio (Development Studio), which includes all four host compilers, all traditional tools (ADTS = PDM+SEU+SDA+RLU+DFU+AFP+CGU), and unlimited licenses of the workstation-based toolset named WebSphere Development Studio Client (formerly WebSphere Development Tools).

If you are an existing customer who has a subscription, you can upgrade to Development Studio free of charge. Without a Software Subscription, there is an upgrade fee. New licenses of Development Studio are priced very competitive compared to the combined prices of all constituent products. As of V5R1, there is no way to purchase the compilers or tools individually. So if you have RPG at V5R1 or higher, you must have Development Studio and hence are entitled to Development Studio Client.

For consultants who do not have an iSeries of their own, but still wish to have the client tools, Development Studio Client is also made available as a passport advantage product so it can be purchased "off the shelf" from IBM Direct.

Development Studio has been a huge success, with over 80,000 licenses sold. Just as every development machine used to have PDM and SEU, every development machine will now have all the modern Application Development tools from IBM. This ubiquity is especially important for business partners who build and sell software. These Business Partners are now free to build software using any of the technologies or tools in Development Studio, and can assume their customers will have the tools required to tailor everything from RPG to Java and Web user interfaces. This effectively raises the lowest common denominator to a level unparalleled by any other operating system.

IBM Software group, Toronto Laboratory

WebSphere Development Studio Client Advanced Edition 6.0.1

Workstation License order through Passport Advantage **Upgrade from WDSC 6.0 to 6.0.1 using Rational Product updater**

http://www.lotus.com/services/passport.nsf/WebDocs/Passport_Advantage_Home

iSeries	iSeries	iSeries *	iSeries	Web Facing *	iSeries	+CODE +VisualAge RPG	
Java	Debug	Struts Web	Web Service	WDHT support	Projects RSE		
JSF	EGL Java generation	Trace	Profiling	DB	XML	App Server	HATS Toolkit
	EGL * COBOL generation	EJB *	Test * Cases	Portal *	<div style="border: 1px solid black; padding: 2px; display: inline-block;"> WDS Lite Technology preview </div>		
www.ibm.com/software/awdtools/iseries WebSphere Development Studio Client V6.0.1 based on RAD V6							

3 | **WDSC | RSE advanced** | © 2004, 2006 IBM Corporation

There is now only one application development product sold by IBM, for iSeries, as of V4R5. This is WebSphere Development Studio (Development Studio), which includes all four host compilers, all traditional tools (ADTS = PDM+SEU+SDA+RLU+DFU+AFP+CGU), and unlimited licenses of the workstation-based toolset named WebSphere Development Studio Client (formerly WebSphere Development Tools).

If you are an existing customer who has a subscription, you can upgrade to Development Studio free of charge. Without a Software Subscription, there is an upgrade fee. New licenses of Development Studio are priced very competitive compared to the combined prices of all constituent products. As of V5R1, there is no way to purchase the compilers or tools individually. So if you have RPG at V5R1 or higher, you must have Development Studio and hence are entitled to Development Studio Client.

For consultants who do not have an iSeries of their own, but still wish to have the client tools, Development Studio Client is also made available as a passport advantage product so it can be purchased "off the shelf" from IBM Direct.

Development Studio has been a huge success, with over 80,000 licenses sold. Just as every development machine used to have PDM and SEU, every development machine will now have all the modern Application Development tools from IBM. This ubiquity is especially important for business partners who build and sell software. These Business Partners are now free to build software using any of the technologies or tools in Development Studio, and can assume their customers will have the tools required to tailor everything from RPG to Java and Web user interfaces. This effectively raises the lowest common denominator to a level unparalleled by any other operating system.

Table of contents

▣▣▣ **What's new in V6.0.1**

Customizing Workbench and Editor

User Actions and Compile Commands

Running Interactive Commands in RSE

RSE Filters and Filter pools

Working Disconnected

iSeries Projects

Agenda



Installation

WDSsc 6.0.1 is an electronic update to WDSsc 6.0. It can be installed directly from the Internet via the Rational Product Updater (after GA on Feb 14th)

Product	Version	Install Date
IBM WebSphere Development Studio ...	6.0.0	12-Jan-2006 2:46 PM
6.0.1 Refresh Pack	6.0.1	
Interim Fix 6.0.1.1 for iSeries Tutorials		

IBM WebSphere Development Studio Client for iSeries, Version 6.0.1, Readme file

Contents

[About this release](#)


[Before von begin](#)

Manual downloads and iSeries PTFs will be made available after electronic GA.

WDS Sc Lite – Technology Preview

- **WDS Sc Lite is a slimmed down workbench with only the:**
 - Eclipse workbench (branded as the Rational Software Development Platform)
 - Remote System Explorer
 - iSeries Projects
 - iSeries Integrated Debugger
- **Requires only 256 MB RAM !!!**
- **Optional installation feature for 6.0.1**
 - Must already have full WDS Sc 6.0.1 installed
 - Creates a second copy of the workbench
- **Fully supported technology preview**
 - Preview of future packaging directions ☺

WDS Sc Lite – Installation and Startup



Remote Systems Explorer – 6.0.1 Enhancements

- V5R4 RPG, COBOL, and CL language support
 - Program verifiers (RPG & COBOL)
 - Syntax checkers
 - Online language references
- Multiple views of a single source member (Remote Systems LPEX Editor)
- Autosave
 - Unsaved changes periodically backed up to a local temporary location
 - Only for Remote Systems LPEX Editor
 - Preference to configure how often changes should be backed up

Multiple Views for a Single Source Member

Same source member, multiple **editable** views



The screenshot displays two views of a source member in a code editor. The top view, titled 'ORDENTR.RPGLE X', shows lines 69 through 7300. The bottom view, titled 'WDSDEMO|QRPGLSRC(ORDENTR): 2', shows lines 727 through 8. A context menu is open over the bottom view, with 'Vertical split' highlighted. The menu options include: New (Prompt F4, Syntax Check Line), Cut (Ctrl+X), Copy (Ctrl+Insert), Paste (Ctrl+V), Select (Selected, Deselect Alt+U), Filter view (Show all Ctrl+W), Source (View), Open new view (Ctrl+2), Next view (Ctrl+Alt+Right), Previous view (Ctrl+Alt+Left), Add to Snippets..., and Save.

Line	Column	Text
006300	D	DistrictID
006400	D	WarehousID
006500	D	OrderID
006600	//	
006700	//	Customer info returned by SLTCUSTR
006800	D	CustInfo DS INZ
006900	D	CustId 4
007000	D	CustFName 16
007100	D	CustInitial 2
007200	D	CustLName 16
007300	D	CustAddr1 20

Line	Column	Text
064500	C	PARM
064600	C	PARM
064700	//	
064800	//	Parameter list for SLTCUSTR progr
064900	C	CustSlt PLIST
065000	C	PARM
065100	//	
065200	//	Parameter list for SLTPARTR progr
065300	C	PartSlt PLIST
065400	C	PARM
065500	//	

Autosave

Autosave preferences



Dialog when opening a member and autosave backup exists

iSeries Web Services Tools

- Single wizard to convert i5/OS program or service program procedure into a Web Service
Generates all required code for deploying Web Service to WebSphere Application Server
Popup available from an ILE RPG, COBOL or PCML member or file
- Automatically determines program (or procedure) parameters when invoked from RSE




Table of contents

▣ **Customizing Workbench and Editor**

User Actions and Compile Commands

Running Interactive Commands in RSE

RSE Filters and Filter pools


Working Disconnected

iSeries Projects

Agenda




The Remote System Explorer Perspective



This is the familiar default appearance of the Remote System Explorer Perspective.

Customizing the Workbench



The Remote System Explorer Perspective can be customized to look like this.

The editor takes up most of the space, now. Its appearance has been changed.

The iSeries Table view resides below the editor and all other views have been either closed or moved to the left margin as fast views.

Customizing the Workbench

- **Customize Perspective**

- View can be
 - moved
 - re-sized
 - closed
 - hidden as Fast view
- Add other views

- **Save Perspective AS...**

Replace existing or create new perspective

- **Use Window -> Preferences**

Workbench, Perspectives

Make Default, Delete


Perspectives can be modified to fit your work style. Move, re-size or close existing views. Open other views that you want to add to the perspective. Save the customized layout as a new perspective using Window -> Save Perspective as.

Settings for your own perspectives as well as the ones shipped with the product, can be maintained from Window -> Preferences, expand Workbench and select the Perspectives page.

Editor Preferences

- LPEX Editor
 - Appearance
 - Parsers, Parser Settings

- Remote Systems, iSeries, LPEX Editor Parsers
 - Language specific settings



There are two places in the preferences that allow editor customization: LPEX Editor and Remote Systems, iSeries, LPEX Editor Parsers.

Besides appearance i.e. colour settings, the editor behaviour can also be modified.

Examples are syntax checking and column sensitive editing.

Table of contents

Customizing Workbench and Editor

▣ **User Actions and Compile Commands**

Running Interactive Commands in RSE

RSE Filters and Filter pools

Working Disconnected

iSeries Projects

Agenda

RSE: User Actions

▪ User-Defined Actions ... like PDM!

- Right-click on iSeries Objects -> Work With
 - User Actions
 - Create, delete or change user-defined actions
 - Scope them so you only see them when appropriate
 - Named Types
 - Create named types to scope actions against
 - EG. "RPG" might be RPG + RPGLE + SQLRPGLE

▪ ... and even beyond PDM!

- Create user actions for libs/objects, members ... and even jobs and IFS folders and files!

While IBM supplies a number of useful actions for remote iSeries objects, it is not possible to supply them all. Like PDM, you can easily define your own actions. To create your own actions, use the Work With actions in the popup menu for iSeries Objects. These user-defined actions will appear in the popup menus for remote resources. To avoid seeing all actions in all popup menus, you scope each action to one or more object or member types. You first define named collections of object or member types, then you create your actions and scope them to one of these named collections of types. Your actions will then only appear for object or members that match one of the types in the collection. These actions can be created for objects, members, jobs and IFS folders and files.

Defining User Actions

Define your own actions for object and member popup menus


19

Remote System Explorer | Advanced

Use Work With -> User Actions to define an object or member action. Object actions only appear in the popup menus for libraries or objects. Member actions only appear in the popup menus for members. When you define the action, you initially specify a label to show in the popup menu and an iSeries command to run when that action is selected. This command can use substitution variables that are identical to those in PDM. There are also numerous options you can specify to affect the action, and you can scope it precisely: for example, object actions can be scoped one or more type and attribute pairs, and member actions by one or more simple or generic member types.


Substitution Variables

- Many substitution variables
 - Superset of PDM
- Different sets for objects vs members vs jobs vs IFS
- Use Insert Variable to see list
 - or Ctrl+Space to see list: or type '&' to get prompted



All PDM substitution variables are supported for the command, and some new ones that PDM didn't support.


When you type &, you see a popup selection list, or you can type Ctrl+Space or press the Insert Variables button. From the list, double click to insert the selected variable, at the cursor position.



Once your action is defined, you can use it. Right click on an object matching one of the types you specified, and expand the User Actions menu in the pop-up. Your action appears in the menu. Select it. If you chose to prompt the command (via the Prompt option), you will see the GUI prompt for the command. When the command has finished running, its results are logged in the Commands view.

User Actions for Jobs

- Yes, you can create user actions for Jobs too!



You can also create user actions for Jobs, which will appear in the User Actions popup menu for jobs in the iSeries Jobs subsystem under a connection. The substitution variables include variables for the selected job's number, user and name.

IBM Software Group | WebSphere software **IBM**

User Actions for IFS

- And even IFS folder and files

You can choose between QShell commands or QSYS commands!

The substitution variables change, depending on command type

For QSYS cmds

For QShell cmds

Similar for Local, Unix, Windows and Linux user actions


© 2004, 2006 IBM Corporation

You can also create user actions for IFS folders and files, which appear in the User Actions popup menu for folders and files in the IFS Files subsystem under a connection.

You can create user actions that are QShell commands or *CMD objects as usual. The substitution variables change depending on the type of command: for qsys commands you get the PDM substitution variables, slightly different to deal with folder/file names versus object/member names. For qshell commands, you get a different list using eclipse-style `${...}` variables, with many variables for all aspects of the selected folder/file name, but a number of other environment variables.

Note the qshell-support is the same as when creating local, unix, windows or linux user actions, which are also supported.


Running User Actions for IFS



IFS user actions show up in the right click of the IFS files or folders, as shown here. If the action is defined to prompt, then you get a prompt dialog where you can edit the command before submitting it.

Work With Compile Commands

- You can change IBM or vendor supplied compile commands, and add your own



In addition to user actions, there is specific support for creating compile commands too. Use the Work With -> Compile Commands option from the iSeries Objects subsystem under an iSeries connection. IBM pre-supplies compile commands, and enables vendors to pre-supply commands as well, some of which do.

Customizing Compile Commands

Create new or edit existing

Right click for more actions

Commands per member type

Brings up larger window for editing

Browse iSeries for *CMD object


Subset of PDM substitution variables allowed

- &F - Name of file containing selected member
- &L - Object or member library name
- &N - Name of selected resource
- &O - Object library, from Command Execution properties
- &R - Replace object when compiling, *YES or *NO. From Command
- &X - Object or member text, in single quotes

26 Remote System Explorer | Advanced © 2004, 2006 IBM Corporation

In the Work With Compile Commands dialog, you can create new compile commands and edit existing ones. To edit an existing one, first find it by selecting the member type it applies to (or add a new member type if necessary) at the top of the dialog, and selecting the command in the list of commands on the left. Then edit the command and press Apply. You can also right-click on a command to delete it, copy/paste it, or re-order it. Note you cannot delete IBM-supplied commands, but after editing them, you can restore them to their shipped value.

Creating New Compile Command



Work With Compile Commands

Parent profile: PhilCoulthard

Member type: RPGLE Add... Remove

Compile Commands:

New compile command:

Label: My RPG Compile Command

Command: CALL MYCOMPILE &L/&F &N

Insert variable... Edit... Browse...

Prompt...

Create Revert

Close

Work With Compile

Parent profile:

Member type:

Compile Commands:

New command
CRTBNDRPG
CRTRPGMOD
My RPG Compile Command

27 Remote System Explorer | Advanced © 2004, 2006 IBM Corporation

To create a new compile command, select “New command” on the left, and then enter the label to show, and command to run, and press Create. The command will show up on the list on the left, and will also now be available at runtime, as we see on the next slide...

Running New Compile Command

The screenshot shows the Remote System Explorer interface. A context menu is open over a member named 'PAYROLL.rpgle'. The menu options include 'Go To', 'Open With', 'Browse With', 'Rename', 'Copy', 'Move', 'Delete', 'Verify', 'Verify (Prompt)', 'Compile', 'Compile (Prompt)', 'User Actions', 'Add To iSeries Project...', and 'Make Available Offline'. The 'Compile' option is selected, and a sub-menu is visible showing 'CRTBNDPRG', 'CRTTRPGMOD', and 'My RPG Compile Command'. A checkmark is next to 'My RPG Compile Command'. A callout box with arrows pointing to the 'My RPG Compile Command' and the 'Error List' window contains the text: 'You will see the Error List view if the command generates an event file'.

The 'iSeries Error List - CODELAB/EVFEVENT(PAYROLLG)' window is open, displaying a table of errors:

ID	Message	Severity	Line	Location	Connection
RN59308	Compilation stopped. Severity 40 errors found in program.	50	0	CODELAB/QRPGLESRC(PAYROLLG)	My iSeries
RNF2120	External descriptions for file MSTDSP not found; file is ignored.	40	27	CODELAB/QRPGLESRC(PAYROLLG)	My iSeries
RNF2120	External descriptions for file PRJMST not found; file is ignored.	40	29	CODELAB/QRPGLESRC(PAYROLLG)	My iSeries
RNF2120	External descriptions for file RSNMST not found; file is ignored.	40	30	CODELAB/QRPGLESRC(PAYROLLG)	My iSeries
RNF7030	The name or indicator ACODE is not defined.	30	103	CODELAB/QRPGLESRC(PAYROLLG)	My iSeries
RNF7030	The name or indicator EMPAPL is not defined.	30	54	CODELAB/QRPGLESRC(PAYROLLG)	My iSeries
RNF7030	The name or indicator PRUDE is not defined.	30	257	CODELAB/QRPGLESRC(PAYROLLG)	My iSeries
RNF7030	The name or indicator PRCMP is not defined.	30	264	CODELAB/QRPGLESRC(PAYROLLG)	My iSeries

Here we see our new compile command appearing when we right click on a member of the type we created the command for. Note the checkmark appears beside the last-used compile command for the selected member's type. When the compile command runs, if it generates an event file that event file is automatically retrieved and the errors produced by the compile are displayed in the Error List window, where you can double click to open the editor and position it at the error.

Defining IFS Compile Commands

- Yes, you can even create compile commands for IFS files ... and even local, Unix, Windows and Linux!

Work With Compile Commands

Parent profile: PhilCoulthard

Source type: java

Compile Commands:

New command: Selected compile command:

Label: javac

Command: QShell command

Command text: `javac -deprecation -classpath . ${resource_name}`


Legend:

- &FCN - Name of parent folder containing selected file or folder
- &FCP - Fully qualified path of parent folder, including name of selected file or folder
- &FNE - Extension part of the name of the selected file
- &FNR - Name of selected file without the extension
- &FP - Fully qualified path of selected file or folder, including name
- &N - Name of selected file or folder
- &O - Object library, from Command Execution properties
- &R - Replace object when compiling. *YES or *NO. From Command Execution properties

Environment variables:

- \${container_name} - Name of folder containing selected resource, unqualified
- \${container_path} - Path of folder containing selected resource, including name
- \${resource_name_root} - Name of selected resource without the extension
- \${resource_name} - Name of selected resource, unqualified
- \${resource_path_drive} - Drive letter on Windows, empty string on others
- \${resource_path_root} - Root of selected file's path. "c:" on Windows, "/" on others
- \${resource_path} - Path of selected resource, including name
- \${system_filesep} - File separator. "\" on Windows, "/" on Unix and Linux
- \${system_homeid} - Home directory on the target system, for the connection's user ID
- \${system_pathsep} - Path separator. ";" on Windows, ":" on Unix and Linux
- \${system_tmpdir} - Temporary directory on the target system

Running IFS Compile Commands




Here we see our new compile command appearing when we right click on an IFS file of the type we created the command for. Note the checkmark appears beside the last-used compile command for the selected file's type. When an OS/400 compile command runs, if it generates an event file that event file is automatically retrieved and the errors produced by the compile are displayed in the Error List window, where you can double click to open the editor and position it at the error. When a QShell compile command runs, the errors are shown in the Command view, and are double clickable.

Preferences For User Actions and Compile Cmds

Window->
Preferences

Specify preferences here, for all connections

Override per connection via Properties dialog for iSeries Objects



31

Remote Systems

Restore Defaults Apply

There is a preferences dialog that has many preferences which affect substitution variables for user actions and compile commands.

Table of contents

Customizing Workbench and Editor

User Actions and Compile Commands

 **Running Interactive Commands in RSE**

RSE Filters and Filter pools

Working Disconnected

iSeries Projects

Agenda

Running Interactive Commands in RSE

There are three types of iSeries commands in RSE

Normal -> runs in RSE batch job (with adopted user ID)

Batch -> runs via SBMJOB (using preferences for JobD, etc)


Interactive -> runs in interactive job (you must do STRRSESVR)

You will see this prompt in many places. Eg:

When defining User Actions

When defining Compile Commands


When running commands in iSeries Command log view



Within the Remote System Explorer, there are 3 ways to run commands on the iSeries: normal, batch or interactive, as described here. You will see the prompt for the three types of commands throughout the RSE, so its important to know the differences between them.

Running Interactive Commands in RSE

- Step 1: Run STRRSESVR in any emulator



The screenshot shows a terminal window titled "Session A - [24 x 80]" with a menu bar (File, Edit, View, Communication, Actions, Window, Help) and a toolbar. The terminal displays the command "START RSE SERVER (STRRSESVR)" and prompts for input. The user has entered "PhilCoulthard.Mu iSeries" for the connection name. Below this, there is a section for "Additional Parameters" with the following entries:

Parameter	Value	Description
WORKING LIBRARY	COULTHAR	Character value, *PRV, *DFT
REMOTE LOCATION NAME	78AAYG8	
TCP/IP PORT NUMBER	*PRV	1-65534, *PRV, *DFT


Three callout boxes on the right side of the terminal window provide context for the input:

- The first callout points to the connection name and says: "The profile-qualified RSE connection name to associate this interactive session with".
- The second callout points to the WORKING LIBRARY parameter and says: "Where to put user space for history".
- The third callout points to the TCP/IP PORT NUMBER parameter and says: "Host name of your PC".

To run interactive commands, you must run the STRRSESVR command from within an emulator. Specify the name of the connection within the RSE to associate this interactive session with ... qualified by profile. It may help to select the "Qualify connection names" option in the dropdown of the title bar of the Remote Systems view in the RSE, so you can see what profile your connection is in. Also specify a library unique to you, to hold *PRV values for this command, and of course your PC's hostname or IP address.

Running Interactive Commands in RSE

- Step 1: Emulator is now reserved...



```
Session A - [24 x 80]
File Edit View Communication Actions Window Help
IBM RSE Communications Server

Connection Name: PhilCoulthard.My iSeries



(c) Copyright IBM corp., 2001, 2003. All rights reserved.

Job: QPADEV0007/COULTHAR/035300
Command: CALL MYPROGRAM
Completed
```

When the STRRSESVR command is successful, it will reserve the emulator by putting up the screen shown here.

Running Interactive Commands in RSE


- Step 2: Run interactive command in RSE



Now, within the connection associated with the STRRSESVR command, you can run interactive commands from within the RSE, and debug interactive programs. The example here shows running STRPDM from the iSeries command log view. You need to give focus to your reserved emulator to see the results...

Running Interactive Commands in RSE

- Step 2: ... and your command runs in emulator:



```
Session A - [24 x 80]
File Edit View Communication Actions Window Help
AS/400 Programming Development Manager (PDM)

Select one of the following:

1. Work with libraries
2. Work with objects
3. Work with members
4. Work with projects
5. Work with groups
6. Work with parts

9. Work with user-defined options

Selection or command
===>

F3=Exit    F4=Prompt    F9=Retrieve    F10=Command entry
F12=Cancel F18=Change defaults
(C) COPYRIGHT IBM CORP. 1981. 2000.
```

... and here we see that the reserved emulator is now running the interactive command we entered in the RSE.


Run: from popup menus

Run from Popup menu of *PGM

- ✓ iSeries appl. in RSE job
- ✓ Batch
- ✓ Interactive
- ✓ Multi-threaded

Run As

Run(Prompt)




You can run programs from the Remote Systems view or the iSeries Table view in four ways:

- In the RSE communications server job
- In a batch job
- In an interactive job
- In a server job

In the first case, running the program in the same job as the Remote System Explorer communications server job, will tie up that job until your program ends. With batch and interactive jobs, you cannot monitor the status as easily, however, you do not tie up your communications server and you are notified when the program ends. Batch jobs work as you would expect, your application will be submitted to the default batch subsystem.

Note: A multi-threaded debug session creates a new server job and this way keeps the RSE communications server job free for other tasks.

Run Configurations: for easy re-use!



Run configurations are for powerful re-use. If what you want to run a program that takes a number of parameters, or is not straightforward to launch, you can predefine this information into a named configuration. Once created, the configuration appears in the configuration list, and can be selected from there. Every configuration run also appears in the pulldown menu of the Run tool bar button. Clicking the Run tool bar button itself, will run the previous configuration again.

Table of contents

Customizing Workbench and Editor

User Actions and Compile Commands

Running Interactive Commands in RSE

 **RSE Filters and Filter pools**

Working Disconnected

iSeries Projects

Agenda


Drilling Down

- Typically we start using the RSE by just expanding:
 - Expand Library list to see libraries on lib list
 - Expand a library to see all objects in it
 - Expand a source file to see members in it
 - Expand Home directory to see folders in \home in IFS
 - Expand a folder to see all folders and files in it
 - And so on

- But sometimes this produces lists that are too big
 - Its unwieldy to scroll through thousands of things
 - You really want to keep lists small, to a few hundred at most

The Remote System Explorer is all about random access to remote things ... like stuff in QSYS, or jobs, or IFS files. While it is designed to be immediately useful by merely expanding nodes to drill down to what we want, sometimes that can produce unsatisfactory results if this results in vast numbers of items.

*LIB Expand To → For Quick Filtering




One very quick way to reduce the amount of things is to use the Expand To object for libraries. It allows you to expand a library to see only objects of a particular type. This subsetting remains in effect forever, even when you re-expand with the plus sign, until you subsequently choose All or any other expand-to criteria.

Introducing Filters

- Eventually you will need to see a subsetted list
 - Using criteria like generic names, types and attributes
 - All subsystems (nodes under a connection) support “**filters**”
 - These allow fine-grained control over what is shown in the RSE.
- To create a filter, right click on any subsystem and select New -> xxx
 - iSeries Objects -> New -> Library Filter, Object Filter, Member Filter
 - iSeries Commands -> New -> Command Set
 - iSeries Jobs -> New -> Job Filter
 - IFS Files -> New -> Filter
- Or use the fastpath Work With XXX... prompts under iSeries Objects

Eventually, you will find the need to see a subsetted list. That is what filters offer, and the RSE has extensive filter support.

Introducing Filters



RSE filters for iSeries Objects

- **Library filters**
 - Specify simple, generic or special library names
- **Object filters**
 - Specify simple / generic object names, lib-qualified
 - Library name can be simple, generic or special
 - Object name can be simple or generic
 - Specify simple / generic object types and attributes
 - Can specify one or more type:attribute pairs (OR operation)
- **Member filters**
 - Specify simple / generic member names, lib / file-qualified
 - Specify simple / generic member types
 - Can specify one or more member types (OR operation)

There are three types of filters you can create in the iSeries Objects subsystem.

1. Library filters. These list libraries when expanded.
2. Object filters. These list objects when expanded.
3. Member filters. These list members when expanded.

We will see an example of creating each of these. If you are an existing CODE user, you can use File->Import to import filters from CODE Project Organizer.

Library Filters

46 Remote System Explorer | Advanced © 2004, 2006 IBM Corporation

Here we use the Work With Libraries... prompt to create a library filter. Specify the library name, simple or generic, to list when this filter is expanded. Note the generic names in RSE support two asterisks, not just one as is the case with PDM. On the second page, specify the name for this filter.

Expanding Library Filters

The screenshot shows the Remote System Explorer interface. The left pane displays a tree view under 'Remote Systems' with 'My iSeries Objects' expanded to 'My Libraries'. A filter is selected and expanded, showing a list of libraries: ADTSLAB.*lib.prod, ADTSLABJL.*lib.prod, ADTSLAB1.*lib.prod, CODELAB.*lib.prod, CODELABADM.*lib.prod, CODELABCW.*lib.prod, and CNFLIBRY.*lib.prod. A context menu is open over the filter, with 'Change...' highlighted. A callout box points to the 'Change...' option with the text 'Use Change to edit filter later'. Another callout box points to the filter with the text 'Filter is created, and expanded. It lists all libraries matching the given criteria.' A third callout box points to the filter with the text 'Filter exists until you delete it'. A fourth callout box points to the filter with the text 'Filter exists in all connections by default'.

When a library filter is created, it shows up in the list of existing filters for iSeries Objects. You can edit the filter by right clicking on it and selecting the Change... action from its popup menu. When a library filter is expanded, all libraries matching one or more of the filter's filter strings are listed underneath the filter. Note that these libraries can subsequently be expanded, just as they can for the Library List filter.

Object Filters

Remote Systems

New Connection

- Local
- Linux
- My iSeries
 - Work with libraries...
 - Work with objects...
 - Work with members...
 - Library list
 - User libraries
 - My Libraries
 - iSeries Commands
 - iSeries Jobs
 - IPS Files
 - TORASIFB

New

Object Filter
Create a new iSeries object filter

Library: ADTSLAB Browse...

Object: Browse...

Object type: *FILE Browse...

Object attribute: * Browse...

More Types >>

< Back Next > Finish Cancel

New

Object Filter
Name the new filter

Filters are saved for easy re-use. Specify a unique name for this filter. This name will appear in the Remote Systems view, and will be expandable.

Filter name: My Objects

48 Remote System Explorer | Advanced

Here you use the Work With Objects... prompt to create an object filter to list objects in one or more libraries. Specify the library, the object, the type and attribute filtering criteria. All but the object type can be generic.

On the 2nd page of the wizard, you specify the name for this filter.

Filtering objects by type + attribute

When More Types>>> pressed

Prompt for object type

Prompt for object attribute

Specify multiple object type + attribute pairs

Will list *all* objects with *any* of the specified types+attributes

Select Object Type

Select an object type:

- *ALRTBL
- *AUTL
- *BNDDIR
- *CFGL
- *CHTFMT
- *CLD
- *CLS
- *CMD
- *CNIL
- *COSD
- *CSI
- *CSMAP
- *CSTBL
- *CTLD
- *CRG
- *CROD
- *DEVD
- *DOC
- *DTAARA
- *DTAQ
- *EDITG
- *EXTTRG
- *FCT
- *FTI F

Select Object Attribute

Select an object attribute:

- ASM38
- BAS
- BAS38
- CBL
- CBLE
- CBL36
- CBL38
- CLE
- CLLE
- CLP
- CLP38
- CPPL
- CSP
- DFU
- DFUEXC
- DFUNOTEXC
- FTN
- PAS
- PAS38
- PLI
- PLI38
- RMC
- RPG
- RPGF

By using More Types>>>, you can specify more than one object type and attribute combination. Note the attribute can be generic. This multiple-type support is beyond what even PDM supports, and allows for extremely specific lists based on filters.

Expanding Object Filters

Remote Systems

- New Connection
- Local
- Linux
- My iSeries
 - iSeries Objects
 - Work with libraries...
 - Work with objects...
 - Filter created successfully. Expand this again to create another
 - Work with members...
 - Library list
 - User libraries
 - My Libraries
 - My Objects
 - CALLCRI.*pgm.rpgle
 - CALL400.*pgm.clp
 - CLRMSG.*pgm.clp
 - DSPMSG.*pgm.clp
 - GETTIME.*pgm.clp
 - GUIDESI.*pgm.rpgle
 - JAVASETUP.*pgm.clp
 - LABCLEANUP.*pgm.clp
 - LABSETUP.*pgm.clp
 - PRTCUST.*pgm.rpgle
 - PRTINVR.*pgm.clp
 - PRTINVR.*pgm.rpgle
 - RTVUSRCLAS.*pgm.clp

Context Menu:

- New
- Go Into
- Go To
- Open in New Window
- Show in Table
- Refresh
 - Expand
 - Collapse
- Change...
- Rename
- Copy
- Move
- Delete
- Move Up
- Move Down
- Show in Table
- Properties

When an object filter is created, it shows up in the list of existing filters for iSeries Objects. You can edit the filter by right clicking on it and selecting the Change... action from its popup menu. When an object filter is expanded, all objects matching one or more of the filter's filter strings are listed underneath the filter. Note that these objects can subsequently be expanded, if they are files, just as they can from the Library List filter.

Member Filters

Expand

Specify simple, special, or generic library name

Specify simple or generic file name

Specify simple or generic member name

Specify simple or generic member type

More types>> (next page)

Filter name: My Members

51 Remote System Explorer | Advanced © 2004, 2006 IBM Corporation

Here you use the Work With Members... prompt to create an object filter to list objects in one or more libraries. Specify the library, the object, the type and attribute filtering criteria. All but the object type can be generic.

On the 2nd page of the wizard, you specify the name for this filter.

Filtering by member type



When More Types>>> pressed

Specify multiple member types. Handy when generic name won't work

Will list *all* member with *any* of the specified types

By using More Types>>>, you can specify more than one member type. Note that each type can be generic. This multiple-type support is beyond what even PDM supports, and allows for extremely specific lists based on filters.

Expanding Member Filters



Use Change to edit filter later

Filter is created, and expanded. It lists all members matching the given criteria.

Filter exists until you delete it

Filter exists in all connections by default

When a member filter is created, it shows up in the list of existing filters for iSeries Objects. You can edit the filter by right clicking on it and selecting the Change... action from its popup menu. When a member filter is expanded, all members matching one or more of the filter's filter strings are listed underneath the filter.

Filter Pools

- **Eventually you will have too many filters!**
 - Or you will want a filter not to show in all connections
- **Time to turn on “Show Filter Pools”**
 - Expanding subsystems will then first show filter pools
- **Filters are grouped into named pools**
 - By default they are added to the “default filter pool”
 - You can create your own filter pools
 - Then add filters to it
 - Expand a filter pool to see just the filters in it
 - Connections reference filter pools ... only see those you reference
 - The default pool is always referenced
- **Filter pools group filters**
 - Nothing more than a named collection of filters
 - Allow you to group filters by project, release, connection, task, etc.


There is an advanced feature in the RSE for partitioning filters into named collections, called filter pools. To enable this, you must select the "Show Filter Pools" preference. Actually, all filters are contained in a filter pool. By default, they all go into one IBM supplied filter pool, named Default Filter Pool. By turning on the Show Filter Pools preference, you will see these filter pools when you expand a subsystem. When you expand a filter pool, you will then see the filters. Filter pools can be used to effectively group filters by task, or project, or release, or developer, or whatever you like.

Show Filter Pools

The screenshot shows the Remote System Explorer interface. On the left, a tree view is partially expanded to show 'My iSeries' and 'iSeries Objects'. A context menu is open over this area, with 'Show Filter Pools' highlighted. On the right, the same tree view is shown after the preference is enabled, where 'My iSeries' is expanded to show 'My iSeries Objects', which includes 'My iSeries Filter Pools' and 'My iSeries Filters'. Arrows point from the 'Show Filter Pools' menu item to the 'My iSeries Filter Pools' folder in the right-hand view. Below the screenshots are three callout boxes:

- Connections
Subsystems
Filters** (left)
- Connections
Subsystems
Filter Pools
Filters** (middle)
- Show Filter Pools
changes the view to
show filter pools first,
then filters** (right)


Here we see how to turn on the Show Filter Pools preference. Once enabled, when a subsystem is expanded you see not the filters, but first the filter pools referenced by this subsystem in this connection. When a filter pool is expanded, then you see the filters within that filter pool.




To create a new filter pool, right click on the subsystem, then select New -> Filter Pool...

All you need to specify for your new filter pool is a unique name. This is what you see when the subsystem is expanded. Never mind the Profile prompt for now, we will explain that later. It is defaulted so you need not think about it. When Finish is pressed, the filter pool is created, AND a reference to it is added to this subsystem in this connection. No other connection has a reference to this new filter pool yet!

Reference a Filter Pool



By default, only the connection where you created the filter pool has a reference to it, so filters created in it only appear for that connection




To share a filter pool between connections, create a reference to the filter pool from other connections

By default, filter pools you create are not shared by multiple connections. To affect that, create a reference to the same pool from multiple connections. Note any changes made to the filters in the pool are now immediate across all shared connections.


Work With Filter Pools

In Show Filter Pools mode, there are two new actions on subsystems like iSeries Objects:

1. Work With Filter Pools
2. Select Filter Pools



1. WW Filter Pools:
One stop shopping for filter pool management



2. Select Filter Pools:
Easily manage which pools this connection references

When you are in Show Filter Pools mode, you will see a couple actions on subsystems, for managing filter pools and managing references to filter pools.

Table of contents

Customizing Workbench and Editor

User Actions and Compile Commands

Running Interactive Commands in RSE

RSE Filters and Filter pools

 **Working Disconnected**

iSeries Projects

Agenda

Working disconnected

What you *can* do while disconnected

- ✓ Edit local and offline source files / mbrs
- ✓ Syntax check RPG, COBOL, DDS
- ✓ Syntax check CL for cached commands
 - ✓ Prompt RPG and DDS
 - ✓ Prompt CL for cached commands
- ✓ Access language help for RPG, COBOL, DDS
- ✓ Access CL help for cached commands
- ✓ Verify RPG, COBOL, DDS for those members that are cached

What you *cannot* do while disconnected

- ✓ Edit, design or compile host source members
 - ✓ Run or debug host programs
 - ✓ Run host commands
- ✓ Syntax check, prompt or F1 on CL commands not cached
- ✓ Verify members not previously verified

This summarizes what can and cannot be done when working in disconnected mode ... that is, without a live connection to an iSeries host.



Caching

- Verify source member
- Caches information
- To update cache:

Select Verify (Prompt)

Select Refresh cache

Click OK




61

Remote System Explorer

When you verify a member, the external references are automatically cached locally. On subsequent verifies, the local cache is used. To force a refresh of the cache, prompt the verify action and select Refresh Cache.

Cache Settings



You can affect cache settings via the Cache preferences page.

Make Available Offline

In order to work offline, you have to make a local copy of your member first. Use Make Available Offline

This creates an iSeries project, and imports the member(s) to it. This is where you work offline

What are iSeries Projects? Stay tuned...

iSeries Projects Question
Source member PAYROLL will be downloaded locally and added to iSeries project My iSeries_CODELAB. Proceed?
Yes No

63 Remote System Explorer | Advanced © 2004, 2006 IBM Corporation

To prepare for working offline, use the Make Available Offline action on the members you intend to edit. Then, while offline, you edit your source from the iSeries Projects perspective. More on iSeries Projects later.

Table of contents

Customizing Workbench and Editor

RSE Filters and Filter pools

User Actions and Compile Commands

Running Interactive Commands in RSE


Working Disconnected

 **iSeries Projects**

Agenda

iSeries Projects

- A special project type
 - For holding source destined to be compiled on iSeries
- A dedicated perspective
 - For working with all and only iSeries projects



There is a special project type designed to hold source that is destined to be compiled and run on an iSeries. There is a wizard for creating a new iSeries Project. There is a special perspective for working with iSeries projects.

What is an iSeries project?

- **Typical Eclipse project**
 - Contains folders and files, can be shared by a team
 - Can have its own tools and perspectives
- **But also**
 - Holds copies of some source members from an iSeries library
 - Those copies are “pushed” up occasionally and the project re-built

An iSeries Project is a typical Eclipse project. This means it contains folders and files that are in the local file system of the IDE, but these can be synchronized with a central repository for team support.

Since the files are local, there is actions to support "pushing" those files up to an iSeries library, where they become source members. This is done prior to compiling or "building" the source for the purpose of testing.

iSeries Project Library, files, members

- **iSeries Project**
 - Each iSeries project is associated with a single iSeries library
 - 1 to 1 association
 - Use **File -> New -> iSeries Project** wizard to create
- **iSeries Source Physical File**
 - Source physical files represented as folders in the project
 - CCSID, record length, IGC data and description stored as “metadata” for folder
 - Use **New -> iSeries Source Physical File** wizard to create
- **iSeries Member**
 - Members stored as files within “source” folders
 - Uses format: `memberName.membertype ORDRENT.RPGLE`
 - Use **New -> iSeries Source Member** wizard to create

iSeries Projects Perspective

The screenshot displays the iSeries Projects Perspective in WebSphere Development Studio Client Advanced Edition for iSeries. The interface is divided into several panes:


- iSeries Project Navigator:** Shows a tree view of projects under 'My iSeries_CODELAB', including 'QCBLESRC', 'PAYROLL.CBLLE', 'PAYROLL2.CBLLE', 'PAYROLLD.CBLLE', 'QDSSRC', 'EMPMST.PF', 'MSTDSP.DSPF', 'MSTDSP2.DSPF', 'MSTDSPV.DSPF', 'QRPGLSRC', 'PAYROLL.RPGL', 'PAYROLLG.RPGL', 'T7_WFLABXX', and 'toras07m_ORDLIB'.
- Editor:** Displays the source code for 'PAYROLL.CBLLE'. The code includes a header section with fields like 'PROGRAM-IDENTIFICATION DIVISION.', 'PROGRAM-IDENT.', 'AUTHOR.', 'INSTALLATION.', 'DATE-WRITTEN.', and 'DATE-COMPILED.'. It also contains a 'PROGRAM DESCRIPTION' section with details about time reporting master file maintenance.
- Outline:** Shows a hierarchical view of the project structure, including 'IDENTIFICATION DIVISION.', 'ENVIRONMENT C', 'CONFIGURATION', 'INPUT-OUTPUT', 'DATA DIVISION.', 'FILE SECTION', 'WORKING-STATEMENT DIVISION.', and 'PROCEDURE DIVISION'.
- iSeries Build Job Status:** A table showing the status of build jobs. The table has columns for Date/Time Submitted, Job, Project, and Status.

Date/Time Submitted	Job	Project	Status
Sep 18, 2003 11:57:42 AM	011903/COULTHAR/LBEH...	toras07m_ORDLIB	Finished
Sep 18, 2003 8:37:04 PM	012056/COULTHAR/LBEH...	toras07m_ORDLIB	Finished

At the bottom of the window, the status bar indicates 'Remote System Explorer | Advanced' and '© 2004, 2006 IBM Corporation'.

Here we see the iSeries Projects perspective, which you can explicitly open. The primary view is the iSeries Project Navigator that allows exploration of all existing iSeries Projects. There are wizards launchable from the toolbar for creating a new iSeries Project, or creating source physical files and source members within an existing project. The iSeries Projects perspective includes a full copy of the Remote Systems Explorer, as a view, for your convenience. This allows you to easily work with the contents of the associated library while simultaneously working with the local copies of the source within the project.

iSeries Project wizard



Here we see the iSeries Project wizard. First, give the project a name. Any name you want! Then select or create a connection (from the RSE!) that identifies the iSeries with which this project is associated. Also select the library on that iSeries where the contents of this project will be pushed to.

iSeries Project Wizard (next page)

Build style controls how the iSeries project is built on the remote system

New

iSeries Project Properties
Select and configure the active build style for this project.

Active build style:

CL Program
Command
*NONE

Configure...

This build style will upload CL programs specified in the configuration, compile them, and then run them to build this project. The compile commands can be automatically generated.

Provided by IBM plugin "iSeries Projects - Remote Build Styles Plugin" version 5.1.0

< Back Next > Finish Cancel

CL Program Build Style Configuration

Enter the project's source file that contains the COMPILE.CLLE and BIND.CLLE members that will be uploaded to build this project.

Build Source File:
QCLSRC

Automatically generate COMPILE.CLLE prior to each build
 Automatically push all changed members prior to build

OK Cancel

Specify Build Style and style configuration parameters for iSeries Project
more information on next slide ...

Command Build Style Configuration

Enter the command to be submitted to build this project.

Build Command:
|

Automatically push all changed members prior to build

OK Cancel

Here we see the rest of the iSeries Project wizard. Here you specify what to do for the Build action on a project. There are 3 IBM-supplied choices, and ISVs can add more choices. The default is to generate a CL source member containing a compile command for each member that is changed.

Build Styles

- Specify how to build the iSeries project on the remote system
- Three IBM supplied build styles
 - CL program
 - Command
 - *NONE
- ISVs can plug-in additional build styles

CL program

- Automatically generates COMPILE.CLLE and BIND. CLLE
 - Adds compile command for each source file in project
 - Uses last compile command from RSE for specified source type
 - For example, CRTBNDRPG versus CRTRPGMOD
 - At build time these two members are pushed to iSeries, compiled and run

Command

- You specify single command to run build
- Good if you have an existing build script

ISVs can plug-in additional build styles to work with their existing iSeries systems

iSeries Source Physical File Wizard

The screenshot displays two windows from the iSeries Source Physical File Wizard. The left window, titled "iSeries Source Physical File", prompts the user to "Enter or select an iSeries Project:" and shows a tree view of projects. The right window, titled "iSeries Source Physical File Parameters", allows the user to "Specify additional parameters" such as Coded character set ID, Record length, and IGC data.

Select Project

Source File = a folder in your project

- ▶ Until you "Push" your changes.
- ▶ Then a CRTSRCPF is done

Specify attributes that are used when file is finally created in associated library

File name: MYRPGLESRC

Advanced >>

Select an iSeries project and enter the name of the new source physical file being created. The source physical file will map to a folder under the selected iSeries project.

72

Here we see the wizard for creating a new iSeries source physical file. Within the project, this is actually a folder. When the project is pushed to its associated library, this result in a CRTSRCPF command being run to create a file with the attributes specified in this wizard.

iSeries Member wizard

Select the parent folder (src file)

Member = a file in your folder

- ▶ Until you "Push" your changes.
- ▶ Then an ADDPFM is done, or
- ▶ Contents of remote member are replaced

Enter the member name and select source type

73 Remote System Explorer | Advanced © 2004, 2006 IBM Corporation

Here we see the wizard for creating a new iSeries source member within an iSeries project. Actually, it is within a source physical file (aka folder) within an iSeries project. Locally, a member is really a file on disk. The file's extension is the member's type, as in ABC.RPGLE. When this project is pushed to its associated library, this will result in an ADDPFM command being run to create the file with the name and type, in its parent file.

What about existing members?


- Use Import or Add to Project action to copy them
- Files added become folders locally
- Members added are copied to that folder
- Developer works on local copy
- Full power of Eclipse at disposal

Add project action


- Right click on project, select “Show Remote Objects”
- Drill down to source file, right-click, select “Add to Project”
- Drill down to members, right-click, select “Add to Project”

Developer works on local copy

- Edits file
- Pushes changes using “Push” action
- Does a build using “Build” action
- Shares with team using “Synchronize” action



Project "Show Remote Objects" mode



Here we see an iSeries project in the iSeries Navigator, within the iSeries Projects perspective, that has a number of local files and members. Right-clicking on the project or anything in the project, gives a popup menu with the all-important "Show Remote Objects" menu item....

Project "Show Remote Objects" mode

Now showing
both local and
resources

To add a remote member to the project, select **Add To Project**


To do actions against remote objects, use **Show In Remote Systems View**

(Remote) => only exists in associated library
 (Local/Remote) => exists locally and in associated lib
 (Local/Remote) => conflict between local and remote
 otherwise => only exists locally

76 Remote System Explorer | Advanced © 2004, 2006 IBM Corporation

Once "Show Remote Objects" is enabled (it is a toggle) all the objects in the associated library for this project are shown in the iSeries Project Navigator. This navigator is called a "bleed through" view because it lists both local files/members and remote objects, files and members. However, if a file or member exists both locally and remotely, it is not shown twice. Rather, it is only shown once, and its icon and bracketed text identify it as existing in both places. The icons and text enable you to see at a glance which files/members exist only locally, only remotely, or both locally and remotely. In the latter case, the color of the icon indicates if the two are in synch or not. If not, it is an indication you need to "push" your local source to the associated library to get it in synch.

Project Build



After editing, you will want to send the changed members back to the associated library, and then compile them there. This can be done in one step with Submit Build, or in two steps with Push Selected and then Generate COMPILE.CLLE.

iSeries Build Job Status


The screenshot shows the 'iSeries Build Job Status' window. It contains a table with the following data:

Date/Time Submitted	Job	Project	Status
Sep 18, 2003 11:57:42 AM	011903/COULTHAR/LBEH...	toras07m_ORDLIB	Finished
Sep 18, 2003 8:37:04 PM	012056/COULTHAR/LBEH...	toras07m_ORDLIB	Finished
Nov 2, 2003 6:33:49 PM	035448/COULTHAR/LBEH...	My iSeries_CODELAB	Queued

Callouts in the image explain the following features:


- Job where build is running:** Points to the 'Job' column in the table.
- Status of the build:** Points to the 'Status' column in the table.
- Refresh interval determines how frequently status is updated:** Points to the 'Refresh Interval: 30 seconds' control at the bottom of the window.
- Retrieve errors from build to the iSeries Error List:** Points to the 'Retrieve Errors' button in the context menu.

This shows the Build Job Status view where you can monitor your submitted build jobs.



An example of what is generated for the build. This is a CL member. You can affect what compile command is used for each member type.

Using Projects



The typical usage scenario for iSeries projects is to use them for tasks, such as adding a feature to an existing application. Rarely will you use an iSeries project to hold all the source for an application... use an iSeries change management vendor for that. Consider a change that involves 3 developers changing a number of files...

The lead developer will create the iSeries project and synchronize it with the repository. The other developers will use the Eclipse team support to add that project to their workspace. Each will change the properties of the project to associate it with their own private library. The master library containing all the source will be on their library list, so compiles will work, but their private library will only hold the members they work on. If they use an SCM product, then they will use it to check source members out to their private library. These members and files will then be imported into their project, where they will edit them.

After editing, they will "push" their changes to their library and do a "Build" or a compile, and run and test their unique changes.

Every so often, they will do a team synchronization to give their changes to their fellow team members, and pick up the changes of those team members. After a synch, they will push their colleague's files to their own associated library and test the changes all work together.

At the end of the cycle, someone will pick one of the libraries, and use the SCM product to promote their changes back into the test and production stages.

Profiles

- The RSE is designed for team sharing
 - Of connections
 - Of filter pools
 - Of user-defined actions
 - Of compile commands
- Team sharing is enabled by profiles
 - All connections, filter pools, user actions are scoped per profile
 - Each profile is a folder within the RSE project
 - All data stored within subfolders
 - When RSE project is team-synched
 - All out-going changes sent to team repository
 - All in-coming changes received from team repository

We see that with the RSE you will be creating connections, filter pools, user defined actions and compile commands. In a team environment, we might wish to share some or all of this information to save the effort of each team member having to redundantly create them. This is especially for team members working on a shared task, such as maintenance of an application. The RSE leverages the Eclipse team support to enable this. The first order of business for effectively enable team support is to allow delineation between "team" information and "private" information per developer. The RSE enables this by using profiles. Every bit of information you create in the RSE is owned by a specific profile, and each developer decides which profiles they wish to see the information of. Team sharing is done using the Eclipse team support, which uses a central repository, and a "synchronize" action to synchronize individual developer's information with the repository.

Additional Information

- **homepage:**

<http://ibm.com/software/awdtools/iseries>

Select Library link for Labs, Tutorials, Presentations

- **newsgroup:**

<news://news.software.ibm.com/ibm.software.websphere.code400>

- **email distribution list:**

“This is the Websphere Development Studio Client for iSeries (WDSCI-L) mailing list

To post a message email: WDSCI-L@midrange.com

To subscribe, unsubscribe, or change list options,

visit: <http://lists.midrange.com/mailman/listinfo/wdsci-l>

or email: WDSCI-L-request@midrange.com

Before posting, please take a moment to review the archives at <http://archive.midrange.com/wdsci-l>.”

We hope this presentation helped you understand more about Development Studio Client iSeries application development tools. We started with an overview of our strategy for iSeries application development tools, went onto review the Remote System Explorer, the perspective for iSeries programmers to maintain and develop iSeries applications and explained how to extend RSE to include your own iSeries application development tools.

Legal information

Acknowledgement:

- This presentation is a collaborative effort of the IBM Toronto iSeries Application Development presentation team, including work done by:
Phil Coulthard, George Farr, Inge Weiss, Claus Weiss, and Don Yantzi

Disclaimer:

- The information contained in this document has not been submitted to any formal IBM test and is distributed on an as is basis without any warranty either express or implied. The use of this information or the implementation of any of these techniques is a customer responsibility and depends on the customers' ability to evaluate and integrate them into the customers' operational environment. While each item may have been reviewed by IBM for accuracy in a specific situation, there is no guarantee that the same or similar results will result elsewhere. Customers attempting to adapt these techniques to their own environment do so at their own risk.

Reproduction:

- The base presentation is the property of IBM Corporation. Permission must be obtained PRIOR to making copies of this material for any reason.



Trademarks and Disclaimers

© IBM Corporation 1994-2006. All rights reserved.
 References in this document to IBM products or services do not imply that IBM intends to make them available in every country.
 The following terms are trademarks of International Business Machines Corporation in the United States, other countries, or both:

AS/400	e-business on demand	i5/OS
AS/400e	IBM	OS/400
eServer	IBM (logo)	System i5
@server	iSeries	

Rational is a trademark of International Business Machines Corporation and Rational Software Corporation in the United States, other countries, or both.
 Intel, Intel Logo, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo, Celeron, Intel Xeon, Intel SpeedStep, Itanium, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.
 Linux is a trademark of Linus Torvalds in the United States, other countries, or both.
 Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.
 UNIX is a registered trademark of The Open Group in the United States and other countries.
 Java and all Java-based trademarks are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.
 Other company, product or service names may be trademarks or service marks of others.

Information is provided "AS IS" without warranty of any kind.

All customer examples described are presented as illustrations of how those customers have used IBM products and the results they may have achieved. Actual environmental costs and performance characteristics may vary by customer.

Information concerning non-IBM products was obtained from a supplier of these products, published announcement material, or other publicly available sources and does not constitute an endorsement of such products by IBM. Sources for non-IBM list prices and performance numbers are taken from publicly available information, including vendor announcements and vendor worldwide homepages. IBM has not tested these products and cannot confirm the accuracy of performance, capability, or any other claims related to non-IBM products. Questions on the capability of non-IBM products should be addressed to the supplier of those products.

All statements regarding IBM future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only. Contact your local IBM office or IBM authorized reseller for the full text of the specific Statement of Direction.

Some information addresses anticipated future capabilities. Such information is not intended as a definitive statement of a commitment to specific levels of performance, function or delivery schedules with respect to any future products. Such commitments are only made in IBM product announcements. The information is presented here to communicate IBM's current investment and development activities as a good faith effort to help with our customers' future planning.

Performance is based on measurements and projections using standard IBM benchmarks in a controlled environment. The actual throughput or performance that any user will experience will vary depending upon considerations such as the amount of multiprogramming in the user's job stream, the I/O configuration, the storage configuration, and the workload processed. Therefore, no assurance can be given that an individual user will achieve throughput or performance improvements equivalent to the ratios stated here.

Photographs shown are of engineering prototypes. Changes may be incorporated in production models.