



IBM Cluster Systems Management for Linux[®]



Remote Control Guide and Reference

Version 1.1

IBM Cluster Systems Management for Linux[®]



Remote Control Guide and Reference

Version 1.1

Note!

Before using this information and the product it supports, read the information in "Notices" on page 21.

Third Edition (December 2001)

This edition of the *IBM Cluster Systems Management for Linux Remote Control Guide and Reference* applies to IBM Cluster Systems Management for Linux Version 1.1, program number 5765–E88, and to all subsequent releases of this product until otherwise indicated in new editions.

IBM® welcomes your comments. A form for readers' comments may be provided at the back of this publication, or you may address your comments to the following address:

International Business Machines Corporation
Department 55JA, Mail Station P384
2455 South Road
Poughkeepsie, NY 12601-5400
United States of America

FAX (United States & Canada): 1+845+432-9405

FAX (Other Countries):

Your International Access Code +1+845+432-9405

IBMLink™ (United States customers only): IBMUSM10(MHVRCFS)

IBM Mail Exchange: USIB6TC9 at IBMMAIL

Internet e-mail: mhvrcfs@us.ibm.com

If you would like a reply, be sure to include your name, address, telephone number, or FAX number.

Make sure to include the following in your comment or note:

- Title and order number of this book
- Page number or topic related to your comment

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

© **Copyright International Business Machines Corporation 2001. All rights reserved.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

About This Book	v
Who Should Use This Book	v
How to Use This Book	v
Highlighting	v
ISO 9000	v
Related Information	v
How to Obtain Publications	vi
How to Reach Us by E-Mail	vi
Chapter 1. Cluster Systems Management Remote Control Overview	1
Hardware Configuration	1
Networking Configuration	1
Management VLAN	1
Cluster VLAN	2
Public VLAN	2
Hardware and Networking Configuration Diagrams	2
Node Attributes Table	9
Chapter 2. Remote Power	13
Remote Power Architecture	13
Remote Power Configuration	13
Writing a Custom Power Method	14
Node Configuration	14
Adding a New Node	14
Testing Remote Control	15
Chapter 3. Remote Console	17
Hardware Console Configuration	17
ESP and Serial Ports	17
Remote Console Configuration	17
Writing a Custom Console Method	17
Node Configuration	18
Verifying Remote Console Configuration	18
Verifying Equinox ESP Console	18
Equinox Configuration and Diagnostics	18
Equinox Diagnostics	18
Equinox Configuration Examples	19
Serial References	20
Notices	21
Trademarks	22
Publicly Available Software	22
GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION	26
Index	31

About This Book

This book is the updated version of the *IBM Cluster Systems Management for Linux Remote Control HOWTO* (SA22-7856-00) that was last published in June, 2001. This book describes IBM Cluster Systems Management for Linux (CSM) remote control, and the administrative tasks that can be accomplished with greater ease and efficiency by using CSM remote control functions.

Who Should Use This Book

This book is intended for system administrators who want to use IBM Cluster Systems Management for Linux. The system administrator should have experience in UNIX[®] administration and networked systems.

How to Use This Book

This book contains information that describes the IBM Cluster Systems Management for Linux Remote Control functions. It is divided into three chapters:

1. Chapter one contains an overview of IBM Cluster Systems Management for Linux Remote Control.
2. Chapter two contains information on the Remote Power function.
3. Chapter three contains information on the Remote Console function.

Highlighting

The following highlighting conventions are used in this book:

Typographic	Usage
Bold	Identifies commands, subroutines, keywords, files, structures, directories, and other items whose names are predefined by the system. Also identifies graphical objects such as buttons, labels, and icons that the user selects
<i>Italic</i>	Identifies parameters whose actual names or values are to be supplied by the user.
monospace	Identifies examples of specific data values, examples of text similar to what you might see displayed, examples of portions of program code similar to what you might write as a programmer, messages from the system, or information you should actually type.

ISO 9000

ISO 9000 registered quality systems were used in the development and manufacturing of this product.

Related Information

See the following references for information related to IBM Cluster Systems Management for Linux Remote Control:

Table 1.

Web Site	URL	Resources
IBM CSM for Linux High-performance Cluster Management	http://www.ibm.com/servers/eserver/clusters/software/csm.html	<ul style="list-style-type: none">• CSM Publications• CSM FAQ• Firmware updates

Table 1. (continued)

Web Site	URL	Resources
IBM CSM for Linux Remote Control Guide and Reference	http://www.ibm.com/servers/eserver/clusters/library/csmremot.html	<ul style="list-style-type: none"> • IBM Remote Supervisor Adapter User's Guide • IBM Universal Manageability (UM) Services • Conserver open source software • Linux Documentation Project

For information on using serial devices, see these Linux HOWTO documents, located at /usr/doc/HOWTO or on the Linux Documentation Project Web site (<http://metalab.unc.edu/mdw/index.html>):

- *Serial-HOWTO*
- *Serial-Programming-HOWTO*
- *Modem-HOWTO*

How to Obtain Publications

The IBM Cluster Systems Management for Linux publications are available as HTML and PDF files on the CD-ROM in the **/doc** directory or on the installed system in the **/opt/csm/doc** directory. The README is available on the CD-ROM in the root directory (**/**). The file names are as follows:

- *IBM Cluster Systems Management for Linux Administration Guide*, am7LXadm.pdf
- *IBM Cluster Systems Management for Linux Planning and Installation Guide*, am7LXstp.pdf
- *IBM Cluster Systems Management for Linux Remote Control Guide and Reference*, am7LXrem.pdf
- *IBM Cluster Systems Management for Linux Technical Reference*, am7LXcmd.pdf

Publications for IBM Cluster Systems Management for Linux were also available at the time of this release at <http://www.ibm.com/servers/eserver/clusters/software/csm.html>.

How to Reach Us by E-Mail

If you would like to contact us by e-mail, send your comments to cluster@us.ibm.com.

Chapter 1. Cluster Systems Management Remote Control Overview

IBM Cluster Systems Management for Linux (CSM) Remote Control software allows a system administrator to control nodes in a Linux cluster from a remote location. This essentially frees the CSM cluster from any restrictions associated with geographic node location. The two main functions for CSM Remote Control are the remote power and remote console commands. The **rpower** command allows an administrator to query, power on, power off, and reset remote nodes. The **rconsole** command allows an administrator to open a console for a remote node. The CSM administrator runs the **rpower** and **rconsole** commands from a control node called the management server. See the man pages or the *IBM Cluster Systems Management for Linux Technical Reference* for detailed command usage information.

Hardware Configuration

CSM Remote Control cluster software is dependent upon the hardware configuration. For IBM Netfinity® and xSeries™ clusters, CSM hardware control point and internal service processor database attribute values must match the Remote Supervisor adapter (RSA) host names and Internal Service Processor (ISP) text IDs, respectively. This will ensure that the remote control software understands the physical connections and can properly control the target nodes.

The remote power command, **rpower**, is dependent on the physical cabling of the Remote Supervisor adapters and when applicable, the ISPs they control. It is also dependent on the adapter host names and the ISP Text IDs. The remote console command, **rconsole** is dependent on the cabling of the remote console server and the cabling description in the CSM database. These details will be explained in the remote power and remote console sections to help you understand the interdependencies between the hardware and software. With the correct definitions, the **rpower** and **rconsole** commands will target the intended node or node group. (You can control hardware other than the supported IBM hardware by writing custom power and console methods, which is discussed in later sections.)

CSM for Linux is an integral part of the IBM @server Cluster 1300 platform for deploying Linux applications requiring a cluster. The IBM @server Cluster 1300 includes the following hardware:

- xSeries 330 and 342 nodes
- Remote Supervisor adapters (RSAs)
- Ethernet PCI adapters
- Equinox Serial Providers (ESPs).

Networking Configuration

For security reasons, the networking configuration must separate the remote control functions **rpower** and **rconsole** from other clusters functions. An efficient way to do this is to create a virtual LAN (VLAN) for the remote control functions, which is separate and distinct from the more general purpose VLAN connecting the cluster's nodes. Optionally, the cluster VLAN can be isolated from the larger network. See the following sections for more details.

Management VLAN

The management VLAN connects the management server to the cluster's terminal server(s) and to the Remote Supervisor adapter(s) installed in some or all of the nodes. Since this is intended to be an isolated network, traffic flows without encryption using clear text authentication. Access to the **rpower** and **rconsole** commands is limited to root user on the management server. All other nodes have no access to the Management VLAN.

Cluster VLAN

A cluster VLAN subdivides the Ethernet switch so each node can use the cluster VLAN for Network I/O (NFS, tftp, ftp) and job control traffic.

Public VLAN

Each node connects to a public VLAN to allow authorized access to the nodes in the cluster. You may choose to combine the cluster VLAN and public VLAN.

Hardware and Networking Configuration Diagrams

The following diagram (Figure 1) shows the hardware and networking configuration required for using CSM remote control with IBM xSeries 330 nodes. (Figure 3 shows the configuration for IBM xSeries 342 nodes.) See “Node Attributes Table” on page 9 for example node attribute definitions corresponding to Figure 1.

In Figure 1, the Management Server connects to the Management VLAN and the Cluster VLAN through Ethernet adapters. The terminal server, an Equinox Serial Provider (ESP) in this example, connects to the Management VLAN through its Ethernet adapter, and to the cluster nodes through their serial (COM) ports as shown. (An ESP-16 can connect up to 16 nodes. Other terminal servers may have different capacities.) The nodes must be connected to the Cluster VLAN through their Ethernet adapters, and directly or indirectly to an IBM Netfinity Remote Supervisor adapter (RSA). The Management VLAN connects to the RSA in select nodes. (One RSA is required for every 10 nodes.) The RSAs connect to their own node's ISP port, and up to 9 more node ISP ports are daisy-chained from there. Configuration for a Public VLAN is optional and can be defined by the system administrator.

Note: Figures 1-4 assume an installation where eth0 is defined as the first Ethernet adapter in the system. IBM suggests using this type of installation, which can be achieved by connecting the eth0 adapter directly to the Cluster VLAN.




Figure 1. CSM Remote Control Hardware and Networking Configuration for IBM xSeries 330 Nodes

The following diagram (Figure 2) shows the relationship between the CSM node database attributes and the actual (internal) hardware names used in Figure 1. For remote power and remote console to work as expected, this matching of database attribute names to the internal hardware values must be correct for all RSAs, ISPs, and ESPs in the cluster.




Figure 2. CSM Remote Control Database Attributes for IBM xSeries 330 Nodes

The following diagram (Figure 3) shows the hardware and networking configuration required for using CSM remote control with IBM xSeries 342 nodes. This diagram shows two ways of cabling the RSAs. They can each have their own connection to the Management VLAN (mgtn03.pok.ibm.com – mgtn12.pok.ibm.com), or a number of them can be daisy-chained from one RSA connected to the Management VLAN (mgtn13.pok.ibm.com). See Figure 4 for a more detailed view of a few nodes from Figure 3.




Figure 3. CSM Remote Control Hardware and Networking Configuration for IBM xSeries 342 Nodes

The following diagram (Figure 4) is a more detailed view of a few nodes from Figure 3. The diagram shows the relationship between the CSM node database attributes and the actual (internal) hardware names used in Figure 3. For remote power and remote console to work as expected, this matching of database attribute values to the internal hardware names must be correct for all RSAs and ESPs in the cluster.




Figure 4. CSM Remote Control Database Attributes for IBM xSeries 342 Nodes

Node Attributes Table

For planning purposes, it is helpful to fill out a table describing all of the nodes' attributes. In the following example, the cluster has 20 nodes. The attributes correspond to the hardware and networking configuration shown in Figure 1 on page 3. The following page contains a blank template you can fill out.

Note: The console port number (*ConsolePortNum*) is the physical port that the node's serial port is connected to in the console server hardware.

Table 2. Node Attributes Table: Example

Hostname	HWControlPoint	Power Method	Svc ProcName	ConsoleServerName	Console Server Number	Console Method	Console PortNum	HWType	Install/Method
clsn01.pok.ibm.com	mgtn03.pok.ibm.com	netfinity	node01	mgtn02.pok.ibm.com	1	esp	0	netfinity	csmonly
clsn02.pok.ibm.com	mgtn03.pok.ibm.com	netfinity	node02	mgtn02.pok.ibm.com	1	esp	1	netfinity	csmonly
clsn03.pok.ibm.com	mgtn03.pok.ibm.com	netfinity	node03	mgtn02.pok.ibm.com	1	esp	2	netfinity	csmonly
clsn04.pok.ibm.com	mgtn03.pok.ibm.com	netfinity	node04	mgtn02.pok.ibm.com	1	esp	3	netfinity	csmonly
clsn05.pok.ibm.com	mgtn03.pok.ibm.com	netfinity	node05	mgtn02.pok.ibm.com	1	esp	4	netfinity	csmonly
clsn06.pok.ibm.com	mgtn03.pok.ibm.com	netfinity	node06	mgtn02.pok.ibm.com	1	esp	5	netfinity	kickstart
clsn07.pok.ibm.com	mgtn03.pok.ibm.com	netfinity	node07	mgtn02.pok.ibm.com	1	esp	6	netfinity	kickstart
clsn08.pok.ibm.com	mgtn03.pok.ibm.com	netfinity	node08	mgtn02.pok.ibm.com	1	esp	7	netfinity	kickstart
clsn09.pok.ibm.com	mgtn03.pok.ibm.com	netfinity	node09	mgtn02.pok.ibm.com	1	esp	8	netfinity	kickstart
clsn10.pok.ibm.com	mgtn03.pok.ibm.com	netfinity	node10	mgtn02.pok.ibm.com	1	esp	9	netfinity	kickstart
clsn11.pok.ibm.com	mgtn04.pok.ibm.com	netfinity	node01	mgtn02.pok.ibm.com	1	esp	a	netfinity	csmonly
clsn12.pok.ibm.com	mgtn04.pok.ibm.com	netfinity	node02	mgtn02.pok.ibm.com	1	esp	b	netfinity	csmonly
clsn13.pok.ibm.com	mgtn04.pok.ibm.com	netfinity	node03	mgtn02.pok.ibm.com	1	esp	c	netfinity	csmonly
clsn14.pok.ibm.com	mgtn04.pok.ibm.com	netfinity	node04	mgtn02.pok.ibm.com	1	esp	d	netfinity	csmonly
clsn15.pok.ibm.com	mgtn04.pok.ibm.com	netfinity	node05	mgtn02.pok.ibm.com	1	esp	e	netfinity	csmonly
clsn16.pok.ibm.com	mgtn04.pok.ibm.com	netfinity	node06	mgtn02.pok.ibm.com	1	esp	f	netfinity	kickstart
clsn17.pok.ibm.com	mgtn04.pok.ibm.com	netfinity	node07	mgtn03.pok.ibm.com	2	esp	0	netfinity	kickstart
clsn18.pok.ibm.com	mgtn04.pok.ibm.com	netfinity	node08	mgtn03.pok.ibm.com	2	esp	1	netfinity	kickstart
clsn19.pok.ibm.com	mgtn04.pok.ibm.com	netfinity	node09	mgtn03.pok.ibm.com	2	esp	2	netfinity	kickstart
clsn20.pok.ibm.com	mgtn04.pok.ibm.com	netfinity	node10	mgtn03.pok.ibm.com	2	esp	3	netfinity	kickstart

Chapter 2. Remote Power

The remote power command, **rpower**, reboots and resets hardware, powers hardware on and off, and queries node power state. See the **rpower** man page or the *IBM Cluster Systems Management for Linux Technical Reference* for detailed usage information.

The **rpower** command is structured so it can be easily expanded for another hardware type. It uses the *PowerMethod* attribute in the CSM database to determine which underlying hardware control routine will be used. If the *PowerMethod* attribute is *netfinity*, the hardware control routine called is **/opt/csm/bin/netfinity_power**. To use other hardware types you need to change the entry in CSM and write a new custom power method named **/opt/csm/bin/PowerMethod_power**. See “Writing a Custom Power Method” on page 14.

Remote Power Architecture

CSM hardware configuration consists of the following components:

- Management Server
- Isolated Management Network (Management VLAN)
- Remote Supervisor adapters (RSAs)
- Ethernet PCI adapters.

For optimal security, the components must be configured so that the management server is the only PCI adapter attached to the management VLAN, and has sole access to the console servers and the RSA hardware control points.

For each node definition in the CSM database, the *HWControlPoint* attribute value must match the appropriate RSA host name. Likewise, the node *SvcProcName* attribute value in the database must match the text ID of the node's ISP or RSA.

In xSeries 330s, each RSA manages a group of up to ten nodes. By default, each group contains nodes with *SvcProcName* attributes node01 – node10. Since you may have more than one group of nodes, the host name *HWControlPoint* attribute specifies the RSA associated with each group.

Note: The CSM **definnode** and **addnode** commands use *nodexx* as the default *SVCPProcName*. Whether you accept these default names or specify others (for example, node short host names), you must manually set the ISP or RSA text IDs to match.

Remote Power Configuration

There is a direct relationship between the hardware configuration and the CSM database information created with the **definnode** and **addnode** commands. Planning is required prior to running **definnode** or **addnode** to ensure that nodes are defined correctly. For detailed information on the **definnode** and **addnode** commands, see the man page or the *IBM Cluster Systems Management for Linux Technical Reference*. For the define node procedure, see the *IBM Cluster Systems Management for Linux Planning and Installation Guide*.

You can use the **lsnode** command to verify the *SvcProcName* of the node, and the **chnode** commands to change the *SVCPProcName* value when necessary.

You can telnet or establish an http connection to a node's *HWControlPoint* (the host name of an RSA) and use the Advanced Systems Management (ASM) panels or Web pages to verify RSA and ISP text IDs. (You need to know the ISP and RSA user IDs and passwords to make these connections.) To change an ISP's text ID, you must reboot the node of interest using the Remote Supervisor adapter Firmware Update Diskette. The diskette can be downloaded from the “Firmware updates” links at:

<http://www.ibm.com/servers/eserver/clusters/software/csm.html>. The same utilities are available on the Remote Supervisor Adapter Support CD that comes with the adapter. You can also use telnet or Web access to change its text ID by editing "ASM Name" under "Setup/Settings" / "System".

The RSA, and ISP user IDs and passwords are recorded in the `/etc/opt/csm/netfinity_power.config` file on the CSM management server. The file is created and updated by the **addnode** and **definnode** commands, and can be edited manually as required. For ISPs and RSAs, the default user ID shipped with the system is "USERID" and the default password is "PASSWORD" (p-a-s-s-w-zero-r-d). The **addnode** and **definnode** commands write these default values to the **netfinity_power.config** file. IBM suggests you change these default values as soon as possible. To change ISP and RSA user IDs and passwords, use the RSA Firmware Update Diskette, the support CD, or telnet or Web access.

Writing a Custom Power Method

You can write a custom power method to suit your hardware environment. Each environment has its own routine (in `/opt/csm/bin/PowerMethod_power`). The **rpower** command runs the power method and passes the following parameters. If you write a new power method to manage another power type, you must include these parameters in the order shown in the interface definition:

1. *option_string*
2. *target_node_hostname*
3. *HWControlPoint_hostname*
4. *SvcProcName*
5. *remote_action*

Node Configuration

Remote power requires the following CSM attributes for each node:

HWControlPoint

Host name of the RSA on the Management VLAN providing access to the node's remote power capabilities. For an xSeries 330 node, it is the host name of the RSA to which the node's ISP is daisy-chained. For an xSeries 342 node, it is the host name of the node's RSA (if the RSA is connected directly to the Management VLAN), or the host name of the RSA on the Management VLAN to which this node's RSA is daisy-chained.

PowerMethod Determines the program to invoke for a specific type of hardware power control. For example: *netfinity* (which corresponds to `/opt/csm/bin/netfinity_power`).

SvcProcName For x330s, the node's ISP text ID. For x342s, the node's RSA text ID. For example: node01.

To specify the user IDs and passwords for remote power, edit the `/etc/opt/csm/netfinity_power.config` file, and ensure that the ISPs, and RSAs in the nodes have the user IDs and passwords listed in this file.

To replace a node, set the user ID, password, and text ID of the new node's ISP or RSA to the values that were configured for the replaced node.

Adding a New Node

Adding a new node requires some initial planning using the "Node Attributes Table" on page 9 and the **Isnode** command. The text ID of the node's ISP or RSA and the *SvcProcName* attribute must match. The host name of the RSA controlling the node and *HWControlPoint* attribute must also match. Verify that these attributes are correct before running the **definnode** or **addnode** command.

Testing Remote Control

Test your remote control functions before using them in a production environment. Use the **rpower** command to run **query**, **power on**, and **power off** on the nodes to verify that they are configured correctly and are responding accordingly. See the **rpower** man page or the *IBM Cluster Systems Management for Linux Technical Reference* for detailed examples.

Chapter 3. Remote Console

The remote console command, **rconsole**, opens a remote console for each node specified with the command. The method used for opening a remote console is dependent upon the hardware and software supporting the remote console. This section describes remote console hardware configuration, software support, and the relationship between them.

Notes:

1. For Equinox Serial Provider (ESP) terminal servers, you must install Equinox `espx` RPM version 3.02 or later on the Management Server, because this is the minimum level required by Red Hat version 7.1
2. Ethernet adapters on some Equinox terminal servers are only 10 Mb/s, so you must ensure the ports on the Ethernet switches are set accordingly.

Hardware Console Configuration

The console or terminal server is connected to the management VLAN by an Ethernet connection. Each console port is connected to the serial port of a node. The default console configuration is Equinox (ESP); any other terminal server hardware requires different configuration by the system administrator.

ESP and Serial Ports

The serial ports' connection from the ESP to the nodes must be in the same order that the nodes are defined for the Equinox console server in CSM. The CSM database has a number associated with each ESP, and with each port within the ESP. Attention to detail is required when configuring both the hardware connectivity and the definitions of this relationship in the CSM database. More detailed information on this relationship is covered in "Remote Console Configuration".

Remote Console Configuration

The **definnode** command updates the CSM database with the information describing the console server and each node's associated port number. There is a direct relationship between the hardware configuration and the CSM database information created with this command. Planning is required prior to running **definnode** to ensure that nodes are defined correctly. (A sample worksheet is shown in "Node Attributes Table" on page 9.) This section will expand on the CSM database contents and its relationship to the hardware and the **rconsole** command.

The remote console function supports two software environments: Equinox and Conserver. You specify which environment you want to use for the console for each node with the *ConsoleMethod* attribute. Supported values for this attribute are *esp* and *conserver*. For more information about the Conserver software environment, see the Conserver open source software Web site (<http://www.conserver.com>).

Writing a Custom Console Method

You can write a custom console method to suit your hardware environment. Each environment has its own routine (in `/opt/csm/bin/ConsoleMethod_console`) that returns the command that **rconsole** uses in the **xterm** window where the command is run. For example:

- *esp_console*: `cu -l /dev/ttyQ01e0 -s 9600`
- *conserver_console*: `console - Mlocalhost hostname`

The following parameters are passed to any console method. If you write a new console method to manage another console type, you must include these parameters in the order shown in the interface definition:

1. *console_server_hostname*
2. *target_system_hostname*
3. *console_port_number*

4. *console_server_number*

Node Configuration

The `/etc/lilo.conf` and `/etc/inittab` files on each node must contain the following settings, which direct the console to the serial port. When `installnode` is run, these files are automatically modified on each node.

Note: To enable remote console for a CSM-only installation, you must reboot all new nodes after running `installnode`.

- **/etc/lilo.conf** file:

```
serial = 1,9600n8
append = "console=tty1 console=ttyS1,9600"
```

- **/etc/inittab** file:

```
s1:345:respawn:/sbin/agetty 9600 ttyS1 xterm
```

Remote console requires the following CSM attributes for each node:

<i>ConsoleServerName</i>	The console server host name. For example: mgtn02.pok.ibm.com.
<i>ConsoleServerNumber</i>	The console server number. For example: some number, 1 – N. For ESP this is the ESP number associated with the Equinox Serial Provider system.
<i>ConsoleMethod</i>	Determines the program to invoke for a specific type of console server. The attribute value is one of two options: <i>esp</i> <i>conserver</i> .
<i>ConsolePortNum</i>	The console port number. For ESP, this must be a 0 – f single hexadecimal digit.

Verifying Remote Console Configuration

The `Isnode -AI` command lists the node attributes in the CSM database. When the host parameter is specified, either by host name or IP address, the command displays all of the host's attributes.

Verifying Equinox ESP Console

To verify the remote console configuration, use the `esptty` and `Isnode` commands. The `esptty` command opens the Equinox Serial Provider (ESP) Port Diagnostic Utility. This utility allows system administrators and users to verify or modify port characteristics or dump status information about ESP Serial Hub serial ports (ttys).

You can also verify or change a Console Server configuration using the `espcfg` command. This command opens the ESP Configuration Wizard, which allows you to manage Equinox Service Processors. For further information on these verification commands, see the command man pages.

Equinox Configuration and Diagnostics

Note: The `espcfg`, `espdial`, and `esptty` commands are installed when you install the ESP RPM. For more information about ESP software configuration, see `/usr/doc/esp-3.00/INSTALL`.

Equinox Diagnostics

To test the Equinox hardware configuration:

1. Ping the console server from the management server to test the connection.
2. Run the `espcfg` command to:
 - discover ESPs on a network

- configure ESPs
 - install ESPs
 - remove ESPs
 - replace ESPs
 - update ESP flash memory
3. Run the **espdia** command to:
 - obtain ESP device and driver information
 - obtain detailed information about a selected ESP serial port
 4. Verify that the ESP is on the management network associated with the management server by comparing the IP address and *SubNetMask* attribute in the ESP panel to the **ifconfig** command output.

Equinox Configuration Examples

1. To query Equinox Serial Provider (ESP) ports on a remote cluster, type:

```
esptty -c
```

Output is similar to:

ESP Device	UdpState	TcpState	Ports
/dev/esp1	HEARTBEAT	TCP_ACTIVE	16
/dev/esp2	HEARTBEAT	TCP_ACTIVE	16
/dev/esp3	HEARTBEAT	TCP_ACTIVE	16
/dev/esp4	HEARTBEAT	TCP_ACTIVE	16
/dev/esp5	HEARTBEAT	TCP_ACTIVE	16
/dev/esp6	HEARTBEAT	TCP_ACTIVE	16

2. To list the ttys for each port, type:

```
ls /dev/ttyQ*
```

The format of the tty is: **ttyQesp_numberport_number** where:

- *esp_number* is two digits starting with 01
- *port_number* is one hexadecimal digit 0 – f.

Output is similar to:

```
/dev/ttyQ01e0 /dev/ttyQ02e4 /dev/ttyQ03e8 /dev/ttyQ04ec /dev/ttyQ06e0
/dev/ttyQ01e1 /dev/ttyQ02e5 /dev/ttyQ03e9 /dev/ttyQ04ed /dev/ttyQ06e1
/dev/ttyQ01e2 /dev/ttyQ02e6 /dev/ttyQ03ea /dev/ttyQ04ee /dev/ttyQ06e2
/dev/ttyQ01e3 /dev/ttyQ02e7 /dev/ttyQ03eb /dev/ttyQ04ef /dev/ttyQ06e3
/dev/ttyQ01e4 /dev/ttyQ02e8 /dev/ttyQ03ec /dev/ttyQ05e0 /dev/ttyQ06e4
/dev/ttyQ01e5 /dev/ttyQ02e9 /dev/ttyQ03ed /dev/ttyQ05e1 /dev/ttyQ06e5
/dev/ttyQ01e6 /dev/ttyQ02ea /dev/ttyQ03ee /dev/ttyQ05e2 /dev/ttyQ06e6
/dev/ttyQ01e7 /dev/ttyQ02eb /dev/ttyQ03ef /dev/ttyQ05e3 /dev/ttyQ06e7
/dev/ttyQ01e8 /dev/ttyQ02ec /dev/ttyQ04e0 /dev/ttyQ05e4 /dev/ttyQ06e8
/dev/ttyQ01e9 /dev/ttyQ02ed /dev/ttyQ04e1 /dev/ttyQ05e5 /dev/ttyQ06e9
/dev/ttyQ01ea /dev/ttyQ02ee /dev/ttyQ04e2 /dev/ttyQ05e6 /dev/ttyQ06ea
/dev/ttyQ01eb /dev/ttyQ02ef /dev/ttyQ04e3 /dev/ttyQ05e7 /dev/ttyQ06eb
/dev/ttyQ01ec /dev/ttyQ03e0 /dev/ttyQ04e4 /dev/ttyQ05e8 /dev/ttyQ06ec
/dev/ttyQ01ed /dev/ttyQ03e1 /dev/ttyQ04e5 /dev/ttyQ05e9 /dev/ttyQ06ed
/dev/ttyQ01ee /dev/ttyQ03e2 /dev/ttyQ04e6 /dev/ttyQ05ea /dev/ttyQ06ee
/dev/ttyQ01ef /dev/ttyQ03e3 /dev/ttyQ04e7 /dev/ttyQ05eb /dev/ttyQ06ef
/dev/ttyQ02e0 /dev/ttyQ03e4 /dev/ttyQ04e8 /dev/ttyQ05ec
/dev/ttyQ02e1 /dev/ttyQ03e5 /dev/ttyQ04e9 /dev/ttyQ05ed
/dev/ttyQ02e2 /dev/ttyQ03e6 /dev/ttyQ04ea /dev/ttyQ05ee
/dev/ttyQ02e3 /dev/ttyQ03e7 /dev/ttyQ04eb /dev/ttyQ05ef
```

3. To query remote nodes, enter:

```
lsnode -A1 c1sn03
```

Output is similar to:

```
Hostname = clsn03.pok.ibm.com
OSVersion =
UniversalId = 0
InstallDisk =
ConsoleServerName = mgtn02.pok.ibm.com
ConfigChanged = 0
Status = 1
HWControlPoint = mgtn03.pok.ibm.com
OSType =
SvcProcName = node03
InstallMethod =
PowerMethod = netfinity
Macaddr =
PowerStatus = 127
ConsolePortNum = 2
HWType = netfinity
HWModel =
OSDistribution =
ConsoleMethod = esp
LParID =
OSKernel =
InstallDiskType =
ConsoleServerNumber = 1
HWSerialNum =
```

Serial References

For more information on using serial devices, see the following Linux HOWTO documents, located at **/usr/doc/HOWTO** or on the Linux Documentation Project Web site (<http://metalab.unc.edu/mdw/index.html>):

- *Serial-HOWTO*
- *Serial-Programming-HOWTO*
- *Modem-HOWTO*

Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

IBM World Trade Asia Corporation
Licensing
2-31 Roppongi 3-chome, Minato-ku
Tokyo 106, Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
Department LJEB/P905
2455 South Road Road
Poughkeepsie, New York 12601-5400
U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrates programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. You may copy, modify, and distribute these sample programs in any form without payment to IBM for the purposes of developing, using, marketing, or distributing application programs conforming to IBM's application programming interfaces.

Trademarks

The following terms are trademarks of International Business Machines Corporation in the United States, other countries, or both:

- IBM, AIX, AIX 5L, Netfinity, RS/6000, SP, and the e (logo) are trademarks or registered trademarks of International Business Machines Corporation.
- Equinox is a trademark of Equinox Systems, Inc.
- Linux is a registered trademark of Linus Torvalds.
- Myrinet is a trademark of Myricom, Inc.
- Red Hat and RPM are trademarks of Red Hat, Incorporated.
- Java and all Java-based trademarks and logos are registered trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.
- UNIX is a registered trademark of The Open Group in the United States and other countries.
- Other company, product, or service names may be the trademarks or service marks of others.

Publicly Available Software

IBM Cluster Systems Management for Linux includes software that is publicly available:

Advanced TFTP

Advanced TFTP (atftp) is a client/server implementation of the TFTP protocol. It is licensed under the GNU General Public License (GNU GPL), which can be found at <http://www.gnu.org/copyleft/gpl.html>.

cfengine

A software package that is licensed under GPL and is used to create customization scripts.

Conserver	An application that adds logging and multi-user access for remote administration of serial ports, using locally installed multi-port serial interfaces or "reverse-telnet" to console servers or both.
DBD-CSV, Text-CSV_XS	Licensed by GPL or Artistic, these are dynamically loaded Perl modules.
DBI	Licensed by GPL or Artistic, this is a dynamically loaded Perl module.
fping	Copyrighted by Stanford University, this is executed as a separate binary.
Kerberos	Provides authentication of the execution of remote commands.
Perl	Practical Extraction and Report Language is licensed under the Artistic license.
Perl-to-C extensions	Practical Extraction and Report Language-to-C extensions is distributed under the Artistic license.
Pidentd	Public domain program by Peter Eriksson that implements the RFC-1413 identification server.
SQL-Statement	Licensed under GPL or Artistic, this is a dynamically loaded Perl module.
SYSLinux	SYSLinux includes PXELINUX, which CSM uses to control the behavior of network boots. SYSLinux is licensed under the GNU GPL.

This book discusses the use of these products only as they apply specifically to the IBM Cluster Systems Management for Linux product.

Note: The distribution for these products includes the source code and associated documentation. All copyright notices and license conditions in the documentation must be respected. You can find version and distribution information for each of these products in the *Specified Operating Environment* section of the *IBM Cluster Systems Management for Linux Planning and Installation Guide*. For these non-IBM products, the following license terms apply in lieu of the International Program License Agreement.

The inclusion herein of copies of various licenses is not meant to imply endorsement of the principles, methodologies, or views that are contained therein, either express or implied.

For the fping open source code, see the following URL: <http://www.fping.com> (The license is imbedded in the source code.)

For the fping open source code, the following terms apply:

Copyright (c) 1991, 1994, 1997 Board of Trustees
Leland Stanford Jr. University

Redistribution and use in source and binary forms are permitted provided that the above copyright notice and this paragraph are duplicated in all such forms and that any documentation, advertising materials, and other materials related to such distribution and use acknowledge that the software was developed by Stanford University. The name of the University may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

For the DBD-CSF, DBI, Text-CSV_XS and SQL-Statement open source code licensed under the "Artistic License," the following terms apply:

Definitions

"Package" refers to the collection of files distributed by the

Copyright Holder, and derivatives of that collection of files created through textual modification.

"Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder as specified below.

"Copyright Holder" is whoever is named in the copyright or copyrights for the package.

"You" is you, if you're thinking about copying or distributing this Package.

"Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)

"Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that all copies contain the original copyright notices and associated disclaimers.
2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.
3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when you changed that file, and provided that you do at least ONE of the following:
 - a. place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as uunet.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.
 - b. use the modified Package only within your corporation or organization.
 - c. rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide a separate manual page for each non-standard executable that clearly documents how it differs from the Standard Version.
 - d. make other distribution arrangements with the Copyright Holder.
4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:
 - a. distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.
 - b. accompany the distribution with the machine-readable source of the Package with your modifications.
 - c. give non-standard executables non-standard names, and clearly document the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.
 - d. make other distribution arrangements with the Copyright Holder.
5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that you do not advertise this Package as a product of your own. You may embed this Package's interpreter within an executable of

yours (by linking); this shall be construed as a mere form of aggregation, provided that the complete Standard Version of the interpreter is so embedded.

6. The scripts and library files supplied as input to or produced as output from the programs of this Package do not automatically fall under the copyright of this Package, but belong to whomever generated them, and may be sold commercially, and may be aggregated with this Package. If such scripts or library files are aggregated with this Package via the so-called "undump" or "unexec" methods of producing a binary executable image, then distribution of such an image shall neither be construed as a distribution of this Package nor shall it fall under the restrictions of Paragraphs 3 and 4, provided that you do not represent such an executable image as a Standard Version of this Package.
7. C subroutines (or comparably compiled subroutines in other languages supplied by you and linked into this Package in order to emulate subroutines and variables of the language defined by this Package shall not be considered part of this Package, but are the equivalent of input as in Paragraph 6, provided these subroutines do not change the language in any way that would cause it to fail the regression tests for the language.
8. Aggregation of this Package with a commercial distribution is always permitted provided that the use of this Package is embedded; that is, when no overt attempt is made to make this Package's interfaces visible to the end user of the commercial distribution. Such use shall not be construed as a distribution of this Package.
9. The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.
10. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

For the Advanced TFTP (atftp), cfengine, and SYSLinux code, licensed under the GNU GENERAL PUBLIC LICENSE Version 2, June 1991, see the following.

Copyright (c) 1989, 1991 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program. You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.
2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:
 - a. You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
 - b. You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
 - c. If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work

based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:
 - a. Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
 - b. Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
 - c. Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.
5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.
6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.
7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or

otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances. It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.
9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.
12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Index

A

about this book v
adding a new node 14
architecture, Remote Power 13
audience of this book v

C

Cluster Systems Management Remote Control
 overview 1
cluster VLAN 2
configuration, hardware 1
configuration, hardware console 17
configuration, networking 1
configuration, Remote Console 17
configuration, Remote Power 13
configuration and diagnostics, Equinox 18
configuration diagrams, hardware and networking 2
configuration examples, Equinox 19
console method, custom 17
CSM project e-mail address vi

D

diagnostics, configuration, Equinox 18
diagnostics, Equinox 18

E

e-mail address for CSM vi
Equinox configuration and diagnostics 18
Equinox configuration examples 19
Equinox diagnostics 18
Equinox ESP Console, verifying 18
ESP and Serial Ports 17

H

hardware and networking configuration diagrams 2
hardware configuration 1
hardware console configuration 17
highlighting v
how to use this book v

I

ISO 9000 v

M

management VLAN 1

N

networking configuration 1
node, adding new 14

node attributes table 9
node configuration, Remote Console 18
node configuration, Remote Power 14

O

overview, Cluster Systems Management Remote Control 1

P

power method, custom 14
prerequisite knowledge for this book v
public VLAN 2
publications, obtaining vi
publicly available software 22

R

references, serial 20
related information v
Remote Console 17
Remote Console configuration 17
Remote Console configuration, verifying 18
Remote Console node configuration 18
Remote Control, testing 15
Remote Power 13
Remote Power architecture 13
Remote Power configuration 13
Remote Power node configuration 14

S

Serial Ports, ESP 17
serial references 20

T

testing Remote Control 15
trademarks 22

V

VLAN, cluster 2
VLAN, management 1
VLAN, public 2

Readers' Comments — We'd Like to Hear from You

IBM Cluster Systems Management for Linux®
Remote Control Guide and Reference
Version 1.1

Publication No. SA22-7856-02

Overall, how satisfied are you with the information in this book?

	Very Satisfied	Satisfied	Neutral	Dissatisfied	Very Dissatisfied
Overall satisfaction	<input type="checkbox"/>				

How satisfied are you that the information in this book is:

	Very Satisfied	Satisfied	Neutral	Dissatisfied	Very Dissatisfied
Accurate	<input type="checkbox"/>				
Complete	<input type="checkbox"/>				
Easy to find	<input type="checkbox"/>				
Easy to understand	<input type="checkbox"/>				
Well organized	<input type="checkbox"/>				
Applicable to your tasks	<input type="checkbox"/>				

Please tell us how we can improve this book:

Thank you for your responses. May we contact you? Yes No

When you send comments to IBM, you grant IBM a nonexclusive right to use or distribute your comments in any way it believes appropriate without incurring any obligation to you.

Name

Address

Company or Organization

Phone No.

Readers' Comments — We'd Like to Hear from You
SA22-7856-02



Cut or Fold
Along Line

Fold and Tape

Please do not staple

Fold and Tape

PLACE
POSTAGE
STAMP
HERE

IBM Corporation
Department 55JA, Mail Station P384
2455 South Road
Poughkeepsie NY 12601-5400

Fold and Tape

Please do not staple

Fold and Tape

SA22-7856-02

Cut or Fold
Along Line



Program Number: 5765-E88

SA22-7856-02

