

IBM Poughkeepsie
IBM @server zSeries 900

zSeries Channel Communication Supported FICON Topologies, Link Addressing, and Operation

Information contained in this document/presentation is still going through IBM design review. Updates will be made to this document. Contact the owner when you require to have the latest version of this document/presentation.

This document/presentation contains information of a proprietary nature. ALL INFORMATION CONTAINED HEREIN SHALL BE KEPT IN CONFIDENCE. None of this information shall be divulged to persons other than IBM employees authorized by the nature of their duties to receive such information, or individuals of organizations authorized by IBM Corporation in accordance with existing policy regarding release of company information.

© Copyright IBM Corp. 2000, 2001

Kenneth (Ken) Trowell
S/390 and z900
Poughkeepsie
kenneth.t@us.ibm.com
Tel: (845)-433-6552

zSeries FICON - Cascade Switching

- zSeries FICON Cascade switching provides a channel connectivity solution for connection of zSeries Processors and/or Control Units that are installed in extended distance locations
 - ▶ This presentation is one of a series that cover FICON cascade switching
- zSeries I/O configuration infrastructure savings to a customer are:
 - ▶ Large reduction of expensive inter-site fibre links
 - ▶ Reduction in the number of zSeries FICON channels
 - ▶ Reduction in the number of Fibre Channel switch ports
- This allows the zSeries Processors to further participate in the Fibre Channel Fabric infrastructure

zSeries FICON Topology

● FICON native (FC mode - Fibre Channel) Topologies

► Point-to-Point

- No Fibre Channel switch in the channel to control unit path
- FICON channel and CU - Link recovery

► Switched Point-to-Point

- One Fibre Channel switch in the channel to control unit path
- FICON channel and CU - Link and F_Port recovery

► 2-switch Cascade Switching

- There can be up to two Fibre Channel switches in the channel to control unit path
- There maybe more than two switches in the *fibre channel fabric*, but there must only be one possible switching hop between the channel and the target control unit port
- High integrity fabric and persistent F_Port port addresses
- FICON channel and CU - Link, F_port and Fabric recovery


► Multi-switch Cascade Switching

- There can be up multiple Fibre Channel switches in the channel to control unit path
- There maybe more than two switches in the *fibre channel fabric*, and there can be more than one switching hop between the channel and the target control unit port
- High integrity fabric and persistent F_Port port addresses
- FICON channel and CU - Link, F_port and Fabric recovery


► Full cascade switching

- More than two fibre channel switches in the channel to control unit path, total SAN manager, and N_Port port address discovery
- One or more possible switching routes between the channel and the target control unit


FICON - Point-to-Point and Switched Point-to-Point



No FC switch in the channel to CU path. But there can be multiple channel images (LPAR) and multiple CU images sharing the one communication link. .




One FC switch in the channel to CU path. The channel can address multiple CUs on different FC links (F_Port to N_Port links). The LSN (logical Switch Number) is a z/OS term, and is used by HCD, IOCP and IO-OPs. Switch @ is the same as bit 1 -8 of the 24 bit FC port address.




The zSeries and S/390 processors will support both FICON Point-to-Point and Switched Point-to-Point connectivity from the same processor image to the same CU image.

FICON - Single Switch - Switched P-to-P

FICON - Switched Point-to-Point Topology



The LSN (logical Switch Number) is a z/OS term, and is used by HCD, IOCP and IO-OPs. The LSN has to be unique in the scope of the z900 I/O configuration definition process (HCD or IOCP).



The SW @ (switch address) is the same as the Domain Address and is the first 8 bits of the 24 bit FC port address (ddaapp). The SW @ (Domain Address) must be unique within a fabric


Cascade Switching - E_Ports and ISLs

FICON - 2-switch Cascade Switching - Topology




For those processors that support FICON cascade switching, there can be up to 2 Fibre Channel switches in a channel to control unit path when 2 switch cascade switching is supported path. The fibre link between the two switches is referred to as a Inter-switch Link (ISL and the inter-switch link ports are referred to as E_Ports

FICON - Topology Point-to-Point, Switched Point-to-Point 2-Switch Cascade Switching




Up 8 paths are supported from a system (processor or processor image) to a CU (CU image or physical CU). The channel to CU paths can be a mix of FICON, Point-to-Point, Switched Point-to-Point and 2-switch cascade switching, paths.


FICON - 2-switch Cascade Switching




FICON channel 2-switch cascade switching will support up to two Fibre Channel switches in a channel to control unit path. There may be more than two switches in the fibre channel fabric, but there should only be one possible 'switch' switching route between the channel and the target control unit (destination port)



Fibre Channel - Switch Fabrics




The Fibre Channel standard refers to a a Fibre Channel fabric. It is a term used to describe a common connection of switches. All switches that are connected together via inter-switch links are considered to be in the same fabric



For S/390 and z900 processors, a FICON Fibre Channel Fabric is not a configuration definition item.


Fibre Channel Fabric - Multiple ISLs

FICON - Topology
2-Switch Cascade Switching




There can be more than one inter-switch link (ISL) connection between a pair of switches. ISLs are not defined in the zSeries processor I/O definition nor are they seen as unique paths by z/OS. When defining access from a processor FICON channel to a FICON control unit interface, only the FICON channel path (CHPID) and destination link address are defined

FICON - Topology
2-Switch Cascade Switching



Multi-switch Cascade Switching

FICON - Topology
Multi-Switch Cascade Switching



With FICON Multi-switch cascade switching there may be more than two switches in the FICON Channel to CU path and there may be more than one switching path route within the fabric between the FICON channel switch entry port and the Switch to FICON CU exit port (example, switch routing from the FICON channel entry port to the CU exit port - 21 - 22 - 23, or 21 - 24 - 23)


It is strongly recommended that the LSN and the Switch Address (SW @ - Switch Domain address) be the same hexadecimal value.

The switching routing within the fabric between two F_Ports is determined by the fabric (implementation by the switch vendor)


Cascade Switching - Switching Routes

- The following foils show fibre channel fabrics that have the following conditions
 - ▶ Single or Multiple - Channel to CU paths
 - For the multiple paths case, the additional paths are either through the same fabric or through another fabric
 - For FICON, if there are multiple channel to CU paths, it is preferred that they be spread across the FC fabrics
 - ▶ Single or multiple - E_Port to E_port ISLs (Inter-switch links)
 - Which ISL is used is determined by the fabric, not just by the FC D_ID
 - ▶ Single or multiple - F_Port to F_Port switch route
 - They may be more than one switch switching-route between two F_Ports in the same fabric
 - Which switch route is used is determined by the fabric, not just by the FC D_ID
 - ▶ Single or multiple - FC Fabrics
 - For FICON when there are multiple ISL between sites it is recommended that they be spread across switches that are in different fabrics


FICON Cascade Switching Topology




Single Channel to CU path
Single ISL
Single F_Port to F_Port switch route
Single FC Fabric



Single Channel to CU path
Multiple ISLs (multiple ISL routes)
Single F_Port to F_Port switch route
Single FC Fabric





Single Channel to CU path
Single ISLs
Multiple F_Port to F_Port switch routes
Single FC Fabric




Single Channel to CU path
Multiple ISLs (multiple ISL routes)
Multiple F_Port to F_Port switch routes
Single FC Fabric

FICON Cascade Switching Topology



Multiple Sites - Non-Cascade Switching



Multiple Sites - 2-Switch Cascade Switching

