

Sample Questions for Test C2180-403, IBM WebSphere DataPower SOA Appliances Firmware V6.0, System Administration

Note: **Bolded** response option is the correct answer.

item C2180-403.2.1.3

A system administrator is setting up the DataPower appliance for first time use and has used the installation wizard to complete the initial base configuration. Next, the administrator needs to accept a license agreement in order to complete the appliance setup.

What must the administrator do to accept the license agreement?

- A. Login to the WebGUI and click "I agree".**
- B. In the Serial Console type **accept-license**.
- C. Login via SSH and type **license**, and then answer **"yes"** to the prompt.
- D. Send a XML Management Interface SOMA request using the license **do-action** directive.

item C2180-403.3.1.3

A system administrator noticed that access to the administrative services of a DataPower appliance is allowed through all of its Ethernet interfaces.

How can the administrator limit access to these services using only the management Ethernet interface with IP address 10.0.0.20 using the Command Line Interface (CLI)?

- A. `xi52(config)# webmgmt 10.0.0.20 9090`
`xi52(config)# xmlmgmt 10.0.0.20 5550`
`xi52(config)# sshmgmt 10.0.0.20 22`
- B. `xi52(config)# web-mgmt 10.0.0.20 9090`
`xi52(config)# xml-mgmt 10.0.0.20 5550`
`xi52(config)# ssh 10.0.0.20 22`**
- C. `xi52(config)# webmgmt 10.0.0.20/32 9090`
`xi52(config)# xmlmgmt 10.0.0.20/32 5550`
`xi52(config)# sshmgmt 10.0.0.20/32 22`
- D. `xi52(config)# web-mgmt 10.0.0.20/32 9090`
`xi52(config)# xml-mgmt 10.0.0.20/32 5550`
`xi52(config)# ssh 10.0.0.20/32 22}`

item C2180-403.4.3.1

A system administrator needs to configure OAuth 2.0 on DataPower to implement a two-legged authentication process with a Multi-Protocol Gateway service as a resource.

Which OAuth Client Profile options does the administrator require for this purpose? (choose 2)

- A. Set OAuth Role to Client
- B. Set OAuth Role to Enforcement Point for Resource Server**
- C. Set Supported Authorization Grant Type to Client Credentials
- D. Set Supported Authorization Grant Type to Authorization Code
- E. Set Supported Authorization Grant Type to Resource Owner Password Credential**

item C2180-403.5.1.1

A system administrator needs to configure aliases for all IP addresses of each DataPower appliance to minimize application domain variability between appliances.

What should the system administrator configure to accomplish this task?

- A. An alias name in each Ethernet Interface object.
- B. A Host Alias object for all appliance IP addresses.**
- C. Alias names for all appliance IP addresses in the appliance's network settings.
- D. Alias names for all appliance IP addresses in the appliance's /etc/hosts file.

item C2180-403.6.1.3

A company has noticed an intermittent problem with client connections occurring in the DataPower environment. The problem happens at unpredictable times, but continues for approximately 10 minutes every time. The system administrator has decided to use an event trigger to start a packet capture at the first occurrence of the problem. The packet capture must focus on destination port 80 on all interfaces, carry on for 10 minutes, not exceed 10,000 KB, and capture the entire packet.

Which Command Line Interface (CLI) command should the administrator use to configure the event trigger?

- A. packet-capture all temporary://capture.pcap 10 10000 9000 "port 80"
- B. packet-capture-advanced temporary://capture.pcap 600 10000 10 "port 80"
- C. packet-capture-advanced all temporary://capture.pcap 600 10000 -1 "dst port 80"**
- D. interface eth*; packet-capture temporary://capture.pcap 10000 600 -1 "dst port 80"