

## Creating Default Users

Back to Administrator Procedures

If you are using the non-DCE version of Infoprint Manager and are running a "Basic" configuration (formerly known as "commercial"), you should control access to Infoprint administrator and operator functions by creating the default users **admin** and **oper** (security groups).

If you are using the DCE version of Infoprint, you merely need to select the DCE option on the Infoprint Installer to control access to Infoprint. If you are running a non-DCE "Advanced" configuration (formerly known as "production"), refer to the Managing Non DCE Security for Infoprint Manager for AIX procedure that is available from the Infoprint Manager for AIX Operator's Information (<http://www.printers.ibm.com/R5PSC.NSF/Web/aixoper>) on the web.

Running Infoprint as the **root** user is not recommended under any circumstances. The **admin** user will be allowed to perform both administrator and operator tasks on basic, non-DCE Infoprint systems. The **oper** user will be able to perform operator tasks, but will be prohibited from performing administrative tasks. To set up these users, do the following:

1. Access the **Infoprint Utilities** main menu by:
  - If you do not have an **Infoprint Manager** icon on your front panel, open the **Infoprint** folder in the Application Manager and double click on the **Infoprint SMIT** icon. Then click **Infoprint Utilities**.
  - If you do have an **Infoprint Manager** icon on your front panel, open Infoprint Manager's popup menu and click on the **Infoprint SMIT** icon. Then click **Infoprint Utilities**.
2. Click **Create Default Users**.
3. Click **OK** when asked, "Are you sure?"
4. Note the passwords you set for the **admin** and **oper** users because they will be needed in the future.