

IBM System z Technical Conference Dresden – Germany – May 5-9



# **VSAM Redirector Technology** with Live Demo

Wilhelm Mild
z/VSE Solution Architect
zvse@de.ibm.com

15-March-2007

© 2008 IBM Corporation



### **Trademarks**

The following are trademarks of the International Business Machines Corporation in the United States and / or other counties.

CICS*	IBM*	Virtual Image Facility
DB2*	IBM logo*	VM/ESA*
DB2 Connect	IMS	VSE/ESA
DB2 Universal Database	Intelligent Miner	z/VSE
e-business logo*	Multiprise*	VisualAge*
Enterprise Storage Server	MQSeries*	VTAM*
HiperSockets	OS/390*	WebSphere*
	S/390*	xSeries
	SNAP/SHOT* z/Architecture	
marks of IDM Corporation		0.78.4

<sup>\*</sup> Registered trademarks of IBM Corporation

z/VM z/VSE zSeries

System z

The following are trademarks or registered trademarks of other companies.

LINUX is a registered trademark of Linus Torvalds

Tivoli is a trademark of Tivoli Systems Inc.

Java and all Java-related trademarks and logos are trademarks of Sun Microsystems, Inc., in the United States and other countries

UNIX is a registered trademark of The Open Group in the United States and other countries.

Microsoft, Windows and Windows NT are registered trademarks of Microsoft Corporation.


SET and Secure Electronic Transaction are trademarks owned by SET Secure Electronic Transaction LLC.

Intel is a registered trademark of Intel Corporation.



# A typical VSE environment today


- Various different servers (System z, System p, System i, System x, and others)
- VSAM data on VSE (some DB2 environments, some other databases)





## VSE/VSAM applications and data transfer today


- (1) disadvantages of FTP
  - a) NO real-time access/synchronization
  - b) data immediate out of sync, till next FTP
  - c) always the whole file is transferred
  - d) intermediate step database loader needed
     e) FTP is a stateless protocol no guaranteed delivery
  - f) increased network traffic



z/VSE Server




## VSAM Programs with DB2 UDB on Linux on System z



(\*) VSAM Redirector – Common data store solution – with DB2 on Linux on zSeries Solutions without changes to VSAM programs



### VSE/VSAM Redirector - functional view




- **►** Redirector Components:
- ► Generic Exit is based on VSAM Data Access Exit (VDA)
- ► Config phase contains the redirection properties
- ► Redirector client (SVA phase)
- ► Redirector server manages the connections (Java component)
- ► Handler takes care of data processing (Javav component)



# VSAM Redirector – the Client

- The Client, Shipped in VSE phase IESREDIR
- Forwards all requests via TCP/IP socket to VSAM Redirector Server on a remote site
- Important Parameter
  - OWNER=REDIRECTOR
    - VSAM requests are executed by remote site only
    - VSAM does not execute the request
      - controlled by return code from IKQVEX01
    - Allows migrating VSAM data to a database without changing the VSAM programs
  - OWNER=VSAM
    - Both, VSAM and remote site executes the request
    - Allows synchronization of VSAM and database without changing the VSAM programs






# VSAM Redirector – Configuration Table

- Gets assembled as VSE PHASE
  - Does not contain any executable code, just a table

```
IESRDENT CATALOG='MY.VSAM.CATALOG',
      CLUSTER='MY.VSAM.CLUSTER1',
      EXIT='IESREDIR',
      OWNER=REDIRECTOR,
      IP='1.2.3.4'
      HANDLER='com.ibm.vse.db2handler.DB2Handler,
      OPTIONS='dburl=jdbc:db2:database;dbuser=user;
               maptable=maptable; map=mapname;
               dbpassword=password;dbtable=table,
IESRDENT CATALOG='VSESP.USER.CATALOG',
         CLUSTER='MY.TEST.CLUSTER2',
         EXIT='IESVSCAP',
         MODE=JOURNALING,
         DELTADD='DELTAFI',
         DELTATYPE=KSDS,
         SHARE=ENDREQ,
         ORIGIN='TEST2'
```





### The flavors of VSAM redirector

- (1) Remote processing Real time VSAM access to remote
  - a) Remote only processing to DB2 (no VSAM access anymore)
  - **b)** Synchronization (two phase commit of VSAM and DB2)

- (2) Capture VSE local data processing in addition to VSAM
  - a) Capture Exit for VSAM processing
  - **b) MQ Exit** and MQ Series solutions




# VSE/VSAM applications (without any change), access remote relational databases

(1) Real time access VSAM to DB2

b)


a) synchronization (two phase commit of VSAM and DB2)






# VSE/VSAM applications (without any change), access remote relational databases

- (1) Real time access VSAM to DB2
  - a) synchronization (two phase commit of VSAM and DB2)
  - b) Real time push of VSAM data to DB2





# VSE/VSAM applications, access remote relational databases






# (1) Remote processing

### a) Remote only processing – NO VSAM access anymore

Requests for redirected
 VSAM files will be handled by
 VSAM Redirector client and send to the remote system.

•OWNER = REDIRECTOR

- Dataflow for a read/write request:
  - Generic exit is involved
  - •VSAM Redirector Client is called
  - •Redirector client sends request to Redirector Server
  - Handler processes data
  - Return Code if any is translated to VSAM error
- All reads and writes are done from/to remote




No changes required in applications (CICS, batch).



# (1) Remote processing

## a) Synchronization of VSAM with a database



No changes required in applications (CICS, batch).



## (1) Remote processing

### a) Synchronization of VSAM with a database


- Requests for redirected VSAM files will be handled by VSAM Redirector client and send to the remote system.
- •OWNER = VSAM
- •Dataflow for a read/write request:
  - READs will be performed from VSAM only
  - Generic exit calls VSAM Redirector Client
  - Redirector client sends request to Redirector Server
  - •(a) Handler processes the request in the database
  - Return Code is send back to Redirecor client
    - In case of an error it will be translated to a VSAM error
  - •(b) If return code is favorable the request is processed in VSAM
  - •(c-1) If the VSAM request is processed correct the database will get a COMMIT request
  - through the Redirector Client-Server-Handler
  - •(c-2) If the VSAM request ends in error the database will get a ROLLBACK request
- •This is the two phase commit mechanism to keep VSA;m and DB2 in sync



# **Data synchronization – Normalization**

### VSE/VSAM Redirector can store VSAM data normalized

- No changes to the existing VSE applications
- ►The new
  Redirector Handler
  in z/VSE 4.1 can
  store 'VSAM' data
  in multiple DB
  Tables .
- ► Redir Loader utility provided for initial data transfer



- ► Applications on VSE should be able to access DB2 data on Linux
- ► Population of DB2 UDB on Linux with VSAM using VSAM Redirector. (VSAM Redirector is part of VSE)



### **VSAM** Redirector – Normalization - Handler

- Two different Handler with the New VSAM Redirector
  - Old: DB2Handler
    - Is still packaged with z/VSE
    - supports data access consolidation (OWNER=REDIRECTOR)
      as well as data synchronization (OWNER=VSAM)
    - supports DB2, Oracle, MS-SQL, ...
    - was enhanced with new data formats (packed, zoned, date, ...)
  - New: DBHandler
    - enables data Normalization
    - supports data synchronization only (OWNER=VSAM)
      - supports Record-Types
      - supports lists with fixed and variable length
    - supports new data formats (Packed, Zoned, Datum, ...)
      - supports DB2, Oracle, MS-SQL, ...



# VSAM Redirector – Normalization - Handler New Redirector handler in z/VSE 4.1

- Handler to Normalize VSAM data
  - store one VSAM record in multiple tables
    - based on VSAM indicator fields
    - administrator decision
    - for synchronization only (owner = VSAM) READS are done from VSAM
  - relation between tables to be unique
  - definitions via GUI (mapping configuration)
  - SQL loader provided for database load
    - RedirLoader fast initial LOAD of a database from VSAM
    - MQLoader MQ trigger application
    - DeltaLoader Processing of the Delta file insert into the database



# **VSAM** Redirector - Normalization – data types

- New extendable Concept: Converters
  - One Java-class per data type
  - Open interface
  - New data types can be extended easily
- Data types:
  - STRING
  - BINARY
  - BIT
  - Numbers (INTEGER, PACKED, ZONED, FLOAT, FIXEDTEXT, FLOATTEXT), supports Implied decimal positions
  - DATETIME, TOD
  - HEXCHAR
- Various Options
  - Settings (i.e. date format, number of decimals, ...)
  - Error handling: ONERROR= TERMINATE, TO-NULL, TO\_ZERO
  - Text handling: TRIM, PAD, BLANK-TO-NULL, CODEPAGE



# **VSAM** Redirector - Normalization – Record-Types

```
COBOL Copybook:

01 RECORD-3

03 RECORD-TYPE PIC X(1)

03 RECORD-FORMAT-C

05 CUSTOMER-NO PIC X(7)

05 CUSTOMER-NAME PIC X(25)

05 CUSTOMER-ADDRESS PIC X(45)

03 RECORD-FORMAT-P REDEFINES RECORD-FORMAT-C

05 PRODUCT-NO PIC X(7)

05 PRODUCT-CATEGORY PIC X(15)

05 PRODUCT-NAME PIC X(15).
```

Depending on the value of Record-Type field, the data will be store in different database tables

- Type =  $C \rightarrow Customers-Table$
- Type =  $P \rightarrow Products-Table$

The association takes place at runtime for each individual record.

### **Customers**

Table for Record-Type C

CustNo Name Address

### **Products**

Table for Record-Type P

ProducNo Category Name



### **VSAM** Redirector - Normalization – Lists

# COBOL Copybook: 01 RECORD-2. 03 KEYFIELD PIC X(8). 03 COUNTER PIC 9(5) COMP-3. 03 VARIABLE-LIST OCCURS 1 TO 5 DEPENDING ON COUNTER. 05 LISTFIELD-1 PIC 9(9). 05 LISTFIELD-2 PIC X(5). 03 DATAVALUE PIC X(10).

Depending on the value of the field Counter, there will be inserted 1 to 5 rows into the List-Table.

The relation to the Master-Table is defined through the foreign key Keyfield in the List-Table

Normalization takes place at runtime for each individual record.

**Master-Table** 

Master-Table

Keyfield Counter DataValue


**List-Table** 

Table for Lists-Values

Keyfield ListField1 ListField2



# VSAM Programs with DB2 UDB on Linux on System z




(\*) VSAM Redirector – Common data store solution – with DB2 on Linux on zSeries Solutions without changes to VSAM programs



## VSAM Data collection / transformation / journaling on VSE

### **Capture Exit**



#### **CAPTURE – wit Decision Exit as filter**


- **►Vendor Exit** 
  - **►** user (vendor) written phase for data collection/transformation
  - ► has to comply with the documented Exit Interface
- **► Capture Exit** 
  - ► an exit delivered by IBM for capturing changed VSAM data
  - ► an exit delivered by IBM for generating MQ messages

Note: No chaining of Vendor Exit with VSAM Redirector client supported



# z/VSE 4.1 VSAM Redirector – Capture Exit

- Shipped in phase IESVSCAP
- Captures all changes to a VSAM file
  - UPDATE
  - INSERT
  - DELETE




- Creates delta records with header + original data
  - Stored in second VSAM file (delta file)
  - Or creates MQ Series message
- Delta record header contains information about when and by whom the record was changed, and which request
- Allows customers to download the delta file and apply it to a database




# Redirector Capture.

## **Architectural View**






# **VSAM Redirector Capture**






# **Journaling**



Record 1	inserted
Record 2	inserted
Record 3	inserted
Record 2	updated
Record 1	deleted
Record 3	updated
Record 4	inserted
Record 1	inserted
Record 2	updated
Record 4	updated
Record 4	deleted

### or

## cumulative




key


Record 1	inserted
Record 2	updated
Record 3	updated
Record 4	deleted

The last version only of a changed VSAM record is stored into the delta file



### **Delta Record**







### **Delta Header**

Offset	Parameters	Length	Description
0	TODCLOCK	8	Time of change
8	JobName	8	Job name
16	PHASEName	8	Phase name
24	Origin	8	String from Config or file Label
32	PartID	2	Partition ID (i.e. F2)
34	<b>OpCode</b>	1	I=Insert, D=Delete,U=Update
35	Flags	1	X'01'=RRN/RBA follows
36	RRN/RBA	4	RRN/RBA (RRDS/VRDS/ESDS)

### Contains information about:

- → when change took place (TODCLOCK)
- → who did the change (Job/Phase/Partition)
- → request type of change (Insert/Delete/Update)
- → which record was affected (key/RRN/RBA)



# **VSAM Capture Exit - Solution options**


- Delta records can be downloaded for processing
  - Using FTP
  - Using VSE Connector Client
  - After processing, delta records are deleted
- Delta records can be sent to a remote system via MQ Series
  - Asynchronous transportation or messages
  - Trigger program can process incoming messages
- Multiple VSAM files can be 'captured' into the same Delta File or MQ Series queue
  - Distinction possible via 'origin' value in header



## **Solution for FTP Replacement:**

### **Bidirectional updates with VSE connectors**

- ► With VSAM
  Capture the
  performance of
  the VSE
  production
  system protected
- The changes are processed asynchronously and not influenting the production system




- Collect the changed records in a separate VSAM file
  - ► Possibility of cleansing
- ► Process them with the VSE Connectors



provided by IBM



# **Solution with MQ Messaging**




- (\*) **VSAM Redirector + Redirector MQ Exit** allows MQ Solutions without changes to VSAM programs
- (\*\*) WebSphere MQ Client for VSE is free of charge



## **MQ Exit**

### **Integration of VSE Application with MQ Series**

- ► enablement for MQ Series w/o changing existing applications.
- ► Bidirectional processing
- ►Guaranteed processing using asynchroneous data tranfer method MQ



► tools provided by IBM

### IBM System z Technical Conference Dresden – Germany – May 5-9





**Solutions** 

http://www.ibm.com/servers/eserver/zseries/zvse/



### Additional Information

z/VSE Home Page http://www.ibm.com/vse

•z/VSE solutions http://www-1.ibm.com/servers/eserver/zseries/zvse/solutions

•e-business Connectors User's Guide SC33-6719 http://www-1.ibm.com/servers/eserver/zseries/zvse/documentation/#conn



• e-business Solutions for VSE/ESA SG24-5662

•e-business Connectivity for VSE/ESA SG24-5950

CICS Transaction Server for VSE/ESACICS Web SupportSG24-5997-00

• WebSphere for Linux on zSeries Connectivity Handbook SG24-7042

We appreciate your comments at : zvse@de.ibm.com