



# WAVV 2004 Conference



## CICS Web Support: Access to CICS Applications from the Web

**Robin Gemmell**  
**(gemma@uk.ibm.com)**

**Chattanooga, 30 April - 4 May 2004**

## Trademarks

- The following terms are trademarks of International Business Machines Corporation in the United States and/or other countries:

AIX	DB2	OS/390	VisualAge
CICS	MVS/ESA	VSE/ESA	
CICS/VSE	OS/2	VTAM	

- Java and Solaris are trademarks of Sun Microsystems, Inc
- Windows, Windows 95, Windows 98, Windows 2000, and Windows NT are trademarks of Microsoft Corporation, Inc
- Other company, product, and service names may be trademarks or service marks of others

## Agenda

---

- What is CICS Web Support?
- CICS Web Support architecture
- Enabling CICS Web Support
- Writing CICS Web Applications
- Running 3270-based transactions with CICS Web Support
- Further Information and Summary

## Agenda


---

- What is CICS Web Support?
- CICS Web Support architecture
- Enabling CICS Web Support
- Writing CICS Web Applications
- Running 3270-based transactions with CICS Web Support
- Further Information and Summary

## What is CICS Web Support?


- Set of services that enables direct connection from a Web browser to CICS Transaction Server for VSE/ESA
- Enables access to CICS Application Programs and Transactions
- Formerly known as the CICS Web Interface
- New API's provided for "Web aware" applications
- Delivered in CICS Transaction Server for VSE/ESA V1.1.1

## What is CICS Web Support?



- Web browser access to CICS Applications and Transactions
- Direct connection - no intermediate gateways or servers
- Standard HTTP protocol used over TCP/IP
- *Secure Sockets Layer support available with VSE/ESA V2.6*

## Relationship to the CICS Transaction Gateway



## What is CICS Web Support?

- CICS Application program to be invoked specified in URL
- Default URL format:  
*f*<http://hostid:port/converter/alias/program?optional-token>

**hostid** is the IP address or DNS name of the CICS region

**port** is the configured listening port number

**converter** is the name of the program for Decode & Encode processing

- "CICS" if no converter

**alias** is the transaction id of the alias transaction

- "CWBA" is the supplied alias

**program** is the name of the CICS application program to be invoked

**optional-token** is optional data to be passed with the request

- Example URL:


*f*<http://cicstest.ibm.com:1080/cics/cwba/webpgm1>

## Agenda

---

- What is CICS Web Support?
- **CICS Web Support architecture**
- Enabling CICS Web Support
- Writing CICS Web Applications
- Running 3270-based transactions with CICS Web Support
- Further Information and Summary

# CICS Web Support Architecture



## CICS Web Support Architecture

### ■ The Analyzer:

- ƒ Parses the incoming request
- ƒ Determines resources and context for Alias transaction
- ƒ Specifies codepage conversion for body of http request
- ƒ User Replaceable Module


### ■ The supplied default Analyzer:

- ƒ Provides ISO-8859-01 codepage conversation
- ƒ Supports the default CWS URL format
  - <http://hostid:port/converter/alias/program?optional-token>

### ■ The supplied Analyzer programs:

- ƒ DFHWBADX -----> Assembler
- ƒ DFHWBAHX -----> C
- ƒ DFHWBALX -----> PL/I
- ƒ DFHWBAOX -----> COBOL

# CICS Web Support Architecture




# CICS Web Support Architecture

## ■ The Converter

- Provides Decode and Encode functions
  - Maps inbound HTTP request to application COMMAREA
- Decode invoked *before* request passed to CICS application
- Encode invoked *after* CICS application has processed request
  - Maps application COMMAREA to outbound HTTP response
- Converter is optional


# CICS Web Support Architecture



# CICS Web Support Architecture

Accessing existing COMMAREA based applications


- Converter used to shield applications from HTTP and HTML



## CICS Web Support Architecture

Accessing new CICS "Web aware" Applications

- The picture becomes simpler using the new API's....




- NB: "Web aware" applications need to understand HTTP

# CICS Web Support Architecture

## Accessing 3270-based transactions

- Uses the 3270 Bridge support
- Some limitations



Example URL > <http://cics1.ibm.com:1080/cics/cwba/dfhwbtta/ceci>

## Agenda

---

- What is CICS Web Support?
- CICS Web Support architecture
- Enabling CICS Web Support**
- Writing CICS Web Applications
- Running 3270-based transactions with CICS Web Support
- Further Information and Summary

## DFHSIT requirements

- Specify that TCP/IP services are required
  - ƒ TCPI P=YES
- Specify Web 3270 bridge parameters
  - ƒ WEBDELAY=(n,m)
    - n = time transaction remains in terminal wait before being terminated
    - m = time during which state data is kept for a transaction
- Increase EDSA storage
  - ƒ by at least 2M for TCP/IP services
  - ƒ 1M per active Web connection
- Additional SIT parameters if using SSL
  - ƒ ENCRYPTION=WEAK|NORMAL|STRONG
  - ƒ KEYFILE=*name*
  - ƒ SSLDELAY= *number*

## Resource Definitions

- Define at least one TCPI PSERVICE
  - ƒ Specifies IP address, port number, name of the analyzer
  - ƒ Also specifies level of SSL support and SSL certificate
  - ƒ Sample specified in DFH\$SOT
- Install supplied RDO group DFHWEB
  - ƒ Contains definitions for CWS transactions and programs
- Define any required DOCTEMPLATES
  - ƒ Required if using new DOCUMENT API

## Other Requirements

- Define a conversion table using DFHCNV macros
  - ƒ For HTTP conversion between ASCII and EBCDIC
  - ƒ Example DFHCNV table:

```
DFHCNV TYPE=INITIAL
*
DFHCNV TYPE=ENTRY,RTYPE=PC,RNAME=DFHWBHH,USRExit=NO,
        SRVERCP=037,CLINTCP=8859-1
DFHCNV TYPE=SELECT
DFHCNV TYPE=FIELD,OFFSET=0,DATATYP=CHARACTER,DATALEN=32767,
        LAST=YES
*
DFHCNV TYPE=ENTRY,RTYPE=PC,RNAME=DFHWBUD,USRExit=NO,
        SRVERCP=037,CLINTCP=8859-1
DFHCNV TYPE=SELECT
DFHCNV TYPE=FIELD,OFFSET=0,DATATYP=CHARACTER,DATALEN=32767,
        LAST=YES
*
DFHCNV TYPE=FINAL
END
```

- Configure TCP/IP for VSE/ESA

## Other Considerations

### ■ Security

- f* Transactions that compose CICS Web Support
- f* Running Web transactions with end-user specified Userid
- f* Use of Secure Sockets Layer (SSL)
- f* TCP/IP VSE/ESA security facilities

### ■ Operational Support

- f* DFHWBEP - Web Error Program
- f* SPI and CEMT commands

COMMAND	SPI	CEMT
CREATE DOCTEMPLATE		
CREATE TCPIPSERVICE		
DISCARD DOCTEMPLATE		
DISCARD TCPIPSERVICE		
INQUIRE DOCTEMPLATE		
INQUIRE TCPIP		
INQUIRE TCPIPSERVICE		
INQUIRE WEB		
SET TCPIP		
SET TCPIPSERVICE		
SET WEB		

## Agenda

---

- What is CICS Web Support?
- CICS Web Support architecture
- Enabling CICS Web Support
- **Writing CICS Web Applications**
- Running 3270-based transactions with CICS Web Support
- Further Information and Summary

## The new Web API's

### ■ WEB API

*f* HTTP protocol

EXEC CICS WEB EXTRACT

EXEC CICS WEB STARTBROWSE

EXEC CICS WEB READNEXT

EXEC CICS WEB ENDBROWSE

EXEC CICS WEB READ

EXEC CICS WEB RECEIVE

EXEC CICS WEB WRITE

EXEC CICS WEB SEND

EXEC CICS WEB RETRIEVE

### ■ TCP/IP API

*f* Sockets protocol

EXEC CICS EXTRACT TCPIP

EXEC CICS EXTRACT CERTIFICATE

### ■ DOCUMENT API

*f* HTML, XML, etc

EXEC CICS DOCUMENT CREATE

EXEC CICS DOCUMENT INSERT

EXEC CICS DOCUMENT SET

EXEC CICS DOCUMENT RETRIEVE

## The new Web API's....

### ■ EXEC CICS WEB

- f* Retrieve components of the inbound HTTP request
- f* Construct HTTP headers to be returned in HTTP response
- f* Select a document for delivery as the body of the response

### ■ EXEC CICS EXTRACT TCPIP

- f* Retrieve TCP/IP information



### ■ EXEC CICS EXTRACT CERTIFICATE

- f* Retrieve information from the client certificate


### ■ EXEC CICS DOCUMENT

- f* Create and manipulate "Documents"
  - Can be made up of both text and binary elements
  - Can contain templates, symbols and bookmarks
  - Bookmarks can be used to insert data at specific points
  - Documents can be imbedded
  - Codepage information stored with document

## New WEB API's....Processing HTTP Requests



## New WEB API's....Processing HTTP Responses



## Document Templates


- Templates specified by DOCTEMPLATE resource, can be...
  - ƒ VSE sub-library member, CICS file, TS queue, TD queue
  - ƒ Load module, Exit program
- HTML example:

```
<html>
<head>
<title>Address Book</title>
</head>
<body>
<center>
<h1>&person;</h1><br>
&house_number; &street;<br>
&town;<br>
&zip;<br>
&person; can be reached on &home_number; at home or &work_number; during office hours <br>
</center>
</body>
</html>
```

- Example symbol list for the above would be a single string:

```
"person=Barney Rubble&house_number=2&street=Stoney
Lane&town=Bedrock&zip=&home_number=911&work_number=123-456 "
```

## Document Templates...after substitution



## Web API's – code example

\* Create document from existing HTML template

```
EXEC CICS DOCUMENT CREATE DOCTOKEN(DOCTKN)
    TEMPLATE('TEMPL1')
```

\* Get Server TCP/IP address

```
EXEC CICS EXTRACT TCPIP
    SERVERADDR(SRVRADDR) SADDRLENGTH(ADDRL)
```

\* Get Client TCP/IP address

```
EXEC CICS EXTRACT TCPIP
    CLIENTADDR(CLNTADDR) CADDRLENGTH(ADDRL)
```

\* Insert both addresses into document

```
EXEC CICS DOCUMENT INSERT DOCTOKEN(DOCTKN)
    TEXT(DOCTXT) LENGTH(DOCTXTL)
```

\* Add footer to document from existing HTML template

```
EXEC CICS DOCUMENT INSERT DOCTOKEN(DOCTKN)
    TEMPLATE('TEMPL2')
```

\* Send completed document

```
EXEC CICS WEB SEND DOCTOKEN(DOCTKN) CLNTCODEPAGE('iso-8859-1')
```

\* Terminate program

```
EXEC CICS RETURN
```

ADDRL DC F'15'

DOCTXTL DC F'70'

DOCTKN DC CL16

DOCTXT DS 0CL

SRVRTXT DC C'<p> Server Address: '

SRVRADDR DS CL15

SRVRTXT DC C'<p> Client Address: '

CLNTADDR DS CL15

## Web API's – Templates example

### Document Template - TEMPL1

```
<html>
<head>
<title>Simple CWS Demo</title>
</head>
<body>
<h1>Following info produced via the EXEC CICS EXTRACT, DOCUMENT and WEB API's</h1>
```

## Web API's – code example

```
* Create document from existing HTML template
    EXEC CICS DOCUMENT CREATE DOCTOKEN(DOCTKN)
        TEMPLATE('TEMPL1')

* Get Server TCP/IP address
    EXEC CICS EXTRACT TCPIP
        SERVERADDR(SRVRADDR) SADDRLENGTH(ADDRL)

* Get Client TCP/IP address
    EXEC CICS EXTRACT TCPIP
        CLIENTADDR(CLNTADDR) CADDRLENGTH(ADDRL)

* Insert both addresses into document
    EXEC CICS DOCUMENT INSERT DOCTOKEN(DOCTKN)
        TEXT(DOCTXT) LENGTH(DOCTXTL)

* Add footer to document from existing HTML template
    EXEC CICS DOCUMENT INSERT DOCTOKEN(DOCTKN)
        TEMPLATE('TEMPL2')

* Send completed document
    EXEC CICS WEB SEND DOCTOKEN(DOCTKN) CLNTCODEPAGE('iso-8859-1')

* Terminate program
    EXEC CICS RETURN
```

ADDR	DC F'15'
DOCTXTL	DC F'70'
DOCTKN	DC CL16
DOCTXT	DS 0CL
SRVRTXT	DC C'<p> Server Address: '
SRVRADDR	DS CL15
SRVRTXT	DC C'<p> Client Address: '
CLNTADDR	DS CL15

## Web API's – code example

```
* Create document from existing HTML template
      EXEC CICS DOCUMENT CREATE DOCTOKEN(DOCTKN)
                  TEMPLATE('TEMPL1')
* Get Server TCP/IP address
      EXEC CICS EXTRACT TCPIP
                  SERVERADDR(SRVRADDR) SADDRLENGTH(ADDRL)
* Get Client TCP/IP address
      EXEC CICS EXTRACT TCPIP
                  CLIENTADDR(CLNTADDR) CADDRLENGTH(ADDRL)
* Insert both addresses into document
      EXEC CICS DOCUMENT INSERT DOCTOKEN(DOCTKN)
                  TEXT(DOCTXT) LENGTH(DOCTXTL)
* Add footer to document from existing HTML template
      EXEC CICS DOCUMENT INSERT DOCTOKEN(DOCTKN)
                  TEMPLATE('TEMPL2')
* Send completed document
      EXEC CICS WEB SEND DOCTOKEN(DOCTKN) CLNTCODEPAGE('iso-8859-1')
* Terminate program
      EXEC CICS RETURN
```

ADDR	DC F'15'
DOCTXTL	DC F'70'
DOCTKN	DC CL16
DOCTXT	DS 0CL
SRVRTXT	DC C'<p> Server Address: '
SRVRADDR	DS CL15
SRVRTXT	DC C'<p> Client Address: '
CLNTADDR	DS CL15

## Web API's – Templates example

### Document Template - TEMPL2


```
<p><hr>
<p>Foot of simple CICS Web Support API demo page
</body>
</html>
```

## Web API's – code example

```
* Create document from existing HTML template
      EXEC CICS DOCUMENT CREATE DOCTOKEN(DOCTKN)
                  TEMPLATE('TEMPL1')
* Get Server TCP/IP address
      EXEC CICS EXTRACT TCPIP
                  SERVERADDR(SRVRADDR) SADDRLENGTH(ADDRL)
* Get Client TCP/IP address
      EXEC CICS EXTRACT TCPIP
                  CLIENTADDR(CLNTADDR) CADDRLENGTH(ADDRL)
* Insert both addresses into document
      EXEC CICS DOCUMENT INSERT DOCTOKEN(DOCTKN)
                  TEXT(DOCTXT) LENGTH(DOCTXTL)
* Add footer to document from existing HTML template
      EXEC CICS DOCUMENT INSERT DOCTOKEN(DOCTKN)
                  TEMPLATE('TEMPL2')
* Send completed document
      EXEC CICS WEB SEND DOCTOKEN(DOCTKN) CLNTCODEPAGE('iso-8859-1')
* Terminate program
      EXEC CICS RETURN
```

ADDRL	DC F'15'
DOCTXTL	DC F'70'
DOCTKN	DC CL16
DOCTXT	DS 0CL
SRVRTXT	DC C'<p> Server Address: '
SRVRADDR	DS CL15
SRVRTXT	DC C'<p> Client Address: '
CLNTADDR	DS CL15

## Web API's - Example output




## Agenda

---


- What is CICS Web Support
- CICS Web Support architecture
- Enabling CICS Web Support
- Writing CICS Web applications
- Running 3270-based transactions with CICS Web Support**
- Further Information and Summary

## Running 3270 based transactions - Architecture



Example URL > <http://cics1.ibm.com:1080/cics/cwba/dfhwbtta/ceci>

# Creating HTML for BMS applications



## Creating HTML for BMS applications....

A template generated by the standard method contains...

- Constants and input fields from the map
- Buttons to represent:
  - f* ENTER key
  - f* PA1, PA2, PA3 keys
  - f* Program function keys PF1 to PF24
  - f* HTML Reset
- Hidden variables
  - f* For handling conversations/pseudoconversations
  - f* For holding name of map field where cursor is set
- JavaScript
  - f* Function to set the cursor position to a specific field
  - f* Exception handler for tracking cursor movement

## Customising HTML for BMS applications

- Customise via CICS supplied macros
- Edit the generated HTML
- Run time customisation via use of Converter
  - f* Input (Decode)
    - e.g. change AID, change cursor position
  - f* Output (Encode)
    - e.g. add timestamp

## Customising HTML for BMS applications....

Customising via the DFHMDX macro.....

- Defines customization macros used for template creation
- Is invoked from DFHMSX
- Can be used to
  - f* Suppress HTML Reset
  - f* Change or suppress PF keys and associated text
  - f* Provide an HTML title or masthead graphic
  - f* Change the background
  - f* Modify BMS colours
  - f* Suppress parts of the BMS map
  - f* Add Web browser control functions, e.g. JavaScript

## Customising HTML for BMS applications....

### Customising via the DFHWBOUT macro

- Add invocations of DFHWBOUT to BMS source
- Can be used to
  - ƒ Add HTML header information
  - ƒ Add text to HTML page that is not part of BMS map
  - ƒ Add Web browser control functions, e.g. JavaScript

## Examples – DFHMDX & DFHWBOUT

### \* Set default PF keys for all maps and mapsets

DFHMSX

DFHMDX MAPSET=\*,MAP=\*,  
PF1='Help',PF3='Exit',PF4='Save',PF9='Messages'

### \* Change title and PF4 for all maps in mapset DFHWB0

DFHMDX MAPSET=DFHWB0,MAP=\*,  
TITLE='CICS Web Support - Demo Application',  
PF4='Messages'

### \* Add text that appears only on the HTML page

DFHWBOUT '<p>This text illustrates the use of the DFHWBOUT macro,'  
DFHWBOUT ' which can be used to output text that only appears'  
DFHWBOUT ' in HTML templates and not in the corresponding BMS map.'

### \* Add HTML header information to the HTML page

DFHWBOUT '<meta name="author" content="E Phillips Oppenheim">'  
DFHWBOUT '<meta name="owner" content="epoppenheim@xxx.com">'  
DFHWBOUT '<meta name="review" content="20000314">'

## HTML for non-BMS applications

- Default presentation...
- Page produced in fixed width font
- Supplied Headers and Footers
  - f* Mandatory HTML page elements
  - f* Input buttons (ENTER, PF Keys, etc)
- Customisation...
- Provide replacement header and footer templates
- Use a converter for customisation at run time
  - f* Input (Decode)
    - e.g. change AID, change cursor position
  - f* Output (Encode)
    - e.g. add timestamp

## 3270 based transactions – limitations


- The CICS Web Bridge supports
  - ƒ Terminal Control -> SEND, CONVERSE, RECEIVE
  - ƒ Minimum BMS and SEND TEXT
- The following restrictions have been removed by PTF UQ69745:
  - ƒ No dynamic modification of attribute bytes
  - ƒ Multiple SEND MAPs for one screen not supported
  - ƒ Cannot mix BMS and non-BMS SEND commands
  - ƒ Structured fields not supported
  - ƒ Lightpen emulation not supported
  - ƒ Must use same map on a RECEIVE following a SEND

# Accessing Existing CICS Transactions...non-BMS




# Accessing Existing CICS Applications...BMS

BMS application - 3270 screen....




## Accessing Existing CICS Applications...BMS

BMS application - default Web browser appearance....



# Accessing Existing CICS Applications...BMS

## BMS application - customised.....



## Agenda

---

- What is CICS Web Support?
- CICS Web Support architecture
- Enabling CICS Web Support
- Writing CICS Web applications
- Running 3270-based transactions with CICS Web Support
- **Hints & Tips**
- Further Information and Summary

## Hints & Tips

- Apply PQ33097 - Set SOCKETCLOSE parm to '0' instead of 'NO'

## Agenda

---

- What is CICS Web Support?
- CICS Web Support architecture
- Enabling CICS Web Support
- Writing CICS Web applications
- Running 3270-based transactions with CICS Web Support
- Hints & Tips
- **Further Information and Summary**

## Further Information

### ■ Web Sites

*f* **CICS (main site)**

-<http://ibm.com/cics>

*f* **CICS Transaction Server for VSE/ESA**

-<http://ibm.com/cics/platforms/cicsvse/>

*f* **CICS (SupportPacs)**

-<http://ibm.com/cics/txppacs/>

*f* **VSE/ESA**

-<http://www.s390.ibm.com/vse>

*f* **Redbooks**

-<http://www.redbooks.ibm.com>

## Further Information....

### ■ Publications

Title	Number
<b>CICS Transaction Server for VSE/ESA V1.1.1 product publications</b>	
Internet Guide	SC34-5765
Enhancements Guide	GC34-5763
External Interfaces Guide	SC33-1669
<b>IBM Redbooks</b>	
CICS Transaction Server for VSE/ESA: CICS Web Support	SG24-5997
Revealed! Architecting Web Access to CICS	SG24-5466
Getting Started with TCP/IP for VSE/ESA V1.4	SG24-5626
e-business Solutions for VSE/ESA	SG24-5662

*f* Accessible from the CICS and IBM Redbooks Web sites

## Further Information....

---

### ■ Announcement Letters

- f* CICS Transaction Server for VSE/ESA V1.1.1: 200-293
- f* VSE/ESA V2.6: 201-325
- f* VSE/ESA V2.7: 203-043

## Summary

### *CICS Web Support....*

- Access to CICS Application programs and transactions from standard Web Browsers
- Direct connection
- Standard HTTP protocol used
- Secure Sockets Layer supported
- New APIs to enable creation of new Web aware applications
- Provided with CICS Transaction Server for VSE/ESA V1.1.1



# WAVV 2004 Conference



## CICS Web Support: Access to CICS Applications from the Web

**Robin Gemmell**  
**(gummell@uk.ibm.com)**

**Chattanooga, April 30 – May 4 2004**

# Appendix

---

## APPENDIX

## HTTP Request

Request Line

Headers

Body

● **Request Line : method absolute\_path http\_version CRLF**  
**POST /bin/cgi HTTP/1.0**

● **Headers: headername: value CRLF**  
**Accept: image/jpeg**  
**Content-length: 44**

● **Null Line: single CRLF delimits end of headers**

● **Body: URL encoded forms data : name=value pairs**  
**field1=stringa&field2=stringb&field3=stringc**

## HTTP Response

Status Line

Headers

Body

- **Status Line: HTTP\_version status\_code text CRLF**

HTTP/1.0 200 Document follows

- **Headers: headername: value CRLF**

Content-type: text/html

Content-length: 46

Last-modified: Wed, 04 Oct 2000 08:45:00 GMT

- **Null Line: single CRLF delimits end of headers**

- **Body: HTML tags and text**

```
<html><title>A Sample</title><h1>Sample 1</h1></html>
```