


IBM® Analytical Decision Management
Version 17 Release 0

Schema Reference



Note

Before using this information and the product it supports, read the information in "Notices" on page 53.

Product Information

This edition applies to version 17, release 0, modification 0 of IBM Analytical Decision Management and to all subsequent releases and modifications until otherwise indicated in new editions.

© Copyright IBM Corporation 2010, 2015.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

| | |
|--|-----------|
| Element reference | 1 |
| Elements | 1 |
| PredictiveApplication Element | 1 |
| Extended Types | 41 |
| ConstantBoundary Type | 42 |
| ConstantValueSource Type | 42 |
| PrioritizationOptimization Type | 43 |
| VariableReferenceBoundary Type | 43 |
| typeDecisionHierarchyDefineStep Type | 44 |
| typeModelingDefineStep Type | 47 |
| typeObjectiveFunction Type | 49 |
| typeRulesManagementDefineStep Type | 51 |
| Notices | 53 |
| Trademarks | 54 |
| Index | 57 |

Element reference

This guide provides a reference for all the main elements in the XML schema used to configure and customize applications. Each section lists the valid attributes for an element and its parent and child elements.

A copy of the XML schema is also provided with the product for reference purposes. It can be helpful to open the main *workspace.xsd* schema in an XML editor and familiarize yourself with it. The schema is available in the IBM® SPSS® Collaboration and Deployment Services installation directory (for example, *C:\Program Files\IBM\SPSS\Deployment\7.0\Server\components\decision-management\Schemas\workspace.xsd*).

Note: Some schemas and elements are for internal use only, and some have been deprecated since first being introduced. Only *workspace.xsd* should be used.

Elements

PredictiveApplication Element

The PredictiveApplication is a template used when creating new projects using IBM Analytical Decision Management.

Table 1. Attributes for PredictiveApplication

| Attribute | Use | Description | Valid Values |
|---------------|----------|---|---------------|
| appsVersion | optional | For internal use only. Version of Decision Management that last modified this project. Format is expected to be (major).(minor) | <i>string</i> |
| cacheHandle | optional | For internal use only. Run time tracking of the associated cache handle for this object. | <i>string</i> |
| groupTemplate | optional | Deprecated as of Decision Management 6.1. The Application Group definition file spec to use for controlling common presentation aspects of an object from this group. | <i>string</i> |

Table 1. Attributes for PredictiveApplication (continued)

| Attribute | Use | Description | Valid Values |
|------------------------------------|----------|--|--------------|
| initialDimensionForScenarioResults | optional | Dimension that will be displayed initially in Scenario Results. For example, setting initialDimensionForScenarioResults="Offer" makes the Offer dimension the default primary dimension in Scenario Results. This is optional. If no dimension is defined, the first dimension in the application template will be used. | string |
| name | optional | Deprecated as of Decision Management 6.1. Use TitleEntry in the description.xml file for this application. | string |
| objectOrigin | optional | For internal use only. Run time information on the origin of this project. | string |
| previousVersion | optional | For internal use only. Deprecated. Previous version of the Application Template used to create this project. | string |
| priorityDimension | optional | Deprecated. Dimension considered to be the Priority Dimension. Use "hasPriority" attribute in individual Dimension elements. | string |
| templateName | required | The name of this application template. | string |
| templateVersion | required | Version of the application template used to create this application instance. | string |
| testMode | optional | For internal use only. Indicates application should be executed in Test mode. | boolean |
| testModeInteractionPoint | optional | For internal use only. Indicates the interaction point when running in Test mode. | string |

XML Representation

```

<xs:element name="PredictiveApplication" abstract="false">
  <xs:sequence>
    <xs:element name="InterfaceControl" type="typeInterfaceControl">
      <xs:sequence>
        <xs:element name="InterfacePages">
          <xs:sequence>
            <xs:element name="ApplicationHome" type="typeApplicationHomeStep" minOccurs="0">
            </xs:element>
            <xs:element name="DataStep" type="typeDataStep" minOccurs="0">

```

```

</xs:element>
<xs:element name="GlobalSelectionStep" type="typeGlobalSelectionStep" minOccurs="0">
</xs:element>
<xs:element name="DefineStep" type="typeDefineStep" minOccurs="0">
</xs:element>
<xs:element name="CombineStep" type="typeCombineStep" minOccurs="0">
</xs:element>
<xs:element name="OptimizeStep" type="typeOptimizeStep" minOccurs="0">
<xs:sequence>
<xs:element name="OptimizeMethod" type="typeOptimizeType"/>
</xs:sequence>
</xs:element>
<xs:element name="DeployScoreStep" type="typeDeployScoreStep" minOccurs="0">
<xs:sequence>
<xs:element name="ImmediateBatchScoring" type="typeImmediateBatchScoring" minOccurs="0">
</xs:element>
<xs:element name="ScheduledBatchScoring" type="typeScheduledBatchScoring" minOccurs="0">
</xs:element>
<xs:element name="RealTimeScoring" type="typeRealTimeDeploy" minOccurs="0">
</xs:element>
</xs:sequence>
</xs:element>
<xs:element name="ReportStep" minOccurs="0">
</xs:element>
</xs:sequence>
</xs:element>
<xs:element name="InterfaceFeature" type="typeInterfaceFeature" minOccurs="0" maxOccurs="unbounded">
</xs:element>
<xs:element name="ReferenedDimensionHierarchy" type="typeReferencedDimension" minOccurs="0" maxOccurs="unbounded"/>
<xs:element name="SpecialVariableReference" type="typeUserVariableReference" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:element>
<xs:element name="Inputs" type="typeInputs" minOccurs="0"/>
<xs:element name="EntityDimension" type="typeEntityDimension" minOccurs="0">
<xs:sequence>
<xs:element name="Attributes" type="typeAttributeReference" minOccurs="0" maxOccurs="unbounded"/>
<xs:element name="InteractiveQuestions" type="typeInteractiveQuery" minOccurs="0" maxOccurs="unbounded"/>
<xs:element name="Variable" type="typeVariable" minOccurs="0" maxOccurs="unbounded">
<xs:sequence>
<xs:element name="ValueSource" type="typeValueSource"/>
</xs:sequence>
</xs:element>
<xs:element name="DerivedVariable" type="typeDerivedVariable" minOccurs="0" maxOccurs="unbounded">
<xs:sequence>
<xs:element name="VariableExpression" type="typeVariableExpression" minOccurs="0">
</xs:element>
</xs:sequence>
</xs:element>
<xs:element name="Constraint" type="typeConstraint" minOccurs="0" maxOccurs="unbounded">
<xs:sequence>
<xs:element name="Boundary" type="typeConstraintBoundary">
</xs:element>
<xs:element name="Function" type="rules:typeExpression" minOccurs="0"/>
<xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
</xs:element>
<xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0"/>
</xs:element>
<xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:element>
<xs:element name="Selection" type="typeLocalRule" minOccurs="0"/>
<xs:element name="Allocation" type="typeDimensionAllocation" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:element>
<xs:element name="Dimension" type="typeDimension" minOccurs="0" maxOccurs="unbounded">
<xs:sequence>
<xs:element name="Variable" type="typeVariable" minOccurs="0" maxOccurs="unbounded">
<xs:sequence>
<xs:element name="ValueSource" type="typeValueSource"/>
</xs:sequence>
</xs:element>
<xs:element name="Constraint" type="typeConstraint" minOccurs="0" maxOccurs="unbounded">
<xs:sequence>
<xs:element name="Boundary" type="typeConstraintBoundary">
</xs:element>
<xs:element name="Function" type="rules:typeExpression" minOccurs="0"/>
<xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
</xs:element>
<xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0"/>
</xs:element>
<xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:element>
<xs:element name="Member" type="typeDimensionMember" minOccurs="0" maxOccurs="unbounded"/>

```

```

<xs:element name="Property" type="typeProperty" minOccurs="0" maxOccurs="unbounded">
</xs:element>
</xs:sequence>
</xs:element>
<xs:element name="Optimization" type="typeOptimizationDefinition" minOccurs="0">
<xs:sequence>
<xs:element name="ObjectiveFunction" type="typeObjectiveFunction" maxOccurs="unbounded">
<xs:sequence>
<xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
</xs:element>
<xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
</xs:element>
<xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:element>
<xs:element name="Constraint" type="typeConstraint" minOccurs="0" maxOccurs="unbounded">
<xs:sequence>
<xs:element name="Boundary" type="typeConstraintBoundary">
</xs:element>
<xs:element name="Function" type="rules:typeExpression" minOccurs="0"/>
<xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
</xs:element>
<xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
</xs:element>
<xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:element>
<xs:element name="OPLMapping" type="typeOPLMapping" minOccurs="0">
<xs:sequence>
<xs:element name="EntityField" type="typeEntityField" minOccurs="1" maxOccurs="unbounded">
</xs:element>
<xs:element name="OptimizationOutput" type="typeOptimizationOutput" minOccurs="1" maxOccurs="unbounded">
</xs:element>
</xs:sequence>
</xs:element>
<xs:element name="CPLEXConfiguration" type="typeCPLEXConfiguration" minOccurs="0">
<xs:sequence>
<xs:element name="CPLEXSetting" type="typeCPLEXSetting" minOccurs="0" maxOccurs="unbounded">
</xs:element>
</xs:sequence>
</xs:element>
<xs:element name="Deployment" type="typeDeployment" minOccurs="0">
<xs:sequence>
<xs:element name="DeployLabel" type="typeLabelDefinition" minOccurs="0" maxOccurs="unbounded">
</xs:element>
<xs:element name="OutputAttribute" type="typeOutputAttribute" minOccurs="0" maxOccurs="unbounded">
</xs:element>
<xs:element name="InteractionPoint" minOccurs="0" maxOccurs="unbounded">
</xs:element>
</xs:sequence>
</xs:element>
<xs:element name="CurrentStateReport" type="typeCurrentStateReportItem" minOccurs="0"/>
<xs:element name="Report" type="typeReportItem" minOccurs="0" maxOccurs="unbounded"/>
<xs:element name="Tasks" type="typeTaskInformation" minOccurs="0"/>
<xs:element name="UnusedResource" type="typeUnusedResource" minOccurs="0"/>
<xs:element name="StreamSettings" type="typeStreamSettings" minOccurs="0"/>
</xs:sequence>
<xs:attribute name="appsVersion" type="xs:string" use="optional"/>
<xs:attribute name="templateName" type="xs:string" use="required"/>
<xs:attribute name="templateVersion" type="xs:string" use="required"/>
<xs:attribute name="groupTemplate" type="xs:string" use="optional"/>
<xs:attribute name="name" type="xs:string" use="optional"/>
<xs:attribute name="priorityDimension" type="xs:string" use="optional"/>
<xs:attribute name="initialDimensionForScenarioResults" type="xs:string" use="optional"/>
<xs:attribute name="objectOrigin" type="xs:string" use="optional"/>
<xs:attribute name="cacheHandle" type="xs:string" use="optional"/>
<xs:attribute name="previousVersion" type="xs:string" use="optional"/>
<xs:attribute name="testMode" type="xs:boolean" use="optional" default="false"/>
<xs:attribute name="testModeInteractionPoint" type="xs:string" use="optional"/>
</xs:element>
```

Child Elements

CurrentStateReport, Deployment, Dimension, EntityDimension, Inputs, InterfaceControl, Optimization, Report, StreamSettings, Tasks, UnusedResource

InterfaceControl Element

Control of the user interface presented for this application type.

XML Representation

```
<xs:element name="InterfaceControl" type="typeInterfaceControl">
  <xss:sequence>
    <xs:element name="InterfacePages">
      <xss:sequence>
        <xs:element name="ApplicationHome" type="typeApplicationHomeStep" minOccurs="0">
        </xs:element>
        <xs:element name="DataStep" type="typeDataStep" minOccurs="0">
        </xs:element>
        <xs:element name="GlobalSelectionStep" type="typeGlobalSelectionStep" minOccurs="0">
        </xs:element>
        <xs:element name="DefineStep" type="typeDefineStep" minOccurs="0">
        </xs:element>
        <xs:element name="CombineStep" type="typeCombineStep" minOccurs="0">
        </xs:element>
        <xs:element name="OptimizeStep" type="typeOptimizeStep" minOccurs="0">
          <xss:sequence>
            <xs:element name="OptimizeMethod" type="typeOptimizeType"/>
          </xss:sequence>
        </xs:element>
      </xss:sequence>
    <xs:element name="DeployScoreStep" type="typeDeployScoreStep" minOccurs="0">
      <xss:sequence>
        <xs:element name="ImmediateBatchScoring" type="typeImmediateBatchScoring" minOccurs="0">
        </xs:element>
        <xs:element name="ScheduledBatchScoring" type="typeScheduledBatchScoring" minOccurs="0">
        </xs:element>
        <xs:element name="RealTimeScoring" type="typeRealTimeDeploy" minOccurs="0">
        </xs:element>
      </xss:sequence>
    </xs:element>
    <xs:element name="ReportStep" minOccurs="0">
    </xs:element>
  </xss:sequence>
</xs:element>
<xs:element name="InterfaceFeature" type="typeInterfaceFeature" minOccurs="0" maxOccurs="unbounded">
</xs:element>
<xs:element name="ReferenedDimensionHierarchy" type="typeReferencedDimension" minOccurs="0" maxOccurs="unbounded"/>
<xs:element name="SpecialVariableReference" type="typeUserVariableReference" minOccurs="0" maxOccurs="unbounded"/>
</xss:sequence>
</xs:element>
```

Parent Elements

PredictiveApplication

Child Elements

InterfaceFeature, InterfacePages, ReferenedDimensionHierarchy, SpecialVariableReference

InterfacePages Element: Pages to include in the main panel for this application.

Table 2. Attributes for InterfacePages

| Attribute | Use | Description | Valid Values |
|-------------|----------|---|--------------|
| defaultStep | optional | The name of the step/tab to display as the default in the user interface. | string |

XML Representation

```
<xs:element name="InterfacePages">
  <xss:sequence>
    <xs:element name="ApplicationHome" type="typeApplicationHomeStep" minOccurs="0">
    </xs:element>
    <xs:element name="DataStep" type="typeDataStep" minOccurs="0">
    </xs:element>
    <xs:element name="GlobalSelectionStep" type="typeGlobalSelectionStep" minOccurs="0">
    </xs:element>
    <xs:element name="DefineStep" type="typeDefineStep" minOccurs="0">
    </xs:element>
    <xs:element name="CombineStep" type="typeCombineStep" minOccurs="0">
    </xs:element>
    <xs:element name="OptimizeStep" type="typeOptimizeStep" minOccurs="0">
      <xss:sequence>
```

```

<xs:element name="OptimizeMethod" type="typeOptimizeType"/>
</xs:sequence>
</xs:element>
<xs:element name="DeployScoreStep" type="typeDeployScoreStep" minOccurs="0">
<xs:sequence>
<xs:element name="ImmediateBatchScoring" type="typeImmediateBatchScoring" minOccurs="0">
</xs:element>
<xs:element name="ScheduledBatchScoring" type="typeScheduledBatchScoring" minOccurs="0">
</xs:element>
<xs:element name="RealTimeScoring" type="typeRealTimeDeploy" minOccurs="0">
</xs:element>
</xs:sequence>
</xs:element>
<xs:element name="ReportStep" minOccurs="0">
</xs:element>
</xs:sequence>
<xs:attribute name="defaultStep" type="xs:string" use="optional"/>
</xs:element>

```

Parent Elements

InterfaceControl

Child Elements

ApplicationHome, CombineStep, DataStep, DefineStep, DeployScoreStep, GlobalSelectionStep, OptimizeStep, ReportStep

ApplicationHome Element: The application Home page configuration.

Table 3. Attributes for ApplicationHome

| Attribute | Use | Description | Valid Values |
|---------------|----------|---|--------------|
| showGallery | optional | Controls the presentation of the Gallery interaction section. | boolean |
| stepCompleted | optional | Indicates whether the user has marked this panel as completed or not. | boolean |
| stepHidden | optional | The "hidden" state for this panel. | boolean |
| stepIncluded | optional | The logical "included or not" flag for this panel. | boolean |
| stepLocked | optional | The locked state for this panel. | boolean |

XML Representation

```

<xs:element name="ApplicationHome" type="typeApplicationHomeStep" minOccurs="0">
<xs:attribute name="stepIncluded" type="xs:boolean" default="true"/>
<xs:attribute name="stepHidden" type="xs:boolean" default="false"/>
<xs:attribute name="stepLocked" type="xs:boolean" default="false"/>
<xs:attribute name="stepCompleted" type="xs:boolean" use="optional" default="false"/>
<xs:attribute name="showGallery" type="xs:boolean" use="optional" default="false"/>
</xs:element>

```

Parent Elements

InterfacePages

DataStep Element: The Data tab configuration.

Table 4. Attributes for DataStep

| Attribute | Use | Description | Valid Values |
|--------------------|----------|--|----------------|
| lockPrimaryDataSet | optional | Optional flag (default is "false") controlling whether the Project Data Model selection is locked by the administrator or not. | <i>boolean</i> |
| permitExpressions | optional | Flag to indicate whether derived attribute expressions are permitted to extend a data set. | <i>boolean</i> |
| stepCompleted | optional | Indicates whether the user has marked this panel as completed or not. | <i>boolean</i> |
| stepHidden | optional | The "hidden" state for this panel. | <i>boolean</i> |
| stepIncluded | optional | The logical "included or not" flag for this panel. | <i>boolean</i> |
| stepLocked | optional | The locked state for this panel. | <i>boolean</i> |

XML Representation

```
<xs:element name="DataStep" type="typeDataStep" minOccurs="0">
  <xs:attribute name="stepIncluded" type="xs:boolean" default="true"/>
  <xs:attribute name="stepHidden" type="xs:boolean" default="false"/>
  <xs:attribute name="stepLocked" type="xs:boolean" default="false"/>
  <xs:attribute name="stepCompleted" type="xs:boolean" use="optional" default="false"/>
  <xs:attribute name="permitExpressions" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="lockPrimaryDataSet" type="xs:boolean" use="optional" default="false"/>
</xs:element>
```

Parent Elements

InterfacePages

GlobalSelectionStep Element: The Global Selections tab configuration.

Table 5. Attributes for GlobalSelectionStep

| Attribute | Use | Description | Valid Values |
|---------------|----------|---|----------------|
| stepCompleted | optional | Indicates whether the user has marked this panel as completed or not. | <i>boolean</i> |
| stepHidden | optional | The "hidden" state for this panel. | <i>boolean</i> |
| stepIncluded | optional | The logical "included or not" flag for this panel. | <i>boolean</i> |
| stepLocked | optional | The locked state for this panel. | <i>boolean</i> |

XML Representation

```
<xs:element name="GlobalSelectionStep" type="typeGlobalSelectionStep" minOccurs="0">
  <xs:attribute name="stepIncluded" type="xs:boolean" default="true"/>
  <xs:attribute name="stepHidden" type="xs:boolean" default="false"/>
  <xs:attribute name="stepLocked" type="xs:boolean" default="false"/>
  <xs:attribute name="stepCompleted" type="xs:boolean" use="optional" default="false"/>
</xs:element>
```

Parent Elements

InterfacePages

DefineStep Element: The Define tab configuration.

Table 6. Attributes for DefineStep

| Attribute | Use | Description | Valid Values |
|-------------------------|----------|--|--------------|
| enableInteractionPoints | optional | Logical switch controlling whether Interaction Points are presented to the user or not. | boolean |
| enableSimulation | optional | Deprecated as of Decision Management 8.0. Controls presentation of the Define-style Simulation action. | boolean |
| enableTest | optional | Deprecated as of Decision Management 8.0. Controls presentation of the Test action. | boolean |
| stepCompleted | optional | Indicates whether the user has marked this panel as completed or not. | boolean |
| stepHidden | optional | The "hidden" state for this panel. | boolean |
| stepIncluded | optional | The logical "included or not" flag for this panel. | boolean |
| stepLocked | optional | The locked state for this panel. | boolean |

XML Representation

```
<xs:element name="DefineStep" type="typeDefineStep" minOccurs="0">
  <xs:attribute name="stepIncluded" type="xs:boolean" default="true"/>
  <xs:attribute name="stepHidden" type="xs:boolean" default="false"/>
  <xs:attribute name="stepLocked" type="xs:boolean" default="false"/>
  <xs:attribute name="stepCompleted" type="xs:boolean" use="optional" default="false"/>
  <xs:attribute name="enableSimulation" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="enableTest" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="enableInteractionPoints" type="xs:boolean" use="optional" default="true"/>
</xs:element>
```

Table 7. Extended Types

| Type | Description |
|---------------------------------|--|
| typeDecisionHierarchyDefineStep | The decision hierarchy definition step configuration. AggregationRuleSection and PredictiveModelSection may not both be enabled when using more than 2 dimensions. |
| typeModelingDefineStep | The Model definition step configuration. |
| typeRulesManagementDefineStep | Configuration of the Define tab in the Rules Management application. |

Parent Elements

InterfacePages

CombineStep Element: The Combine tab configuration.

Table 8. Attributes for CombineStep

| Attribute | Use | Description | Valid Values |
|---------------|----------|--|--------------|
| enableTest | optional | Indicates whether the "Test" function is enabled or disabled on the Combine tab. | boolean |
| enableWhatif | optional | Indicates whether the "What If?" function is enabled or disabled on the Combine tab. | boolean |
| stepCompleted | optional | Indicates whether the user has marked this panel as completed or not. | boolean |
| stepHidden | optional | The "hidden" state for this panel. | boolean |
| stepIncluded | optional | The logical "included or not" flag for this panel. | boolean |
| stepLocked | optional | The locked state for this panel. | boolean |

XML Representation

```
<xs:element name="CombineStep" type="typeCombineStep" minOccurs="0">
  <xs:attribute name="stepIncluded" type="xs:boolean" default="true"/>
  <xs:attribute name="stepHidden" type="xs:boolean" default="false"/>
  <xs:attribute name="stepLocked" type="xs:boolean" default="false"/>
  <xs:attribute name="stepCompleted" type="xs:boolean" use="optional" default="false"/>
  <xs:attribute default="true" name="enableWhatif" type="xs:boolean"/>
  <xs:attribute default="true" name="enableTest" type="xs:boolean"/>
</xs:element>
```

Parent Elements

InterfacePages

OptimizeStep Element: The Prioritize/Optimize tab configuration.

Table 9. Attributes for OptimizeStep

| Attribute | Use | Description | Valid Values |
|---------------|----------|--|--------------|
| enableTest | optional | Indicates whether the "Test" function is enabled or disabled on the Prioritize/Optimize tab. | boolean |
| enableWhatif | optional | Indicates whether the "What If?" function is enabled or disabled on the Prioritize/Optimize tab. | boolean |
| stepCompleted | optional | Indicates whether the user has marked this panel as completed or not. | boolean |

Table 9. Attributes for OptimizeStep (continued)

| Attribute | Use | Description | Valid Values |
|--------------|----------|--|----------------|
| stepHidden | optional | The "hidden" state for this panel. | <i>boolean</i> |
| stepIncluded | optional | The logical "included or not" flag for this panel. | <i>boolean</i> |
| stepLocked | optional | The locked state for this panel. | <i>boolean</i> |

XML Representation

```
<xs:element name="OptimizeStep" type="typeOptimizeStep" minOccurs="0">
  <xs:attribute name="stepIncluded" type="xs:boolean" default="true"/>
  <xs:attribute name="stepHidden" type="xs:boolean" default="false"/>
  <xs:attribute name="stepLocked" type="xs:boolean" default="false"/>
  <xs:attribute name="stepCompleted" type="xs:boolean" use="optional" default="false"/>
  <xs:sequence>
    <xs:element name="OptimizeMethod" type="typeOptimizeType"/>
  </xs:sequence>
  <xs:attribute name="enableWhatif" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="enableTest" type="xs:boolean" use="optional" default="true"/>
</xs:element>
```

Parent Elements

InterfacePages

Child Elements

OptimizeMethod

OptimizeMethod Element: Method to use for combining or optimizing results to reach a decision.

XML Representation

```
<xs:element name="OptimizeMethod" type="typeOptimizeType"/>
```

Table 10. Extended Types

| Type | Description |
|----------------------------|--|
| PrioritizationOptimization | The Prioritization form of optimization. |

Parent Elements

OptimizeStep

DeployScoreStep Element: The Deploy/Score tab configuration.

Table 11. Attributes for DeployScoreStep

| Attribute | Use | Description | Valid Values |
|-------------------------------|----------|---|----------------|
| hasInteractiveQuestionSection | optional | Interactive questions is a feature that may be used with real time scoring to prompt the user for input attributes when they are missing. | <i>boolean</i> |
| lockBatchScoringOutputFields | optional | Administrator lock of the batch Scoring Output Fields section. | <i>boolean</i> |

Table 11. Attributes for DeployScoreStep (continued)

| Attribute | Use | Description | Valid Values |
|---------------------------------|----------|---|--------------|
| lockInteractiveQuestionSection | optional | Administrator lock of the Interactive Questions section. | boolean |
| lockRealTimeScoringOutputFields | optional | Administrator lock of the real time Scoring Output Fields section. | boolean |
| stepCompleted | optional | Indicates whether the user has marked this panel as completed or not. | boolean |
| stepHidden | optional | The "hidden" state for this panel. | boolean |
| stepIncluded | optional | The logical "included or not" flag for this panel. | boolean |
| stepLocked | optional | The locked state for this panel. | boolean |

XML Representation

```
<xs:element name="DeployScoreStep" type="typeDeployScoreStep" minOccurs="0">
  <xs:attribute name="stepIncluded" type="xs:boolean" default="true"/>
  <xs:attribute name="stepHidden" type="xs:boolean" default="false"/>
  <xs:attribute name="stepLocked" type="xs:boolean" default="false"/>
  <xs:attribute name="stepCompleted" type="xs:boolean" use="optional" default="false"/>
  <xs:sequence>
    <xs:element name="ImmediateBatchScoring" type="typeImmediateBatchScoring" minOccurs="0">
    </xs:element>
    <xs:element name="ScheduledBatchScoring" type="typeScheduledBatchScoring" minOccurs="0">
    </xs:element>
    <xs:element name="RealTimeScoring" type="typeRealTimeDeploy" minOccurs="0">
    </xs:element>
  </xs:sequence>
  <xs:attribute name="hasInteractiveQuestionSection" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="lockInteractiveQuestionSection" type="xs:boolean" use="optional" default="false"/>
  <xs:attribute name="lockRealTimeScoringOutputFields" type="xs:boolean" use="optional" default="false"/>
  <xs:attribute name="lockBatchScoringOutputFields" type="xs:boolean" use="optional" default="false"/>
</xs:element>
```

Parent Elements

InterfacePages

Child Elements

ImmediateBatchScoring, RealTimeScoring, ScheduledBatchScoring

ImmediateBatchScoring Element: Configuration of Immediate Batch scoring.

Table 12. Attributes for ImmediateBatchScoring

| Attribute | Use | Description | Valid Values |
|----------------------|----------|--|--------------|
| enableScoringOptions | optional | Controls whether the Scoring Options will be presented or not. | boolean |

XML Representation

```
<xs:element name="ImmediateBatchScoring" type="typeImmediateBatchScoring" minOccurs="0">
  <xs:attribute name="enableScoringOptions" type="xs:boolean" use="optional" default="false"/>
</xs:element>
```

Parent Elements

DeployScoreStep

ScheduledBatchScoring Element: For internal use only. Not supported.

Table 13. Attributes for ScheduledBatchScoring

| Attribute | Use | Description | Valid Values |
|----------------------|----------|--|----------------|
| enableScoringOptions | optional | Controls whether the Scoring Options will be presented or not. | <i>boolean</i> |

XML Representation

```
<xs:element name="ScheduledBatchScoring" type="typeScheduledBatchScoring" minOccurs="0">
  <xs:attribute name="enableScoringOptions" type="xs:boolean" use="optional" default="false"/>
</xs:element>
```

Parent Elements

DeployScoreStep

RealTimeScoring Element: Configuration of a Real Time Scoring deployment.

Table 14. Attributes for RealTimeScoring

| Attribute | Use | Description | Valid Values |
|----------------------------|----------|---|----------------|
| enableInteractiveQuestions | optional | Flag indicating whether the Interactive Questions interface will be presented on the Deploy panel or not. | <i>boolean</i> |

XML Representation

```
<xs:element name="RealTimeScoring" type="typeRealTimeDeploy" minOccurs="0">
  <xs:attribute name="enableInteractiveQuestions" type="xs:boolean" use="optional" default="true"/>
</xs:element>
```

Parent Elements

DeployScoreStep

ReportStep Element: The Report tab configuration.

Table 15. Attributes for ReportStep

| Attribute | Use | Description | Valid Values |
|--------------------------|----------|--|----------------|
| hideCurrentResults | optional | Optional flag (default is "false") to control whether the Current State report items are hidden from non-administrator users or not. | <i>boolean</i> |
| lockCurrentResultsReport | optional | Optional flag (default is "false") to control the administrator lock of the Current State report selection list. | <i>boolean</i> |

Table 15. Attributes for ReportStep (continued)

| Attribute | Use | Description | Valid Values |
|-------------------------|----------|---|--------------|
| lockCurrentResultsTitle | optional | Optional flag (default is "false") to control the administrator lock of the Current State report section title. | boolean |
| stepCompleted | optional | Indicates whether the user has marked this panel as completed or not. | boolean |
| stepHidden | optional | The "hidden" state for this panel. | boolean |
| stepIncluded | optional | The logical "included or not" flag for this panel. | boolean |
| stepLocked | optional | The locked state for this panel. | boolean |

XML Representation

```
<xs:element name="ReportStep" minOccurs="0">
  <xs:attribute name="stepIncluded" type="xs:boolean" default="true"/>
  <xs:attribute name="stepHidden" type="xs:boolean" default="false"/>
  <xs:attribute name="stepLocked" type="xs:boolean" default="false"/>
  <xs:attribute name="stepCompleted" type="xs:boolean" use="optional" default="false"/>
  <xs:attribute name="hideCurrentResults" type="xs:boolean" use="optional" default="false"/>
  <xs:attribute name="lockCurrentResultsReport" type="xs:boolean" use="optional" default="false"/>
  <xs:attribute name="lockCurrentResultsTitle" type="xs:boolean" use="optional" default="false"/>
</xs:element>
```

Parent Elements

InterfacePages

InterfaceFeature Element: Controllable features to expose in the user interface presented for this application.

Table 16. Attributes for InterfaceFeature

| Attribute | Use | Description | Valid Values |
|-----------|----------|--|---|
| id | required | ID code for the major feature to expose. | ModelReference. Ability to reference models stored in the IBM SPSS Collaboration and Deployment Services Repository. ModelBuild. Ability to build models in IBM Analytical Decision Management applications other than IBM SPSS Modeler Advantage. ModelExport. Ability to save models to the IBM SPSS Collaboration and Deployment Services Repository. RuleExport. Ability to save rules to the IBM SPSS Collaboration and Deployment Services Repository. RuleReference. Ability to reference rules stored in the IBM SPSS Collaboration and Deployment Services Repository. Collaboration. Ability to reference or save objects to the IBM SPSS Collaboration and Deployment Services Repository. UploadDownload. Ability to open stream files from or save stream files to the user's local file system. MetadataDownload. The ability to download a .ZIP file containing metadata about the current project. |

XML Representation

```

<xs:element name="InterfaceFeature" type="typeInterfaceFeature" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="id" type="enumFeatureType" use="required">
    <xs:enumeration value="ModelReference"/>
    <xs:enumeration value="ModelBuild"/>
    <xs:enumeration value="ModelExport"/>
    <xs:enumeration value="RuleExport"/>
    <xs:enumeration value="RuleReference"/>
    <xs:enumeration value="Collaboration"/>
    <xs:enumeration value="UploadDownload"/>
    <xs:enumeration value="MetadataDownload"/>
  </xs:attribute>
</xs:element>

```

Parent Elements

InterfaceControl

ReferencedDimensionHierarchy Element: For internal use only. The Dimension hierarchy as defined in the user interface.

XML Representation

```
<xs:element name="ReferencedDimensionHierarchy" type="typeReferencedDimension" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

InterfaceControl

SpecialVariableReference Element: For internal use only. A list of the variables to be managed in a special way by the user interface.

XML Representation

```
<xs:element name="SpecialVariableReference" type="typeUserVariableReference" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

InterfaceControl

Inputs Element

For internal use only. The primary input source for this application.

XML Representation

```
<xs:element name="Inputs" type="typeInputs" minOccurs="0"/>
```

Parent Elements

PredictiveApplication

EntityDimension Element

Dimension that defined the input data to this predictive application (such as Customer, Product, etc.).

Table 17. Attributes for EntityDimension

| Attribute | Use | Description | Valid Values |
|-----------|----------|---|--------------|
| editable | optional | Flag controlling editability in non-administrator interfaces. | boolean |
| name | optional | Name of the element. | string |

XML Representation

```
<xs:element name="EntityDimension" type="typeEntityDimension" minOccurs="0">
  <xs:attribute name="name" type="xs:string" use="optional"/>
  <xs:attribute name="editable" type="xs:boolean" use="optional" default="true"/>
  <xs:sequence>
    <xs:element name="Attributes" type="typeAttributeReference" minOccurs="0" maxOccurs="unbounded"/>
    <xs:element name="InteractiveQuestions" type="typeInteractiveQuery" minOccurs="0" maxOccurs="unbounded"/>
    <xs:element name="Variable" type="typeVariable" minOccurs="0" maxOccurs="unbounded">
      <xs:sequence>
        <xs:element name="ValueSource" type="typeValueSource"/>
      </xs:sequence>
    </xs:element>
    <xs:element name="DerivedVariable" type="typeDerivedVariable" minOccurs="0" maxOccurs="unbounded">
      <xs:sequence>
        <xs:element name="VariableExpression" type="typeVariableExpression" minOccurs="0">
```

```

        </xs:element>
    </xs:sequence>
</xs:element>
<xs:element name="Constraint" type="typeConstraint" minOccurs="0" maxOccurs="unbounded">
    <xs:sequence>
        <xs:element name="Boundary" type="typeConstraintBoundary">
            </xs:element>
        <xs:element name="Function" type="rules:typeExpression" minOccurs="0"/>
        <xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
            </xs:element>
        <xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0"/>
            </xs:element>
        <xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
            </xs:sequence>
        </xs:element>
    <xs:element name="Selection" type="typeLocalRule" minOccurs="0"/>
    <xs:element name="Allocation" type="typeDimensionAllocation" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:element>

```

Parent Elements

PredictiveApplication

Child Elements

Allocation, Attributes, Constraint, DerivedVariable, InteractiveQuestions, Selection, Variable

Attributes Element: For internal use only. Attributes that define the Entity, defined by the primary data set.

XML Representation

```
<xs:element name="Attributes" type="typeAttributeReference" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

EntityDimension

InteractiveQuestions Element: List of "more input" interactive questions issued by interactive applications.

XML Representation

```
<xs:element name="InteractiveQuestions" type="typeInteractiveQuery" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

EntityDimension

Variable Element: List of Variables defined for the Entity.

Table 18. Attributes for Variable

| Attribute | Use | Description | Valid Values |
|---------------|-----------------|--|--------------|
| alwaysVisible | optional | Indicates if this variable should always be visible in the Prioritize/Optimize step. | boolean |
| dataType | required | Data type of this variable. | string |
| description | optional | Optional variable description. | string |

Table 18. Attributes for Variable (continued)

| Attribute | Use | Description | Valid Values |
|------------------------|----------|--|--------------|
| editable | optional | Flag controlling editability in non-administrator interfaces. | boolean |
| inherited | optional | Indicates whether this variable can be inherited by child dimension members. | boolean |
| isFromTemplate | optional | Internal use only. | boolean |
| name | optional | Name of the element. | string |
| optimizationInputItem | optional | Indicates if this variable is to be controlled in the Prioritize/Optimize step or not. | boolean |
| prompt | optional | When set, this key value controls the text to display when prompting for variable value input. | string |
| simulateAction | optional | If set, this variable will be summarized in the indicated manner during a simulation. | |
| simulateName | optional | When set, this key value controls the text to display when displaying the summarized value of this variable during a simulation. | string |
| simulateNumericDisplay | optional | Optional control of the display of numeric values (Integer, Percentage, or Double) under User Preferences formatting. | |
| tableIndex | optional | Variable index in prioritization table. | int |

XML Representation

```

<xs:element name="Variable" type="typeVariable" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="name" type="xs:string" use="optional"/>
  <xs:attribute name="editable" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="dataType" type="xs:string" use="required"/>
  <xs:attribute name="description" type="xs:string" use="optional"/>
  <xs:attribute name="simulateAction" type="enumVariableValueSummary" use="optional"/>
  <xs:attribute name="simulateName" type="xs:string" use="optional" default="VARIABLE_PROMPT"/>
  <xs:attribute name="simulateNumericDisplay" type="enumNumericDisplay"/>
  <xs:sequence>
    <xs:element name="ValueSource" type="typeValueSource"/>
  </xs:sequence>
  <xs:attribute name="tableIndex" type="xs:int" use="optional" default="0"/>
  <xs:attribute name="prompt" type="xs:string" use="optional" default="VARIABLE_PROMPT"/>
  <xs:attribute name="optimizationInputItem" type="xs:boolean" use="optional" default="false"/>
  <xs:attribute name="inherited" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="isFromTemplate" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="alwaysVisible" type="xs:boolean" use="optional" default="false"/>
</xs:element>
```

Parent Elements

EntityDimension

Child Elements

ValueSource

ValueSource Element: Source of default values for this Variable.

XML Representation

```
<xs:element name="ValueSource" type="typeValueSource"/>
```

Table 19. Extended Types

| Type | Description |
|---------------------|-------------------------|
| ConstantValueSource | A constant value source |

Parent Elements

Variable

DerivedVariable Element: List of DerivedVariables defined for the Entity.

Table 20. Attributes for DerivedVariable

| Attribute | Use | Description | Valid Values |
|------------------------|----------|--|--------------|
| dataType | required | Data type of this variable. | string |
| description | optional | Optional variable description. | string |
| editable | optional | Flag controlling editability in non-administrator interfaces. | boolean |
| name | optional | Name of the element. | string |
| simulateAction | optional | If set, this variable will be summarized in the indicated manner during a simulation. | |
| simulateName | optional | When set, this key value controls the text to display when displaying the summarized value of this variable during a simulation. | string |
| simulateNumericDisplay | optional | Optional control of the display of numeric values (Integer, Percentage, or Double) under User Preferences formatting. | |

XML Representation

```
<xs:element name="DerivedVariable" type="typeDerivedVariable" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="name" type="xs:string" use="optional"/>
  <xs:attribute name="editable" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="dataType" type="xs:string" use="required"/>
  <xs:attribute name="description" type="xs:string" use="optional"/>
  <xs:attribute name="simulateAction" type="enumVariableValueSummary" use="optional"/>
  <xs:attribute name="simulateName" type="xs:string" use="optional" default="VARIABLE_PROMPT"/>
  <xs:attribute name="simulateNumericDisplay" type="enumNumericDisplay"/>
<xs:sequence>
```

```

<xs:element name="VariableExpression" type="typeVariableExpression" minOccurs="0">
</xs:element>
</xs:sequence>
</xs:element>

```

Parent Elements

EntityDimension

Child Elements

VariableExpression

VariableExpression Element: An expression that can be based on other variables.

Table 21. Attributes for VariableExpression

| Attribute | Use | Description | Valid Values |
|------------|----------|--|--------------|
| expression | required | The expression format is the same as that used in the ObjectiveFunction expression format, i.e. a text string with the base variable references embedded with "\${...}". For example, <VariableExpression expression="\${OfferCost} + \${ChannelCost}" /> | string |

XML Representation

```

<xs:element name="VariableExpression" type="typeVariableExpression" minOccurs="0">
  <xs:attribute name="expression" type="xs:string" use="required"/>
</xs:element>

```

Parent Elements

DerivedVariable

Constraint Element: Deprecated. Entity constraints are now defined in the Optimization section. Constraints associated with this Dimension, to be applied in the execution and optimization of this application.

Table 22. Attributes for Constraint

| Attribute | Use | Description | Valid Values |
|-------------|----------|--|--------------|
| description | optional | Optional constraint description. | string |
| dimension | optional | The dimension owns the constraint. If not supplied, the dimension is assumed to be the owner of the Boundary variable. | string |
| editable | optional | Flag controlling editability in non-administrator interfaces. | boolean |
| enabled | optional | Indicates whether this constraint is enabled. | boolean |

Table 22. Attributes for Constraint (continued)

| Attribute | Use | Description | Valid Values |
|--------------|----------|---|---|
| entityScoped | optional | Indicates the scope of this constraint - within an entity or across all entities. | boolean |
| name | optional | Name of the element. | string |
| type | required | Constraint type. | max min equal notEqual lessThan lessThanEqual greaterThan greaterThanEqual |

XML Representation

```

<xs:element name="Constraint" type="typeConstraint" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="name" type="xs:string" use="optional"/>
  <xs:attribute name="editable" type="xs:boolean" use="optional" default="true"/>
  <xs:sequence>
    <xs:element name="Boundary" type="typeConstraintBoundary">
    </xs:element>
    <xs:element name="Function" type="rules:typeExpression" minOccurs="0"/>
    <xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
    </xs:element>
    <xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
    </xs:element>
    <xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="description" type="xs:string" use="optional"/>
  <xs:attribute name="type" type="enumConstraintType" use="required">
    <xs:enumeration value="max"/>
    <xs:enumeration value="min"/>
    <xs:enumeration value="equal"/>
    <xs:enumeration value="notEqual"/>
    <xs:enumeration value="lessThan"/>
    <xs:enumeration value="lessThanEqual"/>
    <xs:enumeration value="greaterThan"/>
    <xs:enumeration value="greaterThanEqual"/>
  </xs:attribute>
  <xs:attribute name="entityScoped" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="enabled" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="dimension" type="xs:string" use="optional"/>
</xs:element>

```

Parent Elements

EntityDimension

Child Elements

Boundary, ExpressionFormat, ExternalUsage, Function, InteractionPoint

Boundary Element: Constraint boundary.

Table 23. Attributes for Boundary

| Attribute | Use | Description | Valid Values |
|-----------|----------|--|--------------|
| value | required | The value or reference defining this boundary. | string |

XML Representation

```
<xs:element name="Boundary" type="typeConstraintBoundary">
  <xs:attribute name="value" type="xs:string" use="required"/>
</xs:element>
```

Table 24. Extended Types

| Type | Description |
|---------------------------|---|
| ConstantBoundary | A constant Constraint boundary. |
| VariableReferenceBoundary | A variable reference Constraint Boundary. |

Parent Elements

Constraint

Function Element: Constraint function definition (internally evaluated constraints).

XML Representation

```
<xs:element name="Function" type="rules:typeExpression" minOccurs="0"/>
```

Table 25. Extended Types

| Type | Description |
|-----------------------|--------------------------------|
| typeObjectiveFunction | Objective Function definition. |

Parent Elements

Constraint

ExternalUsage Element: Defines how this constraint can be enabled or disabled via an OPL variable (externally evaluated constraints).

Table 26. Attributes for ExternalUsage

| Attribute | Use | Description | Valid Values |
|-----------------|----------|---|------------------------|
| controlVariable | required | The OPL variable. | string |
| disabledValue | optional | The value that indicates this object is disabled (default 0). | string |
| enabledValue | optional | The value that indicates this object is enabled (default 1). | string |
| variableType | optional | The OPL variable type (default int). | int float string |

XML Representation

```
<xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
  <xs:attribute name="controlVariable" type="xs:string" use="required"/>
  <xs:attribute name="variableType" type="enumOPLValueType" use="optional" default="int">
    <xs:enumeration value="int"/>
    <xs:enumeration value="float"/>
    <xs:enumeration value="string"/>
  </xs:attribute>
  <xs:attribute name="enabledValue" type="xs:string" use="optional" default="1"/>
  <xs:attribute name="disabledValue" type="xs:string" use="optional" default="0"/>
</xs:element>
```

Parent Elements

Constraint

ExpressionFormat Element: Constraint function format (externally evaluated constraints).

Table 27. Attributes for ExpressionFormat

| Attribute | Use | Description | Valid Values |
|-----------|----------|--|--------------|
| format | required | The format definition for this expression. | string |

XML Representation

```
<xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
  <xs:attribute name="format" type="xs:string" use="required"/>
</xs:element>
```

Parent Elements

Constraint

InteractionPoint Element: For internal use only. Optional Interaction Point name used when differentiating constraint based on interaction points.

XML Representation

```
<xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

Constraint

Selection Element: For internal use only. Selection and Exclusion rules for Entity members.

XML Representation

```
<xs:element name="Selection" type="typeLocalRule" minOccurs="0"/>
```

Parent Elements

EntityDimension

Allocation Element: For internal use only. Allocation rule for the Entity Dimension and next level Dimension(s).

XML Representation

```
<xs:element name="Allocation" type="typeDimensionAllocation" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

EntityDimension

Dimension Element

The business problem's dimensional solution hierarchy.

Table 28. Attributes for Dimension

| Attribute | Use | Description | Valid Values |
|-----------------|----------|---|----------------|
| description | optional | Optional dimension description. | <i>string</i> |
| editable | optional | Flag controlling editability in non-administrator interfaces. | <i>boolean</i> |
| hasPriority | optional | Set to "true" if this dimension can have a priority value associated with it. | <i>boolean</i> |
| name | optional | Name of the element. | <i>string</i> |
| parentDimension | optional | Optional parent dimension for this dimension (hierarchy). | <i>string</i> |

XML Representation

```
<xs:element name="Dimension" type="typeDimension" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="name" type="xs:string" use="optional"/>
  <xs:attribute name="editable" type="xs:boolean" use="optional" default="true"/>
  <xs:sequence>
    <xs:element name="Variable" type="typeVariable" minOccurs="0" maxOccurs="unbounded">
      <xs:sequence>
        <xs:element name="ValueSource" type="typeValueSource"/>
      </xs:sequence>
    </xs:element>
    <xs:element name="Constraint" type="typeConstraint" minOccurs="0" maxOccurs="unbounded">
      <xs:sequence>
        <xs:element name="Boundary" type="typeConstraintBoundary">
        </xs:element>
        <xs:element name="Function" type="rules:typeExpression" minOccurs="0"/>
        <xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0"/>
      </xs:sequence>
      <xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
        </xs:element>
        <xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
      </xs:sequence>
    </xs:element>
    <xs:element name="Member" type="typeDimensionMember" minOccurs="0" maxOccurs="unbounded">
      <xs:element name="Property" type="typeProperty" minOccurs="0" maxOccurs="unbounded">
        </xs:element>
    </xs:sequence>
    <xs:attribute name="parentDimension" type="xs:string" use="optional"/>
    <xs:attribute name="description" type="xs:string" use="optional"/>
    <xs:attribute name="hasPriority" type="xs:boolean" use="optional" default="false"/>
  </xs:element>
```

Parent Elements

PredictiveApplication

Child Elements

Constraint, Member, Property, Variable

Variable Element: List of Variables defined for this Dimension.

Table 29. Attributes for Variable

| Attribute | Use | Description | Valid Values |
|------------------------|-----------------|--|--------------|
| alwaysVisible | optional | Indicates if this variable should always be visible in the Prioritize/Optimize step. | boolean |
| dataType | required | Data type of this variable. | string |
| description | optional | Optional variable description. | string |
| editable | optional | Flag controlling editability in non-administrator interfaces. | boolean |
| inherited | optional | Indicates whether this variable can be inherited by child dimension members. | boolean |
| isFromTemplate | optional | Internal use only. | boolean |
| name | optional | Name of the element. | string |
| optimizationInputItem | optional | Indicates if this variable is to be controlled in the Prioritize/Optimize step or not. | boolean |
| prompt | optional | When set, this key value controls the text to display when prompting for variable value input. | string |
| simulateAction | optional | If set, this variable will be summarized in the indicated manner during a simulation. | |
| simulateName | optional | When set, this key value controls the text to display when displaying the summarized value of this variable during a simulation. | string |
| simulateNumericDisplay | optional | Optional control of the display of numeric values (Integer, Percentage, or Double) under User Preferences formatting. | |
| tableIndex | optional | Variable index in prioritization table. | int |

XML Representation

```

<xs:element name="Variable" type="typeVariable" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="name" type="xs:string" use="optional"/>
  <xs:attribute name="editable" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="dataType" type="xs:string" use="required"/>
  <xs:attribute name="description" type="xs:string" use="optional"/>
  <xs:attribute name="simulateAction" type="enumVariableValueSummary" use="optional"/>
  <xs:attribute name="simulateName" type="xs:string" use="optional" default="VARIABLE_PROMPT"/>
  <xs:attribute name="simulateNumericDisplay" type="enumNumericDisplay"/>
  <xs:sequence>
    <xs:element name="ValueSource" type="typeValueSource"/>
  </xs:sequence>
<xs:attribute name="tableIndex" type="xs:int" use="optional" default="0"/>

```

```

<xs:attribute name="prompt" type="xs:string" use="optional" default="VARIABLE_PROMPT"/>
<xs:attribute name="optimizationInputItem" type="xs:boolean" use="optional" default="false"/>
<xs:attribute name="inherited" type="xs:boolean" use="optional" default="true"/>
<xs:attribute name="isFromTemplate" type="xs:boolean" use="optional" default="true"/>
<xs:attribute name="alwaysVisible" type="xs:boolean" use="optional" default="false"/>
</xs:element>

```

Parent Elements

Dimension

Child Elements

ValueSource

ValueSource Element: Source of default values for this Variable.

XML Representation

```
<xs:element name="ValueSource" type="typeValueSource"/>
```

Table 30. Extended Types

| Type | Description |
|---------------------|-------------------------|
| ConstantValueSource | A constant value source |

Parent Elements

Variable

Constraint Element: Deprecated. List of Constraints on this Dimension. Define constraints in the Optimization section.

Table 31. Attributes for Constraint

| Attribute | Use | Description | Valid Values |
|--------------|----------|--|----------------|
| description | optional | Optional constraint description. | <i>string</i> |
| dimension | optional | The dimension owns the constraint. If not supplied, the dimension is assumed to be the owner of the Boundary variable. | <i>string</i> |
| editable | optional | Flag controlling editability in non-administrator interfaces. | <i>boolean</i> |
| enabled | optional | Indicates whether this constraint is enabled. | <i>boolean</i> |
| entityScoped | optional | Indicates the scope of this constraint - within an entity or across all entities. | <i>boolean</i> |
| name | optional | Name of the element. | <i>string</i> |

Table 31. Attributes for Constraint (continued)

| Attribute | Use | Description | Valid Values |
|-----------|----------|------------------|---|
| type | required | Constraint type. | max min equal notEqual lessThan lessThanEqual greaterThan greaterThanEqual |

XML Representation

```
<xs:element name="Constraint" type="typeConstraint" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="name" type="xs:string" use="optional"/>
  <xs:attribute name="editable" type="xs:boolean" use="optional" default="true"/>
  <xs:sequence>
    <xs:element name="Boundary" type="typeConstraintBoundary">
    </xs:element>
    <xs:element name="Function" type="rules:typeExpression" minOccurs="0"/>
    <xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0"/>
  </xs:sequence>
  <xs:attribute name="description" type="xs:string" use="optional"/>
  <xs:attribute name="type" type="enumConstraintType" use="required">
    <xs:enumeration value="max"/>
    <xs:enumeration value="min"/>
    <xs:enumeration value="equal"/>
    <xs:enumeration value="notEqual"/>
    <xs:enumeration value="lessThan"/>
    <xs:enumeration value="lessThanEqual"/>
    <xs:enumeration value="greaterThan"/>
    <xs:enumeration value="greaterThanEqual"/>
  </xs:attribute>
  <xs:attribute name="entityScoped" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="enabled" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="dimension" type="xs:string" use="optional"/>
</xs:element>
```

Parent Elements

Dimension

Child Elements

Boundary, ExpressionFormat, ExternalUsage, Function, InteractionPoint

Boundary Element: Constraint boundary.

Table 32. Attributes for Boundary

| Attribute | Use | Description | Valid Values |
|-----------|----------|--|--------------|
| value | required | The value or reference defining this boundary. | string |

XML Representation

```
<xs:element name="Boundary" type="typeConstraintBoundary">
  <xs:attribute name="value" type="xs:string" use="required"/>
</xs:element>
```

Table 33. Extended Types

| Type | Description |
|---------------------------|---|
| ConstantBoundary | A constant Constraint boundary. |
| VariableReferenceBoundary | A variable reference Constraint Boundary. |

Parent Elements

Constraint

Function Element: Constraint function definition (internally evaluated constraints).

XML Representation

```
<xss:element name="Function" type="rules:typeExpression" minOccurs="0"/>
```

Table 34. Extended Types

| Type | Description |
|-----------------------|--------------------------------|
| typeObjectiveFunction | Objective Function definition. |

Parent Elements

Constraint

ExternalUsage Element: Defines how this constraint can be enabled or disabled via an OPL variable (externally evaluated constraints).

Table 35. Attributes for ExternalUsage

| Attribute | Use | Description | Valid Values |
|-----------------|----------|---|------------------------|
| controlVariable | required | The OPL variable. | string |
| disabledValue | optional | The value that indicates this object is disabled (default 0). | string |
| enabledValue | optional | The value that indicates this object is enabled (default 1). | string |
| variableType | optional | The OPL variable type (default int). | int float string |

XML Representation

```
<xss:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
  <xss:attribute name="controlVariable" type="xs:string" use="required"/>
  <xss:attribute name="variableType" type="enumOPLValueType" use="optional" default="int">
    <xss:enumeration value="int"/>
    <xss:enumeration value="float"/>
    <xss:enumeration value="string"/>
  </xss:attribute>
  <xss:attribute name="enabledValue" type="xs:string" use="optional" default="1"/>
  <xss:attribute name="disabledValue" type="xs:string" use="optional" default="0"/>
</xss:element>
```

Parent Elements

Constraint

ExpressionFormat Element: Constraint function format (externally evaluated constraints).

Table 36. Attributes for ExpressionFormat

| Attribute | Use | Description | Valid Values |
|-----------|----------|--|--------------|
| format | required | The format definition for this expression. | string |

XML Representation

```
<xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
  <xs:attribute name="format" type="xs:string" use="required"/>
</xs:element>
```

Parent Elements

Constraint

InteractionPoint Element: For internal use only. Optional Interaction Point name used when differentiating constraint based on interaction points.

XML Representation

```
<xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

Constraint

Member Element: For internal use only. Dimension Member definition.

XML Representation

```
<xs:element name="Member" type="typeDimensionMember" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

Dimension

Property Element: Deprecated as of Decision Management 8.0. Properties defined for all members of this Dimension.

Table 37. Attributes for Property

| Attribute | Use | Description | Valid Values |
|--------------|----------|--|--------------|
| dataType | optional | The type of this property. | string |
| defaultValue | optional | Default value, if not specified, for a dimension member. Optional only when the property type is string. | string |

XML Representation

```
<xs:element name="Property" type="typeProperty" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="dataType" type="xs:string" default="string"/>
  <xs:attribute name="defaultValue" type="xs:string" default="" />
</xs:element>
```

Parent Elements

Dimension

Optimization Element

Definition of the optimization to be applied on execution of this application.

Table 38. Attributes for Optimization

| Attribute | Use | Description | Valid Values |
|--------------------|----------|--|----------------------------|
| algorithm | required | Optimizaton algorithm from list of known algorithms. | Heuristic CPLEX None |
| editable | optional | Flag controlling editability in non-administrator interfaces. | boolean |
| name | optional | Name of the element. | string |
| objectiveValueName | optional | The name used to reference the objective function value from constraints and output attributes. This must be specified if more than one objective function is defined. | string |
| optimizationMode | optional | Whether the objective function should be maximized or minimized. | max min |
| path | optional | Path to the external optimization model file (CPLEX algorithm only). | string |

XML Representation

```

<xs:element name="Optimization" type="typeOptimizationDefinition" minOccurs="0">
  <xs:attribute name="name" type="xs:string" use="optional"/>
  <xs:attribute name="editable" type="xs:boolean" use="optional" default="true"/>
  <xs:sequence>
    <xs:element name="ObjectiveFunction" type="typeObjectiveFunction" maxOccurs="unbounded">
      <xs:sequence>
        <xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
        </xs:element>
        <xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
        </xs:element>
        <xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
      </xs:sequence>
    </xs:element>
    <xs:element name="Constraint" type="typeConstraint" minOccurs="0" maxOccurs="unbounded">
      <xs:sequence>
        <xs:element name="Boundary" type="typeConstraintBoundary">
        </xs:element>
        <xs:element name="Function" type="rules:typeExpression" minOccurs="0"/>
        <xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
        </xs:element>
        <xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
        </xs:element>
        <xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
      </xs:sequence>
    </xs:element>
    <xs:element name="OPLMapping" type="typeOPLMapping" minOccurs="0">
      <xs:sequence>
        <xs:element name="EntityField" type="typeEntityField" minOccurs="1" maxOccurs="unbounded">
        </xs:element>
        <xs:element name="OptimizationOutput" type="typeOptimizationOutput" minOccurs="1" maxOccurs="unbounded">
        </xs:element>
      </xs:sequence>
    </xs:element>
  </xs:sequence>
</xs:element>

```

```

<xs:element name="CPLEXConfiguration" type="typeCPLEXConfiguration" minOccurs="0">
  <xs:sequence>
    <xs:element name="CPLEXSetting" type="typeCPLEXSetting" minOccurs="0" maxOccurs="unbounded">
      </xs:element>
    </xs:sequence>
  </xs:element>
</xs:sequence>
<xs:attribute name="algorithm" type="enumOptimizationAlgorithmType" use="required">
  <xs:enumeration value="Heuristic"/>
  <xs:enumeration value="CPLEX"/>
  <xs:enumeration value="None"/>
</xs:attribute>
<xs:attribute name="optimizationMode" type="enumOptimizationMode" use="optional" default="max">
  <xs:enumeration value="max"/>
  <xs:enumeration value="min"/>
</xs:attribute>
<xs:attribute name="path" type="xs:string" use="optional"/>
<xs:attribute name="objectiveValueName" type="xs:string" use="optional"/>
</xs:element>

```

Parent Elements

PredictiveApplication

Child Elements

CPLEXConfiguration, Constraint, OPLMapping, ObjectiveFunction

ObjectiveFunction Element: Objective Function definitions. If multiple definitions are defined, a unique "Name" attribute value must be specified for each one.

Table 39. Attributes for ObjectiveFunction

| Attribute | Use | Description | Valid Values |
|----------------|----------|---|-----------------------------------|
| description | optional | Optional objective function description. | <i>string</i> |
| enabled | optional | Indication of whether this constraint is enabled for at least one interaction point. | <i>boolean</i> |
| functionType | optional | Whether the objective function value can be precomputed for each entity, or can only be calculated after optimization has occurred. | linear nonLinear |
| simulateAction | optional | How the objective value should be summarized when the function is linear. | |

XML Representation

```

<xs:element name="ObjectiveFunction" type="typeObjectiveFunction" maxOccurs="unbounded">
  <xs:sequence>
    <xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
      </xs:element>
    <xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
      </xs:element>
    <xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="description" type="xs:string" use="optional"/>
  <xs:attribute name="enabled" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="functionType" type="enumObjectiveFunctionType" use="optional" default="linear">
    <xs:enumeration value="linear"/>
    <xs:enumeration value="nonLinear"/>
  </xs:attribute>
  <xs:attribute name="simulateAction" type="enumVariableValueSummary" use="optional" default="sum"/>
</xs:element>

```

Parent Elements

Optimization

Child Elements

ExpressionFormat, ExternalUsage, InteractionPoint

ExternalUsage Element: Defines how this objective function can be enabled or disabled via an OPL variable.

Table 40. Attributes for ExternalUsage

| Attribute | Use | Description | Valid Values |
|-----------------|-----------------|---|---|
| controlVariable | required | The OPL variable. | <i>string</i> |
| disabledValue | optional | The value that indicates this object is disabled (default 0). | <i>string</i> |
| enabledValue | optional | The value that indicates this object is enabled (default 1). | <i>string</i> |
| variableType | optional | The OPL variable type (default int). | int float string |

XML Representation

```
<xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
  <xs:attribute name="controlVariable" type="xs:string" use="required"/>
  <xs:attribute name="variableType" type="enumOPLValueType" use="optional" default="int">
    <xs:enumeration value="int"/>
    <xs:enumeration value="float"/>
    <xs:enumeration value="string"/>
  </xs:attribute>
  <xs:attribute name="enabledValue" type="xs:string" use="optional" default="1"/>
  <xs:attribute name="disabledValue" type="xs:string" use="optional" default="0"/>
</xs:element>
```

Parent Elements

ObjectiveFunction

ExpressionFormat Element: Objective function format for externally-defined objective functions.

Table 41. Attributes for ExpressionFormat

| Attribute | Use | Description | Valid Values |
|-----------|-----------------|--|---------------|
| format | required | The format definition for this expression. | <i>string</i> |

XML Representation

```
<xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
  <xs:attribute name="format" type="xs:string" use="required"/>
</xs:element>
```

Parent Elements

ObjectiveFunction

InteractionPoint Element: For internal use only. Optional Interaction Point name used when differentiating the objective function based on interaction points.

XML Representation

```
<xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

ObjectiveFunction

Constraint Element: Constraints associated with this optimization definition, to be applied in the execution and optimization of this application.

Table 42. Attributes for Constraint

| Attribute | Use | Description | Valid Values |
|--------------|----------|--|---|
| description | optional | Optional constraint description. | string |
| dimension | optional | The dimension owns the constraint. If not supplied, the dimension is assumed to be the owner of the Boundary variable. | string |
| editable | optional | Flag controlling editability in non-administrator interfaces. | boolean |
| enabled | optional | Indicates whether this constraint is enabled. | boolean |
| entityScoped | optional | Indicates the scope of this constraint - within an entity or across all entities. | boolean |
| name | optional | Name of the element. | string |
| type | required | Constraint type. | max min equal notEqual lessThan lessThanEqual greaterThan greaterThanEqual |

XML Representation

```
<xs:element name="Constraint" type="typeConstraint" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="name" type="xs:string" use="optional"/>
  <xs:attribute name="editable" type="xs:boolean" use="optional" default="true"/>
  <xs:sequence>
    <xs:element name="Boundary" type="typeConstraintBoundary">
    </xs:element>
    <xs:element name="Function" type="rules:typeExpression" minOccurs="0"/>
    <xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
    </xs:element>
    <xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
    </xs:element>
    <xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="description" type="xs:string" use="optional"/>
  <xs:attribute name="type" type="enumConstraintType" use="required">
    <xs:enumeration value="max"/>
    <xs:enumeration value="min"/>
    <xs:enumeration value="equal"/>
  </xs:attribute>
</xs:element>
```

```

<xs:enumeration value="notEqual"/>
<xs:enumeration value="lessThan"/>
<xs:enumeration value="lessThanEqual"/>
<xs:enumeration value="greaterThan"/>
<xs:enumeration value="greaterThanEqual"/>
</xs:attribute>
<xs:attribute name="entityScoped" type="xs:boolean" use="optional" default="true"/>
<xs:attribute name="enabled" type="xs:boolean" use="optional" default="true"/>
<xs:attribute name="dimension" type="xs:string" use="optional"/>
</xs:element>

```

Parent Elements

Optimization

Child Elements

Boundary, ExpressionFormat, ExternalUsage, Function, InteractionPoint

Boundary Element: Constraint boundary.

Table 43. Attributes for Boundary

| Attribute | Use | Description | Valid Values |
|-----------|-----------------|--|---------------|
| value | required | The value or reference defining this boundary. | <i>string</i> |

XML Representation

```

<xs:element name="Boundary" type="typeConstraintBoundary">
  <xs:attribute name="value" type="xs:string" use="required"/>
</xs:element>

```

Table 44. Extended Types

| Type | Description |
|---------------------------|---|
| ConstantBoundary | A constant Constraint boundary. |
| VariableReferenceBoundary | A variable reference Constraint Boundary. |

Parent Elements

Constraint

Function Element: Constraint function definition (internally evaluated constraints).

XML Representation

```

<xs:element name="Function" type="rules:typeExpression" minOccurs="0"/>

```

Table 45. Extended Types

| Type | Description |
|-----------------------|--------------------------------|
| typeObjectiveFunction | Objective Function definition. |

Parent Elements

Constraint

ExternalUsage Element: Defines how this constraint can be enabled or disabled via an OPL variable (externally evaluated constraints).

Table 46. Attributes for ExternalUsage

| Attribute | Use | Description | Valid Values |
|-----------------|-----------------|---|---|
| controlVariable | required | The OPL variable. | <i>string</i> |
| disabledValue | optional | The value that indicates this object is disabled (default 0). | <i>string</i> |
| enabledValue | optional | The value that indicates this object is enabled (default 1). | <i>string</i> |
| variableType | optional | The OPL variable type (default int). | int float string |

XML Representation

```
<xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
  <xs:attribute name="controlVariable" type="xs:string" use="required"/>
  <xs:attribute name="variableType" type="enumOPLValueType" use="optional" default="int">
    <xs:enumeration value="int"/>
    <xs:enumeration value="float"/>
    <xs:enumeration value="string"/>
  </xs:attribute>
  <xs:attribute name="enabledValue" type="xs:string" use="optional" default="1"/>
  <xs:attribute name="disabledValue" type="xs:string" use="optional" default="0"/>
</xs:element>
```

Parent Elements

Constraint

ExpressionFormat Element: Constraint function format (externally evaluated constraints).

Table 47. Attributes for ExpressionFormat

| Attribute | Use | Description | Valid Values |
|-----------|-----------------|--|---------------|
| format | required | The format definition for this expression. | <i>string</i> |

XML Representation

```
<xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
  <xs:attribute name="format" type="xs:string" use="required"/>
</xs:element>
```

Parent Elements

Constraint

InteractionPoint Element: For internal use only. Optional Interaction Point name used when differentiating constraint based on interaction points.

XML Representation

```
<xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

Constraint

OPLMapping Element: Defines how the OPL inputs and outputs are to be mapped.

Table 48. Attributes for OPLMapping

| Attribute | Use | Description | Valid Values |
|------------------------|-----------------|---|---------------|
| contributionVariable | optional | Deprecated. If supplied, this represents the name of an array variable in the OPL that associates the contribution value of each entity record to the overall objective function. Now replaced by OptimizationOutput element with role of objectiveValue. | <i>string</i> |
| outputDecisionVariable | optional | If supplied, this represents the name of the output decision variable in the OPL that contains the objective value to be returned. This value may exclude other factors used to represent allocation priorities, for example. If this is not supplied, then the raw CPLEX output value is returned. | <i>string</i> |
| tupleSetVariable | required | The name of the tupleset variable in OPL that holds the tuples representing each row of entity data. | <i>string</i> |

XML Representation

```
<xs:element name="OPLMapping" type="typeOPLMapping" minOccurs="0">
  <xs:sequence>
    <xs:element name="EntityField" type="typeEntityField" minOccurs="1" maxOccurs="unbounded">
    </xs:element>
    <xs:element name="OptimizationOutput" type="typeOptimizationOutput" minOccurs="1" maxOccurs="unbounded">
    </xs:element>
  </xs:sequence>
  <xs:attribute name="tupleSetVariable" type="xs:string" use="required"/>
  <xs:attribute name="outputDecisionVariable" type="xs:string" use="optional"/>
  <xs:attribute name="contributionVariable" type="xs:string" use="optional"/>
</xs:element>
```

Parent Elements

Optimization

Child Elements

EntityField, OptimizationOutput

EntityField Element: How input entity data columns map to tuple fields.

Table 49. Attributes for EntityField

| Attribute | Use | Description | Valid Values |
|------------|----------|---|---------------|
| dataReturn | optional | For non-System reference types, specifies which aspect of the data is to be returned. | <i>string</i> |

Table 49. Attributes for EntityField (continued)

| Attribute | Use | Description | Valid Values |
|----------------|----------|---|---|
| name | required | Attribute Name. | string |
| referenceType | required | Reference type. | Variable Objective DimensionMember Attribute System |
| tupleField | required | The OPL field in the tuple that will store the value. | string |
| tupleFieldType | required | The OPL tuple field type. | int float string |

XML Representation

```

<xs:element name="EntityField" type="typeEntityField" minOccurs="1" maxOccurs="unbounded">
  <xs:attribute name="referenceType" type="enumAttributeReferenced" use="required">
    <xs:enumeration value="Variable"/>
    <xs:enumeration value="Objective"/>
    <xs:enumeration value="DimensionMember"/>
    <xs:enumeration value="Attribute"/>
    <xs:enumeration value="System"/>
  </xs:attribute>
  <xs:attribute name="name" type="xs:string" use="required"/>
  <xs:attribute name="dataReturn" type="xs:string" use="optional"/>
  <xs:attribute name="tupleField" type="xs:string" use="required"/>
  <xs:attribute name="tupleFieldType" type="enumOPLValueType" use="required">
    <xs:enumeration value="int"/>
    <xs:enumeration value="float"/>
    <xs:enumeration value="string"/>
  </xs:attribute>
</xs:element>

```

Parent Elements

OPLMapping

OptimizationOutput Element: How optimization output variables are inserted into data columns.

Table 50. Attributes for OptimizationOutput

| Attribute | Use | Description | Valid Values |
|---------------|----------|--|----------------------------------|
| name | required | Attribute Name. The value is ignored if the role is objectiveValue. | string |
| role | optional | The output role. | objectiveValue optimizedValue |
| selectionOnly | optional | If a threshold has been defined for this output and this attribute is set to true, then the corresponding output field will be dropped after the selection threshold has been applied. | boolean |

Table 50. Attributes for OptimizationOutput (continued)

| Attribute | Use | Description | Valid Values |
|----------------|-----------------|---|---|
| thresholdType | optional | The selection boundary type. | equal notEqual lessThan lessThanEqual greaterThan greaterThanEqual |
| thresholdValue | optional | The selection boundary value. | <i>string</i> |
| valueVariable | required | The OPL field in the tuple that will store the value. | <i>string</i> |
| variableType | required | The type of the OPL variable. | int float string |

XML Representation

```
<xs:element name="OptimizationOutput" type="typeOptimizationOutput" minOccurs="1" maxOccurs="unbounded">
  <xs:attribute name="name" type="xs:string" use="required"/>
  <xs:attribute name="valueVariable" type="xs:string" use="required"/>
  <xs:attribute name="role" type="enumOptimizationOutputRole" use="optional" default="optimizedValue">
    <xs:enumeration value="objectiveValue"/>
    <xs:enumeration value="optimizedValue"/>
  </xs:attribute>
  <xs:attribute name="variableType" type="enumOPLValueType" use="required">
    <xs:enumeration value="int"/>
    <xs:enumeration value="float"/>
    <xs:enumeration value="string"/>
  </xs:attribute>
  <xs:attribute name="thresholdType" type="enumSelectionBoundaryType" use="optional">
    <xs:enumeration value="equal"/>
    <xs:enumeration value="notEqual"/>
    <xs:enumeration value="lessThan"/>
    <xs:enumeration value="lessThanEqual"/>
    <xs:enumeration value="greaterThan"/>
    <xs:enumeration value="greaterThanEqual"/>
  </xs:attribute>
  <xs:attribute name="thresholdValue" type="xs:string" use="optional"/>
  <xs:attribute name="selectionOnly" type="xs:boolean" use="optional" default="true"/>
</xs:element>
```

Parent Elements

OPLMapping

CPLEXConfiguration Element: Defines advanced CPLEX configuration settings.

Table 51. Attributes for CPLEXConfiguration

| Attribute | Use | Description | Valid Values |
|-----------------|----------|---|----------------|
| exportModelPath | optional | The location on the IBM SPSS Modeler Server machine to which the prepared OPL model file should be exported. The suffix should be either .lp or .mps. | <i>string</i> |
| isModelExported | optional | Indicates whether the prepared OPL model file should be exported. | <i>boolean</i> |

Table 51. Attributes for CPLEXConfiguration (continued)

| Attribute | Use | Description | Valid Values |
|------------------|----------|--|--------------|
| useCPLEXSettings | optional | Indicates whether the CPLEX settings should be applied to the component. | boolean |

XML Representation

```
<xs:element name="CPLEXConfiguration" type="typeCPLEXConfiguration" minOccurs="0">
  <xs:sequence>
    <xs:element name="CPLEXSetting" type="typeCPLEXSetting" minOccurs="0" maxOccurs="unbounded">
    </xs:element>
  </xs:sequence>
  <xs:attribute name="useCPLEXSettings" type="xs:boolean" use="optional" default="false"/>
  <xs:attribute name="isModelExported" type="xs:boolean" use="optional" default="false"/>
  <xs:attribute name="exportModelPath" type="xs:string" use="optional"/>
</xs:element>
```

Parent Elements

Optimization

Child Elements

CPLEXSetting

CPLEXSetting Element: Defines a specific CPLEX setting.

Table 52. Attributes for CPLEXSetting

| Attribute | Use | Description | Valid Values |
|--------------|----------|---|--------------------------------------|
| settingName | required | The name of the setting (see CPLEX C++ setting value names in CPLEX documentation). | string |
| settingType | required | The type of the OPL setting value. | bool int num long string |
| settingValue | required | The setting value. Note that boolean values are represented using 0 or 1 for false and true respectively. | string |

XML Representation

```
<xs:element name="CPLEXSetting" type="typeCPLEXSetting" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="settingName" type="xs:string" use="required"/>
  <xs:attribute name="settingType" type="enumOPLSettingValueType" use="required">
    <xs:enumeration value="bool"/>
    <xs:enumeration value="int"/>
    <xs:enumeration value="num"/>
    <xs:enumeration value="long"/>
    <xs:enumeration value="string"/>
  </xs:attribute>
  <xs:attribute name="settingValue" type="xs:string" use="required"/>
</xs:element>
```

Parent Elements

CPLEXConfiguration

Deployment Element

Deployment details for this application.

Table 53. Attributes for Deployment

| Attribute | Use | Description | Valid Values |
|-------------------------|----------|--|----------------|
| defaultInteractionPoint | optional | For internal use only. Optional indicator of the Interaction Point that represents the terminal node to be set in the Stream deployment information as the scoring task. | <i>string</i> |
| editable | optional | Flag controlling editability in non-administrator interfaces. | <i>boolean</i> |
| name | optional | Name of the element. | <i>string</i> |

XML Representation

```
<xs:element name="Deployment" type="typeDeployment" minOccurs="0">
  <xs:attribute name="name" type="xs:string" use="optional"/>
  <xs:attribute name="editable" type="xs:boolean" use="optional" default="true"/>
  <xs:sequence>
    <xs:element name="DeployLabel" type="typeLabelDefinition" minOccurs="0" maxOccurs="unbounded">
      </xs:element>
    <xs:element name="OutputAttribute" type="typeOutputAttribute" minOccurs="0" maxOccurs="unbounded">
      </xs:element>
    <xs:element name="InteractionPoint" minOccurs="0" maxOccurs="unbounded">
      </xs:element>
    </xs:sequence>
    <xs:attribute name="defaultInteractionPoint" type="xs:string" use="optional"/>
  </xs:element>
```

Parent Elements

PredictiveApplication

Child Elements

DeployLabel, InteractionPoint, OutputAttribute

DeployLabel Element: List of labels available for the user to select from during deployment.

Table 54. Attributes for DeployLabel

| Attribute | Use | Description | Valid Values |
|--------------|-----------------|---|---------------|
| displayColor | optional | Optional color to use when displaying this label. | <i>string</i> |
| labelId | optional | ID of this label. | <i>string</i> |
| labelName | required | Name of this label. | <i>string</i> |

XML Representation

```
<xs:element name="DeployLabel" type="typeLabelDefinition" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="labelId" type="xs:string" use="optional"/>
  <xs:attribute name="labelName" type="xs:string" use="required"/>
  <xs:attribute name="displayColor" type="xs:string" use="optional"/>
</xs:element>
```

Parent Elements

Deployment

OutputAttribute Element: Default output attributes configured for this application.

Table 55. Attributes for OutputAttribute

| Attribute | Use | Description | Valid Values |
|---------------|----------|--|---|
| name | required | Attribute Name. | string |
| parent | optional | Specifies the output hierarchy for display purposes. | string |
| referenceType | required | Reference type. | Variable Objective DimensionMember Attribute System |
| returnValue | required | Return Value. | string |

XML Representation

```
<xs:element name="OutputAttribute" type="typeOutputAttribute" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="referenceType" type="enumAttributeReferenced" use="required">
    <xs:enumeration value="Variable"/>
    <xs:enumeration value="Objective"/>
    <xs:enumeration value="DimensionMember"/>
    <xs:enumeration value="Attribute"/>
    <xs:enumeration value="System"/>
  </xs:attribute>
  <xs:attribute name="name" type="xs:string" use="required"/>
  <xs:attribute name="returnValue" type="xs:string" use="required"/>
  <xs:attribute name="parent" type="xs:string" use="optional"/>
</xs:element>
```

Parent Elements

Deployment

InteractionPoint Element: For internal use only. List of defined Interaction Points for the application.

Table 56. Attributes for InteractionPoint

| Attribute | Use | Description | Valid Values |
|-----------|----------|---|--------------|
| isEnabled | optional | Control of the enabled/disabled check box for this Interaction Point. | boolean |

XML Representation

```
<xs:element name="InteractionPoint" minOccurs="0" maxOccurs="unbounded">
  <xs:attribute name="isEnabled" type="xs:boolean" use="optional" default="true"/>
</xs:element>
```

Parent Elements

Deployment

CurrentStateReport Element

For internal use only. The optional report to use for summarizing the current state of the application.

XML Representation

```
<xss:element name="CurrentStateReport" type="typeCurrentStateReportItem" minOccurs="0"/>
```

Parent Elements

PredictiveApplication

Report Element

For internal use only. Reports available in this application.

XML Representation

```
<xss:element name="Report" type="typeReportItem" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

PredictiveApplication

Tasks Element

For internal use only. Information on long-running task requests.

XML Representation

```
<xss:element name="Tasks" type="typeTaskInformation" minOccurs="0"/>
```

Parent Elements

PredictiveApplication

UnusedResource Element

The unused elements (Dimensions, Constraints, etc.) which are omitted deselecting the elements in the Project Configuration dialog.

XML Representation

```
<xss:element name="UnusedResource" type="typeUnusedResource" minOccurs="0"/>
```

Parent Elements

PredictiveApplication

StreamSettings Element

Settings to apply to the underlying IBM SPSS Modeler stream.

XML Representation

```
<xss:element name="StreamSettings" type="typeStreamSettings" minOccurs="0"/>
```

Parent Elements

PredictiveApplication

Extended Types

Extended types extend elements in an XML document by adding attributes and child elements. To use an extended type in an XML document, you specify the extended type with the xsi:type attribute for the element. Then you can use the attributes and elements defined by the extended type.

ConstantBoundary Type

A constant Constraint boundary.

Table 57. Attributes for ConstantBoundary

| Attribute | Use | Description | Valid Values |
|-----------|----------|--|---------------|
| value | required | The value or reference defining this boundary. | <i>string</i> |

XML Representation

```
<xs:complexType name="ConstantBoundary">
</xs:complexType>
```

Extends

Boundary

Related Types

ConstantBoundary, VariableReferenceBoundary

ConstantValueSource Type

A constant value source

XML Representation

```
<xs:complexType name="ConstantValueSource">
  <xs:sequence>
    <xs:element name="Value" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

Extends

ValueSource

Child Elements

Value

Related Types

ConstantValueSource

Value Element

Constant value, multiple values get multiple elements and are not delimited.

XML Representation

```
<xs:element name="Value" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
```

PrioritizationOptimization Type

The Prioritization form of optimization.

Table 58. Attributes for PrioritizationOptimization

| Attribute | Use | Description | Valid Values |
|------------------------|----------|---|--------------|
| enableNumReturnsByIP | optional | Flag controlling the ability to specify the number of return values by Interaction Point. | boolean |
| lockConfigurationByIP | optional | Optional admin lock of the ability to change the Configuration by IP control. | boolean |
| lockNumReturns | optional | Optional admin lock of the 'number of returns' input. | boolean |
| sameConfiguraitonForIP | optional | Indicates whether the same Prioritization configuration is to be applied for all Interaction Points (default is "true") or not ("false"). | boolean |

XML Representation

```
<xs:complexType name="PrioritizationOptimization">
</xs:complexType>
```

Extends

OptimizeMethod

Related Types

PrioritizationOptimization

VariableReferenceBoundary Type

A variable reference Constraint Boundary.

Table 59. Attributes for VariableReferenceBoundary

| Attribute | Use | Description | Valid Values |
|-----------|----------|--|--------------|
| value | required | The value or reference defining this boundary. | string |

XML Representation

```
<xs:complexType name="VariableReferenceBoundary">
</xs:complexType>
```

Extends

Boundary

Related Types

ConstantBoundary, VariableReferenceBoundary

typeDecisionHierarchyDefineStep Type

The decision hierarchy definition step configuration. AggregationRuleSection and PredictiveModelSection may not both be enabled when using more than 2 dimensions.

Table 60. Attributes for typeDecisionHierarchyDefineStep

| Attribute | Use | Description | Valid Values |
|-------------------------|----------|--|----------------|
| enableInteractionPoints | optional | Logical switch controlling whether Interaction Points are presented to the user or not. | <i>boolean</i> |
| enableSimulation | optional | Deprecated as of Decision Management 8.0. Controls presentation of the Define-style Simulation action. | <i>boolean</i> |
| enableTest | optional | Deprecated as of Decision Management 8.0. Controls presentation of the Test action. | <i>boolean</i> |
| stepCompleted | optional | Indicates whether the user has marked this panel as completed or not. | <i>boolean</i> |
| stepHidden | optional | The "hidden" state for this panel. | <i>boolean</i> |
| stepIncluded | optional | The logical "included or not" flag for this panel. | <i>boolean</i> |
| stepLocked | optional | The locked state for this panel. | <i>boolean</i> |

XML Representation

```
<xs:complexType name="typeDecisionHierarchyDefineStep">
  <xs:sequence>
    <xs:element name="DimensionSetting" type="typeDimensionSetting" minOccurs="0" maxOccurs="unbounded">
      <xs:sequence>
        <xs:element name="SelectionSection" type="typeSelectionsSection">
        </xs:element>
        <xs:element name="AggregateRuleSection" type="typeAggregateRuleSection">
        </xs:element>
        <xs:element name="PredictiveModelSection" type="typePredictiveModelSection">
        </xs:element>
        <xs:element name="AllocationRuleSection" type="typeAllocationRuleSection">
        </xs:element>
        <xs:element name="PlanningSection" type="typePlanningSection">
        </xs:element>
      </xs:sequence>
    </xs:element>
  </xs:sequence>
</xs:complexType>
```

Extends

DefineStep

Child Elements

DimensionSetting

Related Types

typeDecisionHierarchyDefineStep, typeModelingDefineStep, typeRulesManagementDefineStep

DimensionSetting Element

Configuration(s) of the dimensions (each level in single element or multiple elements).

Table 61. Attributes for DimensionSetting

| Attribute | Use | Description | Valid Values |
|-------------------|----------|--|--------------|
| enableSubInherit | optional | Indicates whether current dimension setting would inherit by sub dimension in one element. | boolean |
| lockDimensionTree | optional | Indicates whether the dimension tree is locked. | boolean |
| name | optional | Dimension name. | string |

XML Representation

```
<xs:element name="DimensionSetting" type="typeDimensionSetting" minOccurs="0" maxOccurs="unbounded">
  <xs:sequence>
    <xs:element name="SelectionSection" type="typeSelectionsSection">
    </xs:element>
    <xs:element name="AggregateRuleSection" type="typeAggregateRuleSection">
    </xs:element>
    <xs:element name="PredictiveModelSection" type="typePredictiveModelSection">
    </xs:element>
    <xs:element name="AllocationRuleSection" type="typeAllocationRuleSection">
    </xs:element>
    <xs:element name="PlanningSection" type="typePlanningSection">
    </xs:element>
  </xs:sequence>
  <xs:attribute name="name" type="xs:string" use="optional"/>
  <xs:attribute name="enableSubInherit" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="lockDimensionTree" type="xs:boolean" use="optional" default="false"/>
</xs:element>
```

Child Elements

AggregateRuleSection, AllocationRuleSection, PlanningSection, PredictiveModelSection, SelectionSection

SelectionSection Element: Configuration of the Selections section.

Table 62. Attributes for SelectionSection

| Attribute | Use | Description | Valid Values |
|--------------|----------|--|--------------|
| enableModels | optional | Models off/on control. | boolean |
| enabled | required | Logical switch controlling whether this section is enabled or not. | boolean |

XML Representation

```
<xs:element name="SelectionSection" type="typeSelectionsSection">
  <xs:attribute name="enabled" type="xs:boolean" use="required"/>
  <xs:attribute name="enableModels" type="xs:boolean" use="optional" default="true"/>
</xs:element>
```

Parent Elements

DimensionSetting

AggregateRuleSection Element: Configuration of the Aggregate Rule section.

Table 63. Attributes for AggregateRuleSection

| Attribute | Use | Description | Valid Values |
|-------------------------------|-----------------|--|----------------|
| enableCategoriesAndThresholds | optional | Controls the appearance of the threshold or value range segmentation with category assignment. | <i>boolean</i> |
| enableModels | optional | Models off/on control. | <i>boolean</i> |
| enabled | required | Logical switch controlling whether this section is enabled or not. | <i>boolean</i> |

XML Representation

```
<xs:element name="AggregateRuleSection" type="typeAggregateRuleSection">
  <xs:attribute name="enabled" type="xs:boolean" use="required"/>
  <xs:attribute name="enableModels" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="enableCategoriesAndThresholds" type="xs:boolean" use="optional" default="true"/>
</xs:element>
```

Parent Elements

DimensionSetting

PredictiveModelSection Element: Configuration of the Predictive Model section.

Table 64. Attributes for PredictiveModelSection

| Attribute | Use | Description | Valid Values |
|-------------------------------|-----------------|--|----------------|
| enableCategoriesAndThresholds | optional | Controls the appearance of the threshold or value range segmentation with category assignment. | <i>boolean</i> |
| enabled | required | Logical switch controlling whether this section is enabled or not. | <i>boolean</i> |

XML Representation

```
<xs:element name="PredictiveModelSection" type="typePredictiveModelSection">
  <xs:attribute name="enabled" type="xs:boolean" use="required"/>
  <xs:attribute name="enableCategoriesAndThresholds" type="xs:boolean" use="optional" default="true"/>
</xs:element>
```

Parent Elements

DimensionSetting

AllocationRuleSection Element: Configuration of the Allocation Rule section.

Table 65. Attributes for AllocationRuleSection

| Attribute | Use | Description | Valid Values |
|-----------------------------|----------|---|----------------|
| enableFirstRuleHitExecution | optional | Permit user option of halting rule execution on first 'true' encountered. | <i>boolean</i> |
| enableListExecution | optional | Permit user option of running the entire rule set, potentially resulting in multiple 'true' events. | <i>boolean</i> |

Table 65. Attributes for AllocationRuleSection (continued)

| Attribute | Use | Description | Valid Values |
|-----------------------|-----------------|---|--------------|
| enableModels | optional | Models off/on control. | boolean |
| enableRandomExecution | optional | Permit user option of telling the execution code to only choose from the available responses. | boolean |
| enabled | required | Logical switch controlling whether this section is enabled or not. | boolean |

XML Representation

```
<xs:element name="AllocationRuleSection" type="typeAllocationRuleSection">
  <xs:attribute name="enabled" type="xs:boolean" use="required"/>
  <xs:attribute name="enableModels" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="enableFirstRuleHitExecution" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="enableListExecution" type="xs:boolean" use="optional" default="true"/>
  <xs:attribute name="enableRandomExecution" type="xs:boolean" use="optional" default="true"/>
</xs:element>
```

Parent Elements

DimensionSetting

PlanningSection Element: Configuration of the Planning section.

Table 66. Attributes for PlanningSection

| Attribute | Use | Description | Valid Values |
|-------------------------|-----------------|--|--------------|
| enableInteractionPoints | required | Logical switch controlling whether Interaction Points are presented to the user or not. | boolean |
| enableStartEndDates | required | Logical switch controlling whether Start and End date limits are presented to the user or not. | boolean |

XML Representation

```
<xs:element name="PlanningSection" type="typePlanningSection">
  <xs:attribute name="enableInteractionPoints" type="xs:boolean" use="required"/>
  <xs:attribute name="enableStartEndDates" type="xs:boolean" use="required"/>
</xs:element>
```

Parent Elements

DimensionSetting

typeModelingDefineStep Type

The Model definition step configuration.

Table 67. Attributes for typeModelingDefineStep

| Attribute | Use | Description | Valid Values |
|---------------------------|----------|---|--------------|
| enableAssociationModeling | optional | Controls the appearance of the Association Modeling subpanel. | boolean |

Table 67. Attributes for typeModelingDefineStep (continued)

| Attribute | Use | Description | Valid Values |
|---------------------------|----------|--|--------------|
| enableAutoModeling | optional | Controls the appearance of the Auto-Modeling subpanel. | boolean |
| enableClusterModeling | optional | Controls the appearance of the Auto-Cluster Modeling subpanel. | boolean |
| enableInteractionPoints | optional | Logical switch controlling whether Interaction Points are presented to the user or not. | boolean |
| enableInteractiveModeling | optional | Controls the appearance of the Interactive Modeling subpanel. | boolean |
| enableManualCluster | optional | Controls the appearance of the manual cluster section in the Auto-Cluster Modeling subpanel. | boolean |
| enableSimulation | optional | Deprecated as of Decision Management 8.0. Controls presentation of the Define-style Simulation action. | boolean |
| enableTest | optional | Deprecated as of Decision Management 8.0. Controls presentation of the Test action. | boolean |
| stepCompleted | optional | Indicates whether the user has marked this panel as completed or not. | boolean |
| stepHidden | optional | The "hidden" state for this panel. | boolean |
| stepIncluded | optional | The logical "included or not" flag for this panel. | boolean |
| stepLocked | optional | The locked state for this panel. | boolean |

XML Representation

```
<xs:complexType name="typeModelingDefineStep">
  <xs:sequence>
    <xs:element name="clusterResults" type="modelResults:typeClusterResults" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
```

Extends

DefineStep

Child Elements

clusterResults

Related Types

typeDecisionHierarchyDefineStep, typeModelingDefineStep, typeRulesManagementDefineStep

clusterResults Element

Cluster model results.

XML Representation

```
<xss:element name="clusterResults" type="modelResults:typeClusterResults" minOccurs="0"/>
```

typeObjectiveFunction Type

Objective Function definition.

Table 68. Attributes for typeObjectiveFunction

| Attribute | Use | Description | Valid Values |
|----------------|----------|---|---------------------|
| description | optional | Optional objective function description. | string |
| enabled | optional | Indication of whether this constraint is enabled for at least one interaction point. | boolean |
| functionType | optional | Whether the objective function value can be precomputed for each entity, or can only be calculated after optimization has occurred. | linear nonLinear |
| simulateAction | optional | How the objective value should be summarized when the function is linear. | |

XML Representation

```
<xss:complexType name="typeObjectiveFunction" mixed="false">
  <xss:sequence>
    <xss:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
      </xss:element>
    <xss:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
      </xss:element>
    <xss:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
  </xss:sequence>
</xss:complexType>
```

Extends

Function

Child Elements

ExpressionFormat, ExternalUsage, InteractionPoint

Related Types

typeObjectiveFunction

ExternalUsage Element

Defines how this objective function can be enabled or disabled via an OPL variable.

Table 69. Attributes for ExternalUsage

| Attribute | Use | Description | Valid Values |
|-----------------|----------|---|------------------------|
| controlVariable | required | The OPL variable. | string |
| disabledValue | optional | The value that indicates this object is disabled (default 0). | string |
| enabledValue | optional | The value that indicates this object is enabled (default 1). | string |
| variableType | optional | The OPL variable type (default int). | int float string |

XML Representation

```
<xs:element name="ExternalUsage" type="typeExternalUsage" minOccurs="0">
  <xs:attribute name="controlVariable" type="xs:string" use="required"/>
  <xs:attribute name="variableType" type="enumOPLValueType" use="optional" default="int">
    <xs:enumeration value="int"/>
    <xs:enumeration value="float"/>
    <xs:enumeration value="string"/>
  </xs:attribute>
  <xs:attribute name="enabledValue" type="xs:string" use="optional" default="1"/>
  <xs:attribute name="disabledValue" type="xs:string" use="optional" default="0"/>
</xs:element>
```

Parent Elements

ObjectiveFunction

ExpressionFormat Element

Objective function format for externally-defined objective functions.

Table 70. Attributes for ExpressionFormat

| Attribute | Use | Description | Valid Values |
|-----------|----------|--|--------------|
| format | required | The format definition for this expression. | string |

XML Representation

```
<xs:element name="ExpressionFormat" type="typeExpressionFormat" minOccurs="0">
  <xs:attribute name="format" type="xs:string" use="required"/>
</xs:element>
```

Parent Elements

ObjectiveFunction

InteractionPoint Element

For internal use only. Optional Interaction Point name used when differentiating the objective function based on interaction points.

XML Representation

```
<xs:element name="InteractionPoint" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
```

Parent Elements

ObjectiveFunction

typeRulesManagementDefineStep Type

Configuration of the Define tab in the Rules Management application.

Table 71. Attributes for typeRulesManagementDefineStep

| Attribute | Use | Description | Valid Values |
|-------------------------|----------|--|--------------|
| enableInteractionPoints | optional | Logical switch controlling whether Interaction Points are presented to the user or not. | boolean |
| enableSimulation | optional | Deprecated as of Decision Management 8.0. Controls presentation of the Define-style Simulation action. | boolean |
| enableTest | optional | Deprecated as of Decision Management 8.0. Controls presentation of the Test action. | boolean |
| stepCompleted | optional | Indicates whether the user has marked this panel as completed or not. | boolean |
| stepHidden | optional | The "hidden" state for this panel. | boolean |
| stepIncluded | optional | The logical "included or not" flag for this panel. | boolean |
| stepLocked | optional | The locked state for this panel. | boolean |

XML Representation

```
<xs:complexType name="typeRulesManagementDefineStep">
</xs:complexType>
```

Extends

DefineStep

Related Types

typeDecisionHierarchyDefineStep, typeModelingDefineStep, typeRulesManagementDefineStep

Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
1623-14, Shimotsuruma, Yamato-shi
Kanagawa 242-8502 Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who want to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Software Group
ATTN: Licensing
200 W. Madison St.
Chicago, IL; 60606
U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

If you are viewing this information softcopy, the photographs and color illustrations may not appear.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Intel, Intel logo, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo, Celeron, Intel Xeon, Intel SpeedStep, Itanium, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Other product and service names might be trademarks of IBM or other companies.

Index

A

AggregateRuleSection element 45
Allocation element 22
AllocationRuleSection element 46
ApplicationHome element 6
Attributes element 16

B

Boundary element 20, 26, 33

C

clusterResults element 49
CombineStep element 9
ConstantBoundary type 42
ConstantValueSource type 42
Constraint element 19, 25, 32
CPLEXConfiguration element 37
CPLEXSetting element 38
CurrentStateReport element 40

D

DataStep element 6
DefineStep element 8
DeployLabel element 39
Deployment element 39
DeployScoreStep element 10
DerivedVariable element 18
Dimension element 23
DimensionSetting element 45

E

element reference 1
EntityDimension element 15
EntityField element 35
ExpressionFormat element 22, 28, 31, 34, 50
ExternalUsage element 21, 27, 31, 33, 50

F

Function element 21, 27, 33

G

GlobalSelectionStep element 7

I

ImmediateBatchScoring element 11
Inputs element 15
InteractionPoint element 22, 28, 32, 34, 40, 50
InteractiveQuestions element 16

InterfaceControl element 4
InterfaceFeature element 13
InterfacePages element 5

M

Member element 28

V

Value element 42
ValueSource element 18, 25
Variable element 16, 23
VariableExpression element 19
VariableReferenceBoundary type 43

O

ObjectiveFunction element 30
OPLMapping element 34
Optimization element 29
OptimizationOutput element 36
OptimizeMethod element 10
OptimizeStep element 9
OutputAttribute element 40

P

PlanningSection element 47
PredictiveApplication element 1
PredictiveModelSection element 46
PrioritizationOptimization type 43
Property element 28

R

RealTimeScoring element 12
ReferencedDimensionHierarchy element 15
Report element 41
ReportStep element 12

S

ScheduledBatchScoring element 12
Selection element 22
SelectionSection element 45
SpecialVariableReference element 15
StreamSettings element 41

T

Tasks element 41
typeDecisionHierarchyDefineStep type 44
typeModelingDefineStep type 47
typeObjectiveFunction type 49
typeRulesManagementDefineStep type 51

U

UnusedResource element 41

IBM[®]