

Sterling Standards Library

Standards Library Property Files

Version 5.3

Build 5308

Sterling Commerce
An AT&T Company

© Copyright 2009 Sterling Commerce, Inc. All rights reserved.

Contents

Overview	4
ach.properties	5
chips.properties	8
enveloping.properties	10
einvoicing.properties	25
messageentryworkstation.properties	29
restoretablelist.properties	31
restoretablemap.properties	33
translator_swift.properties	34
translator_swift_2002.properties	53
translator_swift_2005.properties	70
translator_swift_2006.properties	89
translator_swift_2007.properties	108
translator_swift_2008.properties	127
translator_swift_mp.properties	146
translator_swift_mp_2002.properties	149
translator_swift_mp_2005.properties	153
translator_swift_mp_2006.properties	157
translator_swift_mp_2007.properties	161
translator_swift_mp_2008.properties	165
translator_swift_mx.properties	169
ui_swift_message_types.properties	171

Overview

Property files contain properties that control the operation of the application. By modifying the settings of these properties, you can customize the application, if necessary, to suit your business needs. Property files are located in the `install_dir/properties` directory and are usually named in the following manner: `filename.properties`. Some files have other suffixes including `.xml`, `.xsl`, `.cfg`, and `.ini`. Substitute the appropriate suffix for properties when needed in the instructions provided.

Caution: Since property files directly affect the operation of the application, please ensure that you fully understand the impact of property file changes. When changing configuration files, be sure that you have a complete backup of your system and have fully tested the changes in a test or development environment before moving the changes into production. For more information about working with any property file or property, please contact Sterling Commerce Customer Support.

Leading or trailing whitespace in property files will be respected by the application. This may cause a problem if the system is not expecting whitespace. When editing property files, be careful to trim leading and trailing whitespace before saving each file.

Overriding or Editing Property File Settings

The application supports the use of a customer override (edit) property file to override default property settings in the property files. The customer override property file is not changed during installation of the application upgrades or patches. To prevent having your customized settings overwritten, use overrides whenever possible rather than editing the property files.

If you have made changes to property files either directly or by editing the associated `.in` files in a previous version, your changes may be overwritten when a patch is applied. To prevent this, create a `customer_overrides.properties` file and reapply your modifications using overrides to the applicable property files in the `customer_overrides.properties` file.

For example, if you want to change the maximum size of interchange for ASC X12 in `enveloping.properties` to 100, you need to add the following line to the `customer_overrides.properties` file (and then this value can be overridden by setting the size directly in the envelope):

```
enveloping.enveloping.X12.MaxInterchangeSize=100
```

In this example, `enveloping` represents the `enveloping.properties` file, `enveloping.X12` represents the ASC X12 standard, and `MaxInterchangeSize` represents the property configuring maximum size allowed for interchanges.

ach.properties

The ach.properties file is used to set record format definitions for ACH deenveloping. These parameters include all default settings for the enveloping user interface.

Set treatRequiredFieldsAsOptional=YES to specify that required fields (required by the ACH standards definition) should be treated as optional. By default, these fields are treated as mandatory.

The field format default is:

```
name,offset,length
```

The date format default is:

```
Date_YYMMDD, Date_MMDD, Date_MMY
```

Configuration Settings

The following table describes properties used to configure the ach.properties file in the application:

Property	Description
deenvelope.ACH.File_Header_Record. field.[field_number]	Sets the File_Header_Record field number specified to a name, offset, length, type, and field requirement. Example deenvelope.ACH.File_Header_Record.field.01=RecordTypeCode,0,1,Fixed=1,M
deenvelope.ACH.template.01.field. [field_number]	Sets the template field number specified to a name, offset, length, type, and field requirement. Example deenvelope.ACH.template.01.field.01=RecordTypeCode,0,1,Fixed=9,M
deenvelope.ACH.[trans_type].file_control_ record	Sets the file_control_record for the specified translation type. Example deenvelope.ACH.ACK.file_control_record=01
deenvelope.ACH.[trans_type].batch_ header_record	Sets the batch_header_record for the specified translation type. Example deenvelope.ACH.ADV.batch_header_record=06
deenvelope.ACH.[trans_type].batch_ control_record	Sets the batch_control_record for the specified translation type. Example deenvelope.ACH.ARC.batch_control_record=11
deenvelope.ACH.[trans_type].entry_detail_ _record	Sets the entry_detail_record for the specified translation type. Example deenvelope.ACH.ATX.entry_detail_record=31
deenvelope.ACH.[trans_type].addenda_ record	Sets the addenda_record for the specified translation type. Example deenvelope.ACH.CBR.addenda_record=37

Property	Description
min_addenda_count.[trans_type]	Sets the minimum addenda record count for the specified translation type. Example <code>min_addenda_count.ACK=0</code>
max_addenda_count.[trans_type]	Sets the maximum addenda record count for the specified translation type. Example <code>max_addenda_count.BOC=1</code>
have_PRI	Defines SEC codes that have an addenda record with PRI. Example <code>have_PRI=CCD,CIE,CTX,DNE,ENR,PPD,TRX,WEB</code>
edirule.TotalAmount	Defines the total amount. Example <code>edirule.TotalAmount=EntryDetailRecord,TotalAmount, //TotalAmount/text(),NumberEquality,*,*,*</code>
edirule.RDFI	Defines the receiving DFI Identification. Example <code>edirule.RDFI=EntryDetailRecord, ReceivingDFIIDentification,/ ReceivingDFIIDentification/text()://CheckDigit /text(),StringEquality,*,*,*</code>
edirule.DFIAccountNum	Defines the DFI account number. Example <code>edirule.DFIAccountNum=EntryDetailRecord, DFIAccountNumber,//DFIAccountNumber/text(), StringEquality,*,*,*</code>
edirule.SettlementDate	Defines the settlement date. Example <code>edirule.SettlementDate=BatchHeaderRecord, SettlementDate,//SettlementDate,JulianYYMMDDEquality ,*,*,*</code>
edirule.CreditDebitFlag	Sets the default credit/debit flag. Example <code>edirule.CreditDebitFlag=EntryDetailRecord, TransactionCode,//CreditDebitFlag/text(),Mapping,X12 ,820,*</code>
edirule.AccountQualifier	Defines the account qualifiers that are allowed. Example <code>edirule.AccountQualifier=EntryDetailRecord, TransactionCode,//AccountNumberQualifier/text(), Mapping,X12,820,*</code>

Property	Description
edirulemapping.CreditDebitFlag.[number]	Defines the default rule mapping for the credit/debit flag. Example edirulemapping.CreditDebitFlag.22=C
edirulemapping.AccountQualifier.[number]	Defines the default rule mapping for the account qualifier. Example edirulemapping.AccountQualifier.53=LN

chips.properties

The chips.properties file is used to set global configuration parameters and allowable values for the CHIPS standard.

Configuration Settings

The following table describes properties used to configure the chips.properties file in the application:

Property	Description
tag.[tag_number]	<p>Defines the allowed CHIPS tags.</p> <p>Examples</p> <p>tag.014=Valid Service Message Retrieval tag.016=Receive Retrieval Response tag.017=Resolver Retrieval Response tag.018=Invalid Enquiry/Retrieval tag.025=Payment Message Stored tag.027=Valid Service Message Response tag.028=Invalid Service Message Response tag.031=Receive</p>
transactioncode.[trans_code_number]	<p>Defines the allowed CHIPS transaction codes.</p> <p>Examples</p> <p>transactioncode.01=Delete transactioncode.02=Payment Preference transactioncode.08=Participant Enquiry transactioncode.10=Payment Message transactioncode.22=Service Message transactioncode.39=Payment Message Retrieval transactioncode.40=Receive Retrieval</p>
responsecode.[response_code_number]	<p>Defines the allowed CHIPS response codes.</p> <p>Examples</p> <p>responsecode.25=Payment Message Response responsecode.27=Service Message Response responsecode.29=Payment Preference Response responsecode.31=Receive Notification</p>
response.[response_number]	<p>Defines the allowed CHIPS responses.</p> <p>Examples</p> <p>response.25025=Payment Message Response response.27027=Valid Service Message Response response.27028=Invalid Service Message Response response.29050=Payment Preference Response response.29051=Invalid Payment Preference Response response.31031=Receive Notification</p>

Property	Description
RESPONSEHEADERFIELDS	<p>Defines fields that must contain a response header.</p> <p>Example</p> <pre>RESPONSEHEADERFIELDS=011 014 016 017 018 025 027 028 031 036 038 039 040 050 051 057 058 068 069 101 102</pre>
[REGULAR EXPRESSIONS]	<p>Regular expressions for parsing a CHIPS message.</p> <p>Example</p> <pre>TRANCODEREGEX=^(\d{2})</pre>

enveloping.properties

The enveloping.properties file is used to set global configuration parameters for enveloping. These parameters include all the default setting for the enveloping user interface.

Note: This file should not be edited. Override property settings, if needed, using the customer_overrides.properties file. For detailed instructions on overriding property file settings, see the documentation for the customer_overrides.properties file.

Configuration Settings

The following table describes properties used to configure the enveloping.properties file in the application:

Property	Description
enveloping.[standard]	<p>Specifies the business process used to apply an envelope to one or more messages and then uses the envelope data to process and translate them.</p> <p>Examples</p> <pre>enveloping.X12=X12EnvelopeUnified enveloping.EDIFACT=EDIFACTEnvelopeUnified enveloping.CII=CIIEnvelope enveloping.TRADACOMS=TRADACOMSEnvelope enveloping.ACH=ACHEnvelope enveloping.VDA=VDAEnvelope enveloping.SWIFT=SWIFTEnvelope enveloping.RND=RNDEnvelope enveloping.CHIPS=CHIPSEnvelope enveloping.FEDWIRE=FedwireEnvelope</pre>
enveloping.inner.[standard]	<p>Defines the inner envelope types for the specified standard that uses generic enveloping.</p> <p>Examples</p> <pre>enveloping.inner.TRADACOMS=MHD MTR enveloping.inner.VDA=VDA enveloping.inner.SWIFT=FIN enveloping.inner.RND=RND enveloping.inner.CHIPS=CHIPS enveloping.inner.FEDWIRE=FEDWIRE</pre>
enveloping.outer.[standard]	<p>Defines the outer envelope types for the specified standard that uses generic enveloping.</p> <p>Examples</p> <pre>enveloping.outer.TRADACOMS=STX END enveloping.outer.SWIFT=SWIFT FIN COPY</pre>

Property	Description
enveloping.envelope_level.[standard]. [envelope_level]	<p>Defines the level of a generic envelope.</p> <p>Examples</p> <pre>enveloping.envelope_level.RND.RND=Interchange enveloping.envelope_level.SWIFT.FIN=Interchange enveloping.envelope_level.TRADACOMS.MHD MTR=Transaction enveloping.envelope_level.TRADACOMS.STX END=Interchange enveloping.envelope_level.VDA.VDA=Interchange enveloping.envelope_level.CHIPS.CHIPS=Interchange enveloping.envelope_level.FEDWIRE.FEDWIRE=Interchange</pre>
enveloping.out_required.[standard]	<p>Defines whether a standard using generic enveloping requires an outer envelope. Valid values are True and False (default).</p> <p>Example</p> <pre>enveloping.outer_required.TRADACOMS=TRUE</pre>
deenveloping.support_swift_096	<p>Specifies whether FIN Copy is supported for deenveloping. Valid values are True (default) and False.</p>
enveloping.outbound_pd_values. [standard]	<p>Specifies outbound envelope values to put into process data before the translation map is invoked, so that the values are available for validation during translation.</p> <p>Example</p> <pre>enveloping.outbound_pd_values.SWIFT=SenderID,ReceiverID,ValidationFlag</pre>
enveloping.verify_addresses_while_deenveloping.[standard]_INBOUND	<p>For standards that use generic enveloping, indicates that the Generic Deenvelope service should verify addresses in process data prior to running the deenvelope map. Valid values are False (default) and True.</p> <p>Note: Currently SWIFT Deenveloping map is the only map that may use this function, but the functionality is disabled by default.</p> <p>Example</p> <pre>enveloping.verify_addresses_while_deenveloping.SWIFT_FIN_INBOUND=TRUE</pre>
enveloping.ack_processing_map. [standard]	<p>Defines the map that is executed after deenveloping, if it is determined that a message is an acknowledgement.</p> <p>Example</p> <pre>enveloping.ack_processing_map.SWIFT=SWIFT_FIN_ACK</pre>
enveloping.ack_generation_map. [standard]	<p>Defines the map to use when generating an acknowledgement.</p> <p>Example</p> <pre>enveloping.ack_generation_map.SWIFT=SWIFT_FIN_UAK</pre>
enveloping.inbound_filter_parameters. [standard]	<p>Specifies additional parameters to be used in the envelope to match, as part of the inbound envelope filter.</p> <p>Note: No parameters are currently used by default.</p> <p>Example</p> <pre>enveloping.inbound_filter_parameters.SWIFT=ValidationFlag</pre>

Property	Description
enveloping.inbound_post_filter_parameters.[standard]	<p>Specifies additional parameters to be used in the envelope to match after the envelope filter is applied.</p> <p>Note: This property is used for backward compatibility when a new matching parameter is added, when envelopes exists that do not use the parameter.</p> <p>Example</p> <pre>enveloping.inbound_post_filter_parameters.SWIFT=ValidationFlag,EnvelopeFormat,\MessageFormat,APCorFIN,ClosedUserGroup,SenderIDType,\ReceiverIDType,MessageCategory</pre>
enveloping.inbound_post_filter_parameter_defaults.[standard]	<p>Specifies the default value to use for the envelope if a post-filter parameter is not defined.</p> <p>Example</p> <pre>enveloping.inbound_post_filter_parameter_defaults.SWIFT=*,FIN,\ *,*,*,*,*,Message</pre>
enveloping.correl_override_default.[standard]	<p>Defines whether a standard allows wildcard overrides on outbound envelopes. Valid values are: No, wildcardonly, or all.</p> <p>Note: If an entry does not exist in the properties file for a standard, it is assumed that the value is set to No.</p> <p>Examples</p> <pre>enveloping.correl_override_default.ACH=All enveloping.correl_override_default.CHIPS=No enveloping.correl_override_default.EDIFACT=All enveloping.correl_override_default.FEDWIRE=No enveloping.correl_override_default.RND=No enveloping.correl_override_default.SWIFT=No enveloping.correl_override_default.TRADACOMS=No enveloping.correl_override_default.VDA=No enveloping.correl_override_default.X12=All</pre>
enveloping.genctrlnumname.nameVariations.[standard].inner	<p>Specifies the total number of name variations to attempt when generating the control number name for standards using generic enveloping (that is, the total number of primary names and backup names that are specified in the user interface for the standard).</p> <p>Example</p> <pre>enveloping.genctrlnumname.nameVariations.SWIFT.inner=3</pre>

Property	Description
enveloping.genctrlnumname.component. [standard].inner	<p>Specifies the properties that are used to build the control number name. Allowable properties are: SenderID, SenderIDQual, ReceiverID, and ReceiverIDQual (all four parameters are pulled from the EDI state and work correctly with wildcards), and any envelope parameter.</p> <p>Note: In the enveloping user interface, the variable names must be set as the component name with the variation number appended; prepended by the type of name and an underscore. For example, genctrlnumname_SenderID1).</p> <p>Example</p> <pre>enveloping.genctrlnumname.component.SWIFT.inner=genctrlnumname_SenderID,genctrlnumname_SenderIDQual,genctrlnumname_ReceiverID,genctrlnumname_ReceiverIDQual,genctrlnumname_MessageFormat,genctrlnumname_BusinessArea,genctrlnumname_MessageType,genctrlnumname_ValidationFlag,genctrlnumname_Variant,genctrlnumname_Version</pre>
enveloping.genctrlnumname.appendComponents.[standard].inner	<p>Specifies the subset the components that appear at the end of the generated name (for example, Inbound or Outbound).</p> <p>Note: If a parameter is not specified for this property, the envelope type is appended by default.</p> <p>Example</p> <pre>enveloping.genctrlnumname.appendComponents.SWIFT.inner=genctrlnumname_EnvelopeFormat</pre>
enveloping.genctrlnumname.optionalComponents.[standards].inner	<p>Specifies a comma-separated list of optional components.</p> <p>Example</p> <pre>enveloping.genctrlnumname.optionalComponents.SWIFT.inner=genctrlnumname_SenderID,genctrlnumname_SenderIDQual,genctrlnumname_ReceiverID,genctrlnumname_ReceiverIDQual,genctrlnumname_MessageFormat,genctrlnumname_BusinessArea,genctrlnumname_MessageType,genctrlnumname_ValidationFlag,genctrlnumname_Variant,genctrlnumname_Version,genctrlnumname_EnvelopeFormat</pre>
enveloping.genmapname.namevariations. [standard].inner	<p>Defines dynamically generated names for the pre-enveloping translation map, including a count of the number of variations that the user interface allows.</p> <p>Example</p> <pre>enveloping.genmapname.nameVariations.SWIFT.inner=3 enveloping.genmapname.component.SWIFT.inner=genmapname_SenderID,genmapname_SenderIDQual,genmapname_ReceiverID,genmapname_ReceiverIDQual,genmapname_MessageFormat,genmapname_BusinessArea,genmapname_MessageType,genmapname_ValidationFlag,genmapname_Variant,genmapname_Version</pre>

Property	Description
enveloping.genmapname.component. [standard].inner	<p>Defines dynamically generated names for the pre-enveloping translation map, including a list of components.</p> <p>Example</p> <pre>enveloping.genmapname.nameVariations.SWIFT.inner=3 enveloping.genmapname.component.SWIFT.inner=genmap name_SenderID,genmapname_SenderIDQual,genmapname_R eceiverID,genmapname_ReceiverIDQual,genmapname_Mes sageFormat,genmapname_BusinessArea,genmapname_Mess ageType,genmapname_ValidationFlag,genmapname_Varia nt,genmapname_Version</pre>
enveloping.genmapname. appendComponents.[standard].inner	<p>Defines dynamically generated names for the pre-enveloping translation map, including a list of components that may be appended to build the name.</p> <p>Example</p> <pre>enveloping.genmapname.appendComponents.SWIFT.inner =genmapname_EnvelopeFormat</pre>
enveloping.genmapname. optionalComponents.[standard].inner	<p>Defines dynamically generated names for the pre-enveloping translation map, including a list of optional components that may be used to build the name.</p> <p>Example</p> <pre>enveloping.genmapname.optionalComponents.SWIFT.inn er=genmapname_SenderID,genmapname_SenderIDQual,gen mapname_ReceiverID,genmapname_ReceiverIDQual,genma pname_MessageFormat,genmapname_BusinessArea,genmap name_MessageType,genmapname_ValidationFlag,genmapn ame_Variant,genmapname_Version,genmapname_Envelope Format</pre>
enveloping.genbpname.namevariations. [standard].inner	<p>Defines dynamically generated names for the business process, including a count of the number of variations that the user interface allows.</p> <p>Example</p> <pre>enveloping.genbpname.nameVariations.SWIFT.inner=3</pre>
enveloping.genbpname.component. [standard].inner	<p>Defines dynamically generated names for the business process, including a list of components.</p> <p>Example</p> <pre>enveloping.genbpname.component.SWIFT.inner=genbpna me_SenderID,genbpname_SenderIDQual,genbpname_Recei verID,genbpname_ReceiverIDQual,genbpname_MessageFo rmat,genbpname_BusinessArea,genbpname_MessageType, genbpname_ValidationFlag,genbpname_Variant,genbpna me_Version</pre>
enveloping.genbpname. appendComponents.[standard].inner	<p>Defines dynamically generated names for the business process, including a list of components that may be appended to build the name.</p> <p>Example</p> <pre>enveloping.genbpname.appendComponents.SWIFT.inner= genbpname_EnvelopeFormat</pre>

Property	Description
enveloping.genbpname.optionalComponents.[standard].inner	<p>Defines dynamically generated names for the business process, including a list of optional components that may be used to build the name.</p> <p>Example</p> <pre>enveloping.genbpname.optionalComponents.SWIFT.inner=genbpname_SenderID,genbpname_SenderIDQual,genbpname_ReceiverID,genbpname_ReceiverIDQual,genbpname_MessageFormat,genbpname_BusinessArea,genbpname_MessageType,genbpname_ValidationFlag,genbpname_Variant,genbpname_Version,genbpname_EnvelopeFormat</pre>
enveloping.generrorbpname.namevariations.[standard].inner	<p>Defines dynamically generated names for the error business process, including a count of the number of variations that the user interface allows.</p> <p>Example</p> <pre>enveloping.generrorbpname.nameVariations.SWIFT.inner=3</pre>
enveloping.generrorbpname.component.[standard].inner	<p>Defines dynamically generated names for the error business process, including a list of components.</p> <p>Example</p> <pre>enveloping.generrorbpname.component.SWIFT.inner=generrorbpname_SenderID,generrorbpname_SenderIDQual,generrorbpname_ReceiverID,generrorbpname_ReceiverIDQual,generrorbpname_MessageFormat,generrorbpname_BusinessArea,generrorbpname_MessageType,generrorbpname_ValidationFlag,generrorbpname_Variant,generrorbpname_Version</pre>
enveloping.generrorbpname.appendComponents.[standard].inner	<p>Defines dynamically generated names for the error business process, including a list of components that may be appended to build the name.</p> <p>Example</p> <pre>enveloping.generrorbpname.appendComponents.SWIFT.inner=generrorbpname_EnvelopeFormat</pre>
enveloping.generrorbpname.optionalComponents.[standard].inner	<p>Defines dynamically generated names for the error business process, including a list of optional components that may be used to build the name.</p> <p>Example</p> <pre>enveloping.generrorbpname.optionalComponents.SWIFT.inner=generrorbpname_SenderID,generrorbpname_SenderIDQual,generrorbpname_ReceiverID,generrorbpname_ReceiverIDQual,generrorbpname_MessageFormat,generrorbpname_BusinessArea,generrorbpname_MessageType,generrorbpname_ValidationFlag,generrorbpname_Variant,generrorbpname_Version,generrorbpname_EnvelopeFormat</pre>

Property	Description
enveloping.do.whitespace_processing. [SWIFT]	<p>Flag indicating if whitespace between EDI segments should be removed for a specified standard. Valid values are: True and False.</p> <p>Examples</p> <pre>enveloping.do.edi_whitespace_processing.SWIFT=FALSE enveloping.do.edi_whitespace_processing.TRADACOMS=TRUE enveloping.do.edi_whitespace_processing.VDA=FALSE enveloping.do.edi_whitespace_processing.RND=FALSE</pre>
deenveloping.[standard]. ErrorOn[ack]ReconcileFailure	<p>Flag indicating whether or not to error the Deenveloping service when acknowledgement reconciliation fails for a specified standard.</p> <p>Examples</p> <pre>deenveloping.X12.ErrorOn997ReconcileFailure=FALSE deenveloping.EDIFACT.ErrorOnCONTRLReconcileFailure=FALSE deenveloping.ACH.ErrorOnACKReconcileFailure=FALSE deenveloping.ErrorOnACKReconcileFailure=FALSE</pre>
enveloping.encode_by_outer_envelope. standards	<p>Indicates which standards use the outer envelope for EDI encoding (for batching purposes).</p> <p>Note: If a standard is added to this property, it must also be added to the use_new_key_convention property. The property value is a comma-separated list of standard names. Each standard in the list should also have a set of envelopes (by which to group) defined. If a document has the first type of group_by_envelope defined, it will be grouped based on that envelope. Otherwise, the second type of envelope will be checked, and so on.</p> <p>Examples</p> <pre>enveloping.encode_by_outer_envelope.standards=ACH, EDIFACT, X12</pre>
enveloping.group_by_envelope	<p>Indicates which envelope should be used to group documents for batching purposes.</p> <p>Note: If a document has the first type of group_by_envelope defined, it will be grouped based on that envelope. Otherwise, the second type of envelope will be checked, and so on.</p> <p>Examples</p> <pre>enveloping.group_by_envelope.ACH.1=ACH BATCH enveloping.group_by_envelope.X12.1=GS GE enveloping.group_by_envelope.EDIFACT.1=UNG UNE Syntax 4</pre>

Property	Description
enveloping.use_new_key_convention. standards	<p>Specifies a list of standards for which the multi-group key convention should be used (for example, DOC/GROUP-1_DOC1 instead of DOC/DOC-1). Standards in this list use the new key convention even if encoding by outer envelope is disabled for the enveloping.encode_by_outer_envelope.standards parameter.</p> <p>Example</p> <pre>enveloping.use_new_key_convention.standards=ACH, EDIFACT, X12</pre>
enveloping.[standard]. MaxInterchangeSize	<p>Globally configures a size limit for transactions for the specified standard. This limit can be overridden by setting the maximum size directly in the envelope.</p> <p>Note: To set the size globally, remove the # before the standard for which you want to set the size, and set the maximum size after the equal sign.</p> <p>Example</p> <pre># enveloping.X12.MaxInterchangeSize=0 # enveloping.VDA.MaxInterchangeSize=0 # enveloping.EDIFACT.MaxInterchangeSize=0 # enveloping.TRADACOMS.MaxInterchangeSize=0</pre>
enveloping.[standard].[transaction]. MaxInterchangeSize	<p>Globally configures a size limit for interchanges for the specified standard. This limit can be overridden by setting the maximum size directly in the envelope.</p> <p>Note: To set the size globally, remove the # before the standard/transaction for which you want to set the size, and set the maximum size after the equals sign.</p> <p>Examples</p> <pre># enveloping.X12.810.MaxInterchangeSize=0 # enveloping.X12.850.MaxInterchangeSize=0 # enveloping.EDIFACT.ORDERS.MaxInterchangeSize=0 # enveloping.TRADACOMS.INVOICES.MaxInterchangeSize=0</pre>
enveloping.interchange_override_ correlations.[standard]	<p>List of correlations that override interchange envelope properties.</p> <p>Note: Documents must have the same values for all of these correlations to be placed in the same interchange. Always include EnvelopingInterchangeID in this list. If the standard allows for control number overrides, Out_InterchangeControlNumber should also be in this list.</p> <p>Example</p> <pre>enveloping.interchange_override_correlations.ACH=E nvelopingInterchangeID,Out_DestinationIdentificati on,\Out_OriginIdentification,Out_DestinationName,O ut_OriginName,Out_ReferenceCode,Out_InterchangeCon trolNumber</pre>

Property	Description
enveloping.group_override_correlations. [standard]	<p>List of correlations that override group envelope properties.</p> <p>Note: Documents must have the same values for all of these correlations to be placed in the same group. Always include EnvelopingGroupID in this list. If the standard allows for control number overrides, Out_GroupControlNumber should also be in this list.</p> <p>Example</p> <pre>enveloping.group_override_correlations.ACH=EnvelopingGroupOrder,\Out_RDFI,Out_ODFI,Out_CompanyID,Out_DFIAccountNumber,Out_CompanyEntryDescription,\Out_CompanyName,Out_CompanyDescriptiveDate,Out_CompanyDiscretionaryData,\Out_DiscretionaryData,Out_TransactionCode,Out_IdentificationNumber,\Out_ReceivingCompanyIDNumber,Out_ForeignExchangeReference,Out_ISODestinationCountryCode,\Out_ISOOriginatingCurrencyCode,Out_ISODestinationCurrencyCode,Out_ACHOperatorData,\Out_RoutingNumberOfACHOperator,Out_ServiceClassCode,Out_EffectiveEntryDate,\Out_OriginatorStatusCode,Out_MessageAuthenticationCode,Out_ForeignExchangeIndicator,\Out_ForeignExchangeReferenceIndicator</pre>
enveloping.group_dependency_values. [standard].1	<p>List of parameter names that must be the same in a particular envelope for the documents to be grouped together. This is used, for example, when the group envelope uses values from the transaction envelope when building the output document.</p> <p>Note: The format is envelope type, parameter name, override correlation name (optional).</p> <p>Example</p> <pre>enveloping.group_dependency_values.EDIFACT.1=UNH UNT Syntax 4,MessageType,Out_MessageType</pre>
enveloping.interchange_dependency_values. [standard].1	<p>List of parameter names that must be the same in a particular envelope for the documents to be placed in the same interchange. This is used, for example, when the interchange envelope uses values from the transaction envelope when building the output document.</p> <p>Note: The format is envelope type, parameter name, override correlation name (optional). For EDIFACT, documents cannot be grouped together unless they have the same security settings.</p> <p>Examples</p> <pre>enveloping.interchange_dependency_values.ACH.1=ACH BATCH,BatchingKey enveloping.interchange_dependency_values.EDIFACT.1 =UNG UNE Syntax 4,SecureGroupOutbound,Out_SecureGroupOutbound</pre>
enveloping.docRepair.[standard]	<p>Flag indicating whether document repair is enabled. Valid values are: True or False.</p> <p>Note: Only supported for SWIFT standard.</p> <p>Example</p> <pre>enveloping.docRepair.SWIFT=true</pre>

Property	Description
enveloping.docRepair.[standard].EDIT.mailto	<p>Specifies an e-mail address to which errors that occur on editing documents (during document repair) should be mailed.</p> <p>Note: Only supported for SWIFT standard.</p> <p>Example</p> <pre>enveloping.docRepair.SWIFT.EDIT.mailTo=&SI_ADMIN_MAIL_ADDR</pre>
enveloping.docRepair.[standard].RESEND.mailto	<p>Specifies an mail address to which errors that occur on resending documents (during document repair) should be mailed.</p> <p>Note: Only supported for SWIFT standard.</p> <p>Example</p> <pre>enveloping.docRepair.SWIFT.RESEND.mailTo=&SI_ADMIN_MAIL_ADDR</pre>
enveloping.SWIFT.nextversion	<p>For SWIFT only, specifies the next version for the patch/release.</p> <p>Example</p> <pre>enveloping.SWIFT.nextVersion=2006</pre>
enveloping.SWIFT.nextversionStart	<p>For SWIFT only, specifies the date (YYYYMMDD format) when the next version starts.</p> <p>Example</p> <pre>enveloping.SWIFT.nextVersionStart=20061118</pre>
enveloping.SWIFT.currentversion	<p>For SWIFT only, specifies the current version for the patch/release.</p> <p>Example</p> <pre>enveloping.SWIFT.currentVersion=2005</pre>
enveloping.global.ui.maxControlNumberSize	<p>Defines the default maximum control number size in the enveloping user interface.</p> <p>Example</p> <pre>enveloping.global.ui.maxControlNumberSize=16</pre>
enveloping.maxTransactionControlNumberSize.[standard]	<p>Defines the maximum size for transaction control numbers for the specified standard.</p> <p>Example</p> <pre>enveloping.maxTransactionControlNumberSize.SWIFT=9999999999999999</pre>
enveloping.maxInterchangeControlNumberSize.[standard]	<p>Defines the maximum size for interchange-level control numbers for the specified standard.</p> <p>Example</p> <pre>enveloping.maxInterchangeControlNumberSize.SWIFT=9999999999999999</pre>
deenveloping.interchangetypes	<p>Specifies the number of interchange types for deenveloping.</p> <p>Example</p> <pre>deenveloping.interchangetypes=13</pre>
deenveloping.interchange.[standard]	<p>Specifies the deenveloping interchanges for the indicated standard.</p> <p>Example</p> <pre>deenveloping.interchange.X12=x-application/edi-x12;0;ISA;IEA;variable;3;105;0;X12DeenvelopeUnified</pre>

Property	Description
deenveloping.[standard]	<p>Defines the deenveloping service used to deenvelope interchanges for the specified standard.</p> <p>Example</p> <pre>deenveloping.CII=CIIDeenvelope</pre>
unpersistedStorageType	<p>Storage type for unpersisted documents. Valid values are: FS (file system) or DB (database).</p> <p>Example</p> <pre>unpersistedStorageType=FS</pre>
deenveloping.[standard].SequenceCheckRetryTimeout	<p>Default period of time for retrying sequence checking.</p> <p>Example</p> <pre>deenveloping.X12.SequenceCheckRetryTimeout=30</pre>
checkForBINSegment	<p>For ASC X12 only, flag specifying whether to check for the BIN segment. Valid values are: True (default) and False.</p> <p>Example</p> <pre>checkForBINSegment=true</pre>
replaceXMLChars	<p>For EDIFACT only, indicates the default characters to be replaced in XML.</p> <p>Example</p> <pre>replaceXMLChars=,!@#\$\$%^&*+=(){}[]<>/;:</pre>
trimEnvelopeParms	<p>For JDBC Oracle databases only, whether to trim envelope parameters. Valid values are: True (default) and False.</p> <p>Example</p> <pre>trimEnvelopeParms=true</pre>
deenveloping.ACH.IgnorePadRecords	<p>For ACH only, whether to ignore record padding. Valid values are: True and False (default).</p> <p>Example</p> <pre>deenveloping.ACH.IgnorePadRecords=false</pre>
usePostProcessorBPLinks	<p>Whether to use post processor business process links. Valid values are: True and False (default).</p> <p>Example</p> <pre>usePostProcessorBPLinks=false</pre>

Property	Description
EDIENVELOPE_MAX_LOCK_TIME	<p>Specifies the maximum amount of time that the EDI Enveloping service will hold a lock on an enveloping process. This parameter enables you to fine tune your EDI processing. You can set this parameter in <code>envelope.properties.in</code>, and then use the same parameter here to override the properties file setting where necessary. The default value is 86400 seconds.</p> <p>This parameter is used in Deferred mode to avoid situations where enveloping service releases the lock before it is done processing a message-possibly due to slow response from the database. If there are concurrent EDI enveloping business processes running, an EDI Enveloping service in another business process could possibly retrieve the same message from the database and process it, which would result in duplicate outbound messages.</p> <p>Example EDIENVELOPE_MAX_LOCK_TIME=86400</p>
EDIENVELOPE_LOCK_WAIT_TIME	<p>Specifies the maximum amount of time that the EDI Enveloping service will wait for a lock before returning an error and reporting failure to obtain the lock. The service would use this parameter value when another EDI Enveloping business process has the lock, which causes this EDI Enveloping service instance to have to wait for the lock. The default value is 86400 seconds. This parameter is used in Deferred mode only.</p> <p>Example EDIENVELOPE_LOCK_WAIT_TIME=86000</p>
ensureCorrelationUpdate	<p>For database iSeries only, specifies whether to update correlations. Valid values are: Yes (default) and No.</p> <p>Example ensureCorrelationUpdate=yes</p>
TRACKING_LEVEL	<p>Specifies the level of tracking that is retrieved for the envelope when it is processed. Full specifies to track all events for the envelope.</p>
requiredCorrelation.[correlation_number]	<p>Defines the correlations required by the generic enveloping, deferred enveloping, and acknowledgement generation functionality.</p> <p>Examples requiredCorrelation.1=InterchangeAuthInfo requiredCorrelation.2=InterchangeAuthInfoQualifier requiredCorrelation.3=InterchangeReceiverIDQualifier requiredCorrelation.4=InterchangeSecAuthInfo</p>
defaultHIPAAValidationLevel	<p>Defines the default HIPAA validation level.</p> <p>Example defaultHIPAAValidationLevel=4</p>

Property	Description
deenveloping.harness_hook_pd_values_interchange.[standard]	<p>For generic standards, specifies which values in process data (after the break map is executed) are passed on to the deenvelope data harness hook.</p> <p>Example</p> <pre>deenveloping.harness_hook_pd_values_interchange.RND=MessageType,MessageVersion,\InterchangeControlNumber,InterchangeDateTime,SenderID,ReceiverID,InternalTransmitterCode,\InternalReceiverCode,SenderName,ReceiverName,TestFlag,HeaderMessageType,Standard</pre>
encrypt.parameters	<p>List of envelope parameter names whose corresponding values # should be encrypted when stored in the database (for example, for password or encryption key values).</p> <p>Example</p> <pre>encrypt.parameters=KeyPart1,KeyPart2</pre>
deenveloping.MAX_INTERCHANGE_COUNT	<p>Specifies the maximum number of non-EDI Interchanges that can be processed in a file. The default is 500 and an error is generated when this value is exceeded.</p> <p>Example</p> <pre>deenveloping.MAX_INTERCHANGE_COUNT=500</pre>
document.lifespan	<p>Specifies the document lifespan (in minutes) when an acknowledgement for an EDI Outbound document is expected. The outbound workflow is not archived/purged until the value specified if the corresponding acknowledgement is not received. The default value corresponds to 30 days.</p> <p>Example</p> <pre>document.lifespan=30</pre>
runErrorBPonEnvelopeNotFound	<p>Specifies whether the Interchange Error business process will run when UNH envelope is not found. The default is false (the business process will not run).</p> <p>Example</p> <pre>runErrorBPonEnvelopeNotFound=false</pre>

Property	Description
enveloping.X12.MaxDocsPer Interchange	<p>This property is commented out by default (not used). If you use ASC X12 enveloping and remove the # from the property, and specify a value greater than zero, it allows you to specify the Maximum number of documents per interchange. If you do not specify a value or if you specify zero, the system will not check for maximum documents per interchange. If you specify a value greater than zero, only that number of documents (or less) will include in an interchange.</p> <p>This parameter can work in conjunction with the Limit Interchange Size parameter to limit the number of documents per interchange and also limit the size of the interchange. This may result in less than the maximum number of documents depending upon the size limit you impose.</p> <p>Note: Note that anything specified in the envelope definition will override the global value specified in the enveloping.properties file. Additionally, any correlation overrides will override the value specified in the envelope definition and the enveloping.properties file.</p>
enveloping.EDIFACT.MaxDocsPer Interchange	<p>This property is commented out by default (not used). If you use EDIFACT enveloping and remove the # from the property, and specify a value greater than zero, it allows you to specify the Maximum number of documents per interchange. If you do not specify a value or if you specify zero, the system will not check for maximum documents per interchange. If you specify a value greater than zero, only that number of documents (or less) will include in an interchange.</p> <p>This parameter can work in conjunction with the Limit Interchange Size parameter to limit the number of documents per interchange and also limit the size of the interchange. This may result in less than the maximum number of documents depending upon the size limit you impose.</p> <p>Note: Note that anything specified in the envelope definition will override the global value specified in the enveloping.properties file. Additionally, any correlation overrides will override the value specified in the envelope definition and the enveloping.properties file.</p>

Property	Description
enveloping.VDA.MaxDocsPer Interchange	<p>This property is commented out by default (not used). If you use VDA enveloping and remove the # from the property, and specify a value greater than zero, it allows you to specify the Maximum number of documents per interchange. If you do not specify a value or if you specify zero, the system will not check for maximum documents per interchange. If you specify a value greater than zero, only that number of documents (or less) will include in an interchange.</p> <p>This parameter can work in conjunction with the Limit Interchange Size parameter to limit the number of documents per interchange and also limit the size of the interchange. This may result in less than the maximum number of documents depending upon the size limit you impose.</p> <p>Note: Note that anything specified in the envelope definition will override the global value specified in the enveloping.properties file. Additionally, any correlation overrides will override the value specified in the envelope definition and the enveloping.properties file.</p>
enveloping.TRADACOMS.MaxDocsPer Interchange	<p>This property is commented out by default (not used). If you use TRADACOMS enveloping and remove the # from the property, and specify a value greater than zero, it allows you to specify the Maximum number of documents per interchange. If you do not specify a value or if you specify zero, the system will not check for maximum documents per interchange. If you specify a value greater than zero, only that number of documents (or less) will include in an interchange.</p> <p>This parameter can work in conjunction with the Limit Interchange Size parameter to limit the number of documents per interchange and also limit the size of the interchange. This may result in less than the maximum number of documents depending upon the size limit you impose.</p> <p>Note: Note that anything specified in the envelope definition will override the global value specified in the enveloping.properties file. Additionally, any correlation overrides will override the value specified in the envelope definition and the enveloping.properties file.</p>

einvoicing.properties

The `einvoicing.properties` file is used to set global configuration parameters for the application. These parameters include all the default settings for the Integrated Archive user interface as well as default settings for the e-Invoice services.

Note: This file should not be edited. Override property settings, if needed, using the `customer_overrides.properties` file. For detailed instructions on overriding property file settings, see the documentation for the `customer_overrides.properties` file.

Configuration Settings

The following table describes properties used to configure the `einvoicing.properties` file in the application:

Property	Description
ExternalArchive_BP_Name	<p>Specifies name of the business process used to process external archive files by the application services.</p> <p>Example <code>ExternalArchive_BP_Name=eInvoiceExternalArchive</code></p>
Admin_Email_Address	<p>Defines the administrative E-mail address used by the application services to send notifications.</p> <p>Example <code>Admin_Email_Address=&SI_ADMIN_MAIL_ADDR</code></p>
trustweaver.sig.1	<p>Defines the TrustWeaver electronic signature.</p> <p>Note: If you modify this value, a Signature Mismatch Error will be posted by the TrustWeaver Request Service.</p> <p>Example <code>trustweaver.sig.1=r00ABXQABkRFU2VkZXVYAAJbQqzzF/gG CFTgAgAAeHAAAAIbuyt6ZsEgUZzcgARamF2YS5sYW5nLkludG VnZXIS4qCk94GHOATAAUkABXZhbHVleHIAEGphdmEubGFuZy50 dW1iZXKGrJUdC5TgiwIAAHwAAAAZXVxAH4AAQAAAAi07plz6e jUQA==</code></p>
unitSizeKB	<p>Defines the unit count that is sent to TrustWeaver. The size of the documents (in KB) that are sent to Trustweaver is divided by this value to determine the count.</p> <p>Note: This value is not editable by the users and is verified by the signature set in <code>trustweaver.sig.1</code>. If either of these values are modified by a user, a Signature Mismatch Error will be posted by the TrustWeaver Request Service.</p> <p>Example <code>unitSizeKB=0</code></p>
Archive_Recovery_Folder	<p>Defines the folder in which recovery files from the integrated Archive will be located.</p> <p>Example <code>Archive_Recovery_Folder=&INSTALL_DIR;/data/einvoic e</code></p>

Property	Description
IntegratedArchive.searchresult.pagesize	<p>Specifies how many search results will be displayed per page in the Integrated Archive. The default is 10.</p> <p>Example</p> <pre>IntegratedArchive.searchresult.pagesize=10</pre>
Integratedarchive.reporting.supportedcountrycodes	<p>Indicates the codes for each country in which validations are reported in the Integrated Archive. Country codes are separated by semi-colons in the list.</p> <p>Note: These are the country codes for which the VAT identifier are displayed in the Integrated Archive reports. If the country code is not in this list, then it is considered to be a dummy VAT ID, and is not displayed in the reports.</p> <p>Note:</p> <p>Example</p> <pre>Integratedarchive.reporting.supportedcountrycodes=AT;BE;BG;CY;CZ;DK;EE;FI;FR;DE;EL;HU;IE;IT;LV;LT;LU;MT;NL;PL;PT;RO;SK;SI;ES;SE;GB</pre>
IntegratedArchive.ui.locale.language	<p>Defines the default language used for the Integrated Archive user interface. The default is en (English).</p> <p>Example</p> <pre>IntegratedArchive.ui.locale.language=en</pre>
IntegratedArchive.ui.locale.country	<p>Defines the country code used for the Integrated Archive user interface. The default is us (United States).</p> <p>Example</p> <pre>IntegratedArchive.ui.locale.country=us</pre>
IntegratedArchive.ui.decimalformat.pattern	<p>Defines the default decimal format for the Integrated Archive. The default is #####.00 (or 123456.00).</p> <p>Example</p> <pre>IntegratedArchive.ui.decimalformat.pattern=#####.00</pre>
IntegratedArchive.ui.dateformat.pattern	<p>Specifies the default date format for the Integrated Archive. The default is yyyy-MM-dd (or 2008-04-01 for April 1, 2008).</p> <p>Example</p> <pre>IntegratedArchive.ui.dateformat.pattern=yyyy-MM-dd</pre>
IntegratedArchive.ui.datetimeformat.pattern	<p>Specifies the default date/time format for the Integrated Archive. The default is yyyy-MM-dd hh:mm a (or 2008-04-01 02:04 p for April 1, 2008, 2:04 pm).</p> <p>Example</p> <pre>IntegratedArchive.ui.datetimeformat.pattern=yyyy-MM-dd hh:mm a</pre>
timestamping.countrycodes	<p>Specifies the code for each country for which timestamping is automatically performed. The default is IT (Italy).</p> <p>Example</p> <pre>timestamping.countrycodes = 'IT'</pre>

Property	Description
local.identity	<p>Enables you to specify a default identity to use for creating agreements.</p> <p>Example</p> <pre>local.identity=IDENTITY123</pre>
emailThrottle	<p>Enables you to control the number of e-mail messages sent to a partner or Sterling e-Invoice Gateway administrator. Valid values are true (default - control the number of e-mail messages sent) and False.</p> <p>If a problem is causing repeated failures in the e-Invoice business processes (for example, if there is a missing or bad canonical map or lack of connectivity to the integrated archive), setting this parameter to True ensures that the Sterling e-Invoice Gateway administrator/operator or partner notification contact is not "spammed" with repeated e-mails. Unchecked, the rate of notification e-mails could overwhelm a customer's e-mail system and personal e-mail account. The emailThrottle, emailLimit, and emailTimePeriod parameters work together to check the rate of notification e-mails.</p> <p>Example</p> <pre>emailThrottle=true</pre>
emailLimit	<p>Defines the number email notifications to be sent within the specified time period. If any e-mail notifications were not sent during the specified time period because it would exceed the set limit, a count of how many were skipped will be sent in the next e-mail.</p> <p>Note: If a problem is causing repeated failures in the e-Invoice business processes (for example, if there is a missing or bad canonical map or lack of connectivity to the integrated archive), setting this parameter to a low number so that the Sterling e-Invoice Gateway administrator/operator or partner notification contact is not "spammed" with repeated e-mails. Unchecked, the rate of notification e-mails could overwhelm a customer's e-mail system and personal e-mail account. The emailThrottle, emailLimit, and emailTimePeriod parameters work together to check the rate of notification e-mails.</p> <p>Example</p> <pre>emailLimit=10</pre>

Property	Description
emailTimePeriod	<p>Defines time period (in minutes) in which the number of notification e-mails sent is to be controlled. The e-mail notification limit will be reset after this time period. The time mentioned here is in minutes.</p> <p>Note: If a problem is causing repeated failures in the e-Invoice business processes (for example, if there is a missing or bad canonical map or lack of connectivity to the integrated archive), setting this parameter to a low number so that the Sterling e-Invoice Gateway administrator/operator or partner notification contact is not "spammed" with repeated e-mails. Unchecked, the rate of notification e-mails could overwhelm a customer's e-mail system and personal e-mail account. The emailThrottle, emailLimit, and emailTimePeriod parameters work together to check the rate of notification e-mails.</p> <p>Example emailTimePeriod=1</p>
IntegratedArchive.searchresult.maxnoofinvoices	<p>Determines the number of invoices that can be returned in a search of the Integrated Archive.</p> <p>Example IntegratedArchive.searchresult.maxnoofinvoices=1500</p>

messageentryworkstation.properties

The messageentryworkstation.properties file is used to set global configuration parameters for the Message Entry Workstation.

Configuration Settings

The following table describes properties used to configure the messageentryworkstation.properties file in the application:

Property	Description
MSGTYPE-[type_number]	Specifies the display string for the particular message type. Example MSGTYPE-2=SWIFTMX Cash Reporting
MSGTYPE-[type_number].licenseTag	Specifies the license tag for the particular message type. Example MSGTYPE-2.licenseTag=SWIFTMX
MSGTYPE-[type_number].versions	Specifies standard versions for the particular message type. Format is standard.versions=comma separated version numbers. Example MSGTYPE-2.versions=1.0,3.0,3.1
MSGTYPE-[type_number].[stds_version]	Specifies the filename for the message type and standards version for the particular message type. Format is standard.version=file name. Example MSGTYPE-2.1.0=swift_mx_cr_1.0.xml
enveloping.messageentry	Defines the default message entry envelope used. Example enveloping.messageentry=SWIFTMessageEntryOutbound
messageentry.SWIFT.fireEvent	If set to True, sends out an e-mail notification when an event occurs. An event occurs when the message status changes from the following: <ul style="list-style-type: none">◆ Draft to ReadyToSend◆ ReadyToSend to Rejected If set to False, this parameter turns off event notification. Example messageentry.SWIFT.fireEvent=true
messageentry.SWIFT.READY_TO_SEND.default	The user to which an e-mail should be sent when a message is ready to be sent. Example messageentry.SWIFT.READY_TO_SEND.default=&SI_ADMIN_MAIL_ADDR;

Property	Description
messageentry.SWIFT.REJECTED.default	The user an mail should be sent when a message is rejected. Example <code>messageentry.SWIFT.REJECTED.default=&SI_ADMIN_MAIL_ADDR;</code>

restoretablelist.properties

The restoretablelist.properties file is used to set the history used when a table is restored from an archive.

Configuration Settings

The following table describes properties used to configure the restoretablelist.properties file in the application:

Property	Description
FS_OUTBOUND_HISTY	<p>The columns to use when a table containing outbound messages is restored from archive.</p> <p>Example</p> <pre>FS_OUTBOUND_HISTY=OBJECT_ID TIMESTAMP_RECVD MSG_FORMAT PARTICIPANT_NUM TIMESTAMP_SENT SENT TIMESTAMP_ACKED ACKED MSG_REF FS_MSG_NUM MB_MSG_ID RESENT_COUNT MSG_TYPE ADAPTER_NAME ACKED_MB_MSG_ID WORKFLOW_ID DOC_ID </pre>
FS_INBOUND_HISTY	<p>The columns to use when a table containing inbound messages is restored from archive.</p> <p>Example</p> <pre>FS_INBOUND_HISTY=OBJECT_ID TIMESTAMP_RECVD MSG_TYPE PARTICIPANT_NUM FS_MSG_NUM MB_MSG_ID ADAPTER_NAME TIMESTAMP_ACKED ACKED ACKED_MB_MSG_ID WORKFLOW_ID DOC_ID </pre>
DATA_TABLE	<p>????</p> <p>Example</p>
TRANS_DATA	<p>????</p> <p>Example</p>
DOCUMENT	<p>????</p> <p>Example</p>
DOCUMENT_EXTENSION	<p>????</p> <p>Example</p>
WORKFLOW_CONTEXT	<p>????</p> <p>Example</p>
WF_INST_S	<p>????</p> <p>Example</p>

Property	Description
SI_VERSION	???? Example
CORRELATION_SET	???? Example
EDIINTDOC	???? Example
MSGMDNDUP	???? Example
MSGMDNCORRELATION	???? Example
WEBX_MINED_DATA	???? Example

restoretablemap.properties

The restoretablelist.properties file is used to specify the map used when a table is restored from an archive.

Configuration Settings

The following table describes properties used to configure the restoretablemap.properties file in the application:

Property	Description
FS_OUTBOUND_HISTY	Defines the map used when a table containing outbound messages is restored from archive. Example FS_OUTBOUND_HISTY=FS_OUTBND_RESTORE
FS_INBOUND_HISTY	Defines the map used when a table containing inbound messages is restored from archive. Example FS_INBOUND_HISTY=FS_INBND_RESTORE

translator_swift.properties

The translator_swift.properties file is used to set default global configuration parameters for the SWIFT standard.

The following caveats apply to this properties file:

- ◆ The properties have the following format:
`swiftField.<fieldTag>.<subfield>.<component>.<mt>[ext]`
- ◆ If a field tag has different validation requirements within different sequences of the same message type the following sequence is appended:
`swiftField.<fieldTag>.<subfield>.<component>.<mt>[ext] .<sequence>`
- ◆ If the <mt> component is defined as an asterisk (*), all common group messages apply. For example, n92, n95, n96 where n is a Category 1 through 9.
- ◆ Some field tags allow a valid currency code in addition to a code word validation. The CUR keyword triggers this validation, which checks the external SWIFT_Currencies code list.
- ◆ 16R/16S code word validations are handled internally by the translator through keyfield matching. Therefore, the entries for these field tags are currently not used.

Note: The properties for 16R and 16S are not enough for performing validation. For example, MT307 requires GENL for 16R, Sequence A and LINK for 16R, Subsequence A1. However, these properties do restrict the code words to the specified lists.

To complete the validation the map editor must use keyfield matching and match against a constant (for example, GENL or LINK). If data is not matched, the translator notes a T13 error code.

- ◆ A slash (/) or double slash (//) is always used as the start of a new subfield. Therefore, component and subfield numbers do not exactly match the SWIFT documentation (for example, 41A) when an expanded special function contains subfields or more than one component.
- ◆ Field 22, subfield 2, component 1 is matched with a related field that is dependent on the message type. This validation is handled through the <SB-LC> special function.

Code Word Validations for ISO 15022 Messages

The following caveats apply to this properties file for ISO 15022 messages:

- ◆ For each MT the exceptions list is displayed first (if any exceptions exist).
- ◆ The exceptions list has the following format:
`swiftField.Exceptions.<mt>[ext]`
- ◆ The code word lists are displayed by position and order within the MT.
- ◆ Non-exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext]`
- ◆ Exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext]`

- ◆ Where a subfield greater than two needs to be validated the subfield number is appended:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext].<subfield>`
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
`>`
- ◆ Code words are single-quoted and separated by a comma delimiter.
- ◆ Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present.
- ◆ The <errorCode> will always be the corresponding Kxx code of the field tag.

Special Related Field Tag Properties

Special Related Field Tag properties are used for performing validation when the validation is dependent on a related field. The two cases in which related field processing occurs is for <SB-LC> and for validating an <AMOUNT> where the currency is declared in another field tag.

All related fields must be included with their respective Sequence letters.

Configuration Settings

The following table describes properties used to configure the translator_swift_properties file in the application:

Property	Description
swiftField.[fieldTag].[subfield].[component].[mt]	Defines MT-specific properties. Example <code>swiftField.12.1.1.973='971','972','998':T88</code>
swiftField.[fieldTag].[subfield].[component].[mt]<ext>.[sequence]	Defines MT-specific properties for the specified sequence. Example <code>swiftField.95S.ALTE.D1.SETPRTY.515='ARNU','CCPT','CHTY','CORP','DRLC','FIIN','TXID':NODSS:K95</code>
swiftField.[fieldTag].[qualifier].[mt]<ext>	Defines MT-specific properties. Example <code>swiftField.22H.GALO.308='GAIN','LOSS':K22</code>
swiftField.Exceptions.[mt]<ext>	Defines MT-specific properties for the specified exception. Example <code>swiftField.Exceptions.506=22F.COLA,22H.COLA</code>
mt.smallInputMaximum	Defines MT-specific properties. Example <code>mt.smallInputMaximum=2000</code>
mt.smallOutputMaximum	Defines MT-specific properties. Example <code>mt.smallOutputMaximum=2600</code>

Property	Description
mt.largeInputMaximum	Defines MT-specific properties. Example <code>mt.largeInputMaximum=10000</code>
mt.largeOutputMaximum	Defines MT-specific properties. Example <code>mt.largeOutputMaximum=10600</code>
mt.largeInput	Defines MT-specific properties. Example <code>mt.largeInput=101,102,103,104,106,107,121,206,207,256,300,303,304,306,307,308,320,321,330,340,341,350,360,361,364,365,380,381,405,416,500,501,502,503,504,505,506,507,508,509,510,513,514,515,517,518,519,524,527,528,529,535,536,537,538,540,541,542,543,544,545,546,547,548,549,558,564,565,566,567,568,569,574,575,576,577,578,584,586,587,588,589,700,701,710,711,720,721,760,767,98,198,298,398,498,598,698,798,898,998,9999</code>
mt.largeOutput	Defines MT-specific properties. Example <code>mt.largeOutput=101,102,103,104,106,107,121,206,207,256,300,303,304,306,307,308,320,321,330,340,341,350,360,361,364,365,380,381,405,416,500,501,502,503,504,505,506,507,508,509,510,513,514,515,517,518,519,524,527,528,529,535,536,537,538,540,541,542,543,544,545,546,547,548,549,558,564,565,566,567,568,569,574,575,576,577,578,584,586,587,588,589,700,701,710,711,720,721,760,767,98,198,298,398,498,598,698,798,898,998,9999</code>
mt.rule.32	Defines MT-specific properties. Example <code>mt.rule.32=300,303,304,306,320,330,340,350,360,361,362,364,365,405,582,600,643,645,813</code>
mtFieldTag.F72.other	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.F72.other=192,292,392,492,592,692,792,892,992,395,495,595,695,795,895,995,196,296,396,496,596,696,796,896,996</code>
mtFieldTag.F79.other	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.F79.other=960,964,965,966,967,192,292,392,492,592,692,792,892,992,395,495,595,695,795,895,995,196,296,396,496,596,696,796,896,996,399,499,599,699,799,899,999</code>

Property	Description
mtFieldTag.ERI.F72.narrative	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.ERI.F72.narrative=110,400,410,412,420, 422,430,450,456,516,526,559,577,581,600,601,604, 605,606,607,609,643,644,645,646,700,705,707,710, 720,730,732,734,740,742,747,750,752,754,756,760, 767,768,769,800,802,812,813,820,821,822,823,824, 900,910,935,90,190,290,390,490,590,690,790,890,990 ,91,191,291,391,491,591,691,791,891,991</pre>
mtFieldTag.FLD72	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.FLD72=100,200,201,202,203,204,205,206, 300,303,304,305,306,320,330,340,341,350,360,361, 362,364,365,405</pre>
mtFieldTag.FLD72._STP	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.FLD72._STP=102,103</pre>
mtFieldTag.FLD72._not_STP	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.FLD72._not_STP=102,103</pre>
mtFieldTag.REJTRETN72	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.REJTRETN72=100,102,103,104,107,110,195, 200,201,202,203,204,205,207,295</pre>
mtFieldTag.ERI.F77A	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.ERI.F77A=416,455,456,747,754,810</pre>
mtFieldTag.ERI.F79	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.ERI.F79=582,649,705,707,810,986</pre>
mtFieldTag.REJTRETN79	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.REJTRETN79=195,199,295,299</pre>
mtFieldTag.SB-LC.DATE	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.SB-LC.DATE=360,361,362,364,365</pre>
mtFieldTag.rule.89	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.rule.89=600,601,604,605,606,607,608,609</pre>
mtFieldTag.rule.89.32F	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.rule.89.32F=600,601,604,605,606,607</pre>

Property	Description
mtFieldTag.rule.89.60F	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.60F=608</code>
mtFieldTag.rule.89.60M	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.60M=608</code>
mtFieldTag.rule.89.61	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.61=608</code>
mtFieldTag.rule.89.62F	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62F=608</code>
mtFieldTag.rule.89.62M	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62M=608</code>
mtFieldTag.rule.89.64	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.64=608</code>
mtFieldTag.rule.89.65	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.65=608</code>
mtFieldTag.rule.89.68B.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68B.3.4=609</code>
mtFieldTag.rule.89.68C.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68C.3.4=609</code>
mtFieldTag.specialValidation.T75	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.specialValidation.T75=405,192,292,392,492,592,692,792,892,992,195,295,395,495,595,695,795,895,995,196,296,396,496,596,696,796,896,996</code>
fieldTags.loopRepeat	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.loopRepeat=15A,15B,15C,15D,15E,15F,15G,15H,15I,15J,15K,15L,15M,15N</code>

Property	Description
fieldTags.genericFields	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.genericFields=11A,12A,12B,12C,13A,13B, 13J,13K,17B,19A,19B,20C,20D,22F,22H,24B,25D,36B, 36C,36E,69A,69B,69C,69D,69E,69F,69J,70C,70D,70E, 0F,90A,90B,90E,92A,92B,92C,92D,92E,92F,92J,92K,93A ,93B,93C,93D,94B,94C,94D,94F,94G,95C,95P,95Q,95R, 95S,95T,95U,95V,97A,97B,97C,98A,98B,98C,98D,99A, 99B</pre>
fieldTags.checkCRLFUsage	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFUsage=35B,42A,42D,50D,51A,51D, 52A,52B,52D,53A,53B,53D,54A,54B,54D,55A,55B,55D, 56A,56D,57A,57B,57D,58A,58B,58D,82A,82B,82D,83A, 83D,84A,84B,84D,85A,85B,85D,86A,86B,86D,87A,87B, 87D,88A,88B,88D</pre>
fieldTags.specialExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.specialExceptions=12,12E,12F,14A,14D,14G ,14J,16R,16S,17A,17B,17F,17G,17N,17O,17R,17T,17U, 17V,22,22A,22B,22D,22E,22G,22J,22K,23,23A,23B,23C, 23D,23E,23F,23G,24D,26C,26F,28E,31X,32F,32K,33B, 33G,33K,33S,33T,35A,35H,35N,35S,35U,37K,38B,38E, 38G,38H,38J,39B,39P,40A,40B,40C,40E,40F,41A,41D, 49,60F,61,62F,62M,64,65,68B,68C,71A,77H,94A</pre>
fieldTags.specialExceptions.useSpecificSyntax	<p>Defines MT-specific properties for special cases and exceptions that use a specific syntax.</p> <p>Example</p> <pre>fieldTags.specialExceptions.useSpecificSyntax=50F</pre>
fieldTags.noSlashesAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.noSlashesAllowed=12A,13B,20,20C,20D,21, 21A,21F,21G,21P,21R,94B,95Q,95R,95S,95T,95V</pre>
fieldTags.oneOptionMustBePresent	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.oneOptionMustBePresent=52B,53B,54B,57B, 58B,85B,86B,87B,88B</pre>
fieldTags.checkCRLFPairs	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFPairs=77E</pre>
fieldTags.commonMTExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.commonMTExceptions=77F,77G,77T</pre>

Property	Description
fieldTags.commonMTGenericExceptions	Defines MT-specific properties for special cases and exceptions. Example fieldTags.commonMTGenericExceptions=17B
fieldTags.MT574Exceptions	Defines MT-specific properties for special cases and exceptions. Example fieldTags.MT574Exceptions=22F
fieldTags.CRLFStartsLineAllowed	Defines MT-specific properties for special cases and exceptions. Example fieldTags.CRLFStartsLineAllowed=15A,15B,15C,15D,15E,15F,15G,15H,15I,15J,15K,15L,15M,15N,77E,77T
fieldTags.allBlanksAllowed	Defines MT-specific properties for special cases and exceptions. Example fieldTags.allBlanksAllowed=77E,77T
fieldTags.colonStartsSecondLineAllowed	Defines MT-specific properties for special cases and exceptions. Example fieldTags.colonStartsSecondLineAllowed=77E,77T
fieldTags.PARTYFLDJ.format [format_number]	Defines MT-specific properties for special cases and exceptions. Example fieldTags.PARTYFLDJ.format1=53J,56J,57J,58J,82J,84J,85J,86J,87J,88J
fieldTags.specialValidation	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation=12,31X,35B,82S,68B,68C,38B,50H,42D,50D,50K,52D,53D,54D,55D,56D,57D,58D,59,82D,83D,84D,85D,86D,87D,88D
fieldTags.specialValidation.Errors	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.Errors=T12,T18,T62,T70,T74,T75,T76,T77
fieldTags.specialValidation.T12	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T12=35B
fieldTags.specialValidation.T18	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T18=12
fieldTags.specialValidation.T62	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T62=31X
fieldTags.specialValidation.T70	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T70=82S

Property	Description
fieldTags.specialValidation.T74	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T74=68B,68C
fieldTags.specialValidation.T75	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T75=38B
fieldTags.specialValidation.T76	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T76=50H
fieldTags.specialValidation.T77	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T77=42D,50D,50K,52D,53D,54D,55D,56D,57D,58D,59,82D,83D,84D,85D,86D,87D,88D
fieldTags.regexSun	Defines MT-specific properties for special cases and exceptions. Note: For SUN customers only. Example fieldTags.regexSun=77C,77E
fieldTags.BICPlus.102_not_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.102_not_STP=52A,52C,57A,57C
fieldTags.BICPlus.102_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.102_STP=52A,57A
fieldTags.BICPlus.103_not_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.103_not_STP=52A,52D,56A,56C,56D,57A,57C,57D
fieldTags.BICPlus.103_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.103_STP=52A,56A,57A
fieldTags.relatedFields.[number]	Defines special related field tag properties. Example fieldTags.relatedFields.102=B.32B
fieldTags.relatedFields.Optional.[number]	Defines related fields that do not have to exist. If the field tags do not exist, then a validation error should not be reported at the end of translation when deferred validation entries are processed. Example fieldTags.relatedFields.Optional.206=C.32A

Property	Description
fieldTags.relatedFields.Choice. [message_type].[sequence].[field_tag]	<p>Defines related fields that are part of a choice. If one of the choice fields exists, then the other field tags do not have to exist. Each message type lists the choice options for a particular sequence and field tag.</p> <p>Example</p> <pre>fieldTags.relatedFields.Choice.405.B.32A=B.32A,B.32K</pre>
fieldTags.SB-LC.relatedFields.subfield2	<p>Defines related fields for SB-LC and AMOUNT special functions.</p> <p>Example</p> <pre>fieldTags.SB-LC.relatedFields.subfield2=33G,32B</pre>
fieldTags.[field_tag].relatedFields. [message_type].[sequence].[field]	<p>Defines related fields for SB-LC and AMOUNT special functions.</p> <p>Example</p> <pre>fieldTags.SB-LC.relatedFields.600.A.22=A.33G</pre>
fieldTags.genericCodeWordExceptions	<p>Defines related fields for SB-LC and AMOUNT special functions.</p> <p>Example</p> <pre>fieldTags.genericCodeWordExceptions=69C,69D,92E,93C,98D</pre>
fieldTags.rule.3.100	<p>Defines special rule properties. These are rules that have to be implemented within the translator because they require validations using external code lists.</p> <p>Examples</p> <pre>fieldTags.rule.3.100=32A,72 fieldTags.rule.5.107.B=52A,57A fieldTags.rule.101.303.C=39P fieldTags.rule.257.210=50C</pre>
fieldTags.rule.32.303.D1	<p>Defines special rule 32 properties. These entries are exceptions to the normal C32 processing.</p> <p>Example</p> <pre>fieldTags.rule.32.303.D1=32B,57A,57D,57J</pre>
syntax.[fieldtag][.messageType [extension]]	<p>Defines syntax for a SWIFT Field Tag.</p> <p>If a field tag syntax does not have a message-specific syntax, the message type (and extension) are not appended to the syntax entry.</p> <p>Example</p> <pre>syntax.103.97=3!a</pre>
syntax.genericCodeWord.[field_tag]	<p>Defines special function-related syntaxes.</p> <p>Example</p> <pre>syntax.genericCodeWord.69C=': '4!c'/'[8c] '/'<DATE4>'/'4!c</pre>
syntax.BICPlus	<p>Set this property to "YES" if BIC Plus validation should be performed.</p> <p>Example</p> <pre>syntax.BICPlus=YES</pre>
syntax.NON_GENERIC_FIELD	<p>Defines a syntax for a non-generic field.</p> <p>Example</p> <pre>syntax.NON_GENERIC_FIELD=': '2!n[1a] ':'('.*)'</pre>

Property	Description
syntax.NON_GENERIC_SYSTEM_FIELD	<p>Defines syntax for a non-generic field in a System message (for example. 096, 097).</p> <p>Example</p> <pre>syntax.NON_GENERIC_SYSTEM_FIELD=': '2!n[1c]': ' " (.*)"</pre>
syntax.GENERIC_FIELD	<p>Defines syntax for a generic field.</p> <p>Example</p> <pre>syntax.GENERIC_FIELD=': '2!n1a': '4!c'/'[8c]'/ ' " (.*)"</pre>
syntax.GENERIC_CODE_WORD	<p>Defines syntax for parsing out a qualifier, issuer or DSS, code word, and data content of a generic field. In most cases, the code word will be four characters exactly, but there are a few field tags such as 17B that have one letter code words.</p> <p>Example</p> <pre>syntax.GENERIC_CODE_WORD=': '4!c'/'[8c]'/ '4c" (.*)"</pre>
syntax.HEADER	<p>Defines syntax for a header.</p> <p>Example</p> <pre>syntax.HEADER='{ '3B': ' (".*?") ('-}' ')'}</pre>
syntax.CC	<p>Defines syntax for the special function <CC>.</p> <p>Example</p> <pre>syntax.CC=2!a</pre>
syntax.CUR	<p>Syntax for the special function <CUR>.</p> <p>Example</p> <pre>syntax.CUR=3!a</pre>
syntax.DC_GENERIC	<p>Defines generic syntax for the special function <DC>.</p> <p>Example</p> <pre>syntax.DC_GENERIC=1!a</pre>
syntax.DC_SPECIFIC	<p>Defines specific syntax for the special function <DC>.</p> <p>Example</p> <pre>syntax.DC_SPECIFIC='D' 'C'</pre>
syntax.DM_GENERIC	<p>Defines generic for the special function <DM>.</p> <p>Example</p> <pre>syntax.DM_GENERIC=1!a</pre>
syntax.DM_SPECIFIC	<p>Defines specific syntax for the special function <DM>.</p> <p>Example</p> <pre>syntax.DM_SPECIFIC='D' 'M'</pre>
syntax.DATE1	<p>Defines syntax for the special function <DATE1>.</p> <p>Example</p> <pre>syntax.DATE1=4!n</pre>
syntax.DATE2	<p>Defines syntax for the special function <DATE2>.</p> <p>Example</p> <pre>syntax.DATE2=6!n</pre>

Property	Description
syntax.DATE3	Defines syntax for the special function <DATE3>. Example syntax.DATE3=4!n
syntax.DATE4	Defines syntax for the special function <DATE4>. Example syntax.DATE4=8!n
syntax.YEAR	Defines syntax for the special function <YEAR>. Example syntax.YEAR=4!n
syntax.HHMM	Defines syntax for the special function <HHMM>. Example syntax.HHMM=4!n
syntax.TIME2	Defines syntax for the special function <TIME2>. Example syntax.TIME2=6!n
syntax.OFFSET	Defines syntax for the special function <OFFSET>. Example syntax.OFFSET=4!n
syntax.SWIFTBIC_COPY	Defines syntax for the special function <SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.NONSWIFTBIC_COPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.SWIFTBIC_NONCOPY	Defines syntax for the special function <SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_NONCOPY=6!a2!c[3!c]
syntax.NONSWIFTBIC_NONCOPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_NONCOPY=7!c'1'[3!c]
syntax.MT	Defines syntax for the special function <MT> (message type). Example syntax.MT=3!n
syntax.SUB6_GENERIC	Defines generic syntax for the special function <SUB6>. Example syntax.SUB6_GENERIC=1!a3!c

Property	Description
syntax.SUB6_SPECIFIC	<p>Defines specific syntax for the special function <SUB6>.</p> <p>Example</p> <pre>syntax.SUB6_SPECIFIC=('S'3!n) ('N'3!c) ('F'3!c)</pre>
syntax.SBLC	<p>Defines syntax for the special function <SB-LC>.</p> <p>Example</p> <pre>syntax.SBLC=(4!a2!c)4!n(4!a2!c)</pre>
syntax.INSTR	<p>Defines syntax for the special function <INSTR>.</p> <p>Example</p> <pre>syntax.INSTR=('/'1!c'/'[32x]) ('/'2!c'/'[31x]) ('/'3!c'/'[30x]) ('/'4!c'/'[29x]) ('/'5!c'/'[28x]) ('/'6!c'/'[27x]) ('/'7!c'/'[26x]) ('/'8!c'/'[25x])</pre>
syntax.VARSEQU1_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-1>.</p> <p>Example</p> <pre>syntax.VARSEQU1_GENERIC=34x</pre>
syntax.VARSEQU1_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-1>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU1_SPECIFIC=16x['/'16x]</pre>
syntax.VARSEQU2_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-2>.</p> <p>Example</p> <pre>syntax.VARSEQU2_GENERIC=21x</pre>
syntax.VARSEQU2_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-2>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU2_SPECIFIC=16x['/'4!x]</pre>
syntax.VARSEQU3_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-3>.</p> <p>Example</p> <pre>syntax.VARSEQU3_GENERIC=33x</pre>
syntax.VARSEQU3_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-3>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU3_SPECIFIC=16x['/'16x]</pre>
syntax.VARSEQU4_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-4>.</p> <p>Example</p> <pre>syntax.VARSEQU4_GENERIC=[14x]</pre>
syntax.VARSEQU4_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-4>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU4_SPECIFIC=[4x]['/'8x]</pre>

Property	Description
syntax.ISITC	<p>Defines syntax for the special function <35B/ISITC> that is an ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC='ISIN'1e12!c'CRLF'35x['CRLF'<35B/ISITC/1>]</pre>
syntax.ISITC_NO	<p>Defines syntax for the special function <35B/ISITC> that is a non-ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC_NO=(('/'4!a'/'10x'CRLF') ('/'5!a'/'10x'CRLF')) 35x['CRLF'<35B/ISITC/2>]</pre>
syntax.ISITC1	<p>Defines syntax for the special function <35B/ISITC/1>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC1=35x['CRLF'35x]0-2</pre>
syntax.ISITC2	<p>Defines syntax for the special function <35B/ISITC/2>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC2=35x['CRLF'35x]</pre>
syntax.SIGN_GENERIC	<p>Defines generic syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_GENERIC=1!x 1!y 1!z</pre>
syntax.SIGN_SPECIFIC	<p>Defines specific syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_SPECIFIC='+' '-'</pre>
syntax.IBAN	<p>Defines syntax for the special function <IBAN>.</p> <p>Example</p> <pre>syntax.IBAN=2!A2!n1!B[29B]</pre>
syntax.PARTYFLDJ_GENERIC	<p>Defines generic syntax for <PARTYFLD/J>.</p> <p>Example</p> <pre>syntax.PARTYFLDJ_GENERIC=40x['CRLF'40x]0-4</pre>
syntax.FLD50F_GENERIC	<p>Defines generic syntax for the special function <FLD50F>.</p> <p>Example</p> <pre>syntax.FLD50F_GENERIC=35x</pre>
syntax.FLD50F_SPECIFIC	<p>Defines specific syntax for the special function <FLD50F>.</p> <p>Example</p> <pre>syntax.FLD50F_SPECIFIC=('/'34x) (4!a'/'30x)</pre>
syntax.ERI_CODEWORDS	<p>Defines syntax to validate the ERI code words format.</p> <p>Example</p> <pre>syntax.ERI_CODEWORDS=['/OCMT/'<CUR><NUMBER>15'/' ['/CHGS/'<CUR><NUMBER>15'/']]</pre>

Property	Description
syntax.ERIF61_GENERIC	Defines syntax to validate the generic format of the <ERI_F61> code word. Example syntax.ERIF61_GENERIC=34x
syntax.ERIF61_SPECIFIC	Defines syntax to validate the specific format of the <ERI_F61>code word. Example syntax.ERIF61_SPECIFIC=34x
syntax.ERIFLD72_STRUCTURED_GENERIC	Defines syntax to validate the generic format of the <ERI_FLD72structured> code word. Example syntax.ERIFLD72_STRUCTURED_GENERIC=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5
syntax.ERIFLD72_STRUCTURED_SPECIFIC	Defines syntax to validate the specific format of the <ERI_FLD72structured> code word. Example syntax.ERIFLD72_STRUCTURED_SPECIFIC=210x
syntax.ERIF72_NARRATIVE_GENERIC	Defines syntax to validate the generic format of the <ERI_F72narrative> code word. Example syntax.ERIF72_NARRATIVE_GENERIC=35x['CRLF' 35x] 0-5
syntax.ERIF72_NARRATIVE_SPECIFIC	Defines syntax to validate the specific format of the <ERI_F72narrative> code word. Example syntax.ERIF72_NARRATIVE_SPECIFIC=210x
syntax.ERIF77A_GENERIC	Defines syntax to validate the generic format of the <ERI_F77A> code word. Example syntax.ERIF77A_GENERIC=35x['CRLF' 35x] 0-19
syntax.ERIF77A_SPECIFIC	Defines syntax to validate the specific format of the <ERI_F77A> code word. Example syntax.ERIF77A_SPECIFIC=700x
syntax.ERIF79_GENERIC	Defines syntax to validate the generic format of the <ERI_F79> code word. Example syntax.ERIF79_GENERIC=50x['CRLF' 50x] 0-34
syntax.ERIF79_SPECIFIC	Defines syntax to validate the specific format of the <ERI_F79> code word. Example syntax.ERIF79_SPECIFIC=1750x

Property	Description
syntax.ERIF86_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F86> code word.</p> <p>Example <code>syntax.ERIF86_GENERIC=65x['CRLF' 65x] 0-5</code></p>
syntax.ERIF86_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F86> code word.</p> <p>Example <code>syntax.ERIF86_SPECIFIC=390x</code></p>
syntax.F72_OTHER	<p>Defines syntax to validate field 72 where no special function validation is needed.</p> <p>Example <code>syntax.F72_OTHER=35x['CRLF' 35x] 0-5</code></p>
syntax.F79_OTHER	<p>Defines syntax to validate field 79 where no special function validation is needed.</p> <p>Example <code>syntax.F79_OTHER=50x['CRLF' 50x] 0-34</code></p>
syntax.FLD72	<p>Defines specific syntax for <FLD72>.</p> <p>Example <code>syntax.FLD72=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</code></p>
syntax.FLD79	<p>Defines specific syntax for <FLD79>.</p> <p>Note: Unlike <FLD72>, the specific syntax does not use the special function <INSTR>.</p> <p>Example <code>syntax.FLD79=50x['CRLF' 50x] 0-34</code></p>
syntax.FLD72_NOT_STP	<p>Defines specific syntax for <FLD72_not_STP>.</p> <p>Example <code>syntax.FLD72_NOT_STP=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</code></p>
syntax.FLD72_STP	<p>Defines specific syntax for <FLD72_STP>.</p> <p>Example <code>syntax.FLD72_STP=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</code></p>
syntax.FLD72_STP_INS	<p>Defines specific syntax for the /INS format used by <FLD72_STP>.</p> <p>Example <code>syntax.FLD72_STP_INS=' /INS/' ((<SWIFTBIC>) (<NON-SWIFTBIC>))</code></p>
syntax.REJTRETN72_GENERIC	<p>Defines generic syntax for <RETJT/RETN/72>.</p> <p>Example <code>syntax.REJTRETN72_GENERIC=35x['CRLF' 35x] 0-5</code></p>

Property	Description
syntax.REJTRETN72_SPECIFIC	<p>Defines specific syntax for <RETJT/RETN/72>.</p> <p>Example</p> <pre>syntax.REJTRETN72_SPECIFIC=6!x2!n[1a] ['/' '2c] 'CRLF' (('/' '2!c2!n' '/') ('/' 'X' '1c2!n' '/')) [29x] 'CRLF' 'MREF/' 16x['CRLF' ' 'TREF/' '16x] ['CRLF' ' 'CHGS/' '<CUR><AMOUNT>' 15] ['CRLF' ' 'TEXT/' '29x['CRLF' ' ' '33x] 0-2]</pre>
syntax.REJTRETN79_GENERIC	<p>Defines generic syntax for <RETJT/RETN/79>.</p> <p>Example</p> <pre>syntax.REJTRETN79_GENERIC=50x['CRLF' '50x] 0-34</pre>
syntax.REJTRETN79_SPECIFIC	<p>Defines specific syntax for <REJT/RETN/79>.</p> <p>Example</p> <pre>syntax.REJTRETN79_SPECIFIC=6!x2!n[1a] ['/' '2c] 'CRLF' (('/' '2!c2!n' '/') ('/' 'X' '1c2!n' '/')) [44x] 'CRLF' 'MREF/' 16x['CRLF' ' 'TREF/' '16x] ['CRLF' ' 'CHGS/' '<CUR><AMOUNT>' 15] ['CRLF' ' 'TEXT/' '44x['CRLF' ' ' '48x] 0-31]</pre>
syntax.SPECIAL_FUNCTION	<p>Defines a SWIFT syntax that defines a single special function.</p> <p>Note: The [2n] component covers special functions <AMOUNT> and <NUMBER>.</p> <p>Example</p> <pre>syntax.SPECIAL_FUNCTION='<' (50c) '>' [2n]</pre>
syntax.CODEWORD_IRSX	<p>Defines the code word IRSX.</p> <p>Example</p> <pre>syntax.CODEWORD_IRSX=IRSX</pre>
syntax.CODEWORD_AMOUNT_NEGATIVE	<p>Defines the code word Amount is negative.</p> <p>Example</p> <pre>syntax.CODEWORD_AMOUNT_NEGATIVE=N</pre>
syntax.CODEWORD_ABIC	<p>Defines the code word /ABIC/, used for <PARTYFLD/J> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_ABIC=/ABIC/</pre>
syntax.CODEWORD_NAME	<p>Defines the code word /NAME/, used for <PARTYFLD/J> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_NAME=/NAME/</pre>
syntax.CODEWORD_REJT	<p>Defines the code word /REJT/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_REJT=/REJT/</pre>
syntax.CODEWORD_RETN	<p>Defines the code word /RETN/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_RETN=/RETN/</pre>
syntax.CODEWORD_ERI	<p>Defines the code word /OCMT/, used for ERI-related validation.</p> <p>Example</p> <pre>syntax.CODEWORD_ERI=/OCMT/</pre>

Property	Description
syntax.CODEWORD_INS	Defines the code word /INS/, used for <FLD72_STP> validation. Example syntax.CODEWORD_INS=/INS/
syntax.CODEWORD_ASCT	Defines the code word /ASCT/, used for <35B/ISITC/2> validation. Note: The ISITC functions are now DEPRECATED. Example syntax.CODEWORD_ASCT=/ASCT/
syntax.CODEWORD_NETS	Defines the code word /NETS/, used for <PARTYFLD/J> validation. Example syntax.CODEWORD_NETS=/NETS/
syntax.CODEWORD_SGIS	Defines the code word /SGIS/, used for <PARTYFLD/J> validation. Example syntax.CODEWORD_SGIS=/SGIS/
syntax.CODEWORD_CURR	Defines the code word CURR, that activates validation of rule #101. Example syntax.CODEWORD_CURR=CURR
syntax.CODEWORD_MONT	Defines the code word for evaluating special validation T75. Example syntax.CODEWORD_MONT=MONT
syntax.CODEWORD_OTHR	Defines the code word for evaluating special validation T75. Example syntax.CODEWORD_OTHR=OTHR
syntax.CODEWORD_ISIN	Defines the code word for evaluating special validation T12. Code word ISIN is used for <35B/ISITC> validation. Note: The ISITC functions are now DEPRECATED. Example syntax.CODEWORD_ISIN=ISIN
group.PARTYFLDJ.formats	Defines the regex group numbers where code words can be found that require validation. Example group.PARTYFLDJ.formats=4
group.genericCodeWord.[field_tag].groups	Defines the regex group numbers where code words can be found that require validation. Example group.genericCodeWord.69C.groups=1
group.genericCodeWord.[field_tag].[regex_matching_group_number]	Defines the regex group numbers where code words can be found that require validation. Example group.genericCodeWord.69C.1=10

Property	Description
group.genericCodeWord.[field_tag]. [regex_matching_group_number].subfield	Defines the regex group numbers where code words can be found that require validation. Example group.genericCodeWord.69C.10.subfield=3
codeWords.REJTRET72	Defines special function code word lists. Example codeWords.REJTRET72='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'
codeWords.REJTRET79	Defines special function code word lists. Example codeWords.REJTRET79='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'
codeWords.ISITC1	Defines special function code word lists. Example codeWords.ISITC1='AAUS', 'ACED', 'ACIN', 'ACMN', 'ACUS', 'AEUR', 'ALUX', 'AQCK', 'ASED', 'ASVM', 'AVAL', 'AWKP', 'ASICC'
codeWords.ISITC2	Defines special function code word lists. Example codeWords.ISITC2='/ACLT/', '/ADIS/', '/AEXP/', '/AFLT/', '/AIR/', '/AMD/', '/AOC/', '/AOT/', '/APN/', '/ASC/', '/ASP/', '/ASTY/', '/ATBA/', '/ATK/', '/AYLD/', , '/ASCT/'
codeWords.ISITC2.ASCT	Defines special function code word lists. Example codeWords.ISITC2.ASCT='BA', 'CD', 'CMO', 'CORP', 'CP', 'CPP', 'CS', 'FHA', 'FHL', 'FN', 'FOR', 'FUT', 'GN', 'GOVT', 'IET', 'MF', 'MIO', 'MPO', 'MPP', 'MPT', 'MUNI', 'OPT', 'PS', 'RP', 'RVRP', 'SL', 'TD', 'USTB', 'WAR', 'ZOO'
codeWords.PARTYFLDJ	Defines special function code word lists. Example codeWords.PARTYFLDJ='/ABIC/', '/NAME/', '/ACCT/', '/ADD1/', '/ADD2/', '/CITY/', '/USFW/', '/USCH/', , '/GBSC/', '/CLRC/', '/NETS/', '/SSIS/'

Property	Description
codeWords.PARTYFLDJ.format [format_number]	Defines special function code word lists. Example <code>codeWords.PARTYFLDJ.format2='/NETS/'</code>
codeWords.rule.[rule_number]	Defines special function code word lists. Examples <code>codeWords.rule.5='BEID','TRCO','TESP','MCCO', 'SMDP'</code> <code>codeWords.rule.257='BEID','TRCO','TESP','MCCO', 'SMDP'</code>

translator_swift_2002.properties

The translator_swift.properties file is used to set default global configuration parameters for the 2002 version of the SWIFT standard.

The following caveats apply to this properties file:

- ◆ For each MT (message type) the exceptions list is displayed first (if any exceptions exist). The exceptions list has the following format:
`swiftField.Exceptions.<mt>[ext]`
- ◆ The code word lists are displayed by position and order in the MT.
- ◆ Non-exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext]`
- ◆ Exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext]`
- ◆ When a subfield greater than two must be validated, the subfield number is appended as follows:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext].<subfield>`
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
>
- ◆ Code words are single-quoted and separated by a comma delimiter. Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present. The <errorCode> will always be the corresponding Kxx code of the field tag.
- ◆ All related fields must be included with their respective Sequence letters.
- ◆ If the field tags do not exist, a validation error is not reported at the end of translation when deferred validation entries are processed.
- ◆ If one of the choice fields exists for related fields that are part of a choice, the other field tags do not have to exist. Each message type lists the choice options for a particular sequence and field tag.

Configuration Settings

The following table describes properties used to configure the translator_swift_2002.properties file in the application:

Property	Description
mt.smallInputMaximum	Defines MT-specific properties. Example <code>mt.smallInputMaximum=2000</code>
mt.smallOutputMaximum	Defines MT-specific properties. Example <code>mt.smallOutputMaximum=2600</code>

Property	Description
mt.largeInputMaximum	Defines MT-specific properties. Example <code>mt.largeInputMaximum=10000</code>
mt.largeOutputMaximum	Defines MT-specific properties. Example <code>mt.largeOutputMaximum=10600</code>
mt.largeInput	Defines MT-specific properties. Example <code>mt.largeInput=101,102,103,104,106,107,121,206,207,256,300,303,304,306,307,308,320,321,330,340,341,350,360,361,364,365,380,381,405,416,500,501,502,503,504,505,506,507,508,509,510,513,514,515,517,518,519,524,527,528,529,535,536,537,538,540,541,542,543,544,545,546,547,548,549,558,564,565,566,567,568,569,574,575,576,577,578,584,586,587,588,589,700,701,710,711,720,721,760,767,98,198,298,398,498,598,698,798,898,998,9999</code>
mt.largeOutput	Defines MT-specific properties. Example <code>mt.largeOutput=101,102,103,104,106,107,121,206,207,256,300,303,304,306,307,308,320,321,330,340,341,350,360,361,364,365,380,381,405,416,500,501,502,503,504,505,506,507,508,509,510,513,514,515,517,518,519,524,527,528,529,535,536,537,538,540,541,542,543,544,545,546,547,548,549,558,564,565,566,567,568,569,574,575,576,577,578,584,586,587,588,589,700,701,710,711,720,721,760,767,98,198,298,398,498,598,698,798,898,998,9999</code>
mt.rule.32	Defines MT-specific properties. Example <code>mt.rule.32=300,303,304,306,320,330,340,350,360,361,362,364,365,405,582,600,643,645,813</code>
mtFieldTag.F72.other	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.F72.other=192,292,392,492,592,692,792,892,992,395,495,595,695,795,895,995,196,296,396,496,596,696,796,896,996</code>
mtFieldTag.F79.other	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.F79.other=960,964,965,966,967,192,292,392,492,592,692,792,892,992,395,495,595,695,795,895,995,196,296,396,496,596,696,796,896,996,399,499,599,699,799,899,999</code>

Property	Description
mtFieldTag.ERI.F72.narrative	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.ERI.F72.narrative=110,400,410,412,420, 422,430,450,456,516,526,559,577,581,600,601,604, 605,606,607,609,643,644,645,646,700,705,707,710, 720,730,732,734,740,742,747,750,752,754,756,760, 767,768,769,800,802,812,813,820,821,822,823,824, 900,910,935,90,190,290,390,490,590,690,790,890,990 ,91,191,291,391,491,591,691,791,891,991</pre>
mtFieldTag.FLD72	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.FLD72=100,200,201,202,203,204,205,206, 300,303,304,305,306,320,330,340,341,350,360,361, 362,364,365,405</pre>
mtFieldTag.FLD72._STP	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.FLD72._STP=102,103</pre>
mtFieldTag.FLD72._not_STP	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.FLD72._not_STP=102,103</pre>
mtFieldTag.REJTRETN72	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.REJTRETN72=100,102,103,104,107,110,195, 200,201,202,203,204,205,207,295</pre>
mtFieldTag.ERI.F77A	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.ERI.F77A=416,455,456,747,754,810</pre>
mtFieldTag.ERI.F79	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.ERI.F79=582,649,705,707,810,986</pre>
mtFieldTag.REJTRETN79	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.REJTRETN79=195,199,295,299</pre>
mtFieldTag.SB-LC.DATE	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.SB-LC.DATE=360,361,362,364,365</pre>
mtFieldTag.rule.89	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.rule.89=600,601,604,605,606,607,608,609</pre>
mtFieldTag.rule.89.32F	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.rule.89.32F=600,601,604,605,606,607</pre>

Property	Description
mtFieldTag.rule.89.60F	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.60F=608</code>
mtFieldTag.rule.89.60M	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.60M=608</code>
mtFieldTag.rule.89.61	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.61=608</code>
mtFieldTag.rule.89.62F	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62F=608</code>
mtFieldTag.rule.89.62M	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62M=608</code>
mtFieldTag.rule.89.64	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.64=608</code>
mtFieldTag.rule.89.65	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.65=608</code>
mtFieldTag.rule.89.68B.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68B.3.4=609</code>
mtFieldTag.rule.89.68C.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68C.3.4=609</code>
mtFieldTag.specialValidation.T75	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.specialValidation.T75=405,192,292,392,492,592,692,792,892,992,195,295,395,495,595,695,795,895,995,196,296,396,496,596,696,796,896,996</code>
fieldTags.loopRepeat	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.loopRepeat=15A,15B,15C,15D,15E,15F,15G,15H,15I,15J,15K,15L,15M,15N</code>

Property	Description
fieldTags.genericFields	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.genericFields=11A,12A,12B,12C,13A,13B, 13J,13K,17B,19A,19B,20C,20D,22F,22H,24B,25D,36B, 36C,36E,69A,69B,69C,69D,69E,69F,69J,70C,70D,70E, 0F,90A,90B,90E,92A,92B,92C,92D,92E,92F,92J,92K,93A ,93B,93C,93D,94B,94C,94D,94F,94G,95C,95P,95Q,95R, 95S,95T,95U,95V,97A,97B,97C,98A,98B,98C,98D,99A, 99B</pre>
fieldTags.checkCRLFUsage	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFUsage=35B,42A,42D,50D,51A,51D, 52A,52B,52D,53A,53B,53D,54A,54B,54D,55A,55B,55D, 56A,56D,57A,57B,57D,58A,58B,58D,82A,82B,82D,83A, 83D,84A,84B,84D,85A,85B,85D,86A,86B,86D,87A,87B, 87D,88A,88B,88D</pre>
fieldTags.specialExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.specialExceptions=12,12E,12F,14A,14D,14G ,14J,16R,16S,17A,17B,17F,17G,17N,17O,17R,17T,17U, 17V,22,22A,22B,22D,22E,22G,22J,22K,23,23A,23B,23C, 23D,23E,23F,23G,24D,26C,26F,28E,31X,32F,32K,33B, 33G,33K,33S,33T,35A,35H,35N,35S,35U,37K,38B,38E, 38G,38H,38J,39B,39P,40A,40B,40C,40E,40F,41A,41D, 49,60F,61,62F,62M,64,65,68B,68C,71A,77H,94A</pre>
fieldTags.noSlashesAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.noSlashesAllowed=12A,13B,20,20C,20D,21, 21A,21F,21G,21P,21R,94B,95Q,95R,95S,95T,95U</pre>
fieldTags.oneOptionMustBePresent	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.oneOptionMustBePresent=52B,53B,54B,57B, 58B,85B,86B,87B,88B</pre>
fieldTags.checkCRLFPairs	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFPairs=77E</pre>
fieldTags.commonMTExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.commonMTExceptions=77F,77G,77S,77T</pre>
fieldTags.commonMTGenericExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.commonMTGenericExceptions=17B</pre>
fieldTags.MT574Exceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.MT574Exceptions=22F</pre>

Property	Description
fieldTags.CRLFStartsLineAllowed	Defines MT-specific properties for special cases and exceptions. Example fieldTags.CRLFStartsLineAllowed=15A,15B,15C,15D,15E,15F,15G,15H,15I,15J,15K,15L,15M,15N,77E,77S,77T
fieldTags.allBlanksAllowed	Defines MT-specific properties for special cases and exceptions. Example fieldTags.allBlanksAllowed=77E,77S,77T
fieldTags.colonStartsSecondLineAllowed	Defines MT-specific properties for special cases and exceptions. Example fieldTags.colonStartsSecondLineAllowed=77E,77S,77T
fieldTags.PARTYFLDJ.format [format_number]	Defines MT-specific properties for special cases and exceptions. Example fieldTags.PARTYFLDJ.format1=53J,56J,57J,58J,82J,84J,85J,86J,87J,88J
fieldTags.specialValidation	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation=12,31X,35B,82S,68B,68C,38B,50H,42D,50D,50K,52D,53D,54D,55D,56D,57D,58D,59,82D,83D,84D,85D,86D,87D,88D
fieldTags.specialValidation.Errors	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.Errors=T12,T18,T62,T70,T74,T75,T76,T77
fieldTags.specialValidation.T12	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T12=35B
fieldTags.specialValidation.T18	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T18=12
fieldTags.specialValidation.T62	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T62=31X
fieldTags.specialValidation.T70	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T70=82S
fieldTags.specialValidation.T74	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T74=68B,68C
fieldTags.specialValidation.T75	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T75=38B

Property	Description
fieldTags.specialValidation.T76	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T76=50H
fieldTags.specialValidation.T77	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T77=42D, 50D, 50K, 52D, 53D, 54D, 55D, 56D, 57D, 58D, 59, 82D, 83D, 84D, 85D, 86D, 87D, 88D
fieldTags.regexSun	Defines MT-specific properties for special cases and exceptions. Example fieldTags.regexSun=77C, 77E
fieldTags.BICPlus.102_not_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.102_not_STP=52A, 52C, 57A, 57C
fieldTags.BICPlus.102_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.102_STP=52A, 57A
fieldTags.BICPlus.103_not_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.103_not_STP=52A, 52D, 56A, 56C, 56D, 57A, 57C, 57D
fieldTags.BICPlus.103_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.103_STP=52A, 56A, 57A
fieldTags.[field_tag].relatedFields.subfield2	Defines related fields for SB-LC and AMOUNT special functions. Example fieldTags.SB-LC.relatedFields.subfield2=33G, 32B
fieldTags.genericCodeWordExceptions	Defines related fields for SB-LC and AMOUNT special functions. Example fieldTags.genericCodeWordExceptions=69C, 69D, 92E, 93C, 98D
fieldTags.rule.3.100	Defines Rule 3 properties. Example fieldTags.rule.3.100=32A, 72
syntax.[fieldtag].[message_type_extension]	Defines syntax for a SWIFT Field Tag. Format: syntax.<fieldTag>[.messageType[extension]]=<syntax> If a field tag syntax does not have a message-specific syntax, the message type (and extension) are not appended to the syntax entry. Note: Only MT100 is supported for the 2002 standard. Example syntax.20=16x

Property	Description
syntax.BICPlus	Set this property to "YES" if BIC Plus validation should be performed. Example syntax.BICPlus=YES
syntax.NON_GENERIC_FIELD	Defines syntax for a non-generic field. Example syntax.NON_GENERIC_FIELD=': '2!n[1a]': ' ' (.*) "
syntax.NON_GENERIC_SYSTEM_FIELD	Defines syntax for a non-generic field in a System message (for example. 096, 097). Example syntax.NON_GENERIC_SYSTEM_FIELD=': '2!n[1c]': ' ' (.*) "
syntax.GENERIC_FIELD	Defines syntax for a generic field. Example syntax.GENERIC_FIELD=': '2!n1a': '4!c' / ' [8c] ' / ' (.*) "
syntax.GENERIC_CODE_WORD	Defines syntax for parsing out a qualifier, issuer or DSS, code word, and data content of a generic field. In most cases, the code word will be four characters exactly, but there are a few field tags such as 17B that have one letter code words. Example syntax.GENERIC_CODE_WORD=': '4!c' / ' [8c] ' / '4c' (.*) "
syntax.HEADER	Defines syntax for a header. Example syntax.HEADER='{ '3B': ' (" . * ? ") (' - ' } ' ') }
syntax.CC	Defines syntax for the special function <CC>. Example syntax.CC=2!a
syntax.CUR	Syntax for the special function <CUR>. Example syntax.CUR=3!a
syntax.DC_GENERIC	Defines generic syntax for the special function <DC>. Example syntax.DC_GENERIC=1!a
syntax.DC_SPECIFIC	Defines specific syntax for the special function <DC>. Example syntax.DC_SPECIFIC='D' 'C'
syntax.DM_GENERIC	Defines generic for the special function <DM>. Example syntax.DM_GENERIC=1!a
syntax.DM_SPECIFIC	Defines specific syntax for the special function <DM>. Example syntax.DM_SPECIFIC='D' 'M'

Property	Description
syntax.DATE1	Defines syntax for the special function <DATE1>. Example syntax.DATE1=4!n
syntax.DATE2	Defines syntax for the special function <DATE2>. Example syntax.DATE2=6!n
syntax.DATE3	Defines syntax for the special function <DATE3>. Example syntax.DATE3=4!n
syntax.DATE4	Defines syntax for the special function <DATE4>. Example syntax.DATE4=8!n
syntax.YEAR	Defines syntax for the special function <YEAR>. Example syntax.YEAR=4!n
syntax.HHMM	Defines syntax for the special function <HHMM>. Example syntax.HHMM=4!n
syntax.TIME2	Defines syntax for the special function <TIME2>. Example syntax.TIME2=6!n
syntax.OFFSET	Defines syntax for the special function <OFFSET>. Example syntax.OFFSET=4!n
syntax.SWIFTBIC_COPY	Defines syntax for the special function <SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.NONSWIFTBIC_COPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.SWIFTBIC_NONCOPY	Defines syntax for the special function <SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_NONCOPY=6!a2!c[3!c]
syntax.NONSWIFTBIC_NONCOPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_NONCOPY=7!c'1'[3!c]

Property	Description
syntax.MT	Defines syntax for the special function <MT> (message type). Example syntax.MT=3!n
syntax.SUB6_GENERIC	Defines generic syntax for the special function <SUB6>. Example syntax.SUB6_GENERIC=1!a3!c
syntax.SUB6_SPECIFIC	Defines specific syntax for the special function <SUB6>. Example syntax.SUB6_SPECIFIC=('S'3!n) ('N'3!c) ('F'3!c)
syntax.SBLC	Defines syntax for the special function <SB-LC>. Example syntax.SBLC=(4!a2!c)4!n(4!a2!c)
syntax.INSTR	Defines syntax for the special function <INSTR>. Example syntax.INSTR=('/'1!c'/'[32x]) ('/'2!c'/'[31x]) ('/'3!c'/'[30x]) ('/'4!c'/'[29x]) ('/'5!c'/'[28x]) ('/'6!c'/'[27x]) ('/'7!c'/'[26x]) ('/'8!c'/'[25x])
syntax.VARSEQU1_GENERIC	Defines generic syntax for the special function <VAR-SEQU-1>. Example syntax.VARSEQU1_GENERIC=34x
syntax.VARSEQU1_SPECIFIC	Defines specific syntax for the special function <VAR-SEQU-1>. Note: The special function will validate the specific syntax. Example syntax.VARSEQU1_SPECIFIC=16x['/'16x]
syntax.VARSEQU2_GENERIC	Defines generic syntax for the special function <VAR-SEQU-2>. Example syntax.VARSEQU2_GENERIC=21x
syntax.VARSEQU2_SPECIFIC	Defines specific syntax for the special function <VAR-SEQU-2>. Note: The special function will validate the specific syntax. Example syntax.VARSEQU2_SPECIFIC=16x['/'4!x]
syntax.VARSEQU3_GENERIC	Defines generic syntax for the special function <VAR-SEQU-3>. Example syntax.VARSEQU3_GENERIC=33x
syntax.VARSEQU3_SPECIFIC	Defines specific syntax for the special function <VAR-SEQU-3>. Note: The special function will validate the specific syntax. Example syntax.VARSEQU3_SPECIFIC=16x['/'16x]

Property	Description
syntax.VARSEQU4_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-4>.</p> <p>Example</p> <pre>syntax.VARSEQU4_GENERIC=[14x]</pre>
syntax.VARSEQU4_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-4>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU4_SPECIFIC=[4x] ['/' '8x]</pre>
syntax.ISITC	<p>Defines syntax for the special function <35B/ISITC> that is an ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC='ISIN'1e12!c'CRLF'35x['CRLF'<35B/ISITC/1>]</pre>
syntax.ISITC_NO	<p>Defines syntax for the special function <35B/ISITC> that is a non-ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC_NO=(('/' '4!a'/'10x'CRLF') ('/' '5!a'/'10x'CRLF')) 35x['CRLF'<35B/ISITC/2>]</pre>
syntax.ISITC1	<p>Defines syntax for the special function <35B/ISITC/1>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC1=35x['CRLF'35x]0-2</pre>
syntax.ISITC2	<p>Defines syntax for the special function <35B/ISITC/2>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC2=35x['CRLF'35x]</pre>
syntax.SIGN_GENERIC	<p>Defines generic syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_GENERIC=1!x 1!y 1!z</pre>
syntax.SIGN_SPECIFIC	<p>Defines specific syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_SPECIFIC='+' '-'</pre>
syntax.IBAN	<p>Defines syntax for the special function <IBAN>.</p> <p>Example</p> <pre>syntax.IBAN=2!A2!n1!B[29B]</pre>
syntax.PARTYFLDJ_GENERIC	<p>Defines generic syntax for <PARTYFLD/J>.</p> <p>Example</p> <pre>syntax.PARTYFLDJ_GENERIC=40x['CRLF'40x]0-4</pre>

Property	Description
syntax.ERI_CODEWORDS	Defines syntax to validate the ERI code words format. Example syntax.ERI_CODEWORDS=['/OCMT/' <CUR><NUMBER>15' /' ['/CHGS/' <CUR><NUMBER>15' /']]
syntax.ERIF61_GENERIC	Defines syntax to validate the generic format of the <ERI_F61> code word. Example syntax.ERIF61_GENERIC=34x
syntax.ERIF61_SPECIFIC	Defines syntax to validate the specific format of the <ERI_F61>code word. Example syntax.ERIF61_SPECIFIC=34x
syntax.ERIFLD72_STRUCTURED_GENERIC	Defines syntax to validate the generic format of the <ERI_FLD72structured> code word. Example syntax.ERIFLD72_STRUCTURED_GENERIC=<INSTR> ['CRLF' ((<INSTR>) ('/' '33x))] 0-5
syntax.ERIFLD72_STRUCTURED_SPECIFIC	Defines syntax to validate the specific format of the <ERI_FLD72structured> code word. Example syntax.ERIFLD72_STRUCTURED_SPECIFIC=210x
syntax.ERIF72_NARRATIVE_GENERIC	Defines syntax to validate the generic format of the <ERI_F72narrative> code word. Example syntax.ERIF72_NARRATIVE_GENERIC=35x['CRLF' 35x] 0-5
syntax.ERIF72_NARRATIVE_SPECIFIC	Defines syntax to validate the specific format of the <ERI_F72narrative> code word. Example syntax.ERIF72_NARRATIVE_SPECIFIC=210x
syntax.ERIF77A_GENERIC	Defines syntax to validate the generic format of the <ERI_F77A> code word. Example syntax.ERIF77A_GENERIC=35x['CRLF' 35x] 0-19
syntax.ERIF77A_SPECIFIC	Defines syntax to validate the specific format of the <ERI_F77A> code word. Example syntax.ERIF77A_SPECIFIC=700x
syntax.ERIF79_GENERIC	Defines syntax to validate the generic format of the <ERI_F79> code word. Example syntax.ERIF79_GENERIC=50x['CRLF' 50x] 0-34

Property	Description
syntax.ERIF79_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F79> code word.</p> <p>Example syntax.ERIF79_SPECIFIC=1750x</p>
syntax.ERIF86_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F86> code word.</p> <p>Example syntax.ERIF86_GENERIC=65x['CRLF' 65x] 0-5</p>
syntax.ERIF86_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F86> code word.</p> <p>Example syntax.ERIF86_SPECIFIC=390x</p>
syntax.F72_OTHER	<p>Defines syntax to validate field 72 where no special function validation is needed.</p> <p>Example syntax.F72_OTHER=35x['CRLF' 35x] 0-5</p>
syntax.F79_OTHER	<p>Defines syntax to validate field 79 where no special function validation is needed.</p> <p>Example syntax.F79_OTHER=50x['CRLF' 50x] 0-34</p>
syntax.FLD72	<p>Defines specific syntax for <FLD72>.</p> <p>Example syntax.FLD72=<INSTR>['CRLF' ((<INSTR>) ('/' '33x))] 0-5</p>
syntax.FLD79	<p>Defines specific syntax for <FLD79>.</p> <p>Note: Unlike <FLD72>, the specific syntax does not use the special function <INSTR>.</p> <p>Example syntax.FLD79=50x['CRLF' 50x] 0-34</p>
syntax.FLD72_NOT_STP	<p>Defines specific syntax for <FLD72_not_STP>.</p> <p>Example syntax.FLD72_NOT_STP=<INSTR>['CRLF' ((<INSTR>) ('/' '33x))] 0-5</p>
syntax.FLD72_STP	<p>Defines specific syntax for <FLD72_STP>.</p> <p>Example syntax.FLD72_STP=<INSTR>['CRLF' ((<INSTR>) ('/' '33x))] 0-5</p>
syntax.FLD72_STP_INS	<p>Defines specific syntax for the /INS format used by <FLD72_STP>.</p> <p>Example syntax.FLD72_STP_INS='/INS/' ((<SWIFTBIC>) (<NON-SWIFTBIC>))</p>

Property	Description
syntax.REJTRETN72_GENERIC	Defines generic syntax for <RETJT/RETN/72>. Example syntax.REJTRETN72_GENERIC=35x['CRLF'35x]0-5
syntax.REJTRETN72_SPECIFIC	Defines specific syntax for <RETJT/RETN/72>. Example syntax.REJTRETN72_SPECIFIC=6!x2!n[1a] ['/'2c] 'CRLF' (('/'2!c2!n'/') ('/X'1c2!n'/')) [29x] 'CRLF'/'MREF/' 16x['CRLF'/'TREF/'16x] ['CRLF'/'CHGS/'<CUR><AMOUNT> 15] ['CRLF'/'TEXT/'29x['CRLF'/'/'33x]0-2]
syntax.REJTRETN79_GENERIC	Defines generic syntax for <RETJT/RETN/79>. Example syntax.REJTRETN79_GENERIC=50x['CRLF'50x]0-34
syntax.REJTRETN79_SPECIFIC	Defines specific syntax for <REJT/RETN/79>. Example syntax.REJTRETN79_SPECIFIC=6!x2!n[1a] ['/'2c] 'CRLF' (('/'2!c2!n'/') ('/X'1c2!n'/')) [44x] 'CRLF'/'MREF/' 16x['CRLF'/'TREF/'16x] ['CRLF'/'CHGS/'<CUR><AMOUNT> 15] ['CRLF'/'TEXT/'44x['CRLF'/'/'48x]0-31]
syntax.SPECIAL_FUNCTION	Defines a SWIFT syntax that defines a single special function. Note: The [2n] component covers special functions <AMOUNT> and <NUMBER>. Example syntax.SPECIAL_FUNCTION='<' (50c) '>' [2n]
syntax.CODEWORD_IRSX	Defines the code word IRSX. Example syntax.CODEWORD_IRSX=IRSX
syntax.CODEWORD_AMOUNT_NEGATIVE	Defines the code word Amount is negative. Example syntax.CODEWORD_AMOUNT_NEGATIVE=N
syntax.CODEWORD_ABIC	Defines the code word /ABIC/, used for <PARTYFLD/J> validation. Example syntax.CODEWORD_ABIC=/ABIC/
syntax.CODEWORD_NAME	Defines the code word /NAME/, used for <PARTYFLD/J> validation. Example syntax.CODEWORD_NAME=/NAME/
syntax.CODEWORD_REJT	Defines the code word /REJT/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation. Example syntax.CODEWORD_REJT=/REJT/
syntax.CODEWORD_RETN	Defines the code word /RETN/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation. Example syntax.CODEWORD_RETN=/RETN/

Property	Description
syntax.CODEWORD_ERI	Defines the code word /OCMT/, used for ERI-related validation. Example <code>syntax.CODEWORD_ERI=/OCMT/</code>
syntax.CODEWORD_INS	Defines the code word /INS/, used for <FLD72_STP> validation. Example <code>syntax.CODEWORD_INS=/INS/</code>
syntax.CODEWORD_ASCT	Defines the code word /ASCT/, used for <35B/ISITC/2> validation. Note: The ISITC functions are now DEPRECATED. Example <code>syntax.CODEWORD_ASCT=/ASCT/</code>
syntax.CODEWORD_NETS	Defines the code word /NETS/, used for <PARTYFLD/J> validation. Example <code>syntax.CODEWORD_NETS=/NETS/</code>
syntax.CODEWORD_SIS	Defines the code word /SSIS/, used for <PARTYFLD/J> validation. Example <code>syntax.CODEWORD_SIS=/SSIS/</code>
syntax.CODEWORD_CURR	Defines the code word CURR, that activates validation of rule #101. Example <code>syntax.CODEWORD_CURR=CURR</code>
syntax.CODEWORD_MONT	Defines the code word for evaluating special validation T75. Example <code>syntax.CODEWORD_MONT=MONT</code>
syntax.CODEWORD_OTHR	Defines the code word for evaluating special validation T75. Example <code>syntax.CODEWORD_OTHR=OTHR</code>
syntax.CODEWORD_ISIN	Defines the code word for evaluating special validation T12. Code word ISIN is used for <35B/ISITC> validation. Note: The ISITC functions are now DEPRECATED. Example <code>syntax.CODEWORD_ISIN=ISIN</code>
group.PARTYFLDJ.formats	Defines the regex group numbers where code words can be found that require validation. Example <code>group.PARTYFLDJ.formats=4</code>
group.genericCodeWord.[field_tag].groups	Defines the regex group numbers where code words can be found that require validation. Example <code>group.genericCodeWord.69C.groups=1</code>

Property	Description
group.genericCodeWord.[field_tag]. [regex_matching_group_number]	Defines the regex group numbers where code words can be found that require validation. Example group.genericCodeWord.69C.1=10
group.genericCodeWord.[field_tag]. [regex_matching_group_number].subfield	Defines the regex group numbers where code words can be found that require validation. Example group.genericCodeWord.69C.10.subfield=3
codeWords.REJTRET72	Defines special function code word lists. Example codeWords.REJTRET72='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'
codeWords.REJTRET79	Defines special function code word lists. Example codeWords.REJTRET79='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'
codeWords.ISITC1	Defines special function code word lists. Example codeWords.ISITC1='AAUS', 'ACED', 'ACIN', 'ACMN', 'ACUS', 'AEUR', 'ALUX', 'AQCK', 'ASED', 'ASVM', 'AVAL', 'AWKP', 'ASICC'
codeWords.ISITC2	Defines special function code word lists. Example codeWords.ISITC2='/ACLT/', '/ADIS/', '/AEXP/', '/AFLT/', '/AIR/', '/AMD/', '/AOC/', '/AOT/', '/APN/', '/ASC/', '/ASP/', '/ASTY/', '/ATBA/', '/ATK/', '/AYLD/', , '/ASCT/'
codeWords.ISITC2.ASCT	Defines special function code word lists. Example codeWords.ISITC2.ASCT='BA', 'CD', 'CMO', 'CORP', 'CP', 'CPP', 'CS', 'FHA', 'FHL', 'FN', 'FOR', 'FUT', 'GN', 'GOVT', 'IET', 'MF', 'MIO', 'MPO', 'MPP', 'MPT', 'MUNI', 'OPT', 'PS', 'RP', 'RVRP', 'SL', 'TD', 'USTB', 'WAR', 'ZOO'

Property	Description
codeWords.PARTYFLDJ	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.PARTYFLDJ='/ABIC/', '/NAME/', '/ACCT/', '/ADD1/', '/ADD2/', '/CITY/', '/USFW/', '/USCH/', '/GBSC/', '/CLRC/', '/NETS/', '/SSIS/'</pre>
codeWords.PARTYFLDJ.format [format_number]	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.PARTYFLDJ.format2='/NETS/'</pre>
codeWords.rule.[rule_number]	<p>Defines special function code word lists.</p> <p>Examples</p> <pre>codeWords.rule.5='BEID', 'TRCO', 'TESP', 'MCCO', 'SMDP' codeWords.rule.257='BEID', 'TRCO', 'TESP', 'MCCO', 'SMDP'</pre>

translator_swift_2005.properties

The translator_swift_2005.properties file is used to set global configuration parameters for SWIFT 2005 standards.

The following caveats apply to this properties file:

- ◆ The entries have the following format:
`swiftField.[fieldTag].[subfield].[component].[message]`
- ◆ The properties for 16R and 16S are not enough for performing validation. For example, MT307 requires GENL for 16R, Sequence A and LINK for 16R, Subsequence A1. However, these properties do restrict the code words to the specified lists in the file.
- ◆ For 16R and 16 S, to complete the validation, the Map Editor must use keyfield matching and match against a constant (for example, GENL or LINK). If data is not matched then the translator notes a T13 error code.
- ◆ Field 22, subfield 2, component 1 is matched with a related field that depends on the message type. This validation is handled through the <SB-LC> special function.
- ◆ Some field tags allow any valid currency in addition to a code word validation. The CUR keyword triggers this validation which checks the external Currencies code list.

Code Word Validations for ISO 15022 Messages

The following caveats apply to this properties file for ISO 15022 messages:

- ◆ For each MT the exceptions list is displayed first (if any exceptions exist).
- ◆ The exceptions list has the following format:
`swiftField.Exceptions.<mt>[ext]`
- ◆ The code word lists are displayed by position and order within the MT.
- ◆ Non-exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext]`
- ◆ Exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext]`
- ◆ Where a subfield greater than two needs to be validated the subfield number is appended:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext].<subfield>`
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
>
- ◆ Code words are single-quoted and separated by a comma delimiter.
- ◆ Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present.
- ◆ The <errorCode> will always be the corresponding Kxx code of the field tag.
- ◆ If the field tags do not exist for related fields, a validation error is not reported at the end of translation when deferred validation entries are processed.

- ◆ If one of the choice fields exists for related fields that are part of a choice, the other field tags do not have to exist. Each message type lists the choice options for a particular sequence and field tag.

Configuration Settings

The following table describes properties used to configure the translator_swift_2005.properties file in the application:

Property	Description
swiftField.Exceptions.[message_type]	Defines swiftField properties. Example swiftField.Exceptions.504=22F.STCO
swiftField.[fieldTag].[qualifier]. [message_type]	Defines swiftField properties. Example swiftField.36B.MILT.518='AMOR','FAMT','UNIT':K36
swiftField.[fieldTag].[qualifier].[sequence].[i soBlock].[message_type]	Defines swiftField properties. Example swiftField.23E.1.1.104.B='AUTH','NAUT','OTHR':T47
swiftField.[fieldTag].[qualifier]. [message_type].[subfield]	Defines swiftField properties. Example swiftField.12.1.1.920='940','941','942','950':T88
swiftField.[fieldTag].[qualifier].[sequence].[i soBlock].[message_type].[subfield]	Defines swiftField properties. Example swiftField.93C.UNBA.B2.ACCTINFO.564.3='ELIG', 'NELG':NODSS:K93
mt.smallInputMaximum	Defines MT-specific properties. Example mt.smallInputMaximum=2000
mt.smallOutputMaximum	Defines MT-specific properties. Example mt.smallOutputMaximum=2600
mt.largeInputMaximum	Defines MT-specific properties. Example mt.largeInputMaximum=10000
mt.largeOutputMaximum	Defines MT-specific properties. Example mt.largeOutputMaximum=10600

Property	Description
mt.largeInput	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.largeInput=101,102,103,104,106,107,121,206,207, 256,300,303,304,306,307,308,320,321,330,340,341, 350,360,361,364,365,380,381,405,416,500,501,502, 503,504,505,506,507,508,509,510,513,514,515,517, 518,519,524,527,528,529,535,536,537,538,540,541, 542,543,544,545,546,547,548,549,558,564,565,566, 567,568,569,574,575,576,577,578,584,586,587,588, 589,700,701,710,711,720,721,760,767,98,198,298,398 ,498,598,698,798,898,998,9999</pre>
mt.largeOutput	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.largeOutput=101,102,103,104,106,107,121,206,207 ,256,300,303,304,306,307,308,320,321,330,340,341, 350,360,361,364,365,380,381,405,416,500,501,502, 503,504,505,506,507,508,509,510,513,514,515,517, 518,519,524,527,528,529,535,536,537,538,540,541, 542,543,544,545,546,547,548,549,558,564,565,566, 567,568,569,574,575,576,577,578,584,586,587,588, 589,700,701,710,711,720,721,760,767,98,198,298,398 ,498,598,698,798,898,998,9999</pre>
mt.rule.32	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.rule.32=300,303,304,306,320,330,340,350,360,361 ,362,364,365,405,582,600,643,645,813</pre>
mtFieldTag.F72.other	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.F72.other=192,292,392,492,592,692,792, 892,992,395,495,595,695,795,895,995,196,296,396, 496,596,696,796,896,996</pre>
mtFieldTag.F79.other	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.F79.other=960,964,965,966,967,192,292, 392,492,592,692,792,892,992,395,495,595,695,795, 895,995,196,296,396,496,596,696,796,896,996,399, 499,599,699,799,899,999</pre>
mtFieldTag.ERI.F72.narrative	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.ERI.F72.narrative=110,400,410,412,420, 422,430,450,456,516,526,559,577,581,600,601,604, 605,606,607,609,643,644,645,646,700,705,707,710, 720,730,732,734,740,742,747,750,752,754,756,760, 767,768,769,800,802,812,813,820,821,822,823,824, 900,910,935,90,190,290,390,490,590,690,790,890,990 ,91,191,291,391,491,591,691,791,891,991</pre>

Property	Description
mtFieldTag.FLD72	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.FLD72=100,200,201,202,203,204,205,206,300,303,304,305,306,320,330,340,341,350,360,361,362,364,365,405</code>
mtFieldTag.FLD72._STP	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.FLD72._STP=102,103</code>
mtFieldTag.FLD72._not_STP	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.FLD72._not_STP=102,103</code>
mtFieldTag.REJTRETN72	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.REJTRETN72=100,102,103,104,107,110,195,200,201,202,203,204,205,207,295</code>
mtFieldTag.ERI.F77A	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.ERI.F77A=416,455,456,747,754,810</code>
mtFieldTag.ERI.F79	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.ERI.F79=582,649,705,707,810,986</code>
mtFieldTag.REJTRETN79	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.REJTRETN79=195,199,295,299</code>
mtFieldTag.SB-LC.DATE	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.SB-LC.DATE=360,361,362,364,365</code>
mtFieldTag.rule.89	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89=600,601,604,605,606,607,608,609</code>
mtFieldTag.rule.89.32F	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.32F=600,601,604,605,606,607</code>
mtFieldTag.rule.89.60F	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.60F=608</code>
mtFieldTag.rule.89.60M	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.60M=608</code>

Property	Description
mtFieldTag.rule.89.61	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.61=608</code>
mtFieldTag.rule.89.62F	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62F=608</code>
mtFieldTag.rule.89.62M	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62M=608</code>
mtFieldTag.rule.89.64	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.64=608</code>
mtFieldTag.rule.89.65	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.65=608</code>
mtFieldTag.rule.89.68B.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68B.3.4=609</code>
mtFieldTag.rule.89.68C.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68C.3.4=609</code>
mtFieldTag.specialValidation.T75	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.specialValidation.T75=405,192,292,392,492,592,692,792,892,992,195,295,395,495,595,695,795,895,995,196,296,396,496,596,696,796,896,996</code>
fieldTags.loopRepeat	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.loopRepeat=15A,15B,15C,15D,15E,15F,15G,15H,15I,15J,15K,15L,15M,15N</code>
fieldTags.genericFields	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.genericFields=11A,12A,12B,12C,13A,13B,13J,13K,17B,19A,19B,20C,20D,22F,22H,24B,25D,36B,36C,36E,69A,69B,69C,69D,69E,69F,69J,70C,70D,70E,70F,90A,90B,90E,92A,92B,92C,92D,92E,92F,92J,92K,93A,93B,93C,93D,94B,94C,94D,94F,94G,95C,95P,95Q,95R,95S,95T,95U,95V,97A,97B,97C,98A,98B,98C,98D,99A,99B</code>

Property	Description
fieldTags.checkCRLFUsage	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFUsage=35B,42A,42D,50D,51A,51D, 52A,52B,52D,53A,53B,53D,54A,54B,54D,55A,55B,55D, 56A,56D,57A,57B,57D,58A,58B,58D,82A,82B,82D,83A, 83D,84A,84B,84D,85A,85B,85D,86A,86B,86D,87A,87B, 87D,88A,88B,88D</pre>
fieldTags.specialExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.specialExceptions=12,12E,12F,14A,14D,14G, 14J,16R,16S,17A,17B,17F,17G,17N,17O,17R,17T,17U, 17V,22,22A,22B,22D,22E,22G,22J,22K,23,23A,23B,23C, 23D,23E,23F,23G,24D,26C,26F,28E,31X,32F,32K,33B, 33G,33K,33S,33T,35A,35H,35N,35S,35U,37K,38B,38E, 38G,38H,38J,39B,39P,40A,40B,40C,40E,40F,41A,41D, 49,60F,61,62F,62M,64,65,68B,68C,71A,77H,94A</pre>
fieldTags.noSlashesAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.noSlashesAllowed=12A,13B,20,20C,20D,21, 21A,21F,21G,21P,21R,94B,95Q,95R,95S,95T,95U</pre>
fieldTags.oneOptionMustBePresent	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.oneOptionMustBePresent=52B,53B,54B,57B, 58B,85B,86B,87B,88B</pre>
fieldTags.checkCRLFPairs	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFPairs=77E</pre>
fieldTags.commonMTExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.commonMTExceptions=77F,77G,77T</pre>
fieldTags.commonMTGenericExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.commonMTGenericExceptions=17B</pre>
fieldTags.MT574Exceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.MT574Exceptions=22F</pre>
fieldTags.CRLFStartsLineAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.CRLFStartsLineAllowed=15A,15B,15C,15D, 15E,15F,15G,15H,15I,15J,15K,15L,15M,15N,77E,77S, 77T</pre>
fieldTags.allBlanksAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.allBlanksAllowed=77E,77S,77T</pre>

Property	Description
fieldTags.colonStartsSecondLineAllowed	Defines MT-specific properties for special cases and exceptions. Example fieldTags.colonStartsSecondLineAllowed=77E,77S,77T
fieldTags.PARTYFLDJ.format [format_number]	Defines MT-specific properties for special cases and exceptions. Example fieldTags.PARTYFLDJ.format1=53J,56J,57J,58J,82J, 84J,85J,86J,87J,88J
fieldTags.specialValidation	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation=12,31X,35B,82S,68B, 68C,38B,50H,42D,50D,50K,52D,53D,54D,55D,56D,57D, 58D,59,82D,83D,84D,85D,86D,87D,88D
fieldTags.specialValidation.Errors	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.Errors=T12,T18,T62,T70 ,T74,T75,T76,T77
fieldTags.specialValidation.T12	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T12=35B
fieldTags.specialValidation.T18	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T18=12
fieldTags.specialValidation.T62	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T62=31X
fieldTags.specialValidation.T70	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T70=82S
fieldTags.specialValidation.T74	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T74=68B,68C
fieldTags.specialValidation.T75	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T75=38B
fieldTags.specialValidation.T76	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T76=50H
fieldTags.specialValidation.T77	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T77=42D,50D,50K,52D, 53D,54D,55D,56D,57D,58D,59,82D,83D,84D,85D,86D,87D ,88D

Property	Description
fieldTags.regexSun	Defines MT-specific properties for special cases and exceptions. Note: For SUN customers only. Example <code>fieldTags.regexSun=77C,77E</code>
fieldTags.BICPlus.102_not_STP	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.BICPlus.102_not_STP=52A,52C,57A,57C</code>
fieldTags.BICPlus.102_STP	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.BICPlus.102_STP=52A,57A</code>
fieldTags.BICPlus.103_not_STP	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.BICPlus.103_not_STP=52A,52D,56A,56C,56D,57A,57C,57D</code>
fieldTags.BICPlus.103_STP	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.BICPlus.103_STP=52A,56A,57A</code>
fieldTags.relatedFields.[number]	Defines special related field tag properties. Example <code>fieldTags.relatedFields.102=B.32B</code>
fieldTags.relatedFields.Optional.[number]	Defines related fields that do not have to exist. If the field tags do not exist, then a validation error should not be reported at the end of translation when deferred validation entries are processed. Example <code>fieldTags.relatedFields.Optional.206=C.32A</code>
fieldTags.relatedFields.Choice. [message_type].[sequence].[field_tag]	Defines related fields that are part of a choice. If one of the choice fields exists, then the other field tags do not have to exist. Each message type lists the choice options for a particular sequence and field tag. Example <code>fieldTags.relatedFields.Choice.405.B.32A=B.32A,B.32K</code>
fieldTags.[field_tag].relatedFields. subfield2	Defines related fields for SB-LC and AMOUNT special functions. Example <code>fieldTags.SB-LC.relatedFields.subfield2=33G,32B</code>
fieldTags.[field_tag].relatedFields. [message_type].[sequence].[field]	Defines related fields for SB-LC and AMOUNT special functions. Example <code>fieldTags.SB-LC.relatedFields.600.A.22=A.33G</code>
fieldTags.genericCodeWordExceptions	Defines related fields for SB-LC and AMOUNT special functions. Example <code>fieldTags.genericCodeWordExceptions=69C,69D,92E,93C,98D</code>

Property	Description
fieldTags.rule.[rule_number].[number]	<p>Defines special rule properties. These are rules that have to be implemented within the translator because they require validations using external code lists.</p> <p>Examples</p> <pre>fieldTags.rule.3.100=32A,72 fieldTags.rule.5.107.B=52A,57A fieldTags.rule.101.303.C=39P fieldTags.rule.257.210=50C</pre>
fieldTags.rule.32.303.D1	<p>Defines special rule 32 properties. These entries are exceptions to the normal C32 processing.</p> <p>Example</p> <pre>fieldTags.rule.32.303.D1=32B,57A,57D,57J</pre>
syntax.[fieldtag][.messageType [extension]]	<p>Defines syntax for a SWIFT Field Tag.</p> <p>If a field tag syntax does not have a message-specific syntax, the message type (and extension) are not appended to the syntax entry.</p> <p>Example</p> <pre>syntax.103.97=3!a</pre>
syntax.genericCodeWord.[function]	<p>Defines special function-related syntaxes.</p> <p>Example</p> <pre>syntax.genericCodeWord.69C=': '4!c' / ' [8c] ' / '<DATE4> ' / '4!c'</pre>
syntax.[special_function]	<p>Defines special function-related syntaxes.</p> <p>Example</p> <pre>syntax.ISITC2.AEXP=<DATE2></pre>
syntax.[special_function].[function]	<p>Defines special function-related syntaxes.</p> <p>Example</p> <pre>syntax.PARTYFLDJ.NAME=' /NAME/ ' 34x['CRLF' 34x] 0-4</pre>
syntax.regexSun.[field_tag]	<p>Defines special function-related syntaxes.</p> <p>Note: For SUN customers only.</p> <p>Example</p> <pre>syntax.regexSun.77E=9800x</pre>
syntax.BICPlus	<p>Set this property to "YES" if BIC Plus validation should be performed.</p> <p>Example</p> <pre>syntax.BICPlus=YES</pre>
syntax.NON_GENERIC_FIELD	<p>Defines a syntax for a non-generic field in a System message.</p> <p>Example</p> <pre>syntax.NON_GENERIC_FIELD=': '2!n[1a]': ' "(.*)"</pre>
syntax.NON_GENERIC_SYSTEM_FIELD	<p>Defines syntax for a non-generic field in a System message (for example. 096, 097).</p> <p>Example</p> <pre>syntax.NON_GENERIC_SYSTEM_FIELD=': '2!n[1c]': ' "(.*)"</pre>

Property	Description
syntax.GENERIC_FIELD	<p>Defines syntax for a generic field.</p> <p>Example</p> <pre>syntax.GENERIC_FIELD=': '2!n1a': ': '4!c' / ' [8c] ' / ' " (. *) "</pre>
syntax.GENERIC_CODE_WORD	<p>Defines syntax for parsing out a qualifier, issuer or DSS, code word, and data content of a generic field. In most cases, the code word will be four characters exactly, but there are a few field tags such as 17B that have one letter code words.</p> <p>Example</p> <pre>syntax.GENERIC_CODE_WORD=': '4!c' / ' [8c] ' / '4c' (. *) "</pre>
syntax.HEADER	<p>Defines syntax for a header.</p> <p>Example</p> <pre>syntax.HEADER='{ '3B': ' (" . * ? ") (' - } ' ') ' }</pre>
syntax.CC	<p>Defines syntax for the special function <CC>.</p> <p>Example</p> <pre>syntax.CC=2!a</pre>
syntax.CUR	<p>Syntax for the special function <CUR>.</p> <p>Example</p> <pre>syntax.CUR=3!a</pre>
syntax.DC_GENERIC	<p>Defines generic syntax for the special function <DC>.</p> <p>Example</p> <pre>syntax.DC_GENERIC=1!a</pre>
syntax.DC_SPECIFIC	<p>Defines specific syntax for the special function <DC>.</p> <p>Example</p> <pre>syntax.DC_SPECIFIC='D' 'C'</pre>
syntax.DM_GENERIC	<p>Defines generic for the special function <DM>.</p> <p>Example</p> <pre>syntax.DM_GENERIC=1!a</pre>
syntax.DM_SPECIFIC	<p>Defines specific syntax for the special function <DM>.</p> <p>Example</p> <pre>syntax.DM_SPECIFIC='D' 'M'</pre>
syntax.DATE1	<p>Defines syntax for the special function <DATE1>.</p> <p>Example</p> <pre>syntax.DATE1=4!n</pre>
syntax.DATE2	<p>Defines syntax for the special function <DATE2>.</p> <p>Example</p> <pre>syntax.DATE2=6!n</pre>
syntax.DATE3	<p>Defines syntax for the special function <DATE3>.</p> <p>Example</p> <pre>syntax.DATE3=4!n</pre>

Property	Description
syntax.DATE4	Defines syntax for the special function <DATE4>. Example syntax.DATE4=8!n
syntax.YEAR	Defines syntax for the special function <YEAR>. Example syntax.YEAR=4!n
syntax.HHMM	Defines syntax for the special function <HHMM>. Example syntax.HHMM=4!n
syntax.TIME2	Defines syntax for the special function <TIME2>. Example syntax.TIME2=6!n
syntax.OFFSET	Defines syntax for the special function <OFFSET>. Example syntax.OFFSET=4!n
syntax.SWIFTBIC_COPY	Defines syntax for the special function <SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.NONSWIFTBIC_COPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.SWIFTBIC_NONCOPY	Defines syntax for the special function <SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_NONCOPY=6!a2!c[3!c]
syntax.NONSWIFTBIC_NONCOPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_NONCOPY=7!c'1'[3!c]
syntax.MT	Defines syntax for the special function <MT> (message type). Example syntax.MT=3!n
syntax.SUB6_GENERIC	Defines generic syntax for the special function <SUB6>. Example syntax.SUB6_GENERIC=1!a3!c
syntax.SUB6_SPECIFIC	Defines specific syntax for the special function <SUB6>. Example syntax.SUB6_SPECIFIC=('S'3!n) ('N'3!c) ('F'3!c)

Property	Description
syntax.SBLC	<p>Defines syntax for the special function <SB-LC>.</p> <p>Example</p> <pre>syntax.SBLC=(4!a2!c)4!n(4!a2!c)</pre>
syntax.INSTR	<p>Defines syntax for the special function <INSTR>.</p> <p>Example</p> <pre>syntax.INSTR=('/'1!c'/'[32x]) ('/'2!c'/'[31x]) ('/'3!c'/'[30x]) ('/'4!c'/'[29x]) ('/'5!c'/'[28x]) ('/'6!c'/'[27x]) ('/'7!c'/'[26x]) ('/'8!c'/'[25x])</pre>
syntax.VARSEQU1_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-1>.</p> <p>Example</p> <pre>syntax.VARSEQU1_GENERIC=34x</pre>
syntax.VARSEQU1_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-1>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU1_SPECIFIC=16x['/'16x]</pre>
syntax.VARSEQU2_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-2>.</p> <p>Example</p> <pre>syntax.VARSEQU2_GENERIC=21x</pre>
syntax.VARSEQU2_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-2>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU2_SPECIFIC=16x['/'4!x]</pre>
syntax.VARSEQU3_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-3>.</p> <p>Example</p> <pre>syntax.VARSEQU3_GENERIC=33x</pre>
syntax.VARSEQU3_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-3>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU3_SPECIFIC=16x['/'16x]</pre>
syntax.VARSEQU4_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-4>.</p> <p>Example</p> <pre>syntax.VARSEQU4_GENERIC=[14x]</pre>
syntax.VARSEQU4_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-4>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU4_SPECIFIC=[4x] ['/'8x]</pre>

Property	Description
syntax.ISITC	<p>Defines syntax for the special function <35B/ISITC> that is an ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC='ISIN'1e12!c'CRLF'35x['CRLF'<35B/ISITC/1>]</pre>
syntax.ISITC_NO	<p>Defines syntax for the special function <35B/ISITC> that is a non-ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC_NO=(('/'4!a '/'10x'CRLF') ('/'5!a '/'10x'CRLF')) 35x['CRLF'<35B/ISITC/2>]</pre>
syntax.ISITC1	<p>Defines syntax for the special function <35B/ISITC/1>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC1=35x['CRLF'35x]0-2</pre>
syntax.ISITC2	<p>Defines syntax for the special function <35B/ISITC/2>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC2=35x['CRLF'35x]</pre>
syntax.SIGN_GENERIC	<p>Defines generic syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_GENERIC=1!x 1!y 1!z</pre>
syntax.SIGN_SPECIFIC	<p>Defines specific syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_SPECIFIC='+' '-'</pre>
syntax.IBAN	<p>Defines syntax for the special function <IBAN>.</p> <p>Example</p> <pre>syntax.IBAN=2!A2!n1!B[29B]</pre>
syntax.PARTYFLDJ_GENERIC	<p>Defines generic syntax for <PARTYFLD/J>.</p> <p>Example</p> <pre>syntax.PARTYFLDJ_GENERIC=40x['CRLF'40x]0-4</pre>
syntax.ERI_CODEWORDS	<p>Defines syntax to validate the ERI code words format.</p> <p>Example</p> <pre>syntax.ERI_CODEWORDS=['/OCMT/' '<CUR><NUMBER>15' / ' /CHGS/' '<CUR><NUMBER>15' / ']]</pre>
syntax.ERIF61_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F61> code word.</p> <p>Example</p> <pre>syntax.ERIF61_GENERIC=34x</pre>

Property	Description
syntax.ERIF61_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F61>code word.</p> <p>Example syntax.ERIF61_SPECIFIC=34x</p>
syntax.ERIFLD72_STRUCTURED_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_FLD72structured> code word.</p> <p>Example syntax.ERIFLD72_STRUCTURED_GENERIC=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</p>
syntax.ERIFLD72_STRUCTURED_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_FLD72structured> code word.</p> <p>Example syntax.ERIFLD72_STRUCTURED_SPECIFIC=210x</p>
syntax.ERIF72_NARRATIVE_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F72narrative> code word.</p> <p>Example syntax.ERIF72_NARRATIVE_GENERIC=35x['CRLF' 35x] 0-5</p>
syntax.ERIF72_NARRATIVE_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F72narrative> code word.</p> <p>Example syntax.ERIF72_NARRATIVE_SPECIFIC=210x</p>
syntax.ERIF77A_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F77A> code word.</p> <p>Example syntax.ERIF77A_GENERIC=35x['CRLF' 35x] 0-19</p>
syntax.ERIF77A_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F77A> code word.</p> <p>Example syntax.ERIF77A_SPECIFIC=700x</p>
syntax.ERIF79_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F79> code word.</p> <p>Example syntax.ERIF79_GENERIC=50x['CRLF' 50x] 0-34</p>
syntax.ERIF79_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F79> code word.</p> <p>Example syntax.ERIF79_SPECIFIC=1750x</p>
syntax.ERIF86_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F86> code word.</p> <p>Example syntax.ERIF86_GENERIC=65x['CRLF' 65x] 0-5</p>

Property	Description
syntax.ERIF86_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F86> code word.</p> <p>Example syntax.ERIF86_SPECIFIC=390x</p>
syntax.F72_OTHER	<p>Defines syntax to validate field 72 where no special function validation is needed.</p> <p>Example syntax.F72_OTHER=35x['CRLF' 35x] 0-5</p>
syntax.F79_OTHER	<p>Defines syntax to validate field 79 where no special function validation is needed.</p> <p>Example syntax.F79_OTHER=50x['CRLF' 50x] 0-34</p>
syntax.FLD72	<p>Defines specific syntax for <FLD72>.</p> <p>Example syntax.FLD72=<INSTR>['CRLF' ((<INSTR>) ('/' 33x))] 0-5</p>
syntax.FLD79	<p>Defines specific syntax for <FLD79>.</p> <p>Note: Unlike <FLD72>, the specific syntax does not use the special function <INSTR>.</p> <p>Example syntax.FLD79=50x['CRLF' 50x] 0-34</p>
syntax.FLD72_NOT_STP	<p>Defines specific syntax for <FLD72_not_STP>.</p> <p>Example syntax.FLD72_NOT_STP=<INSTR>['CRLF' ((<INSTR>) ('/' 33x))] 0-5</p>
syntax.FLD72_STP	<p>Defines specific syntax for <FLD72_STP>.</p> <p>Example syntax.FLD72_STP=<INSTR>['CRLF' ((<INSTR>) ('/' 33x))] 0-5</p>
syntax.FLD72_STP_INS	<p>Defines specific syntax for the /INS format used by <FLD72_STP>.</p> <p>Example syntax.FLD72_STP_INS=' /INS/' ((<SWIFTBIC>) (<NON-SWIFTBIC>))</p>
syntax.REJTRETN72_GENERIC	<p>Defines generic syntax for <RETJT/RETN/72>.</p> <p>Example syntax.REJTRETN72_GENERIC=35x['CRLF' 35x] 0-5</p>
syntax.REJTRETN72_SPECIFIC	<p>Defines specific syntax for <RETJT/RETN/72>.</p> <p>Example syntax.REJTRETN72_SPECIFIC=6!x2!n[1a] ['/' 2c] 'CRLF' (('/' 2!c2!n'/') ('/X' 1c2!n'/')) [29x] 'CRLF' '/MREF/' 16x['CRLF' '/TREF/' 16x] ['CRLF' '/CHGS/' <CUR><AMOUNT> 15] ['CRLF' '/TEXT/' 29x['CRLF' '/' 33x] 0-2]</p>

Property	Description
syntax.REJTRETN79_GENERIC	<p>Defines generic syntax for <RETJT/RETN/79>.</p> <p>Example</p> <pre>syntax.REJTRETN79_GENERIC=50x['CRLF'50x]0-34</pre>
syntax.REJTRETN79_SPECIFIC	<p>Defines specific syntax for <REJT/RETN/79>.</p> <p>Example</p> <pre>syntax.REJTRETN79_SPECIFIC=6!x2!n[1a] ['/'2c] 'CRLF' (('/'2!c2!n'/') ('/'X'1c2!n'/')) [44x] 'CRLF' /MREF/' 16x['CRLF' /TREF/'16x] ['CRLF' /CHGS/' <CUR><AMOUNT> 15] ['CRLF' /TEXT/'44x['CRLF' /'48x]0-31]</pre>
syntax.SPECIAL_FUNCTION	<p>Defines a SWIFT syntax that defines a single special function.</p> <p>Note: The [2n] component covers special functions <AMOUNT> and <NUMBER>.</p> <p>Example</p> <pre>syntax.SPECIAL_FUNCTION='<' (50c) '>' [2n]</pre>
syntax.CODEWORD_IRSX	<p>Defines the code word IRSX.</p> <p>Example</p> <pre>syntax.CODEWORD_IRSX=IRSX</pre>
syntax.CODEWORD_AMOUNT_NEGATIVE	<p>Defines a negative code word amount.</p> <p>Example</p> <pre>syntax.CODEWORD_AMOUNT_NEGATIVE=N</pre>
syntax.CODEWORD_ABIC	<p>Defines the code word /ABIC/, used for <PARTYFLD/J> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_ABIC=/ABIC/</pre>
syntax.CODEWORD_NAME	<p>Defines the code word /NAME/, used for <PARTYFLD/J> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_NAME=/NAME/</pre>
syntax.CODEWORD_REJT	<p>Defines the code word /REJT/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_REJT=/REJT/</pre>
syntax.CODEWORD_RETN	<p>Defines the code word /RETN/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_RETN=/RETN/</pre>
syntax.CODEWORD_ERI	<p>Defines the code word /OCMT/, used for ERI-related validation.</p> <p>Example</p> <pre>syntax.CODEWORD_ERI=/OCMT/</pre>
syntax.CODEWORD_INS	<p>Defines the code word /INS/, used for <FLD72_STP> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_INS=/INS/</pre>

Property	Description
<code>syntax.CODEWORD_ASCT</code>	<p>Defines the code word /ASCT/, used for <35B/ISITC/2> validation.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example <code>syntax.CODEWORD_ASCT=/ASCT/</code></p>
<code>syntax.CODEWORD_NETS</code>	<p>Defines the code word /NETS/, used for <PARTYFLD/J> validation.</p> <p>Example <code>syntax.CODEWORD_NETS=/NETS/</code></p>
<code>syntax.CODEWORD_SIS</code>	<p>Defines the code word /SSIS/, used for <PARTYFLD/J> validation.</p> <p>Example <code>syntax.CODEWORD_SIS=/SSIS/</code></p>
<code>syntax.CODEWORD_CURR</code>	<p>Defines the code word CURR, that activates validation of rule #101.</p> <p>Example <code>syntax.CODEWORD_CURR=CURR</code></p>
<code>syntax.CODEWORD_MONT</code>	<p>Defines the code word for evaluating special validation T75.</p> <p>Example <code>syntax.CODEWORD_MONT=MONT</code></p>
<code>syntax.CODEWORD_OTHR</code>	<p>Defines the code word for evaluating special validation T75.</p> <p>Example <code>syntax.CODEWORD_OTHR=OTHR</code></p>
<code>syntax.CODEWORD_ISIN</code>	<p>Defines the code word for evaluating special validation T12. Code word ISIN is used for <35B/ISITC> validation.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example <code>syntax.CODEWORD_ISIN=ISIN</code></p>
<code>group.PARTYFLDJ.formats</code>	<p>Defines the regex group numbers where code words can be found that require validation.</p> <p>Example <code>group.PARTYFLDJ.formats=4</code></p>
<code>group.genericCodeWord.[field_tag].groups</code>	<p>Defines the regex group numbers where code words can be found that require validation.</p> <p>Example <code>group.genericCodeWord.69C.groups=1</code></p>
<code>group.genericCodeWord.[field_tag].[regex_matching_group_number]</code>	<p>Defines the regex group numbers where code words can be found that require validation.</p> <p>Example <code>group.genericCodeWord.69C.1=10</code></p>
<code>group.genericCodeWord.[field_tag].[regex_matching_group_number].subfield</code>	<p>Defines the regex group numbers where code words can be found that require validation.</p> <p>Example <code>group.genericCodeWord.69D.12.subfield=3</code></p>

Property	Description
codeWords.REJTRETN72	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.REJTRETN72='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'</pre>
codeWords.REJTRETN79	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.REJTRETN79='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'</pre>
codeWords.ISITC1	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.ISITC1='AAUS', 'ACED', 'ACIN', 'ACMN', 'ACUS', 'AEUR', 'ALUX', 'AQCK', 'ASED', 'ASVM', 'AVAL', 'AWKP', 'ASICC'</pre>
codeWords.ISITC2	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.ISITC2='/ACLT/', '/ADIS/', '/AEXP/', '/AFLT/', '/AIR/', '/AMD/', '/AOC/', '/AOT/', '/APN/', '/ASC/', '/ASP/', '/ASTY/', '/ATBA/', '/ATK/', '/AYLD/', '/ASCT/'</pre>
codeWords.ISITC2.ASCT	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.ISITC2.ASCT='BA', 'CD', 'CMO', 'CORP', 'CP', 'CPP', 'CS', 'FHA', 'FHL', 'FN', 'FOR', 'FUT', 'GN', 'GOVT', 'IET', 'MF', 'MIO', 'MPO', 'MPP', 'MPT', 'MUNI', 'OPT', 'PS', 'RP', 'RVRP', 'SL', 'TD', 'USTB', 'WAR', 'ZOO'</pre>
codeWords.PARTYFLDJ	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.PARTYFLDJ='/ABIC/', '/NAME/', '/ACCT/', '/ADD1/', '/ADD2/', '/CITY/', '/USFW/', '/USCH/', '/GBSC/', '/CLRC/', '/NETS/', '/SSIS/'</pre>
codeWords.PARTYFLDJ.format [format_number]	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.PARTYFLDJ.format2='/NETS/'</pre>

Property	Description
codeWords.rule.[rule_number]	<p>Defines special function code word lists.</p> <p>Examples</p> <pre>codeWords.rule.5='BEID','TRCO','TESP','MCCO', 'SMDP' codeWords.rule.257='BEID','TRCO','TESP','MCCO', 'SMDP'</pre>

translator_swift_2006.properties

The translator_swift_2006.properties file is used to set global configuration parameters for SWIFT 2006 standards.

The following caveats apply to this properties file:

- ◆ The entries have the following format:
`swiftField.[fieldTag].[subfield].[component].[message]`
- ◆ The properties for 16R and 16S are not enough for performing validation. For example, MT307 requires GENL for 16R, Sequence A and LINK for 16R, Subsequence A1. However, these properties do restrict the code words to the specified lists in the file.
- ◆ For 16R and 16 S, to complete the validation, the Map Editor must use keyfield matching and match against a constant (for example, GENL or LINK). If data is not matched then the translator notes a T13 error code.
- ◆ Field 22, subfield 2, component 1 is matched with a related field that depends on the message type. This validation is handled through the <SB-LC> special function.
- ◆ Some field tags allow any valid currency in addition to a code word validation. The CUR keyword triggers this validation which checks the external Currencies code list.

Code Word Validations for ISO 15022 Messages

The following caveats apply to this properties file for ISO 15022 messages:

- ◆ For each MT the exceptions list is displayed first (if any exceptions exist).
- ◆ The exceptions list has the following format:
`swiftField.Exceptions.<mt>[ext]`
- ◆ The code word lists are displayed by position and order within the MT.
- ◆ Non-exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext]`
- ◆ Exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext]`
- ◆ Where a subfield greater than two needs to be validated the subfield number is appended:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext].<subfield>`
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
>
- ◆ Code words are single-quoted and separated by a comma delimiter.
- ◆ Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present.
- ◆ The <errorCode> will always be the corresponding Kxx code of the field tag.
- ◆ If the field tags do not exist for related fields, a validation error is not reported at the end of translation when deferred validation entries are processed.

- ◆ If one of the choice fields exists for related fields that are part of a choice, the other field tags do not have to exist. Each message type lists the choice options for a particular sequence and field tag.

Configuration Settings

The following table describes properties used to configure the translator_swift_2006.properties file in the application:

Property	Description
swiftField.Exceptions.[message_type]	Defines swiftField properties. Example swiftField.Exceptions.504=22F.STCO
swiftField.[fieldTag].[qualifier]. [message_type]	Defines swiftField properties. Example swiftField.36B.MILT.518='AMOR','FAMT','UNIT':K36
swiftField.[fieldTag].[qualifier].[sequence].[i soBlock].[message_type]	Defines swiftField properties. Example swiftField.23E.1.1.104.B='AUTH','NAUT','OTHR':T47
swiftField.[fieldTag].[qualifier]. [message_type].[subfield]	Defines swiftField properties. Example swiftField.12.1.1.920='940','941','942','950':T88
swiftField.[fieldTag].[qualifier].[sequence].[i soBlock].[message_type].[subfield]	Defines swiftField properties. Example swiftField.93C.UNBA.B2.ACCTINFO.564.3='ELIG', 'NELG':NODSS:K93
mt.smallInputMaximum	Defines MT-specific properties. Example mt.smallInputMaximum=2000
mt.smallOutputMaximum	Defines MT-specific properties. Example mt.smallOutputMaximum=2600
mt.largeInputMaximum	Defines MT-specific properties. Example mt.largeInputMaximum=10000
mt.largeOutputMaximum	Defines MT-specific properties. Example mt.largeOutputMaximum=10600

Property	Description
mt.largeInput	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.largeInput=101,102,103,104,106,107,121,206,207, 256,300,303,304,306,307,308,320,321,330,340,341, 350,360,361,364,365,380,381,405,416,500,501,502, 503,504,505,506,507,508,509,510,513,514,515,517, 518,519,524,527,528,529,535,536,537,538,540,541, 542,543,544,545,546,547,548,549,558,564,565,566, 567,568,569,574,575,576,577,578,584,586,587,588, 589,700,701,710,711,720,721,760,767,98,198,298,398 ,498,598,698,798,898,998,9999</pre>
mt.largeOutput	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.largeOutput=101,102,103,104,106,107,121,206,207 ,256,300,303,304,306,307,308,320,321,330,340,341, 350,360,361,364,365,380,381,405,416,500,501,502, 503,504,505,506,507,508,509,510,513,514,515,517, 518,519,524,527,528,529,535,536,537,538,540,541, 542,543,544,545,546,547,548,549,558,564,565,566, 567,568,569,574,575,576,577,578,584,586,587,588, 589,700,701,710,711,720,721,760,767,98,198,298,398 ,498,598,698,798,898,998,9999</pre>
mt.rule.32	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.rule.32=300,303,304,306,320,330,340,350,360,361 ,362,364,365,405,582,600,643,645,813</pre>
mtFieldTag.F72.other	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.F72.other=192,292,392,492,592,692,792, 892,992,395,495,595,695,795,895,995,196,296,396, 496,596,696,796,896,996</pre>
mtFieldTag.F79.other	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.F79.other=960,964,965,966,967,192,292, 392,492,592,692,792,892,992,395,495,595,695,795, 895,995,196,296,396,496,596,696,796,896,996,399, 499,599,699,799,899,999</pre>
mtFieldTag.ERI.F72.narrative	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.ERI.F72.narrative=110,400,410,412,420, 422,430,450,456,516,526,559,577,581,600,601,604, 605,606,607,609,643,644,645,646,700,705,707,710, 720,730,732,734,740,742,747,750,752,754,756,760, 767,768,769,800,802,812,813,820,821,822,823,824, 900,910,935,90,190,290,390,490,590,690,790,890,990 ,91,191,291,391,491,591,691,791,891,991</pre>

Property	Description
mtFieldTag.FLD72	Defines MT-specific properties for field tag validation. Example mtFieldTag.FLD72=200,201,202,203,204,205,206, 300,303,304,305,306,320,330,340,341,350,360,361, 362,364,365,405
mtFieldTag.FLD72._STP	Defines MT-specific properties for field tag validation. Example mtFieldTag.FLD72._STP=102,103
mtFieldTag.FLD72._not_STP	Defines MT-specific properties for field tag validation. Example mtFieldTag.FLD72._not_STP=102,103
mtFieldTag.REJTRETN72	Defines MT-specific properties for field tag validation. Example mtFieldTag.REJTRETN72=102,103,104,107,110,195,200, 201,202,203,204,205,207,295
mtFieldTag.ERI.F77A	Defines MT-specific properties for field tag validation. Example mtFieldTag.ERI.F77A=416,455,456,747,754,810
mtFieldTag.ERI.F79	Defines MT-specific properties for field tag validation. Example mtFieldTag.ERI.F79=582,649,705,707,810,986
mtFieldTag.REJTRETN79	Defines MT-specific properties for field tag validation. Example mtFieldTag.REJTRETN79=195,199,295,299
mtFieldTag.SB-LC.DATE	Defines MT-specific properties for field tag validation. Example mtFieldTag.SB-LC.DATE=360,361,362,364,365
mtFieldTag.rule.89	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89=600,601,604,605,606,607,608,609
mtFieldTag.rule.89.32F	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89.32F=600,601,604,605,606,607
mtFieldTag.rule.89.60F	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89.60F=608
mtFieldTag.rule.89.60M	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89.60M=608

Property	Description
mtFieldTag.rule.89.61	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.61=608</code>
mtFieldTag.rule.89.62F	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62F=608</code>
mtFieldTag.rule.89.62M	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62M=608</code>
mtFieldTag.rule.89.64	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.64=608</code>
mtFieldTag.rule.89.65	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.65=608</code>
mtFieldTag.rule.89.68B.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68B.3.4=609</code>
mtFieldTag.rule.89.68C.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68C.3.4=609</code>
mtFieldTag.specialValidation.T75	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.specialValidation.T75=405,192,292,392,492,592,692,792,892,992,195,295,395,495,595,695,795,895,995,196,296,396,496,596,696,796,896,996</code>
fieldTags.loopRepeat	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.loopRepeat=15A,15B,15C,15D,15E,15F,15G,15H,15I,15J,15K,15L,15M,15N</code>
fieldTags.genericFields	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.genericFields=11A,12A,12B,12C,13A,13B,13J,13K,17B,19A,19B,20C,20D,22F,22H,24B,25D,36B,36C,36E,69A,69B,69C,69D,69E,69F,69J,70C,70D,70E,70F,90A,90B,90E,92A,92B,92C,92D,92E,92F,92J,92K,93A,93B,93C,93D,94B,94C,94D,94F,94G,95C,95P,95Q,95R,95S,95T,95U,95V,97A,97B,97C,98A,98B,98C,98D,99A,99B</code>

Property	Description
fieldTags.checkCRLFUsage	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFUsage=35B,42A,42D,50D,51A,51D, 52A,52B,52D,53A,53B,53D,54A,54B,54D,55A,55B,55D, 56A,56D,57A,57B,57D,58A,58B,58D,82A,82B,82D,83A, 83D,84A,84B,84D,85A,85B,85D,86A,86B,86D,87A,87B, 87D,88A,88B,88D</pre>
fieldTags.specialExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.specialExceptions=12,12E,12F,14A,14D,14G, 14J,16R,16S,17A,17B,17F,17G,17N,17O,17R,17T,17U, 17V,22,22A,22B,22D,22E,22G,22J,22K,23,23A,23B,23C, 23D,23E,23F,23G,24D,26C,26F,28E,31X,32F,32K,33B, 33G,33K,33S,33T,35A,35H,35N,35S,35U,37K,38B,38E, 38G,38H,38J,39B,39P,40A,40B,40C,40E,40F,41A,41D, 49,60F,61,62F,62M,64,65,68B,68C,71A,77H,94A</pre>
fieldTags.noSlashesAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.noSlashesAllowed=12A,13B,20,20C,20D,21, 21A,21F,21G,21P,21R,94B,95Q,95R,95S,95T,95U,95V</pre>
fieldTags.oneOptionMustBePresent	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.oneOptionMustBePresent=52B,53B,54B,57B, 58B,85B,86B,87B,88B</pre>
fieldTags.checkCRLFPairs	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFPairs=77E</pre>
fieldTags.commonMTExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.commonMTExceptions=77F,77G,77T</pre>
fieldTags.commonMTGenericExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.commonMTGenericExceptions=17B</pre>
fieldTags.MT574Exceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.MT574Exceptions=22F</pre>
fieldTags.CRLFStartsLineAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.CRLFStartsLineAllowed=15A,15B,15C,15D, 15E,15F,15G,15H,15I,15J,15K,15L,15M,15N,77E,77T</pre>
fieldTags.allBlanksAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.allBlanksAllowed=77E,77T</pre>

Property	Description
fieldTags.colonStartsSecondLineAllowed	Defines MT-specific properties for special cases and exceptions. Example fieldTags.colonStartsSecondLineAllowed=77E,77T
fieldTags.PARTYFLDJ.format [format_number]	Defines MT-specific properties for special cases and exceptions. Example fieldTags.PARTYFLDJ.format1=53J,56J,57J,58J,82J, 84J,85J,86J,87J,88J
fieldTags.specialValidation	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation=12,31X,35B,82S,68B, 68C,38B,50H,42D,50D,50K,52D,53D,54D,55D,56D,57D, 58D,59,82D,83D,84D,85D,86D,87D,88D
fieldTags.specialValidation.Errors	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.Errors=T12,T18,T62,T70 ,T74,T75,T76,T77
fieldTags.specialValidation.T12	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T12=35B
fieldTags.specialValidation.T18	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T18=12
fieldTags.specialValidation.T62	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T62=31X
fieldTags.specialValidation.T70	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T70=82S
fieldTags.specialValidation.T74	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T74=68B,68C
fieldTags.specialValidation.T75	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T75=38B
fieldTags.specialValidation.T76	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T76=50H
fieldTags.specialValidation.T77	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T77=42D,50D,50K,52D, 53D,54D,55D,56D,57D,58D,59,82D,83D,84D,85D,86D,87D ,88D

Property	Description
fieldTags.regexSun	Defines MT-specific properties for special cases and exceptions. Note: For SUN customers only. Example fieldTags.regexSun=77C,77E
fieldTags.BICPlus.102_not_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.102_not_STP=52A,52C,57A,57C
fieldTags.BICPlus.102_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.102_STP=52A,57A
fieldTags.BICPlus.103_not_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.103_not_STP=52A,52D,56A,56C,56D,57A,57C,57D
fieldTags.BICPlus.103_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.103_STP=52A,56A,57A
fieldTags.relatedFields.[number]	Defines special related field tag properties. Example fieldTags.relatedFields.102=B.32B
fieldTags.relatedFields.Optional.[number]	Defines related fields that do not have to exist. If the field tags do not exist, then a validation error should not be reported at the end of translation when deferred validation entries are processed. Example fieldTags.relatedFields.Optional.206=C.32A
fieldTags.relatedFields.Choice. [message_type].[sequence].[field_tag]	Defines related fields that are part of a choice. If one of the choice fields exists, then the other field tags do not have to exist. Each message type lists the choice options for a particular sequence and field tag. Example fieldTags.relatedFields.Choice.405.B.32A=B.32A,B.32K
fieldTags.[field_tag].relatedFields. subfield2	Defines related fields for SB-LC and AMOUNT special functions. Example fieldTags.SB-LC.relatedFields.subfield2=33G,32B
fieldTags.[field_tag].relatedFields. [message_type].[sequence].[field]	Defines related fields for SB-LC and AMOUNT special functions. Example fieldTags.SB-LC.relatedFields.600.A.22=A.33G
fieldTags.genericCodeWordExceptions	Defines related fields for SB-LC and AMOUNT special functions. Example fieldTags.genericCodeWordExceptions=69C,69D,92E,93C,98D

Property	Description
fieldTags.rule.[rule_number].[number]	<p>Defines special rule properties. These are rules that have to be implemented within the translator because they require validations using external code lists.</p> <p>Examples</p> <pre>fieldTags.rule.3.100=32A,72 fieldTags.rule.5.107.B=52A,57A fieldTags.rule.101.303.C=39P fieldTags.rule.257.210=50C</pre>
fieldTags.rule.32.303.D1	<p>Defines special rule 32 properties. These entries are exceptions to the normal C32 processing.</p> <p>Example</p> <pre>fieldTags.rule.32.303.D1=32B,57A,57D,57J</pre>
syntax.[fieldtag].[messageType [extension]]	<p>Defines syntax for a SWIFT Field Tag.</p> <p>If a field tag syntax does not have a message-specific syntax, the message type (and extension) are not appended to the syntax entry.</p> <p>Example</p> <pre>syntax.103.97=3!a</pre>
syntax.genericCodeWord.[field_tag]	<p>Defines special function-related syntaxes.</p> <p>Example</p> <pre>syntax.genericCodeWord.69C=': '4!c' / ' [8c] ' / '<DATE4> ' / '4!c</pre>
syntax.[special_function]	<p>Defines special function-related syntaxes.</p> <p>Example</p> <pre>syntax.ISITC2.AEXP=<DATE2></pre>
syntax.[special_function].[function]	<p>Defines special function-related syntaxes.</p> <p>Example</p> <pre>syntax.PARTYFLDJ.NAME=' /NAME/ ' 34x ['CRLF' 34x] 0-4</pre>
syntax.regexSun.[field_tag]	<p>Defines special function-related syntaxes.</p> <p>Note: For SUN customers only.</p> <p>Example</p> <pre>syntax.regexSun.77E=9800x</pre>
syntax.BICPlus	<p>Set this property to "YES" if BIC Plus validation should be performed.</p> <p>Example</p> <pre>syntax.BICPlus=YES</pre>
syntax.NON_GENERIC_FIELD	<p>Defines a syntax for a non-generic field.</p> <p>Example</p> <pre>syntax.NON_GENERIC_FIELD=': '2!n[1a]': ' " (.*) "</pre>
syntax.NON_GENERIC_SYSTEM_FIELD	<p>Defines syntax for a non-generic field in a System message (for example. 096, 097).</p> <p>Example</p> <pre>syntax.NON_GENERIC_SYSTEM_FIELD=': '2!n[1c]': ' " (.*) "</pre>

Property	Description
syntax.GENERIC_FIELD	<p>Defines syntax for a generic field.</p> <p>Example</p> <pre>syntax.GENERIC_FIELD=': '2!n1a': ': '4!c' / ' [8c] ' / ' " (. *) "</pre>
syntax.GENERIC_CODE_WORD	<p>Defines syntax for parsing out a qualifier, issuer or DSS, code word, and data content of a generic field. In most cases, the code word will be four characters exactly, but there are a few field tags such as 17B that have one letter code words.</p> <p>Example</p> <pre>syntax.GENERIC_CODE_WORD=': '4!c' / ' [8c] ' / '4c' (. *) "</pre>
syntax.HEADER	<p>Defines syntax for a header.</p> <p>Example</p> <pre>syntax.HEADER='{ '3B': ' (" . * ? ") (' - } ' ') ' }</pre>
syntax.CC	<p>Defines syntax for the special function <CC>.</p> <p>Example</p> <pre>syntax.CC=2!a</pre>
syntax.CUR	<p>Syntax for the special function <CUR>.</p> <p>Example</p> <pre>syntax.CUR=3!a</pre>
syntax.DC_GENERIC	<p>Defines generic syntax for the special function <DC>.</p> <p>Example</p> <pre>syntax.DC_GENERIC=1!a</pre>
syntax.DC_SPECIFIC	<p>Defines specific syntax for the special function <DC>.</p> <p>Example</p> <pre>syntax.DC_SPECIFIC='D' 'C'</pre>
syntax.DM_GENERIC	<p>Defines generic for the special function <DM>.</p> <p>Example</p> <pre>syntax.DM_GENERIC=1!a</pre>
syntax.DM_SPECIFIC	<p>Defines specific syntax for the special function <DM>.</p> <p>Example</p> <pre>syntax.DM_SPECIFIC='D' 'M'</pre>
syntax.DATE1	<p>Defines syntax for the special function <DATE1>.</p> <p>Example</p> <pre>syntax.DATE1=4!n</pre>
syntax.DATE2	<p>Defines syntax for the special function <DATE2>.</p> <p>Example</p> <pre>syntax.DATE2=6!n</pre>
syntax.DATE3	<p>Defines syntax for the special function <DATE3>.</p> <p>Example</p> <pre>syntax.DATE3=4!n</pre>

Property	Description
syntax.DATE4	Defines syntax for the special function <DATE4>. Example syntax.DATE4=8!n
syntax.YEAR	Defines syntax for the special function <YEAR>. Example syntax.YEAR=4!n
syntax.HHMM	Defines syntax for the special function <HHMM>. Example syntax.HHMM=4!n
syntax.TIME2	Defines syntax for the special function <TIME2>. Example syntax.TIME2=6!n
syntax.OFFSET	Defines syntax for the special function <OFFSET>. Example syntax.OFFSET=4!n
syntax.SWIFTBIC_COPY	Defines syntax for the special function <SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.NONSWIFTBIC_COPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.SWIFTBIC_NONCOPY	Defines syntax for the special function <SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_NONCOPY=6!a2!c[3!c]
syntax.NONSWIFTBIC_NONCOPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_NONCOPY=7!c'1'[3!c]
syntax.MT	Defines syntax for the special function <MT> (message type). Example syntax.MT=3!n
syntax.SUB6_GENERIC	Defines generic syntax for the special function <SUB6>. Example syntax.SUB6_GENERIC=1!a3!c
syntax.SUB6_SPECIFIC	Defines specific syntax for the special function <SUB6>. Example syntax.SUB6_SPECIFIC=('S'3!n) ('N'3!c) ('F'3!c)

Property	Description
syntax.SBLC	<p>Defines syntax for the special function <SB-LC>.</p> <p>Example</p> <pre>syntax.SBLC=(4!a2!c)4!n(4!a2!c)</pre>
syntax.INSTR	<p>Defines syntax for the special function <INSTR>.</p> <p>Example</p> <pre>syntax.INSTR=('/'1!c'/'[32x]) ('/'2!c'/'[31x]) ('/'3!c'/'[30x]) ('/'4!c'/'[29x]) ('/'5!c'/'[28x]) ('/'6!c'/'[27x]) ('/'7!c'/'[26x]) ('/'8!c'/'[25x])</pre>
syntax.VARSEQU1_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-1>.</p> <p>Example</p> <pre>syntax.VARSEQU1_GENERIC=34x</pre>
syntax.VARSEQU1_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-1>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU1_SPECIFIC=16x['/'16x]</pre>
syntax.VARSEQU2_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-2>.</p> <p>Example</p> <pre>syntax.VARSEQU2_GENERIC=21x</pre>
syntax.VARSEQU2_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-2>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU2_SPECIFIC=16x['/'4!x]</pre>
syntax.VARSEQU3_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-3>.</p> <p>Example</p> <pre>syntax.VARSEQU3_GENERIC=33x</pre>
syntax.VARSEQU3_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-3>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU3_SPECIFIC=16x['/'16x]</pre>
syntax.VARSEQU4_GENERIC	<p>Defines generic syntax for the special function <VAR-SEQU-4>.</p> <p>Example</p> <pre>syntax.VARSEQU4_GENERIC=[14x]</pre>
syntax.VARSEQU4_SPECIFIC	<p>Defines specific syntax for the special function <VAR-SEQU-4>.</p> <p>Note: The special function will validate the specific syntax.</p> <p>Example</p> <pre>syntax.VARSEQU4_SPECIFIC=[4x] ['/'8x]</pre>

Property	Description
syntax.ISITC	<p>Defines syntax for the special function <35B/ISITC> that is an ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC='ISIN'1e12!c'CRLF'35x['CRLF'<35B/ISITC/1>]</pre>
syntax.ISITC_NO	<p>Defines syntax for the special function <35B/ISITC> that is a non-ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC_NO=(('/'4!a '/'10x'CRLF') ('/'5!a '/'10x'CRLF')) 35x['CRLF'<35B/ISITC/2>]</pre>
syntax.ISITC1	<p>Defines syntax for the special function <35B/ISITC/1>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC1=35x['CRLF'35x]0-2</pre>
syntax.ISITC2	<p>Defines syntax for the special function <35B/ISITC/2>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC2=35x['CRLF'35x]</pre>
syntax.SIGN_GENERIC	<p>Defines generic syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_GENERIC=1!x 1!y 1!z</pre>
syntax.SIGN_SPECIFIC	<p>Defines specific syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_SPECIFIC='+' '-'</pre>
syntax.IBAN	<p>Defines syntax for the special function <IBAN>.</p> <p>Example</p> <pre>syntax.IBAN=2!A2!n1!B[29B]</pre>
syntax.PARTYFLDJ_GENERIC	<p>Defines generic syntax for <PARTYFLD/J>.</p> <p>Example</p> <pre>syntax.PARTYFLDJ_GENERIC=40x['CRLF'40x]0-4</pre>
syntax.ERI_CODEWORDS	<p>Defines syntax to validate the ERI code words format.</p> <p>Example</p> <pre>syntax.ERI_CODEWORDS=['/OCMT/' '<CUR><NUMBER>15' / ' /CHGS/' '<CUR><NUMBER>15' / ']</pre>
syntax.ERIF61_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F61> code word.</p> <p>Example</p> <pre>syntax.ERIF61_GENERIC=34x</pre>

Property	Description
syntax.ERIF61_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F61>code word.</p> <p>Example syntax.ERIF61_SPECIFIC=34x</p>
syntax.ERIFLD72_STRUCTURED_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_FLD72structured> code word.</p> <p>Example syntax.ERIFLD72_STRUCTURED_GENERIC=<INSTR> ['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</p>
syntax.ERIFLD72_STRUCTURED_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_FLD72structured> code word.</p> <p>Example syntax.ERIFLD72_STRUCTURED_SPECIFIC=210x</p>
syntax.ERIF72_NARRATIVE_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F72narrative> code word.</p> <p>Example syntax.ERIF72_NARRATIVE_GENERIC=35x['CRLF' 35x] 0-5</p>
syntax.ERIF72_NARRATIVE_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F72narrative> code word.</p> <p>Example syntax.ERIF72_NARRATIVE_SPECIFIC=210x</p>
syntax.ERIF77A_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F77A> code word.</p> <p>Example syntax.ERIF77A_GENERIC=35x['CRLF' 35x] 0-19</p>
syntax.ERIF77A_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F77A> code word.</p> <p>Example syntax.ERIF77A_SPECIFIC=700x</p>
syntax.ERIF79_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F79> code word.</p> <p>Example syntax.ERIF79_GENERIC=50x['CRLF' 50x] 0-34</p>
syntax.ERIF79_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F79> code word.</p> <p>Example syntax.ERIF79_SPECIFIC=1750x</p>
syntax.ERIF86_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F86> code word.</p> <p>Example syntax.ERIF86_GENERIC=65x['CRLF' 65x] 0-5</p>

Property	Description
syntax.ERIF86_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F86> code word.</p> <p>Example syntax.ERIF86_SPECIFIC=390x</p>
syntax.F72_OTHER	<p>Defines syntax to validate field 72 where no special function validation is needed.</p> <p>Example syntax.F72_OTHER=35x['CRLF' 35x] 0-5</p>
syntax.F79_OTHER	<p>Defines syntax to validate field 79 where no special function validation is needed.</p> <p>Example syntax.F79_OTHER=50x['CRLF' 50x] 0-34</p>
syntax.FLD72	<p>Defines specific syntax for <FLD72>.</p> <p>Example syntax.FLD72=<INSTR>['CRLF' ((<INSTR>) ('/' 33x))] 0-5</p>
syntax.FLD79	<p>Defines specific syntax for <FLD79>.</p> <p>Note: Unlike <FLD72>, the specific syntax does not use the special function <INSTR>.</p> <p>Example syntax.FLD79=50x['CRLF' 50x] 0-34</p>
syntax.FLD72_NOT_STP	<p>Defines specific syntax for <FLD72_not_STP>.</p> <p>Example syntax.FLD72_NOT_STP=<INSTR>['CRLF' ((<INSTR>) ('/' 33x))] 0-5</p>
syntax.FLD72_STP	<p>Defines specific syntax for <FLD72_STP>.</p> <p>Example syntax.FLD72_STP=<INSTR>['CRLF' ((<INSTR>) ('/' 33x))] 0-5</p>
syntax.FLD72_STP_INS	<p>Defines specific syntax for the /INS format used by <FLD72_STP>.</p> <p>Example syntax.FLD72_STP_INS=' /INS/' ((<SWIFTBIC>) (<NON-SWIFTBIC>))</p>
syntax.REJTRETN72_GENERIC	<p>Defines generic syntax for <RETJT/RETN/72>.</p> <p>Example syntax.REJTRETN72_GENERIC=35x['CRLF' 35x] 0-5</p>
syntax.REJTRETN72_SPECIFIC	<p>Defines specific syntax for <RETJT/RETN/72>.</p> <p>Example syntax.REJTRETN72_SPECIFIC=6!x2!n[1a]['/' 2c] 'CRLF' (('/' 2!c2!n'/') ('/X' 1c2!n'/')) [29x] 'CRLF' '/MREF/' 16x['CRLF' '/TREF/' 16x] ['CRLF' '/CHGS/' <CUR><AMOUNT> 15] ['CRLF' '/TEXT/' 29x['CRLF' '/' 33x] 0-2]</p>

Property	Description
syntax.REJTRETN79_GENERIC	<p>Defines generic syntax for <RETJT/RETN/79>.</p> <p>Example</p> <pre>syntax.REJTRETN79_GENERIC=50x['CRLF'50x]0-34</pre>
syntax.REJTRETN79_SPECIFIC	<p>Defines specific syntax for <REJT/RETN/79>.</p> <p>Example</p> <pre>syntax.REJTRETN79_SPECIFIC=6!x2!n[1a] ['/'2c] 'CRLF' (('/'2!c2!n'/') ('/'X'1c2!n'/')) [44x] 'CRLF' /MREF/' 16x['CRLF' /TREF/'16x] ['CRLF' /CHGS/' <CUR><AMOUNT> 15] ['CRLF' /TEXT/'44x['CRLF' /'48x]0-31]</pre>
syntax.SPECIAL_FUNCTION	<p>Defines a SWIFT syntax that defines a single special function.</p> <p>Note: The [2n] component covers special functions <AMOUNT> and <NUMBER>.</p> <p>Example</p> <pre>syntax.SPECIAL_FUNCTION='<' (50c) '>' [2n]</pre>
syntax.CODEWORD_IRSX	<p>Defines the code word IRSX.</p> <p>Example</p> <pre>syntax.CODEWORD_IRSX=IRSX</pre>
syntax.CODEWORD_AMOUNT_NEGATIVE	<p>Defines a negative code word amount.</p> <p>Example</p> <pre>syntax.CODEWORD_AMOUNT_NEGATIVE=N</pre>
syntax.CODEWORD_ABIC	<p>Defines the code word /ABIC/, used for <PARTYFLD/J> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_ABIC=/ABIC/</pre>
syntax.CODEWORD_NAME	<p>Defines the code word /NAME/, used for <PARTYFLD/J> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_NAME=/NAME/</pre>
syntax.CODEWORD_REJT	<p>Defines the code word /REJT/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_REJT=/REJT/</pre>
syntax.CODEWORD_RETN	<p>Defines the code word /RETN/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_RETN=/RETN/</pre>
syntax.CODEWORD_ERI	<p>Defines the code word /OCMT/, used for ERI-related validation.</p> <p>Example</p> <pre>syntax.CODEWORD_ERI=/OCMT/</pre>
syntax.CODEWORD_INS	<p>Defines the code word /INS/, used for <FLD72_STP> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_INS=/INS/</pre>

Property	Description
<code>syntax.CODEWORD_ASCT</code>	<p>Defines the code word /ASCT/, used for <35B/ISITC/2> validation.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example <code>syntax.CODEWORD_ASCT=/ASCT/</code></p>
<code>syntax.CODEWORD_NETS</code>	<p>Defines the code word /NETS/, used for <PARTYFLD/J> validation.</p> <p>Example <code>syntax.CODEWORD_NETS=/NETS/</code></p>
<code>syntax.CODEWORD_SIS</code>	<p>Defines the code word /SSIS/, used for <PARTYFLD/J> validation.</p> <p>Example <code>syntax.CODEWORD_SIS=/SSIS/</code></p>
<code>syntax.CODEWORD_CURR</code>	<p>Defines the code word CURR, that activates validation of rule #101.</p> <p>Example <code>syntax.CODEWORD_CURR=CURR</code></p>
<code>syntax.CODEWORD_MONT</code>	<p>Defines the code word for evaluating special validation T75.</p> <p>Example <code>syntax.CODEWORD_MONT=MONT</code></p>
<code>syntax.CODEWORD_OTHR</code>	<p>Defines the code word for evaluating special validation T75.</p> <p>Example <code>syntax.CODEWORD_OTHR=OTHR</code></p>
<code>syntax.CODEWORD_ISIN</code>	<p>Defines the code word for evaluating special validation T12. Code word ISIN is used for <35B/ISITC> validation.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example <code>syntax.CODEWORD_ISIN=ISIN</code></p>
<code>group.PARTYFLDJ.formats</code>	<p>Defines the regex group numbers where code words can be found that require validation.</p> <p>Example <code>group.PARTYFLDJ.formats=4</code></p>
<code>group.genericCodeWord.[field_tag].groups</code>	<p>Defines the regex group numbers where code words can be found that require validation.</p> <p>Example <code>group.genericCodeWord.69C.groups=1</code></p>
<code>group.genericCodeWord.[field_tag].[regex_matching_group_number]</code>	<p>Defines the regex group numbers where code words can be found that require validation.</p> <p>Example <code>group.genericCodeWord.69C.1=10</code></p>
<code>group.genericCodeWord.[field_tag].[regex_matching_group_number].subfield</code>	<p>Defines the regex group numbers where code words can be found that require validation.</p> <p>Example <code>group.genericCodeWord.69D.12.subfield=3</code></p>

Property	Description
codeWords.REJTRETN72	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.REJTRETN72='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'</pre>
codeWords.REJTRETN79	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.REJTRETN79='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'</pre>
codeWords.ISITC1	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.ISITC1='AAUS', 'ACED', 'ACIN', 'ACMN', 'ACUS', 'AEUR', 'ALUX', 'AQCK', 'ASED', 'ASVM', 'AVAL', 'AWKP', 'ASICC'</pre>
codeWords.ISITC2	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.ISITC2='/ACLT/', '/ADIS/', '/AEXP/', '/AFLT/', '/AIR/', '/AMD/', '/AOC/', '/AOT/', '/APN/', '/ASC/', '/ASP/', '/ASTY/', '/ATBA/', '/ATK/', '/AYLD/', '/ASCT/'</pre>
codeWords.ISITC2.ASCT	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.ISITC2.ASCT='BA', 'CD', 'CMO', 'CORP', 'CP', 'CPP', 'CS', 'FHA', 'FHL', 'FN', 'FOR', 'FUT', 'GN', 'GOVT', 'IET', 'MF', 'MIO', 'MPO', 'MPP', 'MPT', 'MUNI', 'OPT', 'PS', 'RP', 'RVRP', 'SL', 'TD', 'USTB', 'WAR', 'ZOO'</pre>
codeWords.PARTYFLDJ	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.PARTYFLDJ='/ABIC/', '/NAME/', '/ACCT/', '/ADD1/', '/ADD2/', '/CITY/', '/USFW/', '/USCH/', '/GBSC/', '/CLRC/', '/NETS/', '/SSIS/'</pre>
codeWords.PARTYFLDJ.format [format_number]	<p>Defines special function code word lists.</p> <p>Example</p> <pre>codeWords.PARTYFLDJ.format2='/NETS/'</pre>

Property	Description
codeWords.rule.[rule_number]	Defines special function code word lists. Examples <code>codeWords.rule.5='BEID','TRCO','TESP','MCCO', 'SMDP'</code> <code>codeWords.rule.257='BEID','TRCO','TESP','MCCO', 'SMDP'</code>

translator_swift_2007.properties

The translator_swift_2007.properties file is used to set global configuration parameters for SWIFT 2007 standards.

The following caveats apply to this properties file:

- ◆ The entries have the following format:
`swiftField.[fieldTag].[subfield].[component].[message]`
- ◆ The properties for 16R and 16S are not enough for performing validation. For example, MT307 requires GENL for 16R, Sequence A and LINK for 16R, Subsequence A1. However, these properties do restrict the code words to the specified lists in the file.
- ◆ For 16R and 16 S, to complete the validation, the Map Editor must use keyfield matching and match against a constant (for example, GENL or LINK). If data is not matched then the translator notes a T13 error code.
- ◆ Field 22, subfield 2, component 1 is matched with a related field that depends on the message type. This validation is handled through the <SB-LC> special function.
- ◆ Some field tags allow any valid currency in addition to a code word validation. The CUR keyword triggers this validation which checks the external Currencies code list.

Code Word Validations for ISO 15022 Messages

The following caveats apply to this properties file for ISO 15022 messages:

- ◆ For each MT the exceptions list is displayed first (if any exceptions exist).
- ◆ The exceptions list has the following format:
`swiftField.Exceptions.<mt>[ext]`
- ◆ The code word lists are displayed by position and order within the MT.
- ◆ Non-exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext]`
- ◆ Exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext]`
- ◆ Where a subfield greater than two needs to be validated the subfield number is appended:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext].<subfield>`
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
>
- ◆ Code words are single-quoted and separated by a comma delimiter.
- ◆ Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present.
- ◆ The <errorCode> will always be the corresponding Kxx code of the field tag.
- ◆ If the field tags do not exist for related fields, a validation error is not reported at the end of translation when deferred validation entries are processed.

- ◆ If one of the choice fields exists for related fields that are part of a choice, the other field tags do not have to exist. Each message type lists the choice options for a particular sequence and field tag.

Configuration Settings

The following table describes properties used to configure the translator_swift_2007.properties file in the application:

Property	Description
swiftField.Exceptions.[message_type]	Defines swiftField properties. Example swiftField.Exceptions.504=22F.STCO
swiftField.[fieldTag].[qualifier].[message_type]	Defines swiftField properties. Example swiftField.36B.MILT.500='AMOR','FAMT','UNIT':K36
swiftField.[fieldTag].[qualifier].[sequence].[isoBlock].[message_type]	Defines swiftField properties. Example swiftField.23E.1.1.104.B='AUTH','NAUT','OTHR':T47
swiftField.[fieldTag].[qualifier].[message_type].[subfield]	Defines swiftField properties. Example swiftField.12.1.1.920='940','941','942','950':T88
swiftField.[fieldTag].[qualifier].[sequence].[isoBlock].[message_type].[subfield]	Defines swiftField properties. Example swiftField.93C.UNBA.B2.ACCTINFO.564.3='ELIG','NELG':NODSS:K93
mt.smallInputMaximum	Defines MT-specific properties. Example mt.smallInputMaximum=2000
mt.smallOutputMaximum	Defines MT-specific properties. Example mt.smallOutputMaximum=2600
mt.largeInputMaximum	Defines MT-specific properties. Example mt.largeInputMaximum=10000
mt.largeOutputMaximum	Defines MT-specific properties. Example mt.largeOutputMaximum=10600

Property	Description
mt.largeInput	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.largeInput=101,102,103,104,106,107,121,206,207, 256,300,303,304,306,307,308,320,321,330,340,341, 350,360,361,364,365,380,381,405,416,500,501,502, 503,504,505,506,507,508,509,510,513,514,515,517, 518,519,524,527,528,529,535,536,537,538,540,541, 542,543,544,545,546,547,548,549,558,564,565,566, 567,568,569,574,575,576,577,578,584,586,587,588, 589,700,701,710,711,720,721,760,767,98,198,298,398 ,498,598,698,798,898,998,9999</pre>
mt.largeOutput	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.largeOutput=101,102,103,104,106,107,121,206,207 ,256,300,303,304,306,307,308,320,321,330,340,341, 350,360,361,364,365,380,381,405,416,500,501,502, 503,504,505,506,507,508,509,510,513,514,515,517, 518,519,524,527,528,529,535,536,537,538,540,541, 542,543,544,545,546,547,548,549,558,564,565,566, 567,568,569,574,575,576,577,578,584,586,587,588, 589,700,701,710,711,720,721,760,767,98,198,298,398 ,498,598,698,798,898,998,9999</pre>
mt.rule.32	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.rule.32=300,303,304,306,320,330,340,350,360,361 ,362,364,365,405,582,600,643,645,813</pre>
mtFieldTag.F72.other	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.F72.other=192,292,392,492,592,692,792, 892,992,395,495,595,695,795,895,995,196,296,396, 496,596,696,796,896,996</pre>
mtFieldTag.F79.other	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.F79.other=960,964,965,966,967,192,292, 392,492,592,692,792,892,992,395,495,595,695,795, 895,995,196,296,396,496,596,696,796,896,996,399, 499,599,699,799,899,999</pre>
mtFieldTag.ERI.F72.narrative	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.ERI.F72.narrative=110,400,410,412,420, 422,430,450,456,516,526,559,577,581,600,601,604, 605,606,607,609,643,644,645,646,700,705,707,710, 720,730,732,734,740,742,747,750,752,754,756,760, 767,768,769,800,802,812,813,820,821,822,823,824, 900,910,935,90,190,290,390,490,590,690,790,890,990 ,91,191,291,391,491,591,691,791,891,991</pre>

Property	Description
mtFieldTag.FLD72	Defines MT-specific properties for field tag validation. Example mtFieldTag.FLD72=200,201,202,203,204,205,206, 300,303,304,305,306,320,330,340,341,350,360,361, 362,364,365,405
mtFieldTag.FLD72._STP	Defines MT-specific properties for field tag validation. Example mtFieldTag.FLD72._STP=102,103
mtFieldTag.FLD72._not_STP	Defines MT-specific properties for field tag validation. Example mtFieldTag.FLD72._not_STP=102,103
mtFieldTag.REJTRETN72	Defines MT-specific properties for field tag validation. Example mtFieldTag.REJTRETN72=102,103,104,107,110,195,200, 201,202,203,204,205,207,295
mtFieldTag.ERI.F77A	Defines MT-specific properties for field tag validation. Example mtFieldTag.ERI.F77A=416,455,456,747,754,810
mtFieldTag.ERI.F79	Defines MT-specific properties for field tag validation. Example mtFieldTag.ERI.F79=582,649,705,707,810,986
mtFieldTag.REJTRETN79	Defines MT-specific properties for field tag validation. Example mtFieldTag.REJTRETN79=195,199,295,299
mtFieldTag.SB-LC.DATE	Defines MT-specific properties for field tag validation. Example mtFieldTag.SB-LC.DATE=360,361,362,364,365
mtFieldTag.rule.89	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89=600,601,604,605,606,607,608,609
mtFieldTag.rule.89.32F	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89.32F=600,601,604,605,606,607
mtFieldTag.rule.89.60F	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89.60F=608
mtFieldTag.rule.89.60M	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89.60M=608

Property	Description
mtFieldTag.rule.89.61	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.61=608</code>
mtFieldTag.rule.89.62F	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62F=608</code>
mtFieldTag.rule.89.62M	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62M=608</code>
mtFieldTag.rule.89.64	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.64=608</code>
mtFieldTag.rule.89.65	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.65=608</code>
mtFieldTag.rule.89.68B.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68B.3.4=609</code>
mtFieldTag.rule.89.68C.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68C.3.4=609</code>
mtFieldTag.specialValidation.T75	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.specialValidation.T75=405,192,292,392,492,592,692,792,892,992,195,295,395,495,595,695,795,895,995,196,296,396,496,596,696,796,896,996</code>
fieldTags.loopRepeat	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.loopRepeat=15A,15B,15C,15D,15E,15F,15G,15H,15I,15J,15K,15L,15M,15N</code>
fieldTags.genericFields	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.genericFields=11A,12A,12B,12C,13A,13B,13J,13K,17B,19A,19B,20C,20D,22F,22H,24B,25D,36B,36C,36E,69A,69B,69C,69D,69E,69F,69J,70C,70D,70E,70F,70G,90A,90B,90E,92A,92B,92C,92D,92E,92F,92J,92K,93A,93B,93C,93D,94B,94C,94D,94F,94G,95C,95P,95Q,95R,95S,95T,95U,95V,97A,97B,97C,98A,98B,98C,98D,99A,99B</code>

Property	Description
fieldTags.checkCRLFUsage	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFUsage=35B,42A,42D,50D,51A,51D, 52A,52B,52D,53A,53B,53D,54A,54B,54D,55A,55B,55D, 56A,56B,56D,56F,57A,57B,57D,58A,58B,58D,82A,82B, 82D,83A,83D,84A,84B,84D,85A,85B,85D,86A,86B,86D, 87A,87B,87D,88A,88B,88D</pre>
fieldTags.specialExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.specialExceptions=12,12E,12F,14A,14D,14G, 14J,16R,16S,17A,17B,17F,17G,17N,17O,17R,17T,17U, 17V,22,22A,22B,22D,22E,22G,22J,22K,23,23A,23B,23C, 23D,23E,23F,23G,24D,26C,26F,28E,31X,32F,32K,33B, 33G,33K,33S,33T,35A,35H,35N,35S,35U,37K,38B,38E, 38G,38H,38J,39B,39P,40A,40B,40C,40E,40F,41A,41D, 49,50F,60F,61,62F,62M,64,65,68B,68C,71A,77H,94A</pre>
fieldTags.specialExceptions. useSpecificSyntax	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.specialExceptions.useSpecificSyntax=50F</pre>
fieldTags.noSlashesAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.noSlashesAllowed=12A,13B,20,20C,20D,21, 21A,21F,21G,21P,21R,94B,95Q,95R,95S,95T,95U,95V</pre>
fieldTags.oneOptionMustBePresent	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.oneOptionMustBePresent=52B,53B,54B,56B, 57B,58B,85B,86B,87B,88B</pre>
fieldTags.checkCRLFPairs	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFPairs=77E</pre>
fieldTags.commonMTExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.commonMTExceptions=77F,77G,77T</pre>
fieldTags.commonMTGenericExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.commonMTGenericExceptions=17B</pre>
fieldTags.MT574Exceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.MT574Exceptions=22F</pre>
fieldTags.CRLFStartsLineAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.CRLFStartsLineAllowed=15A,15B,15C,15D, 15E,15F,15G,15H,15I,15J,15K,15L,15M,15N,77E,77T</pre>

Property	Description
fieldTags.allBlanksAllowed	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.allBlanksAllowed=77E,77T</code>
fieldTags.colonStartsSecondLineAllowed	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.colonStartsSecondLineAllowed=77E,77T</code>
fieldTags.PARTYFLDJ.format [format_number]	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.PARTYFLDJ.format1=53J,56J,57J,58J,82J,84J,85J,86J,87J,88J</code>
fieldTags.specialValidation	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation=12,31X,35B,82S,68B,68C,38B,50H,42D,50D,50K,52D,53D,54D,55D,56D,57D,58D,59,82D,83D,84D,85D,86D,87D,88D</code>
fieldTags.specialValidation.Errors	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.Errors=T12,T18,T62,T70,T74,T75,T76,T77</code>
fieldTags.specialValidation.T12	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T12=35B</code>
fieldTags.specialValidation.T18	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T18=12</code>
fieldTags.specialValidation.T62	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T62=31X</code>
fieldTags.specialValidation.T70	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T70=82S</code>
fieldTags.specialValidation.T74	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T74=68B,68C</code>
fieldTags.specialValidation.T75	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T75=38B</code>
fieldTags.specialValidation.T76	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T76=50H</code>

Property	Description
fieldTags.specialValidation.T77	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T77=42D,50D,50K,52D,53D,54D,55D,56D,57D,58D,59,82D,83D,84D,85D,86D,87D,88D
fieldTags.regexSun	Defines MT-specific properties for special cases and exceptions. Note: For SUN customers only. Example fieldTags.regexSun=77C,77E
fieldTags.BICPlus.102_not_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.102_not_STP=52A,52C,57A,57C
fieldTags.BICPlus.102_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.102_STP=52A,57A
fieldTags.BICPlus.103_not_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.103_not_STP=52A,52D,56A,56C,56D,57A,57C,57D
fieldTags.BICPlus.103_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.103_STP=52A,56A,57A
fieldTags.relatedFields.[number]	Defines special related field tag properties. Example fieldTags.relatedFields.102=B.32B
fieldTags.relatedFields.Optional.[number]	Defines related fields that do not have to exist. If the field tags do not exist, then a validation error should not be reported at the end of translation when deferred validation entries are processed. Example fieldTags.relatedFields.Optional.206=C.32A
fieldTags.relatedFields.Choice. [message_type].[sequence].[field_tag]	Defines related fields that are part of a choice. If one of the choice fields exists, then the other field tags do not have to exist. Each message type lists the choice options for a particular sequence and field tag. Example fieldTags.relatedFields.Choice.405.B.32A=B.32A,B.32K
fieldTags.[field_tag].subfield2	Defines related fields for SB-LC and AMOUNT special functions. Example fieldTags.SB-LC.relatedFields.subfield2=33G,32B
fieldTags.[field_tag].relatedFields. [message_type].[sequence].[field]	Defines related fields for SB-LC and AMOUNT special functions. Example fieldTags.SB-LC.relatedFields.600.A.22=A.33G

Property	Description
fieldTags.genericCodeWordExceptions	Defines related fields for SB-LC and AMOUNT special functions. Example fieldTags.genericCodeWordExceptions=69C,69D,92E,93C,98D
fieldTags.rule.[rule_number].[number]	Defines special rule properties. These are rules that have to be implemented within the translator because they require validations using external code lists. Examples fieldTags.rule.3.100=32A,72 fieldTags.rule.5.107.B=52A,57A fieldTags.rule.101.303.C=39P fieldTags.rule.257.210=50C
fieldTags.rule.32.303.D1	Defines special rule 32 properties. These entries are exceptions to the normal C32 processing. Example fieldTags.rule.32.303.D1=32B,57A,57D,57J
syntax.[fieldtag].[messageType [extension]]	Defines syntax for a SWIFT Field Tag. If a field tag syntax does not have a message-specific syntax, the message type (and extension) are not appended to the syntax entry. Example syntax.103.97=3!a
syntax.genericCodeWord.[field_tag]	Defines special function-related syntaxes. Example syntax.genericCodeWord.69C=': '4!c'/'[8c] '/'<DATE4>'/'4!c
syntax.[special_function]	Defines special function-related syntaxes. Example syntax.ISITC2.AEXP=<DATE2>
syntax.[special_function].[format]	Defines special function-related syntaxes. Example syntax.PARTYFLDJ.NAME=' /NAME/ '34x['CRLF' 34x] 0-4
syntax.regexSun.[field_tag]	Defines special function-related syntaxes. Note: For SUN customers only. Example syntax.regexSun.77E=9800x
syntax.BICPlus	Set this property to "YES" if BIC Plus validation should be performed. Example syntax.BICPlus=YES
syntax.NON_GENERIC_FIELD	Defines a syntax for a non-generic field. Example syntax.NON_GENERIC_FIELD=': '2!n[1a] ': ' "(.*) "

Property	Description
syntax.NON_GENERIC_SYSTEM_FIELD	<p>Defines syntax for a non-generic field in a System message (for example. 096, 097).</p> <p>Example syntax.NON_GENERIC_SYSTEM_FIELD=': '2!n[1c]': ' "(.*)" "</p>
syntax.GENERIC_FIELD	<p>Defines syntax for a generic field.</p> <p>Example syntax.GENERIC_FIELD=': '2!n1a': ': '4!c'/'[8c]'/ ' "(.*)" "</p>
syntax.GENERIC_CODE_WORD	<p>Defines syntax for parsing out a qualifier, issuer or DSS, code word, and data content of a generic field. In most cases, the code word will be four characters exactly, but there are a few field tags such as 17B that have one letter code words.</p> <p>Example syntax.GENERIC_CODE_WORD=': '4!c'/'[8c]'/ '4c"(.*)" "</p>
syntax.HEADER	<p>Defines syntax for a header.</p> <p>Example syntax.HEADER='{ '3B': '(".*?") ('-' ' ')' }</p>
syntax.CC	<p>Defines syntax for the special function <CC>.</p> <p>Example syntax.CC=2!a</p>
syntax.CUR	<p>Syntax for the special function <CUR>.</p> <p>Example syntax.CUR=3!a</p>
syntax.DC_GENERIC	<p>Defines generic syntax for the special function <DC>.</p> <p>Example syntax.DC_GENERIC=1!a</p>
syntax.DC_SPECIFIC	<p>Defines specific syntax for the special function <DC>.</p> <p>Example syntax.DC_SPECIFIC='D' 'C'</p>
syntax.DM_GENERIC	<p>Defines generic for the special function <DM>.</p> <p>Example syntax.DM_GENERIC=1!a</p>
syntax.DM_SPECIFIC	<p>Defines specific syntax for the special function <DM>.</p> <p>Example syntax.DM_SPECIFIC='D' 'M'</p>
syntax.DATE1	<p>Defines syntax for the special function <DATE1>.</p> <p>Example syntax.DATE1=4!n</p>
syntax.DATE2	<p>Defines syntax for the special function <DATE2>.</p> <p>Example syntax.DATE2=6!n</p>

Property	Description
syntax.DATE3	Defines syntax for the special function <DATE3>. Example syntax.DATE3=4!n
syntax.DATE4	Defines syntax for the special function <DATE4>. Example syntax.DATE4=8!n
syntax.YEAR	Defines syntax for the special function <YEAR>. Example syntax.YEAR=4!n
syntax.HHMM	Defines syntax for the special function <HHMM>. Example syntax.HHMM=4!n
syntax.TIME2	Defines syntax for the special function <TIME2>. Example syntax.TIME2=6!n
syntax.OFFSET	Defines syntax for the special function <OFFSET>. Example syntax.OFFSET=4!n
syntax.SWIFTBIC_COPY	Defines syntax for the special function <SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.NONSWIFTBIC_COPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.SWIFTBIC_NONCOPY	Defines syntax for the special function <SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_NONCOPY=6!a2!c[3!c]
syntax.NONSWIFTBIC_NONCOPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_NONCOPY=7!c'1'[3!c]
syntax.MT	Defines syntax for the special function <MT> (message type). Example syntax.MT=3!n
syntax.SUB6_GENERIC	Defines generic syntax for the special function <SUB6>. Example syntax.SUB6_GENERIC=1!a3!c

Property	Description
syntax.SUB6_SPECIFIC	Defines specific syntax for the special function <SUB6>. Example syntax.SUB6_SPECIFIC=('S'3!n) ('N'3!c) ('F'3!c)
syntax.SBLC	Defines syntax for the special function <SB-LC>. Example syntax.SBLC=(4!a2!c)4!n(4!a2!c)
syntax.INSTR	Defines syntax for the special function <INSTR>. Example syntax.INSTR=('/'1!c'/'[32x]) ('/'2!c'/'[31x]) ('/'3!c'/'[30x]) ('/'4!c'/'[29x]) ('/'5!c'/'[28x]) ('/'6!c'/'[27x]) ('/'7!c'/'[26x]) ('/'8!c'/'[25x])
syntax.VARSEQU1_GENERIC	Defines generic syntax for the special function <VAR-SEQU-1>. Example syntax.VARSEQU1_GENERIC=34x
syntax.VARSEQU1_SPECIFIC	Defines specific syntax for the special function <VAR-SEQU-1>. Note: The special function will validate the specific syntax. Example syntax.VARSEQU1_SPECIFIC=16x['/'16x]
syntax.VARSEQU2_GENERIC	Defines generic syntax for the special function <VAR-SEQU-2>. Example syntax.VARSEQU2_GENERIC=21x
syntax.VARSEQU2_SPECIFIC	Defines specific syntax for the special function <VAR-SEQU-2>. Note: The special function will validate the specific syntax. Example syntax.VARSEQU2_SPECIFIC=16x['/'4!x]
syntax.VARSEQU3_GENERIC	Defines generic syntax for the special function <VAR-SEQU-3>. Example syntax.VARSEQU3_GENERIC=33x
syntax.VARSEQU3_SPECIFIC	Defines specific syntax for the special function <VAR-SEQU-3>. Note: The special function will validate the specific syntax. Example syntax.VARSEQU3_SPECIFIC=16x['/'16x]
syntax.VARSEQU4_GENERIC	Defines generic syntax for the special function <VAR-SEQU-4>. Example syntax.VARSEQU4_GENERIC=[14x]
syntax.VARSEQU4_SPECIFIC	Defines specific syntax for the special function <VAR-SEQU-4>. Note: The special function will validate the specific syntax. Example syntax.VARSEQU4_SPECIFIC=[4x]['/'8x]

Property	Description
syntax.ISITC	<p>Defines syntax for the special function <35B/ISITC> that is an ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC='ISIN'1e12!c'CRLF'35x['CRLF'<35B/ISITC/1>]</pre>
syntax.ISITC_NO	<p>Defines syntax for the special function <35B/ISITC> that is a non-ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC_NO=(('/'4!a'/'10x'CRLF') ('/'5!a'/'10x'CRLF')) 35x['CRLF'<35B/ISITC/2>]</pre>
syntax.ISITC1	<p>Defines syntax for the special function <35B/ISITC/1>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC1=35x['CRLF'35x]0-2</pre>
syntax.ISITC2	<p>Defines syntax for the special function <35B/ISITC/2>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC2=35x['CRLF'35x]</pre>
syntax.SIGN_GENERIC	<p>Defines generic syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_GENERIC=1!x 1!y 1!z</pre>
syntax.SIGN_SPECIFIC	<p>Defines specific syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_SPECIFIC='+' '-'</pre>
syntax.IBAN	<p>Defines syntax for the special function <IBAN>.</p> <p>Example</p> <pre>syntax.IBAN=2!A2!n1!B[29B]</pre>
syntax.PARTYFLDJ_GENERIC	<p>Defines generic syntax for <PARTYFLD/J>.</p> <p>Example</p> <pre>syntax.PARTYFLDJ_GENERIC=40x['CRLF'40x]0-4</pre>
syntax.FLD50F_GENERIC	<p>Defines generic syntax for the special function <FLD50F>.</p> <p>Example</p> <pre>syntax.FLD50F_GENERIC=35x</pre>
syntax.FLD50F_SPECIFIC	<p>Defines specific syntax for the special function <FLD50F>.</p> <p>Example</p> <pre>syntax.FLD50F_SPECIFIC=('/'34x) (4!a'/'30x)</pre>
syntax.ERI_CODEWORDS	<p>Defines syntax to validate the ERI code words format.</p> <p>Example</p> <pre>syntax.ERI_CODEWORDS=['/'OCMT/'<CUR><NUMBER>15'/' [' /CHGS/'<CUR><NUMBER>15'/']]</pre>

Property	Description
syntax.ERIF61_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F61> code word.</p> <p>Example syntax.ERIF61_GENERIC=34x</p>
syntax.ERIF61_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F61>code word.</p> <p>Example syntax.ERIF61_SPECIFIC=34x</p>
syntax.ERIFLD72_STRUCTURED_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_FLD72structured> code word.</p> <p>Example syntax.ERIFLD72_STRUCTURED_GENERIC=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</p>
syntax.ERIFLD72_STRUCTURED_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_FLD72structured> code word.</p> <p>Example syntax.ERIFLD72_STRUCTURED_SPECIFIC=210x</p>
syntax.ERIF72_NARRATIVE_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F72narrative> code word.</p> <p>Example syntax.ERIF72_NARRATIVE_GENERIC=35x['CRLF' 35x] 0-5</p>
syntax.ERIF72_NARRATIVE_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F72narrative> code word.</p> <p>Example syntax.ERIF72_NARRATIVE_SPECIFIC=210x</p>
syntax.ERIF77A_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F77A> code word.</p> <p>Example syntax.ERIF77A_GENERIC=35x['CRLF' 35x] 0-19</p>
syntax.ERIF77A_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F77A> code word.</p> <p>Example syntax.ERIF77A_SPECIFIC=700x</p>
syntax.ERIF79_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F79> code word.</p> <p>Example syntax.ERIF79_GENERIC=50x['CRLF' 50x] 0-34</p>
syntax.ERIF79_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F79> code word.</p> <p>Example syntax.ERIF79_SPECIFIC=1750x</p>

Property	Description
syntax.ERIF86_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F86> code word.</p> <p>Example syntax.ERIF86_GENERIC=65x['CRLF' 65x] 0-5</p>
syntax.ERIF86_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F86> code word.</p> <p>Example syntax.ERIF86_SPECIFIC=390x</p>
syntax.F72_OTHER	<p>Defines syntax to validate field 72 where no special function validation is needed.</p> <p>Example syntax.F72_OTHER=35x['CRLF' 35x] 0-5</p>
syntax.F79_OTHER	<p>Defines syntax to validate field 79 where no special function validation is needed.</p> <p>Example syntax.F79_OTHER=50x['CRLF' 50x] 0-34</p>
syntax.FLD72	<p>Defines specific syntax for <FLD72>.</p> <p>Example syntax.FLD72=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</p>
syntax.FLD79	<p>Defines specific syntax for <FLD79>.</p> <p>Note: Unlike <FLD72>, the specific syntax does not use the special function <INSTR>.</p> <p>Example syntax.FLD79=50x['CRLF' 50x] 0-34</p>
syntax.FLD72_NOT_STP	<p>Defines specific syntax for <FLD72_not_STP>.</p> <p>Example syntax.FLD72_NOT_STP=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</p>
syntax.FLD72_STP	<p>Defines specific syntax for <FLD72_STP>.</p> <p>Example syntax.FLD72_STP=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</p>
syntax.FLD72_STP_INS	<p>Defines specific syntax for the /INS format used by <FLD72_STP>.</p> <p>Example syntax.FLD72_STP_INS= ' /INS/ ' ((<SWIFTBIC>) (<NON-SWIFTBIC>))</p>
syntax.REJTRETN72_GENERIC	<p>Defines generic syntax for <RETJT/RETN/72>.</p> <p>Example syntax.REJTRETN72_GENERIC=35x['CRLF' 35x] 0-5</p>

Property	Description
syntax.REJTRETN72_SPECIFIC	<p>Defines specific syntax for <RETJT/RETN/72>.</p> <p>Example</p> <pre>syntax.REJTRETN72_SPECIFIC=6!x2!n[1a] ['/'2c] 'CRLF' (('/'2!c2!n'/') ('/'X'1c2!n'/')) [29x] 'CRLF' /MREF/ ' 16x['CRLF' /TREF/ '16x] ['CRLF' /CHGS/ '<CUR><AMOUNT> 15] ['CRLF' /TEXT/ '29x['CRLF' // '33x] 0-2]</pre>
syntax.REJTRETN79_GENERIC	<p>Defines generic syntax for <RETJT/RETN/79>.</p> <p>Example</p> <pre>syntax.REJTRETN79_GENERIC=50x['CRLF' 50x] 0-34</pre>
syntax.REJTRETN79_SPECIFIC	<p>Defines specific syntax for <REJT/RETN/79>.</p> <p>Example</p> <pre>syntax.REJTRETN79_SPECIFIC=6!x2!n[1a] ['/'2c] 'CRLF' (('/'2!c2!n'/') ('/'X'1c2!n'/')) [44x] 'CRLF' /MREF/ ' 16x['CRLF' /TREF/ '16x] ['CRLF' /CHGS/ '<CUR><AMOUNT> 15] ['CRLF' /TEXT/ '44x['CRLF' // '48x] 0-31]</pre>
syntax.SPECIAL_FUNCTION	<p>Defines a SWIFT syntax that defines a single special function.</p> <p>Note: The [2n] component covers special functions <AMOUNT> and <NUMBER>.</p> <p>Example</p> <pre>syntax.SPECIAL_FUNCTION='<' (50c) '>' [2n]</pre>
syntax.CODEWORD_IRSX	<p>Defines the code word IRSX.</p> <p>Example</p> <pre>syntax.CODEWORD_IRSX=IRSX</pre>
syntax.CODEWORD_AMOUNT_NEGATIVE	<p>Defines a negative code word amount.</p> <p>Example</p> <pre>syntax.CODEWORD_AMOUNT_NEGATIVE=N</pre>
syntax.CODEWORD_ABIC	<p>Defines the code word /ABIC/, used for <PARTYFLD/J> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_ABIC=/ABIC/</pre>
syntax.CODEWORD_NAME	<p>Defines the code word /NAME/, used for <PARTYFLD/J> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_NAME=/NAME/</pre>
syntax.CODEWORD_REJT	<p>Defines the code word /REJT/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_REJT=/REJT/</pre>
syntax.CODEWORD_RETN	<p>Defines the code word /RETN/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_RETN=/RETN/</pre>
syntax.CODEWORD_ERI	<p>Defines the code word /OCMT/, used for ERI-related validation.</p> <p>Example</p> <pre>syntax.CODEWORD_ERI=/OCMT/</pre>

Property	Description
syntax.CODEWORD_INS	Defines the code word /INS/, used for <FLD72_STP> validation. Example syntax.CODEWORD_INS=/INS/
syntax.CODEWORD_ASCT	Defines the code word /ASCT/, used for <35B/ISITC/2> validation. Note: The ISITC functions are now DEPRECATED. Example syntax.CODEWORD_ASCT=/ASCT/
syntax.CODEWORD_NETS	Defines the code word /NETS/, used for <PARTYFLD/J> validation. Example syntax.CODEWORD_NETS=/NETS/
syntax.CODEWORD_SIS	Defines the code word /SSIS/, used for <PARTYFLD/J> validation. Example syntax.CODEWORD_SIS=/SSIS/
syntax.CODEWORD_CURR	Defines the code word CURR, that activates validation of rule #101. Example syntax.CODEWORD_CURR=CURR
syntax.CODEWORD_MONT	Defines the code word for evaluating special validation T75. Example syntax.CODEWORD_MONT=MONT
syntax.CODEWORD_OTHR	Defines the code word for evaluating special validation T75. Example syntax.CODEWORD_OTHR=OTHR
syntax.CODEWORD_ISIN	Defines the code word for evaluating special validation T12. Code word ISIN is used for <35B/ISITC> validation. Note: The ISITC functions are now DEPRECATED. Example syntax.CODEWORD_ISIN=ISIN
group.PARTYFLDJ.formats	Defines the regex group numbers where code words can be found that require validation. Example group.PARTYFLDJ.formats=4
group.genericCodeWord.[field_tag].groups	Defines the regex group numbers where code words can be found that require validation. Example group.genericCodeWord.69C.groups=1
group.genericCodeWord.[field_tag].[regex_matching_group_number]	Defines the regex group numbers where code words can be found that require validation. Example group.genericCodeWord.69C.1=10

Property	Description
group.genericCodeWord.[field_tag]. [regex_matching_group_number].subfield	<p>Defines the regex group numbers where code words can be found that require validation.</p> <p>Example</p> <pre>group.genericCodeWord.69D.12.subfield=3</pre>
codeWords.REJTRETN72	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.REJTRETN72='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'</pre>
codeWords.REJTRETN79	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.REJTRETN79='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'</pre>
codeWords.ISITC1	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.ISITC1='AAUS', 'ACED', 'ACIN', 'ACMN', 'ACUS', 'AEUR', 'ALUX', 'AQCK', 'ASED', 'ASVM', 'AVAL', 'AWKP', 'ASICC'</pre>
codeWords.ISITC2	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.ISITC2='/ACLT/', '/ADIS/', '/AEXP/', '/AFLT/', '/AIR/', '/AMD/', '/AOC/', '/AOT/', '/APN/', '/ASC/', '/ASP/', '/ASTY/', '/ATBA/', '/ATK/', '/AYLD/', '/ASCT/'</pre>

Property	Description
codeWords.ISITC2.ASCT	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.ISITC2.ASCT='BA','CD','CMO','CORP','CP', 'CPP','CS','FHA','FHL','FN','FOR','FUT','GN','GOVT', 'IET','MF','MIO','MPO','MPP','MPT','MUNI','OPT', 'PS','RP','RVRP','SL','TD','USTB','WAR','ZOO'</pre>
codeWords.PARTYFLDJ	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.PARTYFLDJ='/ABIC/','/NAME/','/ACCT/','/ADD1/','/ADD2/','/CITY/','/USFW/','/USCH/','/GBSC/','/CLRC/','/NETS/','/SSIS/'</pre>
codeWords.PARTYFLDJ.format [format_number]	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.PARTYFLDJ.format2='/NETS/'</pre>
codeWords.rule.[rule_number]	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Examples</p> <pre>codeWords.rule.5='BEID','TRCO','TESP','MCCO', 'SMDP' codeWords.rule.257='BEID','TRCO','TESP','MCCO', 'SMDP'</pre>

translator_swift_2008.properties

The translator_swift_2008.properties file is used to set global configuration parameters for SWIFT 2008 standards.

The following caveats apply to this properties file:

- ◆ The entries have the following format:
`swiftField.[fieldTag].[subfield].[component].[message]`
- ◆ The properties for 16R and 16S are not enough for performing validation. For example, MT307 requires GENL for 16R, Sequence A and LINK for 16R, Subsequence A1. However, these properties do restrict the code words to the specified lists in the file.
- ◆ For 16R and 16 S, to complete the validation, the Map Editor must use keyfield matching and match against a constant (for example, GENL or LINK). If data is not matched then the translator notes a T13 error code.
- ◆ Field 22, subfield 2, component 1 is matched with a related field that depends on the message type. This validation is handled through the <SB-LC> special function.
- ◆ Some field tags allow any valid currency in addition to a code word validation. The CUR keyword triggers this validation which checks the external Currencies code list.

Code Word Validations for ISO 15022 Messages

The following caveats apply to this properties file for ISO 15022 messages:

- ◆ For each MT the exceptions list is displayed first (if any exceptions exist).
- ◆ The exceptions list has the following format:
`swiftField.Exceptions.<mt>[ext]`
- ◆ The code word lists are displayed by position and order within the MT.
- ◆ Non-exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext]`
- ◆ Exception entries have the following format:
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext]`
- ◆ Where a subfield greater than two needs to be validated the subfield number is appended:
`swiftField.<fieldTag>.<qualifier>.<mt>[ext].<subfield>`
`swiftField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
>
- ◆ Code words are single-quoted and separated by a comma delimiter.
- ◆ Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present.
- ◆ The <errorCode> will always be the corresponding Kxx code of the field tag.
- ◆ If the field tags do not exist for related fields, a validation error is not reported at the end of translation when deferred validation entries are processed.

- ◆ If one of the choice fields exists for related fields that are part of a choice, the other field tags do not have to exist. Each message type lists the choice options for a particular sequence and field tag.

Configuration Settings

The following table describes properties used to configure the translator_swift_2008.properties file in the application:

Property	Description
swiftField.Exceptions.[message_type]	Defines swiftField properties. Example swiftField.Exceptions.504=22F.STCO
swiftField.[fieldTag].[qualifier]. [message_type]	Defines swiftField properties. Example swiftField.36B.MILT.500='AMOR','FAMT','UNIT':K36
swiftField.[fieldTag].[qualifier].[sequence].[i soBlock].[message_type]	Defines swiftField properties. Example swiftField.23E.1.1.104.B='AUTH','NAUT','OTHR':T47
swiftField.[fieldTag].[qualifier]. [message_type].[subfield]	Defines swiftField properties. Example swiftField.12.1.1.920='940','941','942','950':T88
swiftField.[fieldTag].[qualifier].[sequence].[i soBlock].[message_type].[subfield]	Defines swiftField properties. Example swiftField.93C.UNBA.B2.ACCTINFO.564.3='ELIG', 'NELG':NODSS:K93
mt.smallInputMaximum	Defines MT-specific properties. Example mt.smallInputMaximum=2000
mt.smallOutputMaximum	Defines MT-specific properties. Example mt.smallOutputMaximum=2600
mt.largeInputMaximum	Defines MT-specific properties. Example mt.largeInputMaximum=10000
mt.largeOutputMaximum	Defines MT-specific properties. Example mt.largeOutputMaximum=10600

Property	Description
mt.largeInput	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.largeInput=101,102,103,104,106,107,121,206,207, 256,300,303,304,306,307,308,320,321,330,340,341, 350,360,361,364,365,380,381,405,416,500,501,502, 503,504,505,506,507,508,509,510,513,514,515,517, 518,519,524,527,528,529,535,536,537,538,540,541, 542,543,544,545,546,547,548,549,558,564,565,566, 567,568,569,574,575,576,577,578,584,586,587,588, 589,700,701,710,711,720,721,760,767,98,198,298,398 ,498,598,698,798,898,998,9999</pre>
mt.largeOutput	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.largeOutput=101,102,103,104,106,107,121,206,207 ,256,300,303,304,306,307,308,320,321,330,340,341, 350,360,361,364,365,380,381,405,416,500,501,502, 503,504,505,506,507,508,509,510,513,514,515,517, 518,519,524,527,528,529,535,536,537,538,540,541, 542,543,544,545,546,547,548,549,558,564,565,566, 567,568,569,574,575,576,577,578,584,586,587,588, 589,700,701,710,711,720,721,760,767,98,198,298,398 ,498,598,698,798,898,998,9999</pre>
mt.rule.32	<p>Defines MT-specific properties.</p> <p>Example</p> <pre>mt.rule.32=300,303,304,306,320,330,340,350,360,361 ,362,364,365,405,582,600,643,645,813</pre>
mtFieldTag.F72.other	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.F72.other=192,292,392,492,592,692,792, 892,992,395,495,595,695,795,895,995,196,296,396, 496,596,696,796,896,996</pre>
mtFieldTag.F79.other	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.F79.other=960,964,965,966,967,192,292, 392,492,592,692,792,892,992,395,495,595,695,795, 895,995,196,296,396,496,596,696,796,896,996,399, 499,599,699,799,899,999</pre>
mtFieldTag.ERI.F72.narrative	<p>Defines MT-specific properties for field tag validation.</p> <p>Example</p> <pre>mtFieldTag.ERI.F72.narrative=110,400,410,412,420, 422,430,450,456,516,526,559,577,581,600,601,604, 605,606,607,609,643,644,645,646,700,705,707,710, 720,730,732,734,740,742,747,750,752,754,756,760, 767,768,769,800,802,812,813,820,821,822,823,824, 900,910,935,90,190,290,390,490,590,690,790,890,990 ,91,191,291,391,491,591,691,791,891,991</pre>

Property	Description
mtFieldTag.FLD72	Defines MT-specific properties for field tag validation. Example mtFieldTag.FLD72=200,201,202,203,204,205,206, 300,303,304,305,306,320,330,340,341,350,360,361, 362,364,365,405
mtFieldTag.FLD72._STP	Defines MT-specific properties for field tag validation. Example mtFieldTag.FLD72._STP=102,103
mtFieldTag.FLD72._not_STP	Defines MT-specific properties for field tag validation. Example mtFieldTag.FLD72._not_STP=102,103
mtFieldTag.REJTRETN72	Defines MT-specific properties for field tag validation. Example mtFieldTag.REJTRETN72=102,103,104,107,110,195,200, 201,202,203,204,205,207,295
mtFieldTag.ERI.F77A	Defines MT-specific properties for field tag validation. Example mtFieldTag.ERI.F77A=416,455,456,747,754,810
mtFieldTag.ERI.F79	Defines MT-specific properties for field tag validation. Example mtFieldTag.ERI.F79=582,649,705,707,810,986
mtFieldTag.REJTRETN79	Defines MT-specific properties for field tag validation. Example mtFieldTag.REJTRETN79=195,199,295,299
mtFieldTag.SB-LC.DATE	Defines MT-specific properties for field tag validation. Example mtFieldTag.SB-LC.DATE=360,361,362,364,365
mtFieldTag.rule.89	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89=600,601,604,605,606,607,608,609
mtFieldTag.rule.89.32F	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89.32F=600,601,604,605,606,607
mtFieldTag.rule.89.60F	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89.60F=608
mtFieldTag.rule.89.60M	Defines MT-specific properties for field tag validation. Example mtFieldTag.rule.89.60M=608

Property	Description
mtFieldTag.rule.89.61	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.61=608</code>
mtFieldTag.rule.89.62F	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62F=608</code>
mtFieldTag.rule.89.62M	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.62M=608</code>
mtFieldTag.rule.89.64	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.64=608</code>
mtFieldTag.rule.89.65	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.65=608</code>
mtFieldTag.rule.89.68B.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68B.3.4=609</code>
mtFieldTag.rule.89.68C.3.4	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.rule.89.68C.3.4=609</code>
mtFieldTag.specialValidation.T75	Defines MT-specific properties for field tag validation. Example <code>mtFieldTag.specialValidation.T75=405,192,292,392,492,592,692,792,892,992,195,295,395,495,595,695,795,895,995,196,296,396,496,596,696,796,896,996</code>
fieldTags.loopRepeat	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.loopRepeat=15A,15B,15C,15D,15E,15F,15G,15H,15I,15J,15K,15L,15M,15N</code>
fieldTags.genericFields	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.genericFields=11A,12A,12B,12C,13A,13B,13J,13K,17B,19A,19B,20C,20D,22F,22H,24B,25D,36B,36C,36E,69A,69B,69C,69D,69E,69F,69J,70C,70D,70E,70F,70G,90A,90B,90E,92A,92B,92C,92D,92E,92F,92J,92K,93A,93B,93C,93D,94B,94C,94D,94F,94G,95C,95P,95Q,95R,95S,95T,95U,95V,97A,97B,97C,98A,98B,98C,98D,99A,99B</code>

Property	Description
fieldTags.checkCRLFUsage	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFUsage=35B,42A,42D,50D,51A,51D, 52A,52B,52D,53A,53B,53D,54A,54B,54D,55A,55B,55D, 56A,56B,56D,56F,57A,57B,57D,58A,58B,58D,82A,82B, 82D,83A,83D,84A,84B,84D,85A,85B,85D,86A,86B,86D, 87A,87B,87D,88A,88B,88D</pre>
fieldTags.specialExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.specialExceptions=12,12E,12F,14A,14D,14G, 14J,16R,16S,17A,17B,17F,17G,17N,17O,17R,17T,17U, 17V,22,22A,22B,22D,22E,22G,22J,22K,23,23A,23B,23C, 23D,23E,23F,23G,24D,26C,26F,28E,31X,32F,32K,33B, 33G,33K,33S,33T,35A,35H,35N,35S,35U,37K,38B,38E, 38G,38H,38J,39B,39P,40A,40B,40C,40E,40F,41A,41D, 49,50F,60F,61,62F,62M,64,65,68B,68C,71A,77H,94A</pre>
fieldTags.specialExceptions. useSpecificSyntax	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.specialExceptions.useSpecificSyntax=50F</pre>
fieldTags.noSlashesAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.noSlashesAllowed=12A,13B,20,20C,20D,21, 21A,21F,21G,21P,21R,94B,95Q,95R,95S,95T,95U,95V</pre>
fieldTags.oneOptionMustBePresent	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.oneOptionMustBePresent=52B,53B,54B,56B, 57B,58B,85B,86B,87B,88B</pre>
fieldTags.checkCRLFPairs	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.checkCRLFPairs=77E</pre>
fieldTags.commonMTExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.commonMTExceptions=77F,77G,77T</pre>
fieldTags.commonMTGenericExceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.commonMTGenericExceptions=17B</pre>
fieldTags.MT574Exceptions	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.MT574Exceptions=22F</pre>
fieldTags.CRLFStartsLineAllowed	<p>Defines MT-specific properties for special cases and exceptions.</p> <p>Example</p> <pre>fieldTags.CRLFStartsLineAllowed=15A,15B,15C,15D, 15E,15F,15G,15H,15I,15J,15K,15L,15M,15N,77E,77T</pre>

Property	Description
fieldTags.allBlanksAllowed	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.allBlanksAllowed=77E,77T</code>
fieldTags.colonStartsSecondLineAllowed	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.colonStartsSecondLineAllowed=77E,77T</code>
fieldTags.PARTYFLDJ.format [format_number]	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.PARTYFLDJ.format1=53J,56J,57J,58J,82J,84J,85J,86J,87J,88J</code>
fieldTags.specialValidation	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation=12,31X,35B,82S,68B,68C,38B,50H,42D,50D,50K,52D,53D,54D,55D,56D,57D,58D,59,82D,83D,84D,85D,86D,87D,88D</code>
fieldTags.specialValidation.Errors	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.Errors=T12,T18,T62,T70,T74,T75,T76,T77</code>
fieldTags.specialValidation.T12	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T12=35B</code>
fieldTags.specialValidation.T18	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T18=12</code>
fieldTags.specialValidation.T62	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T62=31X</code>
fieldTags.specialValidation.T70	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T70=82S</code>
fieldTags.specialValidation.T74	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T74=68B,68C</code>
fieldTags.specialValidation.T75	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T75=38B</code>
fieldTags.specialValidation.T76	Defines MT-specific properties for special cases and exceptions. Example <code>fieldTags.specialValidation.T76=50H</code>

Property	Description
fieldTags.specialValidation.T77	Defines MT-specific properties for special cases and exceptions. Example fieldTags.specialValidation.T77=42D,50D,50K,52D,53D,54D,55D,56D,57D,58D,59,82D,83D,84D,85D,86D,87D,88D
fieldTags.regexSun	Defines MT-specific properties for special cases and exceptions. Note: For SUN customers only. Example fieldTags.regexSun=77C,77E
fieldTags.BICPlus.102_not_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.102_not_STP=52A,52C,57A,57C
fieldTags.BICPlus.102_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.102_STP=52A,57A
fieldTags.BICPlus.103_not_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.103_not_STP=52A,52D,56A,56C,56D,57A,57C,57D
fieldTags.BICPlus.103_STP	Defines MT-specific properties for special cases and exceptions. Example fieldTags.BICPlus.103_STP=52A,56A,57A
fieldTags.relatedFields.[number]	Defines special related field tag properties. Example fieldTags.relatedFields.102=B.32B
fieldTags.relatedFields.Optional.[number]	Defines related fields that do not have to exist. If the field tags do not exist, then a validation error should not be reported at the end of translation when deferred validation entries are processed. Example fieldTags.relatedFields.Optional.206=C.32A
fieldTags.relatedFields.Choice. [message_type].[sequence].[field_tag]	Defines related fields that are part of a choice. If one of the choice fields exists, then the other field tags do not have to exist. Each message type lists the choice options for a particular sequence and field tag. Example fieldTags.relatedFields.Choice.405.B.32A=B.32A,B.32K
fieldTags.[field_tag].subfield2	Defines related fields for SB-LC and AMOUNT special functions. Example fieldTags.SB-LC.relatedFields.subfield2=33G,32B
fieldTags.[field_tag].relatedFields. [message_type].[sequence].[field]	Defines related fields for SB-LC and AMOUNT special functions. Example fieldTags.SB-LC.relatedFields.600.A.22=A.33G

Property	Description
fieldTags.genericCodeWordExceptions	Defines related fields for SB-LC and AMOUNT special functions. Example fieldTags.genericCodeWordExceptions=69C,69D,92E,93C,98D
fieldTags.rule.[rule_number].[number]	Defines special rule properties. These are rules that have to be implemented within the translator because they require validations using external code lists. Examples fieldTags.rule.3.100=32A,72 fieldTags.rule.5.107.B=52A,57A fieldTags.rule.101.303.C=39P fieldTags.rule.257.210=50C
fieldTags.rule.32.303.D1	Defines special rule 32 properties. These entries are exceptions to the normal C32 processing. Example fieldTags.rule.32.303.D1=32B,57A,57D,57J
syntax.[fieldtag].[messageType [extension]]	Defines syntax for a SWIFT Field Tag. If a field tag syntax does not have a message-specific syntax, the message type (and extension) are not appended to the syntax entry. Example syntax.103.97=3!a
syntax.genericCodeWord.[field_tag]	Defines special function-related syntaxes. Example syntax.genericCodeWord.69C=': '4!c'/'[8c] '/'<DATE4>'/'4!c
syntax.[special_function]	Defines special function-related syntaxes. Example syntax.ISITC2.AEXP=<DATE2>
syntax.[special_function].[format]	Defines special function-related syntaxes. Example syntax.PARTYFLDJ.NAME=' /NAME/ '34x['CRLF' 34x] 0-4
syntax.regexSun.[field_tag]	Defines special function-related syntaxes. Note: For SUN customers only. Example syntax.regexSun.77E=9800x
syntax.BICPlus	Set this property to "YES" if BIC Plus validation should be performed. Example syntax.BICPlus=YES
syntax.NON_GENERIC_FIELD	Defines a syntax for a non-generic field. Example syntax.NON_GENERIC_FIELD=': '2!n[1a] ':' (.*)

Property	Description
syntax.NON_GENERIC_SYSTEM_FIELD	<p>Defines syntax for a non-generic field in a System message (for example. 096, 097).</p> <p>Example <code>syntax.NON_GENERIC_SYSTEM_FIELD=': '2!n[1c]': '(.*)'</code></p>
syntax.GENERIC_FIELD	<p>Defines syntax for a generic field.</p> <p>Example <code>syntax.GENERIC_FIELD=': '2!n1a': '4!c'/'[8c]''/ '(.*)'</code></p>
syntax.GENERIC_CODE_WORD	<p>Defines syntax for parsing out a qualifier, issuer or DSS, code word, and data content of a generic field. In most cases, the code word will be four characters exactly, but there are a few field tags such as 17B that have one letter code words.</p> <p>Example <code>syntax.GENERIC_CODE_WORD=': '4!c'/'[8c]''/'4c'(.*)'</code></p>
syntax.HEADER	<p>Defines syntax for a header.</p> <p>Example <code>syntax.HEADER='{ '3B': '(. *?)" ('-}' ')'</code></p>
syntax.CC	<p>Defines syntax for the special function <CC>.</p> <p>Example <code>syntax.CC=2!a</code></p>
syntax.CUR	<p>Syntax for the special function <CUR>.</p> <p>Example <code>syntax.CUR=3!a</code></p>
syntax.DC_GENERIC	<p>Defines generic syntax for the special function <DC>.</p> <p>Example <code>syntax.DC_GENERIC=1!a</code></p>
syntax.DC_SPECIFIC	<p>Defines specific syntax for the special function <DC>.</p> <p>Example <code>syntax.DC_SPECIFIC='D' 'C'</code></p>
syntax.DM_GENERIC	<p>Defines generic for the special function <DM>.</p> <p>Example <code>syntax.DM_GENERIC=1!a</code></p>
syntax.DM_SPECIFIC	<p>Defines specific syntax for the special function <DM>.</p> <p>Example <code>syntax.DM_SPECIFIC='D' 'M'</code></p>
syntax.DATE1	<p>Defines syntax for the special function <DATE1>.</p> <p>Example <code>syntax.DATE1=4!n</code></p>
syntax.DATE2	<p>Defines syntax for the special function <DATE2>.</p> <p>Example <code>syntax.DATE2=6!n</code></p>

Property	Description
syntax.DATE3	Defines syntax for the special function <DATE3>. Example syntax.DATE3=4!n
syntax.DATE4	Defines syntax for the special function <DATE4>. Example syntax.DATE4=8!n
syntax.YEAR	Defines syntax for the special function <YEAR>. Example syntax.YEAR=4!n
syntax.HHMM	Defines syntax for the special function <HHMM>. Example syntax.HHMM=4!n
syntax.TIME2	Defines syntax for the special function <TIME2>. Example syntax.TIME2=6!n
syntax.OFFSET	Defines syntax for the special function <OFFSET>. Example syntax.OFFSET=4!n
syntax.SWIFTBIC_COPY	Defines syntax for the special function <SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.NONSWIFTBIC_COPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used within the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_COPY=4!a2!a1!c1!c[3!c]
syntax.SWIFTBIC_NONCOPY	Defines syntax for the special function <SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.SWIFTBIC_NONCOPY=6!a2!c[3!c]
syntax.NONSWIFTBIC_NONCOPY	Defines syntax for the special function <NON-SWIFTBIC> where it is used outside the context of the copy fields of the common message groups. Example syntax.NONSWIFTBIC_NONCOPY=7!c'1'[3!c]
syntax.MT	Defines syntax for the special function <MT> (message type). Example syntax.MT=3!n
syntax.SUB6_GENERIC	Defines generic syntax for the special function <SUB6>. Example syntax.SUB6_GENERIC=1!a3!c

Property	Description
syntax.SUB6_SPECIFIC	Defines specific syntax for the special function <SUB6>. Example syntax.SUB6_SPECIFIC=('S'3!n) ('N'3!c) ('F'3!c)
syntax.SBLC	Defines syntax for the special function <SB-LC>. Example syntax.SBLC=(4!a2!c)4!n(4!a2!c)
syntax.INSTR	Defines syntax for the special function <INSTR>. Example syntax.INSTR=('/'1!c'/'[32x]) ('/'2!c'/'[31x]) ('/'3!c'/'[30x]) ('/'4!c'/'[29x]) ('/'5!c'/'[28x]) ('/'6!c'/'[27x]) ('/'7!c'/'[26x]) ('/'8!c'/'[25x])
syntax.VARSEQU1_GENERIC	Defines generic syntax for the special function <VAR-SEQU-1>. Example syntax.VARSEQU1_GENERIC=34x
syntax.VARSEQU1_SPECIFIC	Defines specific syntax for the special function <VAR-SEQU-1>. Note: The special function will validate the specific syntax. Example syntax.VARSEQU1_SPECIFIC=16x['/'16x]
syntax.VARSEQU2_GENERIC	Defines generic syntax for the special function <VAR-SEQU-2>. Example syntax.VARSEQU2_GENERIC=21x
syntax.VARSEQU2_SPECIFIC	Defines specific syntax for the special function <VAR-SEQU-2>. Note: The special function will validate the specific syntax. Example syntax.VARSEQU2_SPECIFIC=16x['/'4!x]
syntax.VARSEQU3_GENERIC	Defines generic syntax for the special function <VAR-SEQU-3>. Example syntax.VARSEQU3_GENERIC=33x
syntax.VARSEQU3_SPECIFIC	Defines specific syntax for the special function <VAR-SEQU-3>. Note: The special function will validate the specific syntax. Example syntax.VARSEQU3_SPECIFIC=16x['/'16x]
syntax.VARSEQU4_GENERIC	Defines generic syntax for the special function <VAR-SEQU-4>. Example syntax.VARSEQU4_GENERIC=[14x]
syntax.VARSEQU4_SPECIFIC	Defines specific syntax for the special function <VAR-SEQU-4>. Note: The special function will validate the specific syntax. Example syntax.VARSEQU4_SPECIFIC=[4x] ['/'8x]

Property	Description
syntax.ISITC	<p>Defines syntax for the special function <35B/ISITC> that is an ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC='ISIN'1e12!c'CRLF'35x['CRLF'<35B/ISITC/1>]</pre>
syntax.ISITC_NO	<p>Defines syntax for the special function <35B/ISITC> that is a non-ISIN format.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC_NO=(('/'4!a'/'10x'CRLF') ('/'5!a'/'10x'CRLF'))35x['CRLF'<35B/ISITC/2>]</pre>
syntax.ISITC1	<p>Defines syntax for the special function <35B/ISITC/1>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC1=35x['CRLF'35x]0-2</pre>
syntax.ISITC2	<p>Defines syntax for the special function <35B/ISITC/2>.</p> <p>Note: The ISITC functions are now DEPRECATED.</p> <p>Example</p> <pre>syntax.ISITC2=35x['CRLF'35x]</pre>
syntax.SIGN_GENERIC	<p>Defines generic syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_GENERIC=1!x 1!y 1!z</pre>
syntax.SIGN_SPECIFIC	<p>Defines specific syntax for the special function <SIGN>.</p> <p>Example</p> <pre>syntax.SIGN_SPECIFIC='+' '-'</pre>
syntax.IBAN	<p>Defines syntax for the special function <IBAN>.</p> <p>Example</p> <pre>syntax.IBAN=2!A2!n1!B[29B]</pre>
syntax.PARTYFLDJ_GENERIC	<p>Defines generic syntax for <PARTYFLD/J>.</p> <p>Example</p> <pre>syntax.PARTYFLDJ_GENERIC=40x['CRLF'40x]0-4</pre>
syntax.FLD50F_GENERIC	<p>Defines generic syntax for the special function <FLD50F>.</p> <p>Example</p> <pre>syntax.FLD50F_GENERIC=35x</pre>
syntax.FLD50F_SPECIFIC	<p>Defines specific syntax for the special function <FLD50F>.</p> <p>Example</p> <pre>syntax.FLD50F_SPECIFIC=('/'34x) (4!a'/'30x)</pre>
syntax.ERI_CODEWORDS	<p>Defines syntax to validate the ERI code words format.</p> <p>Example</p> <pre>syntax.ERI_CODEWORDS=['/OCMT/'<CUR><NUMBER>15'/' ['/CHGS/'<CUR><NUMBER>15'/']]</pre>

Property	Description
syntax.ERIF61_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F61> code word.</p> <p>Example syntax.ERIF61_GENERIC=34x</p>
syntax.ERIF61_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F61>code word.</p> <p>Example syntax.ERIF61_SPECIFIC=34x</p>
syntax.ERIFLD72_STRUCTURED_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_FLD72structured> code word.</p> <p>Example syntax.ERIFLD72_STRUCTURED_GENERIC=<INSTR> ['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</p>
syntax.ERIFLD72_STRUCTURED_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_FLD72structured> code word.</p> <p>Example syntax.ERIFLD72_STRUCTURED_SPECIFIC=210x</p>
syntax.ERIF72_NARRATIVE_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F72narrative> code word.</p> <p>Example syntax.ERIF72_NARRATIVE_GENERIC=35x['CRLF' 35x] 0-5</p>
syntax.ERIF72_NARRATIVE_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F72narrative> code word.</p> <p>Example syntax.ERIF72_NARRATIVE_SPECIFIC=210x</p>
syntax.ERIF77A_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F77A> code word.</p> <p>Example syntax.ERIF77A_GENERIC=35x['CRLF' 35x] 0-19</p>
syntax.ERIF77A_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F77A> code word.</p> <p>Example syntax.ERIF77A_SPECIFIC=700x</p>
syntax.ERIF79_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F79> code word.</p> <p>Example syntax.ERIF79_GENERIC=50x['CRLF' 50x] 0-34</p>
syntax.ERIF79_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F79> code word.</p> <p>Example syntax.ERIF79_SPECIFIC=1750x</p>

Property	Description
syntax.ERIF86_GENERIC	<p>Defines syntax to validate the generic format of the <ERI_F86> code word.</p> <p>Example syntax.ERIF86_GENERIC=65x['CRLF' 65x] 0-5</p>
syntax.ERIF86_SPECIFIC	<p>Defines syntax to validate the specific format of the <ERI_F86> code word.</p> <p>Example syntax.ERIF86_SPECIFIC=390x</p>
syntax.F72_OTHER	<p>Defines syntax to validate field 72 where no special function validation is needed.</p> <p>Example syntax.F72_OTHER=35x['CRLF' 35x] 0-5</p>
syntax.F79_OTHER	<p>Defines syntax to validate field 79 where no special function validation is needed.</p> <p>Example syntax.F79_OTHER=50x['CRLF' 50x] 0-34</p>
syntax.FLD72	<p>Defines specific syntax for <FLD72>.</p> <p>Example syntax.FLD72=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</p>
syntax.FLD79	<p>Defines specific syntax for <FLD79>.</p> <p>Note: Unlike <FLD72>, the specific syntax does not use the special function <INSTR>.</p> <p>Example syntax.FLD79=50x['CRLF' 50x] 0-34</p>
syntax.FLD72_NOT_STP	<p>Defines specific syntax for <FLD72_not_STP>.</p> <p>Example syntax.FLD72_NOT_STP=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</p>
syntax.FLD72_STP	<p>Defines specific syntax for <FLD72_STP>.</p> <p>Example syntax.FLD72_STP=<INSTR>['CRLF' ((<INSTR>) ('/' '33x'))] 0-5</p>
syntax.FLD72_STP_INS	<p>Defines specific syntax for the /INS format used by <FLD72_STP>.</p> <p>Example syntax.FLD72_STP_INS= ' /INS/ ' ((<SWIFTBIC>) (<NON-SWIFTBIC>))</p>
syntax.REJTRETN72_GENERIC	<p>Defines generic syntax for <RETJT/RETN/72>.</p> <p>Example syntax.REJTRETN72_GENERIC=35x['CRLF' 35x] 0-5</p>

Property	Description
syntax.REJTRETN72_SPECIFIC	<p>Defines specific syntax for <RETJT/RETN/72>.</p> <p>Example</p> <pre>syntax.REJTRETN72_SPECIFIC=6!x2!n[1a] ['/' '2c] 'CRLF' (('/' '2!c2!n' '/') ('/' 'X' '1c2!n' '/')) [29x] 'CRLF' ' /MREF/ ' 16x['CRLF' ' /TREF/ '16x] ['CRLF' ' /CHGS/ ' <CUR><AMOUNT> 15] ['CRLF' ' /TEXT/ '29x['CRLF' ' // '33x] 0-2]</pre>
syntax.REJTRETN79_GENERIC	<p>Defines generic syntax for <RETJT/RETN/79>.</p> <p>Example</p> <pre>syntax.REJTRETN79_GENERIC=50x['CRLF' '50x] 0-34</pre>
syntax.REJTRETN79_SPECIFIC	<p>Defines specific syntax for <REJT/RETN/79>.</p> <p>Example</p> <pre>syntax.REJTRETN79_SPECIFIC=6!x2!n[1a] ['/' '2c] 'CRLF' (('/' '2!c2!n' '/') ('/' 'X' '1c2!n' '/')) [44x] 'CRLF' ' /MREF/ ' 16x['CRLF' ' /TREF/ '16x] ['CRLF' ' /CHGS/ ' <CUR><AMOUNT> 15] ['CRLF' ' /TEXT/ '44x['CRLF' ' // '48x] 0-31]</pre>
syntax.SPECIAL_FUNCTION	<p>Defines a SWIFT syntax that defines a single special function.</p> <p>Note: The [2n] component covers special functions <AMOUNT> and <NUMBER>.</p> <p>Example</p> <pre>syntax.SPECIAL_FUNCTION='<' (50c) '>' [2n]</pre>
syntax.CODEWORD_IRSX	<p>Defines the code word IRSX.</p> <p>Example</p> <pre>syntax.CODEWORD_IRSX=IRSX</pre>
syntax.CODEWORD_AMOUNT_NEGATIVE	<p>Defines a negative code word amount.</p> <p>Example</p> <pre>syntax.CODEWORD_AMOUNT_NEGATIVE=N</pre>
syntax.CODEWORD_ABIC	<p>Defines the code word /ABIC/, used for <PARTYFLD/J> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_ABIC=/ABIC/</pre>
syntax.CODEWORD_NAME	<p>Defines the code word /NAME/, used for <PARTYFLD/J> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_NAME=/NAME/</pre>
syntax.CODEWORD_REJT	<p>Defines the code word /REJT/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_REJT=/REJT/</pre>
syntax.CODEWORD_RETN	<p>Defines the code word /RETN/, used for <RETJT/RETN/72> and <REJT/RETN/79> validation.</p> <p>Example</p> <pre>syntax.CODEWORD_RETN=/RETN/</pre>
syntax.CODEWORD_ERI	<p>Defines the code word /OCMT/, used for ERI-related validation.</p> <p>Example</p> <pre>syntax.CODEWORD_ERI=/OCMT/</pre>

Property	Description
syntax.CODEWORD_INS	Defines the code word /INS/, used for <FLD72_STP> validation. Example syntax.CODEWORD_INS=/INS/
syntax.CODEWORD_ASCT	Defines the code word /ASCT/, used for <35B/ISITC/2> validation. Note: The ISITC functions are now DEPRECATED. Example syntax.CODEWORD_ASCT=/ASCT/
syntax.CODEWORD_NETS	Defines the code word /NETS/, used for <PARTYFLD/J> validation. Example syntax.CODEWORD_NETS=/NETS/
syntax.CODEWORD_SIS	Defines the code word /SSIS/, used for <PARTYFLD/J> validation. Example syntax.CODEWORD_SIS=/SSIS/
syntax.CODEWORD_CURR	Defines the code word CURR, that activates validation of rule #101. Example syntax.CODEWORD_CURR=CURR
syntax.CODEWORD_MONT	Defines the code word for evaluating special validation T75. Example syntax.CODEWORD_MONT=MONT
syntax.CODEWORD_OTHR	Defines the code word for evaluating special validation T75. Example syntax.CODEWORD_OTHR=OTHR
syntax.CODEWORD_ISIN	Defines the code word for evaluating special validation T12. Code word ISIN is used for <35B/ISITC> validation. Note: The ISITC functions are now DEPRECATED. Example syntax.CODEWORD_ISIN=ISIN
group.PARTYFLDJ.formats	Defines the regex group numbers where code words can be found that require validation. Example group.PARTYFLDJ.formats=4
group.genericCodeWord.[field_tag].groups	Defines the regex group numbers where code words can be found that require validation. Example group.genericCodeWord.69C.groups=1
group.genericCodeWord.[field_tag].[regex_matching_group_number]	Defines the regex group numbers where code words can be found that require validation. Example group.genericCodeWord.69C.1=10

Property	Description
group.genericCodeWord.[field_tag]. [regex_matching_group_number].subfield	<p>Defines the regex group numbers where code words can be found that require validation.</p> <p>Example</p> <pre>group.genericCodeWord.69D.12.subfield=3</pre>
codeWords.REJTRETN72	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.REJTRETN72='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'</pre>
codeWords.REJTRETN79	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.REJTRETN79='/AC01/', '/AC02/', '/AC03/', '/AC04/', '/AC05/', '/AC06/', '/AM01/', '/AM02/', '/AM03/', '/AM04/', '/AM05/', '/AM06/', '/AM07/', '/AM08/', '/AG01/', '/AG02/', '/BE01/', '/BE02/', '/BE03/', '/BE04/', '/BE05/', '/DT01/', '/MS01/', '/PY01/', '/RC01/', '/RC02/', '/RC03/', '/RC04/', '/RF01/', '/TM01/'</pre>
codeWords.ISITC1	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.ISITC1='AAUS', 'ACED', 'ACIN', 'ACMN', 'ACUS', 'AEUR', 'ALUX', 'AQCK', 'ASED', 'ASVM', 'AVAL', 'AWKP', 'ASICC'</pre>
codeWords.ISITC2	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.ISITC2='/ACLT/', '/ADIS/', '/AEXP/', '/AFLT/', '/AIR/', '/AMD/', '/AOC/', '/AOT/', '/APN/', '/ASC/', '/ASP/', '/ASTY/', '/ATBA/', '/ATK/', '/AYLD/', '/ASCT/'</pre>

Property	Description
codeWords.ISITC2.ASCT	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.ISITC2.ASCT='BA','CD','CMO','CORP','CP', 'CPP','CS','FHA','FHL','FN','FOR','FUT','GN','GOVT', 'IET','MF','MIO','MPO','MPP','MPT','MUNI','OPT', 'PS','RP','RVRP','SL','TD','USTB','WAR','ZOO'</pre>
codeWords.PARTYFLDJ	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.PARTYFLDJ='/ABIC/','/NAME/','/ACCT/','/ADD1/','/ADD2/','/CITY/','/USFW/','/USCH/','/GBSC/','/CLRC/','/NETS/','/SSIS/'</pre>
codeWords.PARTYFLDJ.format [format_number]	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Example</p> <pre>codeWords.PARTYFLDJ.format2='/NETS/'</pre>
codeWords.rule.[rule_number]	<p>Defines special function code word lists.</p> <p>Note: These are code word properties needed for validating special functions such as REJT/RETN/72 or PARTYFLDJ.</p> <p>Examples</p> <pre>codeWords.rule.5='BEID','TRCO','TESP','MCCO', 'SMDP' codeWords.rule.257='BEID','TRCO','TESP','MCCO', 'SMDP'</pre>

translator_swift_mp.properties

The translator_swift_mp.properties file is used to set global configuration parameters for SWIFT Market Practices and Fund Templates.

Special Field Exceptions and Required Code Words

The following caveats apply for special field exceptions and required code words:

- ◆ The special field exceptions and required code words properties have the following format:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>`
- ◆ If a field tag has different validation requirements in different sequences of the same message type, the sequence is appended as follows:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>.<sequence>`
- ◆ If the <mt> component is defined as an asterisk (*), all common group messages apply. For example, n92, n95, n96, where n is a Category 1 through 9.
- ◆ Some field tags allow a valid currency code in addition to a code word validation. The CUR keyword triggers this validation, which checks the external SWIFT_Currencies code list.

Code Word Validations for ISO 15022 Messages

The following caveats apply for ISO 15022 messages:

- ◆ For each MT the exceptions list is displayed first (if any exceptions exist). The exceptions list has the following format:
`mpField.Exceptions.<mt>[ext].<marketPracticeID>`
- ◆ The code word lists are displayed by position and order within the MT. Non-exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>`
- ◆ Exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<marketPracticeID>`
- ◆ Where a subfield greater than two needs to be validated, the subfield number is appended:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>.<subfield>`
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
- ◆ Code words are single-quoted and separated by a comma delimiter. Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present. The <errorCode> will always be the corresponding Kxx code of the field tag.

- ◆ See the translator_swift.properties file for similar examples. Note that the translator_swift.properties file does not use the **mpField** prefix and it does not use a market practice ID, because it is not applicable for standard SWIFT messages.

Configuration Settings

The following table describes properties used to configure the translator_swift_mp.properties file in the application:

Property	Description
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 1	
mpField.23G.1.1.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.SMPG02='CANC','NEWM':T86
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 2	
mpField.22F.TRTR.515.SMPG02	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.TRTR.515.SMPG02='TRAD':NODSS:K22
mpField.90A.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90A.DEAL.515.SMPG02='PRIC':K90
mpField.90B.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90B.DEAL.515.SMPG02='PRIC':K90
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 1	
mpField.28E.2.1.536.IOA001	Defines the codes allowed for the specified field. Example mpField.28E.2.1.536.IOA001='LAST','MORE','ONLY':T97
mpField.23G.1.1.515.IOA001	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.IOA001='NEWM':T86
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 2	

Property	Description
mpField.22F.SFRE.536.IOA001	<p>Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present.</p> <p>Example</p> <pre>mpField.22F.SFRE.536.IOA001='ADHO','DAIL','INDA','MNTH','WEEK','YEAR','ANNU','SANN':NODSS:K22</pre>
mpField.22F.CODE.536.IOA001	<p>Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present.</p> <p>Example</p> <pre>mpField.22F.CODE.536.IOA001='COMP':NODSS:K22</pre>

translator_swift_mp_2002.properties

The translator_swift_mp_2002.properties file is used to set global configuration parameters for Market Practices and Fund Templates.

Special Field Exceptions and Required Code Words

The following caveats apply for special field exceptions and required code words:

- ◆ The special field exceptions and required code words properties have the following format:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>`
- ◆ If a field tag has different validation requirements in different sequences of the same message type, the sequence is appended as follows:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>.<sequence>`
- ◆ If the <mt> component is defined as an asterisk (*), all common group messages apply. For example, n92, n95, n96, where n is a Category 1 through 9.
- ◆ Some field tags allow a valid currency code in addition to a code word validation. The CUR keyword triggers this validation, which checks the external SWIFT_Currencies code list.

Code Word Validations for ISO 15022 Messages

The following caveats apply for ISO 15022 messages:

- ◆ For each MT the exceptions list is displayed first (if any exceptions exist). The exceptions list has the following format:
`mpField.Exceptions.<mt>[ext].<marketPracticeID>`
- ◆ The code word lists are displayed by position and order within the MT. Non-exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>`
- ◆ Exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<marketPracticeID>`
- ◆ Where a subfield greater than two needs to be validated, the subfield number is appended:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>.<subfield>`
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
- ◆ Code words are single-quoted and separated by a comma delimiter. Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present. The <errorCode> will always be the corresponding Kxx code of the field tag.

- ◆ See the translator_swift.properties file for similar examples. Note that the translator_swift.properties file does not use the **mpField** prefix and it does not use a market practice ID, because it is not applicable for standard SWIFT messages.

Configuration Settings

The following table describes properties used to configure the translator_swift_mp_2002.properties file in the application:

Property	Description
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 1	
mpField.23G.1.1.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.SMPG02='CANC','NEWM':T86
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 2	
mpField.22F.TRTR.515.SMPG02	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.TRTR.515.SMPG02='TRAD':NODSS:K22
mpField.90A.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90A.DEAL.515.SMPG02='PRIC':K90
mpField.90B.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90B.DEAL.515.SMPG02='PRIC':K90
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 1	
mpField.28E.2.1.536.IOA001	Defines the codes allowed for the specified field. Example mpField.28E.2.1.536.IOA001='LAST','MORE','ONLY':T97
mpField.23G.1.1.515.IOA001	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.IOA001='NEWM':T86
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 2	
mpField.22F.SFRE.536.IOA001	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.SFRE.536.IOA001='ADHO','DAIL','INDA','MNTH','WEEK','YEAR','ANNU','SANN':NODSS:K22

Property	Description
mpField.22F.CODE.536.IOA001	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.CODE.536.IOA001='COMP':NODSS:K22

translator_swift_mp_2005.properties

The translator_swift_mp_2005.properties file is used to set global configuration parameters for Market Practices and Fund Templates.

Special Field Exceptions and Required Code Words

The following caveats apply for special field exceptions and required code words:

- ◆ The special field exceptions and required code words properties have the following format:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>`
- ◆ If a field tag has different validation requirements in different sequences of the same message type, the sequence is appended as follows:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>.<sequence>`
- ◆ If the <mt> component is defined as an asterisk (*), all common group messages apply. For example, n92, n95, n96, where n is a Category 1 through 9.
- ◆ Some field tags allow a valid currency code in addition to a code word validation. The CUR keyword triggers this validation, which checks the external SWIFT_Currencies code list.

Code Word Validations for ISO 15022 Messages

The following caveats apply for ISO 15022 messages:

- ◆ For each MT the exceptions list is displayed first (if any exceptions exist). The exceptions list has the following format:
`mpField.Exceptions.<mt>[ext].<marketPracticeID>`
- ◆ The code word lists are displayed by position and order within the MT. Non-exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>`
- ◆ Exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<marketPracticeID>`
- ◆ Where a subfield greater than two needs to be validated, the subfield number is appended:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>.<subfield>`
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
- ◆ Code words are single-quoted and separated by a comma delimiter. Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present. The <errorCode> will always be the corresponding Kxx code of the field tag.

- ◆ See the translator_swift.properties file for similar examples. Note that the translator_swift.properties file does not use the **mpField** prefix and it does not use a market practice ID, because it is not applicable for standard SWIFT messages.

Configuration Settings

The following table describes properties used to configure the translator_swift_mp_2005.properties file in the application:

Property	Description
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 1	
mpField.23G.1.1.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.SMPG02='CANC','NEWM':T86
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 2	
mpField.22F.TRTR.515.SMPG02	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.TRTR.515.SMPG02='TRAD':NODSS:K22
mpField.90A.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90A.DEAL.515.SMPG02='PRIC':K90
mpField.90B.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90B.DEAL.515.SMPG02='PRIC':K90
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 1	
mpField.28E.2.1.536.IOA001	Defines the codes allowed for the specified field. Example mpField.28E.2.1.536.IOA001='LAST','MORE','ONLY':T97
mpField.23G.1.1.515.IOA001	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.IOA001='NEWM':T86
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 2	
mpField.22F.SFRE.536.IOA001	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.SFRE.536.IOA001='ADHO','DAIL','INDA','MNTH','WEEK','YEAR','ANNU','SANN':NODSS:K22

Property	Description
mpField.22F.CODE.536.IOA001	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.CODE.536.IOA001='COMP':NODSS:K22

translator_swift_mp_2006.properties

The translator_swift_mp_2006.properties file is used to set global configuration parameters for Market Practices and Fund Templates.

Special Field Exceptions and Required Code Words

The following caveats apply for special field exceptions and required code words:

- ◆ The special field exceptions and required code words properties have the following format:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>`
- ◆ If a field tag has different validation requirements in different sequences of the same message type, the sequence is appended as follows:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>.<sequence>`
- ◆ If the <mt> component is defined as an asterisk (*), all common group messages apply. For example, n92, n95, n96, where n is a Category 1 through 9.
- ◆ Some field tags allow a valid currency code in addition to a code word validation. The CUR keyword triggers this validation, which checks the external SWIFT_Currencies code list.

Code Word Validations for ISO 15022 Messages

The following caveats apply for ISO 15022 messages:

- ◆ For each MT the exceptions list is displayed first (if any exceptions exist). The exceptions list has the following format:
`mpField.Exceptions.<mt>[ext].<marketPracticeID>`
- ◆ The code word lists are displayed by position and order within the MT. Non-exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>`
- ◆ Exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<marketPracticeID>`
- ◆ Where a subfield greater than two needs to be validated, the subfield number is appended:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>.<subfield>`
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
- ◆ Code words are single-quoted and separated by a comma delimiter. Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present. The <errorCode> will always be the corresponding Kxx code of the field tag.

- ◆ See the translator_swift.properties file for similar examples. Note that the translator_swift.properties file does not use the **mpField** prefix and it does not use a market practice ID, because it is not applicable for standard SWIFT messages.

Configuration Settings

The following table describes properties used to configure the translator_swift_mp_2006.properties file in the application:

Property	Description
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 1	
mpField.23G.1.1.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.SMPG02='CANC','NEWM':T86
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 2	
mpField.22F.TRTR.515.SMPG02	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.TRTR.515.SMPG02='TRAD';NODSS:K22
mpField.90A.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90A.DEAL.515.SMPG02='PRIC':K90
mpField.90B.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90B.DEAL.515.SMPG02='PRIC':K90
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 1	
mpField.28E.2.1.536.IOA001	Defines the codes allowed for the specified field. Example mpField.28E.2.1.536.IOA001='LAST','MORE','ONLY':T97
mpField.23G.1.1.515.IOA001	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.IOA001='NEWM':T86
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 2	
mpField.22F.SFRE.536.IOA001	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.SFRE.536.IOA001='ADHO','DAIL','INDA','MNTH','WEEK','YEAR','ANNU','SANN':NODSS:K22

Property	Description
mpField.22F.CODE.536.IOA001	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.CODE.536.IOA001='COMP':NODSS:K22

translator_swift_mp_2007.properties

The translator_swift_mp_2007.properties file is used to set global configuration parameters for Market Practices and Fund Templates.

Special Field Exceptions and Required Code Words

The following caveats apply for special field exceptions and required code words:

- ◆ The special field exceptions and required code words properties have the following format:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>`
- ◆ If a field tag has different validation requirements in different sequences of the same message type, the sequence is appended as follows:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>.<sequence>`
- ◆ If the <mt> component is defined as an asterisk (*), all common group messages apply. For example, n92, n95, n96, where n is a Category 1 through 9.
- ◆ Some field tags allow a valid currency code in addition to a code word validation. The CUR keyword triggers this validation, which checks the external SWIFT_Currencies code list.

Code Word Validations for ISO 15022 Messages

The following caveats apply for ISO 15022 messages:

- ◆ For each MT the exceptions list is displayed first (if any exceptions exist). The exceptions list has the following format:
`mpField.Exceptions.<mt>[ext].<marketPracticeID>`
- ◆ The code word lists are displayed by position and order within the MT. Non-exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>`
- ◆ Exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<marketPracticeID>`
- ◆ Where a subfield greater than two needs to be validated, the subfield number is appended:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>.<subfield>`
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
- ◆ Code words are single-quoted and separated by a comma delimiter. Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present. The <errorCode> will always be the corresponding Kxx code of the field tag.

- ◆ See the translator_swift.properties file for similar examples. Note that the translator_swift.properties file does not use the **mpField** prefix and it does not use a market practice ID, because it is not applicable for standard SWIFT messages.

Configuration Settings

The following table describes properties used to configure the translator_swift_mp_2007.properties file in the application:

Property	Description
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 1	
mpField.23G.1.1.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.SMPG02='CANC','NEWM':T86
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 2	
mpField.22F.TRTR.515.SMPG02	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.TRTR.515.SMPG02='TRAD':NODSS:K22
mpField.90A.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90A.DEAL.515.SMPG02='PRIC':K90
mpField.90B.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90B.DEAL.515.SMPG02='PRIC':K90
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 1	
mpField.28E.2.1.536.IOA001	Defines the codes allowed for the specified field. Example mpField.28E.2.1.536.IOA001='LAST','MORE','ONLY':T97
mpField.23G.1.1.515.IOA001	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.IOA001='NEWM':T86
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 2	
mpField.22F.SFRE.536.IOA001	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.SFRE.536.IOA001='ADHO','DAIL','INDA','MNTH','WEEK','YEAR','ANNU','SANN':NODSS:K22

Property	Description
mpField.22F.CODE.536.IOA001	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.CODE.536.IOA001='COMP':NODSS:K22

translator_swift_mp_2008.properties

The translator_swift_mp_2008.properties file is used to set global configuration parameters for Market Practices and Fund Templates.

Special Field Exceptions and Required Code Words

The following caveats apply for special field exceptions and required code words:

- ◆ The special field exceptions and required code words properties have the following format:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>`
- ◆ If a field tag has different validation requirements in different sequences of the same message type, the sequence is appended as follows:
`mpField.<fieldTag>.<subfield>.<component>.<mt>[ext].<marketPracticeID>.<sequence>`
- ◆ If the <mt> component is defined as an asterisk (*), all common group messages apply. For example, n92, n95, n96, where n is a Category 1 through 9.
- ◆ Some field tags allow a valid currency code in addition to a code word validation. The CUR keyword triggers this validation, which checks the external SWIFT_Currencies code list.

Code Word Validations for ISO 15022 Messages

The following caveats apply for ISO 15022 messages:

- ◆ For each MT the exceptions list is displayed first (if any exceptions exist). The exceptions list has the following format:
`mpField.Exceptions.<mt>[ext].<marketPracticeID>`
- ◆ The code word lists are displayed by position and order within the MT. Non-exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>`
- ◆ Exception entries have the following format:
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<marketPracticeID>`
- ◆ Where a subfield greater than two needs to be validated, the subfield number is appended:
`mpField.<fieldTag>.<qualifier>.<mt>[ext].<marketPracticeID>.<subfield>`
`mpField.<fieldTag>.<qualifier>.<sequence>.<isoBlock>.<mt>[ext].<subfield>`
- ◆ Code words are single-quoted and separated by a comma delimiter. Code word lists have the following format:
`'<codeWord>' [, '<codeWord>'] 0-n[:NODSS]:<errorCode>`
- ◆ NODSS indicates that the code word validation is only performed if no DSS is present. The <errorCode> will always be the corresponding Kxx code of the field tag.

- ◆ See the translator_swift.properties file for similar examples. Note that the translator_swift.properties file does not use the **mpField** prefix and it does not use a market practice ID, because it is not applicable for standard SWIFT messages.

Configuration Settings

The following table describes properties used to configure the translator_swift_mp_2008.properties file in the application:

Property	Description
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 1	
mpField.23G.1.1.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.SMPG02='CANC','NEWM':T86
Market Practice MT515 Germany: Trade Confirmation - Broker to Asset Manager Section 2	
mpField.22F.TRTR.515.SMPG02	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.TRTR.515.SMPG02='TRAD':NODSS:K22
mpField.90A.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90A.DEAL.515.SMPG02='PRIC':K90
mpField.90B.DEAL.515.SMPG02	Defines the codes allowed for the specified field. Example mpField.90B.DEAL.515.SMPG02='PRIC':K90
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 1	
mpField.28E.2.1.536.IOA001	Defines the codes allowed for the specified field. Example mpField.28E.2.1.536.IOA001='LAST','MORE','ONLY':T97
mpField.23G.1.1.515.IOA001	Defines the codes allowed for the specified field. Example mpField.23G.1.1.515.IOA001='NEWM':T86
Market Practice MT536 United States: ISITC-IOA NA Reconciliation Working Group Section 2	
mpField.22F.SFRE.536.IOA001	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.SFRE.536.IOA001='ADHO','DAIL','INDA','MNTH','WEEK','YEAR','ANNU','SANN':NODSS:K22

Property	Description
mpField.22F.CODE.536.IOA001	Defines the codes allowed for the specified field. NODSS indicates that the code word validation is only performed if no DSS is present. Example mpField.22F.CODE.536.IOA001='COMP':NODSS:K22

translator_swift_mx.properties

The translator_swift_mx.properties file is used to set global configuration parameters for the following SWIFTNet message types:

- ◆ SWIFTNet Cash Reporting version 3.0, 3.1, 3.2, 4.0
- ◆ SWIFTNet Exceptions and Investigations 1.0, 1.1, and 1.2
- ◆ SWIFTNet Funds 2.0, 2.1, 2.2, 3.0, 3.1, and 4.0
- ◆ SWIFTNet Trade Services Utility 1.0

Entries are in the following format:

```
swiftMX.<release>.<message>.<element>[.<attribute>]=<defaultValidationFunction>  
[,<parentElement>:<validationFunction>]0-n
```

In the above format, <validationFunction> is one of the following values:

Format	SWIFT Standards Class	Description
BIC	Sw.Stds.D00001	BIC
BEI	Sw.Stds.D00002	BEI
IBAN	Sw.Stds.D00003	IBAN
CC	Sw.Stds.D00004	Country
CURACTIVE	Sw.Stds.D00005	ActiveCurrency
CURACTHIST	Sw.Stds.D00006	ActiveOrHistoricCurrency
AMOUNT	Sw.Stds.D00007	CurrencyAmount
CUR	Sw.Stds.D00007	CurrencyAmount
BICOrBEI	Sw.Stds.D00008	AnyBIC
LANG	Sw.Stds.E00001	LanguageCode
NONE	N/A	Used when no validation should be performed.

Configuration Settings

The following table describes properties used to configure the translator_swift_mx.properties file in the application:

Property	Description
swiftMX.[release].[message].[element] [.[attribute]]	Defines properties for SWIFTNet Cash Reporting 2.0. Example swiftMX.camt.003.001.02.AcctSvcr=BIC

Property	Description
swiftMX.[release].[message].[element] [.attribute]	Defines properties for SWIFTNet Cash Reporting 3.0. Example swiftMX.camt.006.001.03.Ctry=CC
swiftMX.[release].[message].[element] [.attribute]	Defines properties for SWIFTNet Cash Reporting 3.1. Example swiftMX.camt.005.001.03.CcyAndAmtRg.Ccy=CUR
swiftMX.[release].[message].[element] [.attribute]	Defines properties for SWIFTNet Exceptions and Investigations 1.0. Example swiftMX.camt.007.002.01.Cretr=BICOrBEI
swiftMX.[release].[message].[element] [.attribute]	Defines properties for SWIFTNet Exceptions and Investigations 1.1. Example swiftMX.camt.007.002.02.IBAN=IBAN
swiftMX.[release].[message].[element] [.attribute]	Defines properties for SWIFTNet Funds 2.0. Example swiftMX.sese.001.001.01.BICOrBEI=BICOrBEI
swiftMX.[release].[message].[element] [.attribute]	Defines properties for SWIFTNet Funds 2.1. Example swiftMX.reda.003.001.02.BICOrBEI=BICOrBEI
swiftMX.[release].[message].[element] [.attribute]	Defines properties for SWIFTNet Funds 2.2. Example swiftMX.sese.013.001.01.CshCmpnt.Ccy=CUR
swiftMX.[release].[message].[element] [.attribute]	Defines properties for SWIFTNet Funds 3.0. Example swiftMX.acmt.002.001.01.CtryOfBirth=CC
swiftMX.[release].[message].[element] [.attribute]	Defines properties for SWIFTNet Funds 3.1. Example swiftMX.sese.016.001.01.TtlAmtYrToDt=AMOUNT
swiftMX.[release].[message].[element] [.attribute]	Defines properties for SWIFTNet Funds 4.0. Example swiftMX.camt.042.001.03.Amt.Ccy=CURACTIVE, CshInBrkdwnDtls:CURACTHIST,ComssnDtls:CURACTHIST, CshOutBrkdwnDtls:CURACTHIST
swiftMX.[release].[message].[element] [.attribute]	Defines properties for SWIFTNet Trade Services Utility 1.0. Examples swiftMX.tsmt.009.001.02.BuyrBk=BIC swiftMX.tsmt.009.001.02.SellrBk=BIC

ui_swift_message_types.properties

The `ui_swift_message_types.properties` file is used to set global configuration parameters for SWIFT message types.

Entries are in the following format:

```
MessageType.[message_type].[category].[message]=swift.message.type.[description]
```

Configuration Settings

The following table describes properties used to configure the `ui_swift_message_types.properties` file in the application:

Property	Description
MessageType.[message_type].[message_type_number]	Defines valid message types for MT messages. Example <code>MessageType.MT.097=swift.message.type.MT097</code>
MessageType.[message_type].[category].[message]	Defines valid message types for SWIFTNet Funds. Examples <code>MessageType.Funds.semt.003.001.01=swift.message.type.semt.003.001.01</code> <code>MessageType.Funds.sese.009.001.01=swift.message.type.sese.009.001.01</code> <code>MessageType.Funds.camt.041.001.02=swift.message.type.camt.041.001.02</code> <code>MessageType.Funds.setr.017.001.02=swift.message.type.setr.017.001.02</code> <code>MessageType.Funds.reda.003.001.02=swift.message.type.reda.003.001.02</code> <code>MessageType.Funds.acmt.002.001.01=swift.message.type.acmt.002.001.01</code>
MessageType.[message_type].[category].[message]	Defines valid message types for SWIFTNet Trade Services. Example <code>MessageType.TradeServices.tsmt.001.001.02=swift.message.type.tsmt.001.001.02</code>
MessageType.[message_type].[category].[message]	Defines valid message types for SWIFTNet Exceptions and Investigations. Example <code>MessageType.Exceptions.camt.007.002.01=swift.message.type.camt.007.002.01</code>
MessageType.[message_type].[category].[message]	Defines valid message types for SWIFTNet Cash Reporting. Example <code>MessageType.CashReporting.camt.003.001.02=swift.message.type.camt.003.001.02</code>