



Image Services Resource Adapter

Deployment Guide

For IBM WebSphere Application Server Version 9.x

Release 3.4 Fix pack 8

February 2018

© Copyright International Business Machines Corporation 1984, 2018. All rights reserved.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

About This Manual.....	6
Conventions Used in the Document.....	6
Related References.....	6
Comments and Suggestions.....	6
1. ISRA Deployment.....	7
Deployment Requirements.....	7
Hardware Requirements.....	7
Software Requirements	7
Deploying ISRA in a Standalone Environment.....	8
Deploying ISRA in a Clustered Environment.....	11
Deploying ISRA in an Application Server Cell.....	16
Mandatory Requirements for ISRA.....	19
2. ISRA Configuration.....	22
Configuring Deployed ISRA.....	22
Changing ISRA Specific Parameters.....	23
Configurable ra.xml properties	25
DomainName	25
OrganizationName	26
LoggingLevel	26
LoggingMode	27
PageBufferSize	27
CacheRefreshInterval.....	28
SecurityCacheMode	28
MetaDataCacheRefreshMode	29
LogFileName	29
LogFileSize	30
LdapImplClassName	30
LdapImplClassString	31
InherentLogin	31
DeploymentInstance	31
PCHLogging	32
AllowAnonymousUser	33
RPCLogging	33
ClientCodepage	34
GMTEnabled flag.....	35

ISLocale	35
IgnoreObjectBusyMsgInDocMigration	35
Configuring WebSphere-Specific Parameters	35
Configuring Multiple IS Server with ISRA	37
3. Configuring and Deploying ISRA Console and Sample Application	38
ISRA Console	38
Configuring Sample Application	38
Deploying ISRA Console and Sample Application in Standalone Environment	41
Deploying ISRA Console and Sample Application in a Clustered Environment	43
Using the ISRA Console	46
Deploying IBM FileNet Image Viewer in Standalone Environment	48
Deploying IBM FileNet Image Viewer in Clustered Environment	50
IBM FileNet Image Viewer Quick Start Feature	53
Enabling Quick Start Feature	53
Known Issues in the Quick Start Feature	54
Testing Sample Application	55
4. LDAP Configuration	57
Mapping Existing LDAP Server Users to IS	57
Changing ISRA Specific Parameters for LDAP	59
5. Undeployment	60
Undeploying ISRA in a Standalone Environment	60
Undeploying ISRA in a Clustered Environment	61
Undeploying ISRA Console and Sample Application/FNImageViewer Application in a Standalone Environment	62
Undeploying ISRA Console and Sample Application/FNImageViewer Application in a Clustered Environment	63
6. Troubleshooting	65
Disabling NCH Broadcasts	65
Appendix A : ra.xml	66

ra.xml	66
Notices	70
Notices	70
COPYRIGHT LICENSE:	71
Trademarks	71
Index	73

About This Manual

This manual provides information about configuring IBM FileNet Image Services Resource Adapter (ISRA) 3.4.0.x on IBM WebSphere Application Server 9.x. For installing ISRA 3.4.0.x, refer to the separate ISRA Installation Guide.

Conventions Used in the Document

The table lists the formatting conventions used in this document.

<u>Conventions</u>	<u>Description</u>
Fixed Size font	Used for commands entered at the system command prompt.
Arial font	Used for important notes.
Bold	Occasionally used to refer to portions of user interface, such as the Next button or the Install button.

Related References

For all ImageViewer parameters, see the FNImageViewer documentation provided with ISRA installation media.

<ISRA-home>\ISRA340\FNImageViewer\docs

For all P8 System Manager related information, see the P8 System Manager Documentation, provided with ISRA installation media.

<ISRA-home>\ISRA340\SystemManager\docs

Comments and Suggestions

IBM FileNet invites all customers to communicate with the [Documentation group](#) on any question or comment related to IBM FileNet manuals and online help.

Send email to comments@us.ibm.com. We will make every effort to respond within one week. Your suggestions help us improve the products we deliver.

1 . ISRA Deployment

This chapter describes the deployment of ISRA on IBM WebSphere Application Server version 9.x.

Note The installation procedure for IBM WebSphere Application Server V9 and installing ISRA in clustered environment is outside the scope of this document, and it is assumed the required settings and configurations are satisfied.

The ISRA module is a set of Java interfaces/classes that implements J2EE Connector Architecture specified contracts and the EIS specific functionality. ISRA plugs into IBM WebSphere Application Server in a modular manner.

Deployment Requirements

This section lists the minimum software and hardware requirements for successful deployment of ISRA on an IBM WebSphere Application Server V9.

Caution You must manually create all the xml related to the deployment of ISRA or use a pre-existing file that is valid. Do not copy xml contents straight from the Deployment Guide.

Hardware Requirements

- Refer to the IBM WebSphere system requirements section at <http://www-01.ibm.com/software/webservers/appserv/was/requirements>
- The IBM WebSphere documentation is available at <http://www.ibm.com/developerworks/websphere/zones/portal/proddoc/>
- ISRA installation requires approximately 120 MB free disk space.

Software Requirements

- IBM WebSphere Application Server 9.x installed on IBM AIX 7.2 or Windows Server 2012 R2. For other operating systems, refer to [System Requirements for WebSphere Application Server 9.0](#).
- IBM WebSphere Network Deployment Manager 9.x installed on IBM AIX 7.2 or Windows Server 2012 R2. For other operating systems, refer to [System Requirements for WebSphere Application Server 9.0](#).
- IBM FileNet IS 4.1.x and above.

Deploying ISRA in a Standalone Environment

Note The screenshots shown for deployment/undeployment of ISRA, sample application, or FNImageViewer (taken on IBM WebSphere Application Server 9.x on Windows Server 2012 R2) may look slightly different on the user's machine, depending on the server, platform version, or settings.


To remove/undeploy previous ISRA Versions (3.1/3.2/3.3), see the [Undeployment](#) section. Also, stop any running ISRA Sample and FNImageViewer before the undeployment is done. After the successful undeployment, complete the following steps for new/re-deployment of ISRA.

ISRA is deployed by using the WebSphere Administrative console.

To deploy ISRA, complete the following steps:

1. Start the WebSphere 'First steps'. Log in as the root user and execute the WebSphere `firststeps.sh` script, as follows:

```
# cd <WebSphere home>/AppServer/profiles/default/firststeps
# ./firststeps.sh
```




2. Click **Start the server**.
3. Launch a web browser and enter the URL: `http://<server>:<port>/admin`


Here, 'server' is name of the host where WebSphere server is running and 'port' is the port number on which the admin server is listening.

Log in to the WebSphere Administrative console, which is a web-based interface.


The WebSphere Administrative console screen appears:




4. Enter the **User ID** and click **Log in**. The following screen appears:




5. Navigate to **Resources >Resource Adapters >Resource Adapters**. The following screen appears:




6. Click **Install RAR**. The following screen appears:




7. Click **Browse** to navigate to the directory where ISRA.rar is located. In the case of ISRA 3.4.0 GA version, the ISRA.rar file is in the “jar” folder of ISRA 3.4.0 installation dir. In the case of an ISRA Fix pack (such as, 3.4 Fix pack 1), the ISRA.rar file is in the fix pack extracted directory. Select **ISRA.rar**, and click **Next**. The General Properties screen appears.



8. Click **OK**. The ISRA.rar file gets uploaded. A confirmation message is displayed, as shown in the following screen:



9. Click the **Save** link in the **Messages** box (in the right pane).



10. Deploying ISRA is completed.
11. Next step is to complete the Mandatory steps necessary for ISRA.
Refer to [Mandatory Requirements for ISRA](#) section.
12. Restart the WebSphere Node (or Application Server) after deployment. This step is required to ensure that the ISRA classes are in the Application Server's CLASSPATH.
13. To verify the ISRA deployment, deploy the ISRA Console and Sample Application provided with ISRA and log in through the Sample Application.

Note User can configure multiple Connection Factories with unique JNDI names to connect to multiple IS servers from ISRA. Configuration of multiple Connection Factories is explained in the [Configuring Deployed ISRA](#) section.

Deploying ISRA in a Clustered Environment


In a clustered environment, ISRA is deployed by using the WebSphere Network Deployment Manager Administrative console.

Note After installing Network Deployment Manager, you need to create a Deployment Manager profile by using the Profile Creation Wizard. For example, the “dmgr” profile mentioned in the following first step of ISRA deployment.

To deploy ISRA, complete the following steps:

1. Start the WebSphere ‘First Steps’. Log in as the root user and execute the WebSphere `firststeps.sh` script, as follows:


```
# cd <DeploymentManager home>/profiles/dmgr/firststeps
# ./firststeps.sh
```




2. Click **Start the Deployment Manager**.
3. Launch a web browser and enter the URL: `http://<server>:<port>/admin`
Here, 'server' is name of the host where WebSphere Network Deployment Manager is running and 'port' is the port number on which the admin server is listening. By default, this port number is 9091.
Log in to the WebSphere Network Deployment Manager Administrative console, which is a web-based interface.
The WebSphere Administrative console screen appears.




4. Enter **User ID** and click **OK**. The following screen appears:




5. Navigate to **Resources >Resource Adapters >Resource Adapters**. The following screen appears:




6. Click **Install RAR**. The following screen appears:




7. Select the node where ISRA is to be deployed.
8. Click **Browse** to navigate to the directory where ISRA 3.4.0 is saved. Select the **ISRA.rar** file from the ISRA installation directory. Click **Next**. The General Properties screen appears.



9. Mention the path for the ISRA.jar in the class path and click **OK**. The ISRA.rar file gets uploaded. A confirmation message is displayed, as shown in the following screen:



10. Click **Save** to save the changes to the master configuration. The following screen appears:



11. Deploying ISRA is completed.
12. Next step is to complete the mandatory steps necessary for ISRA. Refer to the [Mandatory Requirements for ISRA](#) section.
13. To verify the ISRA deployment, deploy the ISRA Console and Sample Application provided with ISRA and log in through the Sample Application.
14. Restart the WebSphere cluster by using the Network Deployment Manager after deployment. This step is required to ensure that ISRA is deployed correctly in the cluster.

Note User can configure multiple Connection Factories with unique JNDI names to connect to multiple IS servers from ISRA. Configuration of multiple Connection Factories is explained in the [Configuring Deployed ISRA](#) section.

Note Deployment of ISRA on cluster on WAS can be automated. Refer to the [developerWorks title: Automation of ISRA Deployment on WAS Cluster](#) article.

Deploying ISRA in an Application Server Cell

Note The screenshots shown for deployment/undeployment of ISRA, Sample Application, or FNImageViewer (taken on IBM WebSphere Application Server 9.x on Windows Server 2012 R2) may look slightly different on the user's machine, depending on the server, platform version, or settings.

ISRA is deployed by using the WebSphere Administrative console.

To deploy ISRA, complete the following steps:

1. Start the WebSphere 'First steps'. Log in as the root user and execute the WebSphere `firststeps.sh` script, as follows:

```
# cd <WebSphere home>/AppServer/profiles/default/firststeps
# ./firststeps.sh
```



2. Click **Start the server**.

Launch a web browser and enter the URL,
`http://<server>:<port>/ibm/console`, in the browser to open the IBM WebSphere console.


Here, 'server' is name of the host where WebSphere server is running and 'port' is the port number on which the admin server is listening. By default, this port number is 9060.

Log in to the WebSphere Administrative console, which is a web-based interface.


The WebSphere Administrative console screen appears:




3. Enter **User ID** and click **Log in**. The following screen appears.




4. Navigate to **Resources > Resource Adapters > Resource Adapters**. The following screen appears:




5. Select the **Cell** option where ISRA is to be deployed.
6. Click **New**.



7. Enter the **Name** for the resource adapter and specify the archive path as the path of the ISRA.rar file. The rar file needs to be manually copied to each node in the cell and the path must be identical.



8. Specify ISRA.jar, log4j-1.2.8.jar, and listener.jar in the class path. The path of ISRA.jar has to be provided in the class path of the resource adapter. Click **Apply**.



9. Click the **Save** link to save the changes.
10. For configuration, see the [ISRA Configuration](#) section.

Mandatory Requirements for ISRA

The mandatory requirements for ISRA 3.4.0:

Steps to include listener.jar and log4j-1.2.8.jar in the classpath of Application Server are:

1. Find the listener.jar and log4j-1.2.8.jar in the path "<ISRA-home>\ISRA340\SystemManager".
2. Log in to the WebSphere Administrative console.
3. Navigate to **Servers > Server Types> WebSphere application servers** and select the server.
4. Under Server Infrastructure, expand the **Java and Process Management** link, and click the **Process Definition** link.
5. Under Additional Properties, click **Java Virtual Machine**.
6. Include **listener.jar** and **log4j-1.2.8.jar** in the **Classpath**, as shown in the following screen:

Application servers > server1 > Process definition > Java Virtual Machine

Use this page to configure advanced Java(TM) virtual machine settings.

Configuration Runtime

General Properties

Classpath
C:\Softwares\israclasses\listener.jar

Boot Classpath

☐ Verbose class loading
☐ Verbose garbage collection
☐ Verbose JNI

Additional Properties
Custom properties

Note If the operating system is Unix/Linux, you must use colon (:) as a separator for each jar file path appended to the classpath text field and if it is Windows, you must use semicolon (;).

7. In case of Windows operating system, include the folder in which **WinPerfMon.dll** is present in the system path. In UNIX, this file is not required.
8. Enter the initial and maximum JVM heap size as 512.

Explanation for Terminal name and ISRALock folder:

The first instance of ISRA deployed on an Application Server creates a folder named "ISRALock" and a **file named** ¹ "ISRALock.0" inside that folder. The counter "0" in the file name "ISRALock.0" increments subsequently with each new deployment of ISRA and the same is appended to the terminal name generated for an ISRA instance. This folder is created in the path resolved by the system property "user.dir", which is the same path where the ISRA logs are generated. This functionality has been introduced in ISRA 3.2.1 to support vertical cluster environment.

Terminal name identifies ISRA instance with a unique ID so that IS can distinguish each ISRA client uniquely for communication. Earlier, the terminal name used to be of the form "SV<instance number>.<Counter1>@IPAddress". In a vertical cluster, ISRA can be deployed across the cluster on a single machine. But in such a scenario, all the managed server instances in a cluster have the same ISRA instance deployed and generate the same terminal name, as the "IPAddress" and "instance number" are same for all the ISRA instances. The current format of a terminal name generated by ISRA is "R<instance number><Counter1><Counter2>@IPAddress", where Counter2 is the counter that is appended to the files created in the ISRALock folder. The files that are created in the ISRALock folder are automatically removed if the managed servers are gracefully shut down (in case of proper JVM shutdown).

¹ ISRALock.0 (0-9 and a-z) would be created in ISRA 3.4 FP3 and above. Prior versions of ISRA would have files created as ISRALock.0000 (0000-9999).

For “[DeploymentInstance](#)” [property setting](#), see the following [Configurable ra.xml properties](#) section

2. ISRA Configuration

This chapter describes how to configure ISRA on IBM WebSphere Application Server version 9.x, after it is deployed.


Configuring Deployed ISRA

This section describes the procedure to edit ISRA deployment properties by using the WebSphere Administrative console.


ISRA uses a deployment descriptor called **ra.xml** to define its operational parameters. The deployment descriptor is defined by Sun Microsystems in the J2EE Connector 1.0 specification. It describes the Resource Adapter related attributes, types, and its deployment properties by using a standard Document Type Definition (DTD).

To edit the ISRA deployment descriptor, complete the following steps:


1. Launch a web browser window and log in to the WebSphere Administrative console or Network Deployment Administrative console depending on whether ISRA is deployed in standalone or clustered environment.
2. Expand the **Resources** node.
3. Click the deployed ISRA to edit under the **Resource Adapters** node.
4. Click **J2C Connection Factories**. The following screen appears:



5. Click **New**. The following screen appears:



6. Provide a name for the Connection Factory. Provide the **JNDI name**, for example, ISCF. Click **Apply**.
7. Click the **Save** link in the **Messages** box. The following screen appears
8. Click **OK**. On successful creation of Connection Factory, the following screen appears:




Changing ISRA Specific Parameters


After ISRA is deployed, some parameters of the Deployment Descriptor need to be changed to configure it for the target IS server.

To change ISRA specific parameters, complete the following steps:


1. Navigate to **Resources> Resource Adapters> Resource Adapters**. The following screen appears:



2. Under **Name** column, click **ISRA**.
3. Under **Additional Properties**, click **J2C Connection Factories**. The following screen appears:



4. Click the already created ISRA Connection Factory or the **ISCF** link.
5. Under **Additional Properties**, click **Custom Properties**. The different parameters, which may be customized, are displayed.



6. To customize each parameter, click the parameter name, modify and then save the changes. For details, see the Configurable ra.xml properties section.

Configurable ra.xml properties


Note All properties that described in the deployment descriptor are mandatory and no property must be removed. The default values must be specified for properties that users do not want to use.

The configurable properties to be set (modified) in **ra.xml** are:

- [DomainName](#)
- [OrganizationName](#)
- [LoggingLevel](#)
- [LoggingMode](#)
- [PageBufferSize](#)
- [CacheRefreshInterval](#)
- [SecurityCacheMode](#)
- [MetaDataCacheRefreshMode](#)
- [LogFileName](#)
- [LogFileSize](#)
- [LdapImplClassName](#)
- [LdapImplClassString](#)
- [InherentLogin](#)
- [DeploymentInstance](#)
- [PCHLogging](#)
- [AllowAnonymousUser](#)
- [RPCLogging](#)
- [ClientCodepage](#)
- [GMTEnabled flag](#)
- [ISLocale](#)
- [IgnoreObjectBusyMsgInDocMigration](#)

DomainName

This is the name of the domain of the IS server. Click **DomainName**. The default value for DomainName is FileNetIS. It must be set according to the operational environment.



OrganizationName

This is the FileNet IS organization name. The default value for OrganizationName is IBM. Click **OrganizationName** to change the value to the target IS server.

The screenshot shows the IBM FileNet ISRA console interface. On the left is a navigation tree with categories like 'Guided Activities', 'Servers', 'Applications', 'Jobs', 'Services', 'Resources', 'Runtime Operations', 'Security', 'Operational policies', 'Environment', 'System administration', 'Users and Groups', and 'Monitoring and Tuning'. The 'Resources' category is expanded, showing 'Resource Adapters' and 'ISRC'. The main panel displays the 'OrganizationName' configuration page under the path 'Resource adapters > ISRA > ISRC connection factories > ISRC > Custom properties > OrganizationName'. The page includes a 'Configuration' tab and a 'General Properties' section with fields for 'Scope' (set to 'cells/orb2Cell01:nodes/orb2Node03'), 'Name' (set to 'OrganizationName'), 'Value' (set to 'IBM'), and 'Description' (set to 'Organization name of the Image Services Server'). There is also a 'Type' dropdown set to 'java.lang.String' and buttons for 'Apply', 'OK', 'Reset', and 'Cancel'.


LoggingLevel

This is an integer representing the amount of log information to be generated. The values are dynamically updated by using the ISRA Console. The valid values are:

Logging Level	Description
-1	Disables ISRA Logging
0	Only Error and Warning messages are logged by ISRA
1	Informative messages are also logged by ISRA
2	Prints debug message in the log

Click **LoggingLevel** to change the value.

The default value of LoggingLevel is 0. It can be modified to other valid Logging Levels. It is recommended to keep the logging level to 0. LoggingLevel can be increased if user encounters a problem while accessing ISRA through the application.




LoggingMode

This is an integer representing the mode of logging. The valid values are:

Logging Level	Description
0	No logging
1	Only console logging
2	Only file logging
3	Both console logging and file logging

Click **LoggingMode**.

The default Value of LoggingMode is 3. It can be changed to other valid values according to the operational environment.



PageBufferSize

This is an integer value specified in kilobytes (KB). PageBufferSize specifies the chunk size that ISRA uses to transfer page data to and from IS. The default value is 64 KB. Specifying a higher value requires more memory for the Application

Server process and a low PageBufferSize means more trips to IS. The value must be set to an average page size on the target IS. The document buffer size on IS and ISRA must match to optimize image transfer performance.

The screenshot shows the WebSphere configuration console. On the left is a navigation tree with categories like Servers, Applications, Jobs, Services, Resources, Concurrency, Mail, URL, Resource Environment, Runtime Operations, Security, Operational policies, Environment, System administration, and Users and Groups. The 'Resources' category is expanded, showing 'Resource Adapters' and 'J2C connection factories'. The main pane shows the configuration for 'Cell=orbt2Cell01, Profile=Dmgr01' under 'Resource adapters'. The breadcrumb path is 'Resource adapters > ISRA > J2C connection factories > ISCE > Custom properties > PageBufferSize'. The page title is 'PageBufferSize'. The description says: 'Use this page to specify custom properties that your enterprise information system (EIS) requires for the resource providers and resource factories that you configure. For example, most database vendors require additional custom properties for data sources that access the database.' The configuration form has a 'General Properties' section with a 'Scope' field containing 'cells/orbt2Cell01:nodes/orbt2Node03', a 'Name' field containing 'PageBufferSize', a 'Value' field containing '64', and a 'Description' field containing 'Page data fetch size (in kilo bytes)'. The 'Type' dropdown is set to 'java.lang.Integer'. At the bottom are 'Apply', 'OK', 'Reset', and 'Cancel' buttons.

CacheRefreshInterval

This is an integer value specified in minutes. ISRA stores metadata information, such as Document class, Indices, and menu details in a local cache for faster retrieval. ISRA refreshes the cache information based on the CacheRefreshInterval value. The default value is 30 minutes. Click **Apply** after modifying the property.

The screenshot shows the WebSphere configuration console. On the left is a navigation tree with categories like Servers, Applications, Jobs, Services, Resources, Concurrency, Mail, URL, Resource Environment, Runtime Operations, Security, Operational policies, Environment, System administration, and Users and Groups. The 'Resources' category is expanded, showing 'Resource Adapters' and 'J2C connection factories'. The main pane shows the configuration for 'Cell=orbt2Cell01, Profile=Dmgr01' under 'Resource adapters'. The breadcrumb path is 'Resource adapters > ISRA > J2C connection factories > ISCE > Custom properties > CacheRefreshInterval'. The page title is 'CacheRefreshInterval'. The description says: 'Use this page to specify custom properties that your enterprise information system (EIS) requires for the resource providers and resource factories that you configure. For example, most database vendors require additional custom properties for data sources that access the database.' The configuration form has a 'General Properties' section with a 'Scope' field containing 'cells/orbt2Cell01:nodes/orbt2Node03', a 'Name' field containing 'CacheRefreshInterval', a 'Value' field containing '30', and a 'Description' field containing 'Cache refresh interval(in minutes)'. The 'Type' dropdown is set to 'java.lang.Integer'. At the bottom are 'Apply', 'OK', 'Reset', and 'Cancel' buttons.

Note To configure ISRA for multiple IS servers, create a Connection Factory for each IS that you want to connect. DomainName and OrganizationName pair must be distinct among the configured Connection Factories.

SecurityCacheMode

This parameter can take two values:

<u>Value</u>	<u>Setting</u>
1	Caches both users and groups
2	Caches only groups

MetaDataCacheRefreshMode

This parameter can have a value in the range of (0-15).

<u>Value</u>	<u>Setting</u>
0	No Metadata cache refresh
1	Printer cache refresh only
2	Document class cache refresh only
4	Key fields cache refresh only
8	Menu value cache refresh only
15	Is the default value for this parameter, which refreshes all metadata.

Add corresponding values to get a combination of data.


For example, $1+2 = 3$ Printer and document class data

$1+2+4 = 7$ Printer, document class, and key fields data

$0+1+2+4+8 = 15$ all data

LogFileName

The LogFileName is a string containing the name and path of the log file. Click **LogFileName** to change the value. The default value of LogFileName is **ISRA.log**. A complete or relative path can be provided to create the log file at a specific location on disk.




To ensure that each ISRA instance has a unique log file, the following steps are completed:

- Configurable property “DeploymentInstance” is read from ra.xml and appended to the log file name. If not specified, the default value “1” is used as the deployment instance of ISRA.
- The unique ID used for terminal ID generation in ISRA is appended to the log file name.

For instance, if the log file name configured in ra.xml is **ISRA.log** and the deployment instance is 1, the modified log file name would be **ISRA_1_0.log**. Here, “0-9 and a-z” is the unique ID ² generated at runtime. This ensures a unique name of the log file for each instance of ISRA.

LogFileSize

This is an integer representing the maximum size of the log file in Megabytes (MB). When the size of the file reaches this maximum limit, the log file is renamed, and a new file is created with the same name. For example, **ISRA_1_0.log** is renamed to **ISRA_1_0_1.log**, and a new file **ISRA_1_0.log** is created. The default value of LogFileSize is 5 MB. Automatic purging of old ISRA log files has been implemented leaving behind only five latest versions.



LdapImplClassName

It is the name of the Implementation class for LDAP Authentication. This parameter contains the complete path of the LDAP Implementation class to be entered along with the LDAP Implementation Class Name.

The default value is ‘com.filenet.is.ra.fnis.FN_IS_IPlanetImpl’.

The value of the property for LDAP implementation for Active directory is com.filenet.is.ra.fnis.FN_IS_ActiveDirImpl and for Novell NDS, the value is com.filenet.is.ra.fnis.FN_IS_NovellINDSImpl.

² The modified log file name would be ISRA_1_<unique-ID>.log. The value for unique ID is 0-9, a-z in ISRA 3.4 FP3 and above. Older versions of ISRA use the unique ID value between 0000-9999.

LdapImplClassString

This parameter is a general string that takes in all the LDAP server specific parameters required for authentication. It takes the following inputs:

- Server Name – Name of the server/ machine on which LDAP server exists.

Note In case that the LDAP server is located on a different subnet, it may be necessary to enter the IP address or a full domain name.

- Port Number – LDAP server's port number used for transactions.
- User Path – Organization unit under which the users are filed in the LDAP directory server.

The three parameters must be separated by semicolon and must appear in the order - server name, port number, and user path. An example of LDAPImplClassString is:

- **For Active Directory**

filenetserver;389;ADS.com

- **For IPlanet**

filenetserver;389;ou=ISRA, dc=odc, dc=filenet, dc=com

- **For Novell NDS**

filenetserver;389;ou= ISRA, ou=odc,ou=filenet,o=com

InherentLogin

To use LDAP security, the value must be set to 1 from the default value 0.

DeploymentInstance

This is the instance number of ISRA that is being deployed. It is a user-defined number between 0 and 99. The default value for this parameter is 0 when none is specified. The maximum is 99, which means that 99 different instances of ISRA can be deployed in a WebSphere Application Server node.

Each deployment/JNDI of ISRA on the same Web/Application server requires its own instance number. For example, there can be two ISRA applications deployed on the same Web/Application server. Each deployment would require its own instance number and JNDI name. This number is used on the IS server to differentiate between multiple connections from the same IP address of the Web/Application server.

IS always expects unique IDs from ISRA clients, and when it receives duplicate IDs from ISRA, it rejects communication.

Hence, it is always advised to increment the deployment instance number when another instance of ISRA is deployed to achieve its unique ID.

Format of the terminal ID is used by ISRA and IS in distinguishing a unique ISRA instance.

RXXYYYYZ@<ip-address>

Where,


XX = takes values from 0 to 99. If there is only one instance, it defaults to 0. Else, the value must be set to the number of deployment instances.

YYY = Counter that increments with the creation of a new LogonSession object (Values in base 36).

Z = Unique ID generated per ISRA instance. Introduced to support ISRA in a clustered environment (Unique ID is a number in Base 36).

<ip-address> = IP Address of the machine where ISRA is deployed.


The unique ID is obtained from the place holder file ISRALock.z (where Z=Unique ID) that is created in the ISRALock folder. Each cluster member creates its own place holder file (such as, ISRALock.0, ISRALock.1, and so on) within the common ISRALock folder.



PCHLogging


This is a String parameter to enable/disable PCH logging in ISRA. The default value for this is "Disabled". PCHLogging enables user to log performance monitoring data of IS.

PCHLogging	Description
Enabled	Enables the PCHLogging.
Disabled	Disables the PCHLogging. This is the default value.



AllowAnonymousUser

It is a Boolean value to allow anonymous user logon through LDAP, when blank password is passed from user/client. The default value of this parameter is "false".



RPCLogging


This is an integer representing the RPC logging level. The valid values are:

RPCLogging	Description
0	No logging
1	File logging

The default value of RPCLogging parameter is 0. It can be changed to 1, if RPC logging is required.

The RPC LogFileSize is taken as double the size of that of ISRA LogFileSize. Hence, when the size of the RPC log file reaches its maximum limit (10MB), the log file is renamed, and a new file is created with the same name. For example, ISRA_1_0_RPC.log is renamed to ISRA_1_0_RPC_1.log, and a new file

ISRA_1_0_RPC.log is created. Automatic purging of old ISRA RPC log files has been implemented leaving behind only five latest versions.



ClientCodepage

This is the code page for encoding text and sticky note annotations. The default value of this property is Cp1252.

On Microsoft Windows platform, the Locale character set is the Windows Code Page (1252 for US English and Western Europe), whereas on a UNIX platform, it is an ISO 8859-X character set (ISO 8859-1 for US English and Western Europe).

Thus, if the client locale character set is Windows Code Page based (for example, Cp1252 for US English and Western Europe) and the server is UNIX based, the Windows Code Page must be used for encoding the annotations data before committing to the server. This is because there is an inconsistency in characters mapping between Microsoft Windows Code Pages and the equivalent ISO 8859-X series. For instance, Code page 1252 is built on ISO 8859-1 but uses the range 0x80-0x9F for extra printable characters rather than the C1 control codes used in ISO8859-1.

For Annotations data, ISRA internally retrieves the IS character set and uses the equivalent Windows Code Pages for the following ISO encodings:

ISO Encoding	MS Windows counterpart
ISO8859_1	Cp1252
ISO8859_2	Cp1250
ISO8859_5	Cp1251
ISO8859_6	Cp1256
ISO8859_7	Cp1253
ISO8859_8	Cp1255
ISO8859_9	Cp1254
ISO8859_13	Cp1257

Note Specifying an incorrect code page may lead to inconsistency and/or corruption of annotations data.

GMTEnabled flag

This parameter takes two values:

1. true
2. false

The default value of this parameter is false.

Setting “GMTEnabled” to false: When the flag is set to false, it is assumed that the ISRA client application is not “GMT Enabled”, that is, the client applications do not perform any time zone conversion. ISRA returns the date committed on the IS to client applications after adjusting the difference between the Application Server time zone and the GMT time zone. As a result, the dates displayed in applications are in accordance with the dates committed on the IS.

Setting “GMTEnabled” to true: When the flag is set to true, it is assumed that the client application is “GMT Enabled”, that is, the client applications display the dates in GMT. In this case, ISRA returns the date committed on the IS in the GMT time zone, without any adjustment. Set this value to true only if you have made changes to your application after an upgrade to ISRA 3.3 FP6 or ISRA 3.4 FP2.

ISLocale

This is a string parameter which represents the ISRA locale. The administrator can set the value of this configurable property as that of the IS locale. It is a lowercase two letter code as defined by ISO-639. The default value of this parameter is “en” (English locale). The ResourceBundle used in ISRA depends on the value set by the user for this property.

IgnoreObjectBusyMsgInDocMigration

This is a Boolean parameter which can be set to true to ignore the [77,0,11 The object is busy] error, in case of DocMigration. The default value for this parameter is false.

Configuring WebSphere-Specific Parameters

After the configurable properties are set for ISRA, the application server specific parameters need to be configured. In case of WebSphere Server, the properties that need to be specified are:

- Connection timeout
- Maximum connections
- Minimum connections
- Reap time
- Unused timeout
- Aged timeout
- Purge policy

To configure these properties, complete the following steps:

1. Navigate to **Resources > Resource Adapters > ISRA > J2C Connection Factories > ConnectionFactoryName (ISCF) > Connection Pool Properties**.
2. Set the **Connection timeout**, **Maximum connections**, **Minimum connections**, **Reap time**, **Unused timeout**, **Aged timeout**, and **Purge policy**.



A description of each attribute is as follows:

- **Connection timeout:** Defines the time (in seconds) that the Pool Manager waits after reaching the maximum number of connections to abort and throw a `ResourceAllocationException`. If the maximum number of connections is not reached or is set to zero (0), the Connection timeout is not used.

If the Connection timeout is zero (0), the Pool Manager waits indefinitely.
- **Maximum connections:** Represents maximum number of Managed connections that can be created by the `ManagedConnectionFactory`. After this number is reached, no new connections are created, and the requester waits for the Connection timeout or a `ResourceAllocationException` to be thrown. If Maximum connections is set to zero (0), the number of connections can grow indefinitely. Maximum connections must be greater than or equal to Minimum connections.
- **Minimum Connections:** Represents minimum number of Managed connections maintained by the Application Server. If this number is reached, the garbage collector does not discard any Managed connections. If the actual number of connections is lower than the value specified by the minimum connections settings, no attempt is made to increase the number of connections to the minimum value. Minimum connections must be less than or equal to Maximum connections. Set this value to 0 for ISRA.
- **Reap time:** Represents the time (in seconds) after which the garbage collector runs. The garbage collector discards all unused connections for the value specified by Unused timeout.
- **Unused timeout:** Represents the time (in seconds) after which an unused connection is discarded. If this value is set to 0, the garbage collector is disabled.
- **Aged timeout:** Specifies the interval (in seconds) after which an unused, aged connection is discarded. Set the Aged timeout value higher than the Reap timeout value for optimal performance.
- **Purge policy:** Specifies how to purge connections when a stale connection or fatal connection error is detected. If user sets the purge policy for this data


source object to EntirePool, all connections in the pool are marked stale. Any connection not in use is immediately closed. If user sets the Purge policy for this data source object to FailingConnectionOnly, only the connection that caused the StaleConnectionException is closed.

Note It is recommended that user sets the values of the **Reap time** and **Unused timeout** to ensure that WebSphere and ISRA free the unused IS server resources. The actual values of these parameters depend on the application scenario. But in general, they must be set to a low value to free the IS resources. For example, set **Unused timeout** to 1800 seconds (30 minutes) and **Reap time** to 120 Seconds (2 minutes).

Configuring Multiple IS Server with ISRA

To configure ISRA for accessing multiple IS servers, create a Connection Factory for each IS that user wants to connect.

The following screen shows Connection Factories configured for multiple IS servers:



3. Configuring and Deploying ISRA Console and Sample Application

ISRA Console

The LoadISRA utility from ISRA 3.4.0 is now replaced with the ISRA Console (in ISRA 3.4 Fix pack 1 and above). This ISRA console is developed to show the ra.xml properties in a formatted table and also features buttons to enable/disable/edit logging levels dynamically.

The dynamic update of logging allows the user to enable and change logging levels while the ISRA is running and without needing to restart the appserver. The console also features links to launch Sample Application and to view JVM statistics.

This console is available as a Web Module (ISRAConsole.war) within ISRAConsole.ear and gets deployed automatically during the deployment of ISRAConsole.ear.

Resource Adapter class loading in Websphere Application Server and jndiISRA.properties:

WebSphere Application Server, by design, does not load the adapter classes immediately on application server restart. The classes are loaded only after a user logs in using ISRA the first time after restart.

Upon loading of the classes, ISRA security cache gets created, to load IS users into ISRA memory.

In ISRA 3.4 Fix pack 1, a new properties file - jndiISRA.properties is introduced, where the user can mention the JNDI names of the ISRA Connection Factories. Those mentioned in the properties file get loaded automatically upon WebSphere Application Server restart.

Configuring Sample Application

The ISRA console and Sample Application are packaged within a single Enterprise Application Archive File (**ISRAConsole.ear**).

ISRAConsole.ear consists of:

- Two web modules:
 - ISRASampleWEB.war (ISRA Sample Application)
 - ISRAConsole.war (ISRA Console)
- Deployment descriptor (application.xml)

This chapter illustrates the deployment and configuration of the ISRA Console and Sample Application on IBM WebSphere Server 9.x in a managed environment.

Note ISRA product media comes with an IBM FileNet Image Viewer, which can be used to display the TIFF, JPEG, BMP, and other supported file formats on a Java-enabled browser.

This Sample Application is intended solely for illustrative purposes and it must not be expected to perform useful work, or be used for production deployment. This Sample Application is to be used strictly as reference material.

It is assumed that ISRA is deployed and configured for the target IS.

In ISRA 3.4 fix pack 1, a new properties file "jndiISRA.properties" is introduced and it gets created in Application Server home directory. The JNDI names of connection factories mentioned in this properties file, which is used by Sample Application to display on the login page. Two JNDI names "ISCF" and "ISCF1" are mentioned in the file by default. Additional library names can be included by providing comma-separated entries. The property file is mandatory and it should contain the same names as the JNDI Binding Paths specified for the configured ISRA ConnectionFactories.

For configuring the Sample Application, certain properties need to be updated in the web.xml of the **ISRASampleWEB.war**.

To extract **web.xml** from **ISRASampleWEB.war**, complete the following steps:

1. Use the jar binary from <WAS_HOME>\java\bin to extract the ISRAConsole.ear and the ISRASampleWEB.war.
2. Open a Command window/Commandline Console/Terminal Window and cd to <ISRA-home>\ISRA340\Sample and run:
 - a. mkdir tmp1
 - b. copy ISRAConsole.ear tmp1
 - c. cd tmp1
 - d. "<WAS_HOME>\java\bin\jar" -xvf ISRAConsole.ear
 - e. mkdir tmp2
 - f. copy ISRASampleWEB.war tmp2
 - g. cd tmp2
 - h. "<WAS_HOME>\java\bin\jar" -xvf ISRASampleWEB.war
3. Open the file <ISRA-home>\ISRA340\Sample\tmp1\tmp2\WEB-INF\web.xml in an editor.
4. To enable extended annotation functionality, modify the following parameters in **web.xml**:
 - a. Change env-entry-value for "DOCCLASSNAME" to the document class configured in the IS for digital signatures.
`<env-entry-value>digDocClass</env-entry-value>`
 - b. Change env-entry-value for "MAXROWS" to the number of records to be fetched from the given document class.
`<env-entry-value>200</env-entry-value>`
5. To enable remote printing functionality, modify the following parameters in **web.xml**:

- a. Change env-entry-value for "USEPRINTVIEWOPTION" to either Yes or No. This value determines whether to honor the print/view preference set in the **web.xml** or to take the value returned by ViewOne. The default value is No.

```
<env-entry-value>No</env-entry-value>
```

- b. Change env-entry-value for "PRINTVIEWOPTION" to either View Only =1, Print Only =2, Print/View =3. This value indicates the value of Print/View. The default value is 3.

```
<env-entry-value>3</env-entry-value>
```

Note If the PRINTVIEWOPTION is set to 3 (default), the sticky note is saved as a normal sticky note. If PRINTVIEWOPTION value is specified as 1 or 2, the annotations are saved as an extended annotation (***Extended annotations** are non-standard annotations which are saved with a class name parameter (F_CLASSNAME) of "Proprietary", a class id property (CLASS_ID) of {A91E5DF2-6B7B-11D1-B6D7-00609705F027} and a subclass name property (F_SUBCLASS) that describes the annotation.*

The value of PRINTVIEWOPTION is honored for each sticky note individually, and not for all the sticky notes on a document as a whole.

Thus, the setting for PRINTVIEWOPTION is processed for either a new annotation being added or an existing annotation being modified.

6. The Sample Application uses the crimson implementation of DocumentBuilderFactory class to implement the remote printing functionality. IBM WebSphere Application Server does not provide the crimson implementation of DocumentBuilderFactory class.

Hence, if remote printing functionality is desired, complete the following steps to bundle crimson.jar with the Sample Application:

- a. Open the link, <http://xml.apache.org/dist/crimson/>, in a web browser.
 - b. Download the file crimson-1.1.3-bin.zip.
 - c. Extract all the files from crimson-1.1.3-bin.zip in C:\ (or any local drive). Crimson.jar can be located under the "C:\crimson-1.1.3\" folder.
 - d. Bundle crimson.jar within the "WEB-INF\lib" directory of ISRASampleWEB.war.
7. Use the jar binary from <WAS_HOME>\java\bin to rebuild the ISRAConsole.ear and the ISRASampleWEB.war.
 8. If not already open, open a command window/ command line console/ terminal window and cd to <ISRAhome>\ISRA340\Sample\tmp1\tmp2 and run:
 - a. del ISRASampleWEB.war
 - b. "<WAS_HOME>\java\bin\jar" -cvf ISRASampleWEB.war *
 - c. copy ISRASampleWEB.war ..
 - d. Enter y to overwrite the old ISRASampleWEB.war
 - e. cd ..
 - f. del ISRAConsole.ear
 - g. rmdir /S /Q tmp2 (In Windows 2012 PowerShell, use only rmdir tmp2)
 - h. "<WAS_HOME>\java\bin\jar" -cvf ISRAConsole.ear *

- i. copy ISRAConsole.ear ..
- j. Enter y to overwrite the old ISRAConsole.ear
- k. cd ..
- l. rmdir /S /Q tmp1 (In Windows 2012 PowerShell, use only rmdir tmp1)


Deploying ISRA Console and Sample Application in Standalone Environment

This section describes how to deploy the ISRA Console and Sample Application on a WebSphere Server to access ISRA in a standalone environment.


It is deployed through the WebSphere Network Manager Administrative console. The steps to deploy are:

1. Start the WebSphere first steps. Log in as the root user, change directory to `<WebSphere home>/AppServer/profiles/default/firststeps` and execute the `firststeps.sh` script, as follows:


```
# cd <WebSphere home>/AppServer/profiles/default/firststeps
# ./firststeps.sh
```
2. Log in to the WebSphere Administrative console
3. Click **Applications > Application Types > WebSphere Enterprise Applications > Install**. The following screen appears:




4. Click **Browse** to locate the **ISRAConsole.ear** and deploy the Console and Sample Application in the target environment. Also, specify a name for the application, the default name is ISRA Console.
5. Click **Next**. The following screen appears.




6. Click **Next** until the **Summary** screen appears.




7. Click **Finish**. The following screen appears:



8. Click the **Save** (directly to the master configuration) link. The following screen appears:



9. Click **Applications> Application Types> WebSphere Enterprise Applications**. Check the ISRA console and click **Start**. A message as shown in the following screen, appears:



Deploying ISRA Console and Sample Application in a Clustered Environment


This section describes how to deploy the ISRA Console and Sample Application on WebSphere Application Server to access ISRA in a clustered environment.

Note The Console and Sample Application must be deployed on an environment where session affinity is enabled.


The ISRA Console and Sample Application is deployed through the WebSphere Network Manager Admin console. The steps to deploy are:

1. Start the WebSphere first steps. Log in as the root user, change directory to `<DeploymentManager home>/profiles/dmgr/firststeps` and execute the `firststeps.sh` script, as follows:


```
# cd <DeploymentManager home>/profiles/dmgr/firststeps
# ./firststeps.sh
```
2. Log in to the WebSphere Network Manager admin console.
3. Click **Applications> Application Types> WebSphere Enterprise Applications> Install**. The following screen appears:




4. Click **Browse** to locate the **ISRAConsole.ear** and deploy the Console and Sample Application in the target environment.
5. Click **Next**. The following screen appears:




6. Click **Next**. The following screen appears:




7. Select the correct check boxes and click **Next**. The following screen appears:




8. Select **Cluster/Server** from “Clusters and Servers” list and check the module. Click **Next**. The following screen appears:




9. Click **Next**. The Summary screen appears.



10. Click **Finish**. The following screen appears:




11. Click **Save**.



12. Click **Applications > Application Types > WebSphere Enterprise Applications**. Select **ISRA Console** and click **Start**. ISRA Console and Sample Application get started.

A message, as shown in the following screen, is displayed:



13. To update web server plug-in, run the following command:


```
<DeploymentManager home>/profiles/dmgr/bin/GenPluginCfg.sh
```

Note The user must update web server plug-in after deploying web/enterprise applications.

Using the ISRA Console

To access the ISRA Console, complete the following steps:

1. Go to the location where the application is available:
(http://<AppServerName>: <AppServerPort>/<ApplicationContextRoot>)
ApplicationContextRoot is **ISRAConsole**



2. Enter the JNDI name of the library and click **Submit**.

A page showing the current values configured in the ra.xml is shown along with controls to edit the ISRA logging levels.

To access the ISRA Sample Application, a link is provided on the page.


The screenshot shows the 'ISRA Administration Console' interface. On the left, there is a 'Set ISRA Logging' section with radio buttons for 'No Logging', 'Warning and Exceptions Logging', 'Information Logging', and 'Debug Logging' (which is selected). Below these is a checkbox for 'Enable RPC Logging' which is checked. There are buttons for 'Change Logging Level' and 'View JVM Statistics'. At the bottom of the left panel are links for 'ISRA Sample Application' and 'Main Page'. The main area on the right displays 'ISRA Release Version : ISRA_3.4_FixPack_8 (Build:isr400.049.001)' and a table titled 'ISCF: Custom Properties defined in ra.xml'.

Custom Property	Value
IS Domain Name	ISRAIS42
IS Organisation Name	IBM
Product Name	IBM FileNet Image Services Resource Adapter
Product Version	ISRA 3.4.0 Enterprise
Cache Refresh Interval (in minutes)	30
Deployment Instance	0
Client Code Page	Cp1252
Char Set Encoding	ISO8859_1
Page Buffer Size (Bytes)	65536
Log File Name	C:\Program Files\IBM\WebSphere\AppServer\profiles\AppSrv04\ISRA_0_8.log
RPC Log File Name	C:\Program Files\IBM\WebSphere\AppServer\profiles\AppSrv04\ISRA_0_8_RPC.log
RPC Logging Mode	1
Logging Level	2
Logging Mode	3
Log File Size (Bytes)	5242880
Security cache mode	1
Meta Data Cache Mode	15
LDAP Implementation Class Name	com.filenet.is.ra.fnis.FN_IS_IPlanetImpl
LDAP Implementation Class String	filenetserver;389;ou=filenet,ou=people,dc=filenetroot

Changes to the logging level settings are applied to ISRA with immediate effect. The changes to logging levels are updated in the properties displayed on the screen.

The changes are valid till the application server is recycled. When the application server is restarted, the log-level settings specified in the ra.xml are used.

3. The JVM statistics can be used to study the memory usage in the Application Server JVM.




Deploying IBM FileNet Image Viewer in Standalone Environment


The IBM FileNet Image Viewer is used by the ISRA Sample Application to display documents of specific mime types (TIFF, JPEG and BMP). Skip this section and move to the next, if you do not want the IBM FileNet Image Viewer configured with the ISRA Sample Application.

The steps to deploy the IBM FileNet Image Viewer in a Standalone environment are:


1. Launch the WebSphere Administrative console. Click **Applications > Application Types > WebSphere Enterprise applications**. The following screen appears:




- Click **Browse**. Navigate through the ISRA installation directory and choose FNImageViewer.ear. Click **Next**, until the **Summary** page appears.




- Click **Finish**. The following screen appears:



- Click **Save to Master Configuration**. The following screen appears:



- Click **Applications > Application Types > WebSphere Enterprise Applications**. Enable the **FNImageViewer** check box and click **Start**. A message, as shown in the following screen, is displayed:




Note FNImageViewer.ear is located under the Sample subfolder in the ISRA installation directory. IBM FileNet Image Viewer files (FNImageViewer.jar) and IBM FileNet Image Viewer documentation are located in the FNImageViewer/docs subfolder in the ISRA installation directory.

Deploying IBM FileNet Image Viewer in Clustered Environment


The IBM FileNet Image viewer is used by the ISRA Sample Application to display documents of specific mime types (TIFF, JPEG and BMP). Skip this section and move to the next, if you do not want the IBM FileNet Image Viewer configured with the ISRA Sample Application.

The steps to deploy the IBM FileNet Image Viewer in a clustered environment are:


1. Launch the WebSphere Network Manager Admin console. Click **Applications > Application Types > WebSphere Enterprise Applications**. The following screen appears:




2. Click **Browse**. Navigate through the ISRA installation directory and choose FNImageViewer.ear. Click **OK**.
3. Click **Next**. The following screen appears:



4. Click **Next**. The following screen appears:




5. Click **Next**. The following screen appears:




6. Click **Next**. The following screen appears:




7. Click **Finish**. The following screen appears:



8. Click **Save to Master Configuration**.



9. Enable the **FNImageViewer** check box and click **Start**. A message, as shown in the following screen, is displayed:



10. To update web server plug-in, run the following command:

```
<DeploymentManager home>/profiles/dmgr/bin/GenPluginCfg.sh
```

Note **FNImageViewer.ear** is located in the `Sample` subfolder in the ISRA installation directory. IBM FileNet Image Viewer files (`FNImageViewer.jar`) and IBM FileNet Image Viewer documentation are located in the `FNImageViewer\docs` subfolder in the ISRA installation directory.

IBM FileNet Image Viewer Quick Start Feature

The Quick Start feature provides a mechanism for initializing a web browser, Java, and Image Viewer session. The background task required to initialize an Image Viewer session is performed at the time when the web browser is initialized, prior to the time when Image Viewer is actually required. This reduces the startup time of Image Viewer. This feature is supported on various operating systems, such as Microsoft Windows 98, Windows NT, Windows 2000 Professional, and Windows XP. The only web browser supported for this feature is Internet Explorer. The Quick Start feature is not enabled by default; you need to manually enable it.

Enabling Quick Start Feature

To enable quick start feature, complete the following steps:

1. Extract `FNImageViewer.ear` from the patch.
2. Check the availability of "quickstart.htm" file in the `FNImageViewer.war` extracted from `FNImageViewer.ear`.
3. Extract `ISRAConsole.ear` from the patch.
4. Extract `ISRASampleWEB.war` file from `ISRAConsole.ear`.
5. Extract 'DisplayDocument.jsp' file from `ISRASampleWEB.war`.
6. Add the highlighted tag to the file as shown in the following code segment:

```
<APPLET CODEBASE = "/FNImageViewer/FNJavaV1Files" ARCHIVE
="ji.jar"
CODE = "ji.applet.jiApplet.class" NAME = " viewONE" WIDTH =
"100%"
```

```
HEIGHT = "97%" HSPACE = 0 VSPACE = 0 ALIGN = middle
MAYSCRIPT="true">
```

```
-- -- --
```

```
<%if(RAVersion2.equalsIgnoreCase("Enterprise")){%>
```

```
-- -- --
```

```
<param name="UserId" value="<%=userId%>">
<param name="quickstartURL" value="quickstart.htm">
<%/*End of if condition where
RAVersion2.equalsIgnoreCase("Enterprise") */%>
</Applet>
```

7. Save and close the file.
8. Bundle the new file into ISRASampleWEB.war
9. Bundle the WAR file into ISRAConsole.ear.
10. Undeploy the old ISRAConsole.ear
11. Deploy the new ISRAConsole.ear.
12. Open a document in IBM FileNet Image Viewer.
13. Right-click the document to open the context menu.
14. From the context menu, click **Preferences > QuickStart** to enable the Quick Start feature. A 'tick' icon appears on the left-hand side of the Quick Start menu indicating that the feature is enabled.

Enabling the Quick Start feature adds an icon within the System tray (bottom right of the Windows desktop) and a menu item "IBM FileNet JavaView QuickStart for Internet Explorer" under **Start > Programs > Startup** menu. After enabling Quick Start, if the machine is rebooted, the Quick Start feature remains enabled. Disabling the Quick Start feature removes the Quick Start icon from the System tray and the menu item "IBM FileNet JavaView QuickStart for Internet Explorer" from the **Start > Programs > Startup** menu. The 'tick' icon on the left-hand side of the Quick Start menu (right click **document > Preferences > QuickStart**) indicating that the feature is enabled also disappears.

Known Issues in the Quick Start Feature

Following are the known issues in IBM FileNet Image Viewer:

- Web session does not end until Quick Start feature is disabled or the user explicitly logs out of the session with the Web server. If the Quick Start feature is enabled, closing the browser window(s) does not terminate the session with the Web server.
- If Quick Start is enabled and Internet Explorer is not the default browser, then on machine re-login or reboot, a message is displayed asking whether to make Internet Explorer the default browser. To avoid the message:

Open a browser window.

1. Select **Tools > Internet Options**.
2. Click the **Programs** tab and clear the **Internet Explorer should check to see whether it is the default browser** check box.
3. Click **Apply**.
4. Click **OK**.

- If the **Always** button is not selected on the security dialog box of the security certificate associated with the Image Viewer, then on machine re-login or reboot, a security dialog box is displayed.
- QuickStart feature is not available in Image Viewer if web server is accessed using IP address instead of host name in the URL.

Testing Sample Application


After the ISRA Sample Application is started, the steps to verify the deployment or to access the ISRA Sample Application are:

1. Open a web browser and enter the URL:


`http://<server>:<port>/context_root.`

For example: `http://9.126.94.39:9088/ISRA/`

The web application context_root is case sensitive. On a WebSphere server, the default port number is 9080. The default context_root of the Sample Application is ISRA.



2. Enter a valid **Username** and **Password** for the configured IS (check configured ConnectionFactory for IS details) and click **Login**.



3. Click **Help (?)** icon on the Sample Application page for details on the interaction parameters and options.

4. LDAP Configuration

In addition to direct IS logging, ISRA 3.4.0 also supports LDAP authentication by third party servers.

It is necessary to map users present on the LDAP server to the IS, before using LDAP authentication.

Note The installation of LDAP server and creation of users on the LDAP machine are out of the scope of this document.

IBM FileNet provides two utilities - ldap_export and ldap_import to map existing users on the LDAP server to the IS. These utilities are part of the IS package and must be executed on the machines running the LDAP server and the IS.

The ldap_export utility is used to export usernames on the LDAP server to an xml file. Whereas, the ldap_import utility imports user names that have been mapped to the xml file and creates corresponding users on the IS.

It is mandatory that the ldap_import algorithm and the xml file be present on the same machines, where IS exists. The ldap_import algorithm uses a hashing algorithm to generate user passwords for the IS.

Mapping Existing LDAP Server Users to IS

To configure user IDs in an IBM FileNet IS library, complete the following steps:

1. Create user entries on the LDAP server. The user attribute “uid” is used to create a user on IS. The remaining attributes (including “password”) can be assigned any value.
2. Use the **LDAP_EXP.exe** utility to export the user entries created into an XML file.
3. LDAP_EXP program has the following parameter options:

Option	Description
s <server>	LDAP server name or IP address, required value.
p <port>	LDAP port number, optional value, 389 is default.
d <binddn>	LDAP administrator bind domain name (DN), required value.
w <bindpw>	LDAP administrator bind password, required value.
t <ldap server type>	Required value for server type: msft – Microsoft Active Directory

Option	Description
	sun – Sun One Directory (iPlanet) nov – Novell eDirectory(NDS) ibm – IBM Directory
b <basedn>	LDAP Base DN, optional value.
g <grouplist filename>	Group list file for input, optional value.
o <XML output filename>	XML output filename, optional value.
l <log filename>	Log filename to use, optional value.
I	Check for special characters on <id> tags only
E	Remove all escape characters – '\'.
k	Use paged results. Windows to AD only
Z	Use secure socket connection
x <grouplist filename>	Group list file name for output, optional value.
v	Verbose log output.
c1 <user object class>	Class type for User, default is 'person'.
c2 <group object class>	Class type for Group, default is 'groupofuniquenames'.
a1 <user attribute>	Attribute to be used for user; default is 'dn'.
a2 <group attribute>	Attribute to be used for group; default is 'dn'
a3 <member attribute>	Attribute to be used for member; default is 'uniqueMember'.

Note User may use /?, -?, /h or -h to generate help.

Example command lines:

- **Sun One directory(iPlanet) server:**

```
ldap_exp -s SunSrvr1 -d "cn=Directory Manager" -w ":/
, . += " -t sun -b "dc=iPlanet ,
dc=com"
```

- **Microsoft Active Directory(AD) server:**

```
ldap_exp -s Win2KSrvr1 -d "CN=Administrator,CN=Users
,DC=win2ksrvr1"
```

```
,DC=com" -w ":/, .++="
-t msft -b "dc=win2ksrvr1,dc=com"
```

- **Novell eDirectory(NDS) server:**

```
ldap_exp.exe -s NovSrvr1 -d "cn=Admin ,o=server" -w ":/ ,.++="
-t nov -b
"o=wa"
```

- **IBM Directory server:**

```
ldap_exp -s IBMSrvr1 -d "Cn=Administrator" -w ":/, .++=" -t ibm
-b "dc=ibmsrvr1, dc=com"
```

4. Use the LDAP_IMPORT.exe for IS libraries to import the user entries from XML file into the specified IBM FileNet IS library.

Parameters:

/?	Help screen
/h<host>[:organization]	IS host or domain name, organization.
/u<id> (used with /p)	Authorized IS user name
/p"<pwd>" (used with /u)	Encrypted IS user password.
/i<file>	XML input file.

For example, to import user entries from XML file:

```
C:\>ldap_import /hIMGSESV:FileNet /ildap_exp.xml
```

Note Options are NOT case sensitive. All the information or error messages are logged to the system log or the file 'ldap_importyyyymmddlog.txt'. If username and password are not specified in the command, it prompts for username and password.

5. The IBM FileNet users created have a password generated from the corresponding user IDs.

Changing ISRA Specific Parameters for LDAP

The configurable properties to be set (modified) in **ra.xml** are:

- LdapImplClassName
- LdapImplClassString
- InherentLogin

Refer to [LdapImplClassName](#), [LdapImplClassString](#), and [InherentLogin](#) in section [Configurable ra.xml Properties](#) for details on the configuration of the respective entities.


5. Undeployment

This section describes the undeployment procedure for the ISRA and the Sample Application from the WebSphere server.


Undeploying ISRA in a Standalone Environment

To undeploy ISRA using the Administrative console:

1. Click **Resources > Resource Adapters > Resource Adapters**. The following screen appears:



2. Select the **ISRA** check box. Click **Delete**. A message, as shown in the the following screen, is displayed:




3. Click the **Save** link in the **Messages** box.


Undeploying ISRA in a Clustered Environment

To undeploy ISRA by using the Administrative console:

1. Click **Resources > Resource Adapters > Resource Adapters**. The following screen appears:



2. Select the **ISRA** check box. Click **Delete**. A message, as shown in the following screen, is displayed:




3. Click the **Save** link in the **Messages** box.


Undeploying ISRA Console and Sample Application/FNImageViewer Application in a Standalone Environment

Undeploying ISRA Console and Applications in a standalone environment on a WebSphere server physically removes the application files.


1. Click **Applications > Application Types > WebSphere Enterprise Applications**. The following screen appears:



2. Select the **FNImageViewer** and **ISRA Console** check boxes. Click **Uninstall**. A message, as shown in the following screen, is displayed:



3. Click **OK**.




4. Click **Save** to link in the **Messages** box.

-
- Note**
1. By selecting the appropriate check boxes, all or one of the applications can be uninstalled.
 2. The user must undeploy the previous version of ISRA Sample Application before deploying the latest version.
-


Undeploying ISRA Console and Sample Application/FNImageViewer Application in a Clustered Environment

Undeploying the ISRA Console and Sample Application in a clustered environment on a WebSphere server physically removes the Sample Application files.


1. Click **Applications > Application Types > WebSphere Enterprise Applications**. The following screen appears:



2. Select the **FNImageViewer** and **ISRA Console** check box and click **Uninstall**. A message, as shown in the following screen, is displayed:



3. Click **OK** to remove the application(s). The following screen appears:



4. Click **Save**. The application gets uninstalled.

Note The user must undeploy the previous version of ISRA Console and Sample Application before deploying the latest version.

6. Troubleshooting

This section describes how to troubleshoot ISRA.

Disabling NCH Broadcasts

ISRA users (application client) need to access IS libraries across routers on networks where broadcasts are disabled. This is done by creating alias entries for the IS libraries in the hosts file, where ISRA is deployed. ISRA must locate the IP address of the NCH server to find other IS services for an IS setup.

ISRA attempts to find the NCH server by generating broadcast packets, even if the NCH server was not reachable using broadcasts. User can disable NCH server location broadcasts to reduce broadcast traffic on the network.

User may want to disable NCH broadcasts if:

- Routers are present between servers
- Want no broadcast activity on the networks.
- Want to force a multi-homed server to use a specific IP address configured by the operating system network directory search facility.

The steps to specify the alias in the hosts file are:

1. Locate **hosts file** on the server. It is located in the `/etc` folder on UNIX systems. On a Microsoft Windows Server, it is located in the `\system32\drivers\etc` folder in the Windows system directory.
2. Open the hosts file with a preferred text editor. If a host file does not exist, create a new file using a preferred text editor.
3. For each IBM FileNet library that user needs to connect through ISRA, entries must be made in the hosts file as: `<IP address of domain:organization> <domain-organization>-nch-server`, where:
 - `<IP address of domain:organization>` is IP address of an IBM FileNet domain and organization identifying the target IBM FileNet library system (NCH Server).
 - `<domain-organization>` is domain and organization name. When specifying the domain-organization name, follow these rules:
 - Delete all characters except ASCII alphanumeric characters and hyphens.
 - Convert all upper case characters to lower case.
 - Insert a hyphen between the domain and organization names.
 - Append nch-server as a literal.

For example, if an IBM FileNet library has a domain, `fn_is`, the organization is `ibm`, and its IP address is `123.45.6.78`, the hosts file entry is:

```
123.45.6.78  fnis-ibm-nch-server
```

Appendix A: ra.xml

ra.xml

```
<?xml version="1.0" encoding="UTF-8"?>

<!DOCTYPE connector PUBLIC "-//Sun Microsystems, Inc.//DTD Connector
1.0//EN" 'http://java.sun.com/dtd/connector_1_0.dtd'>

<connector>
  <display-name>ISRA</display-name>
  <vendor-name>IBM</vendor-name>
  <spec-version>1.0</spec-version>
  <eis-type>IBM FileNet Image Services</eis-type>
  <version>3.4.0</version>
  <license>
    <license-required>>false</license-required>
  </license>
  <resourceadapter>
    <managedconnectionfactory-
class>com.filenet.is.ra.spi.FN_IS_SpiManagedConnectionFactory</managedc
onnectionfactory-class>
    <connectionfactory-
interface>javax.resource.cci.ConnectionFactory</connectionfactory-
interface>
    <connectionfactory-impl-
class>com.filenet.is.ra.cci.FN_IS_CciConnectionFactory</connectionfacto
ry-impl-class>
    <connection-interface>javax.resource.cci.Connection</connection-
interface>
    <connection-impl-
class>com.filenet.is.ra.cci.FN_IS_CciConnection</connection-impl-class>
    <transaction-support>NoTransaction</transaction-support>
  <config-property>
    <description>Domain name of the Image Services
Server</description>
    <config-property-name>DomainName</config-property-name>
    <config-property-type>java.lang.String</config-property-type>
    <config-property-value>FileNetIS</config-property-value>
  </config-property>
  <config-property>
    <description>Organization name of the Image Services
Server</description>
    <config-property-name>OrganizationName</config-property-name>
    <config-property-type>java.lang.String</config-property-type>
    <config-property-value>IBM</config-property-value>
  </config-property>
  <config-property>
    <description>0-Exceptions and Warnings; 1-Info; 2-Debug
Level</description>
    <config-property-name>LoggingLevel</config-property-name>
    <config-property-type>java.lang.Integer</config-property-type>
    <config-property-value>0</config-property-value>
```

```

    </config-property>
    <config-property>
      <description>0-No Logging; 1-Console Logging; 2-File Logging; 3-
Both(File and console)</description>
      <config-property-name>LoggingMode</config-property-name>
      <config-property-type>java.lang.Integer</config-property-type>
      <config-property-value>3</config-property-value>
    </config-property>
    <config-property>
      <description>Page data fetch size (in kilo bytes)</description>
      <config-property-name>PageBufferSize</config-property-name>
      <config-property-type>java.lang.Integer</config-property-type>
      <config-property-value>64</config-property-value>
    </config-property>
    <config-property>
      <description>Cache refresh interval(in minutes)</description>
      <config-property-name>CacheRefreshInterval</config-property-name>
      <config-property-type>java.lang.Integer</config-property-type>
      <config-property-value>30</config-property-value>
    </config-property>
    <!-- Added by IBM for caching of groups only-->
    <config-property>
      <description>Security cache mode(1-caches users and groups 2-
caches groups only)</description>
      <config-property-name>SecurityCacheMode</config-property-name>
      <config-property-type>java.lang.Integer</config-property-type>
      <config-property-value>1</config-property-value>
    </config-property>

    <!-- Added by IBM for selective metadata cache refresh-->
    <config-property>
      <description>Selective metadata refresh(0-No refresh 1-printer
cache 2-doc class cache 4-key fields cache 8-menu values cache
)</description>
      <config-property-name>MetaDataCacheRefreshMode</config-property-
name>
      <config-property-type>java.lang.Integer</config-property-type>
      <config-property-value>15</config-property-value>
    </config-property>

    <config-property>
      <description>Name of the Product</description>
      <config-property-name>ProductName</config-property-name>
      <config-property-type>java.lang.String</config-property-type>
      <config-property-value>IBM FileNet Image Services Resource
Adapter</config-property-value>
    </config-property>
    <config-property>
      <description>Product Version</description>
      <config-property-name>ProductVersion</config-property-name>
      <config-property-type>java.lang.String</config-property-type>
      <config-property-value>ISRA 3.4.0 Enterprise</config-property-
value>
    </config-property>
    <config-property>
      <description>ISRA Logfile name (can include path) </description>
      <config-property-name>LogFileName</config-property-name>

```

```

        <config-property-type>java.lang.String</config-property-type>
        <config-property-value>ISRA.log</config-property-value>
    </config-property>
    <config-property>
        <description>Maximum Size of ISRA LogFile (in mega
bytes)</description>
        <config-property-name>LogFileSize</config-property-name>
        <config-property-type>java.lang.Integer</config-property-type>
        <config-property-value>5</config-property-value>
    </config-property>
    <config-property>
        <description>LDAP Authentication Class Name</description>
        <config-property-name>LdapImplClassName</config-property-
name>
        <config-property-type>java.lang.String</config-property-
type>
        <config-property-
value>com.filenet.is.ra.fnis.FN_IS_IPlanetImpl</config-property-value>
    </config-property>
    <config-property>
        <description>Server details for LDAP Authentication
</description>
        <config-property-name>LdapImplClassString</config-property-
name>
        <config-property-type>java.lang.String</config-property-
type>
        <config-property-
value>filenetserver;389;ou=filenet,ou=people,dc=filenetroot</config-
property-value>
    </config-property>
    <config-property>
        <description>Inherently login through LDAP authentication
or not 0-Direct IS Login;1-LDAP Authentication</description>
        <config-property-name>InherentLogin</config-property-name>
        <config-property-type>java.lang.Integer</config-property-type>
        <config-property-value>0</config-property-value>
    </config-property>
    <config-property>
        <description>ISRA instance that is currently being deployed on a
single machine; Min Value = 1, Max Value = 100</description>
        <config-property-name>DeploymentInstance</config-property-name>
        <config-property-type>java.lang.Integer</config-property-type>
        <config-property-value>1</config-property-value>
    </config-property>
    <config-property>
        <description>Parameter to enable PCH Logging in ISRA
</description>
        <config-property-name>PCHLogging</config-property-name>
        <config-property-type>java.lang.String</config-property-type>
        <config-property-value>Disabled</config-property-value>
    </config-property>
    <config-property>
        <description>LDAP Anonymous user login flag</description>
        <config-property-name>AllowAnonymousUser</config-property-
name>
        <config-property-type>java.lang.Boolean</config-property-type>
        <config-property-value>true</config-property-value>

```

```

</config-property>
<config-property>
  <description>0-No Logging; 1-File Logging</description>
  <config-property-name>RPCLogging</config-property-name>
  <config-property-type>java.lang.Integer</config-property-type>
  <config-property-value>0</config-property-value>
</config-property>
<config-property>
  <description>Codepage for ISRA</description>
  <config-property-name>ClientCodepage</config-property-name>
  <config-property-type>java.lang.String</config-property-type>
  <config-property-value>cp1250</config-property-value>
</config-property>
<config-property>
  <description>Set this flag to true if your application displays
the dates returned from ISRA in GMT Timezone</description>
  <config-property-name>GMTEnabled</config-property-name>
  <config-property-type>java.lang.Boolean</config-property-type>
  <config-property-value>>false</config-property-value>
</config-property>
<config-property>
  <description>Locale of the Image Services Server (two letter ISO
language code, for example en, de, ar, ja)</description>
  <config-property-name>ISLocale</config-property-name>
  <config-property-type>java.lang.String</config-property-type>
  <config-property-value>en</config-property-value>
</config-property>
<config-property>
  <description>It is a configurable parameter to Ignore [77,0,11 The
object is busy] error, incase of DocMigration</description>
  <config-property-name>IgnoreObjectBusyMsgInDocMigration</config-
property-name>
  <config-property-type>java.lang.Boolean</config-property-type>
  <config-property-value>>false</config-property-value>
</config-property>
  <authentication-mechanism>
  <authentication-mechanism-type>BasicPassword</authentication-
mechanism-type>
  <credential-
interface>javax.resource.security.PasswordCredential</credential-
interface>
  </authentication-mechanism>
  <reauthentication-support>>false</reauthentication-support>
</resourceadapter>
</connector>

```

Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing

IBM Corporation

North Castle Drive

Armonk, NY 10504-1785

U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

IBM World Trade Asia Corporation

Licensing

2-31 Roppongi 3-chome, Minato-ku

Tokyo 106-0032, Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation

J46A/G4

555 Bailey Avenue

San Jose, CA 95141-1003

U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs.

Trademarks

- IBM is a registered trademark of International Business Machines Corporation in the United States, other countries, or both.

- Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.
- Cell Broadband Engine is a trademark of Sony Computer Entertainment, Inc. in the United States, other countries, or both and is used under license there from.
- Java and all Java-based trademarks are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.
- Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.
- Intel, Intel logo, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo, Celeron, Intel Xeon, Intel SpeedStep, Itanium, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.
- UNIX is a registered trademark of The Open Group in the United States and other countries.
- Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.
- ITIL is a registered trademark, and a registered community trademark of the Office of Government Commerce, and is registered in the U.S. Patent and Trademark Office.
- IT Infrastructure Library is a registered trademark of the Central Computer and Telecommunications Agency, which is now part of the Office of Government Commerce.
- Other company, product, or service names may be trademarks or service marks of others.

Index

- AllowAnonymousUser, 25, 33
- CacheRefreshInterval, 25, 28
- Changing ISRA Specific Parameters, 23
- Changing ISRA Specific Parameters for LDAP, 59
- ClientCodepage, 25, 34
- Configuring Deployed ISRA, 22
- Configuring Multiple IS Server with ISRA, 37
- Configuring Sample Application, 38
- Configuring WebSphere-Specific Parameters, 35
- Deploying IBM FileNet Image Viewer in Clustered Environment, 50
- Deploying IBM FileNet Image Viewer in Standalone Environment, 48
- Deploying ISRA Console and Sample Application in Clustered Environment, 43
- Deploying ISRA Console and Sample Application in Standalone Environment, 41
- Deploying ISRA in a Clustered Environment, 11
- Deploying ISRA in a Standalone Environment, 8
- Deploying ISRA in an Application Server Cell, 16
- Deployment Requirements, 7
- DeploymentInstance, 21, 25, 31
- Disabling NCH Broadcasts, 65
- DomainName, 25
- Enabling Quick Start Feature, 53
- GMTEnabled flag, 35
- Hardware Requirements, 7
- IBM FileNet Image Viewer Quick Start Feature, 53
- IgnoreObjectBusyMsgInDocMigration, 35
- InherentLogin, 25, 31
- ISLocale, 35
- ISRA Console, 38
- Known Issues in the Quick Start Feature, 54
- LdapImplClassName, 25, 30
- LdapImplClassString, 25, 31
- LogFileName, 25, 29
- LogFileSize, 25, 30
- LoggingLevel, 25, 26
- LoggingMode, 25, 27
- Mandatory Requirements for ISRA, 19
- Mapping Existing LDAP Server Users to IS, 57
- OrganizationName, 25, 26
- PageBufferSize, 25, 27
- PCHLogging, 25, 32
- RPCLogging, 25, 33
- Software Requirements, 7
- Testing Sample Application, 55
- Undeploying ISRA Console and Sample Application/FNImageViewer Application in a Clustered Environment, 63
- Undeploying ISRA Console and Sample Application/FNImageViewer Application in a Standalone Environment, 62
- Undeploying ISRA in a Clustered Environment, 61
- Undeploying ISRA in a Standalone Environment, 60
- Using the ISRA Console, 46