



## IBM Tivoli Training Netcool/Proviso 4.4.3

### *Diagnostic reports*



© 2009 IBM Corporation  
Updated July 10, 2009

This IBM Education Assistant module describes diagnostic reports.

## Objectives

Upon completion of this module, you should be able to:

- View diagnostic reports
- Add diagnostic reports to a report user

Upon completion of this module you should be able to navigate to diagnostic reports and add these reports to a report user.

## Assumptions

Before adding diagnostic reports:

- You must log in to the DataMart host as **pvuser**
- You must have a report user created

Before adding diagnostic reports:

- You must log in to the DataMart host as **pvuser**.
- And you must have a report user created.

## Diagnostic reports

Valuable data flow information can be found using a diagnostic report. This information includes:

- The collection formula used in the report
- The resource used in the report, and the related group

Diagnostic Report									
Daily report for May 6, 2009 through May 6, 2009									
Current resource									
Resource Type	Resource ID	Resource Name	Alias	Type	State	Date of last action	Last action	Origin	User
group	200000095	192.168.14.61	--	generated	on	04/22/09 12:35	Insert	inventory	pvuser
subelement	200000086	192.168.14.61_IF: 24 *100 Mbps* "Fa0/24 "	192.168.14.61_IF: 24 *100 Mbps* "Fa0/24 "	fixed	on	04/22/09 12:34	Insert	inventory	pvuser
Current resource metric counts									
Metric Name	Metric ID	Time zone offset	Raw count	Daily RA count	Weekly RA count	Monthly RA count	Daily GA Count	Weekly GA count	Monthly GA count
Availability Unknown (percent)	10426	-18000	8	1	--	--	1	--	--
Inbound Throughput (bps)	2208	-18000	8	1	--	--	1	--	--
Inbound Utilization (percent)	2206	-18000	8	1	--	--	1	--	--

A diagnostic report is an alternate view of a Netcool/Proviso report. The diagnostic view of a report shows data as it is stored in the database. Diagnostic reports are helpful when troubleshooting data flow problems, especially when a table or chart in a report is unable to display metric data. Troubleshooting information includes:

- The collection formula used to obtain the metric in the report
- And the resource used in the report, along with group membership information

## Navigating to a diagnostic report

The screenshot shows a web browser window displaying the Tivoli Netcool/Proviso interface. The browser's address bar shows the path: [HOME] : NOC Reporting : Devices : Interfaces. The page title is "Tivoli Netcool / Proviso". The main content area is titled "Device Health Summary" and includes a "Group Summary Report" for "Date May 7, 2009" and "Period Daily". Below this, there is a "Health Summary for all Devices" section with two bar charts: "Device Availability (percent)" and "Interface Availability (percent)". The "Device Availability" chart shows a single green bar at 100%. The "Interface Availability" chart shows a red bar at approximately 60% and a green bar at 100%. A legend below the charts explains the color coding: red for resources in the range <math>< 90.0</math>, orange for <math>90.0-99.0</math>, and green for <math>\geq 99.0</math>. A yellow callout bubble with the text "Click Diagnose" points to the "Diagnose" button in the top navigation menu. The footer of the page contains the text "Diagnostic reports" and "© 2009 IBM Corporation".

To view a diagnostic report, the account of the report user must be modified. After the report user account has the diagnostic feature added, the user will have a **Diagnose** button at the top of their portal. When viewing any Netcool/Proviso report, you can click the **Diagnose** button to see the report in the diagnostic view.

## Diagnostic reports prerequisites

Before you add diagnostic reports, you must gather the following information using resource manager (**resmgr**):

1. The database index of the report user who will be able to see diagnostic reports
2. The name of the user property that enables diagnostic reports
3. The database index of the diagnostic report

Before adding diagnostic reports, you must gather the following three values from the database using resource manager, or **resmgr**. The **resmgr** command is a DataMart tool that interacts with the Netcool/Proviso database.

The three values are:

- 1.The database index of the report user who will be able to see diagnostic reports
- 2.The name of the user property that enables diagnostic reports
- 3.The database index of the diagnostic report

You will now look at three **resmgr** commands that will display these values. Use the **resmgr** command as the UNIX® user **pvuser**.

## Finding the report user database index

```
$ resmgr -export rusr -colNames "dbIndex name"
...
#
# cmdLine = -export rusr -colNames "dbIndex
  name"
49000008 | _ | SSSW\\SuperUser | _ |
100003411 | _ | SSSW\\customer_a | _ |
100003412 | _ | SSSW\\customer_z | _ |
100003414 | _ | SSSW\\noc | _ |
```

This first command displays the database index and name of all report users. In this example you will add diagnostic reports to the **noc** user. The **noc** user has the database index of 100003414.

## Finding the user property

```
$ resmgr -export ruprp -colNames "name" | grep -i Troub  
DV_UserTroubleShootingReport |_ |
```

This second command displays a list of available user properties. Because the output of this command is long, it is filtered for the string **Troub**. The name of the user property is **DV\_UserTroubleShootingReport**.

## Finding the diagnostic report database index

```
resmgr -export app -colNames "dbIndex name" | grep -i diag  
49000026|_|Diagnostic Report|_|<E>  
49000033|_|Metric Diagnostic Report|_|<E>
```

This third command displays a list of all reports with their database index. Because the output of this command is long, it is filtered for the string **diag**. The name of the report is **Diagnostic Report**. In this example, the report has the database index of 49000026.

## Adding diagnostic reports to a Web user

After you have gathered these three values, create a relationship among them in the database by combining them in the following command.

```
$ resmgr -import rusr -colNames "dbIndex ruprp.name  
ruprp.value" -line "Report User DB Index|_|Property  
Name|_|Diagnostic Report DB Index|_|"
```

After you have gathered these three values, create a relationship among them in the database by combining them into this **resmgr** command.

In this command:

**Report User DB Index** is the numeric database index associated with the user who will be able to view the diagnostic report page.

**Property Name** is the text string name of the user property.

**Diagnostic Report DB Index** is the numeric database index assigned to the diagnostic report.

## Command example

```
resmgr -import rusr -colNames "dbIndex ruprp.name ruprp.value"  
-line "100003414|_|DV_UserTroubleShootingReport|_|49000026|_|"
```

```
Info : === insert : nothing ON Report User ( SSSW\\noc )  
(exists)
```

```
Info : === insert : nothing ON property (  
DV_UserTroubleShootingReport ) (exists)
```

```
Info : === insert : INSERT ON Ruser property ( 100003414  
49000028 49000026 ) (does not exist)
```

In this example of the previous command, **resmgr** is used to create a link in the database between:

- Report user 100003414
- The user property DV\_UserTroubleShootingReport
- And the diagnostic report 49000026.

The last line of output indicates that a link between these three values was inserted into the database. The user will now be able to use diagnostic reports.

## Summary

You should now be able to:

- Use diagnostic reports
- Add diagnostic reports to a report user

You should now be able to:

- Use diagnostic reports.
- And add diagnostic reports to a report user.

## Training roadmap for *Netcool/Proviso*

[http://www.ibm.com/software/tivoli/education/edu\\_prd.html](http://www.ibm.com/software/tivoli/education/edu_prd.html)



Use this link to explore the training roadmap for IBM Tivoli Netcool/Proviso.

## Trademarks, copyrights, and disclaimers

IBM, the IBM logo, ibm.com, and the following terms are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both:  
Tivoli

If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of other IBM trademarks is available on the Web at "Copyright and trademark information" at <http://www.ibm.com/legal/copytrade.shtml>

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other company, product, or service names may be trademarks or service marks of others.

Product data has been reviewed for accuracy as of the date of initial publication. Product data is subject to change without notice. This document could include technical inaccuracies or typographical errors. IBM may make improvements or changes in the products or programs described herein at any time without notice. Any statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only. References in this document to IBM products, programs, or services does not imply that IBM intends to make such products, programs or services available in all countries in which IBM operates or does business. Any reference to an IBM Program Product in this document is not intended to state or imply that only that program product may be used. Any functionally equivalent program, that does not infringe IBM's intellectual property rights, may be used instead.

THE INFORMATION PROVIDED IN THIS DOCUMENT IS DISTRIBUTED "AS IS" WITHOUT ANY WARRANTY, EITHER EXPRESS OR IMPLIED. IBM EXPRESSLY DISCLAIMS ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NONINFRINGEMENT. IBM shall have no responsibility to update this information. IBM products are warranted, if at all, according to the terms and conditions of the agreements (for example, IBM Customer Agreement, Statement of Limited Warranty, International Program License Agreement, etc.) under which they are provided. Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products in connection with this publication and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products.

IBM makes no representations or warranties, express or implied, regarding non-IBM products and services.

The provision of the information contained herein is not intended to, and does not, grant any right or license under any IBM patents or copyrights. Inquiries regarding patent or copyright licenses should be made, in writing, to:

IBM Director of Licensing  
IBM Corporation  
North Castle Drive  
Armonk, NY 10504-1785  
U.S.A.

Performance is based on measurements and projections using standard IBM benchmarks in a controlled environment. All customer examples described are presented as illustrations of how those customers have used IBM products and the results they may have achieved. The actual throughput or performance that any user will experience will vary depending upon considerations such as the amount of multiprogramming in the user's job stream, the I/O configuration, the storage configuration, and the workload processed. Therefore, no assurance can be given that an individual user will achieve throughput or performance improvements equivalent to the ratios stated here.

© Copyright International Business Machines Corporation 2009. All rights reserved.

Note to U.S. Government Users - Documentation related to restricted rights-Use, duplication or disclosure is subject to restrictions set forth in GSA ADP Schedule Contract and IBM Corp.

