

WebSphere MQ



Constants

Version 7.0

WebSphere MQ



Constants

Version 7.0

Note

Before using this information and the product it supports, be sure to read the general information under notices at the back of this book.

Second edition (January 2009)

This edition of the book applies to the following product:

- IBM WebSphere MQ, Version 7.0

and to any subsequent releases and modifications until otherwise indicated in new editions.

© **Copyright International Business Machines Corporation 2005, 2009.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Tables ix

Chapter 1. WebSphere MQ COPY, header, include, and module files. 1

C header files	1
COBOL COPY files	1
PL/I include files.	3
RPG copy files.	3
Visual Basic module files	5
z/OS Assembler COPY files	6

Chapter 2. Constants 9

MQ_* (String Lengths)	9
MQ_* (Command format String Lengths)	12
MQACH_* (API exit chain area header structure).	13
MQACT_* (Accounting Token)	13
MQACT_* (Command format Action Options).	13
MQACTP_* (Action)	13
MQACTT_* (Accounting Token Types)	13
MQADOPT_* (Adopt New MCA Checks)	14
MQADOPT_* (Adopt New MCA Types).	14
MQAIR_* (Authentication information record structure)	14
MQAIT_* (Authentication Information Type)	14
MQAS_* (Command format Asynchronous State Values)	14
MQAT_* (Put Application Types)	15
MQAUTH_* (Command format Authority Values)	16
MQAUTHOPT_* (Command format Authority Options)	16
MQAXC_* (API exit context structure)	16
MQAXP_* (API exit parameter structure)	17
MQBA_* (Byte Attribute Selectors)	17
MQBACF_* (Command format Byte Parameter Types)	17
MQBL_* (Buffer Length for mqAddString and mqSetString)	17
MQBMHO_* (Buffer to message handle options structure)	18
MQBMHO_* (Buffer To Message Handle Options)	18
MQBND_* (Default Bindings)	18
MQBO_* (Begin options structure).	18
MQBO_* (Begin Options).	18
MQBT_* (Command format Bridge Types)	18
MQCA_* (Character Attribute Selectors).	18
MQCACF_* (Command format Character Parameter Types)	21
MQCACH_* (Command format Character Channel Parameter Types)	25
MQCADSD_* (CICS information header ADS Descriptors)	26
MQCAFTY_* (Connection Affinity Values)	26
MQCAMO_* (Command format Character Monitoring Parameter Types)	26
MQCBC_* (MQCBC constants structure).	27

MQCBCF_* (MQCBC constants Flags)	27
MQCBCT_* (MQCBC constants Callback type)	27
MQCBD_* (MQCBD constants structure)	27
MQCBDO_* (MQCBD constants Callback Options)	27
MQCBO_* (Create-Bag Options for mqCreateBag)	28
MQCBT_* (MQCBD constants This is the type of the Callback Function)	28
MQCC_* (Completion Codes)	28
MQCCSI_* (Coded Character Set Identifiers)	28
MQCCT_* (CICS information header Conversational Task Options).	28
MQCD_* (Channel definition structure)	29
MQCDC_* (Channel Data Conversion)	29
MQCF_* (Capability Flags)	29
MQCFAC_* (CICS information header Facility)	29
MQCFBF_* (Command format byte string filter parameter structure)	30
MQCFBS_* (Command format byte string parameter structure)	30
MQCFC_* (Command format header Control Options)	30
MQCFGR_* (Command format group parameter structure)	30
MQCFH_* (Command format header structure)	30
MQCFIF_* (Command format integer filter parameter structure)	30
MQCFIL_* (Command format integer list parameter structure)	30
MQCFIL64_* (Command format 64-bit integer list parameter structure)	30
MQCFIN_* (Command format integer parameter structure)	30
MQCFIN64_* (Command format 64-bit integer parameter structure)	31
MQCFO_* (Command format Refresh Repository Options)	31
MQCFO_* (Command format Remove Queues Options)	31
MQCFOP_* (Command format Filter Operators)	31
MQCFR_* (CF Recoverability)	31
MQCFSF_* (Command format string filter parameter structure)	31
MQCFSL_* (Command format string list parameter structure)	31
MQCFST_* (Command format string parameter structure)	32
MQCFSTATUS_* (Command format CF Status)	32
MQCFT_* (Command format Types of Structure).	32
MQCFTYPE_* (Command format CF Types)	33
MQCFUNC_* (CICS information header Functions)	33
MQCGWI_* (CICS information header Get Wait Interval)	33
MQCHAD_* (Channel Auto Definition)	33
MQCHIDS_* (Command format Indoubt Status)	33
MQCHLD_* (Command format Channel Dispositions)	34

MQCHS_* (Command format Channel Status).	34	MQDL_* (Distribution Lists).	48
MQCHSH_* (Command format Channel Shared Restart Options).	34	MQDLH_* (Dead-letter header structure)	48
MQCHSR_* (Command format Channel Stop Options)	34	MQDLV_* (Persistent/Non-persistent Message Delivery)	48
MQCHSSTATE_* (Command format Channel Substates)	34	MQDMHO_* (Delete message handle options structure)	48
MQCHT_* (Channel Types)	35	MQDMHO_* (Delete Message Handle Options)	48
MQCHTAB_* (Command format Channel Table Types)	35	MQDMPO_* (Delete message property options structure)	48
MQCI_* (Correlation Identifier).	35	MQDMPO_* (Delete Message Property Options)	48
MQCIH_* (CICS information header structure)	35	MQDNSWLM_* (DNS WLM)	49
MQCIH_* (CICS information header Flags).	36	MQDT_* (Destination Types)	49
MQCLCT_* (Cluster Cache Types).	36	MQDXP_* (Conversion exit parameter structure)	49
MQCLRS_* (Command format Clear Topic String Scope)	36	MQEC_* (Signal Values)	49
MQCLRT_* (Command format Clear Topic String Type)	36	MQEI_* (Expiry).	49
MQCLT_* (CICS information header Link Types).	36	MQENC_* (Encoding).	49
MQCLWL_* (Cluster Workload)	36	MQENC_* (Encoding Masks)	49
MQCMD_* (Command Codes)	37	MQENC_* (Encodings for Binary Integers)	50
MQCMDI_* (Command format Command Information Values).	41	MQENC_* (Encodings for Packed Decimal Integers)	50
MQCMDL_* (Command Levels)	41	MQENC_* (Encodings for Floating Point Numbers)	50
MQCMHO_* (Create message handle options structure)	42	MQEPH_* (Embedded command format header structure)	50
MQCMHO_* (Create Message Handle Options)	42	MQEPH_* (Embedded command format header Flags)	50
MQCNO_* (Connect options structure)	42	MQET_* (Command format Escape Types)	50
MQCNO_* (Connect Options)	42	MQEVO_* (Command format Event Origins)	50
MQCO_* (Close Options).	43	MQEVR_* (Command format Event Recording)	51
MQCODL_* (CICS information header Output Data Length).	43	MQEXPI_* (Expiration Scan Interval).	51
MQCOMPRESS_* (Channel Compression)	43	MQFB_* (Feedback Values)	51
MQCONNID_* (Connection Identifier)	43	MQFC_* (Command format Force Options).	52
MQCOPY_* (Property Copy Options).	43	MQFMT_* (Formats)	52
MQCQT_* (Cluster Queue Types)	44	MQGA_* (Group Attribute Selectors).	54
MQCRC_* (CICS information header Return Codes)	44	MQGACF_* (Command format Group Parameter Types)	54
MQCS_* (MQCBC constants Consumer state)	44	MQGI_* (Group Identifier)	54
MQCSC_* (CICS information header Start Codes)	44	MQGMO_* (Get message options structure)	54
MQCSP_* (Connection security parameters structure)	45	MQGMO_* (Get Message Options)	54
MQCSP_* (Connection security parameters Authentication Types)	45	MQGS_* (Group Status)	55
MQCSRV_* (Command Server Options).	45	MQHA_* (Handle Selectors).	55
MQCT_* (Queue Manager Connection Tag).	45	MQHB_* (Bag Handles)	56
MQCTES_* (CICS information header Task End Status)	45	MQHC_* (Connection Handles)	56
MQCTLO_* (MQCTL options structure)	45	MQHM_* (Message handle)	56
MQCTLO_* (MQCTL options Consumer Control Options)	46	MQHO_* (Object Handle)	56
MQCUOWC_* (CICS information header Unit-of-Work Controls)	46	MQHSTATE_* (Command format Handle States).	56
MQCXP_* (Channel exit parameter structure)	46	MQIA_* (Integer Attribute Selectors)	56
MQDC_* (Destination Class).	46	MQIACF_* (Command format Integer Parameter Types)	61
MQDCC_* (Conversion Options)	46	MQIACH_* (Command format Integer Channel Types)	67
MQDCC_* (Conversion Options Masks and Factors)	47	MQIAMO_* (Command format Integer Monitoring Parameter Types)	70
MQDELO_* (Publish/Subscribe Delete Options)	47	MQIAMO64_* (Command format 64-bit Integer Monitoring Parameter Types)	72
MQDH_* (Distribution header structure)	47	MQIASY_* (Integer System Selectors).	72
MQDHF_* (Distribution header Flags)	47	MQIAUT_* (IMS information header Authenticator)	72
MQDISCONNECT_* (Command format Disconnect Types)	47	MQIAV_* (Integer Attribute Values)	72
		MQICM_* (IMS information header Commit Modes)	73
		MQIDO_* (Command format Indoubt Options)	73
		MQIGQ_* (Intra-Group Queuing)	73
		MQIGQA_* (Intra-Group Queuing Put Authority)	73
		MQIIH_* (IMS information header structure)	73

MQIIH_* (IMS information header Flags)	73	MQOPER_* (Activity Operations)	82
MQIMPO_* (Inquire message property options structure)	73	MQOT_* (Object Types)	82
MQIMPO_* (Inquire Message Property Options)	74	MQOT_* (Extended Object Types)	82
MQINBD_* (Command format Inbound Dispositions)	74	MQPA_* (Put Authority)	83
MQIND_* (Special Index Values)	74	MQPD_* (Property descriptor structure)	83
MQIPADDR_* (IP Address Versions)	74	MQPD_* (Property Descriptor Options)	83
MQISS_* (IMS information header Security Scopes)	74	MQPD_* (Property Support Options)	83
MQIT_* (Index Types)	74	MQPD_* (Property Context)	84
MQITEM_* (Item Type for mqInquireItemInfo)	75	MQPER_* (Persistence Values)	84
MQITIL_* (IMS information header Transaction Instance Identifier)	75	MQPL_* (Platforms)	84
MQITS_* (IMS information header Transaction States)	75	MQPMO_* (Put message options structure)	84
MQKAI_* (KeepAlive Interval)	75	MQPMO_* (Put Message Options)	85
MQMASTER_* (Master administration)	75	MQPMO_* (Put Message Options for publish mask)	85
MQMCAS_* (Command format Message Channel Agent Status)	75	MQPMRF_* (Put Message Record Fields)	85
MQMCAT_* (MCA Types)	75	MQPO_* (Command format Purge Options)	86
MQMCD_* (Publish/Subscribe Options Tag Message Content Descriptor (mcd) Tags)	76	MQPRI_* (Priority)	86
MQMCD_* (Publish/Subscribe Options Tag Tag names)	76	MQPROP_* (Queue and Channel Property Control Values)	86
MQMCD_* (Publish/Subscribe Options Tag XML tag names)	76	MQPROP_* (Maximum Properties Length)	86
MQMCD_* (Publish/Subscribe Options Tag Tag values)	76	MQPRT_* (Put Response Values)	86
MQMD_* (Message descriptor structure)	76	MQPS_* (Command format Pub/Sub Status)	86
MQMDE_* (Message descriptor extension structure)	77	MQPS_* (Publish/Subscribe Tags as strings)	87
MQMDEF_* (Message descriptor extension Flags)	77	MQPS_* (Publish/Subscribe Tags as blank-enclosed strings)	87
MQMDS_* (Message Delivery Sequence)	77	MQPS_* (Publish/Subscribe Command Tag Values as strings)	88
MQMF_* (Message Flags)	77	MQPS_* (Publish/Subscribe Command Tag Values as blank-enclosed strings)	88
MQMHBO_* (Message handle to buffer options structure)	77	MQPS_* (Publish/Subscribe Options Tag Values as strings)	88
MQMHBO_* (Message Handle To Buffer Options)	77	MQPS_* (Publish/Subscribe Options Tag Values as blank-enclosed strings)	89
MQMI_* (Message Identifier)	78	MQPSC_* (Publish/Subscribe Options Tag Publish/Subscribe Command Folder (psc) Tags)	90
MQMMBI_* (Message Mark-Browse Interval)	78	MQPSC_* (Publish/Subscribe Options Tag Tag names)	90
MQMO_* (Match Options)	78	MQPSC_* (Publish/Subscribe Options Tag XML tag names)	91
MQMODE_* (Command format Mode Options)	78	MQPSC_* (Publish/Subscribe Options Tag Values as strings)	91
MQMON_* (Monitoring Values)	78	MQPSC_* (Publish/Subscribe Options Tag Values as strings)	92
MQMT_* (Message Types)	79	MQPSCR_* (Publish/Subscribe Options Tag Publish/Subscribe Response Folder (pscr) Tags)	92
MQMTOK_* (Message Token)	79	MQPSCR_* (Publish/Subscribe Options Tag Tag names)	92
MQNC_* (Name Count)	79	MQPSCR_* (Publish/Subscribe Options Tag XML tag names)	93
MQNPM_* (Nonpersistent Message Class)	79	MQPSCR_* (Publish/Subscribe Options Tag Tag values)	93
MQNPMS_* (NonPersistent-Message Speeds)	79	MQPSM_* (Pub/Sub Mode)	93
MQNT_* (Namelist Types)	79	MQPSPROP_* (Pub/Sub Message Properties)	93
MQNVS_* (Names for Name/Value String)	80	MQPSST_* (Command format Pub/Sub Status Type)	93
MQOA_* (Limits for Selectors for Object Attributes)	80	MQPUBO_* (Publish/Subscribe Publication Options)	93
MQOD_* (Object descriptor structure)	80	MQPXP_* (Publish/subscribe routing exit parameter structure)	94
MQOII_* (Object Instance Identifier)	80	MQQA_* (Inhibit Get Values)	94
MQOL_* (Original Length)	80	MQQA_* (Inhibit Put Values)	94
MQOM_* (Obsolete DB2 Messages options on Inquire Group)	80	MQQA_* (Queue Shareability)	94
MQOO_* (Open Options)	80	MQQA_* (Back-Out Hardening)	94
MQOO_* (Following used in C++ only)	81		
MQOP_* (Operation codes for MQCTL)	81		
MQOP_* (Operation codes for MQCB)	81		
MQOP_* (Operation codes for MQCTL and MQCB)	81		
MQOPEN_* (Values related to MQOPEN_PRIV structure)	81		

MQQDT_* (Queue Definition Types)	94	MQSCO_* (SSL configuration options Key Reset Count)	121
MQQF_* (Queue Flags)	94	MQSCO_* (Command format Queue Definition Scope)	121
MQQMDT_* (Command format Queue Manager Definition Types)	95	MQSCOPE_* (Publish scope)	121
MQQMF_* (Queue Manager Flags)	95	MQSCYC_* (Security Case)	121
MQQMFAC_* (Command format Queue Manager Facility)	95	MQSD_* (Object descriptor structure)	121
MQQMSTA_* (Command format Queue Manager Status)	95	MQSECITEM_* (Command format Security Items)	122
MQQMT_* (Command format Queue Manager Types)	95	MQSECSW_* (Command format Security Switches)	122
MQQO_* (Command format Quiesce Options)	95	MQSECSW_* (Command format Security Switch States)	122
MQQSGD_* (Queue Sharing Group Dispositions)	95	MQSECTYPE_* (Command format Security Types)	123
MQQSGS_* (Command format QSG Status)	96	MQSEG_* (Segmentation)	123
MQQSIE_* (Command format Queue Service-Interval Events)	96	MQSEL_* (Special Selector Values)	123
MQQSO_* (Command format Queue Status Open Options for SET, BROWSE, INPUT)	96	MQSID_* (Security Identifier)	123
MQQSOT_* (Command format Queue Status Open Types)	96	MQSIDT_* (Security Identifier Types)	123
MQQSUM_* (Command format Queue Status Uncommitted Messages)	96	MQSMPO_* (Set message property options structure)	123
MQQT_* (Queue Types)	96	MQSMPO_* (Set Message Property Options)	123
MQQT_* (Extended Queue Types)	97	MQSO_* (Subscribe Options)	124
MQRC_* (Reason Codes)	97	MQSP_* (Syncpoint Availability)	124
MQRCCF_* (Command format header Reason Codes)	109	MQSQQM_* (Shared Queue Queue Manager Name)	124
MQRCVTIME_* (Receive Timeout Types)	116	MQSR_* (Action)	125
MQREADA_* (Read Ahead Values)	116	MQSRO_* (Subscription request options structure)	125
MQRECORDING_* (Recording Options)	116	MQSS_* (Segment Status)	125
MQREGO_* (Publish/Subscribe Registration Options)	116	MQSSL_* (SSL FIPS Requirements)	125
MQRFH_* (Rules and formatting header structure)	117	MQSTAT_* (Stat Options)	125
MQRFH_* (Rules and formatting header Flags)	117	MQSTS_* (Status reporting structure structure)	125
MQRFH2_* (Publish/Subscribe Options Tag RFH2 Top-level folder Tags)	117	MQSUB_* (Durable subscriptions)	125
MQRFH2_* (Publish/Subscribe Options Tag Tag names)	117	MQSUB_* (Durable Subscriptions)	126
MQRFH2_* (Publish/Subscribe Options Tag XML tag names)	118	MQSUBTYPE_* (Command format Subscription Types)	126
MQRL_* (Returned Length)	118	MQSUS_* (Command format Suspend Status)	126
MQRMH_* (Reference message header structure)	118	MQSVC_* (Service Types)	126
MQRMHF_* (Reference message header Flags)	118	MQSVC_* (Service Controls)	126
MQRO_* (Report Options)	118	MQSVC_* (Service Status)	126
MQRO_* (Report Options Masks)	119	MQSYNCPOINT_* (Command format Syncpoint values for Pub/Sub migration)	126
MQROUTE_* (Trace-route Max Activities (MQIACF_MAX_ACTIVITIES))	119	MQSYSP_* (Command format System Parameter Values)	127
MQROUTE_* (Trace-route Detail (MQIACF_ROUTE_DETAIL))	119	MQTA_* (Wildcards)	127
MQROUTE_* (Trace-route Forwarding (MQIACF_ROUTE_FORWARDING))	119	MQTA_* (Subscriptions Allowed)	127
MQROUTE_* (Trace-route Delivery (MQIACF_ROUTE_DELIVERY))	119	MQTA_* (Proxy Sub Propagation)	127
MQROUTE_* (Trace-route Accumulation (MQIACF_ROUTE_ACCUMULATION))	120	MQTA_* (Publications Allowed)	127
MQRP_* (Command format Replace Options)	120	MQTC_* (Trigger Controls)	128
MQRQ_* (Command format Reason Qualifiers)	120	MQTCPKEEP_* (TCP Keepalive)	128
MQRT_* (Command format Refresh Types)	120	MQTCPSTACK_* (TCP Stack Types)	128
MQRU_* (Request Only)	121	MQTIME_* (Command format Time units)	128
MQSCA_* (SSL Client Authentication)	121	MQTM_* (Trigger message structure)	128
MQSCO_* (SSL configuration options structure)	121	MQTM_* (Trigger message character format structure)	128
		MQTOPT_* (Topic Type)	129
		MQTRAXSTR_* (Channel Initiator Trace Autostart)	129
		MQTSOPE_* (Subscription Scope)	129
		MQTT_* (Trigger Types)	129
		MQTYPE_* (Property data types)	129
		MQUA_* (Publish/Subscribe User Attribute Selectors)	129
		MQUIDSUPP_* (Command format User ID Support)	130

MQUNDELIVERED_* (Command format Undelivered values for Pub/Sub migration)	130
MQUOWST_* (Command format UOW States)	130
MQUOWT_* (Command format UOW Types)	130
MQUS_* (Queue Usages)	130
MQUSAGE_* (Command format Page Set Usage Values)	130
MQUSAGE_* (Command format Data Set Usage Values)	131
MQVL_* (%con\$ params ValueLength - mqsetmp)	131
MQVU_* (Variable User ID)	131
MQWDR_* (Cluster workload exit destination record structure)	131
MQWI_* (Wait Interval)	131
MQWIH_* (Workload information header structure)	131
MQWIH_* (Workload information header Flags)	132
MQWQR_* (Cluster workload exit queue record structure)	132
MQWS_* (Wildcard Schema)	132
MQWXP_* (Cluster workload exit parameter structure)	132
MQWXP_* (Cluster Workload Flags)	132
MQXACT_* (API Caller Types)	132
MQXC_* (Exit Commands)	133
MQXCC_* (Exit Responses)	133
MQXDR_* (Exit Response)	133
MQXE_* (Environments)	133
MQXEPO_* (Register Entry Point Options structure)	133
MQXEPO_* (Exit Options)	134
MQXF_* (API Function Identifiers)	134
MQXP_* (API crossing exit parameter structure)	134
MQXPDA_* (Problem Determination Area)	134
MQXPT_* (Transport Types)	135
MQXQH_* (Transmission queue header structure)	135

MQXR_* (Exit Reasons)	135
MQXR2_* (Exit Response 2)	136
MQXT_* (Exit Identifiers)	136
MQXUA_* (Exit User Area Value)	136
MQXWD_* (Exit wait descriptor structure)	136
MQZAC_* (Application context structure)	136
MQZAD_* (Authority data structure)	137
MQZAET_* (Installable Services Entity Types)	137
MQZAO_* (Installable Services Authorizations)	137
MQZAS_* (Installable Services Service Interface Version)	138
MQZAT_* (Authentication Types)	138
MQZCI_* (Installable Services Continuation Indicator)	138
MQZED_* (Entity data structure)	138
MQZFP_* (Free parameters structure)	138
MQZIC_* (Identity context structure)	139
MQZID_* (Function ids common to all services)	139
MQZID_* (Function ids for Authority service)	139
MQZID_* (Function ids for Name service)	139
MQZID_* (Function ids for Userid service)	139
MQZIO_* (Installable Services Initialization Options)	140
MQZNS_* (Name Service Interface Version)	140
MQZSE_* (Installable Services Start-Enumeration Indicator)	140
MQZSL_* (Installable Services Selector Indicator)	140
MQZTO_* (Installable Services Termination Options)	140
MQZUS_* (Userid Service Interface Version)	140

Notices 141

Index 145

Sending your comments to IBM 149

Tables

1. C header files — call prototypes, data types, return codes, constants, and structures 1
2. COBOL copy files - return codes, constants, and structures 1
3. PL/I include files — data types, return codes, constants, and structures 3
4. RPG copy files - return codes, constants, and structures 4
5. Visual Basic module files — call declarations, data types, return codes, constants, and structures 5
6. z/OS Assembler copy files - data types, return codes, constants, and structures 6

Chapter 1. WebSphere® MQ COPY, header, include, and module files

This information is general-use programming interface information.

This chapter contains information to help you use the MQI for the following programming languages.

- “C header files”
- “COBOL COPY files”
- “PL/I include files” on page 3
- “RPG copy files” on page 3
- “Visual Basic module files” on page 5

C header files

Header files are provided to help you write C application programs that use the MQI. These header files are summarized below:

Table 1. C header files — call prototypes, data types, return codes, constants, and structures

File name	Description	i5/OS®	UNIX® systems	Windows®	z/OS®
Call prototypes, data types, return codes, constants, and structures					
CMQC	MQI definitions	C	C	C	C
CMQBC	MQAI definitions	C	C	C	
CMQCFC	PCF definitions	C	C	C	C
CMQPSC	Publish/Subscribe definitions	C	C	C	C
CMQXC	Channel and exit definitions	C	C	C	C
CMQZC	Installable services definitions	C	C	C	
Key: C= Files provided					

COBOL COPY files

Various COPY files are provided to help you write COBOL application programs that use the MQI. These files are summarized below:

Table 2. COBOL copy files - return codes, constants, and structures

File name	Description	i5/OS	UNIX systems	Windows	z/OS
Return codes and constants					
CMQx	MQI definitions	V	V	V	V
CMQCFx	PCF definitions	V	V	V	V
CMQPSx	Publish/Subscribe definitions	V	V	V	V
CMQXx	Channel and exit definitions	V	V	V	V
Structures					

Table 2. COBOL copy files - return codes, constants, and structures (continued)

File name	Description	i5/OS	UNIX systems	Windows	z/OS
CMQAIRx	MQAIR - Authentication information record		V L	V L	
CMQBOx	MQBO - Begin options	V L	V L	V L	
CMQCDx	MQCD - Channel definition	V L	V L	V L	V L
CMQCFBFx	MQCFBF - PCF byte string filter parameter	V L	V L	V L	V L
CMQCFBSx	MQCFBS - PCF byte string parameter	V L	V L	V L	V L
CMQCFGRx	MQCFGR - PCF group parameter	V L	V L	V L	V L
CMQCFHx	MQCFH - PCF header	V L	V L	V L	V L
CMQCFIFx	MQCFIF - PCF integer filter parameter	V L	V L	V L	V L
CMQCFILx	MQCFIL - PCF integer list parameter	V L	V L	V L	V L
CMQCFINx	MQCFIN - PCF integer parameter	V L	V L	V L	V L
CMQCFSFx	MQCFSF - PCF string filter parameter	V L	V L	V L	V L
CMQCFSLx	MQCFSL - PCF string list parameter	V L	V L	V L	V L
CMQCFSTx	MQCFST - PCF string parameter	V L	V L	V L	V L
CMQCFXLx	MQCFIL64 - PCF 64-bit integer list parameter	V L	V L	V L	V L
CMQCFXNx	MQCFIN64 - PCF 64-bit integer parameter	V L	V L	V L	V L
I CMQCHARVx	MQCHARV - Variable length string	V L	V L	V L	V L
CMQCIHx	MQCIH - CICS® bridge header	V L	V L	V L	V L
CMQCNOx	MQCNO - Connect options	V L	V L	V L	V L
CMQCSPx	MQCSP - Security parameters	V L	V L	V L	V L
CMQCXPx	MQCXP - Channel exit parameters	V L			V L
CMQDHx	MQDH - Distribution header	V L	V L	V L	V L
CMQDLHx	MQDLH - Dead-letter header	V L	V L	V L	V L
CMQDXPx	MQDXP - Data conversion exit parameters	V L		V L	
CMQEPHx	MQEPH - Embedded PCF header	V L	V L	V L	V L
CMQGMox	MQGMO - Get message options	V L	V L	V L	V L
CMQIIHx	MQIIH - IMS™ information header	V L	V L	V L	V L
CMQMDx	MQMD - Message descriptor	V L	V L	V L	V L
CMQMD1x	MQMD1 - Message descriptor version 1	V L	V L	V L	V L
CMQMD2x	MQMD2 - Message descriptor version 2	V L	V L	V L	V L
CMQMDEx	MQMDE - Message descriptor extended	V L	V L	V L	V L
CMQODx	MQOD - Object descriptor	V L	V L	V L	V L

Table 2. COBOL copy files - return codes, constants, and structures (continued)

File name	Description	i5/OS	UNIX systems	Windows	z/OS
CMQORx	MQOR - Object record	V L	V L	V L	V L
CMQPMOx	MQPMO - Put message options	V L	V L	V L	V L
CMQRFHx	MQRFH - Rules and formatting header	V L	V L	V L	V L
CMQRFH2x	MQRFH2 - Rules and formatting header 2	V L	V L	V L	V L
CMQRMHx	MQRMH - Reference message header	V L	V L	V L	V L
CMQRRx	MQRR - Response record	V L	V L	V L	
CMQSCOx	MQSCO - SSL configuraton options		V L	V L	
CMQTMx	MQTM - Trigger message	V L		V L	V L
CMQTMCx	MQTMC - Trigger message character	V L	V L		
CMQTM2x	MQTMC2 - Trigger message 2 character	V L	V L	V L	V L
CMQWIHx	MQWIH - Work information header	V L	V L	V L	V L
CMQXQHx	MQXQH - Transmission queue header	V L	V L	V L	V L
Key:					
<ul style="list-style-type: none"> Files with initial values provided, x=V Files without initial values provided, x=L 					

PL/I include files

The following INCLUDE files are provided for the PL/I programming language. These files are available on z/OS only.

Table 3. PL/I include files — data types, return codes, constants, and structures

File name	Description	i5/OS	UNIX systems	Windows	z/OS
Data types, return codes, constants, and structures					
CMQP	MQI definitions				P
CMQCFP	PCF definitions				P
CMQEPP	Entry point definitions				P
CMQPSP	Publish/Subscribe definitions				P
CMQXP	Channel and exit definitions				P
Key: P= File provided					

RPG copy files

The following COPY files are provided for the RPG programming language. These files are available only on i5/OS.

Table 4. RPG copy files - return codes, constants, and structures

File name	Description	i5/OS	UNIX systems	Windows	z/OS
Return codes and constants					
CMQx	MQI definitions	G R			
CMQCFx	PCF definitions	G			
CMQPSx	Publish/Subscribe definitions	G			
CMQXx	Channel and exit definitions	G R			
Structures					
CMQBOx	MQBO - Begin options	G H			
CMQCDx	MQCD - Channel definition	G H R			
CMQCFBFx	MQCFBF - PCF byte string filter parameter	G H			
CMQCFBSx	MQCFBS - PCF byte string parameter	G H			
CMQCFGRx	MQCFGR - PCF group parameter	G H			
CMQCFHx	MQCFH - PCF header	G H			
CMQCFIFx	MQCFIF - PCF integer filter parameter	G H			
CMQCFILx	MQCFIL - PCF integer list parameter	G H			
CMQCFINx	MQCFIN - PCF integer parameter	G H			
CMQCFSFx	MQCFSF - PCF string filter parameter	G H			
CMQCFSLx	MQCFSL - PCF string list parameter	G H			
CMQCFSTx	MQCFST - PCF string parameter	G H			
CMQCFXLx	MQCFIL64 - PCF 64-bit integer list parameter	G H			
CMQCFXNx	MQCFIN64 - PCF 64-bit integer parameter	G H			
I CMQCHARVx	MQCHARV - Variable length string	G H			
CMQCIHx	MQCIH - CICS bridge header	G H			
CMQCNOx	MQCNO - Connect options	G H			
CMQCSPx	MQCSP - Security parameters	G H			
CMQCXPx	MQCXP - Channel exit parameters	G H R			
CMQDHx	MQDH - Distribution header	G H R			
CMQDLHx	MQDLH - Dead-letter header	G H R			
CMQDXPx	MQDXP - Data conversion exit parameters	G H R			
CMQEPHx	MQEPH - Embedded PCF header	G H			
CMQGMox	MQGMO - Get message options	G H R			
CMQIIHx	MQIIH - IMS information header	G H R			
CMQMDx	MQMD - Message descriptor	G H R			
CMQMD1x	MQMD1 - Message descriptor version 1	G H R			

Table 4. RPG copy files - return codes, constants, and structures (continued)

File name	Description	i5/OS	UNIX systems	Windows	z/OS
CMQMD2x	MQMD2 - Message descriptor version 2	G H			
CMQMDEx	MQMDE - Message descriptor extended	G H R			
CMQODx	MQOD - Object descriptor	G H R			
CMQORx	MQOR - Object record	G H R			
CMQPMOx	MQPMO - Put message options	G H R			
CMQXPx	MQXPx - Publish/Subscribe routing exit parameters	G H			
CMQRFHx	MQRFH - Rules and formatting header	G H			
CMQRFH2x	MQRFH2 - Rules and formatting header 2	G H			
CMQRMHx	MQRMH - Reference message header	G H R			
CMQRRx	MQRR - Response record	G H R			
CMQTMx	MQTM - Trigger message	G H R			
CMQTMcx	MQTMC - Trigger message character	G H R			
CMQTM2x	MQTMC2 - Trigger message 2 character	G H R			
CMQWIHx	MQWIH - Work information header	G H			
CMQXQHx	MQXQH - Transmission queue header	G H R			

Key:

- File for static linkage, initialized, provided x=G
- File for static linkage, not initialized, provided x=H
- File for dynamic linkage, initialized, provided, x=R

Visual Basic module files

Header (or form) files are provided to help you write Visual Basic application programs that use the MQI. These header files are supplied in 32-bit versions only and are summarized below:

Table 5. Visual Basic module files — call declarations, data types, return codes, constants, and structures

File name	Description	i5/OS	UNIX systems	Windows	z/OS
Call declarations, data types, return codes, constants, and structures					
CMQB	MQI definitions			B	
CMQBB	MQAI definitions			B	
CMQCFB	PCF definitions			B	
CMQXB	Channel and exit definitions			B	

Key: B= File provided

z/OS Assembler COPY files

Various COPY files are provided to help you write z/OS Assembler application programs that use the MQI. These files are summarized below:

Table 6. z/OS Assembler copy files - data types, return codes, constants, and structures

File name	Description	i5/OS	UNIX systems	Windows	z/OS
Data types, return codes, and constants					
CMQA	MQI definitions				A
CMQCFA	PCF definitions				A
CMQPSA	Publish/Subscribe definitions				A
CMQVERA	Structure version control				A
CMQXA	Channel and exit definitions				A
Structures					
CMQCDA	MQCD - Channel definition				
CMQCFBFA	MQCFBF - PCF byte string filter parameter				
CMQCFBSA	MQCFBS - PCF byte string parameter				A
CMQCFGRA	MQCFGR - PCF group parameter				A
CMQCFHA	MQCFH - PCF header				A
CMQCFIFA	MQCFIF - PCF integer filter parameter				A
CMQCFILA	MQCFIL - PCF integer list parameter				A
CMQCFINA	MQCFIN - PCF integer parameter				A
CMQCFSFA	MQCFSF - PCF string filter parameter				A
CMQCFSLA	MQCFSL - PCF string list parameter				A
CMQCFSTA	MQCFST - PCF string parameter				A
CMQCFXLA	MQCFIL64 - PCF 64-bit integer list parameter				A
CMQCFXNA	MQCFIN64 - PCF 64-bit integer parameter				A
CMQCHARVA	MQCHARV - Variable length string				A
CMQCIHA	MQCIH - CICS bridge header				A
CMQCNOA	MQCNO - Connect options				A
CMQCSPA	MQCSP - Security parameters				A
CMQCXPA	MQCXP - Channel exit parameters				A
CMQDHA	MQDHA - Distribution header				A
CMQDLHA	MQDLH - Dead-letter header				A
CMQDXPA	MQDXP - Data conversion exit parameters				A

Table 6. z/OS Assembler copy files - data types, return codes, constants, and structures (continued)

File name	Description	i5/OS	UNIX systems	Windows	z/OS
CMQEPHA	MQEPH - Embedded PCF header				A
CMQGMOA	MQGMO - Get message options				A
CMQIIHA	MQIIH - IMS information header				A
CMQMDA	MQMD - Message descriptor				A
CMQMD1A	MQMD1 - Message descriptor version 1				A
CMQMD2A	MQMD2 - Message descriptor version 2				A
CMQMDEA	MQMDE - Message descriptor extended				A
CMQODA	MQOD - Object descriptor				A
CMQORA	MQOR - Object record				A
CMQPMOA	MQPMO - Put message options				A
CMQRFHA	MQRFH - Rules and formatting header				A
CMQRFH2A	MQRFH2 - Rules and formatting header 2				A
CMQRMHA	MQRMH - Reference message header				A
CMQTMA	MQTM - Trigger message				A
CMQTMC2A	MQTMC2 - Trigger message 2 character				A
CMQWCRA	MQWCR - Cluster workload cluster record				A
CMQWDRA	MQWDR - Cluster workload destination record				A
CMQWDR1A	MQWDR1 - Cluster workload destination record version 1				A
CMQWDR2A	MQWDR2 - Cluster workload destination record version 2				A
CMQWIHA	MQWIH - Work information header				A
CMQWQRA	MQWQR - Cluster workload queue record				A
CMQWQR1A	MQWQR1 - Cluster workload queue record version 1				A
CMQWQR2A	MQWQR2 - Cluster workload queue record version 2				A
CMQWXP	MQWXP - Cluster workload exit parameters				A
CMQWXP1A	MQWXP1 - Cluster workload exit parameters version 1				A
CMQWXP2A	MQWXP2 - Cluster workload exit parameters version 2				A
CMQWXP3A	MQWXP3 - Cluster workload exit parameters version 3				A

Table 6. z/OS Assembler copy files - data types, return codes, constants, and structures (continued)

File name	Description	i5/OS	UNIX systems	Windows	z/OS
CMQXPA	MQXP - CICS API-crossing exit parameters				A
CMQXQHA	MQXQH - Transmission queue header				A
CMQXWDA	MQXWD - Exit wait descriptor				A
Key: A= File provided					

Chapter 2. Constants

List of all the constants

MQ_* (String Lengths)

MQ_ABEND_CODE_LENGTH	4	X'00000004'
MQ_ACCOUNTING_TOKEN_LENGTH	32	X'00000020'
MQ_APPL_IDENTITY_DATA_LENGTH	32	X'00000020'
MQ_APPL_NAME_LENGTH	28	X'0000001C'
MQ_APPL_ORIGIN_DATA_LENGTH	4	X'00000004'
MQ_APPL_TAG_LENGTH	28	X'0000001C'
MQ_ARM_SUFFIX_LENGTH	2	X'00000002'
MQ_ATTENTION_ID_LENGTH	4	X'00000004'
MQ_AUTH_INFO_CONN_NAME_LENGTH	264	X'00000108'
MQ_AUTH_INFO_DESC_LENGTH	64	X'00000040'
MQ_AUTH_INFO_NAME_LENGTH	48	X'00000030'
MQ_AUTHENTICATOR_LENGTH	8	X'00000008'
MQ_AUTO_REORG_CATALOG_LENGTH	44	X'0000002C'
MQ_AUTO_REORG_TIME_LENGTH	4	X'00000004'
MQ_BATCH_INTERFACE_ID_LENGTH	8	X'00000008'
MQ_BRIDGE_NAME_LENGTH	24	X'00000018'
MQ_CANCEL_CODE_LENGTH	4	X'00000004'
MQ_CF_STRUC_DESC_LENGTH	64	X'00000040'
MQ_CF_STRUC_NAME_LENGTH	12	X'0000000C'
MQ_CHANNEL_DATE_LENGTH	12	X'0000000C'
MQ_CHANNEL_DESC_LENGTH	64	X'00000040'
MQ_CHANNEL_NAME_LENGTH	20	X'00000014'
MQ_CHANNEL_TIME_LENGTH	8	X'00000008'
MQ_CHINIT_SERVICE_PARM_LENGTH	32	X'00000020'
MQ_CICS_FILE_NAME_LENGTH	8	X'00000008'
MQ_CLUSTER_NAME_LENGTH	48	X'00000030'
MQ_CONN_NAME_LENGTH	264	X'00000108'
MQ_CONN_TAG_LENGTH	128	X'00000080'
MQ_CONNECTION_ID_LENGTH	24	X'00000018'
MQ_CORREL_ID_LENGTH	24	X'00000018'
MQ_CREATION_DATE_LENGTH	12	X'0000000C'
MQ_CREATION_TIME_LENGTH	8	X'00000008'
MQ_DATE_LENGTH	12	X'0000000C'
MQ_DISTINGUISHED_NAME_LENGTH	1024	X'00000400'
MQ_DNS_GROUP_NAME_LENGTH	18	X'00000012'

MQ_EXIT_DATA_LENGTH	32	X'00000020'
MQ_EXIT_INFO_NAME_LENGTH	48	X'00000030'
MQ_EXIT_NAME_LENGTH	(value differs by platform or version)	
MQ_EXIT_PD_AREA_LENGTH	48	X'00000030'
MQ_EXIT_USER_AREA_LENGTH	16	X'00000010'
MQ_FACILITY_LENGTH	8	X'00000008'
MQ_FACILITY_LIKE_LENGTH	4	X'00000004'
MQ_FORMAT_LENGTH	8	X'00000008'
MQ_FUNCTION_LENGTH	4	X'00000004'
MQ_GROUP_ID_LENGTH	24	X'00000018'
MQ_LDAP_PASSWORD_LENGTH	32	X'00000020'
MQ_LISTENER_NAME_LENGTH	48	X'00000030'
MQ_LISTENER_DESC_LENGTH	64	X'00000040'
MQ_LOCAL_ADDRESS_LENGTH	48	X'00000030'
MQ_LTERM_OVERRIDE_LENGTH	8	X'00000008'
MQ_LU_NAME_LENGTH	8	X'00000008'
MQ_LUWID_LENGTH	16	X'00000010'
MQ_MAX_EXIT_NAME_LENGTH	128	X'00000080'
MQ_MAX_MCA_USER_ID_LENGTH	64	X'00000040'
MQ_MAX_PROPERTY_NAME_LENGTH	4095	X'00000FFF'
MQ_MAX_USER_ID_LENGTH	64	X'00000040'
MQ_MCA_JOB_NAME_LENGTH	28	X'0000001C'
MQ_MCA_NAME_LENGTH	20	X'00000014'
MQ_MCA_USER_DATA_LENGTH	32	X'00000020'
MQ_MCA_USER_ID_LENGTH	(value differs by platform or version)	
MQ_MFS_MAP_NAME_LENGTH	8	X'00000008'
MQ_MODE_NAME_LENGTH	8	X'00000008'
MQ_MSG_HEADER_LENGTH	4000	X'00000FA0'
MQ_MSG_ID_LENGTH	24	X'00000018'
MQ_MSG_TOKEN_LENGTH	16	X'00000010'
MQ_NAMELIST_DESC_LENGTH	64	X'00000040'
MQ_NAMELIST_NAME_LENGTH	48	X'00000030'
MQ_OBJECT_INSTANCE_ID_LENGTH	24	X'00000018'
MQ_OBJECT_NAME_LENGTH	48	X'00000030'
MQ_PASS_TICKET_APPL_LENGTH	8	X'00000008'
MQ_PASSWORD_LENGTH	12	X'0000000C'
MQ_PROCESS_APPL_ID_LENGTH	256	X'00000100'
MQ_PROCESS_DESC_LENGTH	64	X'00000040'
MQ_PROCESS_ENV_DATA_LENGTH	128	X'00000080'
MQ_PROCESS_NAME_LENGTH	48	X'00000030'

MQ_PROCESS_USER_DATA_LENGTH	128	X'00000080'
MQ_PROGRAM_NAME_LENGTH	20	X'00000014'
MQ_PUT_APPL_NAME_LENGTH	28	X'0000001C'
MQ_PUT_DATE_LENGTH	8	X'00000008'
MQ_PUT_TIME_LENGTH	8	X'00000008'
MQ_Q_DESC_LENGTH	64	X'00000040'
MQ_Q_MGR_DESC_LENGTH	64	X'00000040'
MQ_Q_MGR_IDENTIFIER_LENGTH	48	X'00000030'
MQ_Q_MGR_NAME_LENGTH	48	X'00000030'
MQ_Q_NAME_LENGTH	48	X'00000030'
MQ_QSG_NAME_LENGTH	4	X'00000004'
MQ_REMOTE_SYS_ID_LENGTH	4	X'00000004'
MQ_SECURITY_ID_LENGTH	40	X'00000028'
MQ_SELECTOR_LENGTH	10240	X'00002800'
MQ_SERVICE_ARGS_LENGTH	255	X'000000FF'
MQ_SERVICE_COMMAND_LENGTH	255	X'000000FF'
MQ_SERVICE_DESC_LENGTH	64	X'00000040'
MQ_SERVICE_NAME_LENGTH	32	X'00000020'
MQ_SERVICE_PATH_LENGTH	255	X'000000FF'
MQ_SERVICE_STEP_LENGTH	8	X'00000008'
MQ_SHORT_CONN_NAME_LENGTH	20	X'00000014'
MQ_SHORT_DNAME_LENGTH	256	X'00000100'
MQ_SSL_CIPHER_SPEC_LENGTH	32	X'00000020'
MQ_SSL_CRYPTO_HARDWARE_LENGTH	256	X'00000100'
MQ_SSL_HANDSHAKE_STAGE_LENGTH	32	X'00000020'
MQ_SSL_KEY_LIBRARY_LENGTH	44	X'0000002C'
MQ_SSL_KEY_MEMBER_LENGTH	8	X'00000008'
MQ_SSL_KEY_REPOSITORY_LENGTH	256	X'00000100'
MQ_SSL_PEER_NAME_LENGTH	1024	X'00000400'
MQ_SSL_SHORT_PEER_NAME_LENGTH	256	X'00000100'
MQ_START_CODE_LENGTH	4	X'00000004'
MQ_STORAGE_CLASS_DESC_LENGTH	64	X'00000040'
MQ_STORAGE_CLASS_LENGTH	8	X'00000008'
MQ_SUB_IDENTITY_LENGTH	128	X'00000080'
MQ_SUB_POINT_LENGTH	128	X'00000080'
MQ_TCP_NAME_LENGTH	8	X'00000008'
MQ_TIME_LENGTH	8	X'00000008'
MQ_TOPIC_DESC_LENGTH	64	X'00000040'
MQ_TOPIC_NAME_LENGTH	48	X'00000030'
MQ_TOPIC_STR_LENGTH	10240	X'00002800'
MQ_TOTAL_EXIT_DATA_LENGTH	999	X'000003E7'
MQ_TOTAL_EXIT_NAME_LENGTH	999	X'000003E7'

MQ_TP_NAME_LENGTH	64	X'00000040'
MQ_TPIPE_NAME_LENGTH	8	X'00000008'
MQ_TRAN_INSTANCE_ID_LENGTH	16	X'00000010'
MQ_TRANSACTION_ID_LENGTH	4	X'00000004'
MQ_TRIGGER_DATA_LENGTH	64	X'00000040'
MQ_TRIGGER_PROGRAM_NAME_LENGTH	8	X'00000008'
MQ_TRIGGER_TERM_ID_LENGTH	4	X'00000004'
MQ_TRIGGER_TRANS_ID_LENGTH	4	X'00000004'
MQ_USER_ID_LENGTH	12	X'0000000C'
MQ_XCF_GROUP_NAME_LENGTH	8	X'00000008'
MQ_XCF_MEMBER_NAME_LENGTH	16	X'00000010'

MQ_* (Command format String Lengths)

MQ_ARCHIVE_PFX_LENGTH	36	X'00000024'
MQ_ARCHIVE_UNIT_LENGTH	8	X'00000008'
MQ_ASID_LENGTH	4	X'00000004'
MQ_AUTH_PROFILE_NAME_LENGTH	48	X'00000030'
MQ_CF_LEID_LENGTH	12	X'0000000C'
MQ_COMMAND_MQSC_LENGTH	32768	X'00008000'
MQ_DATA_SET_NAME_LENGTH	44	X'0000002C'
MQ_DB2_NAME_LENGTH	4	X'00000004'
MQ_DSG_NAME_LENGTH	8	X'00000008'
MQ_ENTITY_NAME_LENGTH	64	X'00000040'
MQ_ENV_INFO_LENGTH	96	X'00000060'
MQ_IP_ADDRESS_LENGTH	48	X'00000030'
MQ_LOG_CORREL_ID_LENGTH	8	X'00000008'
MQ_LOG_EXTENT_NAME_LENGTH	24	X'00000018'
MQ_LOG_PATH_LENGTH	1024	X'00000400'
MQ_LRSN_LENGTH	12	X'0000000C'
MQ_ORIGIN_NAME_LENGTH	8	X'00000008'
MQ_PSB_NAME_LENGTH	8	X'00000008'
MQ_PST_ID_LENGTH	8	X'00000008'
MQ_Q_MGR_CPF_LENGTH	4	X'00000004'
MQ_RESPONSE_ID_LENGTH	24	X'00000018'
MQ_RBA_LENGTH	12	X'0000000C'
MQ_SECURITY_PROFILE_LENGTH	40	X'00000028'
MQ_SERVICE_COMPONENT_LENGTH	48	X'00000030'
MQ_SUB_NAME_LENGTH	10240	X'00002800'
MQ_SYSP_SERVICE_LENGTH	32	X'00000020'
MQ_SYSTEM_NAME_LENGTH	8	X'00000008'
MQ_TASK_NUMBER_LENGTH	8	X'00000008'

MQ_TPIPE_PFX_LENGTH	4	X'00000004'
MQ_UOW_ID_LENGTH	256	X'00000100'
MQ_USER_DATA_LENGTH	10240	X'00002800'
MQ_VOLSER_LENGTH	6	X'00000006'

MQACH_* (API exit chain area header structure)

MQACH_STRUC_ID	"ACHb"	
MQACH_STRUC_ID_ARRAY	'A','C','H','b'	
MQACH_VERSION_1	1	X'00000001'
MQACH_CURRENT_VERSION	1	X'00000001'
MQACH_LENGTH_1	(value differs by platform or version)	
MQACH_CURRENT_LENGTH	(value differs by platform or version)	

MQACT_* (Accounting Token)

MQACT_NONE	X'00...00'	(32 nulls)
MQACT_NONE_ARRAY	'\0','\0',...	(32 nulls)

MQACT_* (Command format Action Options)

MQACT_FORCE_REMOVE	1	X'00000001'
MQACT_ADVANCE_LOG	2	X'00000002'
MQACT_COLLECT_STATISTICS	3	X'00000003'
MQACT_PUBSUB	4	X'00000004'

MQACTP_* (Action)

MQACTP_NEW	0	X'00000000'
MQACTP_FORWARD	1	X'00000001'
MQACTP_REPLY	2	X'00000002'
MQACTP_REPORT	3	X'00000003'

MQACTT_* (Accounting Token Types)

MQACTT_UNKNOWN	X'00'	
MQACTT_CICS_LUOW_ID	X'01'	
MQACTT_OS2_DEFAULT	X'04'	
MQACTT_DOS_DEFAULT	X'05'	
MQACTT_UNIX_NUMERIC_ID	X'06'	

MQACTT_OS400_ACCOUNT_TOKEN		X'08'	
MQACTT_WINDOWS_DEFAULT		X'09'	
MQACTT_NT_SECURITY_ID		X'0B'	
MQACTT_USER		X'19'	

MQADOPT_* (Adopt New MCA Checks)

MQADOPT_CHECK_NONE		0	X'00000000'
MQADOPT_CHECK_ALL		1	X'00000001'
MQADOPT_CHECK_Q_MGR_NAME		2	X'00000002'
MQADOPT_CHECK_NET_ADDR		4	X'00000004'

MQADOPT_* (Adopt New MCA Types)

MQADOPT_TYPE_NO		0	X'00000000'
MQADOPT_TYPE_ALL		1	X'00000001'
MQADOPT_TYPE_SVR		2	X'00000002'
MQADOPT_TYPE_SDR		4	X'00000004'
MQADOPT_TYPE_RCVR		8	X'00000008'
MQADOPT_TYPE_CLUSRCVR		16	X'00000010'

MQAIR_* (Authentication information record structure)

MQAIR_STRUC_ID	"AIRb"		
MQAIR_STRUC_ID_ARRAY	'A','I','R','b'		
MQAIR_VERSION_1		1	X'00000001'
MQAIR_CURRENT_VERSION		1	X'00000001'

MQAIT_* (Authentication Information Type)

MQAIT_CRL_LDAP		1	X'00000001'
----------------	--	---	-------------

MQAS_* (Command format Asynchronous State Values)

MQAS_NONE		0	X'00000000'
MQAS_STARTED		1	X'00000001'
MQAS_START_WAIT		2	X'00000002'
MQAS_STOPPED		3	X'00000003'
MQAS_SUSPENDED		4	X'00000004'
MQAS_SUSPENDED_TEMPORARY		5	X'00000005'
MQAS_ACTIVE		6	X'00000006'

MQAS_INACTIVE	7	X'00000007'
---------------	---	-------------

MQAT_* (Put Application Types)

MQAT_UNKNOWN	-1	X'FFFFFFFF'
MQAT_NO_CONTEXT	0	X'00000000'
MQAT_CICS	1	X'00000001'
MQAT_MVS	2	X'00000002'
MQAT_OS390	2	X'00000002'
MQAT_ZOS	2	X'00000002'
MQAT_IMS	3	X'00000003'
MQAT_OS2	4	X'00000004'
MQAT_DOS	5	X'00000005'
MQAT_AIX	6	X'00000006'
MQAT_UNIX	6	X'00000006'
MQAT_QMGR	7	X'00000007'
MQAT_OS400	8	X'00000008'
MQAT_WINDOWS	9	X'00000009'
MQAT_CICS_VSE	10	X'0000000A'
MQAT_WINDOWS_NT	11	X'0000000B'
MQAT_VMS	12	X'0000000C'
MQAT_GUARDIAN	13	X'0000000D'
MQAT_NSK	13	X'0000000D'
MQAT_VOS	14	X'0000000E'
MQAT_OPEN_TP1	15	X'0000000F'
MQAT_VM	18	X'00000012'
MQAT_IMS_BRIDGE	19	X'00000013'
MQAT_XCF	20	X'00000014'
MQAT_CICS_BRIDGE	21	X'00000015'
MQAT_NOTES_AGENT	22	X'00000016'
MQAT_TPF	23	X'00000017'
MQAT_USER	25	X'00000019'
MQAT_BROKER	26	X'0000001A'
MQAT_QMGR_PUBLISH	26	X'0000001A'
MQAT_JAVA	28	X'0000001C'
MQAT_DQM	29	X'0000001D'
MQAT_CHANNEL_INITIATOR	30	X'0000001E'
MQAT_WLM	31	X'0000001F'
MQAT_BATCH	32	X'00000020'
MQAT_RRS_BATCH	33	X'00000021'
MQAT_SIB	34	X'00000022'

MQAT_DEFAULT	(value differs by platform or version)	
MQAT_USER_FIRST	65536	X'00010000'
MQAT_USER_LAST	999999999	X'3B9AC9FF'

MQAUTH_* (Command format Authority Values)

MQAUTH_NONE	0	X'00000000'
MQAUTH_ALT_USER_AUTHORITY	1	X'00000001'
MQAUTH_BROWSE	2	X'00000002'
MQAUTH_CHANGE	3	X'00000003'
MQAUTH_CLEAR	4	X'00000004'
MQAUTH_CONNECT	5	X'00000005'
MQAUTH_CREATE	6	X'00000006'
MQAUTH_DELETE	7	X'00000007'
MQAUTH_DISPLAY	8	X'00000008'
MQAUTH_INPUT	9	X'00000009'
MQAUTH_INQUIRE	10	X'0000000A'
MQAUTH_OUTPUT	11	X'0000000B'
MQAUTH_PASS_ALL_CONTEXT	12	X'0000000C'
MQAUTH_PASS_IDENTITY_CONTEXT	13	X'0000000D'
MQAUTH_SET	14	X'0000000E'
MQAUTH_SET_ALL_CONTEXT	15	X'0000000F'
MQAUTH_SET_IDENTITY_CONTEXT	16	X'00000010'
MQAUTH_CONTROL	17	X'00000011'
MQAUTH_CONTROL_EXTENDED	18	X'00000012'
MQAUTH_PUBLISH	19	X'00000013'
MQAUTH_SUBSCRIBE	20	X'00000014'
MQAUTH_RESUME	21	X'00000015'

MQAUTHOPT_* (Command format Authority Options)

MQAUTHOPT_CUMULATIVE	256	X'00000100'
MQAUTHOPT_ENTITY_EXPLICIT	1	X'00000001'
MQAUTHOPT_ENTITY_SET	2	X'00000002'
MQAUTHOPT_NAME_ALL_MATCHING	32	X'00000020'
MQAUTHOPT_NAME_AS_WILDCARD	64	X'00000040'
MQAUTHOPT_NAME_EXPLICIT	16	X'00000010'

MQAXC_* (API exit context structure)

MQAXC_STRUC_ID	"AXCb"	
----------------	--------	--

MQAXC_STRUC_ID_ARRAY	'A','X','C','b'		
MQAXC_VERSION_1		1	X'00000001'
MQAXC_CURRENT_VERSION		1	X'00000001'

MQAXP_* (API exit parameter structure)

MQAXP_STRUC_ID	"AXPb"		
MQAXP_STRUC_ID_ARRAY	'A','X','P','b'		
MQAXP_VERSION_1		1	X'00000001'
MQAXP_VERSION_2		2	X'00000002'
MQAXP_CURRENT_VERSION		2	X'00000002'

MQBA_* (Byte Attribute Selectors)

MQBA_FIRST		6001	X'00001771'
MQBA_LAST		8000	X'00001F40'

MQBACF_* (Command format Byte Parameter Types)

MQBACF_FIRST		7001	X'00001B59'
MQBACF_EVENT_ACCOUNTING_TOKEN		7001	X'00001B59'
MQBACF_EVENT_SECURITY_ID		7002	X'00001B5A'
MQBACF_RESPONSE_SET		7003	X'00001B5B'
MQBACF_RESPONSE_ID		7004	X'00001B5C'
MQBACF_EXTERNAL_UOW_ID		7005	X'00001B5D'
MQBACF_CONNECTION_ID		7006	X'00001B5E'
MQBACF_GENERIC_CONNECTION_ID		7007	X'00001B5F'
MQBACF_ORIGIN_UOW_ID		7008	X'00001B60'
MQBACF_Q_MGR_UOW_ID		7009	X'00001B61'
MQBACF_ACCOUNTING_TOKEN		7010	X'00001B62'
MQBACF_CORREL_ID		7011	X'00001B63'
MQBACF_GROUP_ID		7012	X'00001B64'
MQBACF_MSG_ID		7013	X'00001B65'
MQBACF_CF_LEID		7014	X'00001B66'
MQBACF_DESTINATION_CORREL_ID		7015	X'00001B67'
MQBACF_SUB_ID		7016	X'00001B68'
MQBACF_LAST_USED		7016	X'00001B68'

MQBL_* (Buffer Length for mqAddString and mqSetString)

MQBL_NULL_TERMINATED		-1	X'FFFFFFFF'
----------------------	--	----	-------------

MQBMHO_* (Buffer to message handle options structure)

MQBMHO_STRUC_ID	"BMHO"		
MQBMHO_STRUC_ID_ARRAY	'B','M','H','O'		
MQBMHO_VERSION_1		1	X'00000001'
MQBMHO_CURRENT_VERSION		1	X'00000001'

MQBMHO_* (Buffer To Message Handle Options)

MQBMHO_NONE		0	X'00000000'
MQBMHO_DELETE_PROPERTIES		1	X'00000001'

MQBND_* (Default Bindings)

MQBND_BIND_ON_OPEN		0	X'00000000'
MQBND_BIND_NOT_FIXED		1	X'00000001'

MQBO_* (Begin options structure)

MQBO_STRUC_ID	"B0bb"		
MQBO_STRUC_ID_ARRAY	'B','O','b','b'		
MQBO_VERSION_1		1	X'00000001'
MQBO_CURRENT_VERSION		1	X'00000001'

MQBO_* (Begin Options)

MQBO_NONE		0	X'00000000'
-----------	--	---	-------------

MQBT_* (Command format Bridge Types)

MQBT_OTMA		1	X'00000001'
-----------	--	---	-------------

MQCA_* (Character Attribute Selectors)

MQCA_ADMIN_TOPIC_NAME		2105	X'00000839'
MQCA_ALTERATION_DATE		2027	X'000007EB'
MQCA_ALTERATION_TIME		2028	X'000007EC'
MQCA_APPL_ID		2001	X'000007D1'
MQCA_AUTH_INFO_CONN_NAME		2053	X'00000805'
MQCA_AUTH_INFO_DESC		2046	X'000007FE'
MQCA_AUTH_INFO_NAME		2045	X'000007FD'
MQCA_AUTO_REORG_CATALOG		2091	X'0000082B'

MQCA_AUTO_REORG_START_TIME	2090	X'0000082A'
MQCA_BACKOUT_REQ_Q_NAME	2019	X'000007E3'
MQCA_BASE_OBJECT_NAME	2002	X'000007D2'
MQCA_BASE_Q_NAME	2002	X'000007D2'
MQCA_BATCH_INTERFACE_ID	2068	X'00000814'
MQCA_CF_STRUC_DESC	2052	X'00000804'
MQCA_CF_STRUC_NAME	2039	X'000007F7'
MQCA_CHANNEL_AUTO_DEF_EXIT	2026	X'000007EA'
MQCA_CHILD	2101	X'00000835'
MQCA_CHINIT_SERVICE_PARM	2076	X'0000081C'
MQCA_CICS_FILE_NAME	2060	X'0000080C'
MQCA_CLUSTER_DATE	2037	X'000007F5'
MQCA_CLUSTER_NAME	2029	X'000007ED'
MQCA_CLUSTER_NAMELIST	2030	X'000007EE'
MQCA_CLUSTER_Q_MGR_NAME	2031	X'000007EF'
MQCA_CLUSTER_TIME	2038	X'000007F6'
MQCA_CLUSTER_WORKLOAD_DATA	2034	X'000007F2'
MQCA_CLUSTER_WORKLOAD_EXIT	2033	X'000007F1'
MQCA_COMMAND_INPUT_Q_NAME	2003	X'000007D3'
MQCA_COMMAND_REPLY_Q_NAME	2067	X'00000813'
MQCA_CREATION_DATE	2004	X'000007D4'
MQCA_CREATION_TIME	2005	X'000007D5'
MQCA_DEAD_LETTER_Q_NAME	2006	X'000007D6'
MQCA_DEF_XMIT_Q_NAME	2025	X'000007E9'
MQCA_DNS_GROUP	2071	X'00000817'
MQCA_ENV_DATA	2007	X'000007D7'
MQCA_FIRST	2001	X'000007D1'
MQCA_IGQ_USER_ID	2041	X'000007F9'
MQCA_INITIATION_Q_NAME	2008	X'000007D8'
MQCA_LAST	4000	X'00000FA0'
MQCA_LAST_USED	2108	X'0000083C'
MQCA_LDAP_PASSWORD	2048	X'00000800'
MQCA_LDAP_USER_NAME	2047	X'000007FF'
MQCA_LU_GROUP_NAME	2072	X'00000818'
MQCA_LU_NAME	2073	X'00000819'
MQCA_LU62_ARM_SUFFIX	2074	X'0000081A'
MQCA_MODEL_DURABLE_Q	2096	X'00000830'
MQCA_MODEL_NON_DURABLE_Q	2097	X'00000831'
MQCA_MONITOR_Q_NAME	2066	X'00000812'
MQCA_NAMELIST_DESC	2009	X'000007D9'
MQCA_NAMELIST_NAME	2010	X'000007DA'
MQCA_NAMES	2020	X'000007E4'

MQCA_PARENT	2102	X'00000836'
MQCA_PASS_TICKET_APPL	2086	X'00000826'
MQCA_PROCESS_DESC	2011	X'000007DB'
MQCA_PROCESS_NAME	2012	X'000007DC'
MQCA_Q_DESC	2013	X'000007DD'
MQCA_Q_MGR_DESC	2014	X'000007DE'
MQCA_Q_MGR_IDENTIFIER	2032	X'000007F0'
MQCA_Q_MGR_NAME	2015	X'000007DF'
MQCA_Q_NAME	2016	X'000007E0'
MQCA_QSG_NAME	2040	X'000007F8'
MQCA_REMOTE_Q_MGR_NAME	2017	X'000007E1'
MQCA_REMOTE_Q_NAME	2018	X'000007E2'
MQCA_REPOSITORY_NAME	2035	X'000007F3'
MQCA_REPOSITORY_NAMELIST	2036	X'000007F4'
MQCA_RESUME_DATE	2098	X'00000832'
MQCA_RESUME_TIME	2099	X'00000833'
MQCA_SERVICE_DESC	2078	X'0000081E'
MQCA_SERVICE_NAME	2077	X'0000081D'
MQCA_SERVICE_START_ARGS	2080	X'00000820'
MQCA_SERVICE_START_COMMAND	2079	X'0000081F'
MQCA_SERVICE_STOP_ARGS	2082	X'00000822'
MQCA_SERVICE_STOP_COMMAND	2081	X'00000821'
MQCA_STDERR_DESTINATION	2084	X'00000824'
MQCA_STDOUT_DESTINATION	2083	X'00000823'
MQCA_SSL_CRL_NAMELIST	2050	X'00000802'
MQCA_SSL_CRYPTOHARDWARE	2051	X'00000803'
MQCA_SSL_KEY_LIBRARY	2069	X'00000815'
MQCA_SSL_KEY_MEMBER	2070	X'00000816'
MQCA_SSL_KEY_REPOSITORY	2049	X'00000801'
MQCA_STORAGE_CLASS	2022	X'000007E6'
MQCA_STORAGE_CLASS_DESC	2042	X'000007FA'
MQCA_SYSTEM_LOG_Q_NAME	2065	X'00000811'
MQCA_TCP_NAME	2075	X'0000081B'
MQCA_TOPIC_DESC	2093	X'0000082D'
MQCA_TOPIC_NAME	2092	X'0000082C'
MQCA_TOPIC_STRING_FILTER	2108	X'0000083C'
MQCA_TOPIC_STRING	2094	X'0000082E'
MQCA_TPIPE_NAME	2085	X'00000825'
MQCA_TRIGGER_CHANNEL_NAME	2064	X'00000810'
MQCA_TRIGGER_DATA	2023	X'000007E7'
MQCA_TRIGGER_PROGRAM_NAME	2062	X'0000080E'
MQCA_TRIGGER_TERM_ID	2063	X'0000080F'

MQCA_TRIGGER_TRANS_ID	2061	X'0000080D'
MQCA_USER_DATA	2021	X'000007E5'
MQCA_USER_LIST	4000	X'00000FA0'
MQCA_XCF_GROUP_NAME	2043	X'000007FB'
MQCA_XCF_MEMBER_NAME	2044	X'000007FC'
MQCA_XMIT_Q_NAME	2024	X'000007E8'

MQCACF_* (Command format Character Parameter Types)

MQCACF_FIRST	3001	X'00000BB9'
MQCACF_FROM_Q_NAME	3001	X'00000BB9'
MQCACF_TO_Q_NAME	3002	X'00000BBA'
MQCACF_FROM_PROCESS_NAME	3003	X'00000BBB'
MQCACF_TO_PROCESS_NAME	3004	X'00000BBC'
MQCACF_FROM_NAMELIST_NAME	3005	X'00000BBD'
MQCACF_TO_NAMELIST_NAME	3006	X'00000BBE'
MQCACF_FROM_CHANNEL_NAME	3007	X'00000BBF'
MQCACF_TO_CHANNEL_NAME	3008	X'00000BC0'
MQCACF_FROM_AUTH_INFO_NAME	3009	X'00000BC1'
MQCACF_TO_AUTH_INFO_NAME	3010	X'00000BC2'
MQCACF_Q_NAMES	3011	X'00000BC3'
MQCACF_PROCESS_NAMES	3012	X'00000BC4'
MQCACF_NAMELIST_NAMES	3013	X'00000BC5'
MQCACF_ESCAPE_TEXT	3014	X'00000BC6'
MQCACF_LOCAL_Q_NAMES	3015	X'00000BC7'
MQCACF_MODEL_Q_NAMES	3016	X'00000BC8'
MQCACF_ALIAS_Q_NAMES	3017	X'00000BC9'
MQCACF_REMOTE_Q_NAMES	3018	X'00000BCA'
MQCACF_SENDER_CHANNEL_NAMES	3019	X'00000BCB'
MQCACF_SERVER_CHANNEL_NAMES	3020	X'00000BCC'
MQCACF_REQUESTER_CHANNEL_NAMES	3021	X'00000BCD'
MQCACF_RECEIVER_CHANNEL_NAMES	3022	X'00000BCE'
MQCACF_OBJECT_Q_MGR_NAME	3023	X'00000BCF'
MQCACF_APPL_NAME	3024	X'00000BD0'
MQCACF_USER_IDENTIFIER	3025	X'00000BD1'
MQCACF_AUX_ERROR_DATA_STR_1	3026	X'00000BD2'
MQCACF_AUX_ERROR_DATA_STR_2	3027	X'00000BD3'
MQCACF_AUX_ERROR_DATA_STR_3	3028	X'00000BD4'
MQCACF_BRIDGE_NAME	3029	X'00000BD5'
MQCACF_STREAM_NAME	3030	X'00000BD6'
MQCACF_TOPIC	3031	X'00000BD7'
MQCACF_PARENT_Q_MGR_NAME	3032	X'00000BD8'

MQCACF_CORREL_ID	3033	X'00000BD9'
MQCACF_PUBLISH_TIMESTAMP	3034	X'00000BDA'
MQCACF_STRING_DATA	3035	X'00000BDB'
MQCACF_SUPPORTED_STREAM_NAME	3036	X'00000BDC'
MQCACF_REG_TOPIC	3037	X'00000BDD'
MQCACF_REG_TIME	3038	X'00000BDE'
MQCACF_REG_USER_ID	3039	X'00000BDF'
MQCACF_CHILD_Q_MGR_NAME	3040	X'00000BE0'
MQCACF_REG_STREAM_NAME	3041	X'00000BE1'
MQCACF_REG_Q_MGR_NAME	3042	X'00000BE2'
MQCACF_REG_Q_NAME	3043	X'00000BE3'
MQCACF_REG_CORREL_ID	3044	X'00000BE4'
MQCACF_EVENT_USER_ID	3045	X'00000BE5'
MQCACF_OBJECT_NAME	3046	X'00000BE6'
MQCACF_EVENT_Q_MGR	3047	X'00000BE7'
MQCACF_AUTH_INFO_NAMES	3048	X'00000BE8'
MQCACF_EVENT_APPL_IDENTITY	3049	X'00000BE9'
MQCACF_EVENT_APPL_NAME	3050	X'00000BEA'
MQCACF_EVENT_APPL_ORIGIN	3051	X'00000BEB'
MQCACF_SUBSCRIPTION_NAME	3052	X'00000BEC'
MQCACF_REG_SUB_NAME	3053	X'00000BED'
MQCACF_SUBSCRIPTION_IDENTITY	3054	X'00000BEE'
MQCACF_REG_SUB_IDENTITY	3055	X'00000BEF'
MQCACF_SUBSCRIPTION_USER_DATA	3056	X'00000BF0'
MQCACF_REG_SUB_USER_DATA	3057	X'00000BF1'
MQCACF_APPL_TAG	3058	X'00000BF2'
MQCACF_DATA_SET_NAME	3059	X'00000BF3'
MQCACF_UOW_START_DATE	3060	X'00000BF4'
MQCACF_UOW_START_TIME	3061	X'00000BF5'
MQCACF_UOW_LOG_START_DATE	3062	X'00000BF6'
MQCACF_UOW_LOG_START_TIME	3063	X'00000BF7'
MQCACF_UOW_LOG_EXTENT_NAME	3064	X'00000BF8'
MQCACF_PRINCIPAL_ENTITY_NAMES	3065	X'00000BF9'
MQCACF_GROUP_ENTITY_NAMES	3066	X'00000BFA'
MQCACF_AUTH_PROFILE_NAME	3067	X'00000BFB'
MQCACF_ENTITY_NAME	3068	X'00000BFC'
MQCACF_SERVICE_COMPONENT	3069	X'00000BFD'
MQCACF_RESPONSE_Q_MGR_NAME	3070	X'00000BFE'
MQCACF_CURRENT_LOG_EXTENT_NAME	3071	X'00000BFF'
MQCACF_RESTART_LOG_EXTENT_NAME	3072	X'00000C00'
MQCACF_MEDIA_LOG_EXTENT_NAME	3073	X'00000C01'
MQCACF_LOG_PATH	3074	X'00000C02'

MQCACF_COMMAND_MQSC	3075	X'00000C03'
MQCACF_Q_MGR_CPF	3076	X'00000C04'
MQCACF_USAGE_LOG_RBA	3078	X'00000C06'
MQCACF_USAGE_LOG_LRSN	3079	X'00000C07'
MQCACF_COMMAND_SCOPE	3080	X'00000C08'
MQCACF_ASID	3081	X'00000C09'
MQCACF_PSB_NAME	3082	X'00000C0A'
MQCACF_PST_ID	3083	X'00000C0B'
MQCACF_TASK_NUMBER	3084	X'00000C0C'
MQCACF_TRANSACTION_ID	3085	X'00000C0D'
MQCACF_Q_MGR_UOW_ID	3086	X'00000C0E'
MQCACF_ORIGIN_NAME	3088	X'00000C10'
MQCACF_ENV_INFO	3089	X'00000C11'
MQCACF_SECURITY_PROFILE	3090	X'00000C12'
MQCACF_CONFIGURATION_DATE	3091	X'00000C13'
MQCACF_CONFIGURATION_TIME	3092	X'00000C14'
MQCACF_FROM_CF_STRUC_NAME	3093	X'00000C15'
MQCACF_TO_CF_STRUC_NAME	3094	X'00000C16'
MQCACF_CF_STRUC_NAMES	3095	X'00000C17'
MQCACF_FAIL_DATE	3096	X'00000C18'
MQCACF_FAIL_TIME	3097	X'00000C19'
MQCACF_BACKUP_DATE	3098	X'00000C1A'
MQCACF_BACKUP_TIME	3099	X'00000C1B'
MQCACF_SYSTEM_NAME	3100	X'00000C1C'
MQCACF_CF_STRUC_BACKUP_START	3101	X'00000C1D'
MQCACF_CF_STRUC_BACKUP_END	3102	X'00000C1E'
MQCACF_CF_STRUC_LOG_Q_MGRS	3103	X'00000C1F'
MQCACF_FROM_STORAGE_CLASS	3104	X'00000C20'
MQCACF_TO_STORAGE_CLASS	3105	X'00000C21'
MQCACF_STORAGE_CLASS_NAMES	3106	X'00000C22'
MQCACF_DSG_NAME	3108	X'00000C24'
MQCACF_DB2_NAME	3109	X'00000C25'
MQCACF_SYSP_CMD_USER_ID	3110	X'00000C26'
MQCACF_SYSP_OTMA_GROUP	3111	X'00000C27'
MQCACF_SYSP_OTMA_MEMBER	3112	X'00000C28'
MQCACF_SYSP_OTMA_DRU_EXIT	3113	X'00000C29'
MQCACF_SYSP_OTMA_TPIPE_PFX	3114	X'00000C2A'
MQCACF_SYSP_ARCHIVE_PFX1	3115	X'00000C2B'
MQCACF_SYSP_ARCHIVE_UNIT1	3116	X'00000C2C'
MQCACF_SYSP_LOG_CORREL_ID	3117	X'00000C2D'
MQCACF_SYSP_UNIT_VOLSER	3118	X'00000C2E'
MQCACF_SYSP_Q_MGR_TIME	3119	X'00000C2F'

MQCACF_SYSP_Q_MGR_DATE	3120	X'00000C30'
MQCACF_SYSP_Q_MGR_RBA	3121	X'00000C31'
MQCACF_SYSP_LOG_RBA	3122	X'00000C32'
MQCACF_SYSP_SERVICE	3123	X'00000C33'
MQCACF_FROM_LISTENER_NAME	3124	X'00000C34'
MQCACF_TO_LISTENER_NAME	3125	X'00000C35'
MQCACF_FROM_SERVICE_NAME	3126	X'00000C36'
MQCACF_TO_SERVICE_NAME	3127	X'00000C37'
MQCACF_LAST_PUT_DATE	3128	X'00000C38'
MQCACF_LAST_PUT_TIME	3129	X'00000C39'
MQCACF_LAST_GET_DATE	3130	X'00000C3A'
MQCACF_LAST_GET_TIME	3131	X'00000C3B'
MQCACF_OPERATION_DATE	3132	X'00000C3C'
MQCACF_OPERATION_TIME	3133	X'00000C3D'
MQCACF_ACTIVITY_DESC	3134	X'00000C3E'
MQCACF_APPL_IDENTITY_DATA	3135	X'00000C3F'
MQCACF_APPL_ORIGIN_DATA	3136	X'00000C40'
MQCACF_PUT_DATE	3137	X'00000C41'
MQCACF_PUT_TIME	3138	X'00000C42'
MQCACF_REPLY_TO_Q	3139	X'00000C43'
MQCACF_REPLY_TO_Q_MGR	3140	X'00000C44'
MQCACF_RESOLVED_Q_NAME	3141	X'00000C45'
MQCACF_STRUC_ID	3142	X'00000C46'
MQCACF_VALUE_NAME	3143	X'00000C47'
MQCACF_SERVICE_START_DATE	3144	X'00000C48'
MQCACF_SERVICE_START_TIME	3145	X'00000C49'
MQCACF_SYSP_OFFLINE_RBA	3146	X'00000C4A'
MQCACF_SYSP_ARCHIVE_PFX2	3147	X'00000C4B'
MQCACF_SYSP_ARCHIVE_UNIT2	3148	X'00000C4C'
MQCACF_TO_TOPIC_NAME	3149	X'00000C4D'
MQCACF_FROM_TOPIC_NAME	3150	X'00000C4E'
MQCACF_TOPIC_NAMES	3151	X'00000C4F'
MQCACF_SUB_NAME	3152	X'00000C50'
MQCACF_DESTINATION_Q_MGR	3153	X'00000C51'
MQCACF_DESTINATION	3154	X'00000C52'
MQCACF_SUB_USER_ID	3156	X'00000C54'
MQCACF_SUB_USER_DATA	3159	X'00000C57'
MQCACF_SUB_SELECTOR	3160	X'00000C58'
MQCACF_LAST_PUB_DATE	3161	X'00000C59'
MQCACF_LAST_PUB_TIME	3162	X'00000C5A'
MQCACF_FROM_SUB_NAME	3163	X'00000C5B'
MQCACF_TO_SUB_NAME	3164	X'00000C5C'

MQCACF_LAST_MSG_TIME	3167	X'00000C5F'
MQCACF_LAST_MSG_DATE	3168	X'00000C60'
MQCACF_SUBSCRIPTION_POINT	3169	X'00000C61'
MQCACF_FILTER	3170	X'00000C62'
MQCACF_NONE	3171	X'00000C63'
MQCACF_ADMIN_TOPIC_NAMES	3172	X'00000C64'
MQCACF_LAST_USED	3172	X'00000C64'

MQCACH_* (Command format Character Channel Parameter Types)

MQCACH_FIRST	3501	X'00000DAD'
MQCACH_CHANNEL_NAME	3501	X'00000DAD'
MQCACH_DESC	3502	X'00000DAE'
MQCACH_MODE_NAME	3503	X'00000DAF'
MQCACH_TP_NAME	3504	X'00000DB0'
MQCACH_XMIT_Q_NAME	3505	X'00000DB1'
MQCACH_CONNECTION_NAME	3506	X'00000DB2'
MQCACH_MCA_NAME	3507	X'00000DB3'
MQCACH_SEC_EXIT_NAME	3508	X'00000DB4'
MQCACH_MSG_EXIT_NAME	3509	X'00000DB5'
MQCACH_SEND_EXIT_NAME	3510	X'00000DB6'
MQCACH_RCV_EXIT_NAME	3511	X'00000DB7'
MQCACH_CHANNEL_NAMES	3512	X'00000DB8'
MQCACH_SEC_EXIT_USER_DATA	3513	X'00000DB9'
MQCACH_MSG_EXIT_USER_DATA	3514	X'00000DBA'
MQCACH_SEND_EXIT_USER_DATA	3515	X'00000DBB'
MQCACH_RCV_EXIT_USER_DATA	3516	X'00000DBC'
MQCACH_USER_ID	3517	X'00000DBD'
MQCACH_PASSWORD	3518	X'00000DBE'
MQCACH_LOCAL_ADDRESS	3520	X'00000DC0'
MQCACH_LOCAL_NAME	3521	X'00000DC1'
MQCACH_LAST_MSG_TIME	3524	X'00000DC4'
MQCACH_LAST_MSG_DATE	3525	X'00000DC5'
MQCACH_MCA_USER_ID	3527	X'00000DC7'
MQCACH_CHANNEL_START_TIME	3528	X'00000DC8'
MQCACH_CHANNEL_START_DATE	3529	X'00000DC9'
MQCACH_MCA_JOB_NAME	3530	X'00000DCA'
MQCACH_LAST_LUWID	3531	X'00000DCB'
MQCACH_CURRENT_LUWID	3532	X'00000DCC'
MQCACH_FORMAT_NAME	3533	X'00000DCD'
MQCACH_MR_EXIT_NAME	3534	X'00000DCE'
MQCACH_MR_EXIT_USER_DATA	3535	X'00000DCF'

MQCACH_SSL_CIPHER_SPEC	3544	X'00000DD8'
MQCACH_SSL_PEER_NAME	3545	X'00000DD9'
MQCACH_SSL_HANDSHAKE_STAGE	3546	X'00000DDA'
MQCACH_SSL_SHORT_PEER_NAME	3547	X'00000ddb'
MQCACH_REMOTE_APPL_TAG	3548	X'00000DDC'
MQCACH_SSL_CERT_USER_ID	3549	X'00000DDD'
MQCACH_SSL_CERT_ISSUER_NAME	3550	X'00000DDE'
MQCACH_LU_NAME	3551	X'00000DDF'
MQCACH_IP_ADDRESS	3552	X'00000DE0'
MQCACH_TCP_NAME	3553	X'00000DE1'
MQCACH_LISTENER_NAME	3554	X'00000DE2'
MQCACH_LISTENER_DESC	3555	X'00000DE3'
MQCACH_LISTENER_START_DATE	3556	X'00000DE4'
MQCACH_LISTENER_START_TIME	3557	X'00000DE5'
MQCACH_SSL_KEY_RESET_DATE	3558	X'00000DE6'
MQCACH_SSL_KEY_RESET_TIME	3559	X'00000DE7'
MQCACH_LAST_USED	3559	X'00000DE7'

MQCADSD_* (CICS information header ADS Descriptors)

MQCADSD_NONE	0	X'00000000'
MQCADSD_SEND	1	X'00000001'
MQCADSD_RECV	16	X'00000010'
MQCADSD_MSGFORMAT	256	X'00000100'

MQCAFTY_* (Connection Affinity Values)

MQCAFTY_NONE	0	X'00000000'
MQCAFTY_PREFERRED	1	X'00000001'

MQCAMO_* (Command format Character Monitoring Parameter Types)

MQCAMO_FIRST	2701	X'00000A8D'
MQCAMO_CLOSE_DATE	2701	X'00000A8D'
MQCAMO_CLOSE_TIME	2702	X'00000A8E'
MQCAMO_CONN_DATE	2703	X'00000A8F'
MQCAMO_CONN_TIME	2704	X'00000A90'
MQCAMO_DISC_DATE	2705	X'00000A91'
MQCAMO_DISC_TIME	2706	X'00000A92'
MQCAMO_END_DATE	2707	X'00000A93'
MQCAMO_END_TIME	2708	X'00000A94'
MQCAMO_OPEN_DATE	2709	X'00000A95'

MQCAMO_OPEN_TIME	2710	X'00000A96'
MQCAMO_START_DATE	2711	X'00000A97'
MQCAMO_START_TIME	2712	X'00000A98'
MQCAMO_LAST_USED	2712	X'00000A98'

MQCBC_* (MQCBC constants structure)

MQCBC_STRUC_ID	"CBCb"	
MQCBC_STRUC_ID_ARRAY	'C','B','C','b'	
MQCBC_VERSION_1	1	X'00000001'
MQCBC_CURRENT_VERSION	1	X'00000001'

MQCBCF_* (MQCBC constants Flags)

MQCBCF_NONE	0	X'00000000'
MQCBCF_READA_BUFFER_EMPTY	1	X'00000001'

MQCBCT_* (MQCBC constants Callback type)

MQCBCT_START_CALL	1	X'00000001'
MQCBCT_STOP_CALL	2	X'00000002'
MQCBCT_REGISTER_CALL	3	X'00000003'
MQCBCT_DEREGISTER_CALL	4	X'00000004'
MQCBCT_EVENT_CALL	5	X'00000005'
MQCBCT_MSG_REMOVED	6	X'00000006'
MQCBCT_MSG_NOT_REMOVED	7	X'00000007'

MQCBD_* (MQCBD constants structure)

MQCBD_STRUC_ID	"CBDb"	
MQCBD_STRUC_ID_ARRAY	'C','B','D','b'	
MQCBD_VERSION_1	1	X'00000001'
MQCBD_CURRENT_VERSION	1	X'00000001'

MQCBDO_* (MQCBD constants Callback Options)

MQCBDO_NONE	0	X'00000000'
MQCBDO_START_CALL	1	X'00000001'
MQCBDO_STOP_CALL	4	X'00000004'
MQCBDO_REGISTER_CALL	256	X'00000100'
MQCBDO_DEREGISTER_CALL	512	X'00000200'

MQCBDO_FAIL_IF QUIESCING	8192	X'00002000'
--------------------------	------	-------------

MQCBO_* (Create-Bag Options for mqCreateBag)

MQCBO_NONE	0	X'00000000'
MQCBO_USER_BAG	0	X'00000000'
MQCBO_ADMIN_BAG	1	X'00000001'
MQCBO_COMMAND_BAG	16	X'00000010'
MQCBO_SYSTEM_BAG	32	X'00000020'
MQCBO_GROUP_BAG	64	X'00000040'
MQCBO_LIST_FORM_ALLOWED	2	X'00000002'
MQCBO_LIST_FORM_INHIBITED	0	X'00000000'
MQCBO_REORDER_AS_REQUIRED	4	X'00000004'
MQCBO_DO_NOT_REORDER	0	X'00000000'
MQCBO_CHECK_SELECTORS	8	X'00000008'
MQCBO_DO_NOT_CHECK_SELECTORS	0	X'00000000'

MQCBT_* (MQCBD constants This is the type of the Callback Function)

MQCBT_MESSAGE_CONSUMER	1	X'00000001'
MQCBT_EVENT_HANDLER	2	X'00000002'

MQCC_* (Completion Codes)

MQCC_OK	0	X'00000000'
MQCC_WARNING	1	X'00000001'
MQCC_FAILED	2	X'00000002'
MQCC_UNKNOWN	-1	X'FFFFFFFF'

MQCCSI_* (Coded Character Set Identifiers)

MQCCSI_UNDEFINED	0	X'00000000'
MQCCSI_DEFAULT	0	X'00000000'
MQCCSI_Q_MGR	0	X'00000000'
MQCCSI_INHERIT	-2	X'FFFFFFFF'
MQCCSI_EMBEDDED	-1	X'FFFFFFFF'
MQCCSI_APPL	-3	X'FFFFFFFF'

MQCCT_* (CICS information header Conversational Task Options)

MQCCT_YES	1	X'00000001'
-----------	---	-------------

MQCCT_NO	0	X'00000000'
----------	---	-------------

MQCD_* (Channel definition structure)

MQCD_VERSION_1	1	X'00000001'
MQCD_VERSION_2	2	X'00000002'
MQCD_VERSION_3	3	X'00000003'
MQCD_VERSION_4	4	X'00000004'
MQCD_VERSION_5	5	X'00000005'
MQCD_VERSION_6	6	X'00000006'
MQCD_VERSION_7	7	X'00000007'
MQCD_VERSION_8	8	X'00000008'
MQCD_VERSION_9	9	X'00000009'
MQCD_CURRENT_VERSION	9	X'00000009'
MQCD_LENGTH_4	(value differs by platform or version)	
MQCD_LENGTH_5	(value differs by platform or version)	
MQCD_LENGTH_6	(value differs by platform or version)	
MQCD_LENGTH_7	(value differs by platform or version)	
MQCD_LENGTH_8	(value differs by platform or version)	
MQCD_LENGTH_9	(value differs by platform or version)	
MQCD_CURRENT_LENGTH	(value differs by platform or version)	

MQCDC_* (Channel Data Conversion)

MQCDC_SENDER_CONVERSION	1	X'00000001'
MQCDC_NO_SENDER_CONVERSION	0	X'00000000'

MQCF_* (Capability Flags)

MQCF_NONE	0	X'00000000'
MQCF_DIST_LISTS	1	X'00000001'

MQCFAC_* (CICS information header Facility)

MQCFAC_NONE	X'00...00'	(8 nulls)
MQCFAC_NONE_ARRAY	'\0','\0',...	(8 nulls)

MQCFBF_* (Command format byte string filter parameter structure)

MQCFBF_STRUC_LENGTH_FIXED	20	X'00000014'
---------------------------	----	-------------

MQCFBS_* (Command format byte string parameter structure)

MQCFBS_STRUC_LENGTH_FIXED	16	X'00000010'
---------------------------	----	-------------

MQCFC_* (Command format header Control Options)

MQCFC_LAST	1	X'00000001'
MQCFC_NOT_LAST	0	X'00000000'

MQCFGR_* (Command format group parameter structure)

MQCFGR_STRUC_LENGTH	16	X'00000010'
---------------------	----	-------------

MQCFH_* (Command format header structure)

MQCFH_STRUC_LENGTH	36	X'00000024'
MQCFH_VERSION_1	1	X'00000001'
MQCFH_VERSION_2	2	X'00000002'
MQCFH_VERSION_3	3	X'00000003'
MQCFH_CURRENT_VERSION	3	X'00000003'

MQCFIF_* (Command format integer filter parameter structure)

MQCFIF_STRUC_LENGTH	20	X'00000014'
---------------------	----	-------------

MQCFIL_* (Command format integer list parameter structure)

MQCFIL_STRUC_LENGTH_FIXED	16	X'00000010'
---------------------------	----	-------------

MQCFIL64_* (Command format 64-bit integer list parameter structure)

MQCFIL64_STRUC_LENGTH_FIXED	16	X'00000010'
-----------------------------	----	-------------

MQCFIN_* (Command format integer parameter structure)

MQCFIN_STRUC_LENGTH	16	X'00000010'
---------------------	----	-------------

MQCFIN64_* (Command format 64-bit integer parameter structure)

MQCFIN64_STRUC_LENGTH	24	X'00000018'
-----------------------	----	-------------

MQCFO_* (Command format Refresh Repository Options)

MQCFO_REFRESH_REPOSITORY_YES	1	X'00000001'
MQCFO_REFRESH_REPOSITORY_NO	0	X'00000000'

MQCFO_* (Command format Remove Queues Options)

MQCFO_REMOVE_QUEUES_YES	1	X'00000001'
MQCFO_REMOVE_QUEUES_NO	0	X'00000000'

MQCFOP_* (Command format Filter Operators)

MQCFOP_LESS	1	X'00000001'
MQCFOP_EQUAL	2	X'00000002'
MQCFOP_GREATER	4	X'00000004'
MQCFOP_NOT_LESS	6	X'00000006'
MQCFOP_NOT_EQUAL	5	X'00000005'
MQCFOP_NOT_GREATER	3	X'00000003'
MQCFOP_LIKE	18	X'00000012'
MQCFOP_NOT_LIKE	21	X'00000015'
MQCFOP_CONTAINS	10	X'0000000A'
MQCFOP_EXCLUDES	13	X'0000000D'
MQCFOP_CONTAINS_GEN	26	X'0000001A'
MQCFOP_EXCLUDES_GEN	29	X'0000001D'

MQCFR_* (CF Recoverability)

MQCFR_YES	1	X'00000001'
MQCFR_NO	0	X'00000000'

MQCFSF_* (Command format string filter parameter structure)

MQCFSF_STRUC_LENGTH_FIXED	24	X'00000018'
---------------------------	----	-------------

MQCFSL_* (Command format string list parameter structure)

MQCFSL_STRUC_LENGTH_FIXED	24	X'00000018'
---------------------------	----	-------------

MQCFST_* (Command format string parameter structure)

MQCFST_STRUC_LENGTH_FIXED	20	X'00000014'
---------------------------	----	-------------

MQCFSTATUS_* (Command format CF Status)

MQCFSTATUS_NOT_FOUND	0	X'00000000'
MQCFSTATUS_ACTIVE	1	X'00000001'
MQCFSTATUS_IN_RECOVER	2	X'00000002'
MQCFSTATUS_IN_BACKUP	3	X'00000003'
MQCFSTATUS_FAILED	4	X'00000004'
MQCFSTATUS_NONE	5	X'00000005'
MQCFSTATUS_UNKNOWN	6	X'00000006'
MQCFSTATUS_ADMIN_INCOMPLETE	20	X'00000014'
MQCFSTATUS_NEVER_USED	21	X'00000015'
MQCFSTATUS_NO_BACKUP	22	X'00000016'
MQCFSTATUS_NOT_FAILED	23	X'00000017'
MQCFSTATUS_NOT_RECOVERABLE	24	X'00000018'
MQCFSTATUS_XES_ERROR	25	X'00000019'

MQCFT_* (Command format Types of Structure)

MQCFT_NONE	0	X'00000000'
MQCFT_COMMAND	1	X'00000001'
MQCFT_RESPONSE	2	X'00000002'
MQCFT_INTEGER	3	X'00000003'
MQCFT_STRING	4	X'00000004'
MQCFT_INTEGER_LIST	5	X'00000005'
MQCFT_STRING_LIST	6	X'00000006'
MQCFT_EVENT	7	X'00000007'
MQCFT_USER	8	X'00000008'
MQCFT_BYTE_STRING	9	X'00000009'
MQCFT_TRACE_ROUTE	10	X'0000000A'
MQCFT_REPORT	12	X'0000000C'
MQCFT_INTEGER_FILTER	13	X'0000000D'
MQCFT_STRING_FILTER	14	X'0000000E'
MQCFT_BYTE_STRING_FILTER	15	X'0000000F'
MQCFT_COMMAND_XR	16	X'00000010'
MQCFT_XR_MSG	17	X'00000011'
MQCFT_XR_ITEM	18	X'00000012'
MQCFT_XR_SUMMARY	19	X'00000013'
MQCFT_GROUP	20	X'00000014'

MQCFT_STATISTICS	21	X'00000015'
MQCFT_ACCOUNTING	22	X'00000016'
MQCFT_INTEGER64	23	X'00000017'
MQCFT_INTEGER64_LIST	25	X'00000019'

MQCFTYPE_* (Command format CF Types)

MQCFTYPE_APPL	0	X'00000000'
MQCFTYPE_ADMIN	1	X'00000001'

MQCFUNC_* (CICS information header Functions)

MQCFUNC_MQCONN	"CONN"	
MQCFUNC_MQGET	"GETb"	
MQCFUNC_MQINQ	"INQb"	
MQCFUNC_MQOPEN	"OPEN"	
MQCFUNC_MQPUT	"PUTb"	
MQCFUNC_MQPUT1	"PUT1"	
MQCFUNC_NONE	"bbbb"	
MQCFUNC_MQCONN_ARRAY	'C','O','N','N'	
MQCFUNC_MQGET_ARRAY	'G','E','T','b'	
MQCFUNC_MQINQ_ARRAY	'I','N','Q','b'	
MQCFUNC_MQOPEN_ARRAY	'O','P','E','N'	
MQCFUNC_MQPUT_ARRAY	'P','U','T','b'	
MQCFUNC_MQPUT1_ARRAY	'P','U','T','1'	
MQCFUNC_NONE_ARRAY	'b','b','b','b'	

MQCGWI_* (CICS information header Get Wait Interval)

MQCGWI_DEFAULT	-2	X'FFFFFFFE'
----------------	----	-------------

MQCHAD_* (Channel Auto Definition)

MQCHAD_DISABLED	0	X'00000000'
MQCHAD_ENABLED	1	X'00000001'

MQCHIDS_* (Command format Indoubt Status)

MQCHIDS_NOT_INDOUBT	0	X'00000000'
MQCHIDS_INDOUBT	1	X'00000001'

MQCHLD_* (Command format Channel Dispositions)

MQCHLD_ALL	-1	X'FFFFFFFF'
MQCHLD_DEFAULT	1	X'00000001'
MQCHLD_SHARED	2	X'00000002'
MQCHLD_PRIVATE	4	X'00000004'
MQCHLD_FIXSHARED	5	X'00000005'

MQCHS_* (Command format Channel Status)

MQCHS_INACTIVE	0	X'00000000'
MQCHS_BINDING	1	X'00000001'
MQCHS_STARTING	2	X'00000002'
MQCHS_RUNNING	3	X'00000003'
MQCHS_STOPPING	4	X'00000004'
MQCHS_RETRYING	5	X'00000005'
MQCHS_STOPPED	6	X'00000006'
MQCHS_REQUESTING	7	X'00000007'
MQCHS_PAUSED	8	X'00000008'
MQCHS_INITIALIZING	13	X'0000000D'

MQCHSH_* (Command format Channel Shared Restart Options)

MQCHSH_RESTART_NO	0	X'00000000'
MQCHSH_RESTART_YES	1	X'00000001'

MQCHSR_* (Command format Channel Stop Options)

MQCHSR_STOP_NOT_REQUESTED	0	X'00000000'
MQCHSR_STOP_REQUESTED	1	X'00000001'

MQCHSSTATE_* (Command format Channel Substates)

MQCHSSTATE_OTHER	0	X'00000000'
MQCHSSTATE_END_OF_BATCH	100	X'00000064'
MQCHSSTATE_SENDING	200	X'000000C8'
MQCHSSTATE_RECEIVING	300	X'0000012C'
MQCHSSTATE_SERIALIZING	400	X'00000190'
MQCHSSTATE_RESYNCHING	500	X'000001F4'
MQCHSSTATE_HEARTBEATING	600	X'00000258'
MQCHSSTATE_IN_SCYEXIT	700	X'000002BC'
MQCHSSTATE_IN_RCVEXIT	800	X'00000320'

MQCHSSTATE_IN_SENDEXIT	900	X'00000384'
MQCHSSTATE_IN_MSGEXIT	1000	X'000003E8'
MQCHSSTATE_IN_MREXIT	1100	X'0000044C'
MQCHSSTATE_IN_CHADEXIT	1200	X'000004B0'
MQCHSSTATE_NET_CONNECTING	1250	X'000004E2'
MQCHSSTATE_SSL_HANDSHAKING	1300	X'00000514'
MQCHSSTATE_NAME_SERVER	1400	X'00000578'
MQCHSSTATE_IN_MQPUT	1500	X'000005DC'
MQCHSSTATE_IN_MQGET	1600	X'00000640'
MQCHSSTATE_IN_MQI_CALL	1700	X'000006A4'
MQCHSSTATE_COMPRESSING	1800	X'00000708'

MQCHT_* (Channel Types)

MQCHT_SENDER	1	X'00000001'
MQCHT_SERVER	2	X'00000002'
MQCHT_RECEIVER	3	X'00000003'
MQCHT_REQUESTER	4	X'00000004'
MQCHT_ALL	5	X'00000005'
MQCHT_CLNTCONN	6	X'00000006'
MQCHT_SVRCONN	7	X'00000007'
MQCHT_CLUSRCVR	8	X'00000008'
MQCHT_CLUSSDR	9	X'00000009'

MQCHTAB_* (Command format Channel Table Types)

MQCHTAB_Q_MGR	1	X'00000001'
MQCHTAB_CLNTCONN	2	X'00000002'

MQCI_* (Correlation Identifier)

MQCI_NONE	X'00...00'	(24 nulls)
MQCI_NONE_ARRAY	'\0','\0',...	(24 nulls)
MQCI_NEW_SESSION	X'414D5121...'	
MQCI_NEW_SESSION_ARRAY	'\x41','\x4D','\51','\x21',...	

MQCIH_* (CICS information header structure)

MQCIH_STRUC_ID	"CIHb"	
MQCIH_STRUC_ID_ARRAY	'C','I','H','b'	
MQCIH_VERSION_1		1 X'00000001'

MQCIH_VERSION_2	2	X'00000002'
MQCIH_CURRENT_VERSION	2	X'00000002'
MQCIH_LENGTH_1	164	X'000000A4'
MQCIH_LENGTH_2	180	X'000000B4'
MQCIH_CURRENT_LENGTH	180	X'000000B4'

MQCIH_* (CICS information header Flags)

MQCIH_NONE	0	X'00000000'
MQCIH_PASS_EXPIRATION	1	X'00000001'
MQCIH_UNLIMITED_EXPIRATION	0	X'00000000'
MQCIH_REPLY_WITHOUT_NULLS	2	X'00000002'
MQCIH_REPLY_WITH_NULLS	0	X'00000000'
MQCIH_SYNC_ON_RETURN	4	X'00000004'
MQCIH_NO_SYNC_ON_RETURN	0	X'00000000'

MQCLCT_* (Cluster Cache Types)

MQCLCT_STATIC	0	X'00000000'
MQCLCT_DYNAMIC	1	X'00000001'

MQCLRS_* (Command format Clear Topic String Scope)

MQCLRS_LOCAL	1	X'00000001'
MQCLRS_GLOBAL	2	X'00000002'

MQCLRT_* (Command format Clear Topic String Type)

MQCLRT_RETAINED	1	X'00000001'
-----------------	---	-------------

MQCLT_* (CICS information header Link Types)

MQCLT_PROGRAM	1	X'00000001'
MQCLT_TRANSACTION	2	X'00000002'

MQCLWL_* (Cluster Workload)

MQCLWL_USEQ_LOCAL	0	X'00000000'
MQCLWL_USEQ_ANY	1	X'00000001'
MQCLWL_USEQ_AS_Q_MGR	-3	X'FFFFFFFD'

MQCMD_* (Command Codes)

MQCMD_NONE	0	X'00000000'
MQCMD_CHANGE_Q_MGR	1	X'00000001'
MQCMD_INQUIRE_Q_MGR	2	X'00000002'
MQCMD_CHANGE_PROCESS	3	X'00000003'
MQCMD_COPY_PROCESS	4	X'00000004'
MQCMD_CREATE_PROCESS	5	X'00000005'
MQCMD_DELETE_PROCESS	6	X'00000006'
MQCMD_INQUIRE_PROCESS	7	X'00000007'
MQCMD_CHANGE_Q	8	X'00000008'
MQCMD_CLEAR_Q	9	X'00000009'
MQCMD_COPY_Q	10	X'0000000A'
MQCMD_CREATE_Q	11	X'0000000B'
MQCMD_DELETE_Q	12	X'0000000C'
MQCMD_INQUIRE_Q	13	X'0000000D'
MQCMD_REFRESH_Q_MGR	16	X'00000010'
MQCMD_RESET_Q_STATS	17	X'00000011'
MQCMD_INQUIRE_Q_NAMES	18	X'00000012'
MQCMD_INQUIRE_PROCESS_NAMES	19	X'00000013'
MQCMD_INQUIRE_CHANNEL_NAMES	20	X'00000014'
MQCMD_CHANGE_CHANNEL	21	X'00000015'
MQCMD_COPY_CHANNEL	22	X'00000016'
MQCMD_CREATE_CHANNEL	23	X'00000017'
MQCMD_DELETE_CHANNEL	24	X'00000018'
MQCMD_INQUIRE_CHANNEL	25	X'00000019'
MQCMD_PING_CHANNEL	26	X'0000001A'
MQCMD_RESET_CHANNEL	27	X'0000001B'
MQCMD_START_CHANNEL	28	X'0000001C'
MQCMD_STOP_CHANNEL	29	X'0000001D'
MQCMD_START_CHANNEL_INIT	30	X'0000001E'
MQCMD_START_CHANNEL_LISTENER	31	X'0000001F'
MQCMD_CHANGE_NAMELIST	32	X'00000020'
MQCMD_COPY_NAMELIST	33	X'00000021'
MQCMD_CREATE_NAMELIST	34	X'00000022'
MQCMD_DELETE_NAMELIST	35	X'00000023'
MQCMD_INQUIRE_NAMELIST	36	X'00000024'
MQCMD_INQUIRE_NAMELIST_NAMES	37	X'00000025'
MQCMD_ESCAPE	38	X'00000026'
MQCMD_RESOLVE_CHANNEL	39	X'00000027'
MQCMD_PING_Q_MGR	40	X'00000028'
MQCMD_INQUIRE_Q_STATUS	41	X'00000029'

MQCMD_INQUIRE_CHANNEL_STATUS	42	X'0000002A'
MQCMD_CONFIG_EVENT	43	X'0000002B'
MQCMD_Q_MGR_EVENT	44	X'0000002C'
MQCMD_PERFM_EVENT	45	X'0000002D'
MQCMD_CHANNEL_EVENT	46	X'0000002E'
MQCMD_DELETE_PUBLICATION	60	X'0000003C'
MQCMD_DEREGISTER_PUBLISHER	61	X'0000003D'
MQCMD_DEREGISTER_SUBSCRIBER	62	X'0000003E'
MQCMD_PUBLISH	63	X'0000003F'
MQCMD_REGISTER_PUBLISHER	64	X'00000040'
MQCMD_REGISTER_SUBSCRIBER	65	X'00000041'
MQCMD_REQUEST_UPDATE	66	X'00000042'
MQCMD_BROKER_INTERNAL	67	X'00000043'
MQCMD_ACTIVITY_MSG	69	X'00000045'
MQCMD_INQUIRE_CLUSTER_Q_MGR	70	X'00000046'
MQCMD_RESUME_Q_MGR_CLUSTER	71	X'00000047'
MQCMD_SUSPEND_Q_MGR_CLUSTER	72	X'00000048'
MQCMD_REFRESH_CLUSTER	73	X'00000049'
MQCMD_RESET_CLUSTER	74	X'0000004A'
MQCMD_TRACE_ROUTE	75	X'0000004B'
MQCMD_REFRESH_SECURITY	78	X'0000004E'
MQCMD_CHANGE_AUTH_INFO	79	X'0000004F'
MQCMD_COPY_AUTH_INFO	80	X'00000050'
MQCMD_CREATE_AUTH_INFO	81	X'00000051'
MQCMD_DELETE_AUTH_INFO	82	X'00000052'
MQCMD_INQUIRE_AUTH_INFO	83	X'00000053'
MQCMD_INQUIRE_AUTH_INFO_NAMES	84	X'00000054'
MQCMD_INQUIRE_CONNECTION	85	X'00000055'
MQCMD_STOP_CONNECTION	86	X'00000056'
MQCMD_INQUIRE_AUTH_RECS	87	X'00000057'
MQCMD_INQUIRE_ENTITY_AUTH	88	X'00000058'
MQCMD_DELETE_AUTH_REC	89	X'00000059'
MQCMD_SET_AUTH_REC	90	X'0000005A'
MQCMD_LOGGER_EVENT	91	X'0000005B'
MQCMD_RESET_Q_MGR	92	X'0000005C'
MQCMD_CHANGE_LISTENER	93	X'0000005D'
MQCMD_COPY_LISTENER	94	X'0000005E'
MQCMD_CREATE_LISTENER	95	X'0000005F'
MQCMD_DELETE_LISTENER	96	X'00000060'
MQCMD_INQUIRE_LISTENER	97	X'00000061'
MQCMD_INQUIRE_LISTENER_STATUS	98	X'00000062'
MQCMD_COMMAND_EVENT	99	X'00000063'

MQCMD_CHANGE_SECURITY	100	X'00000064'
MQCMD_CHANGE_CF_STRUC	101	X'00000065'
MQCMD_CHANGE_STG_CLASS	102	X'00000066'
MQCMD_CHANGE_TRACE	103	X'00000067'
MQCMD_ARCHIVE_LOG	104	X'00000068'
MQCMD_BACKUP_CF_STRUC	105	X'00000069'
MQCMD_CREATE_BUFFER_POOL	106	X'0000006A'
MQCMD_CREATE_PAGE_SET	107	X'0000006B'
MQCMD_CREATE_CF_STRUC	108	X'0000006C'
MQCMD_CREATE_STG_CLASS	109	X'0000006D'
MQCMD_COPY_CF_STRUC	110	X'0000006E'
MQCMD_COPY_STG_CLASS	111	X'0000006F'
MQCMD_DELETE_CF_STRUC	112	X'00000070'
MQCMD_DELETE_STG_CLASS	113	X'00000071'
MQCMD_INQUIRE_ARCHIVE	114	X'00000072'
MQCMD_INQUIRE_CF_STRUC	115	X'00000073'
MQCMD_INQUIRE_CF_STRUC_STATUS	116	X'00000074'
MQCMD_INQUIRE_CMD_SERVER	117	X'00000075'
MQCMD_INQUIRE_CHANNEL_INIT	118	X'00000076'
MQCMD_INQUIRE_QSG	119	X'00000077'
MQCMD_INQUIRE_LOG	120	X'00000078'
MQCMD_INQUIRE_SECURITY	121	X'00000079'
MQCMD_INQUIRE_STG_CLASS	122	X'0000007A'
MQCMD_INQUIRE_SYSTEM	123	X'0000007B'
MQCMD_INQUIRE_THREAD	124	X'0000007C'
MQCMD_INQUIRE_TRACE	125	X'0000007D'
MQCMD_INQUIRE_USAGE	126	X'0000007E'
MQCMD_MOVE_Q	127	X'0000007F'
MQCMD_RECOVER_BSDS	128	X'00000080'
MQCMD_RECOVER_CF_STRUC	129	X'00000081'
MQCMD_RESET_TPIPE	130	X'00000082'
MQCMD_RESOLVE_INDOUBT	131	X'00000083'
MQCMD_RESUME_Q_MGR	132	X'00000084'
MQCMD_REVERIFY_SECURITY	133	X'00000085'
MQCMD_SET_ARCHIVE	134	X'00000086'
MQCMD_SET_LOG	136	X'00000088'
MQCMD_SET_SYSTEM	137	X'00000089'
MQCMD_START_CMD_SERVER	138	X'0000008A'
MQCMD_START_Q_MGR	139	X'0000008B'
MQCMD_START_TRACE	140	X'0000008C'
MQCMD_STOP_CHANNEL_INIT	141	X'0000008D'
MQCMD_STOP_CHANNEL_LISTENER	142	X'0000008E'

MQCMD_STOP_CMD_SERVER	143	X'0000008F'
MQCMD_STOP_Q_MGR	144	X'00000090'
MQCMD_STOP_TRACE	145	X'00000091'
MQCMD_SUSPEND_Q_MGR	146	X'00000092'
MQCMD_INQUIRE_CF_STRUC_NAMES	147	X'00000093'
MQCMD_INQUIRE_STG_CLASS_NAMES	148	X'00000094'
MQCMD_CHANGE_SERVICE	149	X'00000095'
MQCMD_COPY_SERVICE	150	X'00000096'
MQCMD_CREATE_SERVICE	151	X'00000097'
MQCMD_DELETE_SERVICE	152	X'00000098'
MQCMD_INQUIRE_SERVICE	153	X'00000099'
MQCMD_INQUIRE_SERVICE_STATUS	154	X'0000009A'
MQCMD_START_SERVICE	155	X'0000009B'
MQCMD_STOP_SERVICE	156	X'0000009C'
MQCMD_DELETE_BUFFER_POOL	157	X'0000009D'
MQCMD_DELETE_PAGE_SET	158	X'0000009E'
MQCMD_CHANGE_BUFFER_POOL	159	X'0000009F'
MQCMD_CHANGE_PAGE_SET	160	X'000000A0'
MQCMD_INQUIRE_Q_MGR_STATUS	161	X'000000A1'
MQCMD_CREATE_LOG	162	X'000000A2'
MQCMD_STATISTICS_MQI	164	X'000000A4'
MQCMD_STATISTICS_Q	165	X'000000A5'
MQCMD_STATISTICS_CHANNEL	166	X'000000A6'
MQCMD_ACCOUNTING_MQI	167	X'000000A7'
MQCMD_ACCOUNTING_Q	168	X'000000A8'
MQCMD_INQUIRE_AUTH_SERVICE	169	X'000000A9'
MQCMD_CHANGE_TOPIC	170	X'000000AA'
MQCMD_COPY_TOPIC	171	X'000000AB'
MQCMD_CREATE_TOPIC	172	X'000000AC'
MQCMD_DELETE_TOPIC	173	X'000000AD'
MQCMD_INQUIRE_TOPIC	174	X'000000AE'
MQCMD_INQUIRE_TOPIC_NAMES	175	X'000000AF'
MQCMD_INQUIRE_SUBSCRIPTION	176	X'000000B0'
MQCMD_CREATE_SUBSCRIPTION	177	X'000000B1'
MQCMD_CHANGE_SUBSCRIPTION	178	X'000000B2'
MQCMD_DELETE_SUBSCRIPTION	179	X'000000B3'
MQCMD_COPY_SUBSCRIPTION	181	X'000000B5'
MQCMD_INQUIRE_SUB_STATUS	182	X'000000B6'
MQCMD_INQUIRE_TOPIC_STATUS	183	X'000000B7'
MQCMD_CLEAR_TOPIC_STRING	184	X'000000B8'
MQCMD_INQUIRE_PUBSUB_STATUS	185	X'000000B9'

MQCMDI_* (Command format Command Information Values)

MQCMDI_CMDSCOPE_ACCEPTED	1	X'00000001'
MQCMDI_CMDSCOPE_GENERATED	2	X'00000002'
MQCMDI_CMDSCOPE_COMPLETED	3	X'00000003'
MQCMDI_QSG_DISP_COMPLETED	4	X'00000004'
MQCMDI_COMMAND_ACCEPTED	5	X'00000005'
MQCMDI_CLUSTER_REQUEST_QUEUED	6	X'00000006'
MQCMDI_CHANNEL_INIT_STARTED	7	X'00000007'
MQCMDI_RECOVER_STARTED	11	X'0000000B'
MQCMDI_BACKUP_STARTED	12	X'0000000C'
MQCMDI_RECOVER_COMPLETED	13	X'0000000D'
MQCMDI_SEC_TIMER_ZERO	14	X'0000000E'
MQCMDI_REFRESH_CONFIGURATION	16	X'00000010'
MQCMDI_SEC_SIGNOFF_ERROR	17	X'00000011'
MQCMDI_IMS_BRIDGE_SUSPENDED	18	X'00000012'
MQCMDI_DB2_SUSPENDED	19	X'00000013'
MQCMDI_DB2_OBSOLETE_MSGS	20	X'00000014'
MQCMDI_SEC_UPPERCASE	21	X'00000015'
MQCMDI_SEC_MIXEDCASE	22	X'00000016'

MQCMDL_* (Command Levels)

MQCMDL_LEVEL_1	100	X'00000064'
MQCMDL_LEVEL_101	101	X'00000065'
MQCMDL_LEVEL_110	110	X'0000006E'
MQCMDL_LEVEL_114	114	X'00000072'
MQCMDL_LEVEL_120	120	X'00000078'
MQCMDL_LEVEL_200	200	X'000000C8'
MQCMDL_LEVEL_201	201	X'000000C9'
MQCMDL_LEVEL_210	210	X'000000D2'
MQCMDL_LEVEL_211	211	X'000000D3'
MQCMDL_LEVEL_220	220	X'000000DC'
MQCMDL_LEVEL_221	221	X'000000DD'
MQCMDL_LEVEL_230	230	X'000000E6'
MQCMDL_LEVEL_320	320	X'00000140'
MQCMDL_LEVEL_420	420	X'000001A4'
MQCMDL_LEVEL_500	500	X'000001F4'
MQCMDL_LEVEL_510	510	X'000001FE'
MQCMDL_LEVEL_520	520	X'00000208'
MQCMDL_LEVEL_530	530	X'00000212'
MQCMDL_LEVEL_531	531	X'00000213'

MQCMDL_LEVEL_600	600	X'00000258'
MQCMDL_LEVEL_700	700	X'000002BC'

MQCMHO_* (Create message handle options structure)

MQCMHO_STRUC_ID	"CMHO"	
MQCMHO_STRUC_ID_ARRAY	'C','M','H','O'	
MQCMHO_VERSION_1	1	X'00000001'
MQCMHO_CURRENT_VERSION	1	X'00000001'

MQCMHO_* (Create Message Handle Options)

MQCMHO_DEFAULT_VALIDATION	0	X'00000000'
MQCMHO_NO_VALIDATION	1	X'00000001'
MQCMHO_VALIDATE	2	X'00000002'
MQCMHO_NONE	0	X'00000000'

MQCNO_* (Connect options structure)

MQCNO_STRUC_ID	"CNOb"	
MQCNO_STRUC_ID_ARRAY	'C','N','O','b'	
MQCNO_VERSION_1	1	X'00000001'
MQCNO_VERSION_2	2	X'00000002'
MQCNO_VERSION_3	3	X'00000003'
MQCNO_VERSION_4	4	X'00000004'
MQCNO_VERSION_5	5	X'00000005'
MQCNO_CURRENT_VERSION	5	X'00000005'

MQCNO_* (Connect Options)

MQCNO_STANDARD_BINDING	0	X'00000000'
MQCNO_FASTPATH_BINDING	1	X'00000001'
MQCNO_SERIALIZE_CONN_TAG_Q_MGR	2	X'00000002'
MQCNO_SERIALIZE_CONN_TAG_QSG	4	X'00000004'
MQCNO_RESTRICT_CONN_TAG_Q_MGR	8	X'00000008'
MQCNO_RESTRICT_CONN_TAG_QSG	16	X'00000010'
MQCNO_HANDLE_SHARE_NONE	32	X'00000020'
MQCNO_HANDLE_SHARE_BLOCK	64	X'00000040'
MQCNO_HANDLE_SHARE_NO_BLOCK	128	X'00000080'
MQCNO_SHARED_BINDING	256	X'00000100'
MQCNO_ISOLATED_BINDING	512	X'00000200'

MQCNO_ACCOUNTING_MQI_ENABLED	4096	X'00001000'
MQCNO_ACCOUNTING_MQI_DISABLED	8192	X'00002000'
MQCNO_ACCOUNTING_Q_ENABLED	16384	X'00004000'
MQCNO_ACCOUNTING_Q_DISABLED	32768	X'00008000'
MQCNO_NO_CONV_SHARING	65536	X'00010000'
MQCNO_ALL_CONVS_SHARE	262144	X'00040000'
MQCNO_CD_FOR_OUTPUT_ONLY	524288	X'00080000'
MQCNO_USE_CD_SELECTION	1048576	X'00100000'
MQCNO_NONE	0	X'00000000'

MQCO_* (Close Options)

MQCO_IMMEDIATE	0	X'00000000'
MQCO_NONE	0	X'00000000'
MQCO_DELETE	1	X'00000001'
MQCO_DELETE_PURGE	2	X'00000002'
MQCO_KEEP_SUB	4	X'00000004'
MQCO_REMOVE_SUB	8	X'00000008'
MQCO_QUIESCE	32	X'00000020'

MQCODL_* (CICS information header Output Data Length)

MQCODL_AS_INPUT	-1	X'FFFFFFFF'
-----------------	----	-------------

MQCOMPRESS_* (Channel Compression)

MQCOMPRESS_NOT_AVAILABLE	-1	X'FFFFFFFF'
MQCOMPRESS_NONE	0	X'00000000'
MQCOMPRESS_RLE	1	X'00000001'
MQCOMPRESS_ZLIBFAST	2	X'00000002'
MQCOMPRESS_ZLIBHIGH	4	X'00000004'
MQCOMPRESS_SYSTEM	8	X'00000008'
MQCOMPRESS_ANY	268435455	X'0FFFFFFFF'

MQCONNID_* (Connection Identifier)

MQCONNID_NONE	X'00...00'	(24 nulls)
MQCONNID_NONE_ARRAY	'\0','\0',...	(24 nulls)

MQCOPY_* (Property Copy Options)

MQCOPY_NONE	0	X'00000000'
-------------	---	-------------

MQCOPY_ALL	1	X'00000001'
MQCOPY_FORWARD	2	X'00000002'
MQCOPY_PUBLISH	4	X'00000004'
MQCOPY_REPLY	8	X'00000008'
MQCOPY_REPORT	16	X'00000010'
MQCOPY_DEFAULT	22	X'00000016'

MQCQT_* (Cluster Queue Types)

MQCQT_LOCAL_Q	1	X'00000001'
MQCQT_ALIAS_Q	2	X'00000002'
MQCQT_REMOTE_Q	3	X'00000003'
MQCQT_Q_MGR_ALIAS	4	X'00000004'

MQCRC_* (CICS information header Return Codes)

MQCRC_OK	0	X'00000000'
MQCRC_CICS_EXEC_ERROR	1	X'00000001'
MQCRC_MQ_API_ERROR	2	X'00000002'
MQCRC_BRIDGE_ERROR	3	X'00000003'
MQCRC_BRIDGE_ABEND	4	X'00000004'
MQCRC_APPLICATION_ABEND	5	X'00000005'
MQCRC_SECURITY_ERROR	6	X'00000006'
MQCRC_PROGRAM_NOT_AVAILABLE	7	X'00000007'
MQCRC_BRIDGE_TIMEOUT	8	X'00000008'
MQCRC_TRANSID_NOT_AVAILABLE	9	X'00000009'

MQCS_* (MQCBC constants Consumer state)

MQCS_NONE	0	X'00000000'
MQCS_SUSPENDED_TEMPORARY	1	X'00000001'
MQCS_SUSPENDED_USER_ACTION	2	X'00000002'
MQCS_SUSPENDED	3	X'00000003'
MQCS_STOPPED	4	X'00000004'

MQCSC_* (CICS information header Start Codes)

MQCSC_START	"Sbbb"	
MQCSC_STARTDATA	"SDbb"	
MQCSC_TERMINPUT	"TDbb"	
MQCSC_NONE	"bbbb"	

MQCSC_START_ARRAY	'S','b','b','b'	
MQCSC_STARTDATA_ARRAY	'S','D','b','b'	
MQCSC_TERMINPUT_ARRAY	'T','D','b','b'	
MQCSC_NONE_ARRAY	'b','b','b','b'	

MQCSP_* (Connection security parameters structure)

MQCSP_STRUC_ID	"CSPb"	
MQCSP_STRUC_ID_ARRAY	'C','S','P','b'	
MQCSP_VERSION_1		1 X'00000001'
MQCSP_CURRENT_VERSION		1 X'00000001'

MQCSP_* (Connection security parameters Authentication Types)

MQCSP_AUTH_NONE		0	X'00000000'
MQCSP_AUTH_USER_ID_AND_PWD		1	X'00000001'

MQCSRV_* (Command Server Options)

MQCSRV_CONVERT_NO		0	X'00000000'
MQCSRV_CONVERT_YES		1	X'00000001'
MQCSRV_DLQ_NO		0	X'00000000'
MQCSRV_DLQ_YES		1	X'00000001'

MQCT_* (Queue Manager Connection Tag)

MQCT_NONE	X'00...00'	(128 nulls)
MQCT_NONE_ARRAY	'\0','\0',...	(128 nulls)

MQCTES_* (CICS information header Task End Status)

MQCTES_NOSYNC		0	X'00000000'
MQCTES_COMMIT		256	X'00000100'
MQCTES_BACKOUT		4352	X'00001100'
MQCTES_ENDTASK		65536	X'00010000'

MQCTLO_* (MQCTL options structure)

MQCTLO_STRUC_ID	"CTLO"		
MQCTLO_STRUC_ID_ARRAY	'C','T','L','O'		
MQCTLO_VERSION_1		1	X'00000001'

MQCTLO_CURRENT_VERSION	1	X'00000001'
------------------------	---	-------------

MQCTLO_* (MQCTL options Consumer Control Options)

MQCTLO_NONE	0	X'00000000'
MQCTLO_THREAD_AFFINITY	1	X'00000001'
MQCTLO_FAIL_IF QUIESCING	8192	X'00002000'

MQCUOWC_* (CICS information header Unit-of-Work Controls)

MQCUOWC_ONLY	273	X'00000111'
MQCUOWC_CONTINUE	65536	X'00010000'
MQCUOWC_FIRST	17	X'00000011'
MQCUOWC_MIDDLE	16	X'00000010'
MQCUOWC_LAST	272	X'00000110'
MQCUOWC_COMMIT	256	X'00000100'
MQCUOWC_BACKOUT	4352	X'00001100'

MQCXP_* (Channel exit parameter structure)

MQCXP_STRUC_ID	"CXPb"	
MQCXP_STRUC_ID_ARRAY	'C','X','P','b'	
MQCXP_VERSION_1	1	X'00000001'
MQCXP_VERSION_2	2	X'00000002'
MQCXP_VERSION_3	3	X'00000003'
MQCXP_VERSION_4	4	X'00000004'
MQCXP_VERSION_5	5	X'00000005'
MQCXP_VERSION_6	6	X'00000006'
MQCXP_VERSION_7	7	X'00000007'
MQCXP_CURRENT_VERSION	7	X'00000007'

MQDC_* (Destination Class)

MQDC_MANAGED	1	X'00000001'
MQDC_PROVIDED	2	X'00000002'

MQDCC_* (Conversion Options)

MQDCC_DEFAULT_CONVERSION	1	X'00000001'
MQDCC_FILL_TARGET_BUFFER	2	X'00000002'
MQDCC_INT_DEFAULT_CONVERSION	4	X'00000004'

MQDCC_SOURCE_ENC_NATIVE	(value differs by platform or version)	
MQDCC_SOURCE_ENC_NORMAL	16	X'00000010'
MQDCC_SOURCE_ENC_REVERSED	32	X'00000020'
MQDCC_SOURCE_ENC_UNDEFINED	0	X'00000000'
MQDCC_TARGET_ENC_NATIVE	(value differs by platform or version)	
MQDCC_TARGET_ENC_NORMAL	256	X'00000100'
MQDCC_TARGET_ENC_REVERSED	512	X'00000200'
MQDCC_TARGET_ENC_UNDEFINED	0	X'00000000'
MQDCC_NONE	0	X'00000000'

MQDCC_* (Conversion Options Masks and Factors)

MQDCC_SOURCE_ENC_MASK	240	X'000000F0'
MQDCC_TARGET_ENC_MASK	3840	X'00000F00'
MQDCC_SOURCE_ENC_FACTOR	16	X'00000010'
MQDCC_TARGET_ENC_FACTOR	256	X'00000100'

MQDELO_* (Publish/Subscribe Delete Options)

MQDELO_NONE	0	X'00000000'
MQDELO_LOCAL	4	X'00000004'

MQDH_* (Distribution header structure)

MQDH_STRUC_ID	"DHbb"	
MQDH_STRUC_ID_ARRAY	'D','H','b','b'	
MQDH_VERSION_1	1	X'00000001'
MQDH_CURRENT_VERSION	1	X'00000001'

MQDHF_* (Distribution header Flags)

MQDHF_NEW_MSG_IDS	1	X'00000001'
MQDHF_NONE	0	X'00000000'

MQDISCONNECT_* (Command format Disconnect Types)

MQDISCONNECT_NORMAL	0	X'00000000'
MQDISCONNECT_IMPLICIT	1	X'00000001'
MQDISCONNECT_Q_MGR	2	X'00000002'

MQDL_* (Distribution Lists)

MQDL_SUPPORTED	1	X'00000001'
MQDL_NOT_SUPPORTED	0	X'00000000'

MQDLH_* (Dead-letter header structure)

MQDLH_STRUC_ID	"DLhb"	
MQDLH_STRUC_ID_ARRAY	'D','L','H','b'	
MQDLH_VERSION_1	1	X'00000001'
MQDLH_CURRENT_VERSION	1	X'00000001'

MQDLV_* (Persistent/Non-persistent Message Delivery)

MQDLV_AS_PARENT	0	X'00000000'
MQDLV_ALL	1	X'00000001'
MQDLV_ALL_DUR	2	X'00000002'
MQDLV_ALL_AVAIL	3	X'00000003'

MQDMHO_* (Delete message handle options structure)

MQDMHO_STRUC_ID	"DMHO"	
MQDMHO_STRUC_ID_ARRAY	'D','M','H','O'	
MQDMHO_VERSION_1	1	X'00000001'
MQDMHO_CURRENT_VERSION	1	X'00000001'

MQDMHO_* (Delete Message Handle Options)

MQDMHO_NONE	0	X'00000000'
-------------	---	-------------

MQDMPO_* (Delete message property options structure)

MQDMPO_STRUC_ID	"DMPO"	
MQDMPO_STRUC_ID_ARRAY	'D','M','P','O'	
MQDMPO_VERSION_1	1	X'00000001'
MQDMPO_CURRENT_VERSION	1	X'00000001'

MQDMPO_* (Delete Message Property Options)

MQDMPO_DEL_FIRST	0	X'00000000'
MQDMPO_DEL_PROP_UNDER_CURSOR	1	X'00000001'
MQDMPO_NONE	0	X'00000000'

MQDNSWLM_* (DNS WLM)

MQDNSWLM_NO	0	X'00000000'
MQDNSWLM_YES	1	X'00000001'

MQDT_* (Destination Types)

MQDT_APPL	1	X'00000001'
MQDT_BROKER	2	X'00000002'

MQDXP_* (Conversion exit parameter structure)

MQDXP_STRUC_ID	"DXPb"	
MQDXP_STRUC_ID_ARRAY	'D','X','P','b'	
MQDXP_VERSION_1	1	X'00000001'
MQDXP_CURRENT_VERSION	1	X'00000001'

MQEC_* (Signal Values)

MQEC_MSG_ARRIVED	2	X'00000002'
MQEC_WAIT_INTERVAL_EXPIRED	3	X'00000003'
MQEC_WAIT_CANCELED	4	X'00000004'
MQEC_Q_MGR QUIESCING	5	X'00000005'
MQEC_CONNECTION QUIESCING	6	X'00000006'

MQEI_* (Expiry)

MQEI_UNLIMITED	-1	X'FFFFFFFF'
----------------	----	-------------

MQENC_* (Encoding)

MQENC_NATIVE	(value differs by platform or version)	
--------------	--	--

MQENC_* (Encoding Masks)

MQENC_INTEGER_MASK	15	X'0000000F'
MQENC_DECIMAL_MASK	240	X'000000F0'
MQENC_FLOAT_MASK	3840	X'00000F00'
MQENC_RESERVED_MASK	-4096	X'FFFFFF00'

MQENC_* (Encodings for Binary Integers)

MQENC_INTEGER_UNDEFINED	0	X'00000000'
MQENC_INTEGER_NORMAL	1	X'00000001'
MQENC_INTEGER_REVERSED	2	X'00000002'

MQENC_* (Encodings for Packed Decimal Integers)

MQENC_DECIMAL_UNDEFINED	0	X'00000000'
MQENC_DECIMAL_NORMAL	16	X'00000010'
MQENC_DECIMAL_REVERSED	32	X'00000020'

MQENC_* (Encodings for Floating Point Numbers)

MQENC_FLOAT_UNDEFINED	0	X'00000000'
MQENC_FLOAT_IEEE_NORMAL	256	X'00000100'
MQENC_FLOAT_IEEE_REVERSED	512	X'00000200'
MQENC_FLOAT_S390	768	X'00000300'
MQENC_FLOAT_TNS	1024	X'00000400'

MQEPH_* (Embedded command format header structure)

MQEPH_STRUC_ID	"EPHb"	
MQEPH_STRUC_ID_ARRAY	'E','P','H','b'	
MQEPH_STRUC_LENGTH_FIXED	68	X'00000044'
MQEPH_VERSION_1	1	X'00000001'
MQEPH_CURRENT_VERSION	1	X'00000001'

MQEPH_* (Embedded command format header Flags)

MQEPH_NONE	0	X'00000000'
MQEPH_CCSDID_EMBEDDED	1	X'00000001'

MQET_* (Command format Escape Types)

MQET_MQSC	1	X'00000001'
-----------	---	-------------

MQEVO_* (Command format Event Origins)

MQEVO_OTHER	0	X'00000000'
MQEVO_CONSOLE	1	X'00000001'
MQEVO_INIT	2	X'00000002'

MQEVO_MSG	3	X'00000003'
MQEVO_MQSET	4	X'00000004'
MQEVO_INTERNAL	5	X'00000005'

MQEVR_* (Command format Event Recording)

MQEVR_DISABLED	0	X'00000000'
MQEVR_ENABLED	1	X'00000001'
MQEVR_EXCEPTION	2	X'00000002'
MQEVR_NO_DISPLAY	3	X'00000003'

MQEXPI_* (Expiration Scan Interval)

MQEXPI_OFF	0	X'00000000'
------------	---	-------------

MQFB_* (Feedback Values)

MQFB_NONE	0	X'00000000'
MQFB_SYSTEM_FIRST	1	X'00000001'
MQFB_QUIT	256	X'00000100'
MQFB_EXPIRATION	258	X'00000102'
MQFB_COA	259	X'00000103'
MQFB_COD	260	X'00000104'
MQFB_CHANNEL_COMPLETED	262	X'00000106'
MQFB_CHANNEL_FAIL_RETRY	263	X'00000107'
MQFB_CHANNEL_FAIL	264	X'00000108'
MQFB_APPL_CANNOT_BE_STARTED	265	X'00000109'
MQFB_TM_ERROR	266	X'0000010A'
MQFB_APPL_TYPE_ERROR	267	X'0000010B'
MQFB_STOPPED_BY_MSG_EXIT	268	X'0000010C'
MQFB_ACTIVITY	269	X'0000010D'
MQFB_XMIT_Q_MSG_ERROR	271	X'0000010F'
MQFB_PAN	275	X'00000113'
MQFB_NAN	276	X'00000114'
MQFB_STOPPED_BY_CHAD_EXIT	277	X'00000115'
MQFB_STOPPED_BY_PUBSUB_EXIT	279	X'00000117'
MQFB_NOT_A_REPOSITORY_MSG	280	X'00000118'
MQFB_BIND_OPEN_CLUSRCVR_DEL	281	X'00000119'
MQFB_MAX_ACTIVITIES	282	X'0000011A'
MQFB_NOT_FORWARDED	283	X'0000011B'
MQFB_NOT_DELIVERED	284	X'0000011C'
MQFB_UNSUPPORTED_FORWARDING	285	X'0000011D'

MQFB_UNSUPPORTED_DELIVERY	286	X'0000011E'
MQFB_DATA_LENGTH_ZERO	291	X'00000123'
MQFB_DATA_LENGTH_NEGATIVE	292	X'00000124'
MQFB_DATA_LENGTH_TOO_BIG	293	X'00000125'
MQFB_BUFFER_OVERFLOW	294	X'00000126'
MQFB_LENGTH_OFF_BY_ONE	295	X'00000127'
MQFB_IIH_ERROR	296	X'00000128'
MQFB_NOT_AUTHORIZED_FOR_IMS	298	X'0000012A'
MQFB_IMS_ERROR	300	X'0000012C'
MQFB_IMS_FIRST	301	X'0000012D'
MQFB_IMS_LAST	399	X'0000018F'
MQFB_CICS_INTERNAL_ERROR	401	X'00000191'
MQFB_CICS_NOT_AUTHORIZED	402	X'00000192'
MQFB_CICS_BRIDGE_FAILURE	403	X'00000193'
MQFB_CICS_CORREL_ID_ERROR	404	X'00000194'
MQFB_CICS_CCSID_ERROR	405	X'00000195'
MQFB_CICS_ENCODING_ERROR	406	X'00000196'
MQFB_CICS_CIH_ERROR	407	X'00000197'
MQFB_CICS_UOW_ERROR	408	X'00000198'
MQFB_CICS_COMMAREA_ERROR	409	X'00000199'
MQFB_CICS_APPL_NOT_STARTED	410	X'0000019A'
MQFB_CICS_APPL_ABENDED	411	X'0000019B'
MQFB_CICS_DLQ_ERROR	412	X'0000019C'
MQFB_CICS_UOW_BACKED_OUT	413	X'0000019D'
MQFB_PUBLICATIONS_ON_REQUEST	501	X'000001F5'
MQFB_SUBSCRIBER_IS_PUBLISHER	502	X'000001F6'
MQFB_MSG_SCOPE_MISMATCH	503	X'000001F7'
MQFB_SELECTOR_MISMATCH	504	X'000001F8'
MQFB_SYSTEM_LAST	65535	X'0000FFFF'
MQFB_APPL_FIRST	65536	X'00010000'
MQFB_APPL_LAST	99999999	X'3B9AC9FF'

MQFC_* (Command format Force Options)

MQFC_YES	1	X'00000001'
MQFC_NO	0	X'00000000'

MQFMT_* (Formats)

MQFMT_NONE	"bbbbbbbb"
MQFMT_ADMIN	"MQADMINb"
MQFMT_CHANNEL_COMPLETED	"MQCHCOMb"

MQFMT_CICS	"MQCICSbb"
MQFMT_COMMAND_1	"MQCMD1bb"
MQFMT_COMMAND_2	"MQCMD2bb"
MQFMT_DEAD_LETTER_HEADER	"MQDEADbb"
MQFMT_DIST_HEADER	"MQHDISTb"
MQFMT_EMBEDDED_PCF	"MQHEPCFb"
MQFMT_EVENT	"MQEVENTb"
MQFMT_IMS	"MQIMSbbb"
MQFMT_IMS_VAR_STRING	"MQIMSVSb"
MQFMT_MD_EXTENSION	"MQHMDEbb"
MQFMT_PCF	"MQPCFbbb"
MQFMT_REF_MSG_HEADER	"MQHREFbb"
MQFMT_RF_HEADER	"MQHRFbbb"
MQFMT_RF_HEADER_1	"MQHRFbbb"
MQFMT_RF_HEADER_2	"MQHRF2bb"
MQFMT_STRING	"MQSTRbbb"
MQFMT_TRIGGER	"MQTRIGbb"
MQFMT_WORK_INFO_HEADER	"MQHWIHbb"
MQFMT_XMIT_Q_HEADER	"MQXMITbb"
MQFMT_NONE_ARRAY	'b','b','b','b','b','b','b','b','b'
MQFMT_ADMIN_ARRAY	'M','Q','A','D','M','I','N','b'
MQFMT_CHANNEL_COMPLETED_ARRAY	'M','Q','C','H','C','O','M','b'
MQFMT_CICS_ARRAY	'M','Q','C','I','C','S','b','b'
MQFMT_COMMAND_1_ARRAY	'M','Q','C','M','D','1','b','b'
MQFMT_COMMAND_2_ARRAY	'M','Q','C','M','D','2','b','b'
MQFMT_DEAD_LETTER_HEADER_ARRAY	'M','Q','D','E','A','D','b','b'
MQFMT_DIST_HEADER_ARRAY	'M','Q','H','D','I','S','T','b'
MQFMT_EMBEDDED_PCF_ARRAY	'M','Q','H','E','P','C','F','b'
MQFMT_EVENT_ARRAY	'M','Q','E','V','E','N','T','b'
MQFMT_IMS_ARRAY	'M','Q','I','M','S','b','b','b'
MQFMT_IMS_VAR_STRING_ARRAY	'M','Q','I','M','S','V','S','b'
MQFMT_MD_EXTENSION_ARRAY	'M','Q','H','M','D','E','b','b'
MQFMT_PCF_ARRAY	'M','Q','P','C','F','b','b','b'
MQFMT_REF_MSG_HEADER_ARRAY	'M','Q','H','R','E','F','b','b'
MQFMT_RF_HEADER_ARRAY	'M','Q','H','R','F','b','b','b'
MQFMT_RF_HEADER_1_ARRAY	'M','Q','H','R','F','b','b','b'
MQFMT_RF_HEADER_2_ARRAY	'M','Q','H','R','F','2','b','b'
MQFMT_STRING_ARRAY	'M','Q','S','T','R','b','b','b'
MQFMT_TRIGGER_ARRAY	'M','Q','T','R','I','G','b','b'
MQFMT_WORK_INFO_HEADER_ARRAY	'M','Q','H','W','I','H','b','b'
MQFMT_XMIT_Q_HEADER_ARRAY	'M','Q','X','M','I','T','b','b'

MQGA_* (Group Attribute Selectors)

MQGA_FIRST	8001	X'00001F41'
MQGA_LAST	9000	X'00002328'

MQGACF_* (Command format Group Parameter Types)

MQGACF_FIRST	8001	X'00001F41'
MQGACF_COMMAND_CONTEXT	8001	X'00001F41'
MQGACF_COMMAND_DATA	8002	X'00001F42'
MQGACF_TRACE_ROUTE	8003	X'00001F43'
MQGACF_OPERATION	8004	X'00001F44'
MQGACF_ACTIVITY	8005	X'00001F45'
MQGACF_EMBEDDED_MQMD	8006	X'00001F46'
MQGACF_MESSAGE	8007	X'00001F47'
MQGACF_MQMD	8008	X'00001F48'
MQGACF_VALUE_NAMING	8009	X'00001F49'
MQGACF_Q_ACCOUNTING_DATA	8010	X'00001F4A'
MQGACF_Q_STATISTICS_DATA	8011	X'00001F4B'
MQGACF_CHL_STATISTICS_DATA	8012	X'00001F4C'
MQGACF_LAST_USED	8012	X'00001F4C'

MQGI_* (Group Identifier)

MQGI_NONE	X'00...00'	(24 nulls)
MQGI_NONE_ARRAY	'\0','\0',...	(24 nulls)

MQGMO_* (Get message options structure)

MQGMO_STRUC_ID	"GMOb"	
MQGMO_STRUC_ID_ARRAY	'G','M','O','b'	
MQGMO_VERSION_1	1	X'00000001'
MQGMO_VERSION_2	2	X'00000002'
MQGMO_VERSION_3	3	X'00000003'
MQGMO_VERSION_4	4	X'00000004'
MQGMO_CURRENT_VERSION	4	X'00000004'

MQGMO_* (Get Message Options)

MQGMO_WAIT	1	X'00000001'
MQGMO_NO_WAIT	0	X'00000000'
MQGMO_SET_SIGNAL	8	X'00000008'

MQGMO_FAIL_IF QUIESCING	8192	X'00002000'
MQGMO_SYNCPOINT	2	X'00000002'
MQGMO_SYNCPOINT_IF_PERSISTENT	4096	X'00001000'
MQGMO_NO_SYNCPOINT	4	X'00000004'
MQGMO_MARK_SKIP_BACKOUT	128	X'00000080'
MQGMO_BROWSE_FIRST	16	X'00000010'
MQGMO_BROWSE_NEXT	32	X'00000020'
MQGMO_BROWSE_MSG_UNDER_CURSOR	2048	X'00000800'
MQGMO_BROWSE_HANDLE	17825808	X'01100010'
MQGMO_BROWSE_CO_OP	18874384	X'01200010'
MQGMO_MSG_UNDER_CURSOR	256	X'00000100'
MQGMO_LOCK	512	X'00000200'
MQGMO_UNLOCK	1024	X'00000400'
MQGMO_ACCEPT_TRUNCATED_MSG	64	X'00000040'
MQGMO_CONVERT	16384	X'00004000'
MQGMO_LOGICAL_ORDER	32768	X'00008000'
MQGMO_COMPLETE_MSG	65536	X'00010000'
MQGMO_ALL_MSGS_AVAILABLE	131072	X'00020000'
MQGMO_ALL_SEGMENTS_AVAILABLE	262144	X'00040000'
MQGMO_MARK_BROWSE_HANDLE	1048576	X'00100000'
MQGMO_MARK_BROWSE_CO_OP	2097152	X'00200000'
MQGMO_UNMARK_BROWSE_CO_OP	4194304	X'00400000'
MQGMO_UNMARK_BROWSE_HANDLE	8388608	X'00800000'
MQGMO_UNMARKED_BROWSE_MSG	16777216	X'01000000'
MQGMO_PROPERTIES_FORCE_MQRFH2	33554432	X'02000000'
MQGMO_NO_PROPERTIES	67108864	X'04000000'
MQGMO_PROPERTIES_IN_HANDLE	134217728	X'08000000'
MQGMO_PROPERTIES_COMPATIBILITY	268435456	X'10000000'
MQGMO_PROPERTIES_AS_Q_DEF	0	X'00000000'
MQGMO_NONE	0	X'00000000'

MQGS_* (Group Status)

MQGS_NOT_IN_GROUP	'b'	
MQGS_MSG_IN_GROUP	'G'	
MQGS_LAST_MSG_IN_GROUP	'L'	

MQHA_* (Handle Selectors)

MQHA_FIRST	4001	X'00000FA1'
MQHA_BAG_HANDLE	4001	X'00000FA1'

MQHA_LAST_USED	4001	X'00000FA1'
MQHA_LAST	6000	X'00001770'

MQHB_* (Bag Handles)

MQHB_UNUSABLE_HBAG	-1	X'FFFFFFFF'
MQHB_NONE	-2	X'FFFFFFFE'

MQHC_* (Connection Handles)

MQHC_DEF_HCONN	0	X'00000000'
MQHC_UNUSABLE_HCONN	-1	X'FFFFFFFF'
MQHC_UNASSOCIATED_HCONN	-3	X'FFFFFFFD'

MQHM_* (Message handle)

MQHM_UNUSABLE_HMSG	-1	X'FFFFFFFF'
MQHM_NONE	0	X'00000000'

MQHO_* (Object Handle)

MQHO_UNUSABLE_HOBJ	-1	X'FFFFFFFF'
MQHO_NONE	0	X'00000000'

MQHSTATE_* (Command format Handle States)

MQHSTATE_INACTIVE	0	X'00000000'
MQHSTATE_ACTIVE	1	X'00000001'

MQIA_* (Integer Attribute Selectors)

MQIA_ACCOUNTING_CONN_OVERRIDE	136	X'00000088'
MQIA_ACCOUNTING_INTERVAL	135	X'00000087'
MQIA_ACCOUNTING_MQI	133	X'00000085'
MQIA_ACCOUNTING_Q	134	X'00000086'
MQIA_ACTIVE_CHANNELS	100	X'00000064'
MQIA_ACTIVITY_RECORDING	138	X'0000008A'
MQIA_ADOPTNEWMCA_CHECK	102	X'00000066'
MQIA_ADOPTNEWMCA_TYPE	103	X'00000067'
MQIA_ADOPTNEWMCA_INTERVAL	104	X'00000068'
MQIA_APPL_TYPE	1	X'00000001'
MQIA_ARCHIVE	60	X'0000003C'

MQIA_AUTH_INFO_TYPE	66	X'00000042'
MQIA_AUTHORITY_EVENT	47	X'0000002F'
MQIA_AUTO_REORG_INTERVAL	174	X'000000AE'
MQIA_AUTO_REORGANIZATION	173	X'000000AD'
MQIA_BACKOUT_THRESHOLD	22	X'00000016'
MQIA_BASE_TYPE	193	X'000000C1'
MQIA_BATCH_INTERFACE_AUTO	86	X'00000056'
MQIA_BRIDGE_EVENT	74	X'0000004A'
MQIA_CF_LEVEL	70	X'00000046'
MQIA_CF_RECOVER	71	X'00000047'
MQIA_CHANNEL_AUTO_DEF	55	X'00000037'
MQIA_CHANNEL_AUTO_DEF_EVENT	56	X'00000038'
MQIA_CHANNEL_EVENT	73	X'00000049'
MQIA_CHINIT_ADAPTERS	101	X'00000065'
MQIA_CHINIT_CONTROL	119	X'00000077'
MQIA_CHINIT_DISPATCHERS	105	X'00000069'
MQIA_CHINIT_TRACE_AUTO_START	117	X'00000075'
MQIA_CHINIT_TRACE_TABLE_SIZE	118	X'00000076'
MQIA_CLUSTER_Q_TYPE	59	X'0000003B'
MQIA_CLUSTER_WORKLOAD_LENGTH	58	X'0000003A'
MQIA_CLWL_MRU_CHANNELS	97	X'00000061'
MQIA_CLWL_Q_RANK	95	X'0000005F'
MQIA_CLWL_Q_PRIORITY	96	X'00000060'
MQIA_CLWL_USEQ	98	X'00000062'
MQIA_CMD_SERVER_AUTO	87	X'00000057'
MQIA_CMD_SERVER_CONTROL	120	X'00000078'
MQIA_CMD_SERVER_CONVERT_MSG	88	X'00000058'
MQIA_CMD_SERVER_DLQ_MSG	89	X'00000059'
MQIA_CODED_CHAR_SET_ID	2	X'00000002'
MQIA_COMMAND_EVENT	99	X'00000063'
MQIA_COMMAND_LEVEL	31	X'0000001F'
MQIA_CONFIGURATION_EVENT	51	X'00000033'
MQIA_CPI_LEVEL	27	X'0000001B'
MQIA_CURRENT_Q_DEPTH	3	X'00000003'
MQIA_DEF_BIND	61	X'0000003D'
MQIA_DEF_INPUT_OPEN_OPTION	4	X'00000004'
MQIA_DEF_PERSISTENCE	5	X'00000005'
MQIA_DEF_PRIORITY	6	X'00000006'
MQIA_DEF_PUT_RESPONSE_TYPE	184	X'000000B8'
MQIA_DEF_READ_AHEAD	188	X'000000BC'
MQIA_DEFINITION_TYPE	7	X'00000007'
MQIA_DIST_LISTS	34	X'00000022'

MQIA_DNS_WLM	106	X'0000006A'
MQIA_DURABLE_SUB	175	X'000000AF'
MQIA_EXPIRY_INTERVAL	39	X'00000027'
MQIA_FIRST	1	X'00000001'
MQIA_HARDEN_GET_BACKOUT	8	X'00000008'
MQIA_HIGH_Q_DEPTH	36	X'00000024'
MQIA_IGQ_PUT_AUTHORITY	65	X'00000041'
MQIA_INDEX_TYPE	57	X'00000039'
MQIA_INHIBIT_EVENT	48	X'00000030'
MQIA_INHIBIT_GET	9	X'00000009'
MQIA_INHIBIT_PUB	181	X'000000B5'
MQIA_INHIBIT_PUT	10	X'0000000A'
MQIA_INHIBIT_SUB	182	X'000000B6'
MQIA_INTRA_GROUP_QUEUEING	64	X'00000040'
MQIA_IP_ADDRESS_VERSION	93	X'0000005D'
MQIA_LAST	2000	X'000007D0'
MQIA_LAST_USED	219	X'000000DB'
MQIA_LISTENER_PORT_NUMBER	85	X'00000055'
MQIA_LISTENER_TIMER	107	X'0000006B'
MQIA_LOGGER_EVENT	94	X'0000005E'
MQIA_LU62_CHANNELS	108	X'0000006C'
MQIA_LOCAL_EVENT	49	X'00000031'
MQIA_MSG_MARK_BROWSE_INTERVAL	68	X'00000044'
MQIA_MAX_CHANNELS	109	X'0000006D'
MQIA_MAX_CLIENTS	172	X'000000AC'
MQIA_MAX_GLOBAL_LOCKS	83	X'00000053'
MQIA_MAX_HANDLES	11	X'0000000B'
MQIA_MAX_LOCAL_LOCKS	84	X'00000054'
MQIA_MAX_MSG_LENGTH	13	X'0000000D'
MQIA_MAX_OPEN_Q	80	X'00000050'
MQIA_MAX_PRIORITY	14	X'0000000E'
MQIA_MAX_PROPERTIES_LENGTH	192	X'000000C0'
MQIA_MAX_Q_DEPTH	15	X'0000000F'
MQIA_MAX_Q_TRIGGERS	90	X'0000005A'
MQIA_MAX_RECOVERY_TASKS	171	X'000000AB'
MQIA_MAX_UNCOMMITTED_MSGS	33	X'00000021'
MQIA_MONITOR_INTERVAL	81	X'00000051'
MQIA_MONITORING_AUTO_CLUSSDR	124	X'0000007C'
MQIA_MONITORING_CHANNEL	122	X'0000007A'
MQIA_MONITORING_Q	123	X'0000007B'
MQIA_MSG_DELIVERY_SEQUENCE	16	X'00000010'
MQIA_MSG_DEQ_COUNT	38	X'00000026'

MQIA_MSG_ENQ_COUNT	37	X'00000025'
MQIA_NAME_COUNT	19	X'00000013'
MQIA_NAMELIST_TYPE	72	X'00000048'
MQIA_NPM_CLASS	78	X'0000004E'
MQIA_NPM_DELIVERY	196	X'000000C4'
MQIA_OPEN_INPUT_COUNT	17	X'00000011'
MQIA_OPEN_OUTPUT_COUNT	18	X'00000012'
MQIA_OUTBOUND_PORT_MAX	140	X'0000008C'
MQIA_OUTBOUND_PORT_MIN	110	X'0000006E'
MQIA_PAGESET_ID	62	X'0000003E'
MQIA_PERFORMANCE_EVENT	53	X'00000035'
MQIA_PLATFORM	32	X'00000020'
MQIA_PM_DELIVERY	195	X'000000C3'
MQIA_PROPERTY_CONTROL	190	X'000000BE'
MQIA_PROXY_SUB	199	X'000000C7'
MQIA_PUB_COUNT	215	X'000000D7'
MQIA_PUB_SCOPE	219	X'000000DB'
MQIA_PUBSUB_MAXMSG_RETRY_COUNT	206	X'000000CE'
MQIA_PUBSUB_MODE	187	X'000000BB'
MQIA_PUBSUB_NP_MSG	203	X'000000CB'
MQIA_PUBSUB_NP_RESP	205	X'000000CD'
MQIA_PUBSUB_SYNC_PT	207	X'000000CF'
MQIA_Q_DEPTH_HIGH_EVENT	43	X'0000002B'
MQIA_Q_DEPTH_HIGH_LIMIT	40	X'00000028'
MQIA_Q_DEPTH_LOW_EVENT	44	X'0000002C'
MQIA_Q_DEPTH_LOW_LIMIT	41	X'00000029'
MQIA_Q_DEPTH_MAX_EVENT	42	X'0000002A'
MQIA_Q_SERVICE_INTERVAL	54	X'00000036'
MQIA_Q_SERVICE_INTERVAL_EVENT	46	X'0000002E'
MQIA_Q_TYPE	20	X'00000014'
MQIA_Q_USERS	82	X'00000052'
MQIA_QMOPT_CONS_COMMS_MSGS	155	X'0000009B'
MQIA_QMOPT_CONS_CRITICAL_MSGS	154	X'0000009A'
MQIA_QMOPT_CONS_ERROR_MSGS	153	X'00000099'
MQIA_QMOPT_CONS_INFO_MSGS	151	X'00000097'
MQIA_QMOPT_CONS_REORG_MSGS	156	X'0000009C'
MQIA_QMOPT_CONS_SYSTEM_MSGS	157	X'0000009D'
MQIA_QMOPT_CONS_WARNING_MSGS	152	X'00000098'
MQIA_QMOPT_CSMT_ON_ERROR	150	X'00000096'
MQIA_QMOPT_INTERNAL_DUMP	170	X'000000AA'
MQIA_QMOPT_LOG_COMMS_MSGS	162	X'000000A2'
MQIA_QMOPT_LOG_CRITICAL_MSGS	161	X'000000A1'

MQIA_QMOPT_LOG_ERROR_MSGS	160	X'000000A0'
MQIA_QMOPT_LOG_INFO_MSGS	158	X'0000009E'
MQIA_QMOPT_LOG_REORG_MSGS	163	X'000000A3'
MQIA_QMOPT_LOG_SYSTEM_MSGS	164	X'000000A4'
MQIA_QMOPT_LOG_WARNING_MSGS	159	X'0000009F'
MQIA_QMOPT_TRACE_COMMS	166	X'000000A6'
MQIA_QMOPT_TRACE_CONVERSION	168	X'000000A8'
MQIA_QMOPT_TRACE_REORG	167	X'000000A7'
MQIA_QMOPT_TRACE_MQI_CALLS	165	X'000000A5'
MQIA_QMOPT_TRACE_SYSTEM	169	X'000000A9'
MQIA_QSG_DISP	63	X'0000003F'
MQIA_READ_AHEAD	189	X'000000BD'
MQIA_RECEIVE_TIMEOUT	111	X'0000006F'
MQIA_RECEIVE_TIMEOUT_MIN	113	X'00000071'
MQIA_RECEIVE_TIMEOUT_TYPE	112	X'00000070'
MQIA_REMOTE_EVENT	50	X'00000032'
MQIA_RETENTION_INTERVAL	21	X'00000015'
MQIA_SCOPE	45	X'0000002D'
MQIA_SECURITY_CASE	141	X'0000008D'
MQIA_SERVICE_CONTROL	139	X'0000008B'
MQIA_SERVICE_TYPE	121	X'00000079'
MQIA_SHAREABILITY	23	X'00000017'
MQIA_SHARED_Q_Q_MGR_NAME	77	X'0000004D'
MQIA_SSL_EVENT	75	X'0000004B'
MQIA_SSL_FIPS_REQUIRED	92	X'0000005C'
MQIA_SSL_RESET_COUNT	76	X'0000004C'
MQIA_SSL_TASKS	69	X'00000045'
MQIA_START_STOP_EVENT	52	X'00000034'
MQIA_STATISTICS_CHANNEL	129	X'00000081'
MQIA_STATISTICS_AUTO_CLUSSDR	130	X'00000082'
MQIA_STATISTICS_INTERVAL	131	X'00000083'
MQIA_STATISTICS_MQI	127	X'0000007F'
MQIA_STATISTICS_Q	128	X'00000080'
MQIA_SUB_COUNT	204	X'000000CC'
MQIA_SUB_SCOPE	218	X'000000DA'
MQIA_SYNCPOINT	30	X'0000001E'
MQIA_TCP_CHANNELS	114	X'00000072'
MQIA_TCP_KEEP_ALIVE	115	X'00000073'
MQIA_TCP_STACK_TYPE	116	X'00000074'
MQIA_TIME_SINCE_RESET	35	X'00000023'
MQIA_TOPIC_DEF_PERSISTENCE	185	X'000000B9'
MQIA_TOPIC_TYPE	208	X'000000D0'

MQIA_TRACE_ROUTE_RECORDING	137	X'00000089'
MQIA_TREE_LIFE_TIME	183	X'000000B7'
MQIA_TRIGGER_CONTROL	24	X'00000018'
MQIA_TRIGGER_DEPTH	29	X'0000001D'
MQIA_TRIGGER_INTERVAL	25	X'00000019'
MQIA_TRIGGER_MSG_PRIORITY	26	X'0000001A'
MQIA_TRIGGER_TYPE	28	X'0000001C'
MQIA_TRIGGER_RESTART	91	X'0000005B'
MQIA_USAGE	12	X'0000000C'
MQIA_USER_LIST	2000	X'000007D0'
MQIA_WILDCARD_OPERATION	216	X'000000D8'

MQIACF_* (Command format Integer Parameter Types)

MQIACF_FIRST	1001	X'000003E9'
MQIACF_Q_MGR_ATTRS	1001	X'000003E9'
MQIACF_Q_ATTRS	1002	X'000003EA'
MQIACF_PROCESS_ATTRS	1003	X'000003EB'
MQIACF_NAMELIST_ATTRS	1004	X'000003EC'
MQIACF_FORCE	1005	X'000003ED'
MQIACF_REPLACE	1006	X'000003EE'
MQIACF_PURGE	1007	X'000003EF'
MQIACF_QUIESCE	1008	X'000003F0'
MQIACF_MODE	1008	X'000003F0'
MQIACF_ALL	1009	X'000003F1'
MQIACF_EVENT_APPL_TYPE	1010	X'000003F2'
MQIACF_EVENT_ORIGIN	1011	X'000003F3'
MQIACF_PARAMETER_ID	1012	X'000003F4'
MQIACF_ERROR_ID	1013	X'000003F5'
MQIACF_ERROR_IDENTIFIER	1013	X'000003F5'
MQIACF_SELECTOR	1014	X'000003F6'
MQIACF_CHANNEL_ATTRS	1015	X'000003F7'
MQIACF_OBJECT_TYPE	1016	X'000003F8'
MQIACF_ESCAPE_TYPE	1017	X'000003F9'
MQIACF_ERROR_OFFSET	1018	X'000003FA'
MQIACF_AUTH_INFO_ATTRS	1019	X'000003FB'
MQIACF_REASON_QUALIFIER	1020	X'000003FC'
MQIACF_COMMAND	1021	X'000003FD'
MQIACF_OPEN_OPTIONS	1022	X'000003FE'
MQIACF_OPEN_TYPE	1023	X'000003FF'
MQIACF_PROCESS_ID	1024	X'00000400'
MQIACF_THREAD_ID	1025	X'00000401'

MQIACF_Q_STATUS_ATTRS	1026	X'00000402'
MQIACF_UNCOMMITTED_MSGS	1027	X'00000403'
MQIACF_HANDLE_STATE	1028	X'00000404'
MQIACF_AUX_ERROR_DATA_INT_1	1070	X'0000042E'
MQIACF_AUX_ERROR_DATA_INT_2	1071	X'0000042F'
MQIACF_CONV_REASON_CODE	1072	X'00000430'
MQIACF_BRIDGE_TYPE	1073	X'00000431'
MQIACF_INQUIRY	1074	X'00000432'
MQIACF_WAIT_INTERVAL	1075	X'00000433'
MQIACF_OPTIONS	1076	X'00000434'
MQIACF_BROKER_OPTIONS	1077	X'00000435'
MQIACF_REFRESH_TYPE	1078	X'00000436'
MQIACF_SEQUENCE_NUMBER	1079	X'00000437'
MQIACF_INTEGER_DATA	1080	X'00000438'
MQIACF_REGISTRATION_OPTIONS	1081	X'00000439'
MQIACF_PUBLICATION_OPTIONS	1082	X'0000043A'
MQIACF_CLUSTER_INFO	1083	X'0000043B'
MQIACF_Q_MGR_DEFINITION_TYPE	1084	X'0000043C'
MQIACF_Q_MGR_TYPE	1085	X'0000043D'
MQIACF_ACTION	1086	X'0000043E'
MQIACF_SUSPEND	1087	X'0000043F'
MQIACF_BROKER_COUNT	1088	X'00000440'
MQIACF_APPL_COUNT	1089	X'00000441'
MQIACF_ANONYMOUS_COUNT	1090	X'00000442'
MQIACF_REG_REG_OPTIONS	1091	X'00000443'
MQIACF_DELETE_OPTIONS	1092	X'00000444'
MQIACF_CLUSTER_Q_MGR_ATTRS	1093	X'00000445'
MQIACF_REFRESH_INTERVAL	1094	X'00000446'
MQIACF_REFRESH_REPOSITORY	1095	X'00000447'
MQIACF_REMOVE_QUEUES	1096	X'00000448'
MQIACF_OPEN_INPUT_TYPE	1098	X'0000044A'
MQIACF_OPEN_OUTPUT	1099	X'0000044B'
MQIACF_OPEN_SET	1100	X'0000044C'
MQIACF_OPEN_INQUIRE	1101	X'0000044D'
MQIACF_OPEN_BROWSE	1102	X'0000044E'
MQIACF_Q_STATUS_TYPE	1103	X'0000044F'
MQIACF_Q_HANDLE	1104	X'00000450'
MQIACF_Q_STATUS	1105	X'00000451'
MQIACF_SECURITY_TYPE	1106	X'00000452'
MQIACF_CONNECTION_ATTRS	1107	X'00000453'
MQIACF_CONNECT_OPTIONS	1108	X'00000454'
MQIACF_CONN_INFO_TYPE	1110	X'00000456'

MQIACF_CONN_INFO_CONN	1111	X'00000457'
MQIACF_CONN_INFO_HANDLE	1112	X'00000458'
MQIACF_CONN_INFO_ALL	1113	X'00000459'
MQIACF_AUTH_PROFILE_ATTRS	1114	X'0000045A'
MQIACF_AUTHORIZATION_LIST	1115	X'0000045B'
MQIACF_AUTH_ADD_AUTHS	1116	X'0000045C'
MQIACF_AUTH_REMOVE_AUTHS	1117	X'0000045D'
MQIACF_ENTITY_TYPE	1118	X'0000045E'
MQIACF_COMMAND_INFO	1120	X'00000460'
MQIACF_CMDSCOPE_Q_MGR_COUNT	1121	X'00000461'
MQIACF_Q_MGR_SYSTEM	1122	X'00000462'
MQIACF_Q_MGR_EVENT	1123	X'00000463'
MQIACF_Q_MGR_DQM	1124	X'00000464'
MQIACF_Q_MGR_CLUSTER	1125	X'00000465'
MQIACF_QSG_DISPS	1126	X'00000466'
MQIACF_UOW_STATE	1128	X'00000468'
MQIACF_SECURITY_ITEM	1129	X'00000469'
MQIACF_CF_STRUC_STATUS	1130	X'0000046A'
MQIACF_UOW_TYPE	1132	X'0000046C'
MQIACF_CF_STRUC_ATTRS	1133	X'0000046D'
MQIACF_EXCLUDE_INTERVAL	1134	X'0000046E'
MQIACF_CF_STATUS_TYPE	1135	X'0000046F'
MQIACF_CF_STATUS_SUMMARY	1136	X'00000470'
MQIACF_CF_STATUS_CONNECT	1137	X'00000471'
MQIACF_CF_STATUS_BACKUP	1138	X'00000472'
MQIACF_CF_STRUC_TYPE	1139	X'00000473'
MQIACF_CF_STRUC_SIZE_MAX	1140	X'00000474'
MQIACF_CF_STRUC_SIZE_USED	1141	X'00000475'
MQIACF_CF_STRUC_ENTRIES_MAX	1142	X'00000476'
MQIACF_CF_STRUC_ENTRIES_USED	1143	X'00000477'
MQIACF_CF_STRUC_BACKUP_SIZE	1144	X'00000478'
MQIACF_MOVE_TYPE	1145	X'00000479'
MQIACF_MOVE_TYPE_MOVE	1146	X'0000047A'
MQIACF_MOVE_TYPE_ADD	1147	X'0000047B'
MQIACF_Q_MGR_NUMBER	1148	X'0000047C'
MQIACF_Q_MGR_STATUS	1149	X'0000047D'
MQIACF_DB2_CONN_STATUS	1150	X'0000047E'
MQIACF_SECURITY_ATTRS	1151	X'0000047F'
MQIACF_SECURITY_TIMEOUT	1152	X'00000480'
MQIACF_SECURITY_INTERVAL	1153	X'00000481'
MQIACF_SECURITY_SWITCH	1154	X'00000482'
MQIACF_SECURITY_SETTING	1155	X'00000483'

MQIACF_STORAGE_CLASS_ATTRS	1156	X'00000484'
MQIACF_USAGE_TYPE	1157	X'00000485'
MQIACF_BUFFER_POOL_ID	1158	X'00000486'
MQIACF_USAGE_TOTAL_PAGES	1159	X'00000487'
MQIACF_USAGE_UNUSED_PAGES	1160	X'00000488'
MQIACF_USAGE_PERSIST_PAGES	1161	X'00000489'
MQIACF_USAGE_NONPERSIST_PAGES	1162	X'0000048A'
MQIACF_USAGE_RESTART_EXTENTS	1163	X'0000048B'
MQIACF_USAGE_EXPAND_COUNT	1164	X'0000048C'
MQIACF_PAGESET_STATUS	1165	X'0000048D'
MQIACF_USAGE_TOTAL_BUFFERS	1166	X'0000048E'
MQIACF_USAGE_DATA_SET_TYPE	1167	X'0000048F'
MQIACF_USAGE_PAGESET	1168	X'00000490'
MQIACF_USAGE_DATA_SET	1169	X'00000491'
MQIACF_USAGE_BUFFER_POOL	1170	X'00000492'
MQIACF_MOVE_COUNT	1171	X'00000493'
MQIACF_EXPIRY_Q_COUNT	1172	X'00000494'
MQIACF_CONFIGURATION_OBJECTS	1173	X'00000495'
MQIACF_CONFIGURATION_EVENTS	1174	X'00000496'
MQIACF_SYSP_TYPE	1175	X'00000497'
MQIACF_SYSP_DEALLOC_INTERVAL	1176	X'00000498'
MQIACF_SYSP_MAX_ARCHIVE	1177	X'00000499'
MQIACF_SYSP_MAX_READ_TAPES	1178	X'0000049A'
MQIACF_SYSP_IN_BUFFER_SIZE	1179	X'0000049B'
MQIACF_SYSP_OUT_BUFFER_SIZE	1180	X'0000049C'
MQIACF_SYSP_OUT_BUFFER_COUNT	1181	X'0000049D'
MQIACF_SYSP_ARCHIVE	1182	X'0000049E'
MQIACF_SYSP_DUAL_ACTIVE	1183	X'0000049F'
MQIACF_SYSP_DUAL_ARCHIVE	1184	X'000004A0'
MQIACF_SYSP_DUAL_BSDS	1185	X'000004A1'
MQIACF_SYSP_MAX_CONNS	1186	X'000004A2'
MQIACF_SYSP_MAX_CONNS_FORE	1187	X'000004A3'
MQIACF_SYSP_MAX_CONNS_BACK	1188	X'000004A4'
MQIACF_SYSP_EXIT_INTERVAL	1189	X'000004A5'
MQIACF_SYSP_EXIT_TASKS	1190	X'000004A6'
MQIACF_SYSP_CHKPOINT_COUNT	1191	X'000004A7'
MQIACF_SYSP_OTMA_INTERVAL	1192	X'000004A8'
MQIACF_SYSP_Q_INDEX_DEFER	1193	X'000004A9'
MQIACF_SYSP_DB2_TASKS	1194	X'000004AA'
MQIACF_SYSP_RESLEVEL_AUDIT	1195	X'000004AB'
MQIACF_SYSP_ROUTING_CODE	1196	X'000004AC'
MQIACF_SYSP_SMF_ACCOUNTING	1197	X'000004AD'

MQIACF_SYSP_SMF_STATS	1198	X'000004AE'
MQIACF_SYSP_SMF_INTERVAL	1199	X'000004AF'
MQIACF_SYSP_TRACE_CLASS	1200	X'000004B0'
MQIACF_SYSP_TRACE_SIZE	1201	X'000004B1'
MQIACF_SYSP_WLM_INTERVAL	1202	X'000004B2'
MQIACF_SYSP_ALLOC_UNIT	1203	X'000004B3'
MQIACF_SYSP_ARCHIVE_RETAIN	1204	X'000004B4'
MQIACF_SYSP_ARCHIVE_WTOR	1205	X'000004B5'
MQIACF_SYSP_BLOCK_SIZE	1206	X'000004B6'
MQIACF_SYSP_CATALOG	1207	X'000004B7'
MQIACF_SYSP_COMPACT	1208	X'000004B8'
MQIACF_SYSP_ALLOC_PRIMARY	1209	X'000004B9'
MQIACF_SYSP_ALLOC_SECONDARY	1210	X'000004BA'
MQIACF_SYSP_PROTECT	1211	X'000004BB'
MQIACF_SYSP QUIESCE_INTERVAL	1212	X'000004BC'
MQIACF_SYSP_TIMESTAMP	1213	X'000004BD'
MQIACF_SYSP_UNIT_ADDRESS	1214	X'000004BE'
MQIACF_SYSP_UNIT_STATUS	1215	X'000004BF'
MQIACF_SYSP_LOG_COPY	1216	X'000004C0'
MQIACF_SYSP_LOG_USED	1217	X'000004C1'
MQIACF_SYSP_LOG_SUSPEND	1218	X'000004C2'
MQIACF_SYSP_OFFLOAD_STATUS	1219	X'000004C3'
MQIACF_SYSP_TOTAL_LOGS	1220	X'000004C4'
MQIACF_SYSP_FULL_LOGS	1221	X'000004C5'
MQIACF_LISTENER_ATTRS	1222	X'000004C6'
MQIACF_LISTENER_STATUS_ATTRS	1223	X'000004C7'
MQIACF_SERVICE_ATTRS	1224	X'000004C8'
MQIACF_SERVICE_STATUS_ATTRS	1225	X'000004C9'
MQIACF_Q_TIME_INDICATOR	1226	X'000004CA'
MQIACF_OLDEST_MSG_AGE	1227	X'000004CB'
MQIACF_AUTH_OPTIONS	1228	X'000004CC'
MQIACF_Q_MGR_STATUS_ATTRS	1229	X'000004CD'
MQIACF_CONNECTION_COUNT	1230	X'000004CE'
MQIACF_Q_MGR_FACILITY	1231	X'000004CF'
MQIACF_CHINIT_STATUS	1232	X'000004D0'
MQIACF_CMD_SERVER_STATUS	1233	X'000004D1'
MQIACF_ROUTE_DETAIL	1234	X'000004D2'
MQIACF_RECORDED_ACTIVITIES	1235	X'000004D3'
MQIACF_MAX_ACTIVITIES	1236	X'000004D4'
MQIACF_DISCONTINUITY_COUNT	1237	X'000004D5'
MQIACF_ROUTE_ACCUMULATION	1238	X'000004D6'
MQIACF_ROUTE_DELIVERY	1239	X'000004D7'

MQIACF_OPERATION_TYPE	1240	X'000004D8'
MQIACF_BACKOUT_COUNT	1241	X'000004D9'
MQIACF_COMP_CODE	1242	X'000004DA'
MQIACF_ENCODING	1243	X'000004DB'
MQIACF_EXPIRY	1244	X'000004DC'
MQIACF_FEEDBACK	1245	X'000004DD'
MQIACF_MSG_FLAGS	1247	X'000004DF'
MQIACF_MSG_LENGTH	1248	X'000004E0'
MQIACF_MSG_TYPE	1249	X'000004E1'
MQIACF_OFFSET	1250	X'000004E2'
MQIACF_ORIGINAL_LENGTH	1251	X'000004E3'
MQIACF_PERSISTENCE	1252	X'000004E4'
MQIACF_PRIORITY	1253	X'000004E5'
MQIACF_REASON_CODE	1254	X'000004E6'
MQIACF_REPORT	1255	X'000004E7'
MQIACF_VERSION	1256	X'000004E8'
MQIACF_UNRECORDED_ACTIVITIES	1257	X'000004E9'
MQIACF_MONITORING	1258	X'000004EA'
MQIACF_ROUTE_FORWARDING	1259	X'000004EB'
MQIACF_SERVICE_STATUS	1260	X'000004EC'
MQIACF_Q_TYPES	1261	X'000004ED'
MQIACF_USER_ID_SUPPORT	1262	X'000004EE'
MQIACF_INTERFACE_VERSION	1263	X'000004EF'
MQIACF_AUTH_SERVICE_ATTRS	1264	X'000004F0'
MQIACF_USAGE_EXPAND_TYPE	1265	X'000004F1'
MQIACF_SYSP_CLUSTER_CACHE	1266	X'000004F2'
MQIACF_SYSP_DB2_BLOB_TASKS	1267	X'000004F3'
MQIACF_SYSP_WLM_INT_UNITS	1268	X'000004F4'
MQIACF_TOPIC_ATTRS	1269	X'000004F5'
MQIACF_PUBSUB_PROPERTIES	1271	X'000004F7'
MQIACF_DESTINATION_CLASS	1273	X'000004F9'
MQIACF_DURABLE_SUBSCRIPTION	1274	X'000004FA'
MQIACF_SUBSCRIPTION_SCOPE	1275	X'000004FB'
MQIACF_VARIABLE_USER_ID	1277	X'000004FD'
MQIACF_REQUEST_ONLY	1280	X'00000500'
MQIACF_PUB_PRIORITY	1283	X'00000503'
MQIACF_SUB_ATTRS	1287	X'00000507'
MQIACF_WILDCARD_SCHEMA	1288	X'00000508'
MQIACF_SUB_TYPE	1289	X'00000509'
MQIACF_MESSAGE_COUNT	1290	X'0000050A'
MQIACF_Q_MGR_PUBSUB	1291	X'0000050B'
MQIACF_Q_MGR_VERSION	1292	X'0000050C'

MQIACF_SUB_STATUS_ATTRS	1294	X'0000050E'
MQIACF_TOPIC_STATUS	1295	X'0000050F'
MQIACF_TOPIC_SUB	1296	X'00000510'
MQIACF_TOPIC_PUB	1297	X'00000511'
MQIACF_RETAINED_PUBLICATION	1300	X'00000514'
MQIACF_TOPIC_STATUS_ATTRS	1301	X'00000515'
MQIACF_TOPIC_STATUS_TYPE	1302	X'00000516'
MQIACF_SUB_OPTIONS	1303	X'00000517'
MQIACF_PUBLISH_COUNT	1304	X'00000518'
MQIACF_CLEAR_TYPE	1305	X'00000519'
MQIACF_CLEAR_SCOPE	1306	X'0000051A'
MQIACF_SUB_LEVEL	1307	X'0000051B'
MQIACF_ASYNC_STATE	1308	X'0000051C'
MQIACF_SUB_SUMMARY	1309	X'0000051D'
MQIACF_OBSOLETE_MSGS	1310	X'0000051E'
MQIACF_PUBSUB_STATUS	1311	X'0000051F'
MQIACF_PS_STATUS_TYPE	1314	X'00000522'
MQIACF_PUBSUB_STATUS_ATTRS	1318	X'00000526'
MQIACF_LAST_USED	1318	X'00000526'

MQIACH_* (Command format Integer Channel Types)

MQIACH_FIRST	1501	X'000005DD'
MQIACH_XMIT_PROTOCOL_TYPE	1501	X'000005DD'
MQIACH_BATCH_SIZE	1502	X'000005DE'
MQIACH_DISC_INTERVAL	1503	X'000005DF'
MQIACH_SHORT_TIMER	1504	X'000005E0'
MQIACH_SHORT_RETRY	1505	X'000005E1'
MQIACH_LONG_TIMER	1506	X'000005E2'
MQIACH_LONG_RETRY	1507	X'000005E3'
MQIACH_PUT_AUTHORITY	1508	X'000005E4'
MQIACH_SEQUENCE_NUMBER_WRAP	1509	X'000005E5'
MQIACH_MAX_MSG_LENGTH	1510	X'000005E6'
MQIACH_CHANNEL_TYPE	1511	X'000005E7'
MQIACH_DATA_COUNT	1512	X'000005E8'
MQIACH_NAME_COUNT	1513	X'000005E9'
MQIACH_MSG_SEQUENCE_NUMBER	1514	X'000005EA'
MQIACH_DATA_CONVERSION	1515	X'000005EB'
MQIACH_IN_DOUBT	1516	X'000005EC'
MQIACH_MCA_TYPE	1517	X'000005ED'
MQIACH_SESSION_COUNT	1518	X'000005EE'
MQIACH_ADAPTER	1519	X'000005EF'

MQIACH_COMMAND_COUNT	1520	X'000005F0'
MQIACH_SOCKET	1521	X'000005F1'
MQIACH_PORT	1522	X'000005F2'
MQIACH_CHANNEL_INSTANCE_TYPE	1523	X'000005F3'
MQIACH_CHANNEL_INSTANCE_ATTRS	1524	X'000005F4'
MQIACH_CHANNEL_ERROR_DATA	1525	X'000005F5'
MQIACH_CHANNEL_TABLE	1526	X'000005F6'
MQIACH_CHANNEL_STATUS	1527	X'000005F7'
MQIACH_INDOUBT_STATUS	1528	X'000005F8'
MQIACH_LAST_SEQ_NUMBER	1529	X'000005F9'
MQIACH_LAST_SEQUENCE_NUMBER	1529	X'000005F9'
MQIACH_CURRENT_MSGS	1531	X'000005FB'
MQIACH_CURRENT_SEQ_NUMBER	1532	X'000005FC'
MQIACH_CURRENT_SEQUENCE_NUMBER	1532	X'000005FC'
MQIACH_SSL_RETURN_CODE	1533	X'000005FD'
MQIACH_MSGS	1534	X'000005FE'
MQIACH_BYTES_SENT	1535	X'000005FF'
MQIACH_BYTES_RCVD	1536	X'00000600'
MQIACH_BYTES_RECEIVED	1536	X'00000600'
MQIACH_BATCHES	1537	X'00000601'
MQIACH_BUFFERS_SENT	1538	X'00000602'
MQIACH_BUFFERS_RCVD	1539	X'00000603'
MQIACH_BUFFERS_RECEIVED	1539	X'00000603'
MQIACH_LONG_RETRIES_LEFT	1540	X'00000604'
MQIACH_SHORT_RETRIES_LEFT	1541	X'00000605'
MQIACH_MCA_STATUS	1542	X'00000606'
MQIACH_STOP_REQUESTED	1543	X'00000607'
MQIACH_MR_COUNT	1544	X'00000608'
MQIACH_MR_INTERVAL	1545	X'00000609'
MQIACH_NPM_SPEED	1562	X'0000061A'
MQIACH_HB_INTERVAL	1563	X'0000061B'
MQIACH_BATCH_INTERVAL	1564	X'0000061C'
MQIACH_NETWORK_PRIORITY	1565	X'0000061D'
MQIACH_KEEP_ALIVE_INTERVAL	1566	X'0000061E'
MQIACH_BATCH_HB	1567	X'0000061F'
MQIACH_SSL_CLIENT_AUTH	1568	X'00000620'
MQIACH_ALLOC_RETRY	1570	X'00000622'
MQIACH_ALLOC_FAST_TIMER	1571	X'00000623'
MQIACH_ALLOC_SLOW_TIMER	1572	X'00000624'
MQIACH_DISC_RETRY	1573	X'00000625'
MQIACH_PORT_NUMBER	1574	X'00000626'
MQIACH_HDR_COMPRESSION	1575	X'00000627'

MQIACH_MSG_COMPRESSION	1576	X'00000628'
MQIACH_CLWL_CHANNEL_RANK	1577	X'00000629'
MQIACH_CLWL_CHANNEL_PRIORITY	1578	X'0000062A'
MQIACH_CLWL_CHANNEL_WEIGHT	1579	X'0000062B'
MQIACH_CHANNEL_DISP	1580	X'0000062C'
MQIACH_INBOUND_DISP	1581	X'0000062D'
MQIACH_CHANNEL_TYPES	1582	X'0000062E'
MQIACH_ADAPS_STARTED	1583	X'0000062F'
MQIACH_ADAPS_MAX	1584	X'00000630'
MQIACH_DISPS_STARTED	1585	X'00000631'
MQIACH_DISPS_MAX	1586	X'00000632'
MQIACH_SSLTASKS_STARTED	1587	X'00000633'
MQIACH_SSLTASKS_MAX	1588	X'00000634'
MQIACH_CURRENT_CHL	1589	X'00000635'
MQIACH_CURRENT_CHL_MAX	1590	X'00000636'
MQIACH_CURRENT_CHL_TCP	1591	X'00000637'
MQIACH_CURRENT_CHL_LU62	1592	X'00000638'
MQIACH_ACTIVE_CHL	1593	X'00000639'
MQIACH_ACTIVE_CHL_MAX	1594	X'0000063A'
MQIACH_ACTIVE_CHL_PAUSED	1595	X'0000063B'
MQIACH_ACTIVE_CHL_STARTED	1596	X'0000063C'
MQIACH_ACTIVE_CHL_STOPPED	1597	X'0000063D'
MQIACH_ACTIVE_CHL_RETRY	1598	X'0000063E'
MQIACH_LISTENER_STATUS	1599	X'0000063F'
MQIACH_SHARED_CHL_RESTART	1600	X'00000640'
MQIACH_LISTENER_CONTROL	1601	X'00000641'
MQIACH_BACKLOG	1602	X'00000642'
MQIACH_XMITQ_TIME_INDICATOR	1604	X'00000644'
MQIACH_NETWORK_TIME_INDICATOR	1605	X'00000645'
MQIACH_EXIT_TIME_INDICATOR	1606	X'00000646'
MQIACH_BATCH_SIZE_INDICATOR	1607	X'00000647'
MQIACH_XMITQ_MSGS_AVAILABLE	1608	X'00000648'
MQIACH_CHANNEL_SUBSTATE	1609	X'00000649'
MQIACH_SSL_KEY_RESETS	1610	X'0000064A'
MQIACH_COMPRESSION_RATE	1611	X'0000064B'
MQIACH_COMPRESSION_TIME	1612	X'0000064C'
MQIACH_MAX_XMIT_SIZE	1613	X'0000064D'
MQIACH_DEF_CHANNEL_DISP	1614	X'0000064E'
MQIACH_SHARING_CONVERSATIONS	1615	X'0000064F'
MQIACH_MAX_SHARING_CONVS	1616	X'00000650'
MQIACH_CURRENT_SHARING_CONVS	1617	X'00000651'
MQIACH_MAX_INSTANCES	1618	X'00000652'

MQIACH_MAX_INSTS_PER_CLIENT	1619	X'00000653'
MQIACH_CLIENT_CHANNEL_WEIGHT	1620	X'00000654'
MQIACH_CONNECTION_AFFINITY	1621	X'00000655'
MQIACH_LAST_USED	1621	X'00000655'

MQIAMO_* (Command format Integer Monitoring Parameter Types)

MQIAMO_FIRST	701	X'000002BD'
MQIAMO_AVG_BATCH_SIZE	702	X'000002BE'
MQIAMO_AVG_Q_TIME	703	X'000002BF'
MQIAMO_BACKOUTS	704	X'000002C0'
MQIAMO_BROWSES	705	X'000002C1'
MQIAMO_BROWSE_MAX_BYTES	706	X'000002C2'
MQIAMO_BROWSE_MIN_BYTES	707	X'000002C3'
MQIAMO_BROWSES_FAILED	708	X'000002C4'
MQIAMO_CLOSES	709	X'000002C5'
MQIAMO_COMMITS	710	X'000002C6'
MQIAMO_COMMITS_FAILED	711	X'000002C7'
MQIAMO_CONNS	712	X'000002C8'
MQIAMO_CONNS_MAX	713	X'000002C9'
MQIAMO_DISCS	714	X'000002CA'
MQIAMO_DISCS_IMPLICIT	715	X'000002CB'
MQIAMO_DISC_TYPE	716	X'000002CC'
MQIAMO_EXIT_TIME_AVG	717	X'000002CD'
MQIAMO_EXIT_TIME_MAX	718	X'000002CE'
MQIAMO_EXIT_TIME_MIN	719	X'000002CF'
MQIAMO_FULL_BATCHES	720	X'000002D0'
MQIAMO_GENERATED_MSGS	721	X'000002D1'
MQIAMO_GETS	722	X'000002D2'
MQIAMO_GET_MAX_BYTES	723	X'000002D3'
MQIAMO_GET_MIN_BYTES	724	X'000002D4'
MQIAMO_GETS_FAILED	725	X'000002D5'
MQIAMO_INCOMPLETE_BATCHES	726	X'000002D6'
MQIAMO_INQS	727	X'000002D7'
MQIAMO_MSGS	728	X'000002D8'
MQIAMO_NET_TIME_AVG	729	X'000002D9'
MQIAMO_NET_TIME_MAX	730	X'000002DA'
MQIAMO_NET_TIME_MIN	731	X'000002DB'
MQIAMO_OBJECT_COUNT	732	X'000002DC'
MQIAMO_OPENS	733	X'000002DD'
MQIAMO_PUT1S	734	X'000002DE'
MQIAMO_PUTS	735	X'000002DF'

MQIAMO_PUT_MAX_BYTES	736	X'000002E0'
MQIAMO_PUT_MIN_BYTES	737	X'000002E1'
MQIAMO_PUT_RETRIES	738	X'000002E2'
MQIAMO_Q_MAX_DEPTH	739	X'000002E3'
MQIAMO_Q_MIN_DEPTH	740	X'000002E4'
MQIAMO_Q_TIME_AVG	741	X'000002E5'
MQIAMO_Q_TIME_MAX	742	X'000002E6'
MQIAMO_Q_TIME_MIN	743	X'000002E7'
MQIAMO_SETS	744	X'000002E8'
MQIAMO_CONNS_FAILED	749	X'000002ED'
MQIAMO_OPENS_FAILED	751	X'000002EF'
MQIAMO_INQS_FAILED	752	X'000002F0'
MQIAMO_SETS_FAILED	753	X'000002F1'
MQIAMO_PUTS_FAILED	754	X'000002F2'
MQIAMO_PUT1S_FAILED	755	X'000002F3'
MQIAMO_CLOSES_FAILED	757	X'000002F5'
MQIAMO_MSGS_EXPIRED	758	X'000002F6'
MQIAMO_MSGS_NOT_QUEUED	759	X'000002F7'
MQIAMO_MSGS_PURGED	760	X'000002F8'
MQIAMO_SUBS_DUR	764	X'000002FC'
MQIAMO_SUBS_NDUR	765	X'000002FD'
MQIAMO_SUBS_FAILED	766	X'000002FE'
MQIAMO_SUBRQS	767	X'000002FF'
MQIAMO_SUBRQS_FAILED	768	X'00000300'
MQIAMO_CBS	769	X'00000301'
MQIAMO_CBS_FAILED	770	X'00000302'
MQIAMO_CTLs	771	X'00000303'
MQIAMO_CTLs_FAILED	772	X'00000304'
MQIAMO_STATS	773	X'00000305'
MQIAMO_STATS_FAILED	774	X'00000306'
MQIAMO_SUB_DUR_HIGHWATER	775	X'00000307'
MQIAMO_SUB_DUR_LOWWATER	776	X'00000308'
MQIAMO_SUB_NDUR_HIGHWATER	777	X'00000309'
MQIAMO_SUB_NDUR_LOWWATER	778	X'0000030A'
MQIAMO_TOPIC_PUTS	779	X'0000030B'
MQIAMO_TOPIC_PUTS_FAILED	780	X'0000030C'
MQIAMO_TOPIC_PUT1S	781	X'0000030D'
MQIAMO_TOPIC_PUT1S_FAILED	782	X'0000030E'
MQIAMO_PUBLISH_MSG_COUNT	784	X'00000310'
MQIAMO_UNSUBS_DUR	786	X'00000312'
MQIAMO_UNSUBS_NDUR	787	X'00000313'
MQIAMO_UNSUBS_FAILED	788	X'00000314'

MQIAMO_LAST_USED	788	X'00000314'
------------------	-----	-------------

MQIAMO64_* (Command format 64-bit Integer Monitoring Parameter Types)

MQIAMO64_AVG_Q_TIME	703	X'000002BF'
MQIAMO64_Q_TIME_AVG	741	X'000002E5'
MQIAMO64_Q_TIME_MAX	742	X'000002E6'
MQIAMO64_Q_TIME_MIN	743	X'000002E7'
MQIAMO64_BROWSE_BYTES	745	X'000002E9'
MQIAMO64_BYTES	746	X'000002EA'
MQIAMO64_GET_BYTES	747	X'000002EB'
MQIAMO64_PUT_BYTES	748	X'000002EC'
MQIAMO64_TOPIC_PUT_BYTES	783	X'0000030F'
MQIAMO64_PUBLISH_MSG_BYTES	785	X'00000311'

MQIASY_* (Integer System Selectors)

MQIASY_FIRST	-1	X'FFFFFFFF'
MQIASY_CODED_CHAR_SET_ID	-1	X'FFFFFFFF'
MQIASY_TYPE	-2	X'FFFFFFFFE'
MQIASY_COMMAND	-3	X'FFFFFFFFD'
MQIASY_MSG_SEQ_NUMBER	-4	X'FFFFFFFFC'
MQIASY_CONTROL	-5	X'FFFFFFFFB'
MQIASY_COMP_CODE	-6	X'FFFFFFFFA'
MQIASY_REASON	-7	X'FFFFFFFF9'
MQIASY_BAG_OPTIONS	-8	X'FFFFFFFF8'
MQIASY_VERSION	-9	X'FFFFFFFF7'
MQIASY_LAST_USED	-9	X'FFFFFFFF7'
MQIASY_LAST	-2000	X'FFFFFF830'

MQIAUT_* (IMS information header Authenticator)

MQIAUT_NONE	"bbbbbbbb"
MQIAUT_NONE_ARRAY	'b','b','b','b','b','b','b','b'

MQIAV_* (Integer Attribute Values)

MQIAV_NOT_APPLICABLE	-1	X'FFFFFFFF'
MQIAV_UNDEFINED	-2	X'FFFFFFFFE'

MQICM_* (IMS information header Commit Modes)

MQICM_COMMIT_THEN_SEND	'0'	
MQICM_SEND_THEN_COMMIT	'1'	

MQIDO_* (Command format Indoubt Options)

MQIDO_COMMIT		1	X'00000001'
MQIDO_BACKOUT		2	X'00000002'

MQIGQ_* (Intra-Group Queuing)

MQIGQ_DISABLED		0	X'00000000'
MQIGQ_ENABLED		1	X'00000001'

MQIGQPA_* (Intra-Group Queuing Put Authority)

MQIGQPA_DEFAULT		1	X'00000001'
MQIGQPA_CONTEXT		2	X'00000002'
MQIGQPA_ONLY_IGQ		3	X'00000003'
MQIGQPA_ALTERNATE_OR_IGQ		4	X'00000004'

MQIIH_* (IMS information header structure)

MQIIH_STRUC_ID	"IIHb"		
MQIIH_STRUC_ID_ARRAY	'I','I','H','b'		
MQIIH_VERSION_1		1	X'00000001'
MQIIH_CURRENT_VERSION		1	X'00000001'
MQIIH_LENGTH_1		84	X'00000054'

MQIIH_* (IMS information header Flags)

MQIIH_NONE		0	X'00000000'
MQIIH_PASS_EXPIRATION		1	X'00000001'
MQIIH_UNLIMITED_EXPIRATION		0	X'00000000'
MQIIH_REPLY_FORMAT_NONE		8	X'00000008'
MQIIH_IGNORE_PURG		16	X'00000010'

MQIMPO_* (Inquire message property options structure)

MQIMPO_STRUC_ID	"IMPO"		
MQIMPO_STRUC_ID_ARRAY	'I','M','P','O'		

MQIMPO_VERSION_1	1	X'00000001'
MQIMPO_CURRENT_VERSION	1	X'00000001'

MQIMPO_* (Inquire Message Property Options)

MQIMPO_CONVERT_TYPE	2	X'00000002'
MQIMPO_QUERY_LENGTH	4	X'00000004'
MQIMPO_INQ_FIRST	0	X'00000000'
MQIMPO_INQ_NEXT	8	X'00000008'
MQIMPO_INQ_PROP_UNDER_CURSOR	16	X'00000010'
MQIMPO_CONVERT_VALUE	32	X'00000020'
MQIMPO_NONE	0	X'00000000'

MQINBD_* (Command format Inbound Dispositions)

MQINBD_Q_MGR	0	X'00000000'
MQINBD_GROUP	3	X'00000003'

MQIND_* (Special Index Values)

MQIND_NONE	-1	X'FFFFFFFF'
MQIND_ALL	-2	X'FFFFFFFE'

MQIPADDR_* (IP Address Versions)

MQIPADDR_IPV4	0	X'00000000'
MQIPADDR_IPV6	1	X'00000001'

MQISS_* (IMS information header Security Scopes)

MQISS_CHECK	'C'	
MQISS_FULL	'F'	

MQIT_* (Index Types)

MQIT_NONE	0	X'00000000'
MQIT_MSG_ID	1	X'00000001'
MQIT_CORREL_ID	2	X'00000002'
MQIT_MSG_TOKEN	4	X'00000004'
MQIT_GROUP_ID	5	X'00000005'

MQITEM_* (Item Type for mqInquireItemInfo)

MQITEM_INTEGER		1	X'00000001'
MQITEM_STRING		2	X'00000002'
MQITEM_BAG		3	X'00000003'
MQITEM_BYTE_STRING		4	X'00000004'
MQITEM_INTEGER_FILTER		5	X'00000005'
MQITEM_STRING_FILTER		6	X'00000006'
MQITEM_INTEGER64		7	X'00000007'
MQITEM_BYTE_STRING_FILTER		8	X'00000008'

MQITII_* (IMS information header Transaction Instance Identifier)

MQITII_NONE	X'00...00'	(16 nulls)
MQITII_NONE_ARRAY	'\0','\0',...	(16 nulls)

MQITS_* (IMS information header Transaction States)

MQITS_IN_CONVERSATION	'C'	
MQITS_NOT_IN_CONVERSATION	'b'	
MQITS_ARCHITECTED	'A'	

MQKAI_* (KeepAlive Interval)

MQKAI_AUTO		-1	X'FFFFFFFF'
------------	--	----	-------------

MQMASTER_* (Master administration)

MQMASTER_NO		0	X'00000000'
MQMASTER_YES		1	X'00000001'

MQMCAS_* (Command format Message Channel Agent Status)

MQMCAS_STOPPED		0	X'00000000'
MQMCAS_RUNNING		3	X'00000003'

MQMCAT_* (MCA Types)

MQMCAT_PROCESS		1	X'00000001'
MQMCAT_THREAD		2	X'00000002'

MQMCD_* (Publish/Subscribe Options Tag Message Content Descriptor (mcd) Tags)

MQMCD_FOLDER_VERSION		1	X'00000001'
----------------------	--	---	-------------

MQMCD_* (Publish/Subscribe Options Tag Tag names)

MQMCD_MSG_DOMAIN	"Msd"	
MQMCD_MSG_SET	"Set"	
MQMCD_MSG_TYPE	"Type"	
MQMCD_MSG_FORMAT	"Fmt"	

MQMCD_* (Publish/Subscribe Options Tag XML tag names)

MQMCD_MSG_DOMAIN_B	"<Msd>"	
MQMCD_MSG_DOMAIN_E	"</Msd>"	
MQMCD_MSG_SET_B	"<Set>"	
MQMCD_MSG_SET_E	"</Set>"	
MQMCD_MSG_TYPE_B	"<Type>"	
MQMCD_MSG_TYPE_E	"</Type>"	
MQMCD_MSG_FORMAT_B	"<Fmt>"	
MQMCD_MSG_FORMAT_E	"</Fmt>"	

MQMCD_* (Publish/Subscribe Options Tag Tag values)

MQMCD_DOMAIN_NONE	"none"	
MQMCD_DOMAIN_NEON	"neon"	
MQMCD_DOMAIN_MRM	"mrm"	
MQMCD_DOMAIN_JMS_NONE	"jms_none"	
MQMCD_DOMAIN_JMS_TEXT	"jms_text"	
MQMCD_DOMAIN_JMS_OBJECT	"jms_object"	
MQMCD_DOMAIN_JMS_MAP	"jms_map"	
MQMCD_DOMAIN_JMS_STREAM	"jms_stream"	
MQMCD_DOMAIN_JMS_BYTES	"jms_bytes"	

MQMD_* (Message descriptor structure)

MQMD_STRUC_ID	"MDbb"		
MQMD_STRUC_ID_ARRAY	'M','D','b','b'		
MQMD_VERSION_1		1	X'00000001'

MQMD_VERSION_2		2	X'00000002'
MQMD_CURRENT_VERSION		2	X'00000002'

MQMDE_* (Message descriptor extension structure)

MQMDE_STRUC_ID	"MDEb"		
MQMDE_STRUC_ID_ARRAY	'M','D','E','b'		
MQMDE_VERSION_2		2	X'00000002'
MQMDE_CURRENT_VERSION		2	X'00000002'
MQMDE_LENGTH_2		72	X'00000048'

MQMDEF_* (Message descriptor extension Flags)

MQMDEF_NONE		0	X'00000000'
-------------	--	---	-------------

MQMDS_* (Message Delivery Sequence)

MQMDS_PRIORITY		0	X'00000000'
MQMDS_FIFO		1	X'00000001'

MQMF_* (Message Flags)

MQMF_SEGMENTATION_INHIBITED		0	X'00000000'
MQMF_SEGMENTATION_ALLOWED		1	X'00000001'
MQMF_MSG_IN_GROUP		8	X'00000008'
MQMF_LAST_MSG_IN_GROUP		16	X'00000010'
MQMF_SEGMENT		2	X'00000002'
MQMF_LAST_SEGMENT		4	X'00000004'
MQMF_NONE		0	X'00000000'

MQMHBO_* (Message handle to buffer options structure)

MQMHBO_STRUC_ID	"MHBO"		
MQMHBO_STRUC_ID_ARRAY	'M','H','B','O'		
MQMHBO_VERSION_1		1	X'00000001'
MQMHBO_CURRENT_VERSION		1	X'00000001'

MQMHBO_* (Message Handle To Buffer Options)

MQMHBO_PROPERTIES_IN_MQRFH2		1	X'00000001'
MQMHBO_DELETE_PROPERTIES		2	X'00000002'

MQMHBO_NONE	0	X'00000000'
-------------	---	-------------

MQMI_* (Message Identifier)

MQMI_NONE	X'00...00'	(24 nulls)
MQMI_NONE_ARRAY	'\0','\0',...	(24 nulls)

MQMMBI_* (Message Mark-Browse Interval)

MQMMBI_UNLIMITED	-1	X'FFFFFFFF'
------------------	----	-------------

MQMO_* (Match Options)

MQMO_MATCH_MSG_ID	1	X'00000001'
MQMO_MATCH_CORREL_ID	2	X'00000002'
MQMO_MATCH_GROUP_ID	4	X'00000004'
MQMO_MATCH_MSG_SEQ_NUMBER	8	X'00000008'
MQMO_MATCH_OFFSET	16	X'00000010'
MQMO_MATCH_MSG_TOKEN	32	X'00000020'
MQMO_NONE	0	X'00000000'

MQMODE_* (Command format Mode Options)

MQMODE_FORCE	0	X'00000000'
MQMODE_QUIESCE	1	X'00000001'
MQMODE_TERMINATE	2	X'00000002'

MQMON_* (Monitoring Values)

MQMON_NOT_AVAILABLE	-1	X'FFFFFFFF'
MQMON_NONE	-1	X'FFFFFFFF'
MQMON_Q_MGR	-3	X'FFFFFFFD'
MQMON_OFF	0	X'00000000'
MQMON_ON	1	X'00000001'
MQMON_DISABLED	0	X'00000000'
MQMON_ENABLED	1	X'00000001'
MQMON_LOW	17	X'00000011'
MQMON_MEDIUM	33	X'00000021'
MQMON_HIGH	65	X'00000041'

MQMT_* (Message Types)

MQMT_SYSTEM_FIRST	1	X'00000001'
MQMT_REQUEST	1	X'00000001'
MQMT_REPLY	2	X'00000002'
MQMT_DATAGRAM	8	X'00000008'
MQMT_REPORT	4	X'00000004'
MQMT_MQE_FIELDS_FROM_MQE	112	X'00000070'
MQMT_MQE_FIELDS	113	X'00000071'
MQMT_SYSTEM_LAST	65535	X'0000FFFF'
MQMT_APPL_FIRST	65536	X'00010000'
MQMT_APPL_LAST	99999999	X'3B9AC9FF'

MQMTOK_* (Message Token)

MQMTOK_NONE	X'00...00'	(16 nulls)
MQMTOK_NONE_ARRAY	'\0','\0',...	(16 nulls)

MQNC_* (Name Count)

MQNC_MAX_NAMELIST_NAME_COUNT	256	X'00000100'
------------------------------	-----	-------------

MQNPM_* (Nonpersistent Message Class)

MQNPM_CLASS_NORMAL	0	X'00000000'
MQNPM_CLASS_HIGH	10	X'0000000A'

MQNPMS_* (NonPersistent-Message Speeds)

MQNPMS_NORMAL	1	X'00000001'
MQNPMS_FAST	2	X'00000002'

MQNT_* (Namelist Types)

MQNT_NONE	0	X'00000000'
MQNT_Q	1	X'00000001'
MQNT_CLUSTER	2	X'00000002'
MQNT_AUTH_INFO	4	X'00000004'
MQNT_ALL	1001	X'000003E9'

MQNVS_* (Names for Name/Value String)

MQNVS_APPL_TYPE	"OPT_APP_GRPb"	
MQNVS_MSG_TYPE	"OPT_MSG_TYPEb"	

MQOA_* (Limits for Selectors for Object Attributes)

MQOA_FIRST	1	X'00000001'
MQOA_LAST	9000	X'00002328'

MQOD_* (Object descriptor structure)

MQOD_STRUC_ID	"0Dbb"	
MQOD_STRUC_ID_ARRAY	'0','D','b','b'	
MQOD_VERSION_1	1	X'00000001'
MQOD_VERSION_2	2	X'00000002'
MQOD_VERSION_3	3	X'00000003'
MQOD_VERSION_4	4	X'00000004'
MQOD_CURRENT_VERSION	4	X'00000004'
MQOD_CURRENT_LENGTH	(value differs by platform or version)	

MQOII_* (Object Instance Identifier)

MQOII_NONE	X'00...00'	(24 nulls)
MQOII_NONE_ARRAY	'\0','\0',...	(24 nulls)

MQOL_* (Original Length)

MQOL_UNDEFINED	-1	X'FFFFFFFF'
----------------	----	-------------

MQOM_* (Obsolete DB2 Messages options on Inquire Group)

MQOM_NO	0	X'00000000'
MQOM_YES	1	X'00000001'

MQOO_* (Open Options)

MQOO_BIND_AS_Q_DEF	0	X'00000000'
MQOO_READ_AHEAD_AS_Q_DEF	0	X'00000000'
MQOO_INPUT_AS_Q_DEF	1	X'00000001'
MQOO_INPUT_SHARED	2	X'00000002'

MQOO_INPUT_EXCLUSIVE	4	X'00000004'
MQOO_BROWSE	8	X'00000008'
MQOO_OUTPUT	16	X'00000010'
MQOO_INQUIRE	32	X'00000020'
MQOO_SET	64	X'00000040'
MQOO_SAVE_ALL_CONTEXT	128	X'00000080'
MQOO_PASS_IDENTITY_CONTEXT	256	X'00000100'
MQOO_PASS_ALL_CONTEXT	512	X'00000200'
MQOO_SET_IDENTITY_CONTEXT	1024	X'00000400'
MQOO_SET_ALL_CONTEXT	2048	X'00000800'
MQOO_ALTERNATE_USER_AUTHORITY	4096	X'00001000'
MQOO_FAIL_IF QUIESCING	8192	X'00002000'
MQOO_BIND_ON_OPEN	16384	X'00004000'
MQOO_BIND_NOT_FIXED	32768	X'00008000'
MQOO_CO_OP	131072	X'00020000'
MQOO_NO_READ_AHEAD	524288	X'00080000'
MQOO_READ_AHEAD	1048576	X'00100000'

MQOO_* (Following used in C++ only)

MQOO_RESOLVE_NAMES	65536	X'00010000'
MQOO_RESOLVE_LOCAL_Q	262144	X'00040000'

MQOP_* (Operation codes for MQCTL)

MQOP_START	1	X'00000001'
MQOP_START_WAIT	2	X'00000002'
MQOP_STOP	4	X'00000004'

MQOP_* (Operation codes for MQCB)

MQOP_REGISTER	256	X'00000100'
MQOP_DEREGISTER	512	X'00000200'

MQOP_* (Operation codes for MQCTL and MQCB)

MQOP_SUSPEND	65536	X'00010000'
MQOP_RESUME	131072	X'00020000'

MQOPEN_* (Values related to MQOPEN_PRIV structure)

MQOPEN_PRIV_VERSION_1	1	X'00000001'
-----------------------	---	-------------

MQOPEN_PRIV_CURRENT_VERSION	1	X'00000001'
-----------------------------	---	-------------

MQOPER_* (Activity Operations)

MQOPER_SYSTEM_FIRST	0	X'00000000'
MQOPER_UNKNOWN	0	X'00000000'
MQOPER_BROWSE	1	X'00000001'
MQOPER_DISCARD	2	X'00000002'
MQOPER_GET	3	X'00000003'
MQOPER_PUT	4	X'00000004'
MQOPER_PUT_REPLY	5	X'00000005'
MQOPER_PUT_REPORT	6	X'00000006'
MQOPER_RECEIVE	7	X'00000007'
MQOPER_SEND	8	X'00000008'
MQOPER_TRANSFORM	9	X'00000009'
MQOPER_PUBLISH	10	X'0000000A'
MQOPER_EXCLUDED_PUBLISH	11	X'0000000B'
MQOPER_DISCARDED_PUBLISH	12	X'0000000C'
MQOPER_SYSTEM_LAST	65535	X'0000FFFF'
MQOPER_APPL_FIRST	65536	X'00010000'
MQOPER_APPL_LAST	999999999	X'3B9AC9FF'

MQOT_* (Object Types)

MQOT_NONE	0	X'00000000'
MQOT_Q	1	X'00000001'
MQOT_NAMELIST	2	X'00000002'
MQOT_PROCESS	3	X'00000003'
MQOT_STORAGE_CLASS	4	X'00000004'
MQOT_Q_MGR	5	X'00000005'
MQOT_CHANNEL	6	X'00000006'
MQOT_AUTH_INFO	7	X'00000007'
MQOT_TOPIC	8	X'00000008'
MQOT_CF_STRUC	10	X'0000000A'
MQOT_LISTENER	11	X'0000000B'
MQOT_SERVICE	12	X'0000000C'
MQOT_RESERVED_1	999	X'000003E7'

MQOT_* (Extended Object Types)

MQOT_ALL	1001	X'000003E9'
MQOT_ALIAS_Q	1002	X'000003EA'

MQOT_MODEL_Q	1003	X'000003EB'
MQOT_LOCAL_Q	1004	X'000003EC'
MQOT_REMOTE_Q	1005	X'000003ED'
MQOT_SENDER_CHANNEL	1007	X'000003EF'
MQOT_SERVER_CHANNEL	1008	X'000003F0'
MQOT_REQUESTER_CHANNEL	1009	X'000003F1'
MQOT_RECEIVER_CHANNEL	1010	X'000003F2'
MQOT_CURRENT_CHANNEL	1011	X'000003F3'
MQOT_SAVED_CHANNEL	1012	X'000003F4'
MQOT_SVRCONN_CHANNEL	1013	X'000003F5'
MQOT_CLNTCONN_CHANNEL	1014	X'000003F6'
MQOT_SHORT_CHANNEL	1015	X'000003F7'

MQPA_* (Put Authority)

MQPA_DEFAULT	1	X'00000001'
MQPA_CONTEXT	2	X'00000002'
MQPA_ONLY_MCA	3	X'00000003'
MQPA_ALTERNATE_OR_MCA	4	X'00000004'

MQPD_* (Property descriptor structure)

MQPD_STRUC_ID	"PDbb"	
MQPD_STRUC_ID_ARRAY	'P','D','b','b'	
MQPD_VERSION_1	1	X'00000001'
MQPD_CURRENT_VERSION	1	X'00000001'

MQPD_* (Property Descriptor Options)

MQPD_NONE	0	X'00000000'
-----------	---	-------------

MQPD_* (Property Support Options)

MQPD_SUPPORT_OPTIONAL	1	X'00000001'
MQPD_SUPPORT_REQUIRED	1048576	X'00100000'
MQPD_SUPPORT_REQUIRED_IF_LOCAL	1024	X'00000400'
MQPD_REJECT_UNSUP_MASK	-1048576	X'FFF00000'
MQPD_ACCEPT_UNSUP_IF_XMIT_MASK	1047552	X'000FFC00'
MQPD_ACCEPT_UNSUP_MASK	1023	X'000003FF'

MQPD_* (Property Context)

MQPD_NO_CONTEXT	0	X'00000000'
MQPD_USER_CONTEXT	1	X'00000001'

MQPER_* (Persistence Values)

MQPER_PERSISTENCE_AS_PARENT	-1	X'FFFFFFFF'
MQPER_NOT_PERSISTENT	0	X'00000000'
MQPER_PERSISTENT	1	X'00000001'
MQPER_PERSISTENCE_AS_Q_DEF	2	X'00000002'
MQPER_PERSISTENCE_AS_TOPIC_DEF	2	X'00000002'

MQPL_* (Platforms)

MQPL_MVS	1	X'00000001'
MQPL_OS390	1	X'00000001'
MQPL_ZOS	1	X'00000001'
MQPL_OS2	2	X'00000002'
MQPL_AIX	3	X'00000003'
MQPL_UNIX	3	X'00000003'
MQPL_OS400	4	X'00000004'
MQPL_WINDOWS	5	X'00000005'
MQPL_WINDOWS_NT	11	X'0000000B'
MQPL_VMS	12	X'0000000C'
MQPL_NSK	13	X'0000000D'
MQPL_NSS	13	X'0000000D'
MQPL_OPEN_TP1	15	X'0000000F'
MQPL_VM	18	X'00000012'
MQPL_TPF	23	X'00000017'
MQPL_VSE	27	X'0000001B'
MQPL_NATIVE	1	X'00000001'

MQPMO_* (Put message options structure)

MQPMO_STRUC_ID	"PM0b"	
MQPMO_STRUC_ID_ARRAY	'P','M','0','b'	
MQPMO_VERSION_1	1	X'00000001'
MQPMO_VERSION_2	2	X'00000002'
MQPMO_VERSION_3	3	X'00000003'
MQPMO_CURRENT_VERSION	3	X'00000003'

MQPMO_CURRENT_LENGTH	(value differs by platform or version)	
----------------------	--	--

MQPMO_* (Put Message Options)

MQPMO_SYNCPOINT	2	X'00000002'
MQPMO_NO_SYNCPOINT	4	X'00000004'
MQPMO_DEFAULT_CONTEXT	32	X'00000020'
MQPMO_NEW_MSG_ID	64	X'00000040'
MQPMO_NEW_CORREL_ID	128	X'00000080'
MQPMO_PASS_IDENTITY_CONTEXT	256	X'00000100'
MQPMO_PASS_ALL_CONTEXT	512	X'00000200'
MQPMO_SET_IDENTITY_CONTEXT	1024	X'00000400'
MQPMO_SET_ALL_CONTEXT	2048	X'00000800'
MQPMO_ALTERNATE_USER_AUTHORITY	4096	X'00001000'
MQPMO_FAIL_IF QUIESCING	8192	X'00002000'
MQPMO_NO_CONTEXT	16384	X'00004000'
MQPMO_LOGICAL_ORDER	32768	X'00008000'
MQPMO_ASYNC_RESPONSE	65536	X'00010000'
MQPMO_SYNC_RESPONSE	131072	X'00020000'
MQPMO_RESOLVE_LOCAL_Q	262144	X'00040000'
MQPMO_RETAIN	2097152	X'00200000'
MQPMO_MD_FOR_OUTPUT_ONLY	8388608	X'00800000'
MQPMO_SCOPE_QMGR	67108864	X'04000000'
MQPMO_SUPPRESS_REPLYTO	134217728	X'08000000'
MQPMO_NOT_OWN_SUBS	268435456	X'10000000'
MQPMO_RESPONSE_AS_Q_DEF	0	X'00000000'
MQPMO_RESPONSE_AS_TOPIC_DEF	0	X'00000000'
MQPMO_NONE	0	X'00000000'

MQPMO_* (Put Message Options for publish mask)

MQPMO_PUB_OPTIONS_MASK	2097152	X'00200000'
------------------------	---------	-------------

MQPMRF_* (Put Message Record Fields)

MQPMRF_MSG_ID	1	X'00000001'
MQPMRF_CORREL_ID	2	X'00000002'
MQPMRF_GROUP_ID	4	X'00000004'
MQPMRF_FEEDBACK	8	X'00000008'
MQPMRF_ACCOUNTING_TOKEN	16	X'00000010'
MQPMRF_NONE	0	X'00000000'

MQPO_* (Command format Purge Options)

MQPO_YES	1	X'00000001'
MQPO_NO	0	X'00000000'

MQPRI_* (Priority)

MQPRI_PRIORITY_AS_Q_DEF	-1	X'FFFFFFFF'
MQPRI_PRIORITY_AS_PARENT	-2	X'FFFFFFFE'
MQPRI_PRIORITY_AS_PUBLISHED	-3	X'FFFFFFFD'
MQPRI_PRIORITY_AS_TOPIC_DEF	-1	X'FFFFFFFF'

MQPROP_* (Queue and Channel Property Control Values)

MQPROP_COMPATIBILITY	0	X'00000000'
MQPROP_NONE	1	X'00000001'
MQPROP_ALL	2	X'00000002'
MQPROP_FORCE_MQRFH2	3	X'00000003'

MQPROP_* (Maximum Properties Length)

MQPROP_UNRESTRICTED_LENGTH	-1	X'FFFFFFFF'
----------------------------	----	-------------

MQPRT_* (Put Response Values)

MQPRT_RESPONSE_AS_PARENT	0	X'00000000'
MQPRT_SYNC_RESPONSE	1	X'00000001'
MQPRT_ASYNC_RESPONSE	2	X'00000002'

MQPS_* (Command format Pub/Sub Status)

MQPS_STATUS_INACTIVE	0	X'00000000'
MQPS_STATUS_STARTING	1	X'00000001'
MQPS_STATUS_STOPPING	2	X'00000002'
MQPS_STATUS_ACTIVE	3	X'00000003'
MQPS_STATUS_COMPAT	4	X'00000004'
MQPS_STATUS_ERROR	5	X'00000005'
MQPS_STATUS_REFUSED	6	X'00000006'

MQPS_* (Publish/Subscribe Tags as strings)

MQPS_COMMAND	"MQPSCommand"	
MQPS_COMP_CODE	"MQPSCompCode"	
MQPS_CORREL_ID	"MQPSCorrelId"	
MQPS_DELETE_OPTIONS	"MQPSDe10pts"	
MQPS_ERROR_ID	"MQPSErrorId"	
MQPS_ERROR_POS	"MQPSErrorPos"	
MQPS_INTEGER_DATA	"MQPSIntData"	
MQPS_PARAMETER_ID	"MQSParmId"	
MQPS_PUBLICATION_OPTIONS	"MQSPub0pts"	
MQPS_PUBLISH_TIMESTAMP	"MQSPubTime"	
MQPS_Q_MGR_NAME	"MQPSQMgrName"	
MQPS_Q_NAME	"MQPSQName"	
MQPS_REASON	"MQPSReason"	
MQPS_REASON_TEXT	"MQPSReasonText"	
MQPS_REGISTRATION_OPTIONS	"MQPSReg0pts"	
MQPS_SEQUENCE_NUMBER	"MQPSSeqNum"	
MQPS_STREAM_NAME	"MQPSStreamName"	
MQPS_STRING_DATA	"MQPSStringData"	
MQPS_SUBSCRIPTION_IDENTITY	"MQPSSubIdentity"	
MQPS_SUBSCRIPTION_NAME	"MQPSSubName"	
MQPS_SUBSCRIPTION_USER_DATA	"MQPSSubUserData"	
MQPS_TOPIC	"MQPSTopic"	
MQPS_USER_ID	"MQPSUserId"	

MQPS_* (Publish/Subscribe Tags as blank-enclosed strings)

MQPS_COMMAND_B	"bMQPSCommandb"	
MQPS_COMP_CODE_B	"bMQPSCompCodeb"	
MQPS_CORREL_ID_B	"bMQPSCorrelIdb"	
MQPS_DELETE_OPTIONS_B	"bMQPSDe10ptsb"	
MQPS_ERROR_ID_B	"bMQPSErrorIdb"	
MQPS_ERROR_POS_B	"bMQPSErrorPosb"	
MQPS_INTEGER_DATA_B	"bMQPSIntDatab"	
MQPS_PARAMETER_ID_B	"bMQSParmIdb"	
MQPS_PUBLICATION_OPTIONS_B	"bMQSPub0ptsb"	
MQPS_PUBLISH_TIMESTAMP_B	"bMQSPubTimeb"	
MQPS_Q_MGR_NAME_B	"bMQPSQMgrNameb"	
MQPS_Q_NAME_B	"bMQPSQNameb"	

MQPS_REASON_B	"bMQPSReasonb"	
MQPS_REASON_TEXT_B	"bMQPSReasonTextb"	
MQPS_REGISTRATION_OPTIONS_B	"bMQPSRegOptsb"	
MQPS_SEQUENCE_NUMBER_B	"bMQPSSeqNumb"	
MQPS_STREAM_NAME_B	"bMQPSStreamNameb"	
MQPS_STRING_DATA_B	"bMQPSStringDatab"	
MQPS_SUBSCRIPTION_IDENTITY_B	"bMQPSSubIdentityb"	
MQPS_SUBSCRIPTION_NAME_B	"bMQPSSubNameb"	
MQPS_SUBSCRIPTION_USER_DATA_B	"bMQPSSubUserDatab"	
MQPS_TOPIC_B	"bMQPSTopicb"	
MQPS_USER_ID_B	"bMQPSUserIdb"	

MQPS_* (Publish/Subscribe Command Tag Values as strings)

MQPS_DELETE_PUBLICATION	"DeletePub"	
MQPS_DEREGISTER_PUBLISHER	"DeregPub"	
MQPS_DEREGISTER_SUBSCRIBER	"DeregSub"	
MQPS_PUBLISH	"Publish"	
MQPS_REGISTER_PUBLISHER	"RegPub"	
MQPS_REGISTER_SUBSCRIBER	"RegSub"	
MQPS_REQUEST_UPDATE	"ReqUpdate"	

MQPS_* (Publish/Subscribe Command Tag Values as blank-enclosed strings)

MQPS_DELETE_PUBLICATION_B	"bDeletePubb"	
MQPS_DEREGISTER_PUBLISHER_B	"bDeregPubb"	
MQPS_DEREGISTER_SUBSCRIBER_B	"bDeregSubb"	
MQPS_PUBLISH_B	"bPublishb"	
MQPS_REGISTER_PUBLISHER_B	"bRegPubb"	
MQPS_REGISTER_SUBSCRIBER_B	"bRegSubb"	
MQPS_REQUEST_UPDATE_B	"bReqUpdateb"	

MQPS_* (Publish/Subscribe Options Tag Values as strings)

MQPS_ADD_NAME	"AddName"	
MQPS_ANONYMOUS	"Anon"	
MQPS_CORREL_ID_AS_IDENTITY	"CorrelAsId"	
MQPS_DEREGISTER_ALL	"DeregAll"	

MQPS_DIRECT_REQUESTS	"DirectReq"	
MQPS_DUPLICATES_OK	"DupsOK"	
MQPS_FULL_RESPONSE	"FullResp"	
MQPS_INCLUDE_STREAM_NAME	"InclStreamName"	
MQPS_INFORM_IF_RETAINED	"InformIfRet"	
MQPS_IS_RETAINED_PUBLICATION	"IsRetainedPub"	
MQPS_JOIN_EXCLUSIVE	"JoinExcl"	
MQPS_JOIN_SHARED	"JoinShared"	
MQPS_LEAVE_ONLY	"LeaveOnly"	
MQPS_LOCAL	"Local"	
MQPS_LOCKED	"Locked"	
MQPS_NEW_PUBLICATIONS_ONLY	"NewPubsOnly"	
MQPS_NO_ALTERATION	"NoAlter"	
MQPS_NO_REGISTRATION	"NoReg"	
MQPS_NON_PERSISTENT	"NonPers"	
MQPS_NONE	"None"	
MQPS_OTHER_SUBSCRIBERS_ONLY	"OtherSubsOnly"	
MQPS_PERSISTENT	"Pers"	
MQPS_PERSISTENT_AS_PUBLISH	"PersAsPub"	
MQPS_PERSISTENT_AS_Q	"PersAsQueue"	
MQPS_PUBLISH_ON_REQUEST_ONLY	"PubOnReqOnly"	
MQPS_RETAIN_PUBLICATION	"RetainPub"	
MQPS_VARIABLE_USER_ID	"VariableUserId"	

MQPS_* (Publish/Subscribe Options Tag Values as blank-enclosed strings)

MQPS_ADD_NAME_B	"bAddNameb"	
MQPS_ANONYMOUS_B	"bAnonb"	
MQPS_CORREL_ID_AS_IDENTITY_B	"bCorrelAsIdb"	
MQPS_DEREGISTER_ALL_B	"bDeregAllb"	
MQPS_DIRECT_REQUESTS_B	"bDirectReqb"	
MQPS_DUPLICATES_OK_B	"bDupsOKb"	
MQPS_FULL_RESPONSE_B	"bFullRespb"	
MQPS_INCLUDE_STREAM_NAME_B	"bInclStreamNameb"	
MQPS_INFORM_IF_RETAINED_B	"bInformIfRetb"	
MQPS_IS_RETAINED_PUBLICATION_B	"bIsRetainedPubb"	
MQPS_JOIN_EXCLUSIVE_B	"bJoinExclb"	
MQPS_JOIN_SHARED_B	"bJoinSharedb"	

MQPS_LEAVE_ONLY_B	"bLeaveOnlyb"	
MQPS_LOCAL_B	"bLocalb"	
MQPS_LOCKED_B	"bLockedb"	
MQPS_NEW_PUBLICATIONS_ONLY_B	"bNewPubsOnlyb"	
MQPS_NO_ALTERATION_B	"bNoAlterb"	
MQPS_NO_REGISTRATION_B	"bNoRegb"	
MQPS_NON_PERSISTENT_B	"bNonPersb"	
MQPS_NONE_B	"bNoneb"	
MQPS_OTHER_SUBSCRIBERS_ONLY_B	"bOtherSubsOnlyb"	
MQPS_PERSISTENT_B	"bPersb"	
MQPS_PERSISTENT_AS_PUBLISH_B	"bPersAsPubb"	
MQPS_PERSISTENT_AS_Q_B	"bPersAsQueueb"	
MQPS_PUBLISH_ON_REQUEST_ONLY_B	"bPubOnReqOnlyb"	
MQPS_RETAIN_PUBLICATION_B	"bRetainPubb"	
MQPS_VARIABLE_USER_ID_B	"bVariableUserIdb"	

MQPSC_* (Publish/Subscribe Options Tag Publish/Subscribe Command Folder (psc) Tags)

MQPSC_FOLDER_VERSION	1	X'00000001'
----------------------	---	-------------

MQPSC_* (Publish/Subscribe Options Tag Tag names)

MQPSC_COMMAND	"Command"	
MQPSC_REGISTRATION_OPTION	"RegOpt"	
MQPSC_PUBLICATION_OPTION	"PubOpt"	
MQPSC_DELETE_OPTION	"DelOpt"	
MQPSC_TOPIC	"Topic"	
MQPSC_SUBSCRIPTION_POINT	"SubPoint"	
MQPSC_FILTER	"Filter"	
MQPSC_Q_MGR_NAME	"QMgrName"	
MQPSC_Q_NAME	"QName"	
MQPSC_PUBLISH_TIMESTAMP	"PubTime"	
MQPSC_SEQUENCE_NUMBER	"SeqNum"	
MQPSC_SUBSCRIPTION_NAME	"SubName"	
MQPSC_SUBSCRIPTION_IDENTITY	"SubIdentity"	
MQPSC_SUBSCRIPTION_USER_DATA	"SubUserData"	
MQPSC_CORREL_ID	"CorrelId"	

MQPSC_* (Publish/Subscribe Options Tag XML tag names)

MQPSC_COMMAND_B	"<Command>"	
MQPSC_COMMAND_E	"</Command>"	
MQPSC_REGISTRATION_OPTION_B	"<RegOpt>"	
MQPSC_REGISTRATION_OPTION_E	"</RegOpt>"	
MQPSC_PUBLICATION_OPTION_B	"<PubOpt>"	
MQPSC_PUBLICATION_OPTION_E	"</PubOpt>"	
MQPSC_DELETE_OPTION_B	"<DelOpt>"	
MQPSC_DELETE_OPTION_E	"</DelOpt>"	
MQPSC_TOPIC_B	"<Topic>"	
MQPSC_TOPIC_E	"</Topic>"	
MQPSC_SUBSCRIPTION_POINT_B	"<SubPoint>"	
MQPSC_SUBSCRIPTION_POINT_E	"</SubPoint>"	
MQPSC_FILTER_B	"<Filter>"	
MQPSC_FILTER_E	"</Filter>"	
MQPSC_Q_MGR_NAME_B	"<QMgrName>"	
MQPSC_Q_MGR_NAME_E	"</QMgrName>"	
MQPSC_Q_NAME_B	"<QName>"	
MQPSC_Q_NAME_E	"</QName>"	
MQPSC_PUBLISH_TIMESTAMP_B	"<PubTime>"	
MQPSC_PUBLISH_TIMESTAMP_E	"</PubTime>"	
MQPSC_SEQUENCE_NUMBER_B	"<SeqNum>"	
MQPSC_SEQUENCE_NUMBER_E	"</SeqNum>"	
MQPSC_SUBSCRIPTION_NAME_B	"<SubName>"	
MQPSC_SUBSCRIPTION_NAME_E	"</SubName>"	
MQPSC_SUBSCRIPTION_IDENTITY_B	"<SubIdentity>"	
MQPSC_SUBSCRIPTION_IDENTITY_E	"</SubIdentity>"	
MQPSC_SUBSCRIPTION_USER_DATA_B	"<SubUserData>"	
MQPSC_SUBSCRIPTION_USER_DATA_E	"</SubUserData>"	
MQPSC_CORREL_ID_B	"<CorrelId>"	
MQPSC_CORREL_ID_E	"</CorrelId>"	

MQPSC_* (Publish/Subscribe Options Tag Values as strings)

MQPSC_DELETE_PUBLICATION	"DeletePub"	
MQPSC_DEREGISTER_SUBSCRIBER	"DeregSub"	
MQPSC_PUBLISH	"Publish"	
MQPSC_REGISTER_SUBSCRIBER	"RegSub"	
MQPSC_REQUEST_UPDATE	"ReqUpdate"	

MQPSC_* (Publish/Subscribe Options Tag Values as strings)

MQPSC_ADD_NAME	"AddName"	
MQPSC_CORREL_ID_AS_IDENTITY	"CorrelAsId"	
MQPSC_DEREGISTER_ALL	"DeregAll"	
MQPSC_DUPLICATES_OK	"DupsOK"	
MQPSC_FULL_RESPONSE	"FullResp"	
MQPSC_INFORM_IF_RETAINED	"InformIfRet"	
MQPSC_IS_RETAINED_PUB	"IsRetainedPub"	
MQPSC_JOIN_SHARED	"JoinShared"	
MQPSC_JOIN_EXCLUSIVE	"JoinExcl"	
MQPSC_LEAVE_ONLY	"LeaveOnly"	
MQPSC_LOCAL	"Local"	
MQPSC_LOCKED	"Locked"	
MQPSC_NEW_PUBS_ONLY	"NewPubsOnly"	
MQPSC_NO_ALTERATION	"NoAlter"	
MQPSC_NON_PERSISTENT	"NonPers"	
MQPSC_OTHER_SUBS_ONLY	"OtherSubsOnly"	
MQPSC_PERSISTENT	"Pers"	
MQPSC_PERSISTENT_AS_PUBLISH	"PersAsPub"	
MQPSC_PERSISTENT_AS_Q	"PersAsQueue"	
MQPSC_NONE	"None"	
MQPSC_PUB_ON_REQUEST_ONLY	"PubOnReqOnly"	
MQPSC_RETAIN_PUB	"RetainPub"	
MQPSC_VARIABLE_USER_ID	"VariableUserId"	

MQPSCR_* (Publish/Subscribe Options Tag Publish/Subscribe Response Folder (pscr) Tags)

MQPSCR_FOLDER_VERSION	1	X'00000001'
-----------------------	---	-------------

MQPSCR_* (Publish/Subscribe Options Tag Tag names)

MQPSCR_COMPLETION	"Completion"	
MQPSCR_RESPONSE	"Response"	
MQPSCR_REASON	"Reason"	

MQPSCR_* (Publish/Subscribe Options Tag XML tag names)

MQPSCR_COMPLETION_B	"<Completion>"	
MQPSCR_COMPLETION_E	"</Completion>"	
MQPSCR_RESPONSE_B	"<Response>"	
MQPSCR_RESPONSE_E	"</Response>"	
MQPSCR_REASON_B	"<Reason>"	
MQPSCR_REASON_E	"</Reason>"	

MQPSCR_* (Publish/Subscribe Options Tag Tag values)

MQPSCR_OK	"ok"	
MQPSCR_WARNING	"warning"	
MQPSCR_ERROR	"error"	

MQPSM_* (Pub/Sub Mode)

MQPSM_DISABLED	0	X'00000000'
MQPSM_COMPAT	1	X'00000001'
MQPSM_ENABLED	2	X'00000002'

MQPSPROP_* (Pub/Sub Message Properties)

MQPSPROP_NONE	0	X'00000000'
MQPSPROP_COMPAT	1	X'00000001'
MQPSPROP_RFH2	2	X'00000002'
MQPSPROP_MSGPROP	3	X'00000003'

MQPSST_* (Command format Pub/Sub Status Type)

MQPSST_ALL	0	X'00000000'
MQPSST_LOCAL	1	X'00000001'
MQPSST_PARENT	2	X'00000002'
MQPSST_CHILD	3	X'00000003'

MQPUBO_* (Publish/Subscribe Publication Options)

MQPUBO_NONE	0	X'00000000'
MQPUBO_CORREL_ID_AS_IDENTITY	1	X'00000001'
MQPUBO_RETAIN_PUBLICATION	2	X'00000002'
MQPUBO_OTHER_SUBSCRIBERS_ONLY	4	X'00000004'

MQPUBO_NO_REGISTRATION	8	X'00000008'
MQPUBO_IS_RETAINED_PUBLICATION	16	X'00000010'

MQXPX_* (Publish/subscribe routing exit parameter structure)

MQXPX_STRUC_ID	"PXPb"	
MQXPX_STRUC_ID_ARRAY	'P','X','P','b'	
MQXPX_VERSION_1	1	X'00000001'
MQXPX_CURRENT_VERSION	1	X'00000001'

MQQA_* (Inhibit Get Values)

MQQA_GET_INHIBITED	1	X'00000001'
MQQA_GET_ALLOWED	0	X'00000000'

MQQA_* (Inhibit Put Values)

MQQA_PUT_INHIBITED	1	X'00000001'
MQQA_PUT_ALLOWED	0	X'00000000'

MQQA_* (Queue Shareability)

MQQA_SHAREABLE	1	X'00000001'
MQQA_NOT_SHAREABLE	0	X'00000000'

MQQA_* (Back-Out Hardening)

MQQA_BACKOUT_HARDENED	1	X'00000001'
MQQA_BACKOUT_NOT_HARDENED	0	X'00000000'

MQQDT_* (Queue Definition Types)

MQQDT_PREDEFINED	1	X'00000001'
MQQDT_PERMANENT_DYNAMIC	2	X'00000002'
MQQDT_TEMPORARY_DYNAMIC	3	X'00000003'
MQQDT_SHARED_DYNAMIC	4	X'00000004'

MQQF_* (Queue Flags)

MQQF_LOCAL_Q	1	X'00000001'
MQQF_CLWL_USEQ_ANY	64	X'00000040'

MQQF_CLWL_USEQ_LOCAL	128	X'00000080'
----------------------	-----	-------------

MQQMDT_* (Command format Queue Manager Definition Types)

MQQMDT_EXPLICIT_CLUSTER_SENDER	1	X'00000001'
MQQMDT_AUTO_CLUSTER_SENDER	2	X'00000002'
MQQMDT_AUTO_EXP_CLUSTER_SENDER	4	X'00000004'
MQQMDT_CLUSTER_RECEIVER	3	X'00000003'

MQQMF_* (Queue Manager Flags)

MQQMF_REPOSITORY_Q_MGR	2	X'00000002'
MQQMF_CLUSSDR_USER_DEFINED	8	X'00000008'
MQQMF_CLUSSDR_AUTO_DEFINED	16	X'00000010'
MQQMF_AVAILABLE	32	X'00000020'

MQQMFC_* (Command format Queue Manager Facility)

MQQMFC_IMS_BRIDGE	1	X'00000001'
MQQMFC_DB2	2	X'00000002'

MQQMSTA_* (Command format Queue Manager Status)

MQQMSTA_STARTING	1	X'00000001'
MQQMSTA_RUNNING	2	X'00000002'
MQQMSTA QUIESCING	3	X'00000003'

MQQMT_* (Command format Queue Manager Types)

MQQMT_NORMAL	0	X'00000000'
MQQMT_REPOSITORY	1	X'00000001'

MQQO_* (Command format Quiesce Options)

MQQO_YES	1	X'00000001'
MQQO_NO	0	X'00000000'

MQQSGD_* (Queue Sharing Group Dispositions)

MQQSGD_ALL	-1	X'FFFFFFFF'
MQQSGD_Q_MGR	0	X'00000000'
MQQSGD_COPY	1	X'00000001'

MQQSGD_SHARED	2	X'00000002'
MQQSGD_GROUP	3	X'00000003'
MQQSGD_PRIVATE	4	X'00000004'
MQQSGD_LIVE	6	X'00000006'

MQQSGS_* (Command format QSG Status)

MQQSGS_UNKNOWN	0	X'00000000'
MQQSGS_CREATED	1	X'00000001'
MQQSGS_ACTIVE	2	X'00000002'
MQQSGS_INACTIVE	3	X'00000003'
MQQSGS_FAILED	4	X'00000004'
MQQSGS_PENDING	5	X'00000005'

MQQSIE_* (Command format Queue Service-Interval Events)

MQQSIE_NONE	0	X'00000000'
MQQSIE_HIGH	1	X'00000001'
MQQSIE_OK	2	X'00000002'

MQQSO_* (Command format Queue Status Open Options for SET, BROWSE, INPUT)

MQQSO_NO	0	X'00000000'
MQQSO_YES	1	X'00000001'
MQQSO_SHARED	1	X'00000001'
MQQSO_EXCLUSIVE	2	X'00000002'

MQQSOT_* (Command format Queue Status Open Types)

MQQSOT_ALL	1	X'00000001'
MQQSOT_INPUT	2	X'00000002'
MQQSOT_OUTPUT	3	X'00000003'

MQQSUM_* (Command format Queue Status Uncommitted Messages)

MQQSUM_YES	1	X'00000001'
MQQSUM_NO	0	X'00000000'

MQQT_* (Queue Types)

MQQT_LOCAL	1	X'00000001'
------------	---	-------------

MQQT_MODEL	2	X'00000002'
MQQT_ALIAS	3	X'00000003'
MQQT_REMOTE	6	X'00000006'
MQQT_CLUSTER	7	X'00000007'

MQQT_* (Extended Queue Types)

MQQT_ALL	1001	X'000003E9'
----------	------	-------------

MQRC_* (Reason Codes)

MQRC_NONE	0	X'00000000'
MQRC_APPL_FIRST	900	X'00000384'
MQRC_APPL_LAST	999	X'000003E7'
MQRC_ALIAS_BASE_Q_TYPE_ERROR	2001	X'000007D1'
MQRC_ALREADY_CONNECTED	2002	X'000007D2'
MQRC_BACKED_OUT	2003	X'000007D3'
MQRC_BUFFER_ERROR	2004	X'000007D4'
MQRC_BUFFER_LENGTH_ERROR	2005	X'000007D5'
MQRC_CHAR_ATTR_LENGTH_ERROR	2006	X'000007D6'
MQRC_CHAR_ATTRS_ERROR	2007	X'000007D7'
MQRC_CHAR_ATTRS_TOO_SHORT	2008	X'000007D8'
MQRC_CONNECTION_BROKEN	2009	X'000007D9'
MQRC_DATA_LENGTH_ERROR	2010	X'000007DA'
MQRC_DYNAMIC_Q_NAME_ERROR	2011	X'000007DB'
MQRC_ENVIRONMENT_ERROR	2012	X'000007DC'
MQRC_EXPIRY_ERROR	2013	X'000007DD'
MQRC_FEEDBACK_ERROR	2014	X'000007DE'
MQRC_GET_INHIBITED	2016	X'000007E0'
MQRC_HANDLE_NOT_AVAILABLE	2017	X'000007E1'
MQRC_HCONN_ERROR	2018	X'000007E2'
MQRC_HOBJ_ERROR	2019	X'000007E3'
MQRC_INHIBIT_VALUE_ERROR	2020	X'000007E4'
MQRC_INT_ATTR_COUNT_ERROR	2021	X'000007E5'
MQRC_INT_ATTR_COUNT_TOO_SMALL	2022	X'000007E6'
MQRC_INT_ATTRS_ARRAY_ERROR	2023	X'000007E7'
MQRC_SYNCPOINT_LIMIT_REACHED	2024	X'000007E8'
MQRC_MAX_CONNS_LIMIT_REACHED	2025	X'000007E9'
MQRC_MD_ERROR	2026	X'000007EA'
MQRC_MISSING_REPLY_TO_Q	2027	X'000007EB'
MQRC_MSG_TYPE_ERROR	2029	X'000007ED'
MQRC_MSG_TOO_BIG_FOR_Q	2030	X'000007EE'

MQRC_MSG_TOO_BIG_FOR_Q_MGR	2031	X'000007EF'
MQRC_NO_MSG_AVAILABLE	2033	X'000007F1'
MQRC_NO_MSG_UNDER_CURSOR	2034	X'000007F2'
MQRC_NOT_AUTHORIZED	2035	X'000007F3'
MQRC_NOT_OPEN_FOR_BROWSE	2036	X'000007F4'
MQRC_NOT_OPEN_FOR_INPUT	2037	X'000007F5'
MQRC_NOT_OPEN_FOR_INQUIRE	2038	X'000007F6'
MQRC_NOT_OPEN_FOR_OUTPUT	2039	X'000007F7'
MQRC_NOT_OPEN_FOR_SET	2040	X'000007F8'
MQRC_OBJECT_CHANGED	2041	X'000007F9'
MQRC_OBJECT_IN_USE	2042	X'000007FA'
MQRC_OBJECT_TYPE_ERROR	2043	X'000007FB'
MQRC_OD_ERROR	2044	X'000007FC'
MQRC_OPTION_NOT_VALID_FOR_TYPE	2045	X'000007FD'
MQRC_OPTIONS_ERROR	2046	X'000007FE'
MQRC_PERSISTENCE_ERROR	2047	X'000007FF'
MQRC_PERSISTENT_NOT_ALLOWED	2048	X'00000800'
MQRC_PRIORITY_EXCEEDS_MAXIMUM	2049	X'00000801'
MQRC_PRIORITY_ERROR	2050	X'00000802'
MQRC_PUT_INHIBITED	2051	X'00000803'
MQRC_Q_DELETED	2052	X'00000804'
MQRC_Q_FULL	2053	X'00000805'
MQRC_Q_NOT_EMPTY	2055	X'00000807'
MQRC_Q_SPACE_NOT_AVAILABLE	2056	X'00000808'
MQRC_Q_TYPE_ERROR	2057	X'00000809'
MQRC_Q_MGR_NAME_ERROR	2058	X'0000080A'
MQRC_Q_MGR_NOT_AVAILABLE	2059	X'0000080B'
MQRC_REPORT_OPTIONS_ERROR	2061	X'0000080D'
MQRC_SECOND_MARK_NOT_ALLOWED	2062	X'0000080E'
MQRC_SECURITY_ERROR	2063	X'0000080F'
MQRC_SELECTOR_COUNT_ERROR	2065	X'00000811'
MQRC_SELECTOR_LIMIT_EXCEEDED	2066	X'00000812'
MQRC_SELECTOR_ERROR	2067	X'00000813'
MQRC_SELECTOR_NOT_FOR_TYPE	2068	X'00000814'
MQRC_SIGNAL_OUTSTANDING	2069	X'00000815'
MQRC_SIGNAL_REQUEST_ACCEPTED	2070	X'00000816'
MQRC_STORAGE_NOT_AVAILABLE	2071	X'00000817'
MQRC_SYNCPOINT_NOT_AVAILABLE	2072	X'00000818'
MQRC_TRIGGER_CONTROL_ERROR	2075	X'0000081B'
MQRC_TRIGGER_DEPTH_ERROR	2076	X'0000081C'
MQRC_TRIGGER_MSG_PRIORITY_ERR	2077	X'0000081D'
MQRC_TRIGGER_TYPE_ERROR	2078	X'0000081E'

MQRC_TRUNCATED_MSG_ACCEPTED	2079	X'0000081F'
MQRC_TRUNCATED_MSG_FAILED	2080	X'00000820'
MQRC_UNKNOWN_ALIAS_BASE_Q	2082	X'00000822'
MQRC_UNKNOWN_OBJECT_NAME	2085	X'00000825'
MQRC_UNKNOWN_OBJECT_Q_MGR	2086	X'00000826'
MQRC_UNKNOWN_REMOTE_Q_MGR	2087	X'00000827'
MQRC_WAIT_INTERVAL_ERROR	2090	X'0000082A'
MQRC_XMIT_Q_TYPE_ERROR	2091	X'0000082B'
MQRC_XMIT_Q_USAGE_ERROR	2092	X'0000082C'
MQRC_NOT_OPEN_FOR_PASS_ALL	2093	X'0000082D'
MQRC_NOT_OPEN_FOR_PASS_IDENT	2094	X'0000082E'
MQRC_NOT_OPEN_FOR_SET_ALL	2095	X'0000082F'
MQRC_NOT_OPEN_FOR_SET_IDENT	2096	X'00000830'
MQRC_CONTEXT_HANDLE_ERROR	2097	X'00000831'
MQRC_CONTEXT_NOT_AVAILABLE	2098	X'00000832'
MQRC_SIGNAL1_ERROR	2099	X'00000833'
MQRC_OBJECT_ALREADY_EXISTS	2100	X'00000834'
MQRC_OBJECT_DAMAGED	2101	X'00000835'
MQRC_RESOURCE_PROBLEM	2102	X'00000836'
MQRC_ANOTHER_Q_MGR_CONNECTED	2103	X'00000837'
MQRC_UNKNOWN_REPORT_OPTION	2104	X'00000838'
MQRC_STORAGE_CLASS_ERROR	2105	X'00000839'
MQRC_COD_NOT_VALID_FOR_XCF_Q	2106	X'0000083A'
MQRC_XWAIT_CANCELED	2107	X'0000083B'
MQRC_XWAIT_ERROR	2108	X'0000083C'
MQRC_SUPPRESSED_BY_EXIT	2109	X'0000083D'
MQRC_FORMAT_ERROR	2110	X'0000083E'
MQRC_SOURCE_CCSID_ERROR	2111	X'0000083F'
MQRC_SOURCE_INTEGER_ENC_ERROR	2112	X'00000840'
MQRC_SOURCE_DECIMAL_ENC_ERROR	2113	X'00000841'
MQRC_SOURCE_FLOAT_ENC_ERROR	2114	X'00000842'
MQRC_TARGET_CCSID_ERROR	2115	X'00000843'
MQRC_TARGET_INTEGER_ENC_ERROR	2116	X'00000844'
MQRC_TARGET_DECIMAL_ENC_ERROR	2117	X'00000845'
MQRC_TARGET_FLOAT_ENC_ERROR	2118	X'00000846'
MQRC_NOT_CONVERTED	2119	X'00000847'
MQRC_CONVERTED_MSG_TOO_BIG	2120	X'00000848'
MQRC_TRUNCATED	2120	X'00000848'
MQRC_NO_EXTERNAL_PARTICIPANTS	2121	X'00000849'
MQRC_PARTICIPANT_NOT_AVAILABLE	2122	X'0000084A'
MQRC_OUTCOME_MIXED	2123	X'0000084B'
MQRC_OUTCOME_PENDING	2124	X'0000084C'

MQRC_BRIDGE_STARTED	2125	X'0000084D'
MQRC_BRIDGE_STOPPED	2126	X'0000084E'
MQRC_ADAPTER_STORAGE_SHORTAGE	2127	X'0000084F'
MQRC_UOW_IN_PROGRESS	2128	X'00000850'
MQRC_ADAPTER_CONN_LOAD_ERROR	2129	X'00000851'
MQRC_ADAPTER_SERV_LOAD_ERROR	2130	X'00000852'
MQRC_ADAPTER_DEFS_ERROR	2131	X'00000853'
MQRC_ADAPTER_DEFS_LOAD_ERROR	2132	X'00000854'
MQRC_ADAPTER_CONV_LOAD_ERROR	2133	X'00000855'
MQRC_BO_ERROR	2134	X'00000856'
MQRC_DH_ERROR	2135	X'00000857'
MQRC_MULTIPLE_REASONS	2136	X'00000858'
MQRC_OPEN_FAILED	2137	X'00000859'
MQRC_ADAPTER_DISC_LOAD_ERROR	2138	X'0000085A'
MQRC_CNO_ERROR	2139	X'0000085B'
MQRC_CICS_WAIT_FAILED	2140	X'0000085C'
MQRC_DLH_ERROR	2141	X'0000085D'
MQRC_HEADER_ERROR	2142	X'0000085E'
MQRC_SOURCE_LENGTH_ERROR	2143	X'0000085F'
MQRC_TARGET_LENGTH_ERROR	2144	X'00000860'
MQRC_SOURCE_BUFFER_ERROR	2145	X'00000861'
MQRC_TARGET_BUFFER_ERROR	2146	X'00000862'
MQRC_IIH_ERROR	2148	X'00000864'
MQRC_PCF_ERROR	2149	X'00000865'
MQRC_DBCS_ERROR	2150	X'00000866'
MQRC_OBJECT_NAME_ERROR	2152	X'00000868'
MQRC_OBJECT_Q_MGR_NAME_ERROR	2153	X'00000869'
MQRC_RECS_PRESENT_ERROR	2154	X'0000086A'
MQRC_OBJECT_RECORDS_ERROR	2155	X'0000086B'
MQRC_RESPONSE_RECORDS_ERROR	2156	X'0000086C'
MQRC_ASID_MISMATCH	2157	X'0000086D'
MQRC_PMO_RECORD_FLAGS_ERROR	2158	X'0000086E'
MQRC_PUT_MSG_RECORDS_ERROR	2159	X'0000086F'
MQRC_CONN_ID_IN_USE	2160	X'00000870'
MQRC_Q_MGR QUIESCING	2161	X'00000871'
MQRC_Q_MGR_STOPPING	2162	X'00000872'
MQRC_DUPLICATE_RECOV_COORD	2163	X'00000873'
MQRC_PMO_ERROR	2173	X'0000087D'
MQRC_API_EXIT_NOT_FOUND	2182	X'00000886'
MQRC_API_EXIT_LOAD_ERROR	2183	X'00000887'
MQRC_REMOTE_Q_NAME_ERROR	2184	X'00000888'
MQRC_INCONSISTENT_PERSISTENCE	2185	X'00000889'

MQRC_GMO_ERROR	2186	X'0000088A'
MQRC_CICS_BRIDGE_RESTRICTION	2187	X'0000088B'
MQRC_STOPPED_BY_CLUSTER_EXIT	2188	X'0000088C'
MQRC_CLUSTER_RESOLUTION_ERROR	2189	X'0000088D'
MQRC_CONVERTED_STRING_TOO_BIG	2190	X'0000088E'
MQRC_TMC_ERROR	2191	X'0000088F'
MQRC_PAGESET_FULL	2192	X'00000890'
MQRC_STORAGE_MEDIUM_FULL	2192	X'00000890'
MQRC_PAGESET_ERROR	2193	X'00000891'
MQRC_NAME_NOT_VALID_FOR_TYPE	2194	X'00000892'
MQRC_UNEXPECTED_ERROR	2195	X'00000893'
MQRC_UNKNOWN_XMIT_Q	2196	X'00000894'
MQRC_UNKNOWN_DEF_XMIT_Q	2197	X'00000895'
MQRC_DEF_XMIT_Q_TYPE_ERROR	2198	X'00000896'
MQRC_DEF_XMIT_Q_USAGE_ERROR	2199	X'00000897'
MQRC_MSG_MARKED_BROWSE_CO_OP	2200	X'00000898'
MQRC_NAME_IN_USE	2201	X'00000899'
MQRC_CONNECTION QUIESCING	2202	X'0000089A'
MQRC_CONNECTION_STOPPING	2203	X'0000089B'
MQRC_ADAPTER_NOT_AVAILABLE	2204	X'0000089C'
MQRC_MSG_ID_ERROR	2206	X'0000089E'
MQRC_CORREL_ID_ERROR	2207	X'0000089F'
MQRC_FILE_SYSTEM_ERROR	2208	X'000008A0'
MQRC_NO_MSG_LOCKED	2209	X'000008A1'
MQRC_SOAP_DOTNET_ERROR	2210	X'000008A2'
MQRC_SOAP_AXIS_ERROR	2211	X'000008A3'
MQRC_SOAP_URL_ERROR	2212	X'000008A4'
MQRC_FILE_NOT_AUDITED	2216	X'000008A8'
MQRC_CONNECTION_NOT_AUTHORIZED	2217	X'000008A9'
MQRC_MSG_TOO_BIG_FOR_CHANNEL	2218	X'000008AA'
MQRC_CALL_IN_PROGRESS	2219	X'000008AB'
MQRC_RMH_ERROR	2220	X'000008AC'
MQRC_Q_MGR_ACTIVE	2222	X'000008AE'
MQRC_Q_MGR_NOT_ACTIVE	2223	X'000008AF'
MQRC_Q_DEPTH_HIGH	2224	X'000008B0'
MQRC_Q_DEPTH_LOW	2225	X'000008B1'
MQRC_Q_SERVICE_INTERVAL_HIGH	2226	X'000008B2'
MQRC_Q_SERVICE_INTERVAL_OK	2227	X'000008B3'
MQRC_RFH_HEADER_FIELD_ERROR	2228	X'000008B4'
MQRC_RAS_PROPERTY_ERROR	2229	X'000008B5'
MQRC_UNIT_OF_WORK_NOT_STARTED	2232	X'000008B8'
MQRC_CHANNEL_AUTO_DEF_OK	2233	X'000008B9'

MQRC_CHANNEL_AUTO_DEF_ERROR	2234	X'000008BA'
MQRC_CFH_ERROR	2235	X'000008BB'
MQRC_CFIL_ERROR	2236	X'000008BC'
MQRC_CFIN_ERROR	2237	X'000008BD'
MQRC_CFSL_ERROR	2238	X'000008BE'
MQRC_CFST_ERROR	2239	X'000008BF'
MQRC_INCOMPLETE_GROUP	2241	X'000008C1'
MQRC_INCOMPLETE_MSG	2242	X'000008C2'
MQRC_INCONSISTENT_CCSIDS	2243	X'000008C3'
MQRC_INCONSISTENT_ENCODINGS	2244	X'000008C4'
MQRC_INCONSISTENT_UOW	2245	X'000008C5'
MQRC_INVALID_MSG_UNDER_CURSOR	2246	X'000008C6'
MQRC_MATCH_OPTIONS_ERROR	2247	X'000008C7'
MQRC_MDE_ERROR	2248	X'000008C8'
MQRC_MSG_FLAGS_ERROR	2249	X'000008C9'
MQRC_MSG_SEQ_NUMBER_ERROR	2250	X'000008CA'
MQRC_OFFSET_ERROR	2251	X'000008CB'
MQRC_ORIGINAL_LENGTH_ERROR	2252	X'000008CC'
MQRC_SEGMENT_LENGTH_ZERO	2253	X'000008CD'
MQRC_UOW_NOT_AVAILABLE	2255	X'000008CF'
MQRC_WRONG_GMO_VERSION	2256	X'000008D0'
MQRC_WRONG_MD_VERSION	2257	X'000008D1'
MQRC_GROUP_ID_ERROR	2258	X'000008D2'
MQRC_INCONSISTENT_BROWSE	2259	X'000008D3'
MQRC_XQH_ERROR	2260	X'000008D4'
MQRC_SRC_ENV_ERROR	2261	X'000008D5'
MQRC_SRC_NAME_ERROR	2262	X'000008D6'
MQRC_DEST_ENV_ERROR	2263	X'000008D7'
MQRC_DEST_NAME_ERROR	2264	X'000008D8'
MQRC_TM_ERROR	2265	X'000008D9'
MQRC_CLUSTER_EXIT_ERROR	2266	X'000008DA'
MQRC_CLUSTER_EXIT_LOAD_ERROR	2267	X'000008DB'
MQRC_CLUSTER_PUT_INHIBITED	2268	X'000008DC'
MQRC_CLUSTER_RESOURCE_ERROR	2269	X'000008DD'
MQRC_NO_DESTINATIONS_AVAILABLE	2270	X'000008DE'
MQRC_CONN_TAG_IN_USE	2271	X'000008DF'
MQRC_PARTIALLY_CONVERTED	2272	X'000008E0'
MQRC_CONNECTION_ERROR	2273	X'000008E1'
MQRC_OPTION_ENVIRONMENT_ERROR	2274	X'000008E2'
MQRC_CD_ERROR	2277	X'000008E5'
MQRC_CLIENT_CONN_ERROR	2278	X'000008E6'
MQRC_CHANNEL_STOPPED_BY_USER	2279	X'000008E7'

MQRC_HCONFIG_ERROR	2280	X'000008E8'
MQRC_FUNCTION_ERROR	2281	X'000008E9'
MQRC_CHANNEL_STARTED	2282	X'000008EA'
MQRC_CHANNEL_STOPPED	2283	X'000008EB'
MQRC_CHANNEL_CONV_ERROR	2284	X'000008EC'
MQRC_SERVICE_NOT_AVAILABLE	2285	X'000008ED'
MQRC_INITIALIZATION_FAILED	2286	X'000008EE'
MQRC_TERMINATION_FAILED	2287	X'000008EF'
MQRC_UNKNOWN_Q_NAME	2288	X'000008F0'
MQRC_SERVICE_ERROR	2289	X'000008F1'
MQRC_Q_ALREADY_EXISTS	2290	X'000008F2'
MQRC_USER_ID_NOT_AVAILABLE	2291	X'000008F3'
MQRC_UNKNOWN_ENTITY	2292	X'000008F4'
MQRC_UNKNOWN_AUTH_ENTITY	2293	X'000008F5'
MQRC_UNKNOWN_REF_OBJECT	2294	X'000008F6'
MQRC_CHANNEL_ACTIVATED	2295	X'000008F7'
MQRC_CHANNEL_NOT_ACTIVATED	2296	X'000008F8'
MQRC_UOW_CANCELED	2297	X'000008F9'
MQRC_FUNCTION_NOT_SUPPORTED	2298	X'000008FA'
MQRC_SELECTOR_TYPE_ERROR	2299	X'000008FB'
MQRC_COMMAND_TYPE_ERROR	2300	X'000008FC'
MQRC_MULTIPLE_INSTANCE_ERROR	2301	X'000008FD'
MQRC_SYSTEM_ITEM_NOT_ALTERABLE	2302	X'000008FE'
MQRC_BAG_CONVERSION_ERROR	2303	X'000008FF'
MQRC_SELECTOR_OUT_OF_RANGE	2304	X'00000900'
MQRC_SELECTOR_NOT_UNIQUE	2305	X'00000901'
MQRC_INDEX_NOT_PRESENT	2306	X'00000902'
MQRC_STRING_ERROR	2307	X'00000903'
MQRC_ENCODING_NOT_SUPPORTED	2308	X'00000904'
MQRC_SELECTOR_NOT_PRESENT	2309	X'00000905'
MQRC_OUT_SELECTOR_ERROR	2310	X'00000906'
MQRC_STRING_TRUNCATED	2311	X'00000907'
MQRC_SELECTOR_WRONG_TYPE	2312	X'00000908'
MQRC_INCONSISTENT_ITEM_TYPE	2313	X'00000909'
MQRC_INDEX_ERROR	2314	X'0000090A'
MQRC_SYSTEM_BAG_NOT_ALTERABLE	2315	X'0000090B'
MQRC_ITEM_COUNT_ERROR	2316	X'0000090C'
MQRC_FORMAT_NOT_SUPPORTED	2317	X'0000090D'
MQRC_SELECTOR_NOT_SUPPORTED	2318	X'0000090E'
MQRC_ITEM_VALUE_ERROR	2319	X'0000090F'
MQRC_HBAG_ERROR	2320	X'00000910'
MQRC_PARAMETER_MISSING	2321	X'00000911'

MQRC_CMD_SERVER_NOT_AVAILABLE	2322	X'00000912'
MQRC_STRING_LENGTH_ERROR	2323	X'00000913'
MQRC_INQUIRY_COMMAND_ERROR	2324	X'00000914'
MQRC_NESTED_BAG_NOT_SUPPORTED	2325	X'00000915'
MQRC_BAG_WRONG_TYPE	2326	X'00000916'
MQRC_ITEM_TYPE_ERROR	2327	X'00000917'
MQRC_SYSTEM_BAG_NOT_DELETABLE	2328	X'00000918'
MQRC_SYSTEM_ITEM_NOT_DELETABLE	2329	X'00000919'
MQRC_CODED_CHAR_SET_ID_ERROR	2330	X'0000091A'
MQRC_MSG_TOKEN_ERROR	2331	X'0000091B'
MQRC_MISSING_WIH	2332	X'0000091C'
MQRC_WIH_ERROR	2333	X'0000091D'
MQRC_RFH_ERROR	2334	X'0000091E'
MQRC_RFH_STRING_ERROR	2335	X'0000091F'
MQRC_RFH_COMMAND_ERROR	2336	X'00000920'
MQRC_RFH_PARM_ERROR	2337	X'00000921'
MQRC_RFH_DUPLICATE_PARM	2338	X'00000922'
MQRC_RFH_PARM_MISSING	2339	X'00000923'
MQRC_CHAR_CONVERSION_ERROR	2340	X'00000924'
MQRC_UCS2_CONVERSION_ERROR	2341	X'00000925'
MQRC_DB2_NOT_AVAILABLE	2342	X'00000926'
MQRC_OBJECT_NOT_UNIQUE	2343	X'00000927'
MQRC_CONN_TAG_NOT_RELEASED	2344	X'00000928'
MQRC_CF_NOT_AVAILABLE	2345	X'00000929'
MQRC_CF_STRUC_IN_USE	2346	X'0000092A'
MQRC_CF_STRUC_LIST_HDR_IN_USE	2347	X'0000092B'
MQRC_CF_STRUC_AUTH_FAILED	2348	X'0000092C'
MQRC_CF_STRUC_ERROR	2349	X'0000092D'
MQRC_CONN_TAG_NOT_USABLE	2350	X'0000092E'
MQRC_GLOBAL_UOW_CONFLICT	2351	X'0000092F'
MQRC_LOCAL_UOW_CONFLICT	2352	X'00000930'
MQRC_HANDLE_IN_USE_FOR_UOW	2353	X'00000931'
MQRC_UOW_ENLISTMENT_ERROR	2354	X'00000932'
MQRC_UOW_MIX_NOT_SUPPORTED	2355	X'00000933'
MQRC_WXP_ERROR	2356	X'00000934'
MQRC_CURRENT_RECORD_ERROR	2357	X'00000935'
MQRC_NEXT_OFFSET_ERROR	2358	X'00000936'
MQRC_NO_RECORD_AVAILABLE	2359	X'00000937'
MQRC_OBJECT_LEVEL_INCOMPATIBLE	2360	X'00000938'
MQRC_NEXT_RECORD_ERROR	2361	X'00000939'
MQRC_BACKOUT_THRESHOLD_REACHED	2362	X'0000093A'
MQRC_MSG_NOT_MATCHED	2363	X'0000093B'

MQRC_JMS_FORMAT_ERROR	2364	X'0000093C'
MQRC_SEGMENTS_NOT_SUPPORTED	2365	X'0000093D'
MQRC_WRONG_CF_LEVEL	2366	X'0000093E'
MQRC_CONFIG_CREATE_OBJECT	2367	X'0000093F'
MQRC_CONFIG_CHANGE_OBJECT	2368	X'00000940'
MQRC_CONFIG_DELETE_OBJECT	2369	X'00000941'
MQRC_CONFIG_REFRESH_OBJECT	2370	X'00000942'
MQRC_CHANNEL_SSL_ERROR	2371	X'00000943'
MQRC_PARTICIPANT_NOT_DEFINED	2372	X'00000944'
MQRC_CF_STRUC_FAILED	2373	X'00000945'
MQRC_API_EXIT_ERROR	2374	X'00000946'
MQRC_API_EXIT_INIT_ERROR	2375	X'00000947'
MQRC_API_EXIT_TERM_ERROR	2376	X'00000948'
MQRC_EXIT_REASON_ERROR	2377	X'00000949'
MQRC_RESERVED_VALUE_ERROR	2378	X'0000094A'
MQRC_NO_DATA_AVAILABLE	2379	X'0000094B'
MQRC_SCO_ERROR	2380	X'0000094C'
MQRC_KEY_REPOSITORY_ERROR	2381	X'0000094D'
MQRC_CRYPTO_HARDWARE_ERROR	2382	X'0000094E'
MQRC_AUTH_INFO_REC_COUNT_ERROR	2383	X'0000094F'
MQRC_AUTH_INFO_REC_ERROR	2384	X'00000950'
MQRC_AIR_ERROR	2385	X'00000951'
MQRC_AUTH_INFO_TYPE_ERROR	2386	X'00000952'
MQRC_AUTH_INFO_CONN_NAME_ERROR	2387	X'00000953'
MQRC_LDAP_USER_NAME_ERROR	2388	X'00000954'
MQRC_LDAP_USER_NAME_LENGTH_ERR	2389	X'00000955'
MQRC_LDAP_PASSWORD_ERROR	2390	X'00000956'
MQRC_SSL_ALREADY_INITIALIZED	2391	X'00000957'
MQRC_SSL_CONFIG_ERROR	2392	X'00000958'
MQRC_SSL_INITIALIZATION_ERROR	2393	X'00000959'
MQRC_Q_INDEX_TYPE_ERROR	2394	X'0000095A'
MQRC_CFBS_ERROR	2395	X'0000095B'
MQRC_SSL_NOT_ALLOWED	2396	X'0000095C'
MQRC_JSSE_ERROR	2397	X'0000095D'
MQRC_SSL_PEER_NAME_MISMATCH	2398	X'0000095E'
MQRC_SSL_PEER_NAME_ERROR	2399	X'0000095F'
MQRC_UNSUPPORTED_CIPHER_SUITE	2400	X'00000960'
MQRC_SSL_CERTIFICATE_REVOKED	2401	X'00000961'
MQRC_SSL_CERT_STORE_ERROR	2402	X'00000962'
MQRC_CLIENT_EXIT_LOAD_ERROR	2406	X'00000966'
MQRC_CLIENT_EXIT_ERROR	2407	X'00000967'
MQRC_UOW_COMMITTED	2408	X'00000968'

MQRC_SSL_KEY_RESET_ERROR	2409	X'00000969'
MQRC_UNKNOWN_COMPONENT_NAME	2410	X'0000096A'
MQRC_LOGGER_STATUS	2411	X'0000096B'
MQRC_COMMAND_MQSC	2412	X'0000096C'
MQRC_COMMAND_PCF	2413	X'0000096D'
MQRC_CFIF_ERROR	2414	X'0000096E'
MQRC_CFSF_ERROR	2415	X'0000096F'
MQRC_CFGR_ERROR	2416	X'00000970'
MQRC_MSG_NOT_ALLOWED_IN_GROUP	2417	X'00000971'
MQRC_FILTER_OPERATOR_ERROR	2418	X'00000972'
MQRC_NESTED_SELECTOR_ERROR	2419	X'00000973'
MQRC_EPH_ERROR	2420	X'00000974'
MQRC_RFH_FORMAT_ERROR	2421	X'00000975'
MQRC_CFBF_ERROR	2422	X'00000976'
MQRC_CLIENT_CHANNEL_CONFLICT	2423	X'00000977'
MQRC_SD_ERROR	2424	X'00000978'
MQRC_TOPIC_STRING_ERROR	2425	X'00000979'
MQRC_STS_ERROR	2426	X'0000097A'
MQRC_NO_SUBSCRIPTION	2428	X'0000097C'
MQRC_SUBSCRIPTION_IN_USE	2429	X'0000097D'
MQRC_STAT_TYPE_ERROR	2430	X'0000097E'
MQRC_SUB_USER_DATA_ERROR	2431	X'0000097F'
MQRC_SUB_ALREADY_EXISTS	2432	X'00000980'
MQRC_IDENTITY_MISMATCH	2434	X'00000982'
MQRC_ALTER_SUB_ERROR	2435	X'00000983'
MQRC_DURABILITY_NOT_ALLOWED	2436	X'00000984'
MQRC_NO_RETAINED_MSG	2437	X'00000985'
MQRC_SRO_ERROR	2438	X'00000986'
MQRC_SUB_NAME_ERROR	2440	X'00000988'
MQRC_OBJECT_STRING_ERROR	2441	X'00000989'
MQRC_PROPERTY_NAME_ERROR	2442	X'0000098A'
MQRC_SEGMENTATION_NOT_ALLOWED	2443	X'0000098B'
MQRC_CBD_ERROR	2444	X'0000098C'
MQRC_CTLO_ERROR	2445	X'0000098D'
MQRC_NO_CALLBACKS_ACTIVE	2446	X'0000098E'
MQRC_CALLBACK_NOT_REGISTERED	2448	X'00000990'
MQRC_OPTIONS_CHANGED	2457	X'00000999'
MQRC_READ_AHEAD_MSGS	2458	X'0000099A'
MQRC_SELECTOR_SYNTAX_ERROR	2459	X'0000099B'
MQRC_HMSG_ERROR	2460	X'0000099C'
MQRC_CMHO_ERROR	2461	X'0000099D'
MQRC_DMHO_ERROR	2462	X'0000099E'

MQRC_SMPO_ERROR	2463	X'0000099F'
MQRC_IMPO_ERROR	2464	X'000009A0'
MQRC_PROPERTY_NAME_TOO_BIG	2465	X'000009A1'
MQRC_PROP_VALUE_NOT_CONVERTED	2466	X'000009A2'
MQRC_PROP_TYPE_NOT_SUPPORTED	2467	X'000009A3'
MQRC_PROPERTY_VALUE_TOO_BIG	2469	X'000009A5'
MQRC_PROP_CONV_NOT_SUPPORTED	2470	X'000009A6'
MQRC_PROPERTY_NOT_AVAILABLE	2471	X'000009A7'
MQRC_PROP_NUMBER_FORMAT_ERROR	2472	X'000009A8'
MQRC_PROPERTY_TYPE_ERROR	2473	X'000009A9'
MQRC_PROPERTIES_TOO_BIG	2478	X'000009AE'
MQRC_PUT_NOT_RETAINED	2479	X'000009AF'
MQRC_ALIAS_TARGTYPE_CHANGED	2480	X'000009B0'
MQRC_DMPO_ERROR	2481	X'000009B1'
MQRC_PD_ERROR	2482	X'000009B2'
MQRC_CALLBACK_TYPE_ERROR	2483	X'000009B3'
MQRC_CBD_OPTIONS_ERROR	2484	X'000009B4'
MQRC_MAX_MSG_LENGTH_ERROR	2485	X'000009B5'
MQRC_CALLBACK_ROUTINE_ERROR	2486	X'000009B6'
MQRC_CALLBACK_LINK_ERROR	2487	X'000009B7'
MQRC_OPERATION_ERROR	2488	X'000009B8'
MQRC_BMHO_ERROR	2489	X'000009B9'
MQRC_UNSUPPORTED_PROPERTY	2490	X'000009BA'
MQRC_PROP_NAME_NOT_CONVERTED	2492	X'000009BC'
MQRC_GET_ENABLED	2494	X'000009BE'
MQRC_MODULE_NOT_FOUND	2495	X'000009BF'
MQRC_MODULE_INVALID	2496	X'000009C0'
MQRC_MODULE_ENTRY_NOT_FOUND	2497	X'000009C1'
MQRC_MIXED_CONTENT_NOT_ALLOWED	2498	X'000009C2'
MQRC_MSG_HANDLE_IN_USE	2499	X'000009C3'
MQRC_HCONN_ASYNC_ACTIVE	2500	X'000009C4'
MQRC_MHBO_ERROR	2501	X'000009C5'
MQRC_PUBLICATION_FAILURE	2502	X'000009C6'
MQRC_SUB_INHIBITED	2503	X'000009C7'
MQRC_SELECTOR_ALWAYS_FALSE	2504	X'000009C8'
MQRC_XEPO_ERROR	2507	X'000009CB'
MQRC_DURABILITY_NOT_ALTERABLE	2509	X'000009CD'
MQRC_TOPIC_NOT_ALTERABLE	2510	X'000009CE'
MQRC_SUBLEVEL_NOT_ALTERABLE	2512	X'000009D0'
MQRC_PROPERTY_NAME_LENGTH_ERR	2513	X'000009D1'
MQRC_DUPLICATE_GROUP_SUB	2514	X'000009D2'
MQRC_GROUPING_NOT_ALTERABLE	2515	X'000009D3'

MQRC_SELECTOR_INVALID_FOR_TYPE	2516	X'000009D4'
MQRC_HOBJ QUIESCED	2517	X'000009D5'
MQRC_HOBJ QUIESCED_NO_MSGS	2518	X'000009D6'
MQRC_SELECTION_STRING_ERROR	2519	X'000009D7'
MQRC_RES_OBJECT_STRING_ERROR	2520	X'000009D8'
MQRC_CONNECTION_SUSPENDED	2521	X'000009D9'
MQRC_INVALID_DESTINATION	2522	X'000009DA'
MQRC_INVALID_SUBSCRIPTION	2523	X'000009DB'
MQRC_SELECTOR_NOT_ALTERABLE	2524	X'000009DC'
MQRC_RETAINED_MSG_Q_ERROR	2525	X'000009DD'
MQRC_RETAINED_NOT_DELIVERED	2526	X'000009DE'
MQRC_RFH_RESTRICTED_FORMAT_ERR	2527	X'000009DF'
MQRC_CONNECTION_STOPPED	2528	X'000009E0'
MQRC_ASYNC_UOW_CONFLICT	2529	X'000009E1'
MQRC_ASYNC_XA_CONFLICT	2530	X'000009E2'
MQRC_PUBSUB_INHIBITED	2531	X'000009E3'
MQRC_MSG_HANDLE_COPY_FAILURE	2532	X'000009E4'
MQRC_DEST_CLASS_NOT_ALTERABLE	2533	X'000009E5'
MQRC_OPERATION_NOT_ALLOWED	2534	X'000009E6'
MQRC_ACTION_ERROR	2535	X'000009E7'
MQRC_CHANNEL_NOT_AVAILABLE	2537	X'000009E9'
MQRC_HOST_NOT_AVAILABLE	2538	X'000009EA'
MQRC_CHANNEL_CONFIG_ERROR	2539	X'000009EB'
MQRC_UNKNOWN_CHANNEL_NAME	2540	X'000009EC'
MQRC_LOOPING_PUBLICATION	2541	X'000009ED'
MQRC_ALREADY_JOINED	2542	X'000009EE'
MQRC_REOPEN_EXCL_INPUT_ERROR	6100	X'000017D4'
MQRC_REOPEN_INQUIRE_ERROR	6101	X'000017D5'
MQRC_REOPEN_SAVED_CONTEXT_ERR	6102	X'000017D6'
MQRC_REOPEN_TEMPORARY_Q_ERROR	6103	X'000017D7'
MQRC_ATTRIBUTE_LOCKED	6104	X'000017D8'
MQRC_CURSOR_NOT_VALID	6105	X'000017D9'
MQRC_ENCODING_ERROR	6106	X'000017DA'
MQRC_STRUC_ID_ERROR	6107	X'000017DB'
MQRC_NULL_POINTER	6108	X'000017DC'
MQRC_NO_CONNECTION_REFERENCE	6109	X'000017DD'
MQRC_NO_BUFFER	6110	X'000017DE'
MQRC_BINARY_DATA_LENGTH_ERROR	6111	X'000017DF'
MQRC_BUFFER_NOT_AUTOMATIC	6112	X'000017E0'
MQRC_INSUFFICIENT_BUFFER	6113	X'000017E1'
MQRC_INSUFFICIENT_DATA	6114	X'000017E2'
MQRC_DATA_TRUNCATED	6115	X'000017E3'

MQRC_ZERO_LENGTH	6116	X'000017E4'
MQRC_NEGATIVE_LENGTH	6117	X'000017E5'
MQRC_NEGATIVE_OFFSET	6118	X'000017E6'
MQRC_INCONSISTENT_FORMAT	6119	X'000017E7'
MQRC_INCONSISTENT_OBJECT_STATE	6120	X'000017E8'
MQRC_CONTEXT_OBJECT_NOT_VALID	6121	X'000017E9'
MQRC_CONTEXT_OPEN_ERROR	6122	X'000017EA'
MQRC_STRUC_LENGTH_ERROR	6123	X'000017EB'
MQRC_NOT_CONNECTED	6124	X'000017EC'
MQRC_NOT_OPEN	6125	X'000017ED'
MQRC_DISTRIBUTION_LIST_EMPTY	6126	X'000017EE'
MQRC_INCONSISTENT_OPEN_OPTIONS	6127	X'000017EF'
MQRC_WRONG_VERSION	6128	X'000017F0'
MQRC_REFERENCE_ERROR	6129	X'000017F1'

MQRCCF_* (Command format header Reason Codes)

MQRCCF_CFH_TYPE_ERROR	3001	X'00000BB9'
MQRCCF_CFH_LENGTH_ERROR	3002	X'00000BBA'
MQRCCF_CFH_VERSION_ERROR	3003	X'00000BBB'
MQRCCF_CFH_MSG_SEQ_NUMBER_ERR	3004	X'00000BBC'
MQRCCF_CFH_CONTROL_ERROR	3005	X'00000BBD'
MQRCCF_CFH_PARM_COUNT_ERROR	3006	X'00000BBE'
MQRCCF_CFH_COMMAND_ERROR	3007	X'00000BBF'
MQRCCF_COMMAND_FAILED	3008	X'00000BC0'
MQRCCF_CFIN_LENGTH_ERROR	3009	X'00000BC1'
MQRCCF_CFST_LENGTH_ERROR	3010	X'00000BC2'
MQRCCF_CFST_STRING_LENGTH_ERR	3011	X'00000BC3'
MQRCCF_FORCE_VALUE_ERROR	3012	X'00000BC4'
MQRCCF_STRUCTURE_TYPE_ERROR	3013	X'00000BC5'
MQRCCF_CFIN_PARM_ID_ERROR	3014	X'00000BC6'
MQRCCF_CFST_PARM_ID_ERROR	3015	X'00000BC7'
MQRCCF_MSG_LENGTH_ERROR	3016	X'00000BC8'
MQRCCF_CFIN_DUPLICATE_PARM	3017	X'00000BC9'
MQRCCF_CFST_DUPLICATE_PARM	3018	X'00000BCA'
MQRCCF_PARM_COUNT_TOO_SMALL	3019	X'00000BCB'
MQRCCF_PARM_COUNT_TOO_BIG	3020	X'00000BCC'
MQRCCF_Q_ALREADY_IN_CELL	3021	X'00000BCD'
MQRCCF_Q_TYPE_ERROR	3022	X'00000BCE'
MQRCCF_MD_FORMAT_ERROR	3023	X'00000BCF'
MQRCCF_CFSL_LENGTH_ERROR	3024	X'00000BD0'
MQRCCF_REPLACE_VALUE_ERROR	3025	X'00000BD1'

MQRCCF_CFIL_DUPLICATE_VALUE	3026	X'00000BD2'
MQRCCF_CFIL_COUNT_ERROR	3027	X'00000BD3'
MQRCCF_CFIL_LENGTH_ERROR	3028	X'00000BD4'
MQRCCF QUIESCE_VALUE_ERROR	3029	X'00000BD5'
MQRCCF_MODE_VALUE_ERROR	3029	X'00000BD5'
MQRCCF_MSG_SEQ_NUMBER_ERROR	3030	X'00000BD6'
MQRCCF_PING_DATA_COUNT_ERROR	3031	X'00000BD7'
MQRCCF_PING_DATA_COMPARE_ERROR	3032	X'00000BD8'
MQRCCF_CFSL_PARM_ID_ERROR	3033	X'00000BD9'
MQRCCF_CHANNEL_TYPE_ERROR	3034	X'00000BDA'
MQRCCF_PARM_SEQUENCE_ERROR	3035	X'00000BDB'
MQRCCF_XMIT_PROTOCOL_TYPE_ERR	3036	X'00000BDC'
MQRCCF_BATCH_SIZE_ERROR	3037	X'00000BDD'
MQRCCF_DISC_INT_ERROR	3038	X'00000BDE'
MQRCCF_SHORT_RETRY_ERROR	3039	X'00000BDF'
MQRCCF_SHORT_TIMER_ERROR	3040	X'00000BE0'
MQRCCF_LONG_RETRY_ERROR	3041	X'00000BE1'
MQRCCF_LONG_TIMER_ERROR	3042	X'00000BE2'
MQRCCF_SEQ_NUMBER_WRAP_ERROR	3043	X'00000BE3'
MQRCCF_MAX_MSG_LENGTH_ERROR	3044	X'00000BE4'
MQRCCF_PUT_AUTH_ERROR	3045	X'00000BE5'
MQRCCF_PURGE_VALUE_ERROR	3046	X'00000BE6'
MQRCCF_CFIL_PARM_ID_ERROR	3047	X'00000BE7'
MQRCCF_MSG_TRUNCATED	3048	X'00000BE8'
MQRCCF_CCSID_ERROR	3049	X'00000BE9'
MQRCCF_ENCODING_ERROR	3050	X'00000BEA'
MQRCCF_QUEUES_VALUE_ERROR	3051	X'00000BEB'
MQRCCF_DATA_CONV_VALUE_ERROR	3052	X'00000BEC'
MQRCCF_INDOUBT_VALUE_ERROR	3053	X'00000BED'
MQRCCF_ESCAPE_TYPE_ERROR	3054	X'00000BEE'
MQRCCF_REPOS_VALUE_ERROR	3055	X'00000BEF'
MQRCCF_CHANNEL_TABLE_ERROR	3062	X'00000BF6'
MQRCCF_MCA_TYPE_ERROR	3063	X'00000BF7'
MQRCCF_CHL_INST_TYPE_ERROR	3064	X'00000BF8'
MQRCCF_CHL_STATUS_NOT_FOUND	3065	X'00000BF9'
MQRCCF_CFSL_DUPLICATE_PARM	3066	X'00000BFA'
MQRCCF_CFSL_TOTAL_LENGTH_ERROR	3067	X'00000BFB'
MQRCCF_CFSL_COUNT_ERROR	3068	X'00000BFC'
MQRCCF_CFSL_STRING_LENGTH_ERR	3069	X'00000BFD'
MQRCCF_BROKER_DELETED	3070	X'00000BFE'
MQRCCF_STREAM_ERROR	3071	X'00000BFF'
MQRCCF_TOPIC_ERROR	3072	X'00000C00'

MQRCCF_NOT_REGISTERED	3073	X'0000C01'
MQRCCF_Q_MGR_NAME_ERROR	3074	X'0000C02'
MQRCCF_INCORRECT_STREAM	3075	X'0000C03'
MQRCCF_Q_NAME_ERROR	3076	X'0000C04'
MQRCCF_NO_RETAINED_MSG	3077	X'0000C05'
MQRCCF_DUPLICATE_IDENTITY	3078	X'0000C06'
MQRCCF_INCORRECT_Q	3079	X'0000C07'
MQRCCF_CORREL_ID_ERROR	3080	X'0000C08'
MQRCCF_NOT_AUTHORIZED	3081	X'0000C09'
MQRCCF_UNKNOWN_STREAM	3082	X'0000C0A'
MQRCCF_REG_OPTIONS_ERROR	3083	X'0000C0B'
MQRCCF_PUB_OPTIONS_ERROR	3084	X'0000C0C'
MQRCCF_UNKNOWN_BROKER	3085	X'0000C0D'
MQRCCF_Q_MGR_CCSID_ERROR	3086	X'0000C0E'
MQRCCF_DEL_OPTIONS_ERROR	3087	X'0000C0F'
MQRCCF_CLUSTER_NAME_CONFLICT	3088	X'0000C10'
MQRCCF_REPOS_NAME_CONFLICT	3089	X'0000C11'
MQRCCF_CLUSTER_Q_USAGE_ERROR	3090	X'0000C12'
MQRCCF_ACTION_VALUE_ERROR	3091	X'0000C13'
MQRCCF_COMMS_LIBRARY_ERROR	3092	X'0000C14'
MQRCCF_NETBIOS_NAME_ERROR	3093	X'0000C15'
MQRCCF_BROKER_COMMAND_FAILED	3094	X'0000C16'
MQRCCF_CFST_CONFLICTING_PARM	3095	X'0000C17'
MQRCCF_PATH_NOT_VALID	3096	X'0000C18'
MQRCCF_PARM_SYNTAX_ERROR	3097	X'0000C19'
MQRCCF_PWD_LENGTH_ERROR	3098	X'0000C1A'
MQRCCF_FILTER_ERROR	3150	X'0000C4E'
MQRCCF_WRONG_USER	3151	X'0000C4F'
MQRCCF_DUPLICATE_SUBSCRIPTION	3152	X'0000C50'
MQRCCF_SUB_NAME_ERROR	3153	X'0000C51'
MQRCCF_SUB_IDENTITY_ERROR	3154	X'0000C52'
MQRCCF_SUBSCRIPTION_IN_USE	3155	X'0000C53'
MQRCCF_SUBSCRIPTION_LOCKED	3156	X'0000C54'
MQRCCF_ALREADY_JOINED	3157	X'0000C55'
MQRCCF_OBJECT_IN_USE	3160	X'0000C58'
MQRCCF_UNKNOWN_FILE_NAME	3161	X'0000C59'
MQRCCF_FILE_NOT_AVAILABLE	3162	X'0000C5A'
MQRCCF_DISC_RETRY_ERROR	3163	X'0000C5B'
MQRCCF_ALLOC_RETRY_ERROR	3164	X'0000C5C'
MQRCCF_ALLOC_SLOW_TIMER_ERROR	3165	X'0000C5D'
MQRCCF_ALLOC_FAST_TIMER_ERROR	3166	X'0000C5E'
MQRCCF_PORT_NUMBER_ERROR	3167	X'0000C5F'

MQRCCF_CHL_SYSTEM_NOT_ACTIVE	3168	X'00000C60'
MQRCCF_ENTITY_NAME_MISSING	3169	X'00000C61'
MQRCCF_PROFILE_NAME_ERROR	3170	X'00000C62'
MQRCCF_AUTH_VALUE_ERROR	3171	X'00000C63'
MQRCCF_AUTH_VALUE_MISSING	3172	X'00000C64'
MQRCCF_OBJECT_TYPE_MISSING	3173	X'00000C65'
MQRCCF_CONNECTION_ID_ERROR	3174	X'00000C66'
MQRCCF_LOG_TYPE_ERROR	3175	X'00000C67'
MQRCCF_PROGRAM_NOT_AVAILABLE	3176	X'00000C68'
MQRCCF_PROGRAM_AUTH_FAILED	3177	X'00000C69'
MQRCCF_NONE_FOUND	3200	X'00000C80'
MQRCCF_SECURITY_SWITCH_OFF	3201	X'00000C81'
MQRCCF_SECURITY_REFRESH_FAILED	3202	X'00000C82'
MQRCCF_PARM_CONFLICT	3203	X'00000C83'
MQRCCF_COMMAND_INHIBITED	3204	X'00000C84'
MQRCCF_OBJECT_BEING_DELETED	3205	X'00000C85'
MQRCCF_STORAGE_CLASS_IN_USE	3207	X'00000C87'
MQRCCF_OBJECT_NAME_RESTRICTED	3208	X'00000C88'
MQRCCF_OBJECT_LIMIT_EXCEEDED	3209	X'00000C89'
MQRCCF_OBJECT_OPEN_FORCE	3210	X'00000C8A'
MQRCCF_DISPOSITION_CONFLICT	3211	X'00000C8B'
MQRCCF_Q_MGR_NOT_IN_QSG	3212	X'00000C8C'
MQRCCF_ATTR_VALUE_FIXED	3213	X'00000C8D'
MQRCCF_NAMELIST_ERROR	3215	X'00000C8F'
MQRCCF_NO_CHANNEL_INITIATOR	3217	X'00000C91'
MQRCCF_CHANNEL_INITIATOR_ERROR	3218	X'00000C92'
MQRCCF_COMMAND_LEVEL_CONFLICT	3222	X'00000C96'
MQRCCF_Q_ATTR_CONFLICT	3223	X'00000C97'
MQRCCF_EVENTS_DISABLED	3224	X'00000C98'
MQRCCF_COMMAND_SCOPE_ERROR	3225	X'00000C99'
MQRCCF_COMMAND_REPLY_ERROR	3226	X'00000C9A'
MQRCCF_FUNCTION_RESTRICTED	3227	X'00000C9B'
MQRCCF_PARM_MISSING	3228	X'00000C9C'
MQRCCF_PARM_VALUE_ERROR	3229	X'00000C9D'
MQRCCF_COMMAND_LENGTH_ERROR	3230	X'00000C9E'
MQRCCF_COMMAND_ORIGIN_ERROR	3231	X'00000C9F'
MQRCCF_LISTENER_CONFLICT	3232	X'00000CA0'
MQRCCF_LISTENER_STARTED	3233	X'00000CA1'
MQRCCF_LISTENER_STOPPED	3234	X'00000CA2'
MQRCCF_CHANNEL_ERROR	3235	X'00000CA3'
MQRCCF_CF_STRUC_ERROR	3236	X'00000CA4'
MQRCCF_UNKNOWN_USER_ID	3237	X'00000CA5'

MQRCCF_UNEXPECTED_ERROR	3238	X'0000CA6'
MQRCCF_NO_XCF_PARTNER	3239	X'0000CA7'
MQRCCF_CFGR_PARM_ID_ERROR	3240	X'0000CA8'
MQRCCF_CFIF_LENGTH_ERROR	3241	X'0000CA9'
MQRCCF_CFIF_OPERATOR_ERROR	3242	X'0000CAA'
MQRCCF_CFIF_PARM_ID_ERROR	3243	X'0000CAB'
MQRCCF_CFSF_FILTER_VAL_LEN_ERR	3244	X'0000CAC'
MQRCCF_CFSF_LENGTH_ERROR	3245	X'0000CAD'
MQRCCF_CFSF_OPERATOR_ERROR	3246	X'0000CAE'
MQRCCF_CFSF_PARM_ID_ERROR	3247	X'0000CAF'
MQRCCF_TOO_MANY_FILTERS	3248	X'0000CB0'
MQRCCF_LISTENER_RUNNING	3249	X'0000CB1'
MQRCCF_LSTR_STATUS_NOT_FOUND	3250	X'0000CB2'
MQRCCF_SERVICE_RUNNING	3251	X'0000CB3'
MQRCCF_SERV_STATUS_NOT_FOUND	3252	X'0000CB4'
MQRCCF_SERVICE_STOPPED	3253	X'0000CB5'
MQRCCF_CFBS_DUPLICATE_PARM	3254	X'0000CB6'
MQRCCF_CFBS_LENGTH_ERROR	3255	X'0000CB7'
MQRCCF_CFBS_PARM_ID_ERROR	3256	X'0000CB8'
MQRCCF_CFBS_STRING_LENGTH_ERR	3257	X'0000CB9'
MQRCCF_CFGR_LENGTH_ERROR	3258	X'0000CBA'
MQRCCF_CFGR_PARM_COUNT_ERROR	3259	X'0000CBB'
MQRCCF_CONN_NOT_STOPPED	3260	X'0000CBC'
MQRCCF_SERVICE_REQUEST_PENDING	3261	X'0000CBD'
MQRCCF_NO_START_CMD	3262	X'0000CBE'
MQRCCF_NO_STOP_CMD	3263	X'0000CBF'
MQRCCF_CFBF_LENGTH_ERROR	3264	X'0000CC0'
MQRCCF_CFBF_PARM_ID_ERROR	3265	X'0000CC1'
MQRCCF_CFBF_OPERATOR_ERROR	3266	X'0000CC2'
MQRCCF_CFBF_FILTER_VAL_LEN_ERR	3267	X'0000CC3'
MQRCCF_LISTENER_STILL_ACTIVE	3268	X'0000CC4'
MQRCCF_TOPICSTR_ALREADY_EXISTS	3300	X'0000CE4'
MQRCCF_SHARING_CONVS_ERROR	3301	X'0000CE5'
MQRCCF_SHARING_CONVS_TYPE	3302	X'0000CE6'
MQRCCF_SECURITY_CASE_CONFLICT	3303	X'0000CE7'
MQRCCF_TOPIC_TYPE_ERROR	3305	X'0000CE9'
MQRCCF_MAX_INSTANCES_ERROR	3306	X'0000CEA'
MQRCCF_MAX_INSTS_PER_CLNT_ERR	3307	X'0000CEB'
MQRCCF_TOPIC_STRING_NOT_FOUND	3308	X'0000CEC'
MQRCCF_SUBSCRIPTION_POINT_ERR	3309	X'0000CED'
MQRCCF_SUB_ALREADY_EXISTS	3311	X'0000CEF'
MQRCCF_UNKNOWN_OBJECT_NAME	3312	X'0000CF0'

MQRCCF_REMOTE_Q_NAME_ERROR	3313	X'0000CF1'
MQRCCF_DURABILITY_NOT_ALLOWED	3314	X'0000CF2'
MQRCCF_HOBJ_ERROR	3315	X'0000CF3'
MQRCCF_DEST_NAME_ERROR	3316	X'0000CF4'
MQRCCF_INVALID_DESTINATION	3317	X'0000CF5'
MQRCCF_PUBSUB_INHIBITED	3318	X'0000CF6'
MQRCCF_OBJECT_ALREADY_EXISTS	4001	X'0000FA1'
MQRCCF_OBJECT_WRONG_TYPE	4002	X'0000FA2'
MQRCCF_LIKE_OBJECT_WRONG_TYPE	4003	X'0000FA3'
MQRCCF_OBJECT_OPEN	4004	X'0000FA4'
MQRCCF_ATTR_VALUE_ERROR	4005	X'0000FA5'
MQRCCF_UNKNOWN_Q_MGR	4006	X'0000FA6'
MQRCCF_Q_WRONG_TYPE	4007	X'0000FA7'
MQRCCF_OBJECT_NAME_ERROR	4008	X'0000FA8'
MQRCCF_ALLOCATE_FAILED	4009	X'0000FA9'
MQRCCF_HOST_NOT_AVAILABLE	4010	X'0000FAA'
MQRCCF_CONFIGURATION_ERROR	4011	X'0000FAB'
MQRCCF_CONNECTION_REFUSED	4012	X'0000FAC'
MQRCCF_ENTRY_ERROR	4013	X'0000FAD'
MQRCCF_SEND_FAILED	4014	X'0000FAE'
MQRCCF_RECEIVED_DATA_ERROR	4015	X'0000FAF'
MQRCCF_RECEIVE_FAILED	4016	X'0000FB0'
MQRCCF_CONNECTION_CLOSED	4017	X'0000FB1'
MQRCCF_NO_STORAGE	4018	X'0000FB2'
MQRCCF_NO_COMMS_MANAGER	4019	X'0000FB3'
MQRCCF_LISTENER_NOT_STARTED	4020	X'0000FB4'
MQRCCF_BIND_FAILED	4024	X'0000FB8'
MQRCCF_CHANNEL_INDOUBT	4025	X'0000FB9'
MQRCCF_MQCONN_FAILED	4026	X'0000FBA'
MQRCCF_MQOPEN_FAILED	4027	X'0000FBB'
MQRCCF_MQGET_FAILED	4028	X'0000FBC'
MQRCCF_MQPUT_FAILED	4029	X'0000FBD'
MQRCCF_PING_ERROR	4030	X'0000FBE'
MQRCCF_CHANNEL_IN_USE	4031	X'0000FBF'
MQRCCF_CHANNEL_NOT_FOUND	4032	X'0000FC0'
MQRCCF_UNKNOWN_REMOTE_CHANNEL	4033	X'0000FC1'
MQRCCF_REMOTE_QM_UNAVAILABLE	4034	X'0000FC2'
MQRCCF_REMOTE_QM_TERMINATING	4035	X'0000FC3'
MQRCCF_MQINQ_FAILED	4036	X'0000FC4'
MQRCCF_NOT_XMIT_Q	4037	X'0000FC5'
MQRCCF_CHANNEL_DISABLED	4038	X'0000FC6'
MQRCCF_USER_EXIT_NOT_AVAILABLE	4039	X'0000FC7'

MQRCCF_COMMIT_FAILED	4040	X'0000FC8'
MQRCCF_WRONG_CHANNEL_TYPE	4041	X'0000FC9'
MQRCCF_CHANNEL_ALREADY_EXISTS	4042	X'0000FCA'
MQRCCF_DATA_TOO_LARGE	4043	X'0000FCB'
MQRCCF_CHANNEL_NAME_ERROR	4044	X'0000FCC'
MQRCCF_XMIT_Q_NAME_ERROR	4045	X'0000FCD'
MQRCCF_MCA_NAME_ERROR	4047	X'0000FCF'
MQRCCF_SEND_EXIT_NAME_ERROR	4048	X'0000FD0'
MQRCCF_SEC_EXIT_NAME_ERROR	4049	X'0000FD1'
MQRCCF_MSG_EXIT_NAME_ERROR	4050	X'0000FD2'
MQRCCF_RCV_EXIT_NAME_ERROR	4051	X'0000FD3'
MQRCCF_XMIT_Q_NAME_WRONG_TYPE	4052	X'0000FD4'
MQRCCF_MCA_NAME_WRONG_TYPE	4053	X'0000FD5'
MQRCCF_DISC_INT_WRONG_TYPE	4054	X'0000FD6'
MQRCCF_SHORT_RETRY_WRONG_TYPE	4055	X'0000FD7'
MQRCCF_SHORT_TIMER_WRONG_TYPE	4056	X'0000FD8'
MQRCCF_LONG_RETRY_WRONG_TYPE	4057	X'0000FD9'
MQRCCF_LONG_TIMER_WRONG_TYPE	4058	X'0000FDA'
MQRCCF_PUT_AUTH_WRONG_TYPE	4059	X'0000FDB'
MQRCCF_KEEP_ALIVE_INT_ERROR	4060	X'0000FDC'
MQRCCF_MISSING_CONN_NAME	4061	X'0000FDD'
MQRCCF_CONN_NAME_ERROR	4062	X'0000FDE'
MQRCCF_MQSET_FAILED	4063	X'0000FDF'
MQRCCF_CHANNEL_NOT_ACTIVE	4064	X'0000FE0'
MQRCCF_TERMINATED_BY_SEC_EXIT	4065	X'0000FE1'
MQRCCF_DYNAMIC_Q_SCOPE_ERROR	4067	X'0000FE3'
MQRCCF_CELL_DIR_NOT_AVAILABLE	4068	X'0000FE4'
MQRCCF_MR_COUNT_ERROR	4069	X'0000FE5'
MQRCCF_MR_COUNT_WRONG_TYPE	4070	X'0000FE6'
MQRCCF_MR_EXIT_NAME_ERROR	4071	X'0000FE7'
MQRCCF_MR_EXIT_NAME_WRONG_TYPE	4072	X'0000FE8'
MQRCCF_MR_INTERVAL_ERROR	4073	X'0000FE9'
MQRCCF_MR_INTERVAL_WRONG_TYPE	4074	X'0000FEA'
MQRCCF_NPM_SPEED_ERROR	4075	X'0000FEB'
MQRCCF_NPM_SPEED_WRONG_TYPE	4076	X'0000FEC'
MQRCCF_HB_INTERVAL_ERROR	4077	X'0000FED'
MQRCCF_HB_INTERVAL_WRONG_TYPE	4078	X'0000FEE'
MQRCCF_CHAD_ERROR	4079	X'0000FEF'
MQRCCF_CHAD_WRONG_TYPE	4080	X'0000FF0'
MQRCCF_CHAD_EVENT_ERROR	4081	X'0000FF1'
MQRCCF_CHAD_EVENT_WRONG_TYPE	4082	X'0000FF2'
MQRCCF_CHAD_EXIT_ERROR	4083	X'0000FF3'

MQRCCF_CHAD_EXIT_WRONG_TYPE	4084	X'0000FF4'
MQRCCF_SUPPRESSED_BY_EXIT	4085	X'0000FF5'
MQRCCF_BATCH_INT_ERROR	4086	X'0000FF6'
MQRCCF_BATCH_INT_WRONG_TYPE	4087	X'0000FF7'
MQRCCF_NET_PRIORITY_ERROR	4088	X'0000FF8'
MQRCCF_NET_PRIORITY_WRONG_TYPE	4089	X'0000FF9'
MQRCCF_CHANNEL_CLOSED	4090	X'0000FFA'
MQRCCF_Q_STATUS_NOT_FOUND	4091	X'0000FFB'
MQRCCF_SSL_CIPHER_SPEC_ERROR	4092	X'0000FFC'
MQRCCF_SSL_PEER_NAME_ERROR	4093	X'0000FFD'
MQRCCF_SSL_CLIENT_AUTH_ERROR	4094	X'0000FFE'
MQRCCF_RETAINED_NOT_SUPPORTED	4095	X'0000FFF'

MQRCVTIME_* (Receive Timeout Types)

MQRCVTIME_MULTIPLY	0	X'00000000'
MQRCVTIME_ADD	1	X'00000001'
MQRCVTIME_EQUAL	2	X'00000002'

MQREADA_* (Read Ahead Values)

MQREADA_NO	0	X'00000000'
MQREADA_YES	1	X'00000001'
MQREADA_DISABLED	2	X'00000002'
MQREADA_INHIBITED	3	X'00000003'
MQREADA_BACKLOG	4	X'00000004'

MQRECORDING_* (Recording Options)

MQRECORDING_DISABLED	0	X'00000000'
MQRECORDING_Q	1	X'00000001'
MQRECORDING_MSG	2	X'00000002'

MQREGO_* (Publish/Subscribe Registration Options)

MQREGO_NONE	0	X'00000000'
MQREGO_CORREL_ID_AS_IDENTITY	1	X'00000001'
MQREGO_ANONYMOUS	2	X'00000002'
MQREGO_LOCAL	4	X'00000004'
MQREGO_DIRECT_REQUESTS	8	X'00000008'
MQREGO_NEW_PUBLICATIONS_ONLY	16	X'00000010'
MQREGO_PUBLISH_ON_REQUEST_ONLY	32	X'00000020'

MQREGO_DEREGISTER_ALL	64	X'00000040'
MQREGO_INCLUDE_STREAM_NAME	128	X'00000080'
MQREGO_INFORM_IF_RETAINED	256	X'00000100'
MQREGO_DUPLICATES_OK	512	X'00000200'
MQREGO_NON_PERSISTENT	1024	X'00000400'
MQREGO_PERSISTENT	2048	X'00000800'
MQREGO_PERSISTENT_AS_PUBLISH	4096	X'00001000'
MQREGO_PERSISTENT_AS_Q	8192	X'00002000'
MQREGO_ADD_NAME	16384	X'00004000'
MQREGO_NO_ALTERATION	32768	X'00008000'
MQREGO_FULL_RESPONSE	65536	X'00010000'
MQREGO_JOIN_SHARED	131072	X'00020000'
MQREGO_JOIN_EXCLUSIVE	262144	X'00040000'
MQREGO_LEAVE_ONLY	524288	X'00080000'
MQREGO_VARIABLE_USER_ID	1048576	X'00100000'
MQREGO_LOCKED	2097152	X'00200000'

MQRFH_* (Rules and formatting header structure)

MQRFH_STRUC_ID	"RFhb"	
MQRFH_STRUC_ID_ARRAY	'R','F','H','b'	
MQRFH_VERSION_1	1	X'00000001'
MQRFH_VERSION_2	2	X'00000002'
MQRFH_STRUC_LENGTH_FIXED	32	X'00000020'
MQRFH_STRUC_LENGTH_FIXED_2	36	X'00000024'

MQRFH_* (Rules and formatting header Flags)

MQRFH_NONE	0	X'00000000'
MQRFH_NO_FLAGS	0	X'00000000'

MQRFH2_* (Publish/Subscribe Options Tag RFH2 Top-level folder Tags)

MQRFH2_NAME_VALUE_VERSION	1	X'00000001'
---------------------------	---	-------------

MQRFH2_* (Publish/Subscribe Options Tag Tag names)

MQRFH2_PUBSUB_CMD_FOLDER	"psc"	
MQRFH2_PUBSUB_RESP_FOLDER	"pscr"	
MQRFH2_MSG_CONTENT_FOLDER	"mcd"	

MQRFH2_USER_FOLDER	"usr"	
--------------------	-------	--

MQRFH2_* (Publish/Subscribe Options Tag XML tag names)

MQRFH2_PUBSUB_CMD_FOLDER_B	"<psc>"	
MQRFH2_PUBSUB_CMD_FOLDER_E	"</psc>"	
MQRFH2_PUBSUB_RESP_FOLDER_B	"<pscr>"	
MQRFH2_PUBSUB_RESP_FOLDER_E	"</pscr>"	
MQRFH2_MSG_CONTENT_FOLDER_B	"<mcd>"	
MQRFH2_MSG_CONTENT_FOLDER_E	"</mcd>"	
MQRFH2_USER_FOLDER_B	"<usr>"	
MQRFH2_USER_FOLDER_E	"</usr>"	

MQRL_* (Returned Length)

MQRL_UNDEFINED		-1	X'FFFFFFFF'
----------------	--	----	-------------

MQRMH_* (Reference message header structure)

MQRMH_STRUC_ID	"RMhb"		
MQRMH_STRUC_ID_ARRAY	'R','M','H','b'		
MQRMH_VERSION_1		1	X'00000001'
MQRMH_CURRENT_VERSION		1	X'00000001'

MQRMHF_* (Reference message header Flags)

MQRMHF_LAST		1	X'00000001'
MQRMHF_NOT_LAST		0	X'00000000'

MQRO_* (Report Options)

MQRO_EXCEPTION		16777216	X'01000000'
MQRO_EXCEPTION_WITH_DATA		50331648	X'03000000'
MQRO_EXCEPTION_WITH_FULL_DATA		117440512	X'07000000'
MQRO_EXPIRATION		2097152	X'00200000'
MQRO_EXPIRATION_WITH_DATA		6291456	X'00600000'
MQRO_EXPIRATION_WITH_FULL_DATA		14680064	X'00E00000'
MQRO_COA		256	X'00000100'
MQRO_COA_WITH_DATA		768	X'00000300'
MQRO_COA_WITH_FULL_DATA		1792	X'00000700'
MQRO_COD		2048	X'00000800'

MQRO_COD_WITH_DATA	6144	X'00001800'
MQRO_COD_WITH_FULL_DATA	14336	X'00003800'
MQRO_PAN	1	X'00000001'
MQRO_NAN	2	X'00000002'
MQRO_ACTIVITY	4	X'00000004'
MQRO_NEW_MSG_ID	0	X'00000000'
MQRO_PASS_MSG_ID	128	X'00000080'
MQRO_COPY_MSG_ID_TO_CORREL_ID	0	X'00000000'
MQRO_PASS_CORREL_ID	64	X'00000040'
MQRO_DEAD_LETTER_Q	0	X'00000000'
MQRO_DISCARD_MSG	134217728	X'08000000'
MQRO_PASS_DISCARD_AND_EXPIRY	16384	X'00004000'
MQRO_NONE	0	X'00000000'

MQRO_* (Report Options Masks)

MQRO_REJECT_UNSUP_MASK	270270464	X'101C0000'
MQRO_ACCEPT_UNSUP_MASK	-270532353	X'EFE000FF'
MQRO_ACCEPT_UNSUP_IF_XMIT_MASK	261888	X'0003FF00'

MQROUTE_* (Trace-route Max Activities (MQIACF_MAX_ACTIVITIES))

MQROUTE_UNLIMITED_ACTIVITIES	0	X'00000000'
------------------------------	---	-------------

MQROUTE_* (Trace-route Detail (MQIACF_ROUTE_DETAIL))

MQROUTE_DETAIL_LOW	2	X'00000002'
MQROUTE_DETAIL_MEDIUM	8	X'00000008'
MQROUTE_DETAIL_HIGH	32	X'00000020'

MQROUTE_* (Trace-route Forwarding (MQIACF_ROUTE_FORWARDING))

MQROUTE_FORWARD_ALL	256	X'00000100'
MQROUTE_FORWARD_IF_SUPPORTED	512	X'00000200'
MQROUTE_FORWARD_REJ_UNSUP_MASK	-65536	X'FFFF0000'

MQROUTE_* (Trace-route Delivery (MQIACF_ROUTE_DELIVERY))

MQROUTE_DELIVER_YES	4096	X'00001000'
MQROUTE_DELIVER_NO	8192	X'00002000'
MQROUTE_DELIVER_REJ_UNSUP_MASK	-65536	X'FFFF0000'

MROUTE_* (Trace-route Accumulation (MQIACF_ROUTE_ACCUMULATION))

MROUTE_ACCUMULATE_NONE	65539	X'00010003'
MROUTE_ACCUMULATE_IN_MSG	65540	X'00010004'
MROUTE_ACCUMULATE_AND_REPLY	65541	X'00010005'

MGRP_* (Command format Replace Options)

MGRP_YES	1	X'00000001'
MGRP_NO	0	X'00000000'

MQRQ_* (Command format Reason Qualifiers)

MQRQ_CONN_NOT_AUTHORIZED	1	X'00000001'
MQRQ_OPEN_NOT_AUTHORIZED	2	X'00000002'
MQRQ_CLOSE_NOT_AUTHORIZED	3	X'00000003'
MQRQ_CMD_NOT_AUTHORIZED	4	X'00000004'
MQRQ_Q_MGR_STOPPING	5	X'00000005'
MQRQ_Q_MGR QUIESCING	6	X'00000006'
MQRQ_CHANNEL_STOPPED_OK	7	X'00000007'
MQRQ_CHANNEL_STOPPED_ERROR	8	X'00000008'
MQRQ_CHANNEL_STOPPED_RETRY	9	X'00000009'
MQRQ_CHANNEL_STOPPED_DISABLED	10	X'0000000A'
MQRQ_BRIDGE_STOPPED_OK	11	X'0000000B'
MQRQ_BRIDGE_STOPPED_ERROR	12	X'0000000C'
MQRQ_SSL_HANDSHAKE_ERROR	13	X'0000000D'
MQRQ_SSL_CIPHER_SPEC_ERROR	14	X'0000000E'
MQRQ_SSL_CLIENT_AUTH_ERROR	15	X'0000000F'
MQRQ_SSL_PEER_NAME_ERROR	16	X'00000010'
MQRQ_SUB_NOT_AUTHORIZED	17	X'00000011'
MQRQ_SUB_DEST_NOT_AUTHORIZED	18	X'00000012'

MQRT_* (Command format Refresh Types)

MQRT_CONFIGURATION	1	X'00000001'
MQRT_EXPIRY	2	X'00000002'
MQRT_NSPROC	3	X'00000003'
MQRT_PROXYSUB	4	X'00000004'

MQRU_* (Request Only)

MQRU_PUBLISH_ON_REQUEST	1	X'00000001'
MQRU_PUBLISH_ALL	2	X'00000002'

MQSCA_* (SSL Client Authentication)

MQSCA_REQUIRED	0	X'00000000'
MQSCA_OPTIONAL	1	X'00000001'

MQSCO_* (SSL configuration options structure)

MQSCO_STRUC_ID	"SC0b"	
MQSCO_STRUC_ID_ARRAY	'S','C','0','b'	
MQSCO_VERSION_1	1	X'00000001'
MQSCO_VERSION_2	2	X'00000002'
MQSCO_CURRENT_VERSION	2	X'00000002'

MQSCO_* (SSL configuration options Key Reset Count)

MQSCO_RESET_COUNT_DEFAULT	0	X'00000000'
---------------------------	---	-------------

MQSCO_* (Command format Queue Definition Scope)

MQSCO_Q_MGR	1	X'00000001'
MQSCO_CELL	2	X'00000002'

MQSCOPE_* (Publish scope)

MQSCOPE_ALL	0	X'00000000'
MQSCOPE_AS_PARENT	1	X'00000001'
MQSCOPE_QMGR	4	X'00000004'

MQSCYC_* (Security Case)

MQSCYC_UPPER	0	X'00000000'
MQSCYC_MIXED	1	X'00000001'

MQSD_* (Object descriptor structure)

MQSD_STRUC_ID	"SDbb"	
MQSD_STRUC_ID_ARRAY	'S','D','b','b'	

MQSD_VERSION_1	1	X'00000001'
MQSD_CURRENT_VERSION	1	X'00000001'

MQSECITEM_* (Command format Security Items)

MQSECITEM_ALL	0	X'00000000'
MQSECITEM_MQADMIN	1	X'00000001'
MQSECITEM_MQNLIST	2	X'00000002'
MQSECITEM_MQPROC	3	X'00000003'
MQSECITEM_MQQUEUE	4	X'00000004'
MQSECITEM_MQCONN	5	X'00000005'
MQSECITEM_MQCMD5	6	X'00000006'
MQSECITEM_MXADMIN	7	X'00000007'
MQSECITEM_MXNLIST	8	X'00000008'
MQSECITEM_MXPROC	9	X'00000009'
MQSECITEM_MXQUEUE	10	X'0000000A'
MQSECITEM_MXTOPIC	11	X'0000000B'

MQSECSW_* (Command format Security Switches)

MQSECSW_PROCESS	1	X'00000001'
MQSECSW_NAMELIST	2	X'00000002'
MQSECSW_Q	3	X'00000003'
MQSECSW_TOPIC	4	X'00000004'
MQSECSW_CONTEXT	6	X'00000006'
MQSECSW_ALTERNATE_USER	7	X'00000007'
MQSECSW_COMMAND	8	X'00000008'
MQSECSW_CONNECTION	9	X'00000009'
MQSECSW_SUBSYSTEM	10	X'0000000A'
MQSECSW_COMMAND_RESOURCES	11	X'0000000B'
MQSECSW_Q_MGR	15	X'0000000F'
MQSECSW_QSG	16	X'00000010'

MQSECSW_* (Command format Security Switch States)

MQSECSW_OFF_FOUND	21	X'00000015'
MQSECSW_ON_FOUND	22	X'00000016'
MQSECSW_OFF_NOT_FOUND	23	X'00000017'
MQSECSW_ON_NOT_FOUND	24	X'00000018'
MQSECSW_OFF_ERROR	25	X'00000019'
MQSECSW_ON_OVERRIDDEN	26	X'0000001A'

MQSECTYPE_* (Command format Security Types)

MQSECTYPE_AUTHSERV	1	X'00000001'
MQSECTYPE_SSL	2	X'00000002'
MQSECTYPE_CLASSES	3	X'00000003'

MQSEG_* (Segmentation)

MQSEG_INHIBITED	'b'	
MQSEG_ALLOWED	'A'	

MQSEL_* (Special Selector Values)

MQSEL_ANY_SELECTOR	-30001	X'FFFF8ACF'
MQSEL_ANY_USER_SELECTOR	-30002	X'FFFF8ACE'
MQSEL_ANY_SYSTEM_SELECTOR	-30003	X'FFFF8ACD'
MQSEL_ALL_SELECTORS	-30001	X'FFFF8ACF'
MQSEL_ALL_USER_SELECTORS	-30002	X'FFFF8ACE'
MQSEL_ALL_SYSTEM_SELECTORS	-30003	X'FFFF8ACD'

MQSID_* (Security Identifier)

MQSID_NONE	X'00...00'	(40 nulls)
MQSID_NONE_ARRAY	'\0','\0',...	(40 nulls)

MQSIDT_* (Security Identifier Types)

MQSIDT_NONE	X'00'	
MQSIDT_NT_SECURITY_ID	X'01'	
MQSIDT_WAS_SECURITY_ID	X'02'	

MQSMPO_* (Set message property options structure)

MQSMPO_STRUC_ID	"SMPO"	
MQSMPO_STRUC_ID_ARRAY	'S','M','P','O'	
MQSMPO_VERSION_1	1	X'00000001'
MQSMPO_CURRENT_VERSION	1	X'00000001'

MQSMPO_* (Set Message Property Options)

MQSMPO_SET_FIRST	0	X'00000000'
------------------	---	-------------

MQSMPO_SET_PROP_UNDER_CURSOR	1	X'00000001'
MQSMPO_SET_PROP_AFTER_CURSOR	2	X'00000002'
MQSMPO_APPEND_PROPERTY	4	X'00000004'
MQSMPO_SET_PROP_BEFORE_CURSOR	8	X'00000008'
MQSMPO_NONE	0	X'00000000'

MQSO_* (Subscribe Options)

MQSO_NONE	0	X'00000000'
MQSO_NON_DURABLE	0	X'00000000'
MQSO_READ_AHEAD_AS_Q_DEF	0	X'00000000'
MQSO_ALTER	1	X'00000001'
MQSO_CREATE	2	X'00000002'
MQSO_RESUME	4	X'00000004'
MQSO_DURABLE	8	X'00000008'
MQSO_GROUP_SUB	16	X'00000010'
MQSO_MANAGED	32	X'00000020'
MQSO_SET_IDENTITY_CONTEXT	64	X'00000040'
MQSO_FIXED_USERID	256	X'00000100'
MQSO_ANY_USERID	512	X'00000200'
MQSO_PUBLICATIONS_ON_REQUEST	2048	X'00000800'
MQSO_NEW_PUBLICATIONS_ONLY	4096	X'00001000'
MQSO_FAIL_IF QUIESCING	8192	X'00002000'
MQSO_ALTERNATE_USER_AUTHORITY	262144	X'00040000'
MQSO_WILDCARD_CHAR	1048576	X'00100000'
MQSO_WILDCARD_TOPIC	2097152	X'00200000'
MQSO_SET_CORREL_ID	4194304	X'00400000'
MQSO_SCOPE_QMGR	67108864	X'04000000'
MQSO_NO_READ_AHEAD	134217728	X'08000000'
MQSO_READ_AHEAD	268435456	X'10000000'

MQSP_* (Syncpoint Availability)

MQSP_AVAILABLE	1	X'00000001'
MQSP_NOT_AVAILABLE	0	X'00000000'

MQSQM_* (Shared Queue Queue Manager Name)

MQSQM_USE	0	X'00000000'
MQSQM_IGNORE	1	X'00000001'

MQSR_* (Action)

MQSR_ACTION_PUBLICATION	1	X'00000001'
-------------------------	---	-------------

MQSRO_* (Subscription request options structure)

MQSRO_STRUC_ID	"SR0b"	
MQSRO_STRUC_ID_ARRAY	'S','R','0','b'	
MQSRO_VERSION_1	1	X'00000001'
MQSRO_CURRENT_VERSION	1	X'00000001'
MQSRO_NONE	0	X'00000000'
MQSRO_FAIL_IF QUIESCING	8192	X'00002000'

MQSS_* (Segment Status)

MQSS_NOT_A_SEGMENT	'b'	
MQSS_SEGMENT	'S'	
MQSS_LAST_SEGMENT	'L'	

MQSSL_* (SSL FIPS Requirements)

MQSSL_FIPS_NO	0	X'00000000'
MQSSL_FIPS_YES	1	X'00000001'

MQSTAT_* (Stat Options)

MQSTAT_TYPE_ASYNC_ERROR	0	X'00000000'
-------------------------	---	-------------

MQSTS_* (Status reporting structure structure)

MQSTS_STRUC_ID	"STAT"	
MQSTS_STRUC_ID_ARRAY	'S','T','A','T'	
MQSTS_VERSION_1	1	X'00000001'
MQSTS_CURRENT_VERSION	1	X'00000001'

MQSUB_* (Durable subscriptions)

MQSUB_DURABLE_AS_PARENT	0	X'00000000'
MQSUB_DURABLE_ALLOWED	1	X'00000001'
MQSUB_DURABLE_INHIBITED	2	X'00000002'

MQSUB_* (Durable Subscriptions)

MQSUB_DURABLE_ALL	-1	X'FFFFFFFF'
MQSUB_DURABLE_YES	1	X'00000001'
MQSUB_DURABLE_NO	2	X'00000002'

MQSUBTYPE_* (Command format Subscription Types)

MQSUBTYPE_API	1	X'00000001'
MQSUBTYPE_ADMIN	2	X'00000002'
MQSUBTYPE_PROXY	3	X'00000003'
MQSUBTYPE_ALL	-1	X'FFFFFFFF'
MQSUBTYPE_USER	-2	X'FFFFFFFE'

MQSUS_* (Command format Suspend Status)

MQSUS_YES	1	X'00000001'
MQSUS_NO	0	X'00000000'

MQSVC_* (Service Types)

MQSVC_TYPE_COMMAND	0	X'00000000'
MQSVC_TYPE_SERVER	1	X'00000001'

MQSVC_* (Service Controls)

MQSVC_CONTROL_Q_MGR	0	X'00000000'
MQSVC_CONTROL_Q_MGR_START	1	X'00000001'
MQSVC_CONTROL_MANUAL	2	X'00000002'

MQSVC_* (Service Status)

MQSVC_STATUS_STOPPED	0	X'00000000'
MQSVC_STATUS_STARTING	1	X'00000001'
MQSVC_STATUS_RUNNING	2	X'00000002'
MQSVC_STATUS_STOPPING	3	X'00000003'
MQSVC_STATUS_RETRYING	4	X'00000004'

MQSYNCPOINT_* (Command format Syncpoint values for Pub/Sub migration)

MQSYNCPOINT_YES	0	X'00000000'
-----------------	---	-------------

MQSYNCPPOINT_IFPER	1	X'00000001'
--------------------	---	-------------

MQSYSP_* (Command format System Parameter Values)

MQSYSP_NO	0	X'00000000'
MQSYSP_YES	1	X'00000001'
MQSYSP_EXTENDED	2	X'00000002'
MQSYSP_TYPE_INITIAL	10	X'0000000A'
MQSYSP_TYPE_SET	11	X'0000000B'
MQSYSP_TYPE_LOG_COPY	12	X'0000000C'
MQSYSP_TYPE_LOG_STATUS	13	X'0000000D'
MQSYSP_TYPE_ARCHIVE_TAPE	14	X'0000000E'
MQSYSP_ALLOC_BLK	20	X'00000014'
MQSYSP_ALLOC_TRK	21	X'00000015'
MQSYSP_ALLOC_CYL	22	X'00000016'
MQSYSP_STATUS_BUSY	30	X'0000001E'
MQSYSP_STATUS_PREMOUNT	31	X'0000001F'
MQSYSP_STATUS_AVAILABLE	32	X'00000020'
MQSYSP_STATUS_UNKNOWN	33	X'00000021'
MQSYSP_STATUS_ALLOC_ARCHIVE	34	X'00000022'
MQSYSP_STATUS_COPYING_BSDS	35	X'00000023'
MQSYSP_STATUS_COPYING_LOG	36	X'00000024'

MQTA_* (Wildcards)

MQTA_BLOCK	1	X'00000001'
MQTA_PASSTHRU	2	X'00000002'

MQTA_* (Subscriptions Allowed)

MQTA_SUB_AS_PARENT	0	X'00000000'
MQTA_SUB_INHIBITED	1	X'00000001'
MQTA_SUB_ALLOWED	2	X'00000002'

MQTA_* (Proxy Sub Propagation)

MQTA_PROXY_SUB_FORCE	1	X'00000001'
MQTA_PROXY_SUB_FIRSTUSE	2	X'00000002'

MQTA_* (Publications Allowed)

MQTA_PUB_AS_PARENT	0	X'00000000'
--------------------	---	-------------

MQTA_PUB_INHIBITED	1	X'00000001'
MQTA_PUB_ALLOWED	2	X'00000002'

MQTC_* (Trigger Controls)

MQTC_OFF	0	X'00000000'
MQTC_ON	1	X'00000001'

MQTCPKEEP_* (TCP Keepalive)

MQTCPKEEP_NO	0	X'00000000'
MQTCPKEEP_YES	1	X'00000001'

MQTCPSTACK_* (TCP Stack Types)

MQTCPSTACK_SINGLE	0	X'00000000'
MQTCPSTACK_MULTIPLE	1	X'00000001'

MQTIME_* (Command format Time units)

MQTIME_UNIT_MINS	0	X'00000000'
MQTIME_UNIT_SECS	1	X'00000001'

MQTM_* (Trigger message structure)

MQTM_STRUC_ID	"TMbb"	
MQTM_STRUC_ID_ARRAY	'T','M','b','b'	
MQTM_VERSION_1	1	X'00000001'
MQTM_CURRENT_VERSION	1	X'00000001'

MQTMC_* (Trigger message character format structure)

MQTMC_STRUC_ID	"TMCb"	
MQTMC_STRUC_ID_ARRAY	'T','M','C','b'	
MQTMC_VERSION_1	"bbb1"	
MQTMC_VERSION_2	"bbb2"	
MQTMC_CURRENT_VERSION	"bbb2"	
MQTMC_VERSION_1_ARRAY	'b','b','b','1'	
MQTMC_VERSION_2_ARRAY	'b','b','b','2'	
MQTMC_CURRENT_VERSION_ARRAY	'b','b','b','2'	

MQTOPT_* (Topic Type)

MQTOPT_LOCAL	0	X'00000000'
MQTOPT_CLUSTER	1	X'00000001'
MQTOPT_ALL	2	X'00000002'

MQTRAXSTR_* (Channel Initiator Trace Autostart)

MQTRAXSTR_NO	0	X'00000000'
MQTRAXSTR_YES	1	X'00000001'

MQTSCOPE_* (Subscription Scope)

MQTSCOPE_QMGR	1	X'00000001'
MQTSCOPE_ALL	2	X'00000002'

MQTT_* (Trigger Types)

MQTT_NONE	0	X'00000000'
MQTT_FIRST	1	X'00000001'
MQTT_EVERY	2	X'00000002'
MQTT_DEPTH	3	X'00000003'

MQTYPE_* (Property data types)

MQTYPE_AS_SET	0	X'00000000'
MQTYPE_NULL	2	X'00000002'
MQTYPE_BOOLEAN	4	X'00000004'
MQTYPE_BYTE_STRING	8	X'00000008'
MQTYPE_INT8	16	X'00000010'
MQTYPE_INT16	32	X'00000020'
MQTYPE_INT32	64	X'00000040'
MQTYPE_LONG	64	X'00000040'
MQTYPE_INT64	128	X'00000080'
MQTYPE_FLOAT32	256	X'00000100'
MQTYPE_FLOAT64	512	X'00000200'
MQTYPE_STRING	1024	X'00000400'

MQUA_* (Publish/Subscribe User Attribute Selectors)

MQUA_FIRST	65536	X'00010000'
MQUA_LAST	99999999	X'3B9AC9FF'

MQUIDSUPP_* (Command format User ID Support)

MQUIDSUPP_NO	0	X'00000000'
MQUIDSUPP_YES	1	X'00000001'

MQUNDELIVERED_* (Command format Undelivered values for Pub/Sub migration)

MQUNDELIVERED_NORMAL	0	X'00000000'
MQUNDELIVERED_SAFE	1	X'00000001'
MQUNDELIVERED_DISCARD	2	X'00000002'
MQUNDELIVERED_KEEP	3	X'00000003'

MQUOWST_* (Command format UOW States)

MQUOWST_NONE	0	X'00000000'
MQUOWST_ACTIVE	1	X'00000001'
MQUOWST_PREPARED	2	X'00000002'
MQUOWST_UNRESOLVED	3	X'00000003'

MQUOWT_* (Command format UOW Types)

MQUOWT_Q_MGR	0	X'00000000'
MQUOWT_CICS	1	X'00000001'
MQUOWT_RRS	2	X'00000002'
MQUOWT_IMS	3	X'00000003'
MQUOWT_XA	4	X'00000004'

MQUS_* (Queue Usages)

MQUS_NORMAL	0	X'00000000'
MQUS_TRANSMISSION	1	X'00000001'

MQUSAGE_* (Command format Page Set Usage Values)

MQUSAGE_PS_AVAILABLE	0	X'00000000'
MQUSAGE_PS_DEFINED	1	X'00000001'
MQUSAGE_PS_OFFLINE	2	X'00000002'
MQUSAGE_PS_NOT_DEFINED	3	X'00000003'
MQUSAGE_EXPAND_USER	1	X'00000001'
MQUSAGE_EXPAND_SYSTEM	2	X'00000002'
MQUSAGE_EXPAND_NONE	3	X'00000003'

MQUSAGE_* (Command format Data Set Usage Values)

MQUSAGE_DS_OLDEST_ACTIVE_UOW	10	X'0000000A'
MQUSAGE_DS_OLDEST_PS_RECOVERY	11	X'0000000B'
MQUSAGE_DS_OLDEST_CF_RECOVERY	12	X'0000000C'

MQVL_* (%%#con\$ params ValueLength - mqsetmp)

MQVL_NULL_TERMINATED	-1	X'FFFFFFFF'
MQVL_EMPTY_STRING	0	X'00000000'

MQVU_* (Variable User ID)

MQVU_FIXED_USER	1	X'00000001'
MQVU_ANY_USER	2	X'00000002'

MQWDR_* (Cluster workload exit destination record structure)

MQWDR_STRUC_ID	"WDRb"	
MQWDR_STRUC_ID_ARRAY	'W','D','R','b'	
MQWDR_VERSION_1	1	X'00000001'
MQWDR_VERSION_2	2	X'00000002'
MQWDR_CURRENT_VERSION	2	X'00000002'
MQWDR_LENGTH_1	124	X'0000007C'
MQWDR_LENGTH_2	136	X'00000088'
MQWDR_CURRENT_LENGTH	136	X'00000088'

MQWI_* (Wait Interval)

MQWI_UNLIMITED	-1	X'FFFFFFFF'
----------------	----	-------------

MQWIH_* (Workload information header structure)

MQWIH_STRUC_ID	"WIHb"	
MQWIH_STRUC_ID_ARRAY	'W','I','H','b'	
MQWIH_VERSION_1	1	X'00000001'
MQWIH_CURRENT_VERSION	1	X'00000001'
MQWIH_LENGTH_1	120	X'00000078'
MQWIH_CURRENT_LENGTH	120	X'00000078'

MQWIH_* (Workload information header Flags)

MQWIH_NONE	0	X'00000000'
------------	---	-------------

MQWQR_* (Cluster workload exit queue record structure)

MQWQR_STRUC_ID	"WQRb"	
MQWQR_STRUC_ID_ARRAY	'W','Q','R','b'	
MQWQR_VERSION_1	1	X'00000001'
MQWQR_VERSION_2	2	X'00000002'
MQWQR_VERSION_3	3	X'00000003'
MQWQR_CURRENT_VERSION	3	X'00000003'
MQWQR_LENGTH_1	200	X'000000C8'
MQWQR_LENGTH_2	208	X'000000D0'
MQWQR_LENGTH_3	212	X'000000D4'
MQWQR_CURRENT_LENGTH	212	X'000000D4'

MQWS_* (Wildcard Schema)

MQWS_DEFAULT	0	X'00000000'
MQWS_CHAR	1	X'00000001'
MQWS_TOPIC	2	X'00000002'

MQWXP_* (Cluster workload exit parameter structure)

MQWXP_STRUC_ID	"WXPb"	
MQWXP_STRUC_ID_ARRAY	'W','X','P','b'	
MQWXP_VERSION_1	1	X'00000001'
MQWXP_VERSION_2	2	X'00000002'
MQWXP_VERSION_3	3	X'00000003'
MQWXP_CURRENT_VERSION	3	X'00000003'

MQWXP_* (Cluster Workload Flags)

MQWXP_PUT_BY_CLUSTER_CHL	2	X'00000002'
--------------------------	---	-------------

MQXACT_* (API Caller Types)

MQXACT_EXTERNAL	1	X'00000001'
MQXACT_INTERNAL	2	X'00000002'

MQXC_* (Exit Commands)

MQXC_MQOPEN	1	X'00000001'
MQXC_MQCLOSE	2	X'00000002'
MQXC_MQGET	3	X'00000003'
MQXC_MQPUT	4	X'00000004'
MQXC_MQPUT1	5	X'00000005'
MQXC_MQINQ	6	X'00000006'
MQXC_MQSET	8	X'00000008'
MQXC_MQBACK	9	X'00000009'
MQXC_MQCMIT	10	X'0000000A'

MQXCC_* (Exit Responses)

MQXCC_OK	0	X'00000000'
MQXCC_SUPPRESS_FUNCTION	-1	X'FFFFFFFF'
MQXCC_SKIP_FUNCTION	-2	X'FFFFFFFE'
MQXCC_SEND_AND_REQUEST_SEC_MSG	-3	X'FFFFFFFD'
MQXCC_SEND_SEC_MSG	-4	X'FFFFFFFC'
MQXCC_SUPPRESS_EXIT	-5	X'FFFFFFFB'
MQXCC_CLOSE_CHANNEL	-6	X'FFFFFFFA'
MQXCC_REQUEST_ACK	-7	X'FFFFFFF9'
MQXCC_FAILED	-8	X'FFFFFFF8'

MQXDR_* (Exit Response)

MQXDR_OK	0	X'00000000'
MQXDR_CONVERSION_FAILED	1	X'00000001'

MQXE_* (Environments)

MQXE_OTHER	0	X'00000000'
MQXE_MCA	1	X'00000001'
MQXE_MCA_SVRCONN	2	X'00000002'
MQXE_COMMAND_SERVER	3	X'00000003'
MQXE_MQSC	4	X'00000004'

MQXEPO_* (Register Entry Point Options structure)

MQXEPO_STRUC_ID	"XEPO"	
MQXEPO_STRUC_ID_ARRAY	'X','E','P','O'	
MQXEPO_VERSION_1		1 X'00000001'

MQXEPO_CURRENT_VERSION	1	X'00000001'
------------------------	---	-------------

MQXEPO_* (Exit Options)

MQXEPO_NONE	0	X'00000000'
-------------	---	-------------

MQXF_* (API Function Identifiers)

MQXF_INIT	1	X'00000001'
MQXF_TERM	2	X'00000002'
MQXF_CONN	3	X'00000003'
MQXF_CONNX	4	X'00000004'
MQXF_DISC	5	X'00000005'
MQXF_OPEN	6	X'00000006'
MQXF_CLOSE	7	X'00000007'
MQXF_PUT1	8	X'00000008'
MQXF_PUT	9	X'00000009'
MQXF_GET	10	X'0000000A'
MQXF_DATA_CONV_ON_GET	11	X'0000000B'
MQXF_INQ	12	X'0000000C'
MQXF_SET	13	X'0000000D'
MQXF_BEGIN	14	X'0000000E'
MQXF_CMIT	15	X'0000000F'
MQXF_BACK	16	X'00000010'
MQXF_STAT	18	X'00000012'
MQXF_CB	19	X'00000013'
MQXF_CTL	20	X'00000014'
MQXF_CALLBACK	21	X'00000015'
MQXF_SUB	22	X'00000016'
MQXF_SUBRQ	23	X'00000017'

MQXP_* (API crossing exit parameter structure)

MQXP_STRUC_ID	"XPbb"	
MQXP_STRUC_ID_ARRAY	'X','P','b','b'	
MQXP_VERSION_1	1	X'00000001'

MQXPDA_* (Problem Determination Area)

MQXPDA_NONE	X'00...00'	(48 nulls)
MQXPDA_NONE_ARRAY	'\0','\0',...	(48 nulls)

MQXPT_* (Transport Types)

MQXPT_ALL	-1	X'FFFFFFFF'
MQXPT_LOCAL	0	X'00000000'
MQXPT_LU62	1	X'00000001'
MQXPT_TCP	2	X'00000002'
MQXPT_NETBIOS	3	X'00000003'
MQXPT_SPX	4	X'00000004'
MQXPT_DECNET	5	X'00000005'
MQXPT_UDP	6	X'00000006'

MQXQH_* (Transmission queue header structure)

MQXQH_STRUC_ID	"XQHb"	
MQXQH_STRUC_ID_ARRAY	'X','Q','H','b'	
MQXQH_VERSION_1	1	X'00000001'
MQXQH_CURRENT_VERSION	1	X'00000001'

MQXR_* (Exit Reasons)

MQXR_BEFORE	1	X'00000001'
MQXR_AFTER	2	X'00000002'
MQXR_CONNECTION	3	X'00000003'
MQXR_INIT	11	X'0000000B'
MQXR_TERM	12	X'0000000C'
MQXR_MSG	13	X'0000000D'
MQXR_XMIT	14	X'0000000E'
MQXR_SEC_MSG	15	X'0000000F'
MQXR_INIT_SEC	16	X'00000010'
MQXR_RETRY	17	X'00000011'
MQXR_AUTO_CLUSSDR	18	X'00000012'
MQXR_AUTO_RECEIVER	19	X'00000013'
MQXR_CLWL_OPEN	20	X'00000014'
MQXR_CLWL_PUT	21	X'00000015'
MQXR_CLWL_MOVE	22	X'00000016'
MQXR_CLWL_REPOS	23	X'00000017'
MQXR_CLWL_REPOS_MOVE	24	X'00000018'
MQXR_END_BATCH	25	X'00000019'
MQXR_ACK_RECEIVED	26	X'0000001A'
MQXR_AUTO_SVRCONN	27	X'0000001B'
MQXR_AUTO_CLUSRCVR	28	X'0000001C'
MQXR_SEC_PARMs	29	X'0000001D'

MQXR2_* (Exit Response 2)

MQXR2_PUT_WITH_DEF_ACTION	0	X'00000000'
MQXR2_PUT_WITH_DEF_USERID	1	X'00000001'
MQXR2_PUT_WITH_MSG_USERID	2	X'00000002'
MQXR2_USE_AGENT_BUFFER	0	X'00000000'
MQXR2_USE_EXIT_BUFFER	4	X'00000004'
MQXR2_DEFAULT_CONTINUATION	0	X'00000000'
MQXR2_CONTINUE_CHAIN	8	X'00000008'
MQXR2_SUPPRESS_CHAIN	16	X'00000010'
MQXR2_STATIC_CACHE	0	X'00000000'
MQXR2_DYNAMIC_CACHE	32	X'00000020'

MQXT_* (Exit Identifiers)

MQXT_API_CROSSING_EXIT	1	X'00000001'
MQXT_API_EXIT	2	X'00000002'
MQXT_CHANNEL_SEC_EXIT	11	X'0000000B'
MQXT_CHANNEL_MSG_EXIT	12	X'0000000C'
MQXT_CHANNEL_SEND_EXIT	13	X'0000000D'
MQXT_CHANNEL_RCV_EXIT	14	X'0000000E'
MQXT_CHANNEL_MSG_RETRY_EXIT	15	X'0000000F'
MQXT_CHANNEL_AUTO_DEF_EXIT	16	X'00000010'
MQXT_CLUSTER_WORKLOAD_EXIT	20	X'00000014'
MQXT_PUBSUB_ROUTING_EXIT	21	X'00000015'

MQXUA_* (Exit User Area Value)

MQXUA_NONE	X'00...00'	(16 nulls)
MQXUA_NONE_ARRAY	'\0','\0',...	(16 nulls)

MQXWD_* (Exit wait descriptor structure)

MQXWD_STRUC_ID	"XWDb"	
MQXWD_STRUC_ID_ARRAY	'X','W','D','b'	
MQXWD_VERSION_1	1	X'00000001'

MQZAC_* (Application context structure)

MQZAC_STRUC_ID	"ZAcB"	
----------------	--------	--

MQZAC_STRUC_ID_ARRAY	'Z','A','C','b'		
MQZAC_VERSION_1		1	X'00000001'
MQZAC_CURRENT_VERSION		1	X'00000001'

MQZAD_* (Authority data structure)

MQZAD_STRUC_ID	"ZADb"		
MQZAD_STRUC_ID_ARRAY	'Z','A','D','b'		
MQZAD_VERSION_1		1	X'00000001'
MQZAD_VERSION_2		2	X'00000002'
MQZAD_CURRENT_VERSION		2	X'00000002'

MQZAET_* (Installable Services Entity Types)

MQZAET_NONE		0	X'00000000'
MQZAET_PRINCIPAL		1	X'00000001'
MQZAET_GROUP		2	X'00000002'
MQZAET_UNKNOWN		3	X'00000003'

MQZAO_* (Installable Services Authorizations)

MQZAO_CONNECT		1	X'00000001'
MQZAO_BROWSE		2	X'00000002'
MQZAO_INPUT		4	X'00000004'
MQZAO_OUTPUT		8	X'00000008'
MQZAO_INQUIRE		16	X'00000010'
MQZAO_SET		32	X'00000020'
MQZAO_PASS_IDENTITY_CONTEXT		64	X'00000040'
MQZAO_PASS_ALL_CONTEXT		128	X'00000080'
MQZAO_SET_IDENTITY_CONTEXT		256	X'00000100'
MQZAO_SET_ALL_CONTEXT		512	X'00000200'
MQZAO_ALTERNATE_USER_AUTHORITY		1024	X'00000400'
MQZAO_PUBLISH		2048	X'00000800'
MQZAO_SUBSCRIBE		4096	X'00001000'
MQZAO_RESUME		8192	X'00002000'
MQZAO_ALL_MQI		16383	X'00003FFF'
MQZAO_CREATE		65536	X'00010000'
MQZAO_DELETE		131072	X'00020000'
MQZAO_DISPLAY		262144	X'00040000'
MQZAO_CHANGE		524288	X'00080000'
MQZAO_CLEAR		1048576	X'00100000'

MQZAO_CONTROL	2097152	X'00200000'
MQZAO_CONTROL_EXTENDED	4194304	X'00400000'
MQZAO_AUTHORIZE	8388608	X'00800000'
MQZAO_ALL_ADMIN	16646144	X'00FE0000'
MQZAO_ALL	16662527	X'00FE3FFF'
MQZAO_REMOVE	16777216	X'01000000'
MQZAO_NONE	0	X'00000000'

MQZAS_* (Installable Services Service Interface Version)

MQZAS_VERSION_1	1	X'00000001'
MQZAS_VERSION_2	2	X'00000002'
MQZAS_VERSION_3	3	X'00000003'
MQZAS_VERSION_4	4	X'00000004'
MQZAS_VERSION_5	5	X'00000005'

MQZAT_* (Authentication Types)

MQZAT_INITIAL_CONTEXT	0	X'00000000'
MQZAT_CHANGE_CONTEXT	1	X'00000001'

MQZCI_* (Installable Services Continuation Indicator)

MQZCI_DEFAULT	0	X'00000000'
MQZCI_CONTINUE	0	X'00000000'
MQZCI_STOP	1	X'00000001'

MQZED_* (Entity data structure)

MQZED_STRUC_ID	"ZEDb"	
MQZED_STRUC_ID_ARRAY	'Z','E','D','b'	
MQZED_VERSION_1	1	X'00000001'
MQZED_VERSION_2	2	X'00000002'
MQZED_CURRENT_VERSION	2	X'00000002'

MQZFP_* (Free parameters structure)

MQZFP_STRUC_ID	"ZFPb"	
MQZFP_STRUC_ID_ARRAY	'Z','F','P','b'	
MQZFP_VERSION_1	1	X'00000001'
MQZFP_CURRENT_VERSION	1	X'00000001'

MQZIC_* (Identity context structure)

MQZIC_STRUC_ID	"ZICb"		
MQZIC_STRUC_ID_ARRAY	'Z','I','C','b'		
MQZIC_VERSION_1		1	X'00000001'
MQZIC_CURRENT_VERSION		1	X'00000001'

MQZID_* (Function ids common to all services)

MQZID_INIT		0	X'00000000'
MQZID_TERM		1	X'00000001'

MQZID_* (Function ids for Authority service)

MQZID_INIT_AUTHORITY		0	X'00000000'
MQZID_TERM_AUTHORITY		1	X'00000001'
MQZID_CHECK_AUTHORITY		2	X'00000002'
MQZID_COPY_ALL_AUTHORITY		3	X'00000003'
MQZID_DELETE_AUTHORITY		4	X'00000004'
MQZID_SET_AUTHORITY		5	X'00000005'
MQZID_GET_AUTHORITY		6	X'00000006'
MQZID_GET_EXPLICIT_AUTHORITY		7	X'00000007'
MQZID_REFRESH_CACHE		8	X'00000008'
MQZID_ENUMERATE_AUTHORITY_DATA		9	X'00000009'
MQZID_AUTHENTICATE_USER		10	X'0000000A'
MQZID_FREE_USER		11	X'0000000B'
MQZID_INQUIRE		12	X'0000000C'

MQZID_* (Function ids for Name service)

MQZID_INIT_NAME		0	X'00000000'
MQZID_TERM_NAME		1	X'00000001'
MQZID_LOOKUP_NAME		2	X'00000002'
MQZID_INSERT_NAME		3	X'00000003'
MQZID_DELETE_NAME		4	X'00000004'

MQZID_* (Function ids for Userid service)

MQZID_INIT_USERID		0	X'00000000'
MQZID_TERM_USERID		1	X'00000001'
MQZID_FIND_USERID		2	X'00000002'

MQZIO_* (Installable Services Initialization Options)

MQZIO_PRIMARY	0	X'00000000'
MQZIO_SECONDARY	1	X'00000001'

MQZNS_* (Name Service Interface Version)

MQZNS_VERSION_1	1	X'00000001'
-----------------	---	-------------

MQZSE_* (Installable Services Start-Enumeration Indicator)

MQZSE_START	1	X'00000001'
MQZSE_CONTINUE	0	X'00000000'

MQZSL_* (Installable Services Selector Indicator)

MQZSL_NOT_RETURNED	0	X'00000000'
MQZSL_RETURNED	1	X'00000001'

MQZTO_* (Installable Services Termination Options)

MQZTO_PRIMARY	0	X'00000000'
MQZTO_SECONDARY	1	X'00000001'

MQZUS_* (Userid Service Interface Version)

MQZUS_VERSION_1	1	X'00000001'
-----------------	---	-------------

Notices

This information was developed for products and services offered in the United States. IBM® may not offer the products, services, or features discussed in this information in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this information. The furnishing of this information does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing,
IBM Corporation,
North Castle Drive,
Armonk, NY 10504-1785,
U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

IBM World Trade Asia Corporation,
Licensing,
2-31 Roppongi 3-chome, Minato-k,u
Tokyo 106, Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the information. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this information at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM United Kingdom Laboratories,
Mail Point 151,
Hursley Park,
Winchester,
Hampshire,
England
SO21 2JN.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this information and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Programming License Agreement, or any equivalent agreement between us.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. You may copy, modify, and distribute these sample programs in any form without payment to IBM for the purposes of developing, using, marketing, or distributing application programs conforming to IBM's application programming interfaces.

The following are trademarks of International Business Machines Corporation in the United States, or other countries, or both:

CICS	DB2	i5/OS
IBM	IBMLink	IMS
WebSphere	z/OS	

Unix is a trademark of The Open Group in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.

Index

C

constants, values of

- %%#con\$ params ValueLength - mqsetmp 0 (MQVL_*) 131
- Accounting Token 0 (MQACT_*) 13
- Accounting Token Types 0 (MQACTT_*) 13
- Action 0 (MQACTP_*) 13
- Action 0 (MQSR_*) 125
- Activity Operations 0 (MQOPER_*) 82
- Adopt New MCA Checks 0 (MQADOPT_*) 14
- Adopt New MCA Types 0 (MQADOPT_*) 14
- API Caller Types 0 (MQXACT_*) 132
- API crossing exit parameter structure 0 (MQXP_*) 134
- API exit chain area header structure 0 (MQACH_*) 13
- API exit context structure 0 (MQAXC_*) 16
- API exit parameter structure 0 (MQAXP_*) 17
- API Function Identifiers 0 (MQXF_*) 134
- Application context structure 0 (MQZAC_*) 136
- Authentication information record structure 0 (MQAIR_*) 14
- Authentication Information Type 0 (MQAIT_*) 14
- Authentication Types 0 (MQZAT_*) 138
- Authority data structure 0 (MQZAD_*) 137
- Back-Out Hardening 0 (MQQA_*) 94
- Bag Handles 0 (MQHB_*) 56
- Begin Options 0 (MQBO_*) 18
- Begin options structure 0 (MQBO_*) 18
- Buffer Length for mqAddString and mqSetString 0 (MQBL_*) 17
- Buffer To Message Handle Options 0 (MQBMHO_*) 18
- Buffer to message handle options structure 0 (MQBMHO_*) 18
- Byte Attribute Selectors 0 (MQBA_*) 17
- Capability Flags 0 (MQCF_*) 29
- CF Recoverability 0 (MQCFR_*) 31
- Channel Auto Definition 0 (MQCHAD_*) 33
- Channel Compression 0 (MQCOMPRESS_*) 43
- Channel Data Conversion 0 (MQCDC_*) 29
- Channel definition structure 0 (MQCD_*) 29
- Channel exit parameter structure 0 (MQCXP_*) 46

constants, values of (*continued*)

- Channel Initiator Trace Autostart 0 (MQTRAXSTR_*) 129
- Channel Types 0 (MQCHT_*) 35
- Character Attribute Selectors 0 (MQCA_*) 18
- CICS information header ADS Descriptors 0 (MQCADSD_*) 26
- CICS information header Conversational Task Options 0 (MQCCT_*) 28
- CICS information header Facility 0 (MQCFAC_*) 29
- CICS information header Flags 0 (MQCIH_*) 36
- CICS information header Functions 0 (MQCFUNC_*) 33
- CICS information header Get Wait Interval 0 (MQCGWI_*) 33
- CICS information header Link Types 0 (MQCLT_*) 36
- CICS information header Output Data Length 0 (MQCODL_*) 43
- CICS information header Return Codes 0 (MQCRC_*) 44
- CICS information header Start Codes 0 (MQCSC_*) 44
- CICS information header structure 0 (MQCIH_*) 35
- CICS information header Task End Status 0 (MQCTES_*) 45
- CICS information header Unit-of-Work Controls 0 (MQCUOWC_*) 46
- Close Options 0 (MQCO_*) 43
- Cluster Cache Types 0 (MQCLCT_*) 36
- Cluster Queue Types 0 (MQCQT_*) 44
- Cluster Workload 0 (MQCLWL_*) 36
- Cluster workload exit destination record structure 0 (MQWDR_*) 131
- Cluster workload exit parameter structure 0 (MQWXP_*) 132
- Cluster workload exit queue record structure 0 (MQWQR_*) 132
- Cluster Workload Flags 0 (MQWXP_*) 132
- Coded Character Set Identifiers 0 (MQCCSL_*) 28
- Command Codes 0 (MQCMD_*) 37
- Command format 64-bit integer list parameter structure 0 (MQCFIL64_*) 30
- Command format 64-bit Integer Monitoring Parameter Types 0 (MQIAMO64_*) 72
- Command format 64-bit integer parameter structure 0 (MQCFIN64_*) 31

constants, values of (*continued*)

- Command format Action Options 0 (MQACT_*) 13
- Command format Asynchronous State Values 0 (MQAS_*) 14
- Command format Authority Options 0 (MQAUTHOPT_*) 16
- Command format Authority Values 0 (MQAUTH_*) 16
- Command format Bridge Types 0 (MQBT_*) 18
- Command format Byte Parameter Types 0 (MQBACF_*) 17
- Command format byte string filter parameter structure 0 (MQCFBF_*) 30
- Command format byte string parameter structure 0 (MQCFBS_*) 30
- Command format CF Status 0 (MQCFSTATUS_*) 32
- Command format CF Types 0 (MQCFTYPE_*) 33
- Command format Channel Dispositions 0 (MQCHLD_*) 34
- Command format Channel Shared Restart Options 0 (MQCHSH_*) 34
- Command format Channel Status 0 (MQCHS_*) 34
- Command format Channel Stop Options 0 (MQCHSR_*) 34
- Command format Channel Substates 0 (MQCHSSTATE_*) 34
- Command format Channel Table Types 0 (MQCHTAB_*) 35
- Command format Character Channel Parameter Types 0 (MQCACH_*) 25
- Command format Character Monitoring Parameter Types 0 (MQCAMO_*) 26
- Command format Character Parameter Types 0 (MQCACF_*) 21
- Command format Clear Topic String Scope 0 (MQCLRS_*) 36
- Command format Clear Topic String Type 0 (MQCLRT_*) 36
- Command format Command Information Values 0 (MQCMDI_*) 41
- Command format Data Set Usage Values 0 (MQUSAGE_*) 131
- Command format Disconnect Types 0 (MQDISCONNECT_*) 47
- Command format Escape Types 0 (MQET_*) 50
- Command format Event Origins 0 (MQEVO_*) 50
- Command format Event Recording 0 (MQEVR_*) 51

constants, values of (*continued*)

Command format Filter Operators 0 (MQCFOP_*) 31
 Command format Force Options 0 (MQFC_*) 52
 Command format group parameter structure 0 (MQCFGR_*) 30
 Command format Group Parameter Types 0 (MQGACF_*) 54
 Command format Handle States 0 (MQHSTATE_*) 56
 Command format header Control Options 0 (MQCFC_*) 30
 Command format header Reason Codes 0 (MQRCCF_*) 109
 Command format header structure 0 (MQCFH_*) 30
 Command format Inbound Dispositions 0 (MQINBD_*) 74
 Command format Indoubt Options 0 (MQIDO_*) 73
 Command format Indoubt Status 0 (MQCHIDS_*) 33
 Command format Integer Channel Types 0 (MQIACH_*) 67
 Command format integer filter parameter structure 0 (MQCFIF_*) 30
 Command format integer list parameter structure 0 (MQCFIL_*) 30
 Command format Integer Monitoring Parameter Types 0 (MQIAMO_*) 70
 Command format integer parameter structure 0 (MQCFIN_*) 30
 Command format Integer Parameter Types 0 (MQIACF_*) 61
 Command format Message Channel Agent Status 0 (MQMCAS_*) 75
 Command format Mode Options 0 (MQMODE_*) 78
 Command format Page Set Usage Values 0 (MQUSAGE_*) 130
 Command format Pub/Sub Status 0 (MQPS_*) 86
 Command format Pub/Sub Status Type 0 (MQPST_*) 93
 Command format Purge Options 0 (MQPO_*) 86
 Command format QSG Status 0 (MQQSGS_*) 96
 Command format Queue Definition Scope 0 (MQSCO_*) 121
 Command format Queue Manager Definition Types 0 (MQQMDT_*) 95
 Command format Queue Manager Facility 0 (MQQMFAC_*) 95
 Command format Queue Manager Status 0 (MQQMSTA_*) 95
 Command format Queue Manager Types 0 (MQQMT_*) 95
 Command format Queue Service-Interval Events 0 (MQQSIE_*) 96

constants, values of (*continued*)

Command format Queue Status Open Options for SET, BROWSE, INPUT 0 (MQQSO_*) 96
 Command format Queue Status Open Types 0 (MQQSOT_*) 96
 Command format Queue Status Uncommitted Messages 0 (MQQSUM_*) 96
 Command format Quiesce Options 0 (MQQO_*) 95
 Command format Reason Qualifiers 0 (MQRQ_*) 120
 Command format Refresh Repository Options 0 (MQCFO_*) 31
 Command format Refresh Types 0 (MQRT_*) 120
 Command format Remove Queues Options 0 (MQCFO_*) 31
 Command format Replace Options 0 (MQRP_*) 120
 Command format Security Items 0 (MQSECITEM_*) 122
 Command format Security Switch States 0 (MQSECSW_*) 122
 Command format Security Switches 0 (MQSECSW_*) 122
 Command format Security Types 0 (MQSECTYPE_*) 123
 Command format string filter parameter structure 0 (MQCFSF_*) 31
 Command format String Lengths 0 (MQ_*) 12
 Command format string list parameter structure 0 (MQCFSL_*) 31
 Command format string parameter structure 0 (MQCFST_*) 32
 Command format Subscription Types 0 (MQSUBTYPE_*) 126
 Command format Suspend Status 0 (MQSUS_*) 126
 Command format Syncpoint values for Pub/Sub migration 0 (MQSYNCPPOINT_*) 126
 Command format System Parameter Values 0 (MQSYSP_*) 127
 Command format Time units 0 (MQTIME_*) 128
 Command format Types of Structure 0 (MQCFT_*) 32
 Command format Undelivered values for Pub/Sub migration 0 (MQUNDELIVERED_*) 130
 Command format UOW States 0 (MQUOWST_*) 130
 Command format UOW Types 0 (MQUOWT_*) 130
 Command format User ID Support 0 (MQUIDSUPP_*) 130
 Command Levels 0 (MQCMDL_*) 41
 Command Server Options 0 (MQCSR_*) 45
 Completion Codes 0 (MQCC_*) 28
 Connect Options 0 (MQCNO_*) 42
 Connect options structure 0 (MQCNO_*) 42

constants, values of (*continued*)

Connection Affinity Values 0 (MQCAFTY_*) 26
 Connection Handles 0 (MQHC_*) 56
 Connection Identifier 0 (MQCONNID_*) 43
 Connection security parameters Authentication Types 0 (MQCSP_*) 45
 Connection security parameters structure 0 (MQCSP_*) 45
 Conversion exit parameter structure 0 (MQDXP_*) 49
 Conversion Options 0 (MQDCC_*) 46
 Conversion Options Masks and Factors 0 (MQDCC_*) 47
 Correlation Identifier 0 (MQCLI_*) 35
 Create Message Handle Options 0 (MQCMHO_*) 42
 Create message handle options structure 0 (MQCMHO_*) 42
 Create-Bag Options for mqCreateBag 0 (MQCBO_*) 28
 Dead-letter header structure 0 (MQDLH_*) 48
 Default Bindings 0 (MQBND_*) 18
 Delete Message Handle Options 0 (MQDMHO_*) 48
 Delete message handle options structure 0 (MQDMHO_*) 48
 Delete Message Property Options 0 (MQDMPO_*) 48
 Delete message property options structure 0 (MQDMPO_*) 48
 Destination Class 0 (MQDC_*) 46
 Destination Types 0 (MQDT_*) 49
 Distribution header Flags 0 (MQDHF_*) 47
 Distribution header structure 0 (MQDH_*) 47
 Distribution Lists 0 (MQDL_*) 48
 DNS WLM 0 (MQDNSWLM_*) 49
 Durable subscriptions 0 (MQSUB_*) 125
 Durable Subscriptions 0 (MQSUB_*) 126
 Embedded command format header Flags 0 (MQEPH_*) 50
 Embedded command format header structure 0 (MQEPH_*) 50
 Encoding 0 (MQENC_*) 49
 Encoding Masks 0 (MQENC_*) 49
 Encodings for Binary Integers 0 (MQENC_*) 50
 Encodings for Floating Point Numbers 0 (MQENC_*) 50
 Encodings for Packed Decimal Integers 0 (MQENC_*) 50
 Entity data structure 0 (MQZED_*) 138
 Environments 0 (MQXE_*) 133
 Exit Commands 0 (MQXC_*) 133
 Exit Identifiers 0 (MQXT_*) 136
 Exit Options 0 (MQXEPO_*) 134
 Exit Reasons 0 (MQXR_*) 135
 Exit Response 0 (MQXDR_*) 133

constants, values of (*continued*)

- Exit Response 2 0 (MQXR2_*) 136
- Exit Responses 0 (MQXCC_*) 133
- Exit User Area Value 0 (MQXUA_*) 136
- Exit wait descriptor structure 0 (MQXWD_*) 136
- Expiration Scan Interval 0 (MQEXPI_*) 51
- Expiry 0 (MQEI_*) 49
- Extended Object Types 0 (MQOT_*) 82
- Extended Queue Types 0 (MQQT_*) 97
- Feedback Values 0 (MQFB_*) 51
- Following used in C++ only 0 (MQOO_*) 81
- Formats 0 (MQFMT_*) 52
- Free parameters structure 0 (MQZFP_*) 138
- Function ids common to all services 0 (MQZID_*) 139
- Function ids for Authority service 0 (MQZID_*) 139
- Function ids for Name service 0 (MQZID_*) 139
- Function ids for Userid service 0 (MQZID_*) 139
- Get Message Options 0 (MQGMO_*) 54
- Get message options structure 0 (MQGMO_*) 54
- Group Attribute Selectors 0 (MQGA_*) 54
- Group Identifier 0 (MQGI_*) 54
- Group Status 0 (MQGS_*) 55
- Handle Selectors 0 (MQHA_*) 55
- Identity context structure 0 (MQZIC_*) 139
- IMS information header Authenticator 0 (MQIAUT_*) 72
- IMS information header Commit Modes 0 (MQICM_*) 73
- IMS information header Flags 0 (MQIIH_*) 73
- IMS information header Security Scopes 0 (MQISS_*) 74
- IMS information header structure 0 (MQIIH_*) 73
- IMS information header Transaction Instance Identifier 0 (MQITII_*) 75
- IMS information header Transaction States 0 (MQITS_*) 75
- Index Types 0 (MQIT_*) 74
- Inhibit Get Values 0 (MQQA_*) 94
- Inhibit Put Values 0 (MQQA_*) 94
- Inquire Message Property Options 0 (MQIMPO_*) 74
- Inquire message property options structure 0 (MQIMPO_*) 73
- Installable Services Authorizations 0 (MQZAO_*) 137
- Installable Services Continuation Indicator 0 (MQZCI_*) 138
- Installable Services Entity Types 0 (MQZAET_*) 137

constants, values of (*continued*)

- Installable Services Initialization Options 0 (MQZIO_*) 140
- Installable Services Selector Indicator 0 (MQZSL_*) 140
- Installable Services Service Interface Version 0 (MQZAS_*) 138
- Installable Services Start-Enumeration Indicator 0 (MQZSE_*) 140
- Installable Services Termination Options 0 (MQZTO_*) 140
- Integer Attribute Selectors 0 (MQIA_*) 56
- Integer Attribute Values 0 (MQIAV_*) 72
- Integer System Selectors 0 (MQIASY_*) 72
- Intra-Group Queuing 0 (MQIGQ_*) 73
- Intra-Group Queuing Put Authority 0 (MQIGQPA_*) 73
- IP Address Versions 0 (MQIPADDR_*) 74
- Item Type for mqInquireItemInfo 0 (MQITEM_*) 75
- KeepAlive Interval 0 (MQKAI_*) 75
- Limits for Selectors for Object Attributes 0 (MQOA_*) 80
- Master administration 0 (MQMASTER_*) 75
- Match Options 0 (MQMO_*) 78
- Maximum Properties Length 0 (MQPROP_*) 86
- MCA Types 0 (MQMCAT_*) 75
- Message Delivery Sequence 0 (MQMDS_*) 77
- Message descriptor extension Flags 0 (MQMDEF_*) 77
- Message descriptor extension structure 0 (MQMDE_*) 77
- Message descriptor structure 0 (MQMD_*) 76
- Message Flags 0 (MQMF_*) 77
- Message handle 0 (MQHM_*) 56
- Message Handle To Buffer Options 0 (MQMHBO_*) 77
- Message handle to buffer options structure 0 (MQMHBO_*) 77
- Message Identifier 0 (MQMI_*) 78
- Message Mark-Browse Interval 0 (MQMMBI_*) 78
- Message Token 0 (MQMTOK_*) 79
- Message Types 0 (MQMT_*) 79
- Monitoring Values 0 (MQMON_*) 78
- MQCBC constants Callback type 0 (MQCBC_*) 27
- MQCBC constants Consumer state 0 (MQCS_*) 44
- MQCBC constants Flags 0 (MQCBCF_*) 27
- MQCBC constants structure 0 (MQCBC_*) 27
- MQCBD constants Callback Options 0 (MQCBDO_*) 27
- MQCBD constants structure 0 (MQCBD_*) 27

constants, values of (*continued*)

- MQCBD constants This is the type of the Callback Function 0 (MQCBT_*) 28
- MQCTL options Consumer Control Options 0 (MQCTLO_*) 46
- MQCTL options structure 0 (MQCTLO_*) 45
- Name Count 0 (MQNC_*) 79
- Name Service Interface Version 0 (MQZNS_*) 140
- Namelist Types 0 (MQNT_*) 79
- Names for Name/Value String 0 (MQNVS_*) 80
- Nonpersistent Message Class 0 (MQNPM_*) 79
- NonPersistent-Message Speeds 0 (MQNPMS_*) 79
- Object descriptor structure 0 (MQOD_*) 80
- Object descriptor structure 0 (MQSD_*) 121
- Object Handle 0 (MQHO_*) 56
- Object Instance Identifier 0 (MQOIL_*) 80
- Object Types 0 (MQOT_*) 82
- Obsolete DB2 Messages options on Inquire Group 0 (MQOM_*) 80
- Open Options 0 (MQOO_*) 80
- Operation codes for MQCB 0 (MQOP_*) 81
- Operation codes for MQCTL 0 (MQOP_*) 81
- Operation codes for MQCTL and MQCB 0 (MQOP_*) 81
- Original Length 0 (MQOL_*) 80
- Persistence Values 0 (MQPER_*) 84
- Persistent/Non-persistent Message Delivery 0 (MQDLV_*) 48
- Platforms 0 (MQPL_*) 84
- Priority 0 (MQPRI_*) 86
- Problem Determination Area 0 (MQXPDA_*) 134
- Property Context 0 (MQPD_*) 84
- Property Copy Options 0 (MQCOPY_*) 43
- Property data types 0 (MQTYPE_*) 129
- Property Descriptor Options 0 (MQPD_*) 83
- Property descriptor structure 0 (MQPD_*) 83
- Property Support Options 0 (MQPD_*) 83
- Proxy Sub Propagation 0 (MQTA_*) 127
- Pub/Sub Message Properties 0 (MQPSPROP_*) 93
- Pub/Sub Mode 0 (MQPSM_*) 93
- Publications Allowed 0 (MQTA_*) 127
- Publish scope 0 (MQSCOPE_*) 121
- Publish/Subscribe Command Tag Values as blank-enclosed strings 0 (MQPS_*) 88
- Publish/Subscribe Command Tag Values as strings 0 (MQPS_*) 88

constants, values of (*continued*)

Publish/Subscribe Delete Options 0 (MQDELO_*) 47
 Publish/Subscribe Options Tag Message Content Descriptor (mcd) Tags 0 (MQMCD_*) 76
 Publish/Subscribe Options Tag Publish/Subscribe Command Folder (psc) Tags 0 (MQPSC_*) 90
 Publish/Subscribe Options Tag Publish/Subscribe Response Folder (pscr) Tags 0 (MQPSCR_*) 92
 Publish/Subscribe Options Tag RFH2 Top-level folder Tags 0 (MQRFH2_*) 117
 Publish/Subscribe Options Tag Tag names 0 (MQMCD_*) 76
 Publish/Subscribe Options Tag Tag names 0 (MQPSC_*) 90
 Publish/Subscribe Options Tag Tag names 0 (MQPSCR_*) 92
 Publish/Subscribe Options Tag Tag names 0 (MQRFH2_*) 117
 Publish/Subscribe Options Tag Tag values 0 (MQMCD_*) 76
 Publish/Subscribe Options Tag Tag values 0 (MQPSCR_*) 93
 Publish/Subscribe Options Tag Values as blank-enclosed strings 0 (MQPS_*) 89
 Publish/Subscribe Options Tag Values as strings 0 (MQPS_*) 88
 Publish/Subscribe Options Tag Values as strings 0 (MQPSC_*) 91, 92
 Publish/Subscribe Options Tag XML tag names 0 (MQMCD_*) 76
 Publish/Subscribe Options Tag XML tag names 0 (MQPSC_*) 91
 Publish/Subscribe Options Tag XML tag names 0 (MQPSCR_*) 93
 Publish/Subscribe Options Tag XML tag names 0 (MQRFH2_*) 118
 Publish/Subscribe Publication Options 0 (MQPUBO_*) 93
 Publish/Subscribe Registration Options 0 (MQREGO_*) 116
 Publish/subscribe routing exit parameter structure 0 (MQPXP_*) 94
 Publish/Subscribe Tags as blank-enclosed strings 0 (MQPS_*) 87
 Publish/Subscribe Tags as strings 0 (MQPS_*) 87
 Publish/Subscribe User Attribute Selectors 0 (MQUA_*) 129
 Put Application Types 0 (MQAT_*) 15
 Put Authority 0 (MQPA_*) 83
 Put Message Options 0 (MQPMO_*) 85
 Put Message Options for publish mask 0 (MQPMO_*) 85
 Put message options structure 0 (MQPMO_*) 84
 Put Message Record Fields 0 (MQPMRF_*) 85

constants, values of (*continued*)

Put Response Values 0 (MQPRT_*) 86
 Queue and Channel Property Control Values 0 (MQPROP_*) 86
 Queue Definition Types 0 (MQQDT_*) 94
 Queue Flags 0 (MQQF_*) 94
 Queue Manager Connection Tag 0 (MQCT_*) 45
 Queue Manager Flags 0 (MQQMF_*) 95
 Queue Shareability 0 (MQQA_*) 94
 Queue Sharing Group Dispositions 0 (MQQSGD_*) 95
 Queue Types 0 (MQQT_*) 96
 Queue Usages 0 (MQUS_*) 130
 Read Ahead Values 0 (MQREADA_*) 116
 Reason Codes 0 (MQRC_*) 97
 Receive Timeout Types 0 (MQRCVTIME_*) 116
 Recording Options 0 (MQRECORDING_*) 116
 Reference message header Flags 0 (MQRMHF_*) 118
 Reference message header structure 0 (MQRMH_*) 118
 Register Entry Point Options structure 0 (MQXEPO_*) 133
 Report Options 0 (MQRO_*) 118
 Report Options Masks 0 (MQRO_*) 119
 Request Only 0 (MQRU_*) 121
 Returned Length 0 (MQRL_*) 118
 Rules and formatting header Flags 0 (MQRFH_*) 117
 Rules and formatting header structure 0 (MQRFH_*) 117
 Security Case 0 (MQSCYC_*) 121
 Security Identifier 0 (MQSID_*) 123
 Security Identifier Types 0 (MQSIDT_*) 123
 Segment Status 0 (MQSS_*) 125
 Segmentation 0 (MQSEG_*) 123
 Service Controls 0 (MQSVC_*) 126
 Service Status 0 (MQSVC_*) 126
 Service Types 0 (MQSVC_*) 126
 Set Message Property Options 0 (MQSMPO_*) 123
 Set message property options structure 0 (MQSMPO_*) 123
 Shared Queue Queue Manager Name 0 (MQSQQM_*) 124
 Signal Values 0 (MQEC_*) 49
 Special Index Values 0 (MQIND_*) 74
 Special Selector Values 0 (MQSEL_*) 123
 SSL Client Authentication 0 (MQSCA_*) 121
 SSL configuration options Key Reset Count 0 (MQSCO_*) 121
 SSL configuration options structure 0 (MQSCO_*) 121
 SSL FIPS Requirements 0 (MQSSL_*) 125

constants, values of (*continued*)

Stat Options 0 (MQSTAT_*) 125
 Status reporting structure structure 0 (MQSTS_*) 125
 String Lengths 0 (MQ_*) 9
 Subscribe Options 0 (MQSO_*) 124
 Subscription request options structure 0 (MQSRO_*) 125
 Subscription Scope 0 (MQTSCOPE_*) 129
 Subscriptions Allowed 0 (MQTA_*) 127
 Syncpoint Availability 0 (MQSP_*) 124
 TCP Keepalive 0 (MQTCPKEEP_*) 128
 TCP Stack Types 0 (MQTCPSTACK_*) 128
 Topic Type 0 (MQTOPT_*) 129
 Trace-route Accumulation (MQIACF_ROUTE_ACCUMULATION) 0 (MQRROUTE_*) 120
 Trace-route Delivery (MQIACF_ROUTE_DELIVERY) 0 (MQRROUTE_*) 119
 Trace-route Detail (MQIACF_ROUTE_DETAIL) 0 (MQRROUTE_*) 119
 Trace-route Forwarding (MQIACF_ROUTE_FORWARDING) 0 (MQRROUTE_*) 119
 Trace-route Max Activities (MQIACF_MAX_ACTIVITIES) 0 (MQRROUTE_*) 119
 Transmission queue header structure 0 (MQXQH_*) 135
 Transport Types 0 (MQXPT_*) 135
 Trigger Controls 0 (MQTC_*) 128
 Trigger message character format structure 0 (MQTMC_*) 128
 Trigger message structure 0 (MQTM_*) 128
 Trigger Types 0 (MQTT_*) 129
 Userid Service Interface Version 0 (MQZUS_*) 140
 Values related to MQOPEN_PRIV structure 0 (MQOPEN_*) 81
 Variable User ID 0 (MQVU_*) 131
 Wait Interval 0 (MQWI_*) 131
 Wildcard Schema 0 (MQWS_*) 132
 Wildcards 0 (MQTA_*) 127
 Workload information header Flags 0 (MQWIH_*) 132
 Workload information header structure 0 (MQWIH_*) 131

Sending your comments to IBM

If you especially like or dislike anything about this book, please use one of the methods listed below to send your comments to IBM.

Feel free to comment on what you regard as specific errors or omissions, and on the accuracy, organization, subject matter, or completeness of this book.

Please limit your comments to the information in this book and the way in which the information is presented.

To make comments about the functions of IBM products or systems, talk to your IBM representative or to your IBM authorized remarketer.

When you send comments to IBM, you grant IBM a nonexclusive right to use or distribute your comments in any way it believes appropriate, without incurring any obligation to you.

You can send your comments to IBM in any of the following ways:

- By mail, to this address:

User Technologies Department (MP095)
IBM United Kingdom Laboratories
Hursley Park
WINCHESTER,
Hampshire
SO21 2JN
United Kingdom

- By fax:
 - From outside the U.K., after your international access code use 44-1962-816151
 - From within the U.K., use 01962-816151
- Electronically, use the appropriate network ID:
 - IBM Mail Exchange: GBIBM2Q9 at IBMMAIL
 - IBMLink™: HURSLEY(IDRCF)
 - Internet: idrcf@hursley.ibm.com

Whichever method you use, ensure that you include:

- The publication title and order number
- The topic to which your comment applies
- Your name and address/telephone number/fax number/network ID.



SC34-6951-01



Spine information:



WebSphere MQ

Constants

Version 7.0