



WebSphere Product Center

Scripting Reference Guide

Version 5.0.1

Note!

Before using this information and the product it supports, read the information in “Notices” at the end of this document.

27 September 2004

This edition of this document applies to WebSphere Product Center (5724-I68), version 5.0.1, and to all subsequent releases and modifications until otherwise indicated in new editions.

© Copyright International Business Machines Corporations 2000, 2004. All rights reserved.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Table of Contents

TABLE OF CONTENTS	1
INTRODUCTION	1
SCRIPT OPERATIONS CHANGES	2
UPDATED AND NEW SCRIPT OPERATIONS TO SUPPORT ITEM LOCATION HIERARCHIES.....	2
ENABLE REORDERING WITH SCRIPTING.....	13
ADDITIONAL CHANGED SCRIPT OPERATIONS.....	14
WEBSHERE PRODUCT CENTER SCRIPT OPERATIONS	23
BASIC	23
<i>Array</i>	23
<i>Date</i>	23
<i>HashMap</i>	25
<i>LanguageConstruct</i>	26
<i>Numeric</i>	28
<i>RegularExpression</i>	29
<i>ScriptObject</i>	30
Scripting	31
<i>String</i>	31
Zip	38
CONTAINER	38
Attribute Groups	38
<i>Catalog</i>	40
<i>Category</i>	47
<i>CategorySet</i>	51
<i>CategoryTree</i>	51
<i>CategoryTreeMap</i>	57
<i>Item</i>	57
<i>ItemNode</i>	65
<i>ItemSet</i>	66
<i>LookupTable</i>	67
Queues	69
<i>Selection</i>	70
<i>Version</i>	73
Views	73
DOCSTORE	77
<i>Doc</i>	77
DocStore	80
<i>XML Document</i>	80
<i>Sample Script for newXMLDocument</i>	80
ENTRY	81
<i>Entry</i>	81
<i>EntryNode</i>	86
<i>Entry Set</i>	89
<i>UserDefinedLog</i>	90
<i>UserDefinedLogEntry</i>	92

INPUT OUTPUT.....	93
Feed	93
<i>Export environment</i>	96
<i>Messaging</i>	100
<i>Sample Script for Invoking SOAP Server</i>	102
<i>UCCnet Operations</i>	102
Page Layout	110
Reader	110
TarArchive	113
Writer	113
XMLNode	115
SECURITY.....	116
Company	116
Role	116
User	118
AccessPrivilege	121
SPEC.....	123
Inheritance	124
Immutable Spec	125
Locale	126
SpecNode	127
Sequence	129
Spec	130
SpecMap	133
SYSTEMADMIN.....	134
Logger	134
PerformanceTest	135
SystemDB	135
WEB SERVICES.....	136
WORKENTRYLIST.....	139
WorkEntry	139
WorkEntryList	140
WORKFLOW.....	141
ColAreaEntryHistory	142
CollaborationArea	143
Workflow	149
Workflow Step	151
Widget	156
SCRIPT TYPES.....	159
REPORT SCRIPTS.....	159
VALIDATION RULE SCRIPT EXPRESSIONS.....	159
DISTRIBUTION SCRIPTS.....	159
IMPORT AND EXPORT SCRIPTS.....	159
ENTRY MACRO SCRIPTS.....	160
CATALOG DIFFERENCE EXPORT SCRIPTS.....	160
CATALOG IMPORT SCRIPTS.....	161
MAPPING SCRIPT EXPRESSIONS.....	161
ENTRY PREVIEW SCRIPTS.....	162
CATALOG SCRIPTS.....	162
STRING ENUMERATION RULE SCRIPT EXPRESSIONS.....	163
TRIGGER SCRIPTS.....	163
MASS UPDATE SCRIPTS.....	163
CATALOG EXPORT SCRIPTS.....	164

VALUE RULE SCRIPT EXPRESSIONS	164
LOOKUP TABLE IMPORT SCRIPTS.....	165
CATEGORY TREE IMPORT SCRIPTS.....	165
PREDEFINED SCRIPTS.....	165
<i>Search and Replace Macro Including Attribute Drop-down Box.....</i>	<i>165</i>
<i>Post-Save Audit Log Script.....</i>	<i>167</i>

Introduction

The following pages list the script operations that are included in WebSphere Product Center. A description and prototype is provided for each operation.

The prototypes use the following:

Return type - Object - Method - (Parameters)

NOTE: The script operations listed in this document are for reference only and are subject to change. Refer to the Script Sandbox in the WebSphere Product Center product for more up-to-date information.

This document covers the following sections:

- **Script operation changes** - The section includes additional updates to the script operations, which are not identified in the section “WebSphere Product Center Script Operations”. Therefore, it is important to reference both sections.
- **WebSphere Product Center script operations** - The first section includes list of script operations that have been included in the WebSphere Product Center 5.0 Script Sandbox.
- **Script types** – This section defines the script types that are available in WebSphere Product Center.

Script operations changes

This section covers updates that were made to the WebSphere Product Center script library. Removed, new, and updated script operations are included in this section.

Updated and new script operations to support item location hierarchies

The script operations listed in this section are updated and new script operations that have been updated in the script sandbox to support item location hierarchies.

getItemPrimaryKeysForCategory

Description	Returns an array of Strings containing the primary keys of the items in this category. The option Boolean 'ordered' being set to true makes the operation return the ordered children of this category if the catalog is set up to use ordering
Prototype	String[] Category::getItemPrimaryKeysForCategory(Catalog ctg [, Boolean ordered])

getEntryNodeInheritedValue

Description	If this EntryNode inherits its value, return the value. Otherwise, return null.
Prototype	Object EntryNode::getEntryNodeInheritedValue()

deleteEntryNode

Description	Remove this entrynode from the Entry. This operation will only work on Mutli-Occurance attributes, an error will be thrown if used on a non-multit-occurance entryNode.
Prototype	void EntryNode::deleteEntryNode()

setEntryNode

Description	Return the entryNode with path sPath relative to EntryNode. If the path is not already built a NULL will be returned. Use the Entry::setEntryAttrib script operation to create a path that might not exist.
Prototype	EntryNode EntryNode::setEntryNode(String sPath)

setEntryNodeValue

Description	Set the value of this EntryNode and return 1 if the value was set, 0 if nothing changed, and -1 if there was a type conversion error.
-------------	---

Prototype Integer EntryNode::setEntryNodeValue(Object value)

hasInheritedValue

Description Returns TRUE if this EntryNode inherits its value.

Prototype Boolean EntryNode::hasInheritedValue()

getLocationPathForInheritedValue

Description Returns the path for the location from which this EntryNode inherits, or null if it does not inherit its value. The given delimiter is used.

Prototype String EntryNode::getLocationPathForInheritedValue(String delimiter)

setInheriting

Description Sets an item to inherit at a location for sAttribPath.

Prototype void Item::getItemLocationAttrib(Category location, String sAttribPath)

setInheriting

Description Sets an item to inherit at a location for sAttribPath.

Prototype void Item::getItemLocationAttrib(Category location, String sAttribPath)

isInheriting

Description Return true if the item inherit at a location for sAttribPath.

Prototype Boolean Item::isInheriting(Category location, String sAttribPath)

defineLocationSpecificData

Description Sets up location specific data for a catalog. CTR is the category tree that contains the locations. "spc" is the spec of the locations. "inhattrgrps" is an array of attribute groups containing the inheritable attributes.

Prototype void Catalog::defineLocationSpecificData(CategoryTree ctr, Spec spc, AttrGroup[] inhAttrGrps)

removeLocationSpecificData

Description Sets up location specific data for a catalog. CTR is the category tree that contains the locations.

Prototype void Catalog::removeLocationSpecificData(CategoryTree ctr)

setCtgView

Description Sets the container view object with the given name/catalog and returns it. The viewType can be 'ITEM_LIST', 'ITEM_POPUP', 'ITEM_LOCATION', 'BULK_EDIT' or 'ITEM_EDIT'. By default ITEM_EDIT is used. Permissions are [V|E]

Prototype CtgView CtgView::setCtgView(String viewType, String[] attrGroupNames, String[] permissions)

getCtgViewType

Description Returns the type of the view in question as a string. The values can be 'ITEM_LIST', 'ITEM_POPUP', 'ITEM_LOCATION', 'BULK_EDIT', 'ITEM_EDIT', 'CATEGORY_EDIT', 'CATEGORY_BULK_EDIT', 'CATEGORY_RICH_SEARCH', 'ITEM_RICH_SEARCH'

Prototype String CtgView::getCtgViewType()

getCtgViewByName

Description Returns the view with the corresponding name. If no name is specified, returns the default view. Use '[System Default]' to refer to the default view. The viewType can be 'ITEM_LIST', 'ITEM_POPUP', 'ITEM_LOCATION', 'BULK_EDIT', 'ITEM_EDIT', 'CATEGORY_EDIT' or 'CATEGORY_BULK_EDIT'. By default ITEM_EDIT/CATEGORY_EDIT is used. If the view is not found, it returns null.

Prototype CtgView Container::getCtgViewByName([String viewName, String viewType])

getChangedAttributes

Description Returns an array of changed attribute paths. If a location is specified, only the attributes for the location are examined. If a location is specified, and the location does not apply to both entries, null is returned.

Prototype String[] Entry::getChangedAttributes(Entry secondEntry, [Category location])

getLocationPathForInheritedValue

Description	Returns the path for the location from which this EntryNode inherits, or null if it does not inherit its value. The given delimiter is used.
Prototype	String EntryNode::getLocationPathForInheritedValue(String delimiter)

getItemLocationAttrib

Description	Gets a location attribute for an item.
Prototype	Object Item::getItemLocationAttrib(Category location, String sAttribPath)

setInheriting

Description	Sets an item to inherit at a location for sAttribPath.
Prototype	void Item::getItemLocationAttrib(Category location, String sAttribPath)

isInheriting

Description	Return true if the item inherit at a location for sAttribPath.
Prototype	Boolean Item::isInheriting(Category location, String sAttribPath)

getLocation

Description	Return the location (category) for the entry node or null if a global entry node.
Prototype	Category EntryNode::getLocation()

getEntryChangedData

Description	Return an EntryChangedData object encapsulating the changes in data and locations between two entries.
Prototype	EntryChangedData ::getEntryChangedData(Entry oldEntry, Entry newEntry)

getLocationsAddedAvailability

Description	Returns all locations in LOCATIONHIERARCHY that are available in the new entry but not the old entry from which this EntryChangedData object was created.
Prototype	CategorySet EntryChangedData::getLocationsAddedAvailability(CategoryTree

locationHierarchy)

getLocationsRemovedAvailability

Description Returns all locations in LOCATIONHIERARCHY that are available in the old entry but not the new entry from which this EntryChangedData object was created.

Prototype CategorySet
EntryChangedData::getLocationsRemovedAvailability(CategoryTree locationHierarchy)

getLocationsChangedToHaveData

Description Returns all locations in LOCATIONHIERARCHY that (1) are available in both the old entry and the new entry from which this EntryChangedData object was created, and (2) contain no data in the old entry but do contain data in the new entry.

Prototype CategorySet
EntryChangedData::getLocationsChangedToHaveData(CategoryTree locationHierarchy)

getLocationsChangedToHaveNoData

Description Returns all locations in LOCATIONHIERARCHY that (1) are available in both the old entry and the new entry from which this EntryChangedData object was created, and (2) contain no data in the new entry but do contain data in the old entry.

Prototype CategorySet
EntryChangedData::getLocationsChangedToHaveNoData(CategoryTree locationHierarchy)

getLocationsHavingChangedData

Description Returns all locations in LOCATIONHIERARCHY that (1) are available in both the old entry and the new entry from which this EntryChangedData object was created, and (2) have at least one attribute path for which the old and new entries contain different values.

Prototype CategorySet
EntryChangedData::getLocationsHavingChangedData(CategoryTree locationHierarchy)

getModifiedAttributePathsNewEntry

Description Returns the paths of all attributes in LOCATION that (1) are present in both the old entry and the new entry from which this EntryChangedData object was created, and (2) contain different data in the old and new entries. It is possible for an attribute to have different attribute paths across the old entry and the new entry, for example because a multioccurrence sibling has been deleted. In this case, we return the attribute path for the new entry. If LOCATION is not specified or is null, then the comparison is done for global attributes.

Prototype String[]
EntryChangedData::getModifiedAttributePathsNewEntry([Category location])

getModifiedAttributePathsOldEntry

Description Returns the paths of all attributes in LOCATION that (1) are present in both the old entry and the new entry from which this EntryChangedData object was created, and (2) contain different data in the old and new entries. It is possible for the same attribute to have different attribute paths across the old entry and the new entry, for example because a multioccurrence sibling has been deleted. In this case, we return the attribute path for the old entry. If LOCATION is not specified or is null, then the comparison is done for global attributes.

Prototype String[]
EntryChangedData::getModifiedAttributePathsOldEntry([Category location])

getAddedAttributePathsNewEntry

Description Returns the paths of all attributes in LOCATION that (1) are not present in the old entry and (2) are present in the new entry from which this EntryChangedData object was created. If LOCATION is not specified or is null, then the comparison is done for global attributes.

Prototype String[]
EntryChangedData::getAddedAttributePathsNewEntry([Category location])

getDeletedAttributePathsOldEntry

Description Returns the paths of all attributes in LOCATION that (1) are not

present in the new entry and (2) are present in the old entry from which this EntryChangedData object was created. If LOCATION is not specified or is null, then the comparison is done for global attributes.

Prototype String[]
EntryChangedData::getDeletedAttributePathsOldEntry([Category location])

getLocationErrors

Description Returns the locations errors for locations having validation errors.
Will return an empty array if no such errors exists.

Prototype LocationErrors[] EntryValidationErrors::getLocationErrors ()

getLocationForErrors

Description Returns the category associated with the current location errors.

Prototype ICategory LocationErrors::getLocationForErrors ()

getErrorsForLocation

Description [Returns the validation errors for the current location errors. There will be at least one validation error.

Prototype [ValidationError[]] LocationErrors::getErrorsForLocation ()

setItemLocationAttrib

Description Sets the attribute sAttribPath (spec_name/attribute_name) of this item for the given location to sValue.

Prototype void Item::setItemLocationAttrib(Category location, String sAttribPath, Object sValue)

getItemRootEntryNodeForLocation

Description Returns the root EntryNode for this item at the given location.

Prototype EntryNode Item::getItemRootEntryNodeForLocation(Category location)

getItemRootEntryNodesHavingLocationData

Description Returns a list of EntryNodes, each is a root entryNode per location

that has data defined.

Prototype `EntryNode[] Item::getItemRootEntryNodesHavingLocationData()`

makeItemAvailableInLocation

Description Makes this item available in a given location. Available means that an item can have location data for the given location. If `bRecursive` is true than make item available in all descendent locations.

Prototype `void Item::makeItemAvailableInLocation(Category location, [Boolean bRecursive])`

makeItemUnavailableInLocation

Description Makes this item unavailable in a given location. If `bRecursive` is true than make item unavailable in all descendent locations.

Prototype `void Item::makeItemUnavailableInLocation(Category location, [Boolean bRecursive])`

makeItemAvailableInLocations

Description Makes this item available in the given locations. Available means that an item can have location data for the given location. If `bRecursive` is true than make item available in all descendent locations.

Prototype `void Item::makeItemAvailableInLocation(Category[] locations, [Boolean bRecursive])`

makeItemUnavailableInLocations

Description Makes this item unavailable in the given locations. If `bRecursive` is true then make item unavailable in all descendent locations.

Prototype `void Item::makeItemUnavailableInLocations(Category[] locations, [Boolean bRecursive])`

isItemAvailableInLocation

Description Returns true if item is mapped to the given location in the specified category tree.

Prototype `Boolean Item::isItemAvailableInLocation(Category location)`

getLocationsHavingData

Description Returns the category set of locations for which this entry has location specific attributes defined under the specified location or

category tree.

Prototype `CategorySet Item::getLocationsHavingData(Object locationOrCategoryTree)`

locationHasData

Description Returns true if the location has data.

Prototype `Boolean Item::locationHasData(Category location)`

getAvailableLocations

Description Returns `CategorySet` of available locations.

Prototype `CategorySet Item::getAvailableLocations(Object locationOrCategoryTree)`

getSearchResultCtrs

Description Returns the location category trees for which search returned matching locations for this item. Returns null if there are no locations trees found with any matching locations.

Prototype `ICategoryTree[] Item::getSearchResultCtrs()`

getSearchResultForCtr

Description Returns all the matching locations path i.e. full category paths for the given location tree for this item's search result. Returns null if there are no matching locations found the given location tree.

Prototype `String[] Item::getSearchResultForCtr(CategoryTree locationTree)`

setRequiredAttributeGroups

Description Sets the required attribute groups for the workflow step for a given `subViewType`. The parameter `subViewType` can be 'ITEM_LOCATION', 'BULK_EDIT', 'ITEM_EDIT', 'CATEGORY_EDIT', or 'CATEGORY_BULK_EDIT'. The optional parameter `locationHierarchyName` is required when the `subViewType` is 'ITEM_LOCATION'. `WorkflowStep` cannot be of type "SUCCESS", as it is hardwired that an Entry must validate against its Container Spec in order to leave the Success step.

Prototype `void WorkflowStep::setRequiredAttributeGroups(String subViewType, String[]/AttrGroup[] attrGroups, [String locationHierarchyName])`

setEditableAttributeGroups

Description	Sets the editable attribute groups for the workflow step for a given subViewType. The parameter subViewType can be 'ITEM_LOCATION', 'BULK_EDIT', 'ITEM_EDIT', 'CATEGORY_EDIT', or 'CATEGORY_BULK_EDIT'. The optional parameter locationHierarchyName is required when the subViewType is 'ITEM_LOCATION'. WorkflowStep cannot be of type "SUCCESS", as it is hardwired that an Entry must validate against its Container Spec in order to leave the Success step.
Prototype	<code>void WorkflowStep::setEditableAttributeGroups(String subViewType, String[]/AttrGroup[] attrGroups, [String locationHierarchyName])</code>

setViewableAttributeGroups

Description	Sets the viewable attribute groups for the workflow step for a given subViewType. The parameter subViewType can be 'ITEM_LOCATION', 'BULK_EDIT', 'ITEM_EDIT', 'CATEGORY_EDIT', or 'CATEGORY_BULK_EDIT'. The optional parameter locationHierarchyName is required when the subViewType is 'ITEM_LOCATION'. WorkflowStep cannot be of type "SUCCESS", as it is hardwired that an Entry must validate against its Container Spec in order to leave the Success step.
Prototype	<code>void WorkflowStep::setViewableAttributeGroups(String subViewType, String[]/AttrGroup[] attrGroups, [String locationHierarchyName])</code>

getWflStepView

Description	Returns a ctg view with a given subViewType for the workflow step. The parameter subViewType can be 'ITEM_LOCATION', 'BULK_EDIT', 'ITEM_EDIT', 'CATEGORY_EDIT', or 'CATEGORY_BULK_EDIT'. The optional parameter locationHierarchyName is required when the subViewType is 'ITEM_LOCATION'.
Prototype	<code>CtgView WorkflowStep::getWflStepView(String subViewType, [String locationHierarchyName])</code>

getLocationHierarchyNames

Description	Returns the list of location hierarchy names defined in the given workflow step. The optional parameter canModifyAvailability filters the list of location hierarchy names based on the 'modify
-------------	---

location hierarchy availability' flag. If not specified, no filtering takes place.

Prototype `String[] WorkflowStep::getLocationHierarchyNames([Boolean canModifyAvailability])`

getModifyLocationHierarchyAvailability

Description Returns the 'modify location hierarchy availability' flag for a given location hierarchy in the given workflow step. The optional parameter `locationHierarchyName` is required when the `subViewType` is 'ITEM_LOCATION'.

Prototype `Boolean WorkflowStep::getModifyLocationHierarchyAvailability(String locationHierarchyName)`

setModifyLocationHierarchyAvailability

Description Sets the 'modify location hierarchy availability' flag for a given location hierarchy in the given workflow step.

Prototype `void WorkflowStep::setModifyLocationHierarchyAvailability(String locationHierarchyName, Boolean canModifyAvailability)`

getRequiredAttributeGroups

Description Gets the required attribute groups of a workflow step. The result is an array attribute collection names. The optional parameter `subViewType` can be 'ITEM_LOCATION', 'BULK_EDIT', 'ITEM_EDIT', 'CATEGORY_EDIT', or 'CATEGORY_BULK_EDIT'. The optional parameter `locationHierarchyName` is required when the `subViewType` is 'ITEM_LOCATION'.

Prototype `String[] WorkflowStep::getRequiredAttributeGroups([String subViewType], [String locationHierarchyName])`

getEditableAttributeGroups

Description Gets the editable attribute groups of a workflow step. The result is an array attribute collection names. The optional parameter `subViewType` can be 'ITEM_LOCATION', 'BULK_EDIT', 'ITEM_EDIT', 'CATEGORY_EDIT', or 'CATEGORY_BULK_EDIT'. The optional parameter `locationHierarchyName` is required when the `subViewType` is 'ITEM_LOCATION'.

Prototype `String[] WorkflowStep::getEditableAttributeGroups([String`

subViewType], [String locationHierarchyName])

getViewableAttributeGroups

Description Gets the viewable attribute groups of a workflow step. The result is an array attribute collection names. The optional parameter subViewType can be 'ITEM_LOCATION', 'BULK_EDIT', 'ITEM_EDIT', 'CATEGORY_EDIT', or 'CATEGORY_BULK_EDIT'. The optional parameter locationHierarchyName is required when the subViewType is 'ITEM_LOCATION'.

Prototype String[] WorkflowStep::getViewableAttributeGroups([String subViewType], [String locationHierarchyName])

Enable reordering with scripting

In the user interface, catalogs can be added to the Left Pane. If the catalog is set "ordered" by setting the catalog attributes, the user is able to highlight children items or categories and use "cut" and "paste" to change the order. Three script operations were added in this release that allows the reorder, through scripting, of an item or category underneath a parent category. The following script operation have been added to the script library:

- Category:reorderEntry
- Catalog::setOrdered
- Category::getEntryPosition

Category::reorderEntry

Description	This operation is provided for script users to be able to adjust the ordering of either items or categories with a parent category. Ordering is enabled at the catalog level.
Prototype	Integer Category:reorderEntry(ICatalog ctg, IEntry child, Integer position, Boolean bInsertBefore);
Parameters	ICatalog ctg - define the catalog instance IEntry child - the entry instance to be repositioned. This is the source of the move. Integer position - The absolute position (starting at zero) of another Entry in the list. This position indicates the target of the move. Boolean: bInsertBefore - Indicator describing if the child Entry should be inserted before or after the position; true=pre-pended (before), false=appended

	(after). This parameter is optional.
Returns	Integer child: The ID of the recorded child. If the reorder failed, this ID is returned as null.

Catalog::setOrdered

Description	This method is provided to set and unset the catalog ordering.
Prototype	Boolean Catalog::setOrdered(Boolean bOrder)
Parameters	Boolean: bOrder - When set, this sets the catalog ordering. When false his disables the catalog ordering.
Returns	Boolean true if the operation worked, false if it failed

Category::getEntryPosition

Description	This method is provided to get the ordered position of either items or categories with a parent category. Ordering is enabled at the catalog level.
Prototype	Integer Category::getEntryPosition(ICatalog ctg, IEntry child)
Parameters	ICatalog ctg - the catalog instance I Entry child - the entry instance to be repositioned. The source of the move.
Returns	Integer position - position in the order of the child Entry.

Additional changed script operations

This document provides a list of additional script operations that have been modified in WebSphere Product Center 5.0.1 from version 5.0.

Note: The script operations listed in this document are for reference only and are subject to change. Refer to the Script Sandbox in the WebSphere Product Center product for more accurate information.

Each modified script operation listed in the following sections is preceded with one of the acronyms listed in the table below, which represent the type of change that was made.

N	New
D	Deprecated
PU	Prototype updated

DU	Description updated
----	---------------------

Basic: Date

DU setDateField

- Prototype: Date Date::setDateField(String field, Integer value)
- Description: Return a Date equal to the input Date, except that the specified field is set to the given value. Allowed field values are : YEAR MONTH DATE HOUR_OF_DAY MINUTE SECOND

Container: Catalog

D massUpdate

- Prototype: Boolean Catalog::massUpdate (Selection sel, String scriptPath, String parametersPath)
- Description: Do a mass update on the selection, using the script and parameters defined by the given paths (from the docstore)

DU disableContainerProcessingOptions

- Prototype: void Container::disableContainerProcessingOptions(String[] options)
- Description: Disable the specified processing options - possible values: PRE_SCRIPT, POST_SCRIPT, VALUE_RULES, VALIDATION_RULES, DEFAULT_VALUES, DEFAULT_VALUE_RULES, SEQUENCES, TYPE_VALIDATION, MERGE_WITH_OLD_VERSION, MIN_MAX_OCCURANCE, MIN_MAX_LENGTH, POSSIBLE_VALUES, PATTERN_VALIDATION, COL_AREA_LOCKS_VALIDATION, LOCK_CATEGORIES_FOR_ITEM_SAVE, LOCKING, ALL

DU setContainerProperties

- Prototype: void Container::setContainerProperties(HashMap properties)
- Description: The properties specified in the PROPERTIES hashmap are set for the container in question. The hashmap keys can be one of SCRIPT_NAME PRE_SCRIPT_NAME PREVIEW_SCRIPT_NAME ENTRY_BUILD_SCRIPT SCRIPT_RESTRICT_LOCALES. The values are required to be string names. The value for SCRIPT_RESTRICT_LOCALES must be true or false.

N defineLocationSpecificData

- Prototype: void Catalog::defineLocationSpecificData(CategoryTree ctr, Spec spc, AttrGroup[] inhAttrGrps)
- Description: Sets up location specific data for a catalog.

Container: Item

PU new\$CtgItem

- Prototype: new CtgItem([String sCtgName/Catalog ctg, Boolean bRunEntryBuildScript, Boolean bBuildNonPersisted, Boolean bBuildEmptyEntryPicture])
- Description: Returns a new item object. The argument can be a catalog name or a catalog object. The argument being a catalog object allows the propagation of attribute collections to process settings etc. to new items being built with this operation. If no catalog name/object is provided, then the default catalog from the current script context is used. bRunEntryBuildScript or bBuildNonPersisted should be set to false to disable the default behavior of this script operation to run the entry build script or build the non-persisted attributes respectively for this new item.

Container: ItemSet

D setItemSetFetchCategorySpecificAttributes

- Prototype: ItemSet::setItemSetFetchCategorySpecificAttributes

Container: LookupTable

PU put

- Prototype: void put(String sLkpTableName, String sStartKey, String sValue), void put(String sLkpTableName, String sStartKey, String[] asValues)
- Description: Put a new row in the lookup table sLkpTableName

Container: Views

N deleteCtgView

- Prototype: deleteCtgView(CtgView ctgView)
- Description: Delete the catalog view ctgView.

DU setCtgView

- Prototype: CtgView CtgView::setCtgView(String viewType, String[] attrGroupNames, String[] permissions)
- Description: Sets the container view object with the given name/catalog and returns it. The viewType can be 'ITEM_LIST', 'ITEM_POPUP', 'ITEM_LOCATION', 'BULK_EDIT' or 'ITEM_EDIT'. By default ITEM_EDIT is used. Permissions are [V|E]

DU getCtgViewByName

- Prototype: CtgView Container::getCtgViewByName([String viewName, String viewType])
- Description: Returns the view with the corresponding name. If no name is specified, returns the default view. Use '[System Default]' to refer to the default view. The viewType can be 'ITEM_LIST', 'ITEM_POPUP', 'ITEM_LOCATION', 'BULK_EDIT', 'ITEM_EDIT', 'CATEGORY_EDIT' or

'CATEGORY_BULK_EDIT'. By default ITEM_EDIT/CATEGORY_EDIT is used. If the view is not found, it returns null.

Entry: Entry

PU getFlatEntryNodes

- Prototype: `EntryNode[] Entry::getFlatEntryNodes([Boolean skipEmptyGrouping])`
- Description: Returns an array of flat `EntryNodes` of this entry

PU getFlatPrimaryEntryNodes

- Prototype: `EntryNode[] Entry::getFlatPrimaryEntryNodes([Boolean skipEmptyGrouping])`
- Description: Returns an array of flat primary `EntryNodes` of this entry

PU getFlatSecondaryEntryNodes

- Prototype: `EntryNode[] Entry::getFlatSecondaryEntryNodes([Boolean skipEmptyGrouping])`
- Description: Returns an array of flat secondary `EntryNodes` of this entry

N getFlatEntryNodesOf

- Prototype: `EntryNode[] getFlatEntryNodesOf(EntryNode en)`
- Description: Returns an array of all the `entrynodes` under this `entrynode` in depth first order

PU setEntryAttrib

- Prototype: `void Entry::setEntryAttrib(String sAttribPath, Object sValue)`
- Description: Sets the attribute `sAttribPath` (`spec_name/attribute_name`) of this entry to `sValue`. Perform optional checks before update if `bDoChecks` is true.

N getEntryNodeForLocation

- Prototype: `EntryNode Entry::getEntryNodeForLocation(Category location, String sAttribPath)`
- Description: Returns the `EntryNode` for `sAttribPath` (`spec_name/attribute_name`) of this entry for the given location

N setEntryLocationAttrib (Previously setEntryRelationshipAttrib)

- Prototype: `void Entry::setEntryLocationAttrib(Category location, String sAttribPath, Object sValue)`
- Description: Sets the attribute `sAttribPath` (`spec_name/attribute_name`) of this entry for the given location to `sValue`.

N getChangedAttributes

- Prototype: `String[] Entry::getChangedAttributes(Entry secondEntry, [Category location])`
- Description: Returns an array of changed attribute paths. If a location is specified, only the attributes for the location are examined. If a location is specified, and the location does not apply to both entries, null is returned.

PU/DU `getChangedLocations`

- Prototype: `HashMap Entry::getChangedLocations(Entry oldEntry)`
- Description: Returns a `HashMap` that contains 4 `Category[]` mapped to keys `DELETED`, `ADDED`, `MODIFIED`. A location (given by its category) appears in the `Category[]` for `DELETED` if it is in `oldEntry` but not in this entry. It appears in `ADDED`, if it is not in `oldEntry` but is in this entry. And it appears in `MODIFIED` if it is both in `oldEntry` and this entry and some of the attributes changed (and to get the details of those changes, one should call `getChangedEntryNodes` and `getChangedAttributesForMultiOccurrence` for this location).

PU/DU `getChangedAttributesForMultiOccurrence`

- Prototype: `HashMap Entry::getChangedAttributesForMultiOccurrence(Entry oldEntry, [Category location])`
- Description: Returns a `HashMap` that contains 4 `String[]` mapped to keys `DELETED_OLD`, `ADDED_NEW`, `MODIFIED_OLD`, `MODIFIED_NEW`. Used the `XXX_OLD` on `oldEntry` and the `XXX_NEW` on this entry (the new entry). This method determines the differences between the attributes of another `ENTRY` for multi-occurrence (grouping and non-grouping) `ENTRIES`. `ADDED_NEW` and `DELETED_OLD` will only include multi-occurrence attributes (groupings and non-groupings). Note on multi-occurrence non-groupings: The `MODIFIED_NEW` and `_MODIFIED_OLD_lists` will never include any multi-occurrence non-groupings, as multi-occurrence for non-groupings will only show up as Deleted or Added. If a location is specified, only the attributes for the location are examined. If a location is specified, and the location does not apply to both entries, null is returned. Please consult documentation for more details.

DU `getDisplayValue`

- Prototype: `String Entry::getDisplayValue(Locale locale)`
- Description: Returns the primary key value of this entry.

N `getEntryLocationsHavingData`

- Prototype: `CategorySet Entry::getEntryLocationsHavingData(CategoryTree ctr)`

- Description: Returns the set of locations for which this entry has location specific attributes defined in the specified hierarchy.

N `getRootEntryNodeForLocation`

- Prototype: `EntryNode Entry::getRootEntryNodeForLocation(Category location, [Boolean bCreate])`
- Description: Returns the root `EntryNode` for this entry at the given location. `bCreate` returns a root entry node even if there was no data defined already for this location

N `getRootEntryNodesHavingLocationData`

- Prototype: `EntryNode[] Entry::getRootEntryNodesHavingLocationData()`
- Description: Returns a list of `EntryNodes`, each is a root entryNode per location that has data defined.

Entry: `UserDefinedLog`

PU/DU `forEachUserDefinedLogEntry`

- Prototype: `forEachUserDefinedLogEntry(UserDefinedLog UDL, [Entry e,] String[] logEntries [, Boolean bReturnMultipleLogEntries = true]) { statements }`
- Description: Executes the statements for each group of log entries in the given `UserDefinedLog` or, if `Entry e` is defined, each log entry for that specific `Entry`. If `bReturnMultipleLogEntries` is false, the array of log entries will contain only the first (oldest) log in chronological order. This is only a valid option if `Entry e` is not defined. If `bReturnMultipleLogEntries` is true, all logs are populated in the array in ascending chronological order for a given `Entry` (oldest first). By default, `bReturnMultipleLogEntries` is true.

PU/DU `userDefinedLogAddEntry`

- Prototype: `void UserDefinedLog::userDefinedLogAddEntry(Entry entry, [String log_message], [Entry category])`
- Description: Add an entry to the user defined log. If a message is specified, set that for the `UserDefinedLogEntry`. If the category is provided then the logs are only restricted for that category.

PU `userDefinedLogDeleteEntriesFor`

- Prototype: `void UserDefinedLog::userDefinedLogDeleteEntriesFor(Entry entry [, Entry category])`
- Description: Delete all log entries for an entry from the user defined log.

N `userDefinedLogGetEntriesFor`

- Prototype: `UserDefinedLogEntry[]`

UserDefinedLog::userDefinedLogGetEntriesFor(Entry entry[, Entry category])

- Description: Get all log entries for an entry from the user defined log. The category can be provided in order to get the logs associated for that category only.

PU/DU newUserDefinedLogEntry

- Prototype: newUserDefinedLogEntry(Date date, Container container, Entry entry, String log [, Entry category])
- Description: Returns a new user defined log entry object with for the specified entry which is either an item or category (with date/timestamp and log). If the category is also provided the logs will only be associated to that category.

InputOutput: Feed

N startExportByName

- Prototype: Boolean startExportByName(String sName)
- Description: Run the export called sName. Returns TRUE if success.

DU createExport

- Prototype: String createExport(String marketSpecName, String catalogName, String specMapName, String exportScriptName, String syndicationName, [HashMap optionalArgs])
- Description: Creates the Export with given params. An optional parameter charsetName, which may be set in the optionalArgs parameter, describes the file encoding of the export. Otherwise, the Cp1252 is chosen as the default file encoding. Returns Done if successful, Error if not. Here is a complete list of the optional arguments which may be set in the optionalArgs parameter: String approverUserName, String charsetName, String distributionName, String distributionGroupName, String selectionName, String synType, String diffType, String sParamsDocPath. The distributionName and distributionGroupName can be a list of distribution names delimited by the string returned by getStringValueForClassMember(com.ibm.ccd.common.util.Const, CATEGORY_PATH_DELIMITER)

InputOutput: Reader

PU getFullHTTPResponse

- Prototype: <HashMap getFullHTTPResponse(String url, HashMap hmRequestProperties, HashMap hmParameters, String sRequestMethod, [String sEncoding, Doc doc, String sContentType, boolean bGetResponseReader, boolean bPostUserInfo, String sDocStorePath]
- Description: Returns a HashMap (with RESPONSE_READER and RESPONSE_HEADER_FIELDS) for the response for posting

hmParameters or a doc of sContentType against the server at url, Use hmRequestProperties to send specific header information. An optional parameter bGetReader could be used to specify if the function needs to also return the response reader (default is true). An optional parameter bPostUserInfo could be used to specify if the function would need to post the invoking user information (default is false). The response is optionally stored into a document at sDocStorePath in the docstore.

Security: User

PU Clone User

- Prototype: User::cloneUser(String original_username, String username, String firstname, String lastname, String email, Boolean enabled, String password[, Category organization[, HashMap roles[]]]]> </prototype>
- Description: Clones existing user info into a new user. Password field is required. The optional roles and organization fields, when specified, override the roles and/or organization of the existing user.

N getAllUsers

- Prototype: User[] getAllUsers()
- Description: Returns all users

Spec: Spec

N setNodeRuntimeSearchable

- Prototype: void Node::setNodeRuntimeSearchable(Boolean)
- Description: Sets the node to be runtime searchable or not

System Admin: Logger

N getLogger

- Prototype: Logger getLogger(String s)
- Description: Returns a logger (loggers are in the system log directory with the given name)

N loggerDebug

- Prototype: void Logger::loggerDebug(String s)
- Description: Write s to this logger

N loggerInfo

- Prototype: void Logger::loggerInfo(String s)
- Description: Write s to this logger

N loggerWarn

- Prototype: void Logger::loggerWarn(String s)
- Description: Write s to this logger

N loggerFatal

- Prototype: void Logger::loggerFatal(String s)
- Description: Write s to this logger

N getScriptExecutionMode

- Prototype: String getScriptExecutionMode()
- Description: Return the current script execution mode

PU LoggerError

- Prototype: void Logger::loggerError(String s)
- Description: Write s to this logger

Workflow: Collaboration area

N getStepsForEntry

- Prototype: String[] CollaborationArea::getStepsForEntry(Entry entry)
- Description: Returns all the steps that the entry is currently in for the given collaboration area. The return value is a string array containing the stepPaths.

WebSphere Product Center script operations

Basic

Array

add

Description	To add elements to an Array
Prototype	void Array::add(elements)

remove

Description	To remove the element at the specified position
Prototype	void Array::remove(int i)

sort

Description	Return the array sorted
Prototype	Array Array::sort()

Date

addDate

Description	Add the integer value given to the field specified. Allowed field values are : YEAR MONTH DATE HOUR MINUTE
Prototype	Date Date::addDate(String field, Integer value)

formatDate

Description	Use to format a date as a human readable format. The newFormat string is a pattern whose format is identical to the format used by Java
Prototype	String Date::formatDate(String newFormat)

getDateField

Description	Get the value of the field specified. Allowed field values are : YEAR MONTH DATE HOUR_OF_DAY MINUTE SECOND
-------------	--

Prototype	Integer Date::getDateField(String field)
getTime	
Description	Returns the number of seconds since January 1, 1970, 00:00:00 GMT represented by this Date object
Prototype	Integer Date::getTime()
isDateAfter	
Description	Returns true if and only if this date is after otherDate
Prototype	Boolean Date::isDateAfter(Date otherDate)
isDateBefore	
Description	Returns true if and only if this date is before otherDate
Prototype	Boolean Date::isDateBefore(Date otherDate)
new\$Date	
Description	Builds a Date object from a String given a date format
Prototype	new Date(String sFormat, String sDate)
reformatDate	
Description	Takes a date string which is assumed to be formatted according to the pattern indicated by currentDateFormat, and returns a new string formatted according to the newDateFormat provided. If no newDateFormat is given, the WPC dateFormat is used.
Prototype	String reformatDate (String formattedDateString, String currentDateFormat [, String newDateFormat])
setDateField	
Description	Return a Date equal to the input Date, except that the specified field is set to the given value. Allowed field values are : YEAR MONTH DATE HOUR_OF_DAY MINUTE SECOND
Prototype	Date Date::setDateField(String field, Integer value)

value)

today

Description

Returns the current date and time

Prototype

Date today ()

HashMap

containsKey

Description

Returns true if key exists.

Prototype

Boolean HashMap::containsKey(Object key)

containsValue

Description

Returns true if value exists.

Prototype

Boolean HashMap::containsValue(Object val)

forEachHmElement

Description

Executes the statements for each (oKey, oValue) map in hm

Prototype

forEachHmElement(HashMap hm, Object oKey, Object oValue) { statements }

intersectValues

Description

Return the set-intersection of hm1, hm2, ... (only values are considered)

Prototype

HashMap intersectValues(HashMap hm1, HashMap hm2, ...)

keyForValue

Description

Returns a key mapped to valueToSearch in hm or null

Prototype

Object HashMap::keyForValue(Object valueToSearch)

mergeValues

Description

Return the set-union of hm1, hm2, ... (only values are considered)

Prototype

HashMap mergeValues(HashMap hm1, HashMap hm2, ...)

HashMap hm2, ...)

size

Description

Returns the size of a HashMap or any array

Prototype

Integer HashMap::size ()

Language Construct

break-continue

Description

To break/continue from a loop

Prototype

[break | continue]

catchError

Description

Analogous to a try-catch in Java, all statements are executed and errMsg is set to null in the absence of errors

Prototype

catchError(String errMsg) { statements }

escapeForCSV

Description

Escape for CSV

Prototype

String escapeForCSV(String s)

escapeForHTML

Description

Escape for HTML

Prototype

String escapeForHTML(String s)

escapeForJS

Description

Escape for JavaScript

Prototype

String escapeForJS(String s)

for

Description

Equivalent to doing init-statement; while(cond) {t-statements; each-statement;}

Prototype

for(init-statement; cond; each-statement) { t-statements }

if-else

Description

If cond is true t-statements are executed, otherwise f-statements are executed

Prototype

```
if(Boolean cond) { t-statements } [else { f-statements }]
```

logDebug

Description

Logs the debug message with the debug log that is available from the schedule profile details screens. Use with caution because the debug log is maintained in memory.

Prototype

```
void logDebug (String message)
```

logError

Description

Logs the error message with the corresponding item id to the location specified in the context

Prototype

```
void logError(String itemId, String message)
```

logWarning

Description

Logs the warning message with the corresponding item id to the location specified in the context

Prototype

```
void logWarning(String itemId, String message)
```

return

Description

Used in functions: returns e to the caller

Prototype

```
return e
```

throwError

Description

Use to throw a Java-like exception. This operation is usually used in conjunction with the catchError operation

Prototype

```
void throwError (String rejectionCause)
```

useTransaction

Description

Executes the statements in a transaction, rollback takes place if an error occurs

Prototype

```
useTransaction { statements }
```

while

Description	As long as cond is true, t-statements are executed
Prototype	<code>while(Boolean cond) { t-statements }</code>

Numeric

checkDouble

Description	If the input string is null or empty, the default value is returned. Otherwise the original value parsed as an Double is returned.
Prototype	<code>Double checkDouble(String str, Double defaultValue)</code>

checkInt

Description	If the input string is null or empty, the default value is returned. Otherwise the original value parsed as an Integer is returned.
Prototype	<code>Integer checkInt(String str, Integer defaultValue)</code>

max

Description	Return the max
Prototype	<code>Number max(Number a, Number b)</code>

min

Description	Return the min
Prototype	<code>Number min(Number a, Number b)</code>

rand

Description	Returns a random integer that is between 0 and max
Prototype	<code>Integer rand(Integer max)</code>

reformatDouble

Description	Returns a new String representing the number, reformatted to fit the criteria specified by <code>minDigitsBeforeDecPoint</code> and <code>maxDigitsAfterDecPoint</code>
Prototype	<code>String reformatDouble (Double origDouble, Integer minDigitsBeforeDecPoint, Integer</code>

Integer minDigitsBeforeDecPoint, Integer
maxDigitsAfterDecPoint

toDouble

Description Parses str as a Double
Prototype Double toDouble(String str)

toInteger

Description Parses str as an Integer
Prototype Integer toInteger(String str)

RegularExpression

buildRE

Description Returns a regular expression corresponding to the given pattern. Match flags are 0=caseSensitive, 1=ignoreCase, 2=matchMultiline (new lines match as ^ and \$, 4=matchSingleLine (treat multiple lines as one line). Flags are additive.
Prototype new RE(String pattern, Integer matchFlags)

match

Description Return the contents of the parenthesized subexpressions after a successful match
Prototype String[] RE::match(String str)

new\$RE

Description Returns a regular expression corresponding to the given pattern. Optional match flags are 0=caseSensitive, 1=ignoreCase, 2=matchMultiline (new lines match as ^ and \$, 4=matchSingleLine (treat multiple lines as one line). Flags are additive.
Prototype new RE(String pattern, Integer matchFlags)

substitute

Description Return substituteIn with zero or more occurrences of the regular expression specified in the RE

Prototype	object replaced with the substitution string String[] RE::substitute(String substituteIn, String substitution)
-----------	---

ScriptObject

getFunctionByName

Description	Build the function object for the function sFunctionName in this script object
-------------	--

Prototype	FunctionObject ScriptObject::getFunctionByName(String sFunctionName)
-----------	---

getScriptByPath

Description	Build the script object for the script stored at sScriptPath
-------------	--

Prototype	ScriptObject getScriptByPath(String sScriptPath)
-----------	--

getScriptContextValue

Description	Return the value of the variable named sVariableName
-------------	--

Prototype	Object getScriptContextValue(String sVariableName)
-----------	--

invoke

Description	Invoke this function object with the arguments arg1, arg2, etc
-------------	--

Prototype	Object FunctionObject::invoke(Object arg1, Object arg2, etc)
-----------	--

invokeSoapServer

Description	Invoke a soap server. SURL is the URL of the service. SMETHODNAME is the name of the operation called. APARAMVALUES is an array containing the request parameters. APARAMNAMES is an optional array containing the names of the paramters. Returns the return value of the SOAP operation call.
-------------	---

Prototype	Object invokeSoapServer(String sURL, String sMethodName, Object[] aParamValues [,String[]
-----------	---

aParamNames])

runScript

Description

Run this script

Prototype

void ScriptObject::runScript(HashMap
hmContext)

setScriptContextValue

Description

Set the value of the variable named
sVariableName

Prototype

void setScriptContextValue(String
sVariableName, Object oVariableValue)

Scripting

setScriptProgress

Description

Sets the percentage completed value in the
context of a running script

Prototype

setScriptProgress(number percent)

setScriptStatsDeletedCnt

Description

Sets the count of items deleted in the context of a
running script

Prototype

setScriptStatsDeletedCnt(number count)

String

buildCSV

Description

Takes a variable number of arguments, and
returns a string with the arguments concatenated
in csv format

Prototype

String buildCSV (String str1, String str2, ..., String
strN)

buildDelim

Description

Takes a variable number of arguments, and
returns a string with the arguments concatenated
in delim format, using the qualifier to enclose

Prototype	strings that contain the delimiter String buildDelim (String delimiter, String qualifier, String str1, String str2, ..., String strN)
buildFixedWidth	
Description	Takes a variable number of arguments, and returns a string with the arguments concatenated in fixed width format.
Prototype	String buildFixedWidth (String str1, Integer len1, String strN, Integer lenN)
checkString	
Description	If the input string is null or empty, the default value is returned. Otherwise the original value itself is returned.
Prototype	String checkString (String str, String defaultValue)
concat	
Description	Takes a variable number of arguments, and returns a string with the arguments concatenated in the order given
Prototype	String concat (String str1, String str2, ..., String strN)
contains	
Description	Tests if this string contains an occurrence of the match substring
Prototype	Boolean String::contains (String match)
containsUsingLookupTable	
Description	Return true if and only if the string contains at least one of the keys from the lookup table
Prototype	Boolean String::containsUsingLookupTable(LookupTable lkp)
endsWith	
Description	Tests if this string ends with an occurrence of the match substring

Prototype

Boolean String::endsWith (String match)

escapeWithHTMLEntities

Description

Translates all character with HTML character codes less than beg or greater than end to HTML character codes

Prototype

String escapeWithHTMLEntities(String str, Integer beg, Integer end)

getLoginString

Description

Returns the url string needed for login automatically to the given url as the current user. If you are an admin, you can generate a login string for another user by passing the username as an extra parameter. Note that the url should not include the server name/port and should start with '/'. If an error occurs, a null string is returned.

Prototype

String getLoginString(String sUrl, Date dExpirationDate, [String sUserName])

getNameFromPath

Description

if str contains / returns the substring of str after the last / char exclusively, otherwise returns the original string

Prototype

String getNameFromPath(String str)

getPageURL

Description

Return the URL for the page requested given the required object. The required objects are either: an Item, ItemList, or Category

Prototype

String getPageURL(requiredObject)

getParentPath

Description

if str contains / returns the substring of str up to the last / char exclusively, otherwise returns the empty string

Prototype

String getParentPath(String str)

getRidOfRootName

Description

If str contains / gets rid of all preceding first / inclusive

inclusive

Prototype

String getRidOfRootName(String str)

getMemorySummary

Description

Invokes the garbage collector, sleeps for 5 seconds and then returns a string summarizing memory usage.

Prototype

String getMemorySummary()

indexOf

Description

Returns the index within this string of the first occurrence of the specified match substring

Prototype

Integer String::indexOf (String match)

isLowerCase

Description

Checks if all the characters in this string are lower case using the rules of the default locale

Prototype

Boolean String::isLowerCase ()

isStringSingleByte

Description

Returns true if the string is made of single byte characters only, false otherwise

Prototype

Boolean isStringSingleByte(String s)

isUpperCase

Description

Checks if all the characters in this string are upper case using the rules of the default locale

Prototype

Boolean String::isUpperCase ()

lastIndexOf

Description

Returns the index within this string of the rightmost occurrence of the specified match substring

Prototype

Integer String::lastIndexOf (String match)

length

Description

Returns the length of this string

Prototype

Integer String::length ()

newLookupTable

Description Returns a new lookup table with the given spec and name.

Prototype `newLookupTable(Spec spec, String name)`

parseCSV

Description Returns an array of each token, as parsed by the CSV parser. If a field number is provided, just the corresponding token substring is returned.

Prototype `String[] String::parseCSV () | String
String::parserCSV(Integer field)`

parseDelim

Description Returns an array of each token, as parsed by the Delim parser. If a field number is provided, just the corresponding token substring is returned.

Prototype `String[] String::parseDelim (String delimiter) |
String String::parseDelim (String delimiter,
Integer iField)`

parseFixedWidth

Description Returns the corresponding token substring between the two indexes

Prototype `String String::parseFixedWidth (Integer
beginIndex, Integer endIndex)`

removeHTML

Description Returns a new string resulting from removing all html tags from the original string

Prototype `String removeHTML (String str)`

replace

Description Returns a new string resulting from replacing all occurrences of the match substring in this string with the replacement substring

Prototype `String replaceString (String str, String match,
String replacement)`

replaceCharsNotInDecRangeWithHex

Description Does the replace where `iStartDecRange` and `iEndDecRange` are inclusive

	iEndDecRange are inclusive
Prototype	String replaceCharsNotInDecRangeWithHex (String str, Integer iStartDecRange, Integer iEndDecRange, String sEncoding, String sQualifier)
replaceString	
Description	Returns a new string resulting from replacing all occurrences of the match substring in this string with the replacement substring
Prototype	String replace (String str, String match, String replacement)
replaceUsingLookupTable	
Description	Return a string in which any substring matching a key in the lookup table is replace by the corresponding value
Prototype	String String::replaceUsingLookupTable(LookupTable lkp)
resizeString	
Description	Use to increase the size of a string to the finalLength by applying the appropriate padding to the left or right of the string with the given padChar.
Prototype	String resizeString (String str, Integer finalLength, Character padChar, Boolean padToTheRight)
splitLine	
Description	Returns an array of tokens obtained by breaking the line using this parser (e.g. CSV parser, fixed width parser)
Prototype	String[] IParser::splitLine()
startsWith	
Description	Tests if this string begins with an occurrence of the match substring
Prototype	Boolean String::startsWith (String match)

stripOutNonASCII

Description Returns a new string resulting from removing all non-ASCII characters in this string

Prototype String stripOutNonASCII (String str)

substitute

Description Substitutes a string for this regular expression in another string. This method works like the Perl function

Prototype String RE::substitute(String substituteIn, String substitution)

substring

Description Returns a new string that is a substring of this string. The beginIndex is inclusive but endIndex is not.

Prototype String substring (String str, Integer beginIndex [, Integer endIndex])

toLowerCase

Description Converts all of the characters in this string to lower case using the rules of the default locale

Prototype String toLowerCase (String str)

toTitleCase

Description Converts the first alphabet of all the words in a string to upper case

Prototype String toTitleCase (String str)

toUpperCase

Description Converts all of the characters in this string to upper case using the rules of the default locale

Prototype String toUpperCase (String str)

trim

Description Removes white space from both ends of this string

Prototype String trim (String str)

unescapeHTMLEntities

Description Translates all character escaped with HTML character codes to corresponding characters

Prototype String urlEncode(String str)

urlEncode

Description Translates a string into x-www-form-urlencoded format

Prototype String urlEncode(String str)

Zip

unzip

Description Unzip zip file given by srcPath into directory given by dstPath

Prototype Boolean unzip(String srcPath, String dstPath)

zip

Description Zips files under directory given by srcPath and creates zip file given by dstPath

Prototype Boolean zip(String srcPath, String dstPath)

Container

Attribute Groups

addAttributeToAttrGroup

Description Adds an attribute to the attribute collection.

Prototype void
AttrGroup::addAttributeToAttrGroup(String attrPath)

addLocalesToAttrGroup

Description Adds the locales to the Attribute Collection

Prototype void AttrGroup::addLocalesToAttrGroup(String localesCSVString)

addLocalizedNodeToAttrGroup

Description	Associates this localized node with this attribute collection
Prototype	void AttrGroup::addLocalizedNodeToAttrGroup(Node node)

addSpecToAttrGroup

Description	Associates all the nodes of the spec with this attribute collection. If the bDynamic flag is set to true then any additional nodes added to the spec, after the spec has been associated to the Attribute Collection, will become part of the Attribute Collection. If the bDynamic flag is set to false then only the nodes that are part of the spec at this time only will be added to the Attribute Collection.
Prototype	void AttrGroup::addSpecToAttrGroup(Spec spec, [boolean bDynamic])

deleteAttrGroup

Description	Deletes this attribute collection
Prototype	void AttrGroup::deleteAttrGroup()

getAllAttrGroupsForAttribute

Description	Returns an array of AttrGroups where the attrPath is included. Return null if attrPath is not included in any Attribute Group.
Prototype	AttrGroup[] getAllAttrGroupsForAttribute(String attrPath)

getAllAttributePathsFromAttrGroup

Description	Returns all the attribute paths associated with this attribute collection
Prototype	String[] AttrGroup::getAllAttributePathsFromAttrGroup())

getAttrGroupByName

Description	Returns the attribute collection with the given name. Otherwise it becomes null.
-------------	--

Prototype `AttrGroup getAttrGroupByName(String name)`

getAttrGroupName

Description Returns the name of this attribute collection

Prototype `String AttrGroup::getAttrGroupName()`

getAttrGroupType

Description Returns the type of this attribute collection. Type can only be GENERAL or INHERITANCE.

Prototype `String AttrGroup::getAttrGroupType()`

new\$AttrGroup

Description Returns a new attribute collection with the given name, type and description. Type can either be GENERAL or INHERITANCE

Prototype `new AttrGroup(String name, String type, [String desc])`

removeAttributeFromAttrGroup

Description Removes the attribute from the attribute collection.

Prototype `void AttrGroup::removeAttributeFromAttrGroup(String attrPath)`

removeLocalesFromAttrGroup

Description Removes the locales from the Attribute Collection

Prototype `void AttrGroup::removeLocalesFromAttrGroup(String localesCSVString)`

removeSpecFromAttrGroup

Description Disassociates all the nodes of the spec from this attribute collection

Prototype `void AttrGroup::removeSpecFromAttrGroup(Spec spec)`

Catalog

buildTestCatalogData

Description	Create a document at sDocStorePath for the file specification fileSpec with nbRows of random data, with the primary key starting at firstSku
Prototype	buildTestCatalogData(Spec fileSpec, String sDocStorePath, Integer nbRows [, Integer firstSku])

containsByPrimaryKey

Description	Returns true if the catalog or item set contains an item with the primary key sPrimaryKey
Prototype	boolean Catalog::containsByPrimaryKey(String sPrimaryKey) - boolean ItemSet::containsByPrimaryKey(String sPrimaryKey)

deleteCatalog

Description	(deprecated)
Prototype	

disableInheritance

Description	Will not retrieve Inherited data for the container from the database
Prototype	void Container::disableInheritance()

exportCatalog

Description	Use to syndicate a catalog using marketplaceSpec and specMap
Prototype	void Catalog::exportCatalog(Spec marketplaceSpec, SpecMap specMap)

getCatalogAccessControlGroupName

Description	Returns the Access Control Group for this catalog.
Prototype	String Catalog::getCatalogAccessControlGroupName()

getCatalogAttribute

Description	Returns a list of values for the attribute sAttribName
-------------	--

Prototype	String[] Catalog::getCatalogAttribute(String sAttribName)
getCatalogAttributes	
Description	Returns a HashMap mapping attributes to their respective values
Prototype	HashMap Catalog::getCatalogAttributes()
getCatalogCategoryTrees	
Description	Return an array with category trees of this catalog
Prototype	HashMap Catalog::getCatalogCategoryTrees()
getCatalogId	
Description	returns the id of this catalog.
Prototype	Integer Catalog::getCatalogId()
getCatalogItemCountInVersion	
Description	Returns the number of items in the specified version of this catalog
Prototype	Integer Catalog::getCatalogItemCountInVersion(Version version)
getCatalogNamesList	
Description	Return the list of names of available catalogs filtered by catalog privileges LIST (list catalog), VIEW_ITEMS (view items in catalog), MODIFY_ITEMS (modify items in catalog). By default the catalog names for the catalogs with LIST privilege access are returned.
Prototype	String[] getCatalogNamesList([String filterByPrivilege]
getCatalogsByAttributeValue	
Description	Returns all catalogs that have the provided value for the attribute
Prototype	Catalog[] getCatalogsByAttributeValue(String attribute_name, String value)

getCatalogSpec

Description

Returns the spec this catalog. If the optional boolean `bGetImmutableSpec` is set to true, an immutable spec is returned.

Prototype

`Spec Catalog::getCatalogSpec([Boolean bGetImmutableSpec])`

getCatalogVersion

Description

Returns the version of this catalog.

Prototype

`Version Catalog::getCatalogVersion()`

getCatalogVersionSummary

Description

Return an array with versions of this catalog - most recent first

Prototype

`Versions[] Catalog::getCatalogVersionSummary()`

getCategorizedItemCountInVersion

Description

Returns the number of items categorized in the specified category tree for the specified version of this catalog

Prototype

`Integer Catalog::getCategorizedItemCountInVersion(Version version, CategoryTree ctgtree)`

getContainerId

Description

Returns the id of this container.

Prototype

`Integer Container::getContainerId()`

getContainerLocalesForRole

Description

Gets the locales that are allowed for this container specifically for the particular role.

Prototype

`String Container::getContainerLocalesForRole(Role role)`

getCtgByName

Description

Returns the catalog object with the corresponding name. If no name is provided, return the default catalog (if defined).

Prototype	Catalog getCtgByName([String name]
getCtgCategorySpecs	
Description	Returns the category specs for this catalog
Prototype	HashMap Catalog::getCtgCategorySpecs()
getCtgFileDiffStatus	
Description	Returns true or false to indicate whether or not the file was modified between the two versions selected for differences syndication
Prototype	Boolean getCtgFileDiffStatus(String sFileName)
getCtgFileExists	
Description	Returns true or false to indicate whether the physical file really exists
Prototype	Boolean getCtgFileExists(String sFileName)
getCtgItemByAttributeValue	
Description	Returns ItemSet of items from the catalog that have the provided value for the attribute (currently implemented only for nodes in the catalog spec)
Prototype	ItemSet Catalog::getCtgItemByAttributeValue(String node_path, String value)
getCtgItemByPrimaryKey	
Description	Method deprecated. Use Container::getEntryByPrimaryKey. Returns the item from the catalog with the given primary key - this method cannot be used to retrieve newly created items that have not been saved yet.
Prototype	Item Catalog::getCtgItemByPrimaryKey(String sPrimaryKey)
getCtgItemIdByPrimaryKey	
Description	Returns an item id by primary key
Prototype	Integer Catalog::getCtgItemIdByPrimaryKey(String sPrimaryKey)

getCtgName

Description

Returns the name of this catalog

Prototype

String Catalog::getCtgName()

getCtgSpec

Description

Returns the spec this catalog. If the optional boolean `bGetImmutableSpec` is set to true, an immutable spec is retrieved (you can not modify the spec, but it is faster to retrieve). By default you get a mutable spec.

Prototype

Spec Catalog::getCtgSpec([Boolean
bGetImmutableSpec])

getDefaultCatalogName

Description

See `getCtgByName()`. Returns the name of the catalog being used for an aggregation/syndication.

Prototype

(deprecated) String getDefaultCatalogName()

getItemBySku

Description

(deprecated) see `getCtgItemByPrimarykey`

Prototype

(deprecated) see `getCtgItemByPrimarykey`

getItemSetForCatalog

Description

returns an ItemSet of the items in this catalog

Prototype

ItemSet Catalog::getItemSetForCatalog()

getItemSetForPrimaryKeys

Description

Returns an ItemSet of the items in this catalog for the given primary keys - set `bOptimize` to true if you don't plan on changing the items, the item set is then optimized but these items don't keep track of changed attributes

Prototype

ItemSet
Catalog::getItemSetForPrimaryKeys(Array pkeys,
Boolean bOptimize)

getItemsInCategory

Description

Returns an array of the items in this category. The option Boolean 'ordered' being set to true

	<p>makes the operation return the ordered children of this category if the catalog is set up to use ordering.</p>
Prototype	<pre>Item[] Catalog::getItemsInCategory(Category, [Boolean ordered])</pre>
getPrimaryCategoryTree	
Description	Returns the primary category tree of this catalog
Prototype	<pre>CategoryTree Catalog::getPrimaryCategoryTree()</pre>
hasCtgListPermission	
Description	Returns true if the current user has permission to list this catalog, false otherwise
Prototype	<pre>Boolean Catalog::hasCtgListPermission()</pre>
insertNewVersion	
Description	Add a version called sName on this catalog
Prototype	<pre>Version Catalog::insertNewVersion(String sName)</pre>
loadCatalog	
Description	Use to aggregate a file into the catalog using the given fileSpec and the given specmap.
Prototype	<pre>void Catalog::loadCatalog(String docStorePathForFileToLoad, Spec fileSpec, SpecMap specMap, String feedType [itm icm ctr])</pre>
new Catalog	
Description	<p>Returns a new catalog with the given spec and name. Pass optional args in the map with these keys "useInheritance" (default is false), "displayAttribute" (path of node), "accessControlGroup" (pass the ACG object), "isLookupTable" (default is false--set to true to create a lookup table and the Default Lookup Table Hierarchy is used as the category tree). If the displayAttribute is not set, the pk attribute is used.</p>
Prototype	<pre>new Catalog(Spec catalogSpec, String name, CategoryTree categoryTree [,Hashmap</pre>

optionalArgs]

setCatalogAccessControlGroupName

Description Sets the Access Control Group to the given name for this catalog.

Prototype void
Catalog::setCatalogAccessControlGroupName(String acgName)

setContainerProperties

Description The properties specified in the PROPERTIES hashmap are set for the container in question. The hashmap keys can be one of SCRIPT_NAME PRE_SCRIPT_NAME PREVIEW_SCRIPT_NAME ENTRY_BUILD_SCRIPT. The values are required to be string names.

Prototype

setDefaultCtgView

Description Sets the ctgview as the default catalog view.

Prototype void Catalog::setDefaultCtgView(CtgView ctgView)

Category

addChildCategory

Description Adds childCategory as a child of this category

Prototype Boolean Category::addChildCategory(Category childCategory)

addItemSecondarySpecToCategory

Description Associates a secondary spec defining this categories attrs. The optional parameters allows for the Spec to be associated with the category but does not build out the EntryNode structure, useful to improve performance on imports

Prototype void
Category::addSecondarySpecToCategory(String sSpecName, [Boolean bAdd])

addSecondarySpecToCategory

Description	Associates a secondary spec defining this categories attrs.
Prototype	void Category::addSecondarySpecToCategory(String sSpecName)

deleteCategory

Description	Delete the category
Prototype	void Category::deleteCategory()

getCategoryAttrib

Description	Returns the value of the attribute sAttribPath (spec_name/attribute_name) of this category
Prototype	Object Category::getCategoryAttrib(String sAttribPath)

getCategoryChildren

Description	Returns the categories immediately below this category. The option Boolean 'ordered' being set to true makes the operation return the ordered children of this category if the catalog (if not specified, the default catalog) is set up to use ordering. The option restrictToSubtreeWithItems being set to true only returns categories that have items in their sub-trees.
Prototype	Category[] Category::getCategoryChildren([Boolean ordered, Catalog catalog, Boolean restrictToSubtreeWithItems])

getCategoryHasChildren

Description	Returns true if the category has children.
Prototype	Boolean Category::getCategoryHasChildren()

getCategoryLevels

Description	Returns the levels of this category in an array of Integers.
Prototype	Integer[] Category::getCategoryLevels()

getCategoryOrganizations

Description Return the all organizations this category is mapped to

Prototype Organization[]
Category::getCategoryOrganizations()

getCategoryParent

Description Returns this category's parent. If there are multiple parents, only the first one is returned.

Prototype Category Category::getCategoryParent
([CategoryCache cat_cache])

getCategoryParents

Description Returns the parent categories of this Category

Prototype Category[] Category::getCategoryParents ()

getCategoryTree

Description Returns the category tree object this category belongs to. Use getCategoryTreeByName() to get the category tree being used for an aggregation/syndication.

Prototype CategoryTree Category::getCategoryTree()

getFullPaths

Description Returns the full name paths of this Category, using the sDelimiter as the delimiter if provided. The full path returned includes the root categories name if bWithRootName is true.

Prototype String[] Category::getFullPaths ([String sDelimiter], [boolean bWithRootName])

getItemSecondarySpecsForCategory

Description Returns the item secondary specs associated with this category

Prototype Spec[]
Category::getItemSecondarySpecsForCategory([Catalog ctg])

getItemSetForCategory

Description Returns an ItemSet of the items in this category. The option Boolean 'loaded' being set to true

The option Boolean 'ordered' being set to true makes the operation return the ordered children of this category if the catalog is set up to use ordering.

Prototype

ItemSet
Category::getItemSetForCategory(Catalog ctg, [Boolean ordered])

getMappedCategories

Description

Returns the categories in ctr (if any) to which this category is mapped

Prototype

Category[]
Category::getMappedCategories(CategoryTree ctr)

getSecondarySpecsForCategory

Description

Returns the secondary specs defining this categories attrs

Prototype

Spec[]
Category::getSecondarySpecsForCategory()

mapCategoryToOrganizations

Description

Maps the category to all the organizations provided. If bAdd is true, the old mappings are added to otherwise they are overwritten to be the new set of organizations

Prototype

void
Category::mapCategoryToOrganizations(Category[] categories [, boolean bAdd])

removeChildCategory

Description

Remove childCategory from this category's children. Only allowed if childCategory has at least another parent.

Prototype

void Category::removeChildCategory(String categoryName)

removeItemSecondarySpecFromCategory

Description

Disassociates a secondary item spec to from this Category.

Prototype

void
Category::removeItemSecondarySpecFromCategory

Category::removeItemSecondarySpecFromCategory(String sSpecName))

removeSecondarySpecFromCategory

Description Disassociates a secondary spec defining this categories attrs.

Prototype void
Category::removeSecondarySpecFromCategory(String sSpecName))

setCategoryAttrib

Description Sets the attribute sAttribPath (spec_name/attribute_name) of this category to sValue

Prototype void Category::setCategoryAttrib(String sAttribPath, Object sValue)

CategorySet

forEachCategorySetElement

Description Executes the statements for each (oCategory) in the categorySet

Prototype forEachCategorySetElement(CategorySet categorySet, Object oCategory) { statements }

getCategorySetSize

Description Returns the number of categories in a category set

Prototype Integer CategorySet::getCategorySetSize()

CategoryTree

buildCategory

Description Returns a new category object when given the complete path of the new category and the delimiter that separates the categories in the path. If the primary key is not specified, then it should either be automatically set via a sequence or value rule, or it should be set after creation. The

final path part will be initially assigned to the pk, if the pk is not supplied.

Prototype

```
Category CategoryTree::buildCategory(String path, [String delimiter], [String primaryKey])
```

deleteCategoryTree

Description

Delete the category tree ctr. Returns Validation Error array if any validation errors occurred. Null if successful

Prototype

```
ValidationError[] deleteCategoryTree(CategoryTree ctr)
```

getCategoryByPath

Description

Returns the category with a full name path equivalent to sNamePath. sNamePath is expected to be delimited by sDelim. sNamePath should not contain the name of the root category, since we are already restricted to a specific category tree. If bLight is true, not all data for the category is retrieved. If bReadOnly is true, a read only copy of the category is retrieved - bReadOnly should be used in exports, for example

Prototype

```
Category CategoryTree::getCategoryByPath(String sNamePath, String sDelim, [boolean bUsingCode])
```

getCategoryByPathNoCfp

Description

Returns the category with a full name path equivalent to sNamePath. sNamePath is expected to be delimited by sDelim. sNamePath should not contain the name of the root category, since we are already restricted to a specific category tree. If bLight is true, not all data for the category is retrieved. If bReadOnly is true, a read only copy of the category is retrieved - bReadOnly should be used in exports, for example

Prototype

```
Category CategoryTree::getCategoryByPathNoCfp (String sNamePath, String sDelim [, boolean bLight, boolean bReadOnly])
```

getCategoryCache

Description

Returns a CategoryCache for this CategoryTree. The cache will be empty if get_all_categories is false and the size will be the greater of the given size or 100. If get_all_categories is true then the cache will contain all the categories for the given category tree and the size arguments will be ignored. The size of the cache in the latter case will be the greater of the number of categories in the tree or 100

Prototype

CategoryCache
CategoryTree::getCategoryCache(Integer size, Boolean get_all_categories)

getCategorySet

Description

Returns a CategorySet for this CategoryTree

Prototype

CategorySet
CategoryTree::getCategorySet([Boolean bReadOnly])

getCategorySetByAttributeValue

Description

Returns a CategorySet with all categories in the category tree which have the given AttribName and AttribValue

Prototype

CategorySet
CategoryTree::getCategorySetByAttributeValue(String attribName, Object attribValue, [Boolean bReadOnly])

getCategorySetByFullNamePath

Description

Returns an CategorySet of the categories in the category tree from the given full name paths. Do not include the category tree name in the full name paths

Prototype

CategorySet
CategoryTree::getCategorySetByFullNamePath(String[] fullNamePaths, String delimiter)

getCategorySetByItemSecondarySpec

Description

Returns an CategorySet that is a subset of the categories of this tree having the specified spec in their item secondary spec list]

Prototype `CategorySet`
`CategoryTree::getCategorySetByItemSecondarySpec(String specName)`

getCategorySetByLevel

Description Returns an `CategorySet` of the categories in the category tree at a particular level

Prototype `CategorySet`
`CategoryTree::getCategorySetByLevel(Integer level, [Boolean bReadOnly])`

getCategorySetByPrimaryKey

Description Returns a `CategorySet` with the categories in the category tree which have match the primary key

Prototype `CategorySet`
`CategoryTree::getCategorySetByPrimaryKey(String primaryKey, [Boolean bReadOnly])`

getCategorySetByStandAloneSpec

Description Returns an `CategorySet` that is a subset of the categories of this tree having the specified spec in their stand alone spec list

Prototype `CategorySet`
`CategoryTree::getCategorySetByStandAloneSpec(String specName)`

getCategoryTreeByName

Description Returns the category tree object with the corresponding name. If name is not provided, return the category tree being used for the aggregation/syndication.

Prototype `CategoryTree getCategoryTreeByName([String name])`

getCategoryTreeName

Description returns the name of this categoryTree.

Prototype `String CategoryTree::getCategoryTreeName()`

getCategoryTreeNamesList

Description Return the list of names of available category trees filtered by category tree privileges LIST (list

category tree), VIEW_ITEMS (view items in category tree),
 MODIFY_CATEGORY_ATTRIBUTES (modify category attributes in category tree). By default the category tree names for the category tree with LIST privilege access are returned.

Prototype
 String[] getCategoryTreeNamesList([String filterByPrivilege])

getCategoryTreeSpec

Description
 Returns the spec of this category tree

Prototype
 Spec CategoryTree::getCategoryTreeSpec()

getDefaultCategoryTreeName

Description
 See getCategoryTreeByName(). Returns the name of the category tree being used for an aggregation/syndication. Use getCategoryTreeByName() to get the category tree being used for the aggregation/syndication.

Prototype
 (deprecated) String
 getDefaultCategoryTreeName()

getDefaultCtrViewName

Description
 Returns name of default category tree view.

Prototype
 String CategoryTree::getDefaultCtrViewName()

hasCtrListPermission

Description
 Returns true if the current user has permission to list this category tree, false otherwise

Prototype
 Boolean CategoryTree::hasCtrListPermission()

new\$Category

Description
 Returns a new category object when given the complete path of the new category and the delimiter that separates the categories in the path. If the primary key is not specified, then it should either be automatically set via a sequence or value rule, or it should be set after creation. The final path part will be initially assigned to the pk, if the pk is not supplied.

Prototype
 new Category(CategoryTree ctr, String path, [String delimiter], [String primaryKey])

[String delimiter], [String primaryKey]

new CategoryTree

Description

Returns a new category tree with the given primary spec and name. Pass optional args in the map with these keys "useInheritance" (default is false), "displayAttribute" (path of node), "pathAttribute" (path of node), "accessControlGroup" (pass the ACG object), "isOrganizationTree" (default is false--set to true to create an organization tree). If the pathAttribute is not set, the primary key will be used. If the displayAttribute is not set, the pathAttribute is used.

Prototype

```
new CategoryTree(Spec spec, String name  
[,HashMap optionalArgs])
```

setDefaultCtrView

Description

Sets the ctrview as the default category tree view.

Prototype

```
void CategoryTree::setDefaultCtrView(CtgView  
ctrView)
```

saveCategoryTree

Description

Saves this category tree. DO NOT USE in AGGREGATION if you are in a item-to-category feed or a category tree feed. The category tree you are aggregating to gets saved automatically at the end of an aggregation. However, if you side affect another category tree, then call this operation to capture the changes you made. Returns Validation Error array if any validation errors occurred. Null if successful

Prototype

```
ValidationError[]  
CategoryTree::saveCategoryTree ()
```

setCategoryCacheFetchSize

Description

Sets the category cache fetch size (i.e. the number of categories gotten in bulk each time). This is only applicable if the category cache is associated with an ItemSet.

Prototype

```
void  
CategoryCache::setCategoryCacheFetchSize(Inte
```


ger i)

CategoryTreeMap

addCategoryTreeMapping

Description Add a map between the two categories cat1 and cat2

Prototype void
CategoryTreeMap::addCategoryTreeMapping(Category cat1, Category cat2)

getCategoryTreeMap

Description Returns the category tree map between the two category trees ctr1 and ctr2

Prototype CategoryTreeMap
getCategoryTreeMap(CategoryTree ctr1, CategoryTree ctr2)

removeCategoryTreeMapping

Description Remove a map between the two categories cat1 and cat2

Prototype void
CategoryTreeMap::removeCategoryTreeMapping(Category cat1, Category cat2)

saveCategoryTreeMap

Description Save this category tree map

Prototype void CategoryTreeMap::saveCategoryTreeMap()

Item

buildCtgItem

Description

Prototype (deprecated) see new\$CtgItem

cloneItem

Description Create and return a clone of this item.

Prototype Item Item::cloneItem()

deleteCtgItem

Description

Delete the catalog item itm

Prototype

void deleteCtgItem(Item itm)

displayCtgItemAttrib

Description

Returns the html string for displaying item attribute specified by attribute path

Prototype

String Item::displayCtgItemAttrib(String sAttribPath)

forEachCtgItem

Description

Executes the statements for each item in the catalog called sCatalogName

Prototype

forEachCtgItem([String sCatalogName,], Item item) { statements }

getCatalog

Description

Returns the catalog for this item.

Prototype

Catalog Item::getCatalog()

getChangedAttributes

Description

Returns an array of changed attribute paths

Prototype

String[] Entry::getChangedAttributes(Entry secondEntry)

getCtgItemAllCategories

Description

(Deprecated) See getCtgItemCategories. Return the all categories this item is mapped to,

Prototype

Category[] Item::getCtgItemCategories()

getCtgItemAtOldVersion

Description

Returns the old version of the item in the differences syndication.

Prototype

Item Item::getCtgItemAtOldVersion()

getCtgItemAttribByPk

Description

Returns the value of the attribute sAttribPath (spec_name/attribute_name) of this item

Prototype Object Catalog::getCtgItemAttribByPk(String pk, String sAttribPath)

getCtgItemOrganizations

Description Return the all organizations this item is mapped to

Prototype Organization[] Item::getCtgItemOrganizations()

getCtgItemAttrib

Description Returns the value of the attribute sAttribPath (spec_name/attribute_name) of this item

Prototype Object Item::getCtgItemAttrib(String sAttribPath)

getCtgItemAttribNamesList

Description Returns an array of String containing the attribute name of all the attributes of this item (optional parameter allows option exclude categorySpecificAttribute - true by default)

Prototype String[]
Item::getCtgItemAttribNamesList([Boolean bAllAttributes])

getCtgItemAttribs

Description Returns a HashMap mapping the paths (spec_name/attribute_name) of attributes to their respective values

Prototype HashMap Item::getCtgItemAttribs()

getCtgItemAttribsList

Description Returns an array of String containing the paths (spec_name/attribute_name) of all the attributes of this item

Prototype String[] Item::getCtgItemAttribsList()

getCtgItemAttributeNewValue

Description

Prototype (deprecated) use Item::getCtgItemAttrib()

getCtgItemAttributeOldValue

(deprecated) use Item::getCtgItemAtOldVersion()

getCtgItemAttributesStatus

Description Returns a HashMap of {attributePath}->{the difference status (A, M, D, U)} for each attribute of the item.

Prototype HashMap Item::getCtgItemAttributesStatus()

getCtgItemCategories

Description Return the categories this item is mapped to. If catTreeName is given, returns the categories within that ctr only (use the default category tree if no category tree is passed). Also, can use an optional CategoryCache passed in catCache

Prototype Category[] Item::getCtgItemCategories([String catTreeName] [, CategoryCache catCache])

getCtgItemCategoryPaths

Description Returns an array of delimited strings of the category paths this item belongs to. If ctr is given, returns the paths of the categories within that ctr only.

Prototype String[] Item::getCtgItemCategoryPaths(String sPathDelimiter, [Boolean bWithRoot], [CategoryTree ctr])

getCtgItemCatSpecificAttribsList

Description Returns an array of String containing the paths (spec_name/attribute_name) of all the category specific attributes of this item

Prototype String[] Item::getCtgItemCatSpecificAttribsList()

getCtgItemDiffStatus

Description For content difference syndications, returns this item's difference status (A, M, D, U)

Prototype String Item::getCtgItemDiffStatus()

getCtgItemId

Description Returns this item's Id

Prototype Integer Item::getCtgItemId()

getCtgItemMappedAttrib

Description

Returns the value of the attribute mapped to/from sAttribMappedPath (mapped_spec_name/attribute_name) of this item

Prototype

String Item::getCtgItemMappedAttrib(String sAttribMappedPath)

getCtgItemMappedAttribs

Description

Returns a HashMap with the mapped attributes values indexed by their path (mapped_spec_name/attribute_name) of this item

Prototype

HashMap Item::getCtgItemMappedAttribs()

getCtgItemMappedAttribsList

Description

Returns an array of String containing the paths (mapped_spec_name/attribute_name) of all the mapped attributes of this item

Prototype

String[] Item::getCtgItemMappedAttribsList()

getCtgItemPrimaryKey

Description

Returns this item's primary key value

Prototype

String Item::getCtgItemPrimaryKey()

getCtgItemRelatedItemInfo

Description

Returns an array of length 2 containing: [0]=Related Item's Catalog's Name, [1]=Related Item's Primary Key, for the related item represented by the given internal unique item id, at the browsing version of the catalog of the given item

Prototype

String[] Item::getCtgItemRelatedItemInfo(Integer iItemId)

getLinkedItemForNode

Description

Returns the linked item associated with the specified node.

Prototype

Item Item::getLinkedItemForNode(String node_path)

getOriginalItem

Description

Returns the original picture of the item before modification. Deprecated. Please use `Entry::getOriginalEntry`

Prototype

`Item Item::getOriginalItem()`

getRootItemNode

Description

Return the root item node for this item

Prototype

`EntryNode Item::getRootItemNode()`

mapCtgItemToCategory

Description

Map this item to this category. If optional boolean `ADDTOPICTURE` is false, the secondary specs will not be associated and cannot be set; useful for performance. If optional boolean `VALIDATECATEGORY` is true and the category's hierarchy does not have the `VALIDATION_RULES` option disabled, the mapping will only occur if the category passes validation.

Prototype

`void Item::mapCtgItemToCategory(Category category, [Boolean addToPicture], [Boolean validateCategory])`

mapCtgItemToOrganizations

Description

Maps the item to all the organizations provided. If `bAdd` is true, the old mappings are added to otherwise they are overwritten to be the new set of organizations. Deprecated--Call `moveCtgItemToCategories`

Prototype

`void Item::mapCtgItemToOrganizations(Category[] organizations [, boolean bAdd])`

moveCtgItemToCategories

Description

Move item from existing categories to new set of categories, if `bAdd` is true, then category mappings will be added.

Prototype

`void Item::moveCtgItemToCategories(Category[] categories, [, boolean bAdd])`

new\$CtgItem

Description

Returns a new item object. The argument can be a catalog name or a catalog object. The argument being a catalog object allows the propagation of attribute collections to process settings etc. to new items being built with this operation. If no catalog name/object is provided, then the default catalog from the current script context is used. `bRunEntryBuildScript` or `bBuildNonPersisted` should be set to false to disable the default behavior of this script operation to run the entry build script or build the non-persisted attributes respectively for this new item.

Prototype

```
new CtgItem([String sCtgName/Catalog ctg],  
[Boolean bRunEntryBuildScript], [Boolean  
bBuildNonPersisted])
```

removeCtgItemFromCategory

Description

Remove mapping from this item to this category, if the mapping exists.

Prototype

```
void  
Item::removeCtgItemFromCategory(Category  
category)
```

saveCtgItem

Description

Save the item. When called outside of an import script, returns null if the save was successful, otherwise returns an array of `ValidationError`'s. When called in an import, returns null.

Prototype

```
ValidationError[] Item::saveCtgItem()
```

setCtgItemAttrib

Description

Sets the attribute `sAttribPath` (`spec_name/attribute_name`) of this item to `sValue`

Prototype

```
void Item::setCtgItemAttrib(String sAttribPath,  
Object sValue)
```

setCtgItemMappedAttrib

Description

Sets the attribute mapped to/from `sAttribMappedPath` (`mapped_spec_name/attribute_name`) of this item

	to sValue
Prototype	<code>void Item::setCtgItemMappedAttrib(String sAttribPath, Object oValue)</code>
setCtgItemMappedAttribs	
Description	Set the attributes of this item: hmPathValue should contain (path_y, value_x)'s; the item attribute path_x receives value_x if path_y is mapped to path_x in specmap - if no spec map is specified, the specmap of the import is being used.
Prototype	<code>void Item::setCtgItemMappedAttribs(HashMap hmPathValue, [SpecMap specmap])</code>
setCtgItemPrimaryKey	
Description	Sets this item's primary key value
Prototype	<code>void Item::setCtgItemPrimaryKey(String pk)</code>
setCtgItemRelationshipAttrib	
Description	Sets the attribute sAttribPath (spec_name/attribute_path) of type RELATIONSHIP of this item to the related item represented by the given catalog and primary key
Prototype	<code>void Item::setCtgItemRelationshipAttrib(String sAttribPath, Catalog relatedItemCtg, String sRelatedItemPrimaryKey)</code>
setCtgItemRelationshipAttribUsingItem	
Description	Sets the attribute sAttribPath (spec_name/attribute_path) of type RELATIONSHIP of this item to the related item given
Prototype	<code>void Item::setCtgItemRelationshipAttribUsingItem(String sAttribPath, Item relatedItem)</code>
setExitValue	
Description	Set the exit value of an entry in a workflow step. Assumed to be called from an IN(), OUT(), or TIMEOUT() step script function.

Prototype `Entry::setExitValue(String exitValue)`

setIgnoreCategorySpecificAttributes

Description Set whether or not category specific attributes should be processed for the item

Prototype `void
Item::setIgnoreCategorySpecificAttributes(Boolea
n bIgnore)`

validateMappedAttribs

Description Validate a set of attribute values indexed by their mapped path against the destination spec

Prototype `HashMap validateMappedAttribs(HashMap
hmPathValue, [SpecMap specmap])`

ItemNode

getItemNode

Description Return the first item node matching the path sPath

Prototype `ItemNode ItemNode::getItemNode(String sPath)`

getItemNodeChildren

Description Return the children of this ItemNode

Prototype `ItemNode[] ItemNode::getItemNodeChildren()`

getItemNodePath

Description Return the path of this item node

Prototype `String ItemNode::getItemNodePath()`

getItemNodes

Description Return the item nodes matching the path sPath

Prototype `ItemNode[] ItemNode::getItemNodes(String
sPath)`

getItemNodeValue

Description Return the value of this ItemNode

Prototype `String ItemNode::getItemNodeValue()`

setItemNode

Description	Return the itemNode with path sPath (building any node needed along the path) or null if the path is invalid
Prototype	ItemNode ItemNode::setItemNode(String sPath)

setItemNodeRelationshipValue

Description	Set the value of this ItemNode of type RELATIONSHIP to the related item represented by the given catalog and primary key
Prototype	void ItemNode::setItemNodeRelationshipValue(Catalog relatedItemCtg, String sRelatedItemPrimaryKey)

setItemNodeRelationshipValueUsingItem

Description	Set the value of this ItemNode of type RELATIONSHIP to the related item given
Prototype	void ItemNode::setItemNodeRelationshipValueUsingItem(Item relatedItem)

setItemNodeValue

Description	Set the value of this ItemNode and return it
Prototype	Object ItemNode::setItemNodeValue(Object value)

ItemSet

associateCategoryCacheToItemSet

Description	Associates the CategoryCache to the ItemSet so that when items are fetched, the corresponding categories are also fetched in bulk
Prototype	void ItemSet::associateCategoryCacheToItemSet(CategoryCache catCache)

forEachItemSetElement

Description	Executes the statements for each (oItem) map in the ItemSet
-------------	---

the ItemSet
Prototype
forEachItemSetElement(ItemSet is, Object oItem)
{ statements }

getItemSetSize

Description
Returns the number of items in an item set
Prototype
Integer ItemSet::getItemSetSize()

setItemSetFetchCategorySpecificAttributes

Description
Sets the item set to fetch or not fetch category specific attributes
Prototype
void
ItemSet::setItemSetFetchCategorySpecificAttributes(Boolean b)

setItemSetFetchLinkedItems

Description
Sets the item set to fetch or not fetch master linked items
Prototype
void
ItemSet::setItemSetFetchLinkedItems(Boolean b)

setItemSetFetchSize

Description
Sets the item set fetch size (i.e. the number of items gotten in bulk each time)
Prototype
void ItemSet::setItemSetFetchSize(Integer i)

sortItemSet

Description
Sorts the ItemSet for performance
Prototype
void ItemSet::sortItemSet()

LookupTable

addRow

Description
Add a new row to this lookup table - with value(s) sValue/asValues for the key sKey. Returns TRUE if and only if the add was successful.
Prototype
Boolean LookupTable::addRow(String sKey, String sValue), Boolean

LookupTable::addRow(String sKey, String[] asValues)

getKeysFromValues

Description

Reverse lookup of keys using values from the lookup table. The values can either be Paths in the Spec or the column number of the lookup table starting from 0 and not including the Key column.

Prototype

String[]
LookupTable::getKeysFromValues(String[] values)

getLkpByName

Description

Returns the lookup table object with the corresponding name. By default the lookup table is read-only, but can be made mutable by setting the isReadOnly parameter to false.

Prototype

LookupTable getLkpByName(String name, [Boolean isReadOnly])

getLkpId

Description

Return the id of this lookup table.

Prototype

Integer LookupTable::getLkpId()

getLkpKeys

Description

Return the keys of this lookup table

Prototype

String[] LookupTable::getLkpKeys()

lookup

Description

Returns the sSecKey-th value for sKey in the lookup table sLookupTableName or lkp

Prototype

String lookup(String sLookupTableName, String sKey [, String sSecKey]), String
lookup(LookupTable lkp, String sKey [, String sSecKey])

lookupValues

Description

Returns values for sKey in the lookup table lkp

Prototype

String[] lookupValues(LookupTable lkp, String sKey)

sKey)

put

Description

Put a new row in the lookup table
sLkpTableName

Prototype

```
void put(String sLkpTableName, String  
sStartKey, [String sEndKey,] String sValue), void  
put(String sLkpTableName, String sStartKey,  
[String sEndKey,] String[] asValues)
```

Queues

createQueue

Description

Creates a new queue with the given parameters.

Prototype

```
IMsgQueue createQueue (String queueName,  
String queueDesc, MsgQueueProtocolEnum  
protocol, String syncScriptPath))
```

getMessageFromQueue

Description

Gets the indexth oldest message from the given queue. For example, `getMessageFromQueue("Queue1", 2)` would return the 2nd oldest message from the queue with name "Queue1". If there is no such message or queue, returns null.

Prototype

```
Message getMessageFromQueue (String  
queueName, Integer index)
```

getMsgAppResponse

Description

Initiates the request for response for a message.

Prototype

```
Void Message::getMsgAppResponse()
```

getMsgAppResponseDoc

Description

Returns the Doc object for the message.

Prototype

```
Doc Message::getMsgAppResponseDoc()
```

getMsgAttachments

Description

Returns a HashMap of attachment names to attachments for the given message.

Prototype	HashMap Message::getMsgAttachments ()
getMsgByMsgId	
Description	Returns the message object with the message id msgId null otherwise.
Prototype	Message getMsgByMsgId(String msgId)
getMsgDoc	
Description	Returns the Doc object for the message.
Prototype	Doc Message::getMsgDoc()
getMsgId	
Description	Returns the generated unique id for the message.
Prototype	String Message::getMsgId()
getMsgProtocolResponseDoc	
Description	Returns the Doc object for the message.
Prototype	Doc Message::getMsgProtocolResponseDoc()
getMsgQueue	
Description	Returns the MsgQueue object for the message.
Prototype	MsgQueue Message::getMsgQueue()
qmgrGetMsgQueueByName	
Description	Returns the queue if present in the system.
Prototype	MsgQueue qmgrGetMsgQueueByName(String queueName)
sendMsg	
Description	Sends the message. If successful, will return a message object. If it fails it will return null.
Prototype	Message MsgQueue::sendMsg(Doc doc)
setMsgDoc	
Description	Sets the Doc object for the message.
Prototype	void Message::setMsgDoc(IDoc doc)

Selection

addEntryToSelection

Description Add the entry to the basic selection - the entry can be an item or a hierarchy node (does nothing for advanced selection).

Prototype void Selection::addEntryToSelection(Entry entry)

deleteSelection

Description Delete the selection. Return true if the deletion occurred, false if selection was in use.

Prototype boolean Selection::deleteSelection()

getHierarchyNodeSetForSelection

Description Return the hierarchy nodes in that selection as a HierarchyNodeSet

Prototype HierarchyNodeSet
Selection::getHierarchyNodeSetForSelection()

getItemSetForSelection

Description Return the items in that selection as a ItemSet

Prototype ItemSet Selection::getItemSetForSelection()

getSelectionAccessControlGroupName

Description Returns the Access Control Group for this selection.

Prototype String
Selection::getSelectionAccessControlGroupName()
()

getSelectionByName

Description Return the selection called sName

Prototype Selection getSelectionByName(String sName)

getSelectionCatalog

Description Returns the selection's catalog

Prototype Catalog Selection::getSelectionCatalog()

getSelectionHierarchy

Description Returns the selection's hierarchy.

Prototype `Hierarchy Selection::getSelectionHierarchy()`

getSelectionHierarchyNodeCount

Description Returns the number of hierarchy nodes in a selection - returns 0 for advanced selections.

Prototype `Integer Selection::getSelectionHierarchyNodeCount()`

getSelectionItemCount

Description Return count of the items in the selection

Prototype `Integer Selection::getSelectionItemCount()`

getSelectionName

Description Returns the name of this selection

Prototype `String Selection::getSelectionName()`

getSelectionNamesList

Description Return the list of names of available selections for catalog

Prototype `String[] getSelectionNamesList(Catalog catalog)`

new\$AdvancedSelection

Description Builds a new advanced selection (Selection) with the given name/catalog and returns it. Call `saveSelection` to save it.

Prototype `new AdvancedSelection(Catalog catalog, String name, String expression)`

new\$BasicSelection

Description Returns an empty basic selection (Selection) on catalog

Prototype `new BasicSelection(Catalog catalog, String name)`

saveSelection

Description Save the basic or advanced selection to the database

Prototype `void Selection::saveSelection()`

setSelectionAccessControlGroupName

Description	Sets the Access Control Group to the given name for this selection.
Prototype	void Selection::setSelectionAccessControlGroupName(String acgName)

setSelectionName

Description	Returns the name of this selection
Prototype	void Selection::setSelectionName(String name)

Version

getVersionDate

Description	Returns the date of this version
Prototype	Date Version::getVersionDate()

getVersionName

Description	Returns the type of this version
Prototype	String Version::getVersionName()

getVersionType

Description	Returns the type of this version
Prototype	String Version::getVersionType()

Views

Sample script for creating views

addCtgTab

Description	Add container tab object to the catalog view. The tab is added to the end of the list of tabs already defined for the container ctg view.
Prototype	void CtgView::addCtgTab(CtgTab tab)

getCtgTabAttrGroupsList

Description	Returns a list of ordered attribute collections for the catalog view tab
-------------	--

Prototype	the catalog view tab String[] CtgTab::getCtgTabAttrGroupsList()
getCtgTabRow	
Description	Get the set of rows in the current container tab object
Prototype	CtgTabRow[] CtgTab::getCtgTabRow()
getCtgTabs	
Description	Gets an ordered array of container tab objects for the particular container view
Prototype	CtgTab[] CtgView::getCtgTabs()
getCtgViewAttrGroupsList	
Description	Returns list of ordered attribute groups for the catalog view.
Prototype	String[] CtgView::getCtgViewAttrGroupsList()
getCtgViewAttribsList	
Description	Returns list of ordered attribute paths for the catalog view.
Prototype	String[] CtgView::getCtgViewAttribsList()
getCtgViewByName	
Description	Returns the view with the corresponding name. If no name is specified, returns the default view. Use '[System Default]' to refer to the default view. The viewType can be 'ITEM_LIST', 'ITEM_POPUP', 'BULK_EDIT', 'ITEM_EDIT', 'CATEGORY_EDIT' or 'CATEGORY_BULK_EDIT'. By default ITEM_EDIT/CATEGORY_EDIT is used. If the view is not found, it returns null.
Prototype	CtgView Container::getCtgViewByName([String viewName, String viewType])
getCtgViewPermission	
Description	Returns the permission [E-editable V-viewable] for the node specified by the path in the current view.

Prototype `String CtgView::getCtgViewPermission(String attrGroupName)`

getCurrentCtgViewName

Description Returns name of current catalog view (only in Data Entry scripts). Returns an empty string outside of the Data Entry scripts.

Prototype `String getCurrentCtgViewName()`

getDefaultCtgViewName

Description Returns name of default catalog view.

Prototype `String Catalog::getDefaultCtgViewName()`

getListOfCtgViewNames

Description Returns an array of view names available for this catalog. An entry with '[System Default]' is always included as the first entry.

Prototype `String[] Catalog::getListOfViewNames()`

getNewCtgTab

Description Builds a new container tab object with the given name and returns it. The tab needs to be added to the catalog view in order to save it.

Prototype `CtgTab CtgView::getNewCtgTab(String name, AttrGroup[] rows)`

getTabRowPath

Description Returns the attribute path for this tab row.

Prototype `String CtgTabRow::getTabRowPath()`

insertCtgTabAt

Description Insert container tab object to the catalog view at the index position(zero base). If index is invalid, tab is added to the end of the list.

Prototype `void CtgView::insertCtgTabAt(CtgTab tab, Integer index)`

new\$CtgTabRow

Description Builds a new container tab row object for the node specified by the path.

Prototype	CtgTabRow CtgTabRow(String path)
new\$CtgView	
Description	Builds a new Ctg View
Prototype	new CtgView(Container container, String name)
removeCtgTabAt	
Description	Remove container tab object to the catalog view at the index position (zero base)
Prototype	void CtgView::removeCtgTabAt(Integer index)
saveCtgTabs	
Description	Save the container tab objects that were new/modified in the container view
Prototype	void CtgView::saveCtgTabs()
saveCtgView	
Description	Saves the current ctgview to the database
Prototype	Boolean CtgView::saveCtgView()
setCtgTabRow	
Description	Sets the current container tab object to the new set of rows
Prototype	void CtgTab::setCtgTabRow(CtgTabRow[] rows)
setCtgView	
Description	Sets the container view object with the given name/catalog and returns it. The viewType can be 'ITEM_LIST', 'ITEM_POPUP', 'BULK_EDIT' or 'ITEM_EDIT'. By default ITEM_EDIT is used. Permissions are [V E]
Prototype	CtgView CtgView::setCtgView(String viewType, String[] paths, String[] permissions)
setTabular	
Description	Sets the CtgTabRow object (for grouping node only) to display the children in tabular format. string sets to 'T' or 'F'
Prototype	void CtgTabRow::setDisplayTabular(String str)

Sample Script for Creating Views

```
ctg = getCtgByName("Ctg1");
defCtgViewName = ctg.getDefaultCtgViewName();
editCtgView = ctg.getCtgViewByName(defCtgViewName);

mypath = [];
mypath.add("Ctg1/Key");
mypath.add("Ctg1/Group/EAN/en_MY");
mypath.add("Ctg1/Group/EAN/zh_MY");
mypath.add("Ctg1/Group/EAN/ms_MY");

//out.writeln(mypath);
myper = [];
myper.add("E");
myper.add("V");
myper.add("E");
myper.add("V");

newCtgView = newCtgView.setCtgView("ITEM_EDIT", mypath, myper);
newCtgView.saveCtgView();
newCtgView = newCtgView.setCtgView("BULK_EDIT", mypath, myper);
newCtgView.saveCtgView();
```

(given a catalog view, set the ctg view into different subview with different permissions and save them individually)

DocStore

Doc

copyDoc

Description	Copy this document to the specified sPath in the docstore. If the path ends with a '/' it is assumed that the doc needs to be copied to the specified directory with its current name
Prototype	Doc Doc::copyDoc(sPath)

deleteDoc

Description	Delete this document from the docstore
Prototype	void Doc::deleteDoc()

forEachDocument

Description	Executes the statements for each document (used in distribution scripts). If the optional docs_list
-------------	---

parameter is provided, however, the statements are executed for each element of docs_list

Prototype

```
forEachDocument([Doc[] docs_list, ], Doc doc) {  
statements }
```

getDocAttribute

Description

Return the attribute sAttributeName from this document

Prototype

```
String Doc::getDocAttribute(String  
sAttributeName)
```

getDocAttributes

Description

Return the attributes of this document

Prototype

```
HashMap Doc::getDocAttributes()
```

getDocByPath

Description

Return the document with path sPath

Prototype

```
Doc getDocByPath(String sPath)
```

getDocContentAsString

Description

Return the content of this document as a string. WARNING - this means that the entire content of the document, however big, will be returned in a string so the user needs to make sure that any call of this operation is not going to be used in a situation where the content of the document is too big (too big being defined by the amount of memory available to the process this operation is running in).

Prototype

```
String Doc::getDocContentAsString()
```

getDocLastModifiedTimeStamp

Description

Returns the date/time this document was last modified

Prototype

```
Date Doc::getDocLastModifiedTimeStamp()
```

getDocLength

Description

Returns the length of the document in kilo bytes. If bBytes is true, value is returned in bytes instead of Kb. Important when smaller files are

Prototype	Integer Doc::getDocLength([Boolean bBytes concerned])
getDocListByPaths	
Description	Return the document at each path specified in sPaths
Prototype	Doc[] getDocListByPaths(String[] sPaths)
getDocPath	
Description	Return this document path
Prototype	String Doc::getDocPath()
getHrefForDocPath	
Description	Return an absolute path for the document with path sDocPath. This can be used in an HTML reference to provide a link to the document.
Prototype	String getHrefForDocPath(String sDocPath)
moveDoc	
Description	Move this document to the specified sPath in the docstore. If the path ends with a '/' it is assumed that the doc needs to be moved to the specified directory with the same doc name as the source
Prototype	Doc Doc::moveDoc(sPath)
saveMultipartRequestData	
Description	Saves the documents sent through multipart post in the docstore at location:/archives/uploaded/multipart/saveDir/. If a charset is given, that is used. Otherwise, the default_charset_value as specified in austin.properties is used.
Prototype	Doc[] saveMultipartRequestData(String saveDir, [String charset])
setDocAttribute	
Description	Set the attribute sAttributeName to sAttributeValue for this document
Prototype	void Doc::setDocAttribute(String sAttributeName, String sAttributeValue)

DocStore

getDocStoreDirectoriesInDirectory

Description	Return the list of paths of directories under the directory sPath
Prototype	String[] getDocStoreDirectoriesInDirectory(String sPath)

getDocStoreFilesInDirectory

Description	Return the list of paths of documents under the directory sPath
Prototype	String[] getDocStoreFilesInDirectory(String sPath)

getDocStoreSubtreeList

Description	Return the list of files under sPath
Prototype	String[] getDocStoreSubtreeList(String sPath)

XML Document

Sample Script for new\$XMLDocument

new XMLDocument

Description	Creates an XmlDocument from a docstore Doc instance or a string.
Prototype	new XmlDocument(Doc doc/String str)

validateXML

Description	Validates an XmlDocument from a docstore Doc instance
Prototype	String validateXML(String docPath)

Sample Script for new\$XMLDocument

```
var files = getDocStoreFilesInDirectory("dms/files");  
var i;
```



```

var len = files.size();
for( i = 0; i < len; i++)
{
var doc = getDocByPath(files[i]);
var xmlDoc = new XmlDocument(doc);
var action = parseXMLNode("action");
forEachXMLNode("properties/property")
{
...
}
}
}

```

Entry

Entry

displayEntryAttrib

Description	Returns the html string for displaying entry attribute specified by attribute path
Prototype	String Entry::displayEntryAttrib(String sAttribPath)

getChangedAttributesForMultiOccurrence

Description	Returns a HashMap that contains 4 String[] mapped to keys DELETED_OLD, ADDED_NEW, MODIFIED_OLD, MODIFIED_NEW. Used the XXX_OLD on oldEntry and the XXX_NEW on this entry (the new entry). This method determines the differences between the attributes of another ENTRY for multi-occurrence(grouping and non-grouping) ENTRIES. ADDED_NEW and DELETED_OLD will only include multi-occurrence attributes (groupings and non-groupings). Note on multi-occurrence non-groupings: The MODIFIED_NEW and _MODIFIED_OLD_lists will never include any multi-occurrence non-groupings, as multi-occurrence for non-groupings will only show up as Deleted or Added. Please consult documentation for more details.
Prototype	HashMap Entry::getChangedAttributesForMultiOccurrence (Entry oldEntry)

getDestinationEntrySetForRelatedEntries

Description Returns EntrySet with all entries this entry is related to filtering by container if filter Container is provided.

Prototype EntrySet
Entry::getDestinationEntrySetForRelatedEntries(Container filterContainer)

getDisplayValue

Description Returns the display value for the entry. If no display value is available then the primary key value is returned.

Prototype String Entry::getDisplayValue(Locale locale)

getEntryAttrib

Description Returns the value of the attribute sAttribPath (spec_name/attribute_name) of this entry

Prototype Object Entry::getEntryAttrib(String sAttribPath)

getEntryAttribModificationTime

Description Returns the time when the attribute sAttribPath (spec_name/attribute_name) of this entry was last modified

Prototype Date
Entry::getEntryAttribModificationTime(String sAttribPath)

getEntryAttribModifier

Description Returns the user who last modified the attribute sAttribPath (spec_name/attribute_name) of this entry

Prototype String Entry::getEntryAttribModifier(String sAttribPath)

getEntryAttribs

Description Returns a HashMap mapping the paths (spec_name/attribute_name) of attributes to their respective values

Prototype HashMap Entry::getEntryAttribs()

getEntryAttribsList

Description

Returns an array of String containing the paths (spec_name/attribute_name) of all the attributes of this entry

Prototype

String[] Entry::getEntryAttribsList()

getEntryContainer

Description

Gets the holding container for this Entry. Could be a catalog or category tree. Use isEntryAnItem to determine which one.

Prototype

Object Entry::getEntryContainer()

getEntryId

Description

Returns this entry's ID

Prototype

Integer Entry::getEntryId()

getEntryRelatedItemInfo

Description

Returns an array of length 2 containing: [0]=Related Item's Catalog's Name, [1]=Related Item's Primary Key, for the related item represented by the given internal unique item id, at the browsing version of the catalog of the given entry

Prototype

String[] Entry::getEntryRelatedItemInfo(int itemId)

getEntrySaveResult

Description

Returns the result of the last save called on this entry. Returns one of the following strings {ADDED,DELETED,MODIFIED,UNKNOWN}

Prototype

String Entry::getEntrySaveResult()

getEntrySetForPrimaryKeys

Description

Returns an EntrySet of the entries in this container for the given primary keys - set bOptimize to true if you don't plan on changing the entries, the entry set is then optimized but this items don't keep track of changed attributes

Prototype

EntrySet
Container::getEntrySetForPrimaryKeys(Array

pkeys, Boolean bOptimize)

getEntrySetSize

Description

Returns the number of entries in an entry set

Prototype

Integer EntrySet::getEntrySetSize()

getEntryStatus

Description

Returns the status of the entry

Prototype

String Entry::getEntryStatus()

getFlatEntryNodes

Description

Returns an array of flat entryNodes of this entry

Prototype

EntryNode[] Entry::getFlatEntryNodes()

getFlatPrimaryEntryNodes

Description

Returns an array of flat primary entryNodes of this entry

Prototype

EntryNode[] Entry::getFlatPrimaryEntryNodes()

getFlatSecondaryEntryNodes

Description

Returns an array of flat secondary entryNodes of this entry

Prototype

EntryNode[]
Entry::getFlatSecondaryEntryNodes()

getItemsInheritingDataForPath

Description

Returns a array of pairs consisting of the Catalog Name and Primary Key of Items that may be inheriting data from the given Entry. Array has -- catalogName, PrimaryKey!

Prototype

Object[][]
Entry::getItemsInheritingDataForPath(String sAttribPath)

getOriginalEntry

Description

Returns the original picture of the entry as stored in the database. If the entry is new or deleted, this operation returns null.

Prototype

Entry Entry::getOriginalEntry()

getRootEntryNode

Description Return the root entry node for this entry

Prototype `EntryNode Entry::getRootEntryNode()`

getSourceEntrySetForRelatedEntries

Description Returns `EntrySet` with all entries that have an attribute related to this entry filtering by container if `filterContainer` is provided.

Prototype `EntrySet Entry::getSourceEntrySetForRelatedEntries(Container filterContainer)`

isEntryAnItem

Description Returns `TRUE` if this entry is an `Item`, `FALSE` if it is a `Category`.

Prototype `Boolean Entry::isEntryAnItem()`

isEntryCheckedOut

Description Returns `true` if the entry is checked out into a collaboration area otherwise it returns `false`.

Prototype `Boolean Entry::isEntryCheckedOut()`

populateAllNonPersisted

Description Execute non-persisted script for all entrynodes in the entry. Return `true` if the script was completed successfully, `false` otherwise.

Prototype `Boolean Entry::populateAllNonPersisted()`

setEntryAttrib

Description Sets the attribute `sAttribPath (spec_name/attribute_name)` of this entry to `sValue`. Perform optional checks before update if `bDoChecks` is `true`.

Prototype `void Entry::setEntryAttrib(String sAttribPath, Object sValue, [Boolean bDoChecks])`

setEntryRelationshipAttrib

Description Sets the attribute `sAttribPath (spec_name/attribute_path)` of type `RELATIONSHIP` of this entry to the related item

represented by the given catalog and primary key

Prototype

```
void Entry::setEntryRelationshipAttrib(String sAttribPath, Catalog relatedItemCtg, String sRelatedItemPrimaryKey)
```

setEntryRelationshipAttribUsingItem

Description

Sets the attribute sAttribPath (spec_name/attribute_path) of type RELATIONSHIP of this entry to the related item given

Prototype

```
void Entry::setEntryRelationshipAttribUsingItem(String sAttribPath, Item relatedItem)
```

setEntryStatus

Description

Sets the status of the entry

Prototype

```
void Entry::setEntryStatus(String status)
```

EntryNode

deleteEntryNode

Description

Remove this entry node from the item. Please note that at least one occurrence of a node needs to be in the entry picture in order to display correctly all the nodes of the chosen attribute collections. The entry picture is the entry node tree image in memory. When you delete the last occurrence of a node, you don't delete the node per se, but rather you're setting its value to null.

Prototype

```
void EntryNode::deleteEntryNode()
```

getEntry

Description

Returns the Entry behind the EntryNode.

Prototype

```
Entry EntryNode::getEntry()
```

getEntryNode

Description

Return the first entry node matching the path sPath

Prototype `EntryNode EntryNode::getEntryNode(String sPath)`

getEntryNodeChildren

Description Return the children of this EntryNode

Prototype `EntryNode[]
EntryNode::getEntryNodeChildren()`

getEntryNodeExactPath

Description Returns the exact path of this entry node - the following is always true:
`rootNode.getEntryNode(entryNode.getEntryNodeExactPath()) == entryNode`

Prototype `String EntryNode::getEntryNodeExactPath()`

getEntryNodeInheritedValue

Description Return the value of this EntryNode

Prototype `Object
EntryNode::getEntryNodeInheritedValue()`

getEntryNodeInheritedValueSourceEntryUniqueID

Description Returns a system wide unique ID for the entry where this value is inherited from. Returns null otherwise.

Prototype `String
EntryNode::getEntryNodeInheritedValueSourceEntryUniqueID()`

getEntryNodeInheritedDataContainerName

Description Returns the name of the container of the inherited data. Returns null if there is no inherited data.

Prototype `String
EntryNode::getEntryNodeInheritedDataContainerName()`

getEntryNodePath

Description Returns the Spec Node path of this entry node, NOT the relative path of this attr.

Prototype `String EntryNode::getEntryNodePath()`

getEntryNodes

Description

Return the entry nodes matching the path sPath

Prototype

EntryNode[] EntryNode::getEntryNodes(String sPath)

getEntryNodeValue

Description

Return the value of this EntryNode

Prototype

Object EntryNode::getEntryNodeValue()

getNodeFromEntryNode

Description

Returns the Node object for this entry node.

Prototype

Node EntryNode::getNodeFromEntryNode()

getNodePath

Description

Returns the path of this node.

Prototype

String Node::getNodePath()

hasInheritedValue

Description

Returns TRUE if this EntryNode has an inherited value (non-null value in category or catalog item associated via an inheritance rule). Returns FALSE if there is no inherited data.

Prototype

Boolean EntryNode::hasInheritedValue()

hasNonInheritedValue

Description

Returns TRUE if there is a non-inherited value. The presence or absence of inherited values makes no difference

Prototype

Boolean EntryNode::hasNonInheritedValue()

isEntryNodeInheritedDataFromItem

Description

Returns TRUE if the inherited data is from an Item. Returns false if there is no inherited data, or data is from a Category.

Prototype

Boolean
EntryNode::isEntryNodeInheritedDataFromItem(
)

populateNonPersistedForEntryNode

Description	Execute non-persisted script for this entrynode. Return true if the script was completed successfully, false otherwise.
Prototype	Boolean EntryNode::populateNonPersistedForEntryNode ()

setEntryNode

Description	Return the entryNode with path sPath relative to EntryNode, building any node needed along the path, or null if the path is invalid
Prototype	EntryNode EntryNode::setEntryNode(String sPath)

setEntryNodeRelationshipValue

Description	Set the value of this EntryNode of type RELATIONSHIP to the related item represented by the given catalog and primary key
Prototype	void EntryNode::setEntryNodeRelationshipValue(Catalog relatedItemCtg, String sRelatedItemPrimaryKey)

setEntryNodeRelationshipValueUsingItem

Description	Set the value of this EntryNode of type RELATIONSHIP to the related item given
Prototype	void EntryNode::setEntryNodeRelationshipValueUsingItem(Item relatedItem)

setEntryNodeValue

Description	Set the value of this EntryNode and return it
Prototype	Object EntryNode::setEntryNodeValue(Object value)

Entry Set

forEachEntrySetElement

Description	Executes the statements for each (oEntry) in the entrySet
Prototype	forEachEntrySetElement(EntrySet entrySet, Object oEntry) { statements }

UserDefinedLog

dumpUserDefinedLog

Description	Dump all log entries from the user defined log to the Writer provided in no specific order. out - this is the output writer you want to dump the UDL to delim - the delimiter used for the current UDL entries outputType - one of COPY_UDE_OUTPUT, CSV_OUTPUT, XML_OUTPUT COPY_UDE_OUTPUT: dump each UDL entry exactly how it is currently stored CSV_OUTPUT: dump each UDL entry as comma seperated values XML_OUTPUT: dump each UDL entry within XML tags; docTag and hmNodeTags must also be specified docTag - this will comprise the XML tag surrounding the UDL dump hmNodeTags - this is the array of labels for each subtag to surround each delimited value
Prototype	void UserDefinedLog::dumpUserDefinedLog(Writer out, String delim, String outputType, String docTag, HashMap hmNodeTags)

insertUserDefinedLog

Description	Persist the new user defined log object to the database.
Prototype	void UserDefinedLog::insertUserDefinedLog()

newUserDefinedLog

Description	Returns a new user defined log object for this container with the given name and description. an exception ifWill throw a log with the same name already exists for the container.
Prototype	UserDefinedLog Container::newUserDefinedLog(String name,

String description, Boolean isRunningLog

saveUserDefinedLog

Description Update the persisted user defined log object in the database.

Prototype void UserDefinedLog::saveUserDefinedLog()

startBatchProcessingForUserDefinedLog

Description Setup batch processing for the given User Defined Log. This operation is to be used mainly during import/mass update jobs.

Prototype void UserDefinedLog::startBatchProcessingForUserDefinedLog()

stopBatchProcessingForUserDefinedLog

Description Stop batch processing for the given User Defined Log. This operation is to be used mainly during import/mass update jobs.

Prototype void UserDefinedLog::stopBatchProcessingForUserDefinedLog()

userDefinedLogAddEntry

Description Add an entry to the user defined log. If a message is specified, set that for the UserDefinedLogEntry

Prototype void UserDefinedLog::userDefinedLogAddEntry(Entry entry, [String log_message])

userDefinedLogDelete

Description Remove the user defined log object from the database. This action will also drop all entries to the log.

Prototype void UserDefinedLog::userDefinedLogDelete()

userDefinedLogDeleteEntriesFor

Description Delete all log entries for an entry from the user-defined log.

Prototype void UserDefinedLog::userDefinedLogDeleteEntriesFor

or(IEntry entry)

userDefinedLogDeleteEntry

Description

Delete a particular entry from the user defined log.

Prototype

void
UserDefinedLog::userDefinedLogDeleteEntry(UserDefinedLogEntry entry)

userDefinedLogGetContainer

Description

Get the container that is logged by the user defined log.

Prototype

Container
UserDefinedLog::userDefinedLogGetContainer()

userDefinedLogGetDescription

Description

Get the description of the user defined log.

Prototype

String
UserDefinedLog::userDefinedLogGetDescription()
()

userDefinedLogIsRunningLog

Description

Returns whether this user defined log is a running-log.

Prototype

Boolean
UserDefinedLog::userDefinedLogIsRunningLog()

userDefinedLogSetName

Description

Set the name of the user defined log. NOTE: You need to call insertUserDefinedLog/saveUserDefinedLog to persist this change.

Prototype

void
UserDefinedLog::userDefinedLogSetName(String name)

UserDefinedLogEntry

newUserDefinedLogEntry

Description

Returns a new user defined log entry object with for the specified entry which is either an item or category (with date/timestamp and log

Prototype

`newUserDefinedLogEntry(Date date, Container container, Entry entry, String log)`

newUserDefinedLogEntry

Description

Returns a new user defined log entry object with for the specified entry which is either an item or category (with date/timestamp and log

Prototype

`newUserDefinedLogEntry(Date date, Container container, Entry entry, String log)`

userDefinedLogEntryGetTarget

Description

Get the entry object of the user defined log entry.

Prototype

`Entry
UserDefinedLogEntry::userDefinedLogEntryGetTarget()`

userDefinedLogEntrySetDate

Description

Set the date of the user defined log entry.

Prototype

`void
UserDefinedLogEntry::userDefinedLogEntrySetDate(Date date)`

userDefinedLogEntrySetValue

Description

Set the log of the user defined log entry.

Prototype

`void
UserDefinedLogEntry::userDefinedLogEntrySetValue(String log_message)`

InputOutput

Feed

createDataSource

Description

Creates a Data Source of the type ("PULL_FTP", "PULL_FTP", "PUSH_WWW", "DOC_STORE")

with given name. Will not create if a source with same name already exists. extraAttribs can be used to set other attributes of the datasource like "SERVER_ADDRESS", "SERVER_PORT", "USERNAME", "PASSWORD", "FILENAME", "DIRECTORY", "DOC_STORE_PATH"

Prototype

Creates a Data Source of the type (ONLY PUSH_WWW supported) with given name. Will not create if a source with same name already exists

createExport

Description

Creates the Export with given params. An optional parameter "charsetName", which may be set in the "optionalArgs" parameter, describes the file encoding of the export. Otherwise, the Cp1252 is chosen as the default file encoding. Returns Done if successful, Error if not. Here is a complete list of the optional arguments which may be set in the "optionalArgs" parameter: String approverUserName, String charsetName, String distributionName, String selectionName, String synType, String diffType, String sParamsDocPath

Prototype

String createExport(String marketSpecName, String catalogName, String specMapName, String exportScriptName, String syndicationName, [HashMap optionalArgs])

createImport

Description

Creates the Feed with given params. An optional argument sCharsetName, which may be defined in the optionalArgs HashMap, describes the file encoding of the feed. Otherwise, Cp1252 is chosen as the default file encoding. Also, optional parameters to describe if the current container is a collaboration area, and the step path of the workflow step in to which the feed is to be done, could be specified. Returns Done if successful, Error if not. The complete list of optional arguments, which may be set in the optionalArgs parameter, is as follows: String sCharsetName, Boolean bIsCollaborationArea, String sWflStepPath, String sParamsDocPath, String sImportSemantic, and String

sApproverUserName.

Prototype

String createImport(String sImportName, String sImportType, String sSourceName, String sFileSpecName, String sCatalogName, String sSpecMapName, String sCategoryTreeName, String sScriptName, String sACGName, [HashMap optionalArgs])

getExportItemsCount

Description

Returns the number of items being syndicated

Prototype

Integer getExportItemsCount()

Note: This operation replaced

getSyndicationItemsCount (deprecated in v3.3.1)

getExportItemSets

Description

Returns an array of ItemSets being syndicated

Prototype

ItemSet[] getExportItemSets()

getFtp

Description

Use to get a file via FTP. The seventh parameter set where WPC will store the retrieved file. The eighth and the ninth paramters together are optional. The eighth parameter gets the FTP Operation Status and the ninth paramter ensures that the FTP operations are logged. Returns the result as true/false if the eighth and the ninth are not specified otherwise a HashMap is returned. If a true/false is returned, it indicates if the ftp was a success/failure. If the size of the retrieved file is not the same as the size of the remote file the status is set to false. If a HashMap is returned, the first paramater is the true/false which indicates success/failure, the second paramater is the message string of the FTP Operation Status and the third parameter is the FTP Operation error code

Prototype

HashMap/Boolean getFtp(String hostname, String port, String userid, String password, String path, String filename, String sDocStorePath, Boolean deleteRemoteFile, [Boolean detailedTransferStatus, Boolean loggingEnabled])

startAggregationByName

Description	Run the feed called sName on the file sDocPath
Prototype	<code>void startAggregationByName(String sName, String sDocPath)</code>

Export environment

new\$EnvObjectList

Description	Returns a container for the WPC objects to be exported. This class is used to add and retrieve the objects to be exported
Prototype	<code>new EnvObjectList()</code>

setTypeToExport

Description	Sets the object type to be exported. List of acceptable values for sObjectType are: <ul style="list-style-type: none">• ACG• ATTRIBUTE_COLS• CATALOG• CATALOG_CONTENT• CATALOG_VIEW• COLLABORATION_AREA• COLLABORATION_AREA_CONTENT• COMPANY_ATTRIBUTES• CONTAINER_ACCESSPRV• DATASOURCE• DESTINATION_SPEC• DISTRIBUTION• DOC_STORE• EXPORTS• FEEDS• FILE_SPEC• HIERARCHY• HIERARCHY_CONTENT• HIERARCHY_MAPS• HIERARCHY_VIEW• INHERITANCE_RULES• ITEM_CATEGORY_MAPS• JOBS• LOOKUP_TABLE• LOOKUP_TABLE_CONTENT
-------------	---

- LOOKUP_TABLE_SPEC
- MAPS
- MY_SETTINGS
- PRIMARY_SPEC
- REPORTS
- ROLES
- SCRIPT_INPUT_SPEC
- SECONDARY_SPEC
- SPEC
- SUB_SPEC
- USERS
- WORKFLOW

Prototype

```
void EnvObjectList::setTypeToExport(String
sObjectType)
```

addObjectByNameToExport

Description

Sets the entity to be exported by specifying the entity name as an argument. sObjectType is optional. In case of Catalog and Hierarchy Content export, this operation is used to specify the attribute collection associated with the object. In case of DocStore partial export, this operation is used to specify the DocStore path. List of acceptable values for sObjectType are:

- ACG
- ATTRIBUTE_COLS
- CATALOG
- CATALOG_VIEW
- COLLABORATION_AREA
- COLLABORATION_AREA_CONTENT
- COMPANY_ATTRIBUTES
- CONTAINER_ACCESSPRV
- DATASOURCE
- DESTINATION_SPEC
- DISTRIBUTION
- DOC_STORE
- EXPORTS
- FEEDS
- FILE_SPEC
- HIERARCHY
- HIERARCHY_VIEW
- INHERITANCE_RULES
- JOBS
- LOOKUP_TABLE

- LOOKUP_TABLE_CONTENT
- LOOKUP_TABLE_SPEC
- MAPS
- MY_SETTINGS
- PRIMARY_SPEC
- REPORTS
- ROLES
- SCRIPT_INPUT_SPEC
- SECONDARY_SPEC
- SPEC
- SUB_SPEC
- USERS
- WORKFLOW

Prototype

void

EnvObjectList::addObjectByNameToExport(String sEntityName[, String sObjectType])

addAllObjectsToExport

Description

Notifies that all the entities of specific object type be exported. sObjectType is optional. List of acceptable values for sObjectType are:

- ACG
- ATTRIBUTE_COLS
- CATALOG
- CATALOG_CONTENT
- CATALOG_VIEW
- COLLABORATION_AREA
- COLLABORATION_AREA_CONTENT
- COMPANY_ATTRIBUTES
- CONTAINER_ACCESSPRV
- DATASOURCE
- DESTINATION_SPEC
- DISTRIBUTION
- DOC_STORE
- EXPORTS
- FEEDS
- FILE_SPEC
- HIERARCHY
- HIERARCHY_CONTENT
- HIERARCHY_MAPS
- HIERARCHY_VIEW
- INHERITANCE_RULES
- ITEM_CATEGORY_MAPS
- JOBS
- LOOKUP_TABLE
- LOOKUP_TABLE_CONTENT

- LOOKUP_TABLE_SPEC
- MAPS
- MY_SETTINGS
- PRIMARY_SPEC
- REPORTS
- ROLES
- SCRIPT_INPUT_SPEC
- SECONDARY_SPEC
- SPEC
- SUB_SPEC
- USERS
- WORKFLOW

Prototype

void
 EnvObjectList::addAllObjectsToExport([String
 sObjectType])

setCatalogByNameToExport

Description

Sets the Catalog whose contents are to be
 exported

Prototype

void
 EnvObjectList::setCatalogByNameToExport(Strin
 g sCatalog)

setItemCategoryMapToExport

Description

Sets the Catalog and Hierarchy whose Item-
 Category mappings need to be exported

Prototype

void
 EnvObjectList::setItemCategoryMapToExport(Str
 ing sCatalog, String sHierarchy)

setHierarchyMapToExport

Description

Sets the source and destination Hierarchies
 whose mappings need to be exported

Prototype

void
 EnvObjectList::setHierarchyMapToExport(String
 sourceHierarchy, String destHierarchy)

getCatalogNameToExport

Description

Returns the last value set with
 setCatalogByNameToExport

Prototype

String EnvObjectList::getCatalogNameToExport()

getHierarchyNameToExport

Description	Returns the last value set with setHierarchyByNameToExport
Prototype	String EnvObjectList::getHierarchyNameToExport()

getTypeToExport

Description	Returns the last object type set with setTypeToExport
Prototype	String EnvObjectList::getTypeToExport()

getTypesToExport

Description	Returns all the object types, set with setTypeToExport, for exporting
Prototype	String[] EnvObjectList::getTypesToExport()

exportEnv

Description	Exports the WPC objects specified in envObjList at the specified DocStore path. sDocFilePath is the filepath of the zip file that will be exported into the document store - returns the log as a string.
Prototype	String exportEnv(EnvObjectList envObjList, String sDocFilePath)

importEnv

Description	Imports the content of the archive in the docstore at sDocFilePath into this company. - returns the log as a string.
Prototype	String importEnv(String sDocFilePath)

Messaging

General

getDescription

Description	Returns the description of result
Prototype	int UtResult::getDescription()

getMessage

Description

Returns the message of result

Prototype

int UtMessage::getMessage()

getMessageName

Description

Returns the name of this message queue.

Prototype

String MsgQueue::getMessageName()

getStatus

Description

Returns the status of result

Prototype

Integer UtResult::getStatus()

getServiceByName

Description

Returns the web service with the given name. If there is no such web service, returns null.

Prototype

String MsgQueue::getServiceName()

newUCCnetTransporter

Description

Builds a new UCC-Net Transporter object; The properties file is defined by the system.

Prototype

new UCCnetTransporter()

receiveResponse

Description

Returns the result of sending the message, the value of reply gets set

Prototype

UtResult
UCCnetTransporter::receiveResponse(String id,
UtMessage reply)

setMessage

Description

Sets the message

Prototype

UtMessage::setMessage(String message)

submitRequest

Description

Returns the result of sending the message

Prototype

UtResult
UCCnetTransporter::submitRequest(String id,
String docPath)

Sample Script for Invoking SOAP Server

```
paramNames =
[];paramNames.add("sUser");paramNames.add("sCmpCode");paramNames.add("sScript");
paramValues =
[];paramValues.add("Admin");paramValues.add("WPC");paramValues.add("list=getCatalogName
sList());
out.writeln("\list: \" + list); i=5; out.writeln("\res: \" + i*2);");
res = invokeSoapServer("http://foxy:9100/soap/servlet/rpcrouter", "urn:Script",
"executeInlineScript", paramNames, paramValues);
out.println(res);
```

UCCnet Operations

getDescription

Description	Returns the description of result
Prototype	int UtResult::getDescription()

getMessage

Description	Returns the message of result
Prototype	int UtMessage::getMessage()

getStatus

Description	Returns the status of result
Prototype	Integer UtResult::getStatus()

new UCCnetTransporter

Description	Builds a new UCC-Net Transporter object; The properties file is defined by the system.
Prototype	new UCCnetTransporter()

receiveResponse

Description	Returns the result of sending the message, the value of reply gets set
Prototype	UtResult UCCnetTransporter::receiveResponse(String id, UtMessage reply)

setMessage

Description

Sets the message

Prototype

UtMessage::setMessage(String message)

MQ

mqDisconnect

Description

Disconnects from the given queue manager.

Prototype

void MQQueueManager::mqDisconnect()

mqGetMessageDiagnostics

Description

Returns a string containing diagnostic information about the given message.

Prototype

String mqGetMessageDiagnostics(MQMessage message)

mqGetMessageId

Description

Returns the ID of the given message as a String containing a hexadecimal number.

Prototype

String MQMessage::mqGetMessageId()

mqGetQueueMgr

Description

Creates and returns a new MQ queue manager with the given properties.

Prototype

MQQueueManager mqGetQueueMgr(String hostname, String port, String channel, String queueMgrName)

mqGetReceivedMsg

Description

Receives a message from queueName or picks the default inbound queue if queueName not specified. Returns the message, as a MQMessage, or null.

Prototype

MQMessage
MQQueueManager::mqGetReceivedMsg(String queueName, String queueOpenOptions, String messageGetOptions)

mqGetReceivedMsgByMessageID

Description

Finds the message in the given queue with given message ID. The ID is passed in a String containing a hexadecimal number. Returns null if there is no such message in the given queue.

Prototype

MQMessage
MQQueueManager::mqGetReceivedMsgByMessageID(String queueName, String messageId, String passedInQueueOpenOptions, String passedInMessageGetOptions)

mqGetResponseToMsg

Description

Gets the response to the given message from the given queue.

Prototype

MQMessage
MQQueueManager::mqGetResponseToMsg(MQMessage outgoingMessage, String queueOptions, String messageOptions)

mqGetTextFromMsg

Description

Returns a string containing the entire content of a MQMessage, including headers.

Prototype

String mqGetTextFromMsg(MQMessage mqMessage)

mqGetXMLMessageContent

Description

Discards any garbage at the beginning of the input string to get a XML document.

Prototype

String mqGetXMLMessageContent(String orgXmlMsg)

mqSendReply

Description

Sends a reply to the given message, without indicating success or failure.

Prototype

MQMessage
MQQueueManager::mqSendReply(MQMessage receivedMsg, String msgText, String passedInQueueOpenOptions, String passedInMessagePutOptions)

mqSendReplyWithStatus

Description

Sends a reply to the given message, setting the feedback field to indicate the given status. Status must be one of the following (in upper or lower case): SUCCESS, FAIL, VALCHANGE, VALDUPES, MULTIPLE_HITS, FAIL_RETRIEVE_BY_CONTENT, BO_DOES_NOT_EXIST, UNABLE_TO_LOGIN, APP_RESPONSE_TIMEOUT, NONE.

Prototype

MQMessage
MQQueueManager::mqSendReplyWithStatus(MQMessage receivedMsg, String msgText, String status, String passedInQueueOpenOptions, String passedInMessagePutOptions)

mqSendTextMsg

Description

Sends a message provided in the String msgText over queueName. Returns the MQMessage

Prototype

MQMessage
MQQueueManager::mqSendTextMsg(String msgText, String queueName, String queueOpenOptions, String messagePutOptions)

mqSendTextMsgWithReply

Description

Sends a message provided in the String msgText over queueName. The reply queue is specified. Returns the MQMessage object.

Prototype

MQQueueManager::mqSendTextMsgWithReply(String msgText, String queueName, String replyQueueName, String queueOpenOptions, String messagePutOptions)

JMS Operations

jmsDisconnect

Description

Disconnects from the given queue manager.

Prototype

void
QueueSession::jmsDisconnect(QueueConnection qcon)

jmsCreateTextMsg

Description

Creates a new JMS TextMessage using QueueSession information with the text provided.

Prototype

JMSMessage
QueueSession::jmsCreateTextMsg(String msgText)

jmsGetContext

Description

Creates a JMS context.

Prototype

Context jmsGetContext(String url, String jndiFactory)

jmsGetConnectionFactory

Description

Creates and returns a jms connection factory with the specified context.

Prototype

QueueConnectionFactory
Context::jmsGetConnectionFactory(String jmsFactory)

jmsGetMQConnectionFactory

Description

Creates and returns a JMS connection factory for communicating with MQ queues. Note that you do not need a Context to get an MQ connection factory whereas you need a Context for connecting to other JMS queues.

Prototype

QueueConnectionFactory
jmsGetMQConnectionFactory(String mqQueueManager, String mqHostname, String mqChannel, Integer mqPort)

jmsGetQueueByName

Description

Returns a javax.jms.Queue object from the given JNDI Name and Context.

Prototype

javax.jms.Queue jmsGetQueueByName(Context ctx, String name)

jmsGetQueueConnection

Description

Returns a JMS queue connection from the given connection factory.

Prototype QueueConnection
QueueConnectionFactory::jmsGetQueueConnection()

jmsGetQueueSession

Description Returns a JMS queue connection from the given connection factory

Prototype QueueSession
QueueConnection::jmsGetQueueSession()

jmsDisconnect

Description Disconnects from the given queue manager

Prototype void
QueueSession::jmsDisconnect(QueueConnection qcon)

jmsCreateTextMsg

Description Creates a new JMS TextMessage using QueueSession information with the text provided.

Prototype Message
QueueSession::jmsCreateTextMsg(String msgText)

jmsSendMsg

Description Sends a message MSG over queue with name queueName and returns MSG or null. If a MESSAGESTOREPLYTO is provided, the reply to queue and message id are read from it. PROPERTIES is a map from string keys to string values. There are three special keys "TRIGO_REPLY_TO_QUEUE", "TRIGO_COPY_CORRELATION_ID_BYTES", and "TRIGO_COPY_CORRELATION_ID". If TRIGO_REPLY_TO_QUEUE is provided, then it overrides the QUEUENAME or replyto queue in MESSAGESTOREPLYTO provided. replyto queue in MESSAGESTOREPLYTO overrides QUEUENAME. "TRIGO_COPY_CORRELATION_ID" and "TRIGO_COPY_CORRELATION_ID_BYTES" copy over correlation id from MESSAGESTOREPLYTO to MSG. Both can be

provided. Their values need to be boolean (as opposed to strings - as described above)

Prototype

Message QueueSession::jmsSendMsg(Message msg, String queueName[, HashMap properties, Message messageToReplyTo])

jmsSendMsgToQueue

Description

Sends message MSG and returns MSG or null. The message is sent to the queue specified by OUTBOUNDQUEUE, unless OUTBOUNDQUEUE is null. If OUTBOUNDQUEUE is null, MSG is sent to the reply-to queue of MESSAGETOREPLYTO, if MESSAGETOREPLYTO is provided. If OUTBOUNDQUEUE is null and MESSAGETOREPLYTO is not provided, throws an AustinException. If MESSAGETOREPLYTO is provided, the message id is read from it. PROPERTIES is a map from string keys to string values. There is one special (non-JMS) key: TRIGO_INCOMING_REPLY_QUEUE. TRIGO_INCOMING_REPLY_QUEUE indicates a javax.jms.Queue object to which an external application should send replies to this message.

Prototype

JMSMessage
QueueSession::jmsSendMsgToQueue(JMSMessage msg, javax.jms.Queue outboundQueue [, HashMap properties, JMSMessage messageToReplyTo,])

jmsReceiveMsg

Description

Receives next available message from queue QUEUENAME and times out after TIMEOUT milliseconds

Prototype

Message QueueSession::jmsReceiveMsg(String queueName, Integer timeout[, String messageSelector, Message messageToReceiveReplyFor])

jmsReceiveMsgFromQueue

Description

Receives a JMS Message. Times out after TIMEOUT milliseconds. If INBOUNDQUEUE is not null, looks on that queue. If INBOUNDQUEUE is null, and

MESSAGETORECEIVEREPLYFOR is not null, looks on the queue defined in the Reply-To field of MESSAGETORECEIVEREPLYFOR. If INBOUNDQUEUE is null and MESSAGETORECEIVEREPLYFOR is null, throws an AustinException. We now know which queue will be used. If MESSAGESELECTOR and MESSAGETORECEIVEREPLYFOR are both null, selects the first message from that queue. Otherwise selects the first message from the queue (if any) fulfilling all of the conditions defined by MESSAGESELECTOR and MESSAGETORECEIVEREPLYFOR. If MESSAGETORECEIVEREPLYFOR is not null, rejects any message not having a correlation ID equal to MESSAGETORECEIVEREPLYFOR's message ID. If MESSAGESELECTOR is not null, rejects any message not fulfilling the condition defined in messageSelector. If no appropriate message is found, returns null.

Prototype

JMSMessage
 QueueSession::jmsReceiveMsgFromQueue(javax.
 .jms.Queue queue, Integer timeout[, String
 messageSelector, JMSMessage
 messageToReceiveReplyFor])

jmsGetTextFromMsg

Description

Returns a string containing the entire content of a JMS message, including headers.

Prototype

String JMSMessage::jmsGetTextFromMsg()

jmsGetMessageID

Description

Returns a string containing the JMS message id.

Prototype

String JMSMessage::jmsGetMessageID()

jmsGetMessageCorrelationID

Description

Returns a string containing Correlation Id for the JMS message.

Prototype

String
 JMSMessage::jmsGetMessageCorrelationID()

jmsGetMessageProperties

Description	Returns a hashmap from string property names to string values for those priorities.
Prototype	HashMap JMSMessage::jmsGetMessageProperties()

jmsSetMessageText

Description	Sets the provided text for the JMS TextMessage. Only JMS TextMessage type is supported
Prototype	void Message::setJMSMessageText(String msgText)

Page Layout

getPageLayoutByName

Description	Returns the page layout object with the corresponding name
Prototype	IPageLayout getPageLayoutByName(String sPageLayoutName)

new\$PageLayout

Description	Returns a new page layout with the given name
Prototype	new PageLayout(String sPageLayoutName)

savePageLayout

Description	Saves the current page layout
Prototype	void IPageLayout::savePageLayout()

Reader

forEachLine

Description	Executes the statements for each line read from in
Prototype	forEachLine(BufferedReader in, String line) { statements }

getCurrentLine

Description	Returns the current line
-------------	--------------------------

Prototype

String getCurrentLine()

getFullHTTPResponse

Description

Returns a HashMap (with RESPONSE_READER and RESPONSE_HEADER_FIELDS) for the response for posting hmParameters or a doc of sContentType against the server at url, Use hmRequestProperties to send specific header information. An optional parameter bGetReader could be used to specify if the function needs to also return the response reader (default is true). An optional parameter bPostUserInfo could be used to specify if the function would need to post the invoking user information (default is false). The response is optionally stored into a document at sDocStorePath in the docstore.

Prototype

HashMap getFullHTTPResponse(String url, HashMap hmRequestProperties, HashMap hmParameters, String sRequestMethod, [[String sEncoding], [Doc doc, String sContentType], [boolean bGetResponseReader, boolean bPostUserInfo], [String sDocStorePath]])

getHTTPResponse

Description

Returns a reader for the response for posting hmParameters against the server at url, Use hmRequestProperties to send specific header information

Prototype

BufferedReader getHTTPResponse(String url, HashMap hmRequestProperties, HashMap hmParameters, String sRequestMethod [,String sEncoding])

new\$CSVParser

Description

Returns a comma separated parser given the buffered reader

Prototype

new CSVParser(BufferedReader reader)

new\$DelimParser

Description

Returns a delimiter parser which parses based on the given delimiter

Prototype

new DelimParser(BufferedReader reader, String delimiter)

delimiter)

new FixedWidthParser

Description

Returns a fixed width parser given the buffered reader input. fieldPos are optional parameters which indicate the positions of the fields.

Prototype

FixedWidthParser
newFixedWidthParser(BufferedReader input,
[Integer fieldPos1, Integer fieldPos2, ..., Integer
fieldPosN])

new Reader

Description

Returns the buffered reader for the document specified by the path. You may optionally specify a charset that differs from the one stored with the document in the doc store.

Prototype

new Reader(String documentPath [, String
charsetName])

newCSVParser

Description

Returns a Comma Separated Parser given the buffered reader input

Prototype

CSVParser newCSVParser(BufferedReader input)

newDelimParser

Description

Returns a parser which parse based on the delimiter provided

Prototype

DelimiterParser newDelimParser(BufferedReader
input, String delim)

newFixedWidthParser

Description

Returns a fixed width parser given the buffered reader input

Prototype

FixedWidthParser
newFixedWidthParser(BufferedReader input)

nextLine

Description

Returns the next line from the reader

Prototype

String nextLine (BufferedReader in)

TarArchive

addCtgFile

Description	Use to add a supplier ctg file (including images) to a tar archive
Prototype	Boolean TarArchive::addCtgFile(String sFileName [, Boolean bUpperCaseName])

closeTarArchive

Description	Use to close a tar archive and upload to the docstore for future distributions. By default, the archive is deleted after the distribution, unless 'deleteAfterDistribution' is false.
Prototype	void TarArchive::closeTarArchive([Boolean deleteAfterDistribution])

new\$TarArchive

Description	Returns a new tar archive with the given file name
Prototype	new TarArchive(String sFileName)

Writer

close

Description	Close this writer
Prototype	void Writer::close()

createOtherOut

Description	Returns a new scriptfile output with the given name and an optional charset value.
Prototype	Writer createOtherOut(String name, [String charset])

print

Description	Writes o as a string and appends a new line to it into this writer
Prototype	void Writer::print(Object o)

println

Description Writes o as a string and appends a new line to it into this writer

Prototype void Writer::println(Object o)

printXML

Description Writes an XML tag with the text value sValue, the tag name sTagName and the attributes sAttributes

Prototype void Writer::printXML(String sTagName, String sValue, String sAttributes)

save

Description Creates an Doc object with the content in the Writer and saves it in the specified documentPath

Prototype Doc Writer::save(String documentPath)

setOutputAttribute

Description Set an attribute of this writer - which becomes an attribute of the document this writer is flushed into, if any

Prototype void Writer::setOutputAttribute(String sAttributeName, String sAttributeValue)

setOutputName

Description Set the name of this writer - which becomes the name of the document this writer is flushed into, if any

Prototype void Writer::setOutputName(String sName)

write

Description Writes o as a string into this writer

Prototype void Writer::write(Object o)

writeBinaryFile

Description Pipes the dstore file represented sOrigFilePath into a new Doc of name sDestFileName in the directory of the current transaction instance

Prototype `void writeBinaryFile(String sDestFileName, String sOrigFilePath)`

writeDoc

Description Appends doc as a string into this writer

Prototype `void Writer::writeDoc(IDoc doc)`

writeFile

Description Pipes the dostore file represented sFilePath into this writer

Prototype `void Writer::writeFile(String sFilePath)`

writeFileUsingOut

Description Pipes w into this writer

Prototype `void Writer::writeFileUsingOut(Writer w)`

writeln

Description Writes o as a string and appends a new line to it into this writer

Prototype `void Writer::writeln(Object o)`

XMLNode

forEachXMLNode

Description Executes the statements for each XML node having the relative path xPath - paths in the block are relative to xPath. If the node variable is passed in as an argument, it is populated with the XMLNode that is being operated on in each iteration of forEachXMLNode

Prototype `forEachXMLNode(String xPath [, XMLNode node]) { statements }`

getXMLNodeName

Description Returns the name of the current XMLNode.

Prototype `String XMLNode::getXMLNodeName()`

getXMLNodePath

Description Returns the path of the current XMLNode. This path is not an XPath - it is the concatenation of all the names of the parent XMLNode's path, /, and the name of this XMLNode

Prototype String XMLNode::getXMLNodePath()

getXMLNodeValue

Description Returns the value of the current XMLNode.

Prototype String XMLNode::getXMLNodeValue(Boolean bRequired)

parseXMLNode

Description Returns the value given by the sXMLSubPath XPath in the current XML document

Prototype String parseXMLNode (String sXMLSubPath)

Security

Company

getCompanyCode

Description Returns the company code of this company.

Prototype String getCompanyCode()

getCompanyName

Description Returns the name of this company.

Prototype String getCompanyName()

Role

createRole

Description Creates a role object with the specified role name and an optional role descriptio.

Prototype Role createRole(String sRoleName, [String sRoleDesc])

getAccessControlGroupPrivsForRole

Description The return parameter is an array of privileges (which are defined in the format: Catalog__list, Selection__list, SelectionMembers__view_items etc.).

Prototype String[]
Role::getAccessControlGroupPrivsForRole(String acgName)

getAccessControlGroupsForRole

Description Gets the access control groups for the given role

Prototype String[] Role::getAccessControlGroupsForRole()

getLocalesForRole

Description Gets the locales that this role has access to for all containers

Prototype String Role::getLocalesForRole()

getRoleByName

Description Returns a role object for the specified role

Prototype Role getRoleByName(String sRoleName)

getRoleDescription

Description Return the description of the role

Prototype String Role::getRoleDescription()

getRoleName

Description Return the name of the role

Prototype String Role::getRoleName()

getRoles

Description Returns all roles for the current company

Prototype Role[] getRoles()

getRolesForCompany

Description Returns all roles of the given company

Prototype Role[] getRolesForCompany(String sCmpCode)

getUsersFromRole

Description

Returns all users within the Role

Prototype

User[] Role::getUsersFromRole()

setAccessControlGroupForRole

Description

Sets an access control group with the given set of privileges for the role. The parameter privs is an array of privileges (which are picked from the strings in the format: Catalog__list, Selection__list, SelectionMembers__view_items etc.). Please note the the page privileges like PAGE_OBJ_CTG_CONSOLE__view, PAGE_OBJ_CAT_CREATE__view are stored only in the Default ACG.

Prototype

Boolean

Role::setAccessControlGroupForRole(String acgName, String[] privs)

setAllAccessControlGroupForRole

Description

Sets access control group acgName with all privileges except for the ones in privExclusions.

Prototype

void

Role::setAllAccessControlGroupForRole(String acgName, [String[] privExclusions])

setLocalesForRole

Description

Sets the locales that this role has access to for all containers

Prototype

void Role::setLocalesForRole(String localesCSVString)

User

cloneUser

Description

Clones an existing user info into a new user. Password field is required. The optional roles and organization fields, when specified, override the roles and/or organization of the existing user.

Prototype

User ::cloneUser(String original_username, String password, String first_name, String

String username, String firstname, String lastname, String email, Boolean enabled, String password, Category organization, [HashMap roles])

getCurrentUserName

Description

Returns the name of the current user

Prototype

String getCurrentUserName()

getUserAddress

Description

Return the User's Address

Prototype

String User::getUserAddress()

getUserByUsername

Description

Returns the User object for the given User Name

Prototype

User getUserByUsername(String sUserName, String sCmpCode)

getUserCompanyCode

Description

Return the User's Company Code

Prototype

String User::getUserCompanyCode()

getUserCompanyName

Description

Return the User's Company Name

Prototype

String User::getUserCompanyName()

getUserEmail

Description

Return the User's Email Address

Prototype

String User::getUserEmail()

getUserFax

Description

Return the User's Fax Number

Prototype

String User::getUserFax()

getUserFirstName

Description

Return the User's First Name

Prototype

String User::getUserFirstName()

getUserLastName

Description

Return the User's Last Name

Prototype

String User::getUserLastName()

getUserLocale

Description

Returns the locale that is selected by the user for browsing content

Prototype

Locale getUserLocaleForContent()

getUserName

Description

Return the User Name

Prototype

String User::getName()

getUserOrganizations

Description

Return the User's Organizations

Prototype

Category[] User::getUserOrganizations()

getUserPhone

Description

Return the User's Phone Number

Prototype

String User::getUserPhone()

getUserRoles

Description

Return the User's Roles

Prototype

String[] User::getUserRoles()

getUserTitle

Description

Return the User's Title

Prototype

String User::getUserTitle()

saveUser

Description

Save the User's Profile. Returns null if the save was successful, otherwise returns an array of ValidationErrors.

Prototype

ValidationError[] User::saveUser()

setUserAddress

Description

Set the User's Address

Prototype	void User::setUserAddress(String str)
setUserEmail	
Description	Set the User's Email Address
Prototype	void User::setUserEmail(String str)
setUserFax	
Description	Set the User's Fax Number
Prototype	void User::setUserFax(String str)
setUserFirstName	
Description	Set the User's First Name
Prototype	void User::setUserFirstName(String str)
setUserLastName	
Description	Set the User's Last Name
Prototype	void User::setUserLastName(String str)
setUserPhone	
Description	Set the User's Phone Number
Prototype	void User::setUserPhone(String str)
setUserRoles	
Description	Sets the roles for an user
Prototype	Boolean User::setUserRoles(Role[] roles)
setUserTitle	
Description	Set the User's Title
Prototype	void User::setUserTitle(String str)
validateUser	
Description	Validates user based on Username, User Password, and User Company Code
Prototype	boolean validateUser(String sUserName, String sPassword, String sCmpCode)

AccessPrivilege

createAccessControlGroup

Description Creates an access control group object with the specified ACG name and an optional ACG description

Prototype ACG createAccessControlGroup(String sACGName, [String sACGDesc])

getAccessControlGroupName

Description Return the name of the access control group

Prototype String ACG::getAccessControlGroupName()

getAccessControlGroupByName

Description Returns a access control group object for the specified acg name

Prototype ACG getAccessControlGroupByName(String sACGName)

getCtgAccessPrvByRole

Description Returns the catalog access privilege for the catalog and role. Returns catalog access privilege with full access if none was found.

Prototype CtgAccessPrv
Container::getCtgAccessPrvByRole(String sRoleName)

getCtgAccessPrvPermission

Description Returns the permission [E-editable|V-viewable] for the node specified by the path in the current catalog access prv.

Prototype String
CtgAccessPrv::getCtgAccessPrvPermission(String attributeCollectionName)

new CtgAccessPrv

Description Builds a new catalog access privilege object

Prototype new CtgAccessPrv(Container container, String roleName)

saveCtgAccessPrv

Description Saves the current catalog access prv to the database

Prototype Boolean CtgAccessPrv::saveCtgAccessPrv()

setAccessPrv

Description Returns an access privilege object with the new permissions set for the attrGroupName. Permission is [V|E|null], and in case the permission is NULL the path is removed from the access Privilege. Returns TRUE if successful, FALSE if not

Prototype Boolean CtgAccessPrv::setAccessPrv(String attrGroupName, String permission)

setCtgAccessPrv

Description Returns a catalog access privilege object with the permissions set according to the attribute collections. Permissions are [V|E]

Prototype CtgAccessPrv
CtgAccessPrv::setCtgAccessPrv(String[] attrGroups, String[] permissions)

Sample Script for Creating Access Privilege

```
// sample 1: create catalog access prv
ctg = getCtgByName("Ctg1");
newCtgView = new CtgAccessPrv(ctg, "All Roles");

mypath = [];
mypath.add("Ctg1/Key");
mypath.add("Ctg1/Group/EAN/en_MY");
mypath.add("Ctg1/Group/EAN/zh_MY");
mypath.add("Ctg1/Group/EAN/ms_MY");
myper = [];
myper.add("E");
myper.add("V");
myper.add("E");
myper.add("V");

newCtgView = newCtgView.setCtgAccessPrv(mypath, myper);
newCtgView.saveCtgAccessPrv();
```

(to modify existing cap, just fetch a cap and set a new set of path/permissions. Setting empty path/permissions will delete the catalog access privilege)

Spec

Inheritance

addAttributeGroup

Description Add the Attribute Groups to this inheritance rule.

Prototype `void InheritanceRule::addAttributeGroup(String attributeName)`

deleteInheritanceRule

Description Delete the inheritance rule.

Prototype `void InheritanceRule::deleteInheritanceRule()`

getInheritanceRuleByName

Description Returns the inheritance rule for the attribute.

Prototype `InheritanceRule
getInheritanceRuleByName(String sRuleName)`

getInheritanceTargets

Description Gets the inheritance target list. Targets are defined by an array of name and type. For example [my catalog name, CATALOG]

Prototype `String[][]
InheritanceRule::getInheritanceTargets()`

getMappedAttributeGroups

Description Returns an array of Strings representing the names of Attribute Collections mapped to this inheritance rule.

Prototype `String[]
InheritanceRule::getMappedAttributeGroups()`

new\$InheritanceRule

Description Builds a new InheritanceRule object for the specified catalog and attribute

Prototype `new InheritanceRule(Container container, String ruleName)`

reflattenAllInheritanceRules

Description Reflatten all the inheritance rules. WARNING operation might take time

Prototype	void reflattenAllInheritanceRules()
removeAttributeGroup	
Description	Removes the Attribute Groups from this inheritance rule. Returns true if attribute group is removed, false if not.
Prototype	Boolean InheritanceRule::removeAttributeGroup(String attributeName)
saveRule	
Description	Saves the inheritance rule (adding it if it is new). The rule must have at least one attribute collection associated with it. If the rule is a catalog rule then it must have at least one target; if it's a hierarchy rule, then the rule shouldn't have any targets.
Prototype	void InheritanceRule::saveRule()
setInheritanceTargets	
Description	Sets the inheritance target list to the new list of containers. Container is defined by an array of name and type. For example ["my catalog name", "CATALOG"]
Prototype	void InheritanceRule::setInheritanceTargets(String[][] containers)

IMutable Spec

exportXML

Description	Exports a WPC Spec to a String representing a XML file.
Prototype	String IMutableSpec::exportXML()

exportXSD

Description	Exports a WPC Spec to a String representing the contents of XML Schema Definition.
Prototype	String IMutableSpec::exportXSD()

importXML

Description

Imports a XML file to a WPC Spec.

Prototype

ImmutableSpec importXML(String filename)

importXSD

Description

Imports a XML Schema Definition file (.xsd) to a WPC Spec, using the given parameters.

Prototype

```
ImmutableSpec importXSD(String filename,
String specName,
String specType,
String primaryKeyPath,
String maxAncestors,
String topLevelNamespace,
String topLevelName,
String archivedFilename)
```

Locale

addToCompanyLocales

Description

Adds the given locales to the list of locales that are defined for the company.

Prototype

```
void addToCompanyLocales(Locale []companyLocales)
```

getLocaleCode

Description

Returns the 5 letter code (2 letter country code + underscore + 2 letter language code) for the given locale.

Prototype

```
String Locale::getLocaleCode()
```

getLocaleDisplayName

Description

Returns a description of the locale suitable for display.

Prototype

```
String Locale::getLocaleDisplayName()
```

getLocalizedSpecNames

Description

Returns all the specs that are localized.

Prototype

Spec[] getLocalizedSpecNames()

getLocales

Description

return locales associated with the spec

Prototype

Object Spec::getLocales()

getNodeByPath

Description

Returns the node object for path in this spec.

Prototype

Node Spec::getNodeByPath(String path)

getNodeLocale

Description

Returns the locale object for this node if it is a locale specific node.

Prototype

Boolean Node::getNodeLocale()

new\$Locale

Description

Returns a locale with the country and language (two letter codes) combination specified and null if it is not supported

Prototype

new\$Locale(String country_code, String language_code)

removeFromCompanyLocales

Description

Removed the given locales from the list of locales that are defined for the company.

Prototype

void removeFromCompanyLocales(Locale []companyLocales)

replaceCompanyLocales

Description

Sets the given locales for the company. Removes any existing locales.

Prototype

void replaceCompanyLocales(Locale []companyLocales)

SpecNode

buildSpecNode

Description	Returns a new node object of a spec with the given path and node order. Please make sure to use a spec that has been obtained using the new Spec() or buildSpec operation
Prototype	Node buildSpecNode(Spec spec, String path, Integer order)

buildSpecNodeName

Description	Returns the parsed name that was passed in so that it can be used as a spec node name (spec node name only accept letters and characters, others are converted to an underscore _)
Prototype	String buildSpecNodeName(String name)

getNodeAttributeValue

Description	Returns the value of this node's attribute, i.e. MAXLENGTH, MAX_OCCURRENCE, MIN_OCCURRENCE, HELP_URL, TYPE, etc.
Prototype	String Node::getNodeAttributeValue(String attributeName)

getNodeAttributeValues

Description	Returns the values of this node's attribute, i.e. STRING_ENUMERATION.
Prototype	HashMap Node::getNodeAttributeValues(String attributeName)

getNodeChildren

Description	Returns the children for the node.
Prototype	INode[] Node::getNodeChildren()

getNodeLookupTableName

Description	Returns the name of the Lookup Table associated with this node, if one exists.
Prototype	String Node::getNodeLookupTableName()

getNodeName

Description	Returns the name of this node.
-------------	--------------------------------

Prototype	String Node::getNodeName()
getNodePath	
Description	Returns the path of this node.
Prototype	String Node::getNodePath()
getNodeSpec	
Description	Returns the spec object for this node.
Prototype	Spec Node::getNodeSpec()
getSpecNodes	
Description	Returns map of node paths to node objects for this spec.
Prototype	HashMap Spec::getSpecNodes()
isNodeEditable	
Description	Returns true if the node is editable, false otherwise
Prototype	Boolean Node::isNodeEditable()
isNodeGrouping	
Description	Returns true if the node is a grouping node, false otherwise
Prototype	Boolean Node::isNodeGrouping()
isNodeNonPersisted	
Description	Returns true if the node is a non-persisted node, false otherwise
Prototype	Boolean Node::isNodeNonPersisted()
isNodeSpecRoot	
Description	Returns true if the node is a spec root node, false otherwise
Prototype	Boolean Node::isNodeSpecRoot()

Sequence

getSequenceByName

Description Gets the sequence object with the corresponding name where name is defined by the name of the catalog/category tree + "_" + "CTG" / "CATTREE" + "_" + the path of the node the sequence is defined for.

Prototype Sequence getSequenceByName(String name)

getSequenceCurrentValue

Description Returns the current value of this sequence

Prototype String Sequence::getSequenceCurrentValue()

getSequenceNextValue

Description Returns the next value of this sequence

Prototype String Sequence::getSequenceNextValue()

Spec

addToSpecLocales

Description Adds the given locales to the list of locales that are defined for the spec.

Prototype void Spec::addToSpecLocales(Locale []newLocales)

addSubNode

Description Adds a SubNode from a SubSpec.

Prototype Boolean Spec::addSubNode(Node node)

addSubSpec

Description Adds an entire SubSpec using a SubSpec.

Prototype Boolean Spec::addSubSpec(Spec subSpec)

buildSpec

Description Returns a spec object given the name and the type of the spec

Prototype Spec buildSpec(String specName, String specType)

buildTestSpec

Description Returns a new spec object with the specified name, type and number of fields in the spec

Prototype `Spec buildTestSpec(String name, String type, Integer fields)`

deleteSpec

Description Delete this spec

Prototype `void Spec::deleteSpec()`

getSpecAttribNames

Description returns the names of each attribute(node) specified in the spec

Prototype `String[] Spec::getSpecAttribNames()`

getSpecAttribPaths

Description returns the names of each attribute(node) specified in the spec

Prototype `String[] Spec::getSpecAttribPaths()`

getSpecByName

Description Returns the spec object with the corresponding name

Prototype `Spec getSpecByName(String name)`

getSpecName

Description Returns the name of this spec

Prototype `String Spec::getSpecName()`

getSpecMultiOccurAttributePaths

Description Returns the multi occurrence attribute paths for this spec

Prototype `HashMap Spec::getSpecMultiOccurAttributePaths()`

getSpecPrimaryKeyAttributePath

Description Returns the primary key attribute path for this spec, null if it doesn't apply

Prototype	String Spec::getSpecPrimaryKeyAttributePath()
getSpecSequenceAttributePaths	
Description	Returns the sequence attribute paths for this spec.
Prototype	HashMap Spec::getSpecSequenceAttributePaths()
getSpecType	
Description	Returns the type of this spec
Prototype	String Spec::getSpecType()
getSpecUniqueAttributePaths	
Description	Returns the unique attribute paths for this spec.
Prototype	HashMap Spec::getSpecUniqueAttributePaths()
isLocalized	
Description	Returns a boolean if a spec is localized
Prototype	Boolean Spec::isLocalized()
new\$Spec	
Description	Returns a new spec object with the given name and type
Prototype	new Spec(String specName, String specType)
new\$SpecNode	
Description	Returns a new node created in the spec according to the path and order
Prototype	new SpecNode(Spec spec, String path, Integer order)
removeFromSpecLocales	
Description	Removes the given locales from the list of locales that are defined for the spec.
Prototype	void Spec::removeFromSpecLocales(Locale []newLocales)
replaceSpecLocales	
Description	Sets the given locales for the spec. Removes any existing locales.

Prototype `void Spec::replaceSpecLocales(Locale []newLocales)`

saveSpec

Description Save this spec to the database

Prototype `void Spec::saveSpec()`

saveSpecMap

Description Save this spec map to the database

Prototype `void Spec::saveSpecMap()`

setAttribute

Description Set an attribute of a node or a spec. Please consult the documentation for allowable values of `sAttributeName`. Common values are `MAX_OCCURRENCE`, `MIN_OCCURRENCE`, `TYPE`, `DEFAULT_VALUE`. If the optional third parameter "dontReplace" is supplied, and is true, or we are dealing with a node rather than a spec, `sValue` is added to any existing values for this attribute rather than replacing them.

Prototype `void Node::setAttribute(String sAttributeName, String sValue), void Spec::setAttribute(String sAttributeName, String sValue)`

setLocalized

Description Sets the localized property of a spec

Prototype `void Spec::setLocalized(Boolean localized)`

setNodeEditable

Description Sets the node to be editable or non-editable

Prototype `void Node::setNodeEditable(Boolean)`

SpecMap

buildTestSpecMap

Description Returns a new spec map on the specified map type between the source and the destination specs - first delete existing map if there is one

Prototype `SpecMap buildTestSpecMap(String mapName, String mapType, Spec source, Spec destination)`

getDefaultSpecMapName

Description See `getSpecMapByName`. Returns the name of the spec map being used for an aggregation/syndication.

Prototype `(deprecated) String getDefaultSpecMapName()`

getSpecMapByName

Description Returns the specmap object with the corresponding name

Prototype `SpecMap getSpecMapByName([String name])`

getSpecMapDstObject

Description Returns the destination object of this spec map

Prototype `Object SpecMap::getSpecMapDstObject()`

getSpecMapSrcObject

Description Returns the source object of this specmap

Prototype `Object SpecMap::getSpecMapSrcObject()`

map

Description Add a mapping from `sSrcPath` to `sDstPath` to this spec map

Prototype `void SpecMap::map(String sSrcPath, String sDstPath)`

new\$SpecMap

Description Creates a new spec map of the given type between the source and destination objects

Prototype `new SpecMap(String mapType, Object source, Object destination)`

SystemAdmin

Logger

debug

Description Write s to this logger
Prototype String dumpContext([Logger l])

dumpContext

Description Return the script context in a string (and dumps it to the logger l if specified)
Prototype String dumpContext([Logger l])]

dumpSystemLog

Description Return the last nLines of the system log sName
Prototype String dumpSystemLog(String sName, int nbLines)

PerformanceTest

beginPerf

Description Starts timing current block for perf. logging
Prototype beginPerf(String name)

endPerf

Description Ends timing current block for perf. logging
Prototype endPerf(String name)

SystemDB

new\$SystemDB

Description Returns an object that represents the status of the current database
Prototype new SystemDB()

reportAllTableIndexes

Description Reports all the tables and their indexes
Prototype String SystemDB::reportAllTableIndexes()

reportExtraIndexes

Description	Reports the list of indexes that are extra in the current database that could not be there
Prototype	String SystemDB::reportExtraIndexes()

reportIndexStatistics

Description	Reports all the indexes and their current statistics and whether or not they need to be rebuilt
Prototype	String SystemDB::reportIndexStatistics()

reportMissingIndexes

Description	Reports the list of indexes that are missing in the current database that could be there
Prototype	String SystemDB::reportMissingIndexes()

Web Services

createWebService

Description	Creates a new web service with the given parameters. To save and deploy the service x(if DEPLOYED is true), call save(). NAME is the name of the service. DESC is the description of the service. WSDLDOCPATH is the doc path at which the WSDL is stored. PROTOCOL is the protocol. Currently SOAP_HTTP is the only supported protocol. IMPLSCRIPTPATH is the doc path of the service implementation script. It is the callers responsibility to ensure that WSDLDOCPATH and IMPLSCRIPTPATH do not cause the documents for any other web service to be overwritten. STOREINCOMING determines whether incoming requests are stored. STOREOUTGOING determines whether outgoing request are stored. DEPLOYED determines whether the service will be deployed. If a web service with the name of NAME already exists, throws an AustinException.
Prototype	WebService createWebService(String name, String desc, String wsdlDocPath, String protocol, String implScriptPath, Boolean storeIncoming, Boolean storeOutgoing, Boolean deployed)

deleteWebService

Description Deletes the web service in the DB and undeploys it.
Prototype `void WebService::deleteWebService()`

getName implementation

Description Returns the name of this web service
Prototype `String WebService::getName()`

getDesc

Description Returns the description of this web service
Prototype `String WebService::getDesc()`

getUrl

Description Returns the URL for this web service
Prototype `String WebService::getUrl()`

getWsdUrl

Description Returns the WSDL URL for this web service
Prototype `String WebService::getWsdUrl()`

getWsdDocPath

Description Returns the docstore path where the WSDL for this web service is stored.
Prototype `String WebService::getWsdDocPath()`

getProtocol

Description Returns the protocol for this web service.
Prototype `String WebService::getProtocol()`

getImplScriptPath

Description Returns the docstore path where the implementation script for this web service is stored.
Prototype `String WebService::getImplScriptPath()`

getStoreIncoming

Description Returns whether incoming messages for this web service are stored.

Prototype `Boolean WebService::getStoreIncoming()`

getStoreOutgoing

Description Returns whether incoming messages for this web service are stored.

Prototype `Boolean WebService::getStoreOutgoing()`

isDeployed

Description Returns whether this web service is deployed.

Prototype `Boolean WebService::isDeployed()`

setName

Description Sets the name of the given WebService.

Prototype `void WebService::setName(String name)`

setDesc

Description Sets the description of the given WebService.

Prototype `void WebService::setDesc(String desc)`

setStoreIncoming

Description Sets the storeIncoming of the given WebService.

Prototype `void WebService::setStoreIncoming(Boolean storeIncoming)`

setWsdldocPath

Description Sets the docstore path of the WSDL document. The caller must ensure that this does not overwrite the WSDL for any other service.

Prototype `void WebService::setWsdldocPath(String wsdlDocPath)`

setImplScriptPath

Description Sets the docstore path of the implementation script for this webservice. The caller must ensure that this does not overwrite the implementation script for any other service.

Prototype `void WebService::setImplScriptPath(String implScriptPath)`

setProtocol

Description Sets the protocol of the given WebService.
Prototype `void WebService::setProtocol(String protocol)`

setStoreOutgoing

Description Sets whether this WebService should store outgoing messages.
Prototype `void WebService::setStoreOutgoing(Boolean storeOutgoing)`

setDeployed

Description Sets whether this WebService is deployed. The setting will take effect upon saving.
Prototype `void WebService::setDeployed(Boolean deployed)`

saveWebService

Description Saves the web service in the DB. If deployment settings have changed, they take effect upon saving.
Prototype `void WebService::saveWebService()`

WorkEntryList

WorkEntry

getEntryFromWorkEntry

Description Get the Entry held by this WorkEntry
Prototype `Entry WorkEntry::getEntryFromWorkEntry()`

getWorkEntryState

Description Get the current state of this WorkEntry
Prototype `String WorkEntry::getWorkEntryState()`

isWorkEntryMarked

Description Is the current WorkEntry marked
Prototype `Boolean WorkEntry::isWorkEntryMarked()`

isWorkEntryMarkedNew

Description Is the current WorkEntry marked new
Prototype Boolean WorkEntry::isWorkEntryMarkedNew()

markWorkEntryDirty

Description Mark this WorkEntry as being dirty
Prototype void WorkEntry::markWorkEntryDirty()

new WorkEntry

Description Creates a workentry for a given entry
Prototype new WorkEntry(Entry entry, [Boolean markAsNew])

setWorkEntryMarked

Description Marks/unmarks this WorkEntry
Prototype void WorkEntry::setWorkEntryMarked(Boolean mark)

WorkEntryList

addWorkEntry

Description Insert a WorkEntry into the WorkEntryList at the specified index
Prototype void WorkEntryList::addWorkEntry(int index, WorkEntry workEntry)

getIndexesOfEntriesHavingState

Description Get the current indexes of the worklist entries having a particular state
Prototype Map WorkEntryList::getIndexesOfEntriesHavingState(String state)

getMarkedEntries

Description Return an entry set containing the marked entries in this work entry list - with indexes between start and end -
Prototype EntrySet WorkEntryList::getMarkedEntries([start, end])

end])

getWorkEntryAt

Description

Get the WorkEntry for the specified index in the WorkEntryList

Prototype

WorkEntry WorkEntryList::getWorkEntryAt(int i)

getWorkEntryListSize

Description

Gets the size of this work entry list

Prototype

Integer WorkEntryList::getWorkEntryListSize()

new\$WorkEntryList

Description

Create a new work entry list from a catalog or a selection

Prototype

new WorkEntryList(ctgOrSelection, [sortingNodeId], [sortingOrder])

removeWorkEntry

Description

Removes the WorkEntry at the specified index from the WorkEntryList

Prototype

void WorkEntryList::removeWorkEntry(int index)

saveMarkedEntries

Description

Save the set of marked entries for this work entry list - with indexes between start and end - for entries in the step specified by path in the collaboration area colArea with given comment.

Prototype

WorkEntryList::saveMarkedEntries(workList, [start, end, [colArea, path, comment]

syncWorkEntryAt

Description

Sync the work entry at the specified index with it's database picture

Prototype

void WorkEntryList::syncWorkEntryAt(int i)

Workflow

ColAreaEntryHistory

The following is a list of Collaboration Area Entry History/Reporting Operations.

getColAreaEntryHistory

Description	Return the entire history of the entry in the given collaboration area.
Prototype	ColAreaEntryHistory[] getColAreaEntryHistory(String colAreaName, String wflName, String primaryKey)

getColAreaHistoryByTimePeriod

Description	Return the entire history given collaboration area for the given time period.
Prototype	ColAreaEntryHistory[] getColAreaHistoryByTimePeriod(String colAreaName, Date beginDate, Date endDate)

getColAreaHistoryDate

Description	Returns the date for the given collaboration area history event.
Prototype	Date ColAreaEntryHistory::getColAreaHistoryDate()

getColAreaHistoryEntryKey

Description	Returns the entry key for the given collaboration area history event.
Prototype	String ColAreaEntryHistory::getColAreaHistoryEntryKey()

getColAreaHistoryEventAttribute

Description	Returns the attribute value for the given collaboration area history event type attribute name. attrName could be one of the following: COMMENT, EXIT_VALUE, ENTRY_DIFFERENCES
Prototype	String ColAreaEntryHistory::getColAreaHistoryEventAttribute(String attrName)

getColAreaHistoryEventType

Description	Returns the event type for the given collaboration area history event. Event types could be one of the following: CHECKOUT, CHECKIN, ENTERSTEP, LEAVESTEP, SAVEENTRY, DROP, TIMEOUT.
Prototype	String ColAreaEntryHistory::getColAreaHistoryEventType()

getColAreaHistoryStepPath

Description	Returns the step path for the given collaboration area history event.
Prototype	String ColAreaEntryHistory::getColAreaHistoryStepPath()

getColAreaHistoryUser

Description	Returns the username for the given collaboration area history event.
Prototype	String ColAreaEntryHistory::getColAreaHistoryUser()

getColAreaStepHistory

Description	Return the entire history of the step in the given collaboration area.
Prototype	ColAreaEntryHistory[] getColAreaStepHistory(String colAreaName, String wflName, String stepPath)

CollaborationArea

addEntryIntoColArea

Description	Posts a message to add the entry in the given stepPath of the collaboration area. Returns a boolean depending on whether the entry was successfully added or not. You cannot assume that the entry is in the collaboration area when this method returns.
Prototype	boolean CollaborationArea.addEntryIntoColArea(Entry)

CollaborationArea::addEntryIntoColArea(Entry entry, String stepPath)

checkOutEntries

Description

Checks-out the entries in the entrySet into the collaboration area. If stepPath is not specified the entries will be checked-out into the Initial step. The event id is returned. If waitForStatus is false, always return null. If waitForStatus is true, then this operation returns when the separate workflow engine has processed the event. Default is false. Returns a HashMap of entry primary key to the status of the checkout. This method blocks until. Checkout status could be one of the following: CHECKOUT_SUCCESSFUL and ATTRIBUTE_LOCKED. If any attribute is locked in some other collaboration area, then the status of ATTRIBUTE_LOCKED is returned for that entry primary key.

Prototype

HashMap
CollaborationArea::checkOutEntries(EntrySet entrySet, [String stepPath], [boolean waitForStatus])

dropEntries

Description

Posts an event to drops the entries in the entrySet from the collaboration area and to unlock the attributes which were locked in the source catalog for the entry. You cannot assume that this operation has completed when this method returns.

Prototype

void CollaborationArea::dropEntries(EntrySet entrySet)

getColAreaName

Description

Returns the name of the collaboration area.

Prototype

String CollaborationArea::getColAreaName()

getColAreaNames

Description

Returns all of the Collaboration Area Names for the current Company

Prototype

String[] getColAreaNames()

getColAreaContainer

Description

Returns the collaboration area as a container.

Prototype

Container
CollaborationArea::getColAreaContainer()

getColAreaSrcContainer

Description

Returns the source container which this collaboration area is tied to.

Prototype

Container
CollaborationArea::getColAreaSrcContainer()

getColAreaWorkflow

Description

Returns the workflow that this collaboration area is tied to.

Prototype

Workflow
CollaborationArea::getColAreaWorkflow()

getCountOfEntriesInColArea

Description

Returns the entries currently in ALL the steps of the collaboration area.

Prototype

int
CollaborationArea::getCountofEntriesInColArea(
)

getCountOfEntriesInColAreaStep

Description

Returns the entries currently in the given stepPath of the collaboration area.

Prototype

int
CollaborationArea::getCountofEntriesInColAreaS
tep(String stepPath)

getEntries

Description

Returns the entry set for the entries currently in the collaboration area.

Prototype

EntrySet CollaborationArea::getEntries()

getEntriesInStep

Description

Returns the entry set for the entries currently in the step of the collaboration area. The format of the stepPath is Stepname

Prototype	EntrySet CollaborationArea::getEntriesInStep(String stepPath)
getReservedEntriesInStep	
Description	Returns the entry set for the reserved entries currently in the step of the collaboration area. The format of the stepPath is Stepname
Prototype	EntrySet CollaborationArea::getReservedEntriesInStep(String stepPath)
getUsernameForReservedEntryInStep	
Description	Returns the username of the user who locked the entry in a wfl step for a given collaboration area, otherwise it returns null.
Prototype	String CollaborationArea::getUsernameForReservedEntryInStep(Entry entry, String stepPath)
isEntryReservedInStep	
Description	Returns true if the entry is locked in a wfl step for a given collaboration area, otherwise it returns false.
Prototype	Boolean CollaborationArea::isEntryReservedInStep(IEntry entry, String stepPath)
lockColArea	
Description	Locks the Collaboration Area so that no more entries can be checked out into it. Returns true or false depending on whether the lock was successfully applied or not.
Prototype	Boolean CollaborationArea::lockColArea()
moveEntriesToColArea	
Description	Moves the entrySet of entries in the collaboration area to another collaboration area. For now, use only within the IN() script of a workflow step. destColAreaName specifies the name of the destination collaboration area, into whose Initial step the entries will be checked into. Returns a

	boolean depending on whether the entrySet was successfully moved or not.
Prototype	boolean CollaborationArea::moveEntriesToColArea(Entry Set entrySet, String destColAreaName)
moveEntriesToNextStep	
Description	Moves the entries in the entrySet from the step to the next step depending on the exitValue. You cannot assume that this operation has completed when this method returns.
Prototype	void CollaborationArea::moveEntriesToNextStep(Entry Set entrySet, String stepPath, String exitValue)
new\$CollaborationArea	
Description	Create a new collaboration area with the given name, wfl and srcContainer
Prototype	new CollaborationArea(String colAreaName, Workflow wfl, Container srcContainer)
releaseEntryInStep	
Description	Returns true if the entry was unlocked in a wfl step for a given collaboration area, otherwise it returns false. Operation runs synchronously.
Prototype	Boolean CollaborationArea::releaseEntryInStep(Entry entry, String stepPath)
reserveEntryInStep	
Description	Returns true if the entry was reserved in a wfl step for a given collaboration area, otherwise it returns false. Operation runs synchronously.
Prototype	Boolean CollaborationArea::reserveEntryInStepForUser(I Entry entry, String stepPath, [String username])
saveColArea	
Description	Saves the collaboration area.
Prototype	void CollaborationArea::saveColArea()

setColAreaAdminRoles

Description

Sets the admin roles for the collaboration area.

Prototype

void

CollaborationArea::setColAreaAdminRoles(String[] roles)

setColAreaAdminRoles

Description

Sets the admin roles for the collaboration area.

Prototype

void

CollaborationArea::setColAreaAdminRoles(String[] roles)

setColAreaAdminUsers

Description

Sets the admin users for the collaboration area.

Prototype

void

CollaborationArea::setColAreaAdminUsers(String[] users)

setStepEntryTimeout

Description

Expects the entry to actually be in the given collaboration area's specified stepPath.

Provided the entry is found to actually be in the step, its timeout is set to be the moment in time specified by the date argument.

If any of the assumptions are not met (collaboration area has no such stepPath, entry are not in that stepPath, etc.), the operation simply does nothing, i.e. no Exception thrown.

The operation doesn't modify the collaboration area's underlying workflow at all. It should be thought of as operating on an entry in a collaboration area, that is expected to be in a particular stepPath at the moment in time when the op is executed.

Prototype

void

CollaborationArea::setStepEntryTimeout(Entry entry, String stepPath, Date date)

unlockColArea

Description

Unlocks the Collaboration Area so that entries can be checked out into it again. Returns true or

false depending on whether the unlock was successful or not.

Prototype

Boolean CollaborationArea::unlockColArea()

Workflow

createNestedWflStep

Description

Adds a nested workflow step to the workflow. Returns the WorkflowStep object.

Prototype

WorkflowStep Workflow::createNestedWflStep (Workflow nestedWfl)

createWflStep

Description

Adds a new step to the workflow if the step with the given name does not exist. StepType can be one of the following: AND_APPROVAL, OR_APPROVAL, MODIFY, DISPATCH, MERGE, GENERAL, AUTOMATED, PARTIAL_UNDO, CONDENSER. Returns the WorkflowStep object.

Prototype

WorkflowStep Workflow::createNestedWflStep (Workflow nestedWfl)

deleteWfl

Description

Delete a workflow. It throws an exception if the workflow can not be deleted (if used by any collaboration area)

Prototype

void Workflow::deleteWfl()

getAllWflNames

Description

Returns a list of all workflow names.

Prototype

String[] getAllWflNames()

getWflAccessControlGroup

Description

Returns access control group name of the workflow.

Prototype

String Workflow::getWflAccessControlGroup()

getWflByName

Description

Returns the workflow if found otherwise null.

Prototype

Workflow getWflByName(String wflName)

getWflFailureStep

Description

Returns the failure step of the workflow.

Prototype

WorkflowStep Workflow::getWflFailureStep()

getWflInitialStep

Description

Returns the initial step of the workflow.

Prototype

WorkflowStep Workflow::getWflInitialStep()

getWflName

Description

Returns the workflow name.

Prototype

String Workflow::getWflName()

getWflStepByName

Description

Returns the step of the workflow otherwise null.

Prototype

WorkflowStep
Workflow::getWflStepByName(String stepName)

getWflStepPaths

Description

Returns the paths for all the steps of the workflow.

Prototype

String[] Workflow::getWflStepPaths()

getWflSteps

Description

Returns the list of all the steps in the workflow.

Prototype

WorkflowStep[] Workflow::getWflSteps()

getWflSuccessStep

Description

Returns the success step of the workflow.

Prototype

WorkflowStep Workflow::getWflSuccessStep()

new\$Workflow

Description

Create a new workflow of the given container type and with the given name. Container type can be one of the following: CATALOG,

CATEGORY_TREE

Prototype

`new Workflow(String wflName, String containerType)`

saveWfl

Description

Saves the workflow. Returns true or false depending on whether the workflow was successfully saved or not.

Prototype

`Boolean Workflow::saveWfl()`

setWflAccessControlGroup

Description

Sets access control group name of the workflow.

Prototype

`void Workflow::setWflAccessControlGroup(String acg)`

setWflDesc

Description

Sets the workflow description

Prototype

`Workflow::setWflDesc(String wflDesc)`

setWflName

Description

Sets the workflow name

Prototype

`Workflow::setWflName(String wflName)`

Workflow Step

getNextWflStepsForExitValue

Description

Returns the names of the next steps for a particular exitValue of a WorkflowStep.

Prototype

`String[] WorkflowStep::getNextWflStepsForExitValue(String exitValue)`

getWflStepAddEntries

Description

Returns value of 'allow import into step' flag.

Prototype

`Boolean WorkflowStep::getWflStepAddEntries()`

getWflStepCategorizeEntries

Description

Returns value of 'allow recategorization' flag.

Prototype

Boolean

WorkflowStep::getWflStepCategorizeEntries()

getWflStepDefaultScriptPath

Description

Gets the default path of the workflow script for the step: scripts/workflow/<workflow name>/<step name>.

Prototype

String

WorkflowStep::getWflStepDefaultScriptPath()

getWflStepEntryNotification

Description

Gets the notification emails that will get sent when the item gets into the step.

Prototype

String

WorkflowStep::getWflStepEntryNotification()

getWflStepExitValues

Description

Retrieve the exit values of the WorkflowStep.

Prototype

String[] WorkflowStep::getWflStepExitValues()

getWflStepName

Description

Returns the workflow step name.

Prototype

String WorkflowStep::getWflStepName()

getWflStepPerformerRoles

Description

Returns the list of user roles for the workflow step.

Prototype

String[]

WorkflowStep::getWflStepPerformerRoles()

getWflStepPerformerUsers

Description

Returns the list of user names for the workflow step.

Prototype

String[]

WorkflowStep::getWflStepPerformerUsers()

getWflStepScriptPath

Description

Gets the path of the workflow script for the step. If no script is defined, returns null.

Prototype

String WorkflowStep::getWflStepScriptPath()

getWflStepTimeoutDuration

Description

Gets the timeout duration for the workflow step. Returns a string in milliseconds.

Prototype

String
WorkflowStep::getWflStepTimeoutDuration()

getWflStepTimeoutNotification

Description

Gets the notification emails, which will get sent when the step times out.

Prototype

String
WorkflowStep::getWflStepTimeoutNotification()

getWflStepType

Description

Returns the workflow step type.

Prototype

String WorkflowStep::getWflStepType()

getValidationErrorEntryNode

Description

Return the EntryNode associated with this ValidationError.

Prototype

EntryNode
ValidationError::getValidationErrorEntryNode()

getValidationErrorMsg

Description

Return the error message associated with this ValidationError

Prototype

String ValidationError::getValidationErrorMsg()

getWflStepReserveToEdit

Description

Returns the reserve for edit flag for a workflow step.

Prototype

Boolean
WorkflowStep::getWflStepReserveToEdit()

mapWflStepExitValueToNextStep

Description

Maps the exit value of the WorkflowStep to the nextStep. The nextStep can either be the stepName or one WorkflowStep or an array of StepNames or an array of WorkflowSteps.

Prototype

```
void  
WorkflowStep::mapWflStepExitValueToNextStep(String exitValue, String | WorkflowStep |  
WorkflowStep[] nextStep)
```

setWflStepReserveToEdit

Description

Sets the reserve for edit flag for a workflow step.

Prototype

```
void  
WorkflowStep::setWflStepReserveToEdit(Boolea  
n flag)
```

setWflStepAddEntries

Description

Sets value of 'allow import into step' flag.

Prototype

```
void  
WorkflowStep::setWflStepAddEntries(Boolea  
n flag)
```

setWflStepAttributeGroups

Description

Sets the attrinute groups for the workflow step.

Prototype

```
void  
WorkflowStep::setWflStepAttributeGroups(Strin  
g[]/AttrGroup[] attrGroups)
```

setWflStepCategorizeEntries

Description

Sets value of 'allow recategorization' flag.

Prototype

```
void  
WorkflowStep::setWflStepCategorizeEntries(Boolea  
n flag)
```

setWflStepDesc

Description

Sets the desc for the workflow step.

Prototype

```
void WorkflowStep::setWflStepDesc(String  
stepDesc)
```

setWflStepEntryNotification

Description

Sets up the notification emails which will get sent when the item gets into the step. Email addresses must be separated by semi-colons.

Prototype

void
WorkflowStep::setWflStepEntryNotification(String emailAddresses)

setWflStepExitValues

Description

Sets the exit values for the workflow step.

Prototype

void
WorkflowStep::setWflStepExitValues(String[] exitValues)

setWflStepPerformerRoles

Description

Sets the user roles for the workflow step.

Prototype

void
WorkflowStep::setWflStepPerformerRoles(String[] roles)

setWflStepPerformerUsers

Description

Sets the users for the workflow step.

Prototype

void
WorkflowStep::setWflStepPerformerUsers(String[] users)

setWflStepScriptPath

Description

Sets up the workflow script path for this step. If no argument is passed, the default location is used (script/<workflow name>/<step name>). Note that this operation does not check that the script is already loaded (it allows you to load the script later if needed).

Prototype

void WorkflowStep::setWflStepScriptPath([String scriptPath])

setWflStepTimeoutDate

Description

Sets up the timeout date for the workflow step.

Prototype

void
WorkflowStep::setWflStepTimeoutDate(Date

date)

setWflStepTimeoutDuration

Description

Sets up the timeout duration for the workflow step. The duration must be in seconds.

Prototype

void
WorkflowStep::setWflStepTimeoutDuration(int seconds)

setWflStepTimeoutNotification

Description

Sets up the notification emails which will get sent when the step times out. Email addresses must be separated by semi-colons.

Prototype

void
WorkflowStep::setWflStepTimeoutNotification(String emailAddresses)

Widget

addListener

Description

Hook the onchange function handlerFunctionName to changes of widgetObserved - return false iff the operation fails

Prototype

boolean addListener(Widget widgetObserved, String handlerFunctionName)

addListenerForProperty

Description

Hook the onchange function handlerFunctionName to changes of widgetObserved's sProperty - return false iff the operation fails

Prototype

boolean addListenerForProperty(Widget widgetObserved, String sProperty, String handlerFunctionName)

buildWidget

Description

Creates a widget of type sType and name sName

Prototype

Widget buildWidget(String sType, String sName)

getWidget

Description

Returns the relative widget sRelativePath

Prototype

Widget Widget::getWidget(String sRelativePath)

getWidgetProperty

Description

Return the property sPropertyName of this widget

Prototype

Object Widget::getWidgetProperty(String sPropertyName)

initWidgetWithArgs

Description

Call initWidgetWithArgs on the widget

Prototype

void Widget::initWidgetWithArgs(alArgs)

invalidate

Description

Invalidate the widget - so that it gets re-rendered

Prototype

void Widget::invalidate()

isFullScreen

Description

Return true the left navigation bar is hidden

Prototype

Boolean isFullScreen()

renderHorizontalBars

Description

Return an HTML table to display horizontal bars - anHeights[i] should have the length of the i-th bar and asLabels[i] the tooltip for the i-th bar

Prototype

String renderHorizontalBars(Integer barWidth, Integer barHeight, Integer[] anLengths, String[] asLabels)

renderVerticalBars

Description

Return an HTML table to display vertical bars - anHeights[i] should have the length of the i-th column and asLabels[i] the tooltip for the i-th column

Prototype

String renderVerticalBars(Integer barWidth, Integer barHeight, Integer[] anLengths, String[] asLabels)

renderWidget

Description

Render the widgetw

Prototype

Widget::renderWidget(Writer out)

setWidgetProperty

Description

Set the property sPropertyName of this widget to the value oValue

Prototype

void Widget::setWidgetProperty(String sPropertyName, Object oValue)

Script Types

Report Scripts

- Report scripts are used to create custom reports
- When creating a report in WPC, a script is required to define the report output
- The report script is used to define how the information is ordered and formatted

Validation Rule Script Expressions

Definition:

- A validation rule, like a value rule, is used within a specification
- A validation rule is used to validate an attribute based value on a business rule
- A validation rule must return a value of true or false

Other details:

- Implicit object: item object (item)
- Implicit variable: to set the attribute to the resulting value, use "res = "
- The value for "res" needs to be either TRUE or FALSE

Distribution Scripts

Definition:

- Distributions scripts are used to create a custom distribution that is not addressed by the built-in WPC distributions
- Examples: Ariba Catalog Upload, FTP, HTTP POST, email

Import and Export Scripts

Definition:

- Import and Export scripts are used to import data into and export data out of WPC.

Other details:

- Use the operation "logWarning()" to report on lines that have something that you want to flag but still want to load in the catalog

- Use the operation "logError()" to report on lines that have something that you want to flag and when you want to prevent the line to be loaded in the catalog
- To make use of the "Item.saveCtgItem()" operation to save an item in a catalog other than the one specified in the import feed itself, you will need to put the following line at the top of the import script:
setScriptContextValue("\$action", null);

Entry Macro Scripts

Definition:

- The Entry Macro script allows a user to execute a script within the data entry screens
- For example, a script could be written to replace all strings with a given value

Other details:

- Implicit object: item object (item)
- In the context of a macro script, the script runs for each item selected in the data entry screen
- Macro scripts distinguish themselves from Mass Update scripts in that they do not save the items automatically - it is recommended that they do not
- Changes are visible on the screen and users can chose to either save or discard them

Catalog Difference Export Scripts

Definition:

- The Catalog Differences Export script allows one to perform a comparison of two catalog versions
- For each item, the status between the two versions can be accessed
- Four possible types of status: Modified, Added, Deleted, Unmodified

Other details:

- Implicit objects: file object (out), catalog object
- While the catalog object is implicit, there is not actually any implicit variable name through which to reference the catalog. To obtain a variable representing the catalog, simply execute a "getCtgByName()" passing in no arguments.

- In the context of an export, the operation "forEachCtgItem()" doesn't require the catalog name, it will by default get the Catalog Name selected when creating the syndication
- The difference status can be: M (modified), A (added), D (deleted), U (unchanged)
- The operation "getCtgItemAtOldVersion()" allows you to get the item object in the old version; you can then use it to compare it with its more recent version

Catalog Import Scripts

Definition:

- Catalog Import scripts are used during aggregation and can be used to perform advanced operations on incoming data before it is imported into a catalog
- For every import feed, WPC generates a simple script by default, based on the file spec to catalog (or catalog spec) mapping
- Instead of using the default generated script, users can create and use new scripts as needed to perform advanced operations

Other details:

- Implicit objects: file object (in), catalog object
- While the catalog object is implicit, there is not actually any implicit variable name through which to reference the catalog. To obtain a variable representing the catalog, simply execute a "getCtgByName()" passing in no arguments.
- The operation "new CtgItem()" in the context of an item feed or an item to category map feed doesn't require the catalog name; it will by default get the Catalog selected when creating the feed
- To make use of the "Item.saveCtgItem()" operation to save an item in a catalog other than the one specified in the import feed itself, you will need to put the following line at the top of the import script:
setScriptContextValue("\$action", null);
- Catalog import scripts also need to feed a "dummy" catalog if you wish to add or delete entry nodes. In other words, to add and/or delete entry nodes from Catalog A, the import feed itself must be mapped / attached to some other unused Catalog B.

Mapping Script Expressions

Definition:

- Mappings are used during imports and exports to describe, respectively, how incoming data maps to the catalog and how data in the catalog maps to the output file
- Mapping expressions can be associated to individual attribute mappings to create complex mappings involving more than one field

Other details:

- Implicit object: item object (item)

Entry Preview Scripts

Definition:

- The entry preview script allows a user to create a sample view of a current item set, which can be executed from the data entry screens
- For example, a script could be written to view how an item would display using an XML format

Other details:

- The operation "forEachCtgItem()" in the context of a preview script will run on each item selected in the data entry screen

Catalog Scripts

Definition:

- A Catalog script is a sequence of operations that a user specifies to be run at the time of item creation and edit
- This function provides another layer of functionality over the attribute level operations available via catalog specs

Other details:

- Implicit object: item object (item)
- Catalog scripts can be run before or after any other operation (value rules, validation rules) on the item
- The order sequence might be important if there are any dependencies
- The order in which the catalog script will run depends on whether it is selected as a "pre" or "post" script
- Catalog scripts are typically used instead of value rules when more than one field is modified by a rule

String Enumeration Rule Script Expressions

Definition:

- A String Enumeration Rule, like a value rule or a validation rule, is used within a specification
- A String Enumeration Rule can only be used with attributes of type "string enumeration"
- This rule is used to create a list of values available for that attribute

Other details:

- Implicit object: item object (item)
- Implicit variable: to set the attribute to the resulting value, use "res = "
- The value provided as a result must be an array

Trigger Scripts

Definition:

- Trigger scripts are created to avoid the need to populate the same script operations in multiple places
- Trigger scripts are stored in the Document Store and can be called from another script function
- Used to externally trigger events in WPC (e.g. aggregations, syndications, etc.)

Other details:

- To run a trigger script from a browser type the corresponding URL; the URL consists of the WPC application URL, with the company code and the name of the script; for example:
`http://www.WPC.com/utis/invoker.jsp?company_code=<enterYouCompanyCodeHere>&script=<enterTriggerScriptNameHere>`

Mass Update Scripts

Definition:

- The mass update script allows for greater control over multiple updates for a group of items
- Mass Update Scripts run on a scheduler and can report on warnings and errors

Other details:

- Implicit object: item object (item)
- The mass update script will run for each item in the selection
- A "saveCtgItem()" is performed for each item modified

Catalog Export Scripts

Definition:

- Catalog Export scripts are used to perform advanced, on-the-fly operations on data contained in the catalog before it is actually exported to an output file
- Modifications made to the content through the scripting engine at the time of syndication are not applied to the catalog, but rather simply applied to the output file as a one-time content modification
- All syndications require the use of a script
- Contrary to aggregation, selecting a script during syndication cannot be skipped
- However, for each new destination spec you create, three default generated scripts will be available to choose from: CSV, tab-delimited, and fixed-width

Other details:

- Implicit objects: file object (out), catalog object
- While the catalog object is implicit, there is not actually any implicit variable name through which to reference the catalog. To obtain a variable representing the catalog, simply execute a "getCtgByName()" passing in no arguments.
- In the context of an export, the operation "forEachCtgItem()" doesn't require the catalog name, it will by default get the Catalog Name selected when creating the syndication

Value Rule Script Expressions

Definition:

- A value rule is created as a parameter of an attribute in a specification
- A value rule calculates the value of the attribute it is attached to
- When an item is created or saved, the value rule is computed

Other details:

- Implicit object: item object (item)
- Implicit variable: to set the attribute to the resulting value, use "res = "

- The result you provide must be in the format of the attribute (Example: if the attribute is of type "date" then the result must be in the date format)
- If you do not provide a value in your rule, the attribute value will be set to null

Lookup Table Import Scripts

Definition:

- Lookup table scripts are very similar to aggregation scripts; they are used to populate the contents of a lookup table instead of a catalog
- Navigation to access lookup table import scripts is the same as catalog import scripts

Category Tree Import Scripts

Definition:

- Category Tree Import scripts are used during category tree aggregation
- Although a user can create a category tree manually, the Category Tree Import script allows you to build a full category tree in WPC out of an incoming flat file

Other details:

- Implicit objects: file object (in), catalog object
- While the catalog object is implicit, there is not actually any implicit variable name through which to reference the catalog. To obtain a variable representing the catalog, simply execute a "getCtgByName()" passing in no arguments.
- An implicit "saveCategoryTree()" at the end of the aggregation saves all the new categories or modified categories
- The operation "getCategoryTreeByName()" in the context of a category tree feed doesn't require the tree name; it will by default get the Category Tree selected when creating the feed
- Make sure to use a path delimiter that you are not likely to find in your category names (for example, "/" might not be a good choice if you are likely to have categories containing this symbol; instead, select something less likely to be part of the category name (e.g. "////"))

Predefined Scripts

Search and Replace Macro Including Attribute Drop-down

Box

Use the following steps to setup and use a search and replace macro for a catalog that includes a drop-down menu.

1. Navigate to the “Scripts Console” and select “Entry Macro Script”.
2. Click on the “NEW” button.
3. Select the catalog you would like the macro to appear in.
4. For “Select input parameters spec” click on “NEW”.
5. Enter spec name, e.g.: “S & R input spec”.
6. Click on the “+” to add a node to the spec. Call it “Attribute Path”. Create the node by clicking on the “+” to the right of the text box.
7. Set “Type” to “String enumeration” and then select “String enumeration rule” from the pulldown under “Type” and click on the “+” to the right of that pulldown to create the rule.
8. Click on the “trash can” next to “String enumeration”.
9. Next to “String enumeration rule”, click on “CLICK HERE” to enter the “String Enumeration Rule Editor”.
10. Copy the following script into the editor, replacing the text “Enter_Desired_Catalog_Spec_Name_Here” with the name of the catalog spec you require:

```
my_spec = getSpecByName("Enter_Desired_Catalog_Spec_Name_Here");
res = my_spec.getSpecAttribPaths();
```
11. Click on "Save" and then "Close".
12. Click on the “+” next to “S & R input spec” to add another node and name it “Search Pattern”. Click on the “+” next to the text box to create the new node and modify “Maximum Length” to the value “50”.
13. Click on the “+” next to “S & R input spec” to add another node and name it “Replace String”. Click on the “+” next to the text box to create the new node and modify “Maximum Length” to the value “50”.
14. Click on “SAVE” and then “<<|” to return to the previous screen.
15. Select the catalog you would like the macro to appear in. (as in step 3)
16. For “Select input parameters spec”, select the spec you just created: “S & R input spec”.
17. For “type” select “Regular”.

18. For “Entry Macro Script”, enter the name of the macro script, e.g.: “S & R macro”.

19. In the “Catalog Script Editor”, paste the following script:

```
attribPath = inputs["Attribute Path"];
attribValue = item.getCtgItemAttrib(attribPath);
myRe = new RE(inputs["Search Pattern"]);
newAttribValue = myRe.substitute(attribValue, inputs["Replace
String"]);
item.setCtgItemAttrib(attribPath, newAttribValue);
```

20. Click on “save” and then “<<|” to return to the Scripts Console.

Usage

From the Multiple Edit Data Entry screen, check the items you want to run the search and replace against, select “S & R macro” from the “MACRO” pull-down and click on “MACRO”. The macro will now work like the “Sample Replace String Macro Script” except you can now select the desired field via pull-down.

Post-Save Audit Log Script

Here is the post-save audit log script that can be directly leveraged to support the Attribute Change Audit Logs for Catalogs:

```
oItem = item.getOriginalItem();
changedAttributes = item.getChangedAttributes(oItem);
catalogName = item.getCatalog().getCtgName();
userName = getCurrentUserName();

logName = "Item Audit Trail";
containerType = "CATALOG";
containerObject = item.getCatalog();
entryType = "ITEM";
entryObject = item;

userDefinedLog = getUserDefinedLogByName(logName, containerType,
containerObject);

changed = false;

logMessage = "<table width='100%' cellpadding=2 cellspacing=0 border=0
style='border-style:solid; border-width:1; border-color:#646464'><tr
bgcolor='#d3d3d3'><td bgcolor='#d8d8d8' width=120 rowspan='\" +
changedAttributes.size() + \"'> \" + userName + \"</td><td rowspan='\" +
changedAttributes.size() + \"' width=1 bgcolor='#646464'
style='padding:0'><img src='/locales/en_US/images/newlook/spacer.gif'
width=1 border=0></td>\";
if(oItem != null)
{
    for(i=0; i<changedAttributes.size(); i++)
    {
```

```

changed = true;
string = catalogName + ":" + changedAttributes[i];

oldValue = oItem.getCtgItemAttrib(string);
newValue = item.getCtgItemAttrib(string);

if(i!=0)
{
    logMessage = logMessage + "<tr bgcolor='" + (((i/2.0)-(i/2))==0)? "#d0d0d0":"#dfdfdf") + "'>";
}

    logMessage = logMessage + "<td> " + changedAttributes[i] + "
was changed from [<b>" + oldValue + "</b>] to [<b>" + newValue +
"</b>]<td></tr>";
}
}
else
{
    if(item.getCtgItemId() == -1)
    {
        logMessage = logMessage + "<td>Item deleted [<b>" +
item.getCtgItemPrimaryKey() + "</b>]</td></tr>";
    }
    else
    {
        logMessage = logMessage + "<td>Item added [<b>" +
item.getCtgItemPrimaryKey() + "</b>]</td></tr>";
    }
    changed = true;
}

logMessage = logMessage + "</table>";
if(changed == true)
{
    udlLogMessage = new UserDefinedLogEntry(today(), containerType,
containerObject, entryType, entryObject, logMessage);
    userDefinedLog.insertEntryToLog(udlLogMessage);
}
}

```