

Report Modernization Utility for z/OS and OS/390



User's Guide and Reference

Version 1 Release 1

Report Modernization Utility for z/OS and OS/390



User's Guide and Reference

Version 1 Release 1

Note!

Before using this information and the product it supports, be sure to read the general information under "Notices" on page 65.

First Edition (March 2009)

This edition applies to Report Modernization Utility for z/OS Version 1 Release 1, Program Number 5697-P33 and to any subsequent releases until otherwise indicated in new editions. Make sure you are using the correct edition for the level of the product.

The information in this manual was furnished by Foundation Software, Inc.

This publication is available on the Web at:

<http://www.ibm.com/software/awdtools/migration>

Order publications through your IBM representative or the IBM branch office serving your locality. Publications are not stocked at the address below.

A form for readers' comments is provided at the back of this publication. If the form has been removed, address your comments to:

IBM Corporation
H150/090
555 Bailey Avenue
San Jose, CA
95141-1003
U.S.A.

or fax your comments from within the U.S.A., to 800-426-7773, or, from outside the U.S.A., to 408-463-2629.

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

© Copyright Foundation Software, Inc. 2009.

All rights reserved. Unauthorized use or disclosure of any part of the system is prohibited. Foundation Software, Inc. has granted IBM a non-exclusive license to market RMU as Report Modernization Utility.

© Copyright International Business Machines Corporation 2009.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

About this manual	v	Decorating an HTML document	29
Who should use this manual	vii	Debugging RMU Script programs	30
Structure of this manual	ix	Chapter 5. RMU Script language	
How to read syntax diagrams	xi	instruction reference.	33
Chapter 1. Introducing RMU	1	PARM statement.	33
How does it work?	1	DEFINE statement	34
RMU features	1	<object> and </object> tag	35
Chapter 2. Working with RMU	3	<style> and </style> tag	35
Running RMU.	3	<docs_top> and </docs_top> tag	36
Distributing output documents	4	<docs_end> and </docs_end> tag.	37
Summary of available jobs.	5	<page_top> and </page_top> tag	37
Summary of file DD Names	5	<page_end> and </page_end> tag	38
File descriptions	7	Assignment statement.	38
Using the FZHBPARS parser utility.	8	BYPASS statement	41
Chapter 3. Installation and RMU		CALL statement	42
options	11	CONTINUE statement.	42
Installation	11	CONTROL statement	43
RMU default options (FZHOPTAB) table	11	DISPLAY statement.	44
RMU default library locator table (FZHPROC)	13	DO and END-DO statements	44
Setting up the z/OS server (UNIX) environment	14	EVALUATE and END-EVALUATE statements	45
System information.	15	IF, ELSE, and END-IF statements	47
Chapter 4. Working with RMU Script	17	PERFORM statement	47
Basic concepts	17	PROC/END-PROC statement	48
I/O handling.	17	PROCESS statement	49
Coding rules	18	STOP statement	49
Program example	19	STRING statement	50
Creating CSV documents	21	System-defined fields	51
Creating simple HTML documents	24	COBOL verbs, statements, and reserved fields.	52
Creating HTML1 documents with the control breaks			
selection tree	26		
		Chapter 6. Messages.	59
		RMU compiler-generated messages	59
		Notices	65
		Trademarks	66
		Index	67

About this manual

This manual describes how to use the Report Modernization Utility for z/OS licensed program.

In the rest of this document, the Report Modernization Utility for z/OS is referred to as "RMU".

Who should use this manual

This manual is for anyone who wants to convert standard mainframe reports to HTML or Character Separated Values (CSV) file format.

To use RMU properly, you need to be familiar with:

- Job Control (JCL)
- The RMU script language (RMU Script)
- COBOL compiling procedures

Structure of this manual

This manual consists of:

- Chapter 1, “Introducing RMU,” on page 1.
Explains what RMU is and how it works.
- Chapter 2, “Working with RMU,” on page 3.
An overview of the supplied JCL.
- Chapter 3, “Installation and RMU options,” on page 11.
Describes RMU installation and customization.
- Chapter 4, “Working with RMU Script,” on page 17.
Describes in detail how to work with the RMU Script language.
- Chapter 5, “RMU Script language instruction reference,” on page 33.
Describes statements supported by RMU.
- Chapter 6, “Messages,” on page 59.
Provides a list of:
 - COBOL compiler generated messages
 - RMU runtime error messages
 - RMU compiler generated messages

How to read syntax diagrams

The syntactical structure of commands described in this document is shown by means of syntax diagrams.

Figure 1 shows a sample syntax diagram that includes the various notations used to indicate such things as whether:

- An item is a keyword or a variable.
- An item is required or optional.
- A choice is available.
- A default applies if you do not specify a value.
- You can repeat an item.




Figure 1. Sample syntax diagram

Here are some tips for reading and understanding syntax diagrams:

Order of reading

Read the syntax diagrams from left to right, from top to bottom, following the path of the line.

The ►— symbol indicates the beginning of a statement.

The —► symbol indicates that a statement is continued on the next line.

The ►— symbol indicates that a statement is continued from the previous line.

The —► symbol indicates the end of a statement.

Keywords

Keywords appear in uppercase letters.

►►—COMMAND_NAME—►►

Sometimes you only need to type the first few letters of a keyword. The required part of the keyword appears in uppercase letters.

►►

DEFAULT_KEYWORD
KEYword

—►►

In this example, you could type "KEY", "KEYW", "KEYWO", "KEYWOR" or "KEYWORD".

The abbreviated or whole keyword you enter must be spelled exactly as shown.

Variables

Variables appear in lowercase letters. They represent user-supplied names or values.

►►—*required_variable*—►►

Required items

Required items appear on the horizontal line (the main path).

►►—COMMAND_NAME—*required_variable*—►►

Optional items

Optional items appear below the main path.

►►


OPTIONAL_KEYWORD= <i>variable</i>

—►►

Choice of items

If you can choose from two or more items, they appear vertically, in a stack.

If you *must* choose one of the items, one item of the stack appears on the main path.



If choosing one of the items is optional, the entire stack appears below the main path.



If a default value applies when you do not choose any of the items, the default value appears above the main path.



Repeatable items

An arrow returning to the left above the main line indicates an item that can be repeated.




If you need to specify a separator character (such as a comma) between repeatable items, the line with the arrow returning to the left shows the separator character you must specify.




Fragments

Where it makes the syntax diagram easier to read, a section or *fragment* of the syntax is sometimes shown separately.



⋮

fragment_name:



Chapter 1. Introducing RMU

RMU is a stand-alone utility that converts mainframe printer files (reports) to HTML and CSV files. It runs exclusively on the z/OS[®] platform.

The purpose of RMU is to provide a comprehensive tool for converting mainframe reports to an HTML and CSV format which is understood by standard browsers and spreadsheet software such as IE and EXCEL, without the need to modify existing programs. Once the reports are converted, they can be published to z/OS or any other server, or downloaded to a PC platform for local access.

How does it work?

RMU executes on z/OS in background as a batch job. The input and output environment is controlled by means of JCL. RMU Script is available for massaging and decorating the input. The output is published directly to the z/OS server, or written to a file that can be routed or downloaded to any other server or client platform.

RMU features

The main features within RMU are:

- HTML and CSV documents can be produced from standard reports without changing the application programs.
- RMU Script is available for decorating HTML documents. The language can:
 - Decorate HTML text by means of fonts, CSS, colors, and so on. For example:
 - Negative amounts can be turned red.
 - The background can simulate 1403 green-striped printer paper.
 - Place objects such as pictures and special annotations at specific positions in the document.
 - Be used in interpretive mode or compiled and linked mode.
- Simple HTML documents can be produced (the use of RMU Script is optional).
- HTML documents, with a control breaks tree on the left side and the report body on the right side, can be produced (the use of RMU Script is required).
- HTML documents can be published to the z/OS server by pointing the JCL to the z/OS server.
- HTML documents can be created to a disk file and downloaded to any other platform.
- CSV files can be produced (the use of RMU Script is required).

RMU features

Chapter 2. Working with RMU

This section provides an overview of the JCL supplied with RMU.

Running RMU

RMU can be run as a stand-alone batch utility in three ways:

Running RMU without RMU Script

This is the simplest form. The FZHRMU00 program is run without the SYSIN for RMU Script. The input report is read and an output HTML-format document is created without custom decorations. The background color and turf is supplied by the PARM= ('STYLE=&css,TURF=&turf') options on the EXEC statement.

```
//RUNRMU EXEC PGM=FZHRMU00,PARM=('STYLE=&css,TURF=&turf')
```

Where:

&css PDS member containing CSS in FJIDOC0 PDS. This is an optional parameter.

&turf The background color. Valid values are:

1403-paper Simulate 1403 green-striped printer paper. This is the default.

NO Create plain solid background color.

Use the supplied FZHRMUJ0 or FZHRMUX0 job located in the &SYS1.SFZJHCLS library as a template for your own jobs.

Running RMU with compiled RMU Script

In this mode, the FZHRMU00 program is run by invoking a compiled RMU Script program. The name of the RMU Script program to use and the style CSS are supplied by the PARM= on the EXEC statement.

```
//RUNCOMP EXEC PGM=FZHRMU00,PARM=('SCRIPT=&pgmname,STYLE=&css')
```

Where:

&pgmname The name of the script program. This is a required parameter.

&css The PDS member containing CSS in FJIDOC0 PDS. Style is used only if there is no style method coded in the RMU Script. This is an optional parameter.

The SYSIN for the Script source must not be coded in the JCL.

The **&pgmname**, RMU SCRIPT, must have been previously compiled and linked by means of the FZHRMU01 compiler.

Use the supplied FZHLINKJ job located in the &SYS1.SFZJHCLS library as a template to compile and link RMU Script programs.

Use the supplied FZHRMUJ1 or FZHRMUX1 job located in the &SYS1.SFZJHCLS library as a template to run the compiled RMU Script program.

Running RMU with RMU Script in "link and go" mode

In this mode, the FZHRMU00 program compiles and links RMU Script pointed to by the SYSIN and then runs it. SYSIN can be a flat file, a PDS or PDSE member, or an inline source. The background style can be supplied by the PARM= on the EXEC statement.

```
//RUNCOMP EXEC PGM=FZHRMU00,PARM=(STYLE=&css)
```

Where:

&css PDS member containing CSS in FJIDOC0 PDS. Style is used if there is no style method coded in the RMU Script. This is an optional parameter.

The SYSIN is required.

"PARM LINK (&NAME)" must not be specified on the PARM statement in the RMU Script program.

Use the supplied FZHRMUJ2 or FZHRMUX2 job located in the &SYS1.SFZHJCLS library as a template to run as "link and go".

Distributing output documents

RMU can publish the output documents to the z/OS server (UNIX®), or to a regular z/OS flat variable-length file.

When documents are published to a regular z/OS variable-length file, the file must be downloaded to a PC (or another server) for access.

- **When you create simple HTML format**, download the output file as an ASCII text file with an extension of .htm. The downloaded file can be opened with IE or any other compatible browser.
- **When you create HTML1 format**, download the output as a binary file and run the FZHBPARS Java™ parser to build the required directories. See "Using the FZHBPARS parser utility" on page 8 for detailed steps.
- **When you create a CSV file**, download the output file as an ASCII text file with an extension of .csv. The downloaded file then can be imported into any spreadsheet software.

When documents are published to the z/OS server, the z/OS UNIX environment must be established and enabled. A root directory on the z/OS UNIX system must be established for each user. Coordinate access to the UNIX environment with your z/OS system administrator.

RMU determines where to send the output by checking for the existence of the name FJUNIX0 DD in the JCL. PATH= on the FJUNIX0 definition must point to the root directory showing where to write the documents.

If the name FJUNIX0 DD exists in the JCL, RMU assumes that the HTML documents are being sent to a z/OS UNIX System. If the name FJUNIX0 DD does not exist, RMU creates a flat file on z/OS.

Note: UNIX files are handled by the FZHUNIX1 RMU program. This program is dynamically loaded at end of job when combining the output. UNIX is case-sensitive. That is, commands, directory, and file names must be typed exactly as defined on the UNIX system.

When publishing to the z/OS server, RMU must comply with the code set (ASCII or EBCDIC) defined for each document type on the UNIX system. The code set is obtained from the UNIX file, `httpd.conf`.

Note: The layout of the UNIX file, `httpd.conf`, is beyond the scope of this document. Consult with your z/OS system administrator for the location of this file.

The `httpd.conf` file is pointed to by the `FJCONFIG` DD name in the JCL. It can be a z/OS PDS member or a file in the UNIX directory.

If the `FJCONFIG` DD name is not in the JCL, ASCII is assumed for HTML and CSV files, and binary code for gif files.

For a list of available job templates in the `&SYS1.SFZJCLS` library, see “Summary of available jobs.”

For a list of files needed in the JCL, see “Summary of file DD Names.”

Summary of available jobs

These jobs are available:

RMU Script compiler job (FZHRMU01 program):

FZHLINKJ Compile and link RMU Script program.

Jobs to use when the output documents are to be kept on z/OS for downloading to a PC (or other non-z/OS server):

FZHRMUJ0 Run RMU without the RMU Script program.

FZHRMUJ1 Run the compiled RMU Script program.

FZHRMUJ2 Run RMU Script as a “link and go” job.

Jobs to be used when output documents are to be distributed to the z/OS server (UNIX on z/OS):

FZHRMUX0 Run RMU without the RMU Script program.

FZHRMUX1 Run the compiled RMU Script program.

FZHRMUX2 Run RMU Script as a “link and go” job.

Summary of file DD Names

These files are required when running RMU without the RMU Script program:

Table 1. Files required when running RMU without the RMU Script

File	Required or optional
FJIRPT0	Required
FJORPT0	Required
FJIDOC0	Optional
SYSOUT	Required

These files are required when compiling RMU Script:

Table 2. Files required when when compiling RMU Script

File	Required or optional
COBLIST	Optional

Summary of file DD Names

Table 2. Files required when when compiling RMU Script (continued)

File	Required or optional
FJSVC99	Optional
LKEDMAP	Optional
RMULIST	Optional
RMUERR1	Optional
SYSLMOD	Required
SYSIN	Required

These files are required when running RMU with compiled RMU Script:

Table 3. Files required when running RMU with compiled RMU script

File	Required or optional
FJIRPT0	Required
FJORPT0	Required
FJIDOC0	Optional
FJSVC99	Optional
SYSOUT	Required

These files are required when running RMU in "link and go" mode:

Table 4. Files required when running RMU in "link and go" mode

File	Required or optional
COBLIST	Optional
FJIRPT0	Required
FJORPT0	Required
FJIDOC0	Optional
FJSVC99	Optional
LKEDMAP	Optional
RMULIST	Optional
RMUERR1	Optional
SYSOUT	Required
SYSIN	Required

These are additional files needed when publishing to z/OS UNIX:

Table 5. Additional files needed when publishing to z/OS UNIX

File	Required or optional
FJUNIX0	Required
FJDMAP0	Optional
STDERR	Optional
STDOUT	Optional
FJCONFIG	Optional

File descriptions

COBLIST

Output COBOL compiler listing.

RECFM=FBA, LRECL=133.

This file is created when compiling RMU Script and the COBOL option is coded on the PARM in the RMU Script program. This is an optional file. The default is SYSOUT=*

FJCONFIG

Optional z/OS UNIX configuration file for determining the code set for file types. The file is used when publishing the document to the z/OS UNIX server. It can be a z/OS PDS member, or a file in the UNIX directory. If FJCONFIG is not in the JCL, ASCII is assumed for HTML and CSV files, and binary code for gif files.

FJDMAP0

Output list of files published to the z/OS server (z/OS UNIX).

RECFM=VB, LRECL=4096

This is an optional file. The default is SYSOUT=*

FJIDOC0

Input file where HTML templates and CSS files are located.

RECFM=VB, LRECL=4096

This is an optional file. The default is &SYS1.SFZHDOCS PDS. If you are creating custom CSS files, place the FJIDOC0 DD name in the JCL. Concatenate &SYS1.SFZHDOCS first, followed by your own data set names.

FJIRPT0

The input report (report to be converted).

This can be an FBA/VBA or an FB/VB file. Maximum LRECL=512 (including cc).

The first byte must be a valid ANSI print control character.

FJORPT0

The output report (HTML or CSV document).

RECFM=VB, LRECL=4096

When distributing to z/OS UNIX, this file is used as a work file. When creating a z/OS flat file, this file must be downloaded to a PC (or another server). The HTML1 format output must be parsed with the FZHBPARS parser utility. For details, see "Using the FZHBPARS parser utility" on page 8.

FJSVC99

This is an optional DD name for turning SVC99 messages ON or OFF. This is a dummy temporary file used to control RMU's dynamic allocator messages. If supplied, it must be coded as follows:

```
//FJSVC99 DD DSN=&&FJSVC99(&svc99),DISP=NEW
```

Where:

&svc99

Can have one of the values: MSGOFF, MSGALL, or MSGTXT.

Summary of file DD Names

FJUNIX0

z/OS UNIX path (directory on z/OS UNIX showing where to publish the output). This is an HFS file. The maximum buffer length is 4096. The specified path must exist on z/OS UNIX with read and write permissions. When publishing to z/OS UNIX, RMU uses this path as the base directory into which all other created subdirectories and files are placed.

FJUNIX1

z/OS UNIX HFS file internally allocated by RMU. The files are dynamically allocated by RMU. Do not code this file in the JCL.

LKEDMAP

Link Edit map from the link step.

RECFM=FBA, LRECL=133

This file is created when compiling RMU Script and the LKED option is coded on the PARM in the RMU Script program. This is an optional file. The default is SYSOUT=*.

RMULIST

RMU Script compiler listing.

RECFM=FBA, LRECL=133

This file is produced by the RMU Script compiler. This is an optional file. The default is SYSOUT=*.

RMUERR1

RMU Script compiler errors.

RECFM=FBA, LRECL=133

This file is produced by the RMU Script compiler. This is an optional file. The default is SYSOUT=*.

STDERR

Standard z/OS UNIX error file. When publishing to z/OS UNIX, potential UNIX errors are written to this file. The default is STDERR in the home directory on z/OS UNIX.

STDOUT

Standard z/OS UNIX messages file. When publishing to z/OS UNIX, standard UNIX messages are written to this file. The default is STDOUT in the home directory on z/OS UNIX.

SYSIN

SYSIN of the RMU Script program.

RECFM=F, LRECL=80

This is an optional file. If present, the use of the RMU script compiler is assumed.

SYSOUT

Standard SYSOUT file for runtime messages required by every job.

Using the FZHBPARS parser utility

For the HTML1 option, RMU generates a binary format file that contains several HTML, gif, and CSS documents. The downloaded file must be parsed with the Java program, FZHBPARS, before it can be viewed with a browser.

To install the parser program FZHBPARS:

1. On your PC or a server, create a directory for the RMU documents.
This is an example of a Windows[®] command line to create a directory called RMUDOCs:
`md rmudocs`
2. Download from the mainframe (in binary format with no LF/CR) &SYS1.SFZHDOCS(fzhbpars) into the created directory:
`c:\rmudocs\fzhbpars.class`

To view an HTML1 document on your PC or a server, perform these tasks:

1. Make sure that Java VM is installed and running.
2. Download the HTML1 document file from the mainframe (in binary format, no LF/CR) into a directory (assume the rmudocs directory).
3. Switch to the rmudocs directory:
`cd\rmudocs`
4. Enter on the command line:
`java fzhbpars &src &dest`

Where:

&src The downloaded HTML1 document file.

&dest The target directory for the HTML1 documents.

For example (assuming the file name htmlfil1.bin):

```
java fzhbpars htmlfil1.bin htmlfil1
```

At completion, all HTML documents are created in the c:\rmudocs\htmlfil1\r001 directory (drive c: assumed). To view from your default browser, click on the c:\rmudocs\htmlfil1\r001\index.htm file. Alternatively, you can open your browser and enter in the URL:

```
file:///C:/rmudocs/htmlfil1/r001/index.htm
```

When you click on index.htm, a selection tree on the left and the report body on the right side of the screen is displayed. When you click on FJORPT0.htm, the report body is displayed on the screen.

Chapter 3. Installation and RMU options

This section describes RMU installation and customization.

Installation

RMU is installed using SMP/E. Refer to the *Program Directory* (GI10-8807-00) for installation instructions.

RMU consists of these six libraries:

&SYS1.SFZHAMAC	Assembler (BAL) macros.
&SYS1.SFZHASRC	BAL programs source.
&SYS1.SFZHDOCS	HTML templates and CSS files.
&SYS1.SFZHJCLS	JCL library with test programs.
&SYS1.SFZHLOAD	Load library.
&SYS1.SFZHPROC	PROC Library.

At installation, perform the tasks as described in these sections:

- “RMU default options (FZHOPTAB) table.”
- “RMU default library locator table (FZHPROC)S)” on page 13.
- “Setting up the z/OS server (UNIX) environment” on page 14.
- “System information” on page 15.

On completion, tailor and test these jobs located in the &SYS1.SFZHJCLS library:

FZHLINKJ	Compile and link the RMU Script program.
FZHRMUJ0	Run RMU without the Script program.
FZHRMUJ1	Run the compiled Script program.
FZHRMUJ2	Run RMU Script as a “link and go” job.
FZHDELCJ	Copy the test report with print control characters expanded.

If you are distributing HTML reports to the z/OS server (UNIX server on z/OS), tailor and test these jobs:

FZHRMUX0	Run RMU without the Script program.
FZHRMUX1	Run the compiled Script program.
FZHRMUX2	Run RMU Script as a “link and go” job.

Installation is successful if all jobs run to a normal end of job.

For instructions on how to use RMU for general users, see Chapter 2, “Working with RMU,” on page 3.

RMU default options (FZHOPTAB) table

The RMU default options are located in the FZHOPTAB table. The source code for the table is located in the &SYS1.SFZHASRC library.

Users in the United States can use the table as shipped on the product tape.

Users outside the United States should adjust the currency and the decimal character by means of the CURRENCY= and the DECIMAL= parameters respectively.

Installation

To assemble and link the table, use the FZHASMOJ job located in the &SYS1.SFZHJCLS library. You may need to tailor the job name and system libraries.

Figure 2 shows a copy of FZHOPTAB distributed with RMU:

```
FZHOPTAB FSMACRMU TYPE=E,          .E = GENERATE NUCLEUS          X
          OPSYS=MVS,              .OPERATING SYSTEM MVS          X
          COMPANY='FOUNDATION SOFTWARE INC.',          X
          DISTNUM=RMU02139, .DISTRIBUTION ID FOR RMULIST          X
          RELEASE=V1R1.00, .SOFTWARE RELEASE VERS,REL,MOD          X
          RELDATE=02/01/09, .SOFTWARE RELEASE DATE          X
          RMULIST=YES,            .TRANSLATOR DEFAULT LIST OPTION  X
          COBLIST=YES,            .COBOL COMPILER DEFAULT LIST     X
          LKEDLST=YES,            .LINK STEP LIST OPTION          X
          DECIMAL=PERIOD,         .PERIOD/COMMA                   X
          CURRENCY=$,             .CURRENCY SYMBOL                X
          CSVCHAR=',',            .DEFAULT CSV CHARACTER          X
          ERRLIMIT=128,           .ERROR LIMIT COUNTER            X
          TURF=1403-PAPER,        .TURF NO/1403-PAPER             X
          LINESIZE=512,           .MAXIMUM REPORT LINE SIZE (INCL CC) X
          PAGESIZE=66,            .MAXIMUM LINES PER PAGE (1 - 99) X
          MAXSIZE=32767,          .MAX FIELD LENGTH ALLOWED VIA DEFINE X
          FORMAT=HTML             .DEFAULT FORMAT HTML/HTML1/CSV
END FZHOPTAB
```

Figure 2. Copy of FZHOPTAB distributed with RMU

Explanation:

TYPE=E Macro type. Do not change.

OPSYS=MVS Operating system. Do not change.

COMPANY='FOUNDATION SOFTWARE INC.'
Your company name up to 30 characters long.

RELEASE=V1R1.00
Software release. Do not change.

RELDATE=02/01/09
Software release date. Do not change

RMULIST=YES
Default RMU Script compiler LIST option:
YES Print RMU Script listing.
NO Do not print RMU Script listing.

COBLIST=YES
Default COBOL compiler LIST option:
YES Print COBOL listing.

LKEDLST=YES
Default Link LIST option:
YES Print Link listing.
NO Do not print Link listing.

DECIMAL=PERIOD
Default character for decimal point:
PERIOD Use period (.).
COMMA Use comma (,).

CURRENCY=\$

Default currency symbol. The currency symbol must be a single character acceptable by COBOL.

CSVCHAR=',' Default separator character for CSV files. You can change this to a character of your own choosing.

ERRLIMIT=128

Error limit for the RMU Script compiler. The RMU Script compiler terminates after reaching the number of errors specified by this parameter.

TURF=1403-PAPER

Default background 1403-PAPER decorating option:

1403-PAPER Generate HTML with stripes to simulate 1403 printer paper.

NO Do not generate simulated 1403 printer paper.

LINESIZE=512

Maximum input reports line size (including print control character). This parameter is reserved for future use. Do not change.

PAGESIZE=66 Maximum input report lines per page. Do not change.

MAXSIZE=32767

Maximum RMU field size allowed. This size applies to the DEFINE statement in RMU Script. The maximum is 32,767. Do not change.

FORMAT=HTML

Default output format:

HTML Produce a simple HTML report.

HTML1 Produce a HTML report with a selection tree on the left side by control break fields. RMU Script is required unless no control breaks are needed.

CSV Produce a CSV file. Refer to the **CSVCHAR=** parameter for the default character to be used.

RMU default library locator table (FZHPROC)

RMU is compiled with the FZHRMU01 program.

FZHRMU01:

- Is invoked directly from JCL when the RMU Script program is to be compiled and linked only.
- Is invoked indirectly from the FZHRMU00 program when performing "link and go".
- Invokes and performs these tasks as a single step:
 - Converts RMU Script source to z/OS COBOL by means of the FZHRMUS1 utility.
 - Compiles the generated COBOL by means of z/OS Enterprise COBOL.
 - Links the compiled program.

To activate the FZHRMU01 program, perform these steps:

1. Tailor FZH#PROC, located in &SYS1.SFZHJCLS. This proc is read by the FZHRMU01 program. It contains all the information and steps needed to simulate the single step process.

Installation

To tailor, follow the comments embedded in the proc. You will probably need to change these parameters: `TWORK=`, `CWORK=`, `MODEL=`, and `COBLIB=`. You may have to change other parameters, depending on your requirements. Verify the entire proc for potential changes.

If you comment out a keyword, you must also comment out all references to it. The `SYSRDD=&DDname` option can be changed to redirect COBOL listings to a different DDname.

The default COBOL internal printer is set to `FJSYSR`. This DD name is internally allocated and used by Migration Utility. Do not code it in the JCL.

While testing, you can change `SVC99=MSGOFF` in `FZH#PROC` to one of these options:

MSGOFF	Disable dynamic allocator tracing.
MSGON	Display JES messages.
MSGALL	Display input text and JES messages.
MSGSER	Display messages of a serious nature only.
MSGTXT	Display input text only.

Use these options to trace `FZH#PROC` and the dynamic allocation problems that might arise during testing. For production use, `SVC99=MSGOFF` is recommended to avoid excessive console messages.

Note: Messages can be controlled by placing this statement in the JCL:

```
//FJSVC99 DD DSN=&&FJSVC99(&SVC99),DISP=NEW
```

Where: `&SVC99` is one of the previously listed options.

2. Change the `FZHPROC`s table, located in `&SYS1.SFZHASRC`.

You must change this program to point to the RMU libraries installed on your system. Change the `PROCLIB0` constant to point to the PDS where `FZH#PROC` from step #1 is located. Change the `PRODUCT0` constant to the high-level qualifier of the Migration Utility libraries.

Assemble and link the `FZHPROC`s program using the `FZHASMPJ` job located in the `&SYS1.SFZHJCLS` library. This program must be linked into the RMU `&SYS1.SFZHLOAD` library.

Note: `FZHRMU01` loads `FZHPROC`s to locate the `FZH#PROC` member and to acquire a replacement for the `&SYS1` symbol located in `FZH#PROC`. The information in `FZHPROC`s must always point to proper libraries. This means that if you rename or move your RMU libraries, you must also adjust the information in `FZHPROC`s accordingly.

Setting up the z/OS server (UNIX) environment

RMU can automatically publish the output documents to the z/OS server (UNIX) or to a regular z/OS variable-length flat file.

To publish to the z/OS server, the z/OS UNIX environment must be established and enabled. A root directory on the z/OS UNIX system must be established for each user. Coordinate access to UNIX environment with your z/OS system administrator.

RMU determines where to send the output by checking for the existence of the `FJUNIX0` DD name in the JCL. The `PATH=` parameter on the `FJUNIX0` definition points to the root directory showing where to write the documents.

If FJUNIX0 exists, RMU assumes that the HTML documents are being sent to the z/OS UNIX System. If FJUNIX0 does not exist, RMU creates a flat file on z/OS.

Note: UNIX files are handled by the FZHUNIX1 RMU program. This program is dynamically loaded at end of job when combining the output. UNIX is case-sensitive. That is, commands, directory, and file names must be typed exactly as defined on the UNIX system.

When publishing to the z/OS server, RMU must comply with the code set (ASCII or EBCDIC) defined for each document type on the UNIX system. The code set is obtained from the UNIX file, httpd.conf.

httpd.conf is pointed to by the FJCONFIG DD name in the JCL. It can be a z/OS PDS member, or a file in the UNIX directory.

If FJCONFIG is not in the JCL, ASCII is assumed for HTML and CSV files, and binary code for gif files.

These job examples located in &SYS1.SFZHJCLS can be used as templates to build custom jobs for publishing to z/OS UNIX:

FZHRMUX0
FZHRMUX1
FZHRMUX2

System information

These jobs and JCL are distributed in the &SYS1.SFZHJCLS library:

FZH#READ	RMU system information.
FZH#PROC	RMU Script compiler proc.
FZHASMOJ	JCL to assemble the RMU options table.
FZHASMPJ	JCL to assemble the RMU default proc location.
FZHDELCJ	Utility to expand the report print control characters.
FZHLINKJ	Job to compile and link RMU Script programs.
FZHRMUJ0	Job to run the FZHRMU00 utility (without Script program).
FZHRMUJ1	Job to run the FZHRMU00 utility with compiled script.
FZHRMUJ2	Job to run the FZHRMU00 utility with Script compile and "link and go".
FZHRMUX0	Job to run the FZHRMU00 utility (without Script program). Distributes to z/OS UNIX.
FZHRMUX1	Job to run the FZHRMU00 utility with compiled script. Distributes to z/OS UNIX.
FZHRMUX2	Job to run the FZHRMU00 utility with script compile, "link and go". Distributes to z/OS UNIX.
FZHTEST0	RMU Script example. Compile and link only.
FZHTEST1	RMU Script example. Compile, "link and go".
FZHTEST2	RMU Script example. Compile, "link and go".
FZHTEST3	RMU Script example. Compile, "link and go".
FZHTEST4	RMU Script example. Compile, "link and go".
FZHRPT00	Demo report file.

These procs are distributed in the &SYS1.SFZHPROC library:

Proc to compile and Link RMU Script.
Proc to compile, "link and go", z/OS UNIX output.
Proc to compile, "link and go", z/OS file output.
Proc to run compiled script, z/OS UNIX output.
Proc to run compiled script, z/OS file output.

Installation

These members are distributed in the &SYS1.SFZHDOCS library:

FZHBPARS	Java program for parsing HTML docs on PC platform.
FZHRMUL0	RMU logo gif file.
FZHMINUS	Minus sign symbol.
FZHPAGES	Page break symbol.
FZHPLUS0	Plus sign symbol.
FZHRARRW	Arrow symbol.
FZHSTOP0	Stop symbol.
FZHEBASE	HTML template.
FZHEBCSS	Base CSS templates.
FZHEINDEX	JavaScript tree index.
FZHELOAD	JavaScript tree load.
FZHEPCSS	Tree CSS templates.

This BAL source is distributed in &SYS1.SFZHASRC:

FZHOPTAB	RMU options table.
FZHPROCS	RMU default proc locator.

This assembler macro is distributed in &SYS1.SFZHAMAC:

FSMACRMU	RMU Assembler macros needed for FZHOPTAB.
-----------------	---

These modules are distributed in the &SYS1.SFZHLOAD library:

FZHATTCH	RMU internal use. Task attach module.
FZHCPYRT	RMU internal use. Copyright information.
FZHCSV00	CSV file I/O module.
FZHCVDAT	RMU internal use. Date retrieval module.
FZHDDCPY	RMU internal use. Dynamic allocator submodules.
FZHDELCC	Utility program to expand report print control characters.
FZHDYNCV	RMU internal use. EBCDIC/ASCII code conversion module.
FZHGJOB0	RMU internal use. Get job information.
FZHGOPT0	RMU internal use. Dynamic allocator submodules.
FZHGPRM0	RMU internal use. PARM retrieval from EXEC statement.
FZHGUSER	RMU internal use. Registration module.
FZHHTML0	RMU internal use. HTML formatter module.
FZHHTML1	RMU internal use. HTML1 formatter module.
FZHJCL00	RMU internal use. Installation JCL tailoring utility.
FZHJCL01	RMU internal use. Installation JCL tailoring utility.
FZHMVSC0	RMU internal use. Console I/O module.
FZHMVSC1	RMU internal use. Console I/O module.
FZHOPTAB	RMU options table. Prepared by the installer.
FZHPROCS	RMU default proc locator. Prepared by the installer.
FZHRMUB1	RMU internal use. COBOL skeleton.
FZHRMUSP	RMU internal use. I/O module for RMU listing.
FZHRMUS1	RMU internal use. RMU script compiler submodule.
FZHRMUS2	RMU internal use. RMU script compiler submodule.
FZHRMUS3	RMU internal use. RMU script compiler module.
FZHRMUW1	RMU internal use. COBOL and RMU reserved words.
FZHRMU00	RMU main utility for "link and go" or run without RMU script.
FZHRMU01	RMU Script compiler one step driver.
FZHSRC00	RMU developers tool.
FZHSTAE0	RMU compiler abend interrupt handler.
FZHSVC99	Dynamic Allocator program (SVC99 handler).
FZHTEST0	RMU compiled script test program.
FZHUNIX0	RMU internal use. Z/OS UNIX interface module.
FZHUNIX1	RMU internal use. Z/OS UNIX interface module.

Chapter 4. Working with RMU Script

This section describes in detail how to work with the RMU Script language

Basic concepts

RMU Script consists of RMU Script language statements (collectively a script program) that manipulate the input and formats the output document.

The script program is prepared with the ISPF editor in a PDS, as a regular text file. The program must be compiled with the RMU Script compiler and linked as a load module, or linked and executed (run as "link and go"), depending on the JCL used.

The RMU Script compiler translates script statements to COBOL; therefore a z/OS COBOL or LE COBOL compiler is required.

An RMU Script program consists of 10 optional sections as shown here. You must supply at least one section to make it a valid program.

Environment section	The PARM statement with its options. If coded, PARM must be the first statement in the program.
Working Storage section	Defines the fields and variables used in the Activity section.
<style> section	Defines the Cascaded Style Sheets (color, fonts, and so on).
<object> section	Defines the images to be inserted in the output document.
<docs_top> section	Defines the images and text to be inserted at the top of output document.
<docs_end> section	Defines the images and text to be inserted at the bottom of output document.
<page_top> section	Defines the images and text to be inserted at the top of each page in the output document.
<page_end> section	Defines the images and text to be inserted at the bottom of each page in the output document.
Activity section	Contains the language statements that filter the input and construct the output documents.
Control section	Defines control breaks for HTML1 format documents.

I/O handling

Files cannot be defined in RMU Script. I/O is completely concealed from you. One input report and one output document are assumed.

RMU Script activity statements operate on the page buffer. RMU reads in one report page at the time. In this way, all lines on a single page can be accessed as a single resource. Each page contains up to 66 lines. The activity statements are executed from top to bottom as coded in the program.

The report page begins with Channel 1. That is, a "1" in the first position is Channel 1. If there are more than 66 lines on each page, the remaining lines are drained to the output document unchanged. The activity logic is not applied to the remaining lines.

Information on each line is accessed by explicitly coding the line number with substring notation. For example, LINE1 is line 1, LINE2 is line 2 ... LINE66 is line 66. This example evaluates line 1 starting in position 3 for 5 bytes:

```
IF LINE1 (3: 5) = 'abcde'
```

If the line number is not specified, then a subscript named IDX is used to subscript the lines. IDX is a reserved variable, but it can be assigned to a desired line number to be accessed.

Note: The input report must be a valid printer file with the print control character in position 1. RMU expands print control characters to compensate for the blank lines that would normally be seen on a printed report. Therefore, when referring to a specific line by number, the line number is as according to the expanded report.

These are recognized control characters:

1	Channel 1.
(blank)	Space 1.
0	Space 2.
-	Space 3.
+	Suppress space (for RMU, this is the same as space 1).

When coding a Script program, run the FZHDELCJ utility to expand the report control characters. This will help to identify the line numbers of interest. The FZHDELCJ JCL is located in the &SYS1.SFZHJCLS library.

Coding rules

These coding rules apply:

- RMU Script statements can be placed anywhere between columns 1 and 72. Only one statement is allowed on a line. Statements are followed by respective arguments.
- The arguments are separated by one or more spaces.
- Lines that begin with an asterisk (*) are treated as comments.
- Comments can be imbedded anywhere in the program.
- Alphanumeric constant values (literal) are enclosed in quotes. For example:
'abcd'
- A hex literal is coded by placing an X before the hex constant. For example:
X'1234'
- A hex literal must contain a combination of valid hex characters: 0–9, A–F.
- Numeric constant values are coded as numbers with a leading plus or minus sign and, if necessary, a decimal point. Numbers without a sign are treated as positive numbers. For example, -123.55 is a negative number.

Program example

The program shown in Figure 3 reads in the FZHRPT00 test report located in the &SYS1.SFZHJCLS library and produces an HTML1-format document with a control breaks tree on the left side and the report body on the right side of the screen.

The background of the output document simulates 1403 printer paper.

A page break image, fzhpages.gif, is inserted at the top of each page.

When LINE8-LINE55 contains 'DDDD' in position 24 for 4, the value is made red (.em1). When LINE8-LINE55 contains 'EBEE' in position 24 for 4, the value is made blue (.em2).

PARM LIST COBOL LKED FORMAT HTML1 TURF 1403-paper	Environment Section

* This program converts a report to RMU HTML1 format.	* Comments
* Some decorating is inserted via styles and objects.	*

DEFINE COMPANY W 2 A	Working Storage Section
DEFINE BRANCH W 5 A	
DEFINE OFFICER W 4 A	
<style>	
.em1 {color: red;}	Style Section
.em2 {color: blue;}	
</style>	
<page_top>	page_top Section
<IMAGE SRC="images/fzhpages.gif">	
</page_top>	
IF (LINE5 (2: 7) = 'COMPANY')	
AND (LINE5 (13: 6) = 'BRANCH')	
AND (LINE8 (4: 2) IS NUMERIC)	Activity
COMPANY = LINE8 (4: 2)	
BRANCH = LINE8 (14: 3)	
OFFICER = LINE8 (24: 4)	
EVALUATE LINE8-LINE55 (24: 4)	Section
WHEN 'DDDD'	
LINE (24: 4) = .em1	
WHEN 'EBEE'	
LINE (24: 4) = .em2	
END-EVALUATE	
END-IF	
CONTROL COMPANY BRANCH OFFICER	Control Section

Figure 3. Example of RMU script program to produce an HTML1 format document

Figure 4 on page 20 shows a screen print of the generated HTML1 document:

[illegible]

Creating CSV documents

When creating a CSV document, extraneous information such as page titles, field headings, and control break annotations must be removed from the input.

Additionally, you may want to remove float characters from the numeric fields and re-arrange the sign such that the spreadsheet program can intelligently format numeric cells.

Finally, you need to insert a special character between each field to delineate columns for import.

RMU provides methods and statements specifically designed to make these tasks simple.

- To create a CSV file, code `FORMAT CSV='&chr'` on the `PARM` statement where: `&chr` is the separator character to be placed between the fields.
- Use these RMU methods in the assign statement to format column values:
 - `.ETEXT` For alphanumeric fields.
 - `.ENUM1` For numeric and numeric edited fields.
- Use `PAGE-COUNT` and `LINE-COUNT` to determine the page properties.
- Use the `BYPASS` statement to remove a specific line or a range of lines.
- Use the `IDX` subscript to control a `DO` loop for a specific number of lines.

The line is selected for output if at least one method is applied, otherwise the line is bypassed.

Note: CSS (color, fonts, and so on) and images cannot be applied to a CSV file.

The RMU Script program shown in Figure 5 on page 22 creates a CSV file from the `FZHRPT00` report located in `&SYS1.SFZHJCLS`. The source code is `FZHTST4` located in the `&SYS1.SFZHJCLS` library.

Creating CSV documents

```
PARM LIST COBOL LKED FORMAT CSV=':' DECIMAL (PERIOD) CURRENCY($)
*****
* This program converts test report to RMU CSV file format.          *
*                                                                    *
* The program demonstrates how to trim un-needed report lines and  *
* strings from a report. The output is a CSV file ready for import  *
* into a Spreadsheet.                                              *
*                                                                    *
* The trimming is done via the .ETEXT and .ENUM1 RMU methods       *
*****
IF (PAGE-COUNT > 1)
* REPORT TITLES ARE BYPASSED ON ALL BUT FIRST PAGE.
  BYPASS LINE1-LINE7
ELSE
* PRESERVE THE FIRST PAGE TITLE LINES FOR spreadsheet
  LINE1 (2: 80) = .ETEXT
  IDX = 1
  DO 6 TIMES
    IDX = (IDX + 1)
    LINE (02: 07) = .ETEXT
    LINE (13: 06) = .ETEXT
    LINE (23: 07) = .ETEXT
    LINE (34: 14) = .ETEXT
    LINE (52: 06) = .ETEXT
    LINE (62: 10) = .ETEXT
  END-DO
END-IF
IDX = 7
  * Line 8 to LINE-COUNT are detail lines on every page
DO WHILE (IDX < LINE-COUNT)
  IDX = (IDX + 1)
  * get rid of Control break and FINAL lines
  IF (LINE (2: 5) = 'FINAL')
    OR (LINE (2: 6) = 'FILEIN')
    OR (LINE (24: 4) = SPACES)
    BYPASS LINE
  ELSE
  * construct a row of character separated values
    LINE (02: 07) = .ETEXT
    LINE (13: 06) = .ETEXT
    LINE (23: 07) = .ETEXT
    LINE (34: 14) = .ENUM1
    LINE (52: 06) = .ENUM1
    LINE (62: 10) = .ENUM1
  END-IF
END-DO
```

Figure 5. Example of RMU script program to create a CSV file

Figure 6 on page 23 shows the first few records created by the program in Figure 5:

```

4/08/08      COMPANY= 10  THIS IS A TEST REPORT-1                PAGE      1
:           :           :           :           :           :
:           :           :           :           :           :
:           :           :           :           :           :
COMPANY : BRANCH : OFFICER :           :           :           :
C       : NUMBER : NUMBER  : WAGE      : RATE     : BONUS     :
:       :       :         :           :           :           :
10      : 001   : DDDD   : 57500.00  : 10.900   : 6267      :
:       :       : EBEE   : 60000.00  : 11.000   : 6600      :
:       :       : EBEE   : 60000.00  : 11.000   : 6600      :
:       :       : EBEE   : 60000.00  : 11.000   : 6600      :
:       :       : EBEE   : 60000.00  : 11.000   : 6600      :
:       :       : EBEE   : 60000.00  : 11.000   : 6600      :

```

Figure 6. Records created by the example program shown

Creating simple HTML documents

A simple-HTML format document can be created without the use of RMU Script. To do this, use the FZHRMUJ0 JCL located in the &SYS1.SFZJHCLS library.

You can create a simple HTML document with special decorating if needed, such as special colors, fonts and images, as outlined in this section:

- Code FORMAT HTML on the PARM statement.
- Optionally, code <style>, <object>, <docs_top>, < docs_end>, <page_top> and <page_end> sections to define decorating. Use <style> and <object> methods to decorate text. You do so by assigning method names to line text in the Activity section.

Note: Images are not automatically included in the output document; therefore, if images are used, they must be available on the server where you place the document.

- Use PAGE-COUNT and LINE-COUNT to determine the page properties.
- Use the BYPASS statement to remove a specific line or a range of lines.
- Use the IDX subscript to control a DO loop for a specific number of lines.
- Use the EVALUATE statement to loop through a range of lines when a specific location on multiple lines is to be decorated with different methods.

The RMU Script program shown in Figure 7 creates a simple HTML document from the FZHRPT00 report located in the &SYS1.SFZJHCLS library. The source code is in FZHTTEST1 located in the &SYS1.SFZJHCLS library.

```
PARM LIST COBOL LKED FORMAT HTML turf 1403-paper
*****
* This program converts test report to RMU HTML format.          *
* Some decorating is inserted via style and object methods.      *
*****
<style>
  .em1 {color: red; font-weight: normal;}
  .em2 {color: blue;}
  .em3 {color: orange;}
</style>
<page_top>
<IMAGE SRC="images/fzhpages.gif">
</page_top>
IDX = 1
IF (LINE5 (2: 7) = 'COMPANY')
AND (LINE5 (13: 6) = 'BRANCH')
AND (LINE8 (4: 2) IS NUMERIC)
  EVALUATE LINE8-LINE55 (24: 4)
    WHEN 'ZZZZ'
      LINE (1: 80) = .EM1
    WHEN 'EBEE'
      LINE (24: 4) = .EM2
    WHEN OTHER
      LINE (24: 4) = .EM3
  END-EVALUATE
END-IF
```

Figure 7. Example of RMU script program to create a simple HTML document

Figure 8 on page 25 shows a screen print of the generated HTML document:




Figure 8. Screen print of the generated HTML1 document

Creating HTML1 documents with the control breaks selection tree

To create an HTML1-format document with special decorating such as special colors, fonts and images, create an RMU Script as outlined in this section:

- Code `FORMAT HTML1` on the `PARM` statement.
- Use the `DEFINE` statement to define working storage fields for control breaks and other needs.
- Optionally, code `<style>`, `<object>`, `<docs_top>`, `<docs_end>`, `<page_top>` and `<page_end>` sections to define decorating. Use `<style>` and `<object>` methods to decorate text. To do this, you assign method names to line text in the Activity section.

Note: Images are automatically included in the output document if located in the FJIDOC0 library.

- Optionally use `PAGE-COUNT` and `LINE-COUNT` to determine the page properties.
- Optionally use the `BYPASS` statement to remove a specific line or a range of lines.
- Optionally use the `IDX` subscript to control a `DO` loop for a specific number of lines.
- Optionally use the `EVALUATE` statement to loop through a range of lines when a specific location on multiple lines is to be decorated with different methods.
- Use the `CONTROL` statement to declare control break fields. Note that this is a required statement.

Control break fields must be carefully populated from the supplied information in each page. You will probably have to test lines for certain values, such as field titles to make sure that the correct values are used. See Figure 9 on page 27.

The program shown in Figure 9 on page 27 reads in the FZHRPT00 test report located in the `&SYS1.SFZHJCLS` library and produces an HTML1 format document with a control breaks tree on the left side and the report body on the right side of the screen. The source code is in FZHTEST2 located in the `&SYS1.SFZHJCLS` library.

The background of the output document simulates 1403 printer paper. A page break image, `fzhpages.gif`, is inserted at the top of each page.

When `LINE8-LINE55` contains 'DDDD' in position 24 for 4, the value is made red (.em1). When `LINE8-LINE55` contains 'EBEE' in position 24 for 4, the value is made blue (.em2).

```

PARM LIST COBOL LKED FORMAT HTML1 TURF 1403-paper
*****
* This program converts a report to RMU HTML1 format.          *
* Some decorating is inserted via styles and objects.          *
*****
DEFINE COMPANY W 2 A
DEFINE BRANCH W 5 A
DEFINE OFFICER W 4 A
<style>
  .em1 {color: red;}
  .em2 {color: blue;}
</style>
<page_top>
<IMAGE SRC="images/fzhpages.gif">
</page_top>
IF (LINE5 (2: 7) = 'COMPANY')
AND (LINE5 (13: 6) = 'BRANCH')
AND (LINE8 (4: 2) IS NUMERIC)
  COMPANY = LINE8 (4: 2)
  BRANCH = LINE8 (14: 3)
  OFFICER = LINE8 (24: 4)
  EVALUATE LINE8-LINE55 (24: 4)
    WHEN 'DDDD'
      LINE (24: 4) = .em1
    WHEN 'EBEE'
      LINE (24: 4) = .em2
  END-EVALUATE
END-IF
CONTROL COMPANY BRANCH OFFICER

```

Figure 9. Example of RMU script program to produce an HTML1 format document

Figure 10 on page 28 shows a screen print of the generated HTML1 document:

Creating HTML1 documents with the control breaks selection tree




Figure 10. Screen print of the generated HTML1 document

Decorating an HTML document

The output document can be decorated in three ways:

- **Images and special text can be created at the top of the document, the bottom of the document, the top of each page, and the bottom of each page.**

File types recognized as images by RMU files are: JPG, TIF, PSD, PDD, BMP, PNG, and GIF.

To do this, you code valid HTML between these tags:

<docs_top> </docs_top>

This optional section defines the images and text to be inserted at the top of the document.

<docs_end> </docs_end>

This optional section defines the images and text to be inserted at the bottom of the document.

<page_top> </page_top>

This optional section defines the images and text to be inserted at the top of each page.

<page_end> </page_end>

This optional section defines the images and text to be inserted at the bottom of each page.

RMU uses <pre> and </pre> HTML tags to preserve the original document format, including spacing and blank lines. These tags tell HTML to leave the text pre-set as it is. Therefore when coding text, you can type the text without the special tags, or you can put the text between the </pre> and <pre> tags to resume standard default HTML formatting.

This example shows both lines at the top of the document:

```
<docs_top>
  RMU generated document
  as of 11/15/2008
</docs_top>
```

This example shows text as a single line at the top of the document:

```
<docs_top>
  </pre>
  RMU generated document
  as of 11/15/2008
  <pre>
</docs_top>
```

Images included in the HTML text placed between the tags are automatically resolved by RMU if they exist in the FJIDOC0 library.

For example, the code shown here causes the xyzimag1 and gif file to be included in the document from the FJIDOC0 file because of SRC="images/xyzimag1.gif":

```
<docs_top>
  <IMAGE SRC="images/xyzimag1.gif">
  RMU generated document as of 11/15/2008
</docs_top>
```

RMU does not validate any information included between the tags. Errors are discovered when you browse the document.

These images are available in the &SYS1.SFZHDOCS library:

FZHMINUS	Minus sign.
FZHPAGES	Page break line.
FZHPLUS0	Plus sign.
FZHRARRW	Arrow.

Decorating an HTML document

FZHRMUL0 RMU logo.
FZHSTOP0 Stop sign.

- **Special fonts and colors can be applied to line text conditionally.**

The best way of doing this is to declare styles (CSS) in the <style> section and then assign the styles to the text in question on each line.

You can choose to highlight special text. For example, title lines can be made a different color, negative amounts can be turned red, and so on.

Changing the font size is not recommended as it may cause text alignment problems.

Note: When declaring a style in the <style> section, the style parameters are not validated. Errors are discovered when you browse the document.

In this example, the DDDD value on line 8 through line 55 starting in position 24 is made red and EBEE is made blue:

```
<style>
  .em1 {color: red;}
  .em2 {color: blue;}
</style>
EVALUATE LINE8-LINE55 (24: 4)
  WHEN 'DDDD'
    LINE (24: 4) = .em1
  WHEN 'EBEE'
    LINE (24: 4) = .em2
END-EVALUATE
```

Likewise, the IF statement can be used to do the same.

- **Simulated 1403 printer paper background turf is the default.**

The turf can be turned off by specifying TURF NO on the PARM statement at the top of the script program. The default background color will be as defined for the body in the FZHEBCSS member located in the &SYS1.SFZHDOCS library. You can override the default by adding your own body CSS in the <style> section.

Example:

```
PARM TURF NO
<style>
  body {color: black; Background-color: white; font-size: &size%;}
</style>
```

Debugging RMU Script programs

RMU generates COBOL programs that are compiled with standard IBM® COBOL, therefore any runtime problems that you experience are as for any other non-RMU COBOL programs.

Compile RMU Script with the PROCESS LIST,MAP COBOL options. A PROCESS statement can be placed before the PARM statement. Note that multiple PROCESS statements can be coded.

The RMU-generated COBOL contains statement sequence numbers in columns 1 to 6.

There are 3 types of sequence numbers:

#nnnnnn	Statement is generated according to the nnnnnn RMU script statement number.
#BASE	Statement is generated from the COBOL skeleton.

#EOF Statement is generated after the last RMU Script statement is processed.

COBOL runtime problems fall into one of these categories:

- **File I/O errors**

File problems such as wrong LRECL, or no DD in the JCL. RMU intercepts I/O errors and issues an appropriate message. Look at the console and SYSOUT messages for more information.

- **Environmental errors and ABENDs**

Errors associated with such things as JCL issues, RACF®/security problems, and memory problems. Such problems are intercepted and logged by the operating system. In most instances, the job is canceled by the operating system with an appropriate message. Look at the console and SYSOUT messages for more information.

- **Program check interrupts**

Processing problems such as an addressing exception, data exception, or specification exception.

To locate the RMU Script program statement in error:

1. If you have a COBOL debugger, use the debugger report to find the COBOL statement in error.
2. If you do not have a debugger:
 - In the Log or Dump file, find the hex offset of the PSW in your program as displayed by the Operating System.
 - Perform a find on the offset address in your COBOL compiler listing (expanded Assembler listing).
 - The COBOL source statement or line number can be found in the area before the offset.
 - Look at the COBOL listing identified by the line number in error.
3. The RMU Script statement number is in columns 1-6.
 - If #nnnnn is shown, this is the RMU Script statement in error.
 - If '#EOF' or '#BASE' is shown, look backward at statement numbers until you find a #nnnnn or a paragraph name (whichever you find first).
 - For a paragraph name, trace back to the perform statement to locate the routine that invoked it, then repeat the previous step.
4. Determine the cause of the program check interrupt from the located statement. If a protection exception occurred, check for bad subscripts. If a data exception occurred, check for non-numeric data in arithmetic operations.


Chapter 5. RMU Script language instruction reference

This section lists program instructions, syntax, further explanation, and examples, for each instruction supported by RMU.

PARM statement

The PARM statement defines the RMU Script language compiler options. These options override the defaults in the FZHOPTAB options table.

Syntax



Note: Options are coded on the same line following the PARM keyword. If all options do not fit on a single line, multiple PARM lines can be coded as needed.

Parameters

<i>&name</i>	Program name 1 to 8 characters long. The name must be a valid COBOL program name. The default is NONAME.
<i>&format</i>	Type of output. Valid values are: HTML0 Output is simple HTML format. HTML1 Output is HTML format with a directory of control break fields on the left. CSV='&char' Output is a CSV file, where <i>&char</i> is the value separator character for CSV files.
1403-paper	Simulate green-striped 1403 printer paper background.
NO	Use gray background color.
<i>&decimal</i>	Decimal point character. Valid values are: PERIOD Use '.' for decimal point. COMMA Use ',' for decimal point.
<i>&currency</i>	Character to be used as currency symbol.

PARM statement

Examples

```


PARM LIST COBOL LKED FORMAT HTML1 TURF 1403-paper
PARM LINK FZHTST0 LIST COBOL LKED FORMAT HTML1 TURF 1403-paper

```

DEFINE statement

The DEFINE statement defines the RMU Script program variables and field names to be used within the program.

Syntax



Parameters

&field Variable name 1 to 16 characters long. The name must begin with an alpha character. The name can be composed of letters, numbers, and a minus sign ('-').

Example of valid names:

WS-BALANCE
WS-AMOUNT

&length	Field length in bytes. Maximum length for N fields is 18. Maximum length for P fields is 9. Maximum length for alpha fields is 32767.
--------------------	--

<i>&type</i>	Field type. Valid values are:
------------------	-------------------------------

N Unsigned numeric display integer.

A Alphanumeric.

B Signed binary integer, 2- or 4-byte binary integer.

P Signed packed decimal number.

<i>&value</i>	Initial value. An alpha value must be enclosed in quotes, a numeric value must not exceed the field length.
-------------------	---

These reserved values can be coded:

SPACES or SPACE

ZEROS or ZEROES or ZERO

LOW-VALUES or LOW-VALUE

HIGH-VALUES or HIGH-VALUE

Programming notes

RMU does not support decimal places at this time.

Examples of field definitions

```

DEFINE WX-WORK W 10 A
DEFINE WX-NUM W 5 N
DEFINE WX-PACK W 5 P
DEFINE WX-BIN2 W 2 B
DEFINE WX-BIN4 W 4 B

```

```

DEFINE WS-WORK W 10 A VALUE 'ABCDEF'
DEFINE WS-NUM W 5 N VALUE 12345
DEFINE WS-PACK W 5 P VALUE +123456789
DEFINE WS-BIN2 W 2 B VALUE 1234
DEFINE WS-BIN4 W 4 B VALUE 123456789

```

<object> and </object> tag

The <object> tag declares the beginning of object and image definitions to be inserted in the output document. The object section begins with the <object> tag and terminates with the </object> tag. One or more images can be declared between the tags.

```

<object>
  .im&mod {<IMAGE SRC="images/&image.gif">}
  :
  :
</object>

```

Parameters

<i>&mod</i>	Image name modifier. The name is composed of .im&mod. For example, when &mod is "g1", the name is .img1. This name is referenced in the assign statement within the RMU Script program.
<i>&image</i>	The image file name as found in the FJIDOC0 library. For example, fzhpages and fzhplus0 are gif files located in the &SYS1.SFZHD0CS default FJIDOC0 library. To declare these two gif files for use in an RMU Script program, use the code: <pre> <object> .img1 {<IMAGE SRC="images/fzhpages.gif">} .img2 {<IMAGE SRC="images/fzhplus0.gif">} </object> </pre>

Programming notes

When the output is directed to z/OS UNIX, images are copied from the &SYS1.SFZHD0CS file in binary format to the r001\images directory.

When the output is directed to the z/OS flat file for download to a PC or a server, images are included in the download document and parsed on the target PC or server with the FZHBPARS Java utility.

Images are assigned to a specific location in the document. Unresolved images are ignored.

Example:

```
LINE1 (10: 0) = .img1
```

Inserts img1 before position 10 on line 1.

<style> and </style> tag

The <style> tag declares the beginning of Cascaded Style Sheets (CSS) to be applied to the output text. The style section begins with the <style> tag and terminates with the </style> tag. One or more styles can be declared between the tags.

There are three distinct styles that can be declared:

<style> and </style> tag

- Style for document body.
- Colors for .turf1 and .turf2 alternated to simulate 1403 green-striped printer paper.
- Styles for highlighting and decorating text (element styles).

```
<style>
  body {color: &color; Background-color: &color; font-size: &size%;}
  .turf1 {Background-color: &color}
  .turf2 {Background-color: &color}
  .em&n {color: &color;}
:
</style>
```

Parameters

<i>&color</i>	A valid HTML color.
<i>&size</i>	Font size as an absolute size or percentage.
<i>&n</i>	Element name modifier.

Programming notes

All styles are optional.

Body and Element styles can include any combination of values acceptable to HTML. The content enclosed in { } is not validated by MU, therefore special care must be taken to make sure that the specified options are correct. Once defined, the body style is automatically applied to the document body.

.turf1 and .turf2 are special element styles for simulating 1403 printer paper. Color is the only acceptable option. These options are used automatically when the 1403-paper option is in effect. .turf1 and .turf2 colors are alternated to simulate 1403 printer paper.

.em&n styles are for decorating report text. Once defined, .em&n styles can be assigned to specific fields in the document. For example, negative amounts can be turned red and so on. One or more element styles can be defined.

Examples

```
<style>
  body {color: green; Background-color: light-gray; font-size: 100%;}
  .turf1 {Background-color: ccfff1}
  .turf2 {Background-color: 99fff1}
  .em1 {color: red;}
  .em2 {color: blue;}
</style>
```

<docs_top> and </docs_top> tag

The <docs_top> tag declares the beginning of the text and the images to be inserted at the top of the output document. The docs_top section begins with the <docs_top> tag and terminates with the </docs_top> tag.

You must code valid HTML strings between the tags. The content between the tags is placed at the top of the document without validation. Errors are not discovered until the document is browsed.

```
<docs_top>
:
</docs_top>
```

Parameters

None.

Programming notes

Images included in the HTML text placed between the tags are automatically resolved by RMU if they exist in FJIDOC0 library.

For example, the code shown here causes the xyzimag1 and xyzimag2 gif files to be included in the document from the FJIDOC0 file:

```
<docs_top>
  <IMAGE SRC="images/xyzimag1.gif">
  <IMAGE SRC="images/xyzimag2.gif">
</docs_top>
```

<docs_end> and </docs_end> tag

The <docs_end> tag declares the beginning of the text and images to be inserted at the bottom of the output document. The docs_end section begins with the <docs_end> tag and terminates with the </docs_end> tag.

You must code valid HTML strings between the tags. The content between the tags is placed at the bottom of the document without validation. Errors are not discovered until the document is browsed.

```
<docs_end>
:
</docs_end>
```

Parameters

None.

Programming notes

Images included in the HTML text placed between the tags are automatically resolved by RMU if they exist in FJIDOC0 library.

For example, the code shown here causes the xyzimag1 and xyzimag2 gif files to be included in the document from the FJIDOC0 file:

```
<docs_end>
  <IMAGE SRC="images/xyzimag1.gif">
  <IMAGE SRC="images/xyzimag2.gif">
</docs_end>
```

<page_top> and </page_top> tag

The <page_top> tag declares the beginning of the text and images to be inserted at the top of each page in the output document. The page_top section begins with the <page_top> tag and terminates with the </page_top> tag.

You must code valid HTML strings between the tags. The content between the tags is placed at the top of each page in the document without validation. Errors are not discovered until the document is browsed.

<page_top> and </page_top> tag

```
<page_top>
:
</page_top>
```

Parameters

None.

Programming notes

Images included in the HTML text placed between the tags are automatically resolved by RMU if they exist in FJIDOC0 library.

For example, the code shown here causes the xyzimag1 and xyzimag2 gif files to be included in the document from the FJIDOC0 file:

```
<page_top>
  <IMAGE SRC="images/xyzimag1.gif">
  <IMAGE SRC="images/xyzimag2.gif">
</page_top>
```

<page_end> and </page_end> tag

The <page_end> tag declares the beginning of the text and images to be inserted at the bottom of each page in the output document. The page_end section begins with the <page_end> tag and terminates with the </page_end> tag.

You must code valid HTML strings between the tags. The content between the tags is placed at the bottom of each page in the document without validation. Errors are not discovered until the document is browsed.

```
<page_end>
:
</page_end>
```

Parameters

None.

Programming notes

Images included in the HTML text placed between the tags are automatically resolved by RMU if they exist in FJIDOC0 library.

For example, the code shown here causes the xyzimag1 and xyzimag2 gif files to be included in the document from the FJIDOC0 file:

```
<page_end>
  <IMAGE SRC="images/xyzimag1.gif">
  <IMAGE SRC="images/xyzimag2.gif">
</page_end>
```

Assignment statement

The assignment statement assigns a value to a field. The value can be another field, a literal, a style, a method, an image, or an arithmetic expression.

There are four types of assignment statements:

Normal assignment

Assigns field values and arithmetic outcomes to a field.

Style assignment to a line or a part of a line

Assigns fonts and colors (CSS) for decorating line text. The style to be inserted must be defined in the <style> section.


Method assignment to line text (columns) when creating CSV files

De-edits numeric values and prepares line text for spreadsheet use.

Object assignment to a line or line text

Inserts objects (images) in a specific position on the report line. The objects to be inserted must be defined in the <object> section.

Format 1 Assignment



Parameters:


<i>&recfield</i>	Specifies the field name to which the value will be assigned.
<i>&start</i>	Starting position.
<i>&length</i>	Length to be moved.
equal sign (=)	Indicates assignment.
<i>&sendfield</i>	Sending field (field to be copied).
<i>&sendlit</i>	Sending value can be a literal. An alphanumeric literal must be enclosed in quotes.
<i>&formula</i>	Arithmetic expression. It can contain arithmetic operators (+, -, *, /). The outcome of the calculation is placed in the <i>&recfield</i> .

Examples:

```

WS-COMPANY = LINE5 (5: 4)
WS-COMPANY = '1234'
WS-COMPANY = '1234567890 (3:4)
WS-INTEGER = (WS-INTEGER + 1)
  
```

Format 2 Assignment



Parameters:

Assignment statement

<i>&line</i>	Specifies the line to which the value will be assigned.
<i>&start</i>	Starting position.
<i>&length</i>	Text length <i>&style</i> applies to.
equal sign (=)	Indicates assignment.
<i>&style</i>	A style name as declared in the <style> section.

Example:

LINE10 (15:6) = .em1

Format 3 Assignment

Syntax

►► *&line* ————— = — *.ETEXT* —————►
 └──(*&start*:*&length*)──┘ └──.ENUM1──┘

Parameters:

<i>&line</i>	Specifies the line to which the value will be assigned.
equal sign (=)	Indicates assignment.
<i>&start</i>	Starting position.
<i>&length</i>	Text length <i>&style</i> applies to.
.ETEXT	Create plain text field.
.ENUM1	De-edit numeric field.

Examples:

LINE10 (15:6) = .ETEXT
LINE10 (15:6) = .ENUM1

Format 4 Assignment

Syntax

►► *&line* ————— = — *&image* —————►
 └──(*&start*:0)──┘

Parameters:

<i>&line</i>	Specifies the line to which the value will be assigned.
equal sign (=)	Indicates assignment.
<i>&start</i>	Starting position. It can be: <ul style="list-style-type: none">• An absolute number.• A numeric field.• The word "BEFORE" for placing the image before the line.

&image An image name as declared in the <object> section.

Programming notes:

- An image can be inserted before a line or on a line before text. Use the (BEFORE: 0) substring notation to place the image before a line.
- Images placed on a line before text push the line text to the right and may cause column alignment problems.

Examples:

This example places .imag1 on line 10 before position 15:


```
LINE10 (15: 0) = .imag1
```

This example places .imag1 before line 5:

```
LINE5 (BEFORE: 0) = .imag1
```

BYPASS statement

The BYPASS statement tags specific lines or a range of lines for deletion. That is, the bypassed lines are excluded from the output document.



Parameters

LINE	The line number contained in the IDX subscript is bypassed.
&LINE_n	Line number to bypass.
&LINE_{n1}	Low line number of range of lines to bypass.
&LINE_{n2}	High line number of range of lines to bypass.

Examples

This example bypasses line 2:

```
IDX = 2
BYPASS LINE
```

This example bypasses line 4:

```
BYPASS LINE4
```

This example bypasses line 1 through line 10:

```
BYPASS LINE1-LINE10
```

Programming notes

The BYPASS statement is convenient for stripping unneeded report lines from the output document, especially when creating CSV files. For example, running page titles and field headings are not needed in a spreadsheet. Report title lines and heading lines can be conditionally or unconditionally excluded from the output CSV file.


BYPASS statement

The use of BYPASS is not limited to CSV format files. It can also be used to bypass report lines when creating HTML and HTML1 format documents.

CALL statement

The CALL statement makes a call to a user-written program. The user-written program can be written in COBOL, BAL, or any other language that honors standard linkage conventions.

Syntax



Parameters

&program

The program name. This can be:

- A hard-coded program name enclosed in quotes. In this case, it is a static call. That is, the program is included from the SYSLIB at link time.
- A field name that contains the program name. In this case, it is a dynamic call. The program must exist in the JOBLIB/STEPLIB at run time.

&field

Field name as declared in the Library section.


Programming notes

CALL *&program* USING *&field* must be coded on a single line. Additional fields can be coded on the same line or subsequent lines.

CONTINUE statement

The CONTINUE statement is used in combination with the IF statement. It alters the processing logic to after the END-IF statement.

Syntax



Parameters

None.

Examples


```
IF LINE1 (3: 4) = '1234'  
  CONTINUE  
ELSE  
  processing statements  
END-IF
```

CONTROL statement


The CONTROL statement declares control break fields for an HTML1 format document. A selection tree is built on the left side of HTML1 format document in the hierarchy specified on the CONTROL statement.

There are two CONTROL statement formats:

Format 1 Use this format when all fields can be listed on a single line.



Format 2 Use this format when fields cannot be listed on a single line. The list begins with an open parenthesis and ends with a closed parenthesis. The list can span over multiple lines.



Parameters

&field Field name as declared in the Library section.

Programming notes

Reports normally consist of title lines, field headings, detail lines, and control break totals. That is, reports follow a hierarchy as enforced in the programs that create them.

To create a selection tree such that you can navigate directly to a specific page where a new control starts, you must first define fields and variables to hold control break information.

Then, in the Activity section, the fields are populated by control field values from specific positions in the page lines. When populating fields, care must be taken to use the correct position and length where a control break value is printed. This is usually achieved by testing for a specific literal or data type in specific locations on one or more lines of each page.

CONTROL statement

Finally, control breaks are declared by the CONTROL statement. The first listed field is the highest break, followed by the subsequent fields as secondary breaks.


Examples

```
DEFINE COMPANY W 2 A
DEFINE BRANCH W 5 A
DEFINE OFFICER W 4 A
IF (LINE5 (2: 7) = 'COMPANY')
AND (LINE5 (13: 6) = 'BRANCH')
AND (LINE8 (4: 2) IS NUMERIC)
COMPANY = LINE8 (4: 2)
BRANCH = LINE8 (14: 3)
OFFICER = LINE8 (24: 4)
END-IF
CONTROL COMPANY BRANCH OFFICER
```

DISPLAY statement

The DISPLAY statement prints fields, lines, or a literal to SYSOUT.

Syntax



Parameters

<i>&field</i>	Field name, literal, or line.
<i>&start</i>	Starting position.
<i>&length</i>	Text length.

Examples

```
DISPLAY 'COMPANY: ' COMPANY 'BRANCH: ' LINE1 (5: 4)
```


Programming notes

DISPLAY fields can be listed on multiple lines as needed. All packed decimal and binary fields are converted to numeric display format. The sign is not removed.

DO and END-DO statements

The DO and END-DO statements define the scope of repetitive program logic.

Syntax



Parameters

WHILE	Evaluates the condition expression, <i>&condition</i> , at the top of a group of statements.
UNTIL	Evaluates the condition expression, <i>&condition</i> , at the bottom of a group of statements.
<i>&condition</i>	Specifies the condition expression for the continuous execution of the loop. See “IF, ELSE, and END-IF statements” on page 47 for the conditional expression syntax.
<i>&count</i>	The loop counter or limit. The maximum value is 2147483647. <i>&count</i> must be a numeric field or a positive number.
END-DO	Terminates the DO statement.

Programming notes

For DO WHILE, the truth value of the conditional expression, *&condition*, determines whether statements bound by the DO and END-DO pair are to be executed. When the conditional expression is true, the statements are executed. When the conditional expression is false, the processing continues with the next statement following the END-DO.

For DO UNTIL, the statements bound by the DO and END-DO pair are executed. The truth value of the conditional expression, *&condition* (evaluated at the end of the statements), determines whether statements bound by the DO and END-DO pair are to be executed again. When the conditional expression is true, the statements are executed again. When the conditional expression is false, the processing continues with the next statement following the END-DO.

For DO *&count* TIMES, the statements bound by the DO and END-DO pair are executed *&count* times unconditionally.

Examples

```


DEFINE WS-COUNT W B 2 VALUE ZERO
DO UNTIL (WS-COUNT = 6)
    WS-COUNT= (WS-COUNT + 1)
    DISPLAY 'LOOP COUNT OF 6'
END-DO
DO 6 TIMES
    DISPLAY 'LOOP COUNT OF 6'
END-DO

```

EVALUATE and END-EVALUATE statements

The EVALUATE statement provides an elegant way of testing for values.

Syntax



Parameters

<i>&field</i>	The field name to be evaluated.
<i>linex</i> — <i>liney</i>	Range of lines to evaluate, where <i>linex</i> is the low line number and <i>liney</i> is the high line number. <i>linex</i> must be greater than zero and less or equal to <i>liney</i> . <i>liney</i> must be greater than zero and less or equal to LINE-COUNT.
<i>&start</i>	Starting position.
<i>&length</i>	Text length.
<i>&condition</i>	Value to be tested for. It must be a literal or a field with the same data type as <i>&field</i> .
OTHER	Must be the last statement after a series of tests. The statements following OTHER are executed only when all previous tests fail.
END-EVALUATE	Terminates the EVALUATE statement.

Programming notes

When a line range is specified, the reserved field IDX is initialized to *linex* and EVALUATE statements are processed in a loop incrementing IDX by 1 until all lines in the specified range are tested. Up to 8 nested EVALUATE statements are permitted.

Examples


```

EVALUATE LINE8-LINE55 (24: 4)
  WHEN 'DDDD'
    LINE (24: 4) = .EM1
  WHEN 'EBEE'
    LINE (24: 4) = .EM2
  WHEN OTHER
    LINE (24: 4) = .EM3
END-EVALUATE
  
```

IF, ELSE, and END-IF statements

The IF statement conditionally controls execution of the statements bound by the IF and END-IF statements.

Syntax



Parameters

<i>&expression</i>	Conditional expression. It can contain AND, OR, and arithmetic terms.
<i>statements_1</i>	The statements executed if <i>&expression</i> is evaluated to be true.
<i>statements_2</i>	The statements executed if <i>&expression</i> is evaluated to be false. If ELSE is not specified, then no statements are executed.
END-IF	Terminates the logic associated with the previous IF statement.

Programming notes

&expression must be enclosed in parentheses. Multiple expressions can be coded, each starting on a separate line and connected with an AND or an OR logical operator.

Examples

```


IF (LINE5 (2: 7) = 'COMPANY')
AND (LINE5 (13: 6) = 'BRANCH')
AND (LINE8 (4: 2) IS NUMERIC)
  COMPANY = LINE8 (4: 2)
  BRANCH  = LINE8 (14: 3)
  EVALUATE LINE8-LINE55 (24: 4)
    WHEN 'DDDD'
      LINE (24: 4) = .em1
    WHEN 'EBEE'
      LINE (24: 4) = .em2
  END-EVALUATE
END-IF

```

PERFORM statement

The PERFORM statement performs the specified procedure.

Syntax



PERFORM statement

Parameters

&procname Procedure name 1 to 30 characters long. The name can consist of letters, numbers and hyphens. The procedure must be declared at the bottom of the program.

Programming notes

For additional information, see "PROC/END-PROC statement."

PROC/END-PROC statement

The PROC and END-PROC statements are used to declare the beginning and the end of a procedure in the Activity section.

Syntax

Syntax

►—&procname.—PROC—*activity statements*—END-PROC—◄

Parameters

&procname Procedure name 1 to 30 characters long. The name can consist of letters, numbers and hyphens. The first character and the last character must be a letter or a number.

Programming notes

Procedures are declared at the bottom of the script program. One or more procedures can be coded.

Procedures are invoked by means of the PERFORM statement as needed.

Procedures should be used for repetitive logic to make the script program manageable.

RMU does not support the GOTO statement. Therefore procedures must be written in a straight top-to-bottom design.

Examples


```
PERFORM A0001-DECORATE

A0001-DECORATE. PROC
  IF (LINE5 (2: 7) = 'COMPANY')
  AND (LINE5 (13: 6) = 'BRANCH')
  AND (LINE8 (4: 2) IS NUMERIC)
    EVALUATE LINE8-LINE55 (24: 4)
      WHEN 'DDDD'
        LINE (24: 4) = .em1
      WHEN 'EBEE'
        LINE (24: 4) = .em2
    END-EVALUATE
  END-IF
END-PROC
```


STRING statement

The STRING statement concatenates the contents of fields and literal values into a target field.

Syntax



Parameters

<i>&field</i>	Field name to string.
<i>&literal</i>	Literal to string. Must be enclosed in quotes.
<i>&char</i>	A literal enclosed in quotes or a valid field name. The field name, if coded, must be an alphanumeric or display numeric type. The value of <i>&field</i> or <i>&literal</i> is strung into <i>&target</i> up to the <i>&char</i> delimiter. If <i>&char</i> is not found, the entire content is strung.
<i>&target</i>	An alphanumeric field name into which the concatenated strings are placed. The field must be long enough to accommodate all sending strings.
<i>&pointer</i>	A numeric field indicating the starting position in <i>&target</i> . If used, this field must be initialized to the starting position before the STRING statement. At completion, this field contains the number of characters in the <i>&target</i> field placed by the STRING statement.

Programming notes

Multiple fields or literal values can be specified. *&pointer*, if used, is used as the starting position in the *&target*. For example, placing 5 in the pointer tells STRING statement to append values starting at position 5.

If the resulting string is longer than *&target*, the extraneous characters are ignored.

Examples

Assume that the following fields are defined:

```

DEFINE WSTRING W  50 A
DEFINE WCOUNT W   4 B
DEFINE WVALUE1 W  10 A VALUE 'THIS PAYS '
DEFINE WVALUE2 W  15 A VALUE 'BILLS.'

```

Assume that LINE8 (4: 3) contains '10 '.

Case 1:

```

STRING WVALUE1      DELIMITED BY SIZE
      'UTILITY '    DELIMITED BY SIZE
      LINE8 (4: 3)  DELIMITED BY ' '
      'BILLS'       DELIMITED BY SIZE
      INTO WSTRING
END-STRING

```

At execution, WSTRING contains: "THIS PAYS UTILITY 10 BILLS".

Case 2:

```

WSTRING = 'PAYMENT INFORMATION: '
WCOUNT = 22
STRING WVALUE1      DELIMITED BY SIZE
      'UTILITY '    DELIMITED BY SIZE
      LINE8 (4: 3)  DELIMITED BY ' '
      'BILLS'       DELIMITED BY SIZE
      INTO WSTRING WITH POINTER WCOUNT
END-STRING

```

At execution, WSTRING contains: "PAYMENT INFORMATION: THIS PAYS UTILITY 10 BILLS"

System-defined fields

Fields available to programmers:

- | | |
|-----------------------------|--|
| IDX | A 4-byte binary integer used as a subscript when LINE is coded in an argument without a substring.

Also, IDX is used as a subscript in the EVALUATE statement when evaluating a range of lines for a value. |
| I | The same as IDX. |
| IDX2 | A 4-byte binary integer used as a work subscript for the BYPASS statement when bypassing a range of lines. This field is for RMU internal use only. |
| I2 | The same as IDX2. |
| LINE | General purpose name for accessing lines within a page. When coded, the IDX subscript must contain a valid line number within the page buffer. |
| LINE-COUNT | Contains the number of lines in the current page. |
| LINE1 thru LINE66 | References specific lines within a page. |
| PAGE-COUNT | A 4-byte binary integer containing the current page being processed. This field should not be confused with the actual page number that may be shown on report titles. |
| RETURN-CODE | A 4-byte binary integer used as the job return code. |
| SYSDATE or SYSDATE-E | An 8-byte alpha field representing the current date as YY/MM/DD. |
| SYSDATE-9 | A 6-byte numeric field representing the current date as YYMMDD. |

System-defined fields

SYSDATE-LONG or SYSDATE-LONG-E

A 10-byte alpha field representing the current date as CCYY/MM/DD.

SYSDATE-LONG-9

An 8-byte numeric field representing the current date as CCYYMMDD.

SYSTIME An 8-byte alpha field representing the current time as HH.MM.SS.

SYSTIME-9 A 6-byte numeric field representing the current time as HHMMSS.

COBOL verbs, statements, and reserved fields

These words cannot be used as field names in RMU Script:

ABEND-MESSAGE	B-NOT
ABEND-REQUEST	B-OR
ACCEPT	BACKGROUND-COLOR
ACCESS	BACKGROUND-COLOUR
ACCUM	BACKWARD
ACQUIRE	BASIS
ADD	BEEP
ADDRESS	BEFORE
ADVANCING	BEGINNING
AFTER	BELL
ALL	BINARY
ALLOWING	BIT
ALPHABET	BITS
ALPHABETIC-HIGHER	BLANK
ALPHABETIC-LOWER	BLINK
ALPHABETIC	BLOCK
ALPHANUMERIC-EDITED	BOOLEAN
ALPHANUMERIC	BOTTOM
ALSO	BY
ALTER	CALL
ALTERNATE	CANCEL
AND	CBL
ANY	CD
APPLY	CF
ARE	CH
AREA-VALUE	CHAIN
AREA	CHAINING
AREAS	CHANGED
ARITHMETIC	CHARACTER
ASCENDING	CHARACTERS
ASSIGN	CH1
AT	CH10
AUTHOR	CH11
AUTO-SKIP	CH12
AUTO	CH2
AUTOMATIC	CH3
B-AND	CH4
B-EXOR	CH5
B-LESS	CH6

CH7	CONVERTING
CH8	COPY
CH9	CORR
CLASS	CORRESPONDING
CLOCK-UNITS	COUNT
CLOSE	CREATE
COBOL	CRT-UNDER
CODE-SET	CRT
CODE	CTLFOOT
COL	CURRENCY
COLLATING	CURRENT
COLOR	CURSOR
COLUMN	CYCLE
COM-REG	DATA
COMMA	DATE-COMPILED
COMMAND-LINE	DATE-WRITTEN
COMMIT	DATE
COMMITMENT	DAY-OF-WEEK
COMMON	DAY
COMMUNICATION	DB-ACCESS-CONTROL-KEY
COMP-X	DB-DATA-NAME
COMP-0	DB-EXCEPTION
COMP-1	DB-FORMAT-NAME
COMP-2	DB-RECORD-NAME
COMP-3	DB-SET-NAME
COMP-4	DB-STATUS
COMP-5	DB
COMP-6	DBCS
COMP-7	DE
COMP-8	DEBUG-CONTENTS
COMP-9	DEBUG-ITEM
COMP	DEBUG-LINE
COMPUTATIONAL-X	DEBUG-NAME
COMPUTATIONAL-0	DEBUG-SUB-1
COMPUTATIONAL-1	DEBUG-SUB-2
COMPUTATIONAL-2	DEBUG-SUB3
COMPUTATIONAL-3	DEBUGGING
COMPUTATIONAL-4	DECIMAL-POINT
COMPUTATIONAL-5	DECLARATIVES
COMPUTATIONAL-6	DEFAULT
COMPUTATIONAL-7	DELETE
COMPUTATIONAL-8	DELIMITED
COMPUTATIONAL-9	DELIMITER
COMPUTATIONAL	DEPENDING
COMPUTE	DESCENDING
CON	DESTINATION
CONFIGURATION	DETAIL
CONNECT	DISABLE
CONSOLE	DISCONNECT
CONTAINED	DISK
CONTAINS	DISPLAY-1
CONTENT	DISPLAY-2
CONTINUE	DISPLAY-3
CONTROL-AREA	DISPLAY-4
CONTROL	DISPLAY-5
CONTROLS	DISPLAY-6

COBOL verbs, statements, and reserved fields

DISPLAY-7	ERROR
DISPLAY-8	ESCAPE
DISPLAY-9	ESI
DISPLAY	EVALUATE
DIVIDE	EVERY
DIVISION	EXACT
DOWN	EXCEEDS
DROP	EXCEPTION
DUPLICATE	EXCESS-3
DUPLICATES	EXCLUSIVE
DYNAMIC	EXEC
EGCS	EXECUTE
EGI	EXHIBIT
EJECT	EXIT
ELSE	EXTEND
EMI	EXTERNAL
EMPTY-CHECK	EXTERNALLY-DESCRIBED-KEY
EMPTY	FALSE
ENABLE	FD
END-ACCEPT	FETCH
END-ADD	FILE-CONTROL
END-CALL	FILE-ID
END-COMPUTE	FILE
END-DELETE	FILLER
END-DISABLE	FINAL
END-DIVIDE	FIND
END-ENABLE	FINISH
END-EVALUATE	FIRST
END-IF	FIXED
END-MULTIPLY	FOOTING
END-OF-PAGE	FOR
END-PERFORM	FOREGROUND-COLOR
END-READ	FOREGROUND-COLOUR
END-RECEIVE	FORM
END-RECORD	FORMAT
END-RETURN	FREE
END-REWRITE	FROM
END-SEARCH	FULL
END-SEND	FUNCTION
END-START	GENERATE
END-STRING	GET
END-SUBTRACT	GIVING
END-TRANSCIVE	GLOBAL
END-UNSTRING	GO
END-WRITE	GOBACK
END	GREATER
ENDG	GROUP
ENDING	HDR
ENTER	HEADER
ENTRY	HIGH-VALUE
ENVIRONMENT	HIGH-VALUES
EOP	HIGHLIGHT
EQ	I-O-CONTROL
EQUAL	I-O
EQUALS	ID
ERASE	IDENTIFICATION

IDW01	LESS
IDW02	LIKE
IDW03	LIMIT
IDW04	LIMITS
IDW05	LINAGE-COUNTER
IDW06	LINAGE
IDW07	LINE-COUNTER
IDW08	LINES
IF	LINKAGE
IN	LIT
INDEX-1	LOCALLY
INDEX-2	LOCK
INDEX-3	LOW-VALUE
INDEX-4	LOW-VALUES
INDEX-5	MANUAL
INDEX-6	MASK
INDEX-7	MEMBER
INDEX-8	MEMORY
INDEX-9	MERGE
INDEX	MESSAGE
INDEXED	MODE
INDIC	MODIFIED
INDICATE	MODIFY
INDICATOR	MODULES
INDICATORS	MORE-LABELS
INITIAL	MOVE
INITIALIZE	MULTIPLE
INITIATE	MULTIPLY
INPUT-OUTPUT	NATIVE
INPUT	NEGATIVE
INSERT	NEXT
INSPECT	NO-ECHO
INSTALLATION	NO
INTO	NONE
INVALID	NORMAL
IS	NOT
IW-FAKE-INDEX	NULL
IW-PENGI-PAGE	NULLS
IW-RETURN-CODE	NUMBER
IW-WORK-INDEX	NUMERIC-EDITED
JAPANESE	NUMERIC
JUST	OBJECT-COMPUTER
JUSTIFIED	OBJECT
KANJI	OBJECT
KEEP	OCCURS
KEPT	OF
KEY	OFF
KEYBOARD	OMITTED
LAST	ON
LBEL	ONLY
LD	OPEN
LEADING	OPTIONAL
LEFT-JUSTIFY	OR
LEFT	ORDER
LENGTH-CHECK	ORGANIZATION
LENGTH	OTHER

COBOL verbs, statements, and reserved fields

OUTPUT	RC-ABRCODE
OVERFLOW	RC-BOOLEAN
OWNER	RC-CHKOVF0
PACKED-DECIMAL	RC-COBSTAT
PADDING	RC-DATESWP
PAGE-COUNTER	RC-HEXSTR0
PAGE	RC-HEXSTR1
PAGEFOOT	RC-REPCHR0
PALETTE	RC
PARAGRAPH	RD
PARM-LENGTH	READ
PARM-REGISTER-9	READY
PARM-REGISTER	REALM
PASSWORD	RECEIVE
PENGI-CODES	RECONNECT
PENGI-CODE0	RECORD-NAME
PENGI-STATUS	RECORD
PERFORM	RECORDING
PF	RECORDS
PH	REDEFINES
PIC	REEL
PICTURE	REFERENCE
PLUS	REFERENCES
POINTER	RELATION
POS	RELATIVE
POSITION	RELEASE
POSITIVE	RELOAD
PRESENT	REMAINDER
PREVIOUS	REMOVAL
PRINT-SWITCH	RENAMES
PRINTER-1	REPEATED
PRINTER	REPLACE
PRINTING	REPLACING
PRIOR	REPORT
PROCEDURE	REPORTING
PROCEDURES	REPORTS
PROCEED	REQUIRED
PROCESS	RERUN
PROCESSING	RESERVE
PROGRAM-DATE	RESET
PROGRAM-ID	RETAINING
PROGRAM-INFO-TABLE	RETRIEVAL
PROGRAM-NAME	RETURN
PROGRAM-OPSYS	REVERSE-VIDEO
PROGRAM-TIME	REVERSED
PROGRAM-TYPE	REWIND
PROGRAM	REWRITE
PROMPT	RF
PROTECTED	RH
PURGE	RIGHT-JUSTIFY
QUEUE	RIGHT
QUOTE	ROLLBACK
QUOTES	ROLLING
RANDOM	ROUNDED
RANGE	RUN
RC-ABEND00	SAME

SCREEN	SUBFILE
SD	SUBPROGRAM
SEARCH	SUBTRACT
SECTION	SUM
SECURE	SUPPRESS
SECURITY	SWITCH-1
SEGMENT-LIMIT	SWITCH-2
SEGMENT	SWITCH-3
SEL	SWITCH-4
SELECT	SWITCH-5
SEND	SWITCH-6
SENTENCE	SWITCH-7
SEPARATE	SWITCH-8
SEQUENCE	SWITCH
SEQUENTIAL	SYMBOLIC
SERVICE	SYNC
SESSION-ID	SYNCHRONIZED
SET	TABLE
SHARED	TALLY
SHIFT-IN	TALLYING
SHIFT-OUT	TAPE
SIGN	TENANT
SIZE	TERMINAL
SKIP1	TERMINATE
SKIP2	TEST
SKIP3	TEXT
SORT-CONTROL	THAN
SORT-CORE-SIZE	THEN
SORT-FILE-SIZE	THROUGH
SORT-MERGE	THRU
SORT-MESSAGE	TIME
SORT-MODE-SIZE	TIMEOUT
SORT-RETURN	TIMES
SORT	TITLE
SOURCE-COMPUTER	TO
SOURCE	TOP
SPACE-FILL	TRACE
SPACE	TRAILING-SIGN
SPACES	TRAILING
SPECIAL-NAMES	TRANSACTION
STANDARD-1	TRANSCEIVE
STANDARD-2	TRUE
STANDARD-3	TYPE
STANDARD-4	UNDERLINE
STANDARD	UNEQUAL
START	UNIT
STARTING	UNLOCK
STATUS	UNSTRING
STOP	UNTIL
STORE	UP
STRING	UPDATE
STYLE	UPON
SUB-QUEUE-1	USAGE-MODE
SUB-QUEUE-2	USAGE
SUB-QUEUE-3	USE
SUB-SCHEMA	USER

COBOL verbs, statements, and reserved fields

USING
VAL
VALID
VALIDATE
VALUE
VALUES
VARCHAR
VARIABLE
VARYING
WAIT
WHEN-COMPILED
WHEN
WITH
WITHIN
WORDS
WORKING-STORAGE
WRITE-ONLY
WRITE
ZERO-FILL
ZERO
ZEROES
ZEROS

Chapter 6. Messages

There are three types of messages that you can encounter when using RMU:

COBOL compiler-generated messages

RMU converts Script programs to COBOL and then compiles the generated COBOL with a standard LE or z/OS COBOL compiler. COBOL 'I' and 'W' level errors are acceptable. 'E' level errors are serious errors and should be reported to IBM for correction as they can be due to RMU compiler-generated statements.

These messages are generated by the COBOL compiler and are beyond the scope of this document.

RMU runtime error messages

Runtime messages are self-explanatory. File open errors are common due to improper or missing DD names.

For an explanation of runtime messages, refer to *z/OS MVS System Messages*.

RMU compiler-generated messages (listed in this chapter)

RMU compiler-generated messages consist of three parts: A 7-digit message number followed by a comma, a 2-digit condition code and the message text. A condition code of 00 is an advisory message. A condition code of 12 is an error.

RMU compiler-generated messages

RMU0-01,00 AUTO COPY OF IMAGES IGNORED.

Explanation: <object> section was declared for HTML format document. This is an MNOTE statement. MNOTE is informational only.

User response: The images declared (if any) in the section will not be automatically included in the document.

This means that all images used in the document must exist in the &home/images directory on the server where the document is downloaded.

RMU0-01,12 UNPAIRED PARENTHESES ON STATEMENT

Explanation: String was coded with unpaired parentheses.

User response: Code string inside a paired parentheses, example (string).

RMU0-01,12 UNPAIRED QUOTES ON TEXT STATEMENT

Explanation: A quoted string is missing end quote.

User response: Add the quote as needed.

RMU0-02,12 STATEMENTS ARE CODED BEYOND COL 71

Explanation: Text was found beyond column 71.

User response: Correct the problem.

RMU0-03,12 UNPAIRED END-IF/END-DO/EVALUATE STATEMENT

Explanation: A scope terminator is missing. For IF statement, there is no matching END-IF. For DO statement there is no matching END-DO. For EVALUATE statement there is no matching END-EVALUATE.

User response: Add the required scope terminator.

RMU0-04,12 "ELSE" IS OUT OF SEQUENCE

Explanation: ELSE was placed on inappropriate line.

User response: Correct the problem.

RMU0-05,12 "CONTINUE" IS OUT OF SEQUENCE

Explanation: CONTINUE statement is out of sequence.

User response: Correct the problem.

RMU compiler-generated messages

RMU0-06,12 INCOMPLETE STATEMENT

Explanation: Statement requires more arguments.

User response: Complete the statement as required.

RMU0-07,12 LINE IS ILLEGAL (USE LINE1-LINE66)

Explanation: The variable name is not allowed. It conflicts with the reserved LINE nn names.

User response: Use the correct name.

RMU0-08,12 TARGET FIELD NAME EXCEEDS 16 CHRS

Explanation: The field name is longer than 16 characters.

User response: Reduce the field name down to 16 characters or less.

RMU0-09,12 UNDEFINED VARIABLE

Explanation: Variable is not defined and it is not a reserved field.

User response: Correct the problem.

RMU0-10,12 ILLEGAL NAME

Explanation: The name is illegal as coded.

User response: Refer to DEFINE statement for variable naming rules.

RMU0-11,12 ILLEGAL SUBSTRING EXPRESSION

Explanation: The substring is illegal as coded.

User response: Correct the erroneous substring.

RMU0-12,12 IF ARGUMENTS ARE REQUIRED

Explanation: IF statement is not followed by arguments.

User response: Complete the IF statement.

RMU0-13,12 ARGS NOT ENCLOSED IN PARENTHESES

Explanation: IF arguments are coded without parentheses.

User response: IF arguments must be enclosed in parentheses.

RMU0-14,12 SUB START+LENGTH EXCEEDS MAXIMUM

Explanation: The start position plus the length exceeds field capacity.

User response: Correct the substring values such that the sum of start position plus the length does not exceed the field length.

RMU0-15,12 DUPLICATE FIELD NAME

Explanation: The field name has been previously defined or it conflicts with a reserved field name.

User response: Use a different name.

RMU0-16,12 INVALID LENGTH OR EXCEEDS MAXIMUM

Explanation: The field length is invalid or it exceeds maximum allowed length.

User response: Correct the length as follows: Binary field can be 2 or 4 bytes Packed decimal field can be up to 9 bytes Display numeric field can be up to 18 bytes. Alpha field can be up to 32,767 bytes.

RMU0-17,12 TYPE NOT A, N, B OR P

Explanation: Unknown field type.

User response: Code the correct type.

RMU0-18,12 STATEMENT CONTAINS EXTRA ARGUMENTS

Explanation: Extraneous arguments have been detected.

User response: Remove the extraneous arguments.

RMU0-19,12 VALUE IS ILLEGAL AS WRITTEN

Explanation: Field value cannot be resolved as written.

User response: Correct the syntax.

RMU0-20,12 VALUE EXCEEDS FIELD CAPACITY

Explanation: The specified value exceeds field capacity.

User response: Reduce the value to fit the field size.

RMU0-21,12 STATEMENT IS OUT OF SEQUENCE

Explanation: Statement is out of sequence.

User response: Put statements in the correct order according to RMU syntax rules.

RMU0-22,12 &EXPRESS ILLEGAL EXPRESSION

Explanation: Expression is illegal as written.

User response: Correct erroneous expression.

RMU0-23,12 EXCEEDS 2048 NESTED IF STATEMENTS

Explanation: The maximum number of nested IF statements has been exceeded.

User response: Reduce the number of IF statements. Simplify the tests.

RMU0-24,12 NAME IS INVALID OR EXCEEDS 16 CHRS

Explanation: The field name is longer than 16 characters.

User response: Reduce the field name down to 16 characters or less.

RMU0-25,12 &parm INVALID OPTION

Explanation: &parm is unknown option.

User response: Use the correct option.

RMU0-26,12 &var VARIABLE IS NOT NUMERIC TYPE

Explanation: Non-numeric variable used in substring.

User response: Use a numeric value or a numeric variable.

RMU0-27,12 INVALID "DO" STATEMENT SYNTAX

Explanation: The DO statement is illegal as written.

User response: Correct the statement according to DO statement rules.

RMU0-28,12 "TIMES" NOT FOUND

Explanation: Incomplete DO &nn statement.

User response: Correct the statement according to DO &nn TIMES rules.

RMU0-29,12 "W" IS MISSING IN DEFINE STATEMENT

Explanation: DEFINE is improper. "W" following the field name is required.

User response: Correct the erroneous statement.

RMU0-30,12 &var INCOMPATIBLE VARIABLE TYPE

Explanation: The &var type is not compatible with the IF argument type.

User response: Correct the erroneous argument.

RMU0-30,12 &var INCOMPATIBLE VARIABLE TYPE

Explanation: The &var type is not compatible with the WHEN argument type.

User response: Correct the erroneous argument.

RMU0-31,12 "LINE" CANNOT BE A TARGET FIELD

Explanation: LINE is improperly used as a target in ASSIGN statement.

User response: Correct the statement. LINE can be a target of an object or a style only. LINE content cannot be altered by RMU.

RMU0-32,12 LITERAL EXCEEDS 60 CHARACTERS

Explanation: Literal is too long.

User response: Reduce the literal size.

RMU0-33,12 INVALID ASSIGN STATEMENT SYNTAX

Explanation: Assign statement is not valid as written.

User response: Correct the statement to comply with the ASSIGN statement rules.

RMU0-34,12 SUBSTRING NOT VALID FOR P,B TYPE

Explanation: A substring was coded for a Packed decimal or a Binary field.

User response: Remove the substring.

RMU0-35,12 RECURSIVE USE OF "&word"

Explanation: The &word section was previously declared.

User response: Remove the extraneous section.

RMU0-36,12 &word : ILLEGAL NUMBER/ ARGUMENT

Explanation: Argument is illegal as written.

User response: Write the correct argument.

RMU0-37,12 NAME EXCEEDS 8 CHARACTERS

Explanation: Style or Object name exceeds 8 characters.

User response: Reduce the name down to 8 characters. Note that period is included as part of the name.

RMU compiler-generated messages

RMU0-38,12 ARGUMENT IS OUT OF SEQUENCE

Explanation: The argument is out of sequence.

User response: Style and Object arguments are written in pairs as `&name {...}`. Correct the erroneous arguments.

RMU0-39,12 OBJECT USE, SUBSTRING LENGTH NOT 0

Explanation: The length in substring is not zero.

User response: When an object is used as source in assign, the length in the target substring must be zero.

RMU0-40,12 &name DUPLICATE OBJECT NAME

Explanation: The `&name` was previously declared.

User response: Use a unique name.

RMU0-41,12 &name UNDEFINED OBJECT NAME

Explanation: The `&name` is undefined.

User response: Use a defined `&name` from the Style or Object section.

RMU0-42,12 "TURF" IS ILLEGAL IN THIS CONTEXT

Explanation: Illegal use of `.turf1` or `.turf2`.

User response: Correct the erroneous statement.

RMU0-43,12 ZERO START IN SUBSTRING IS ILLEGAL

Explanation: Zero value was used as start position in target field of Assign statement.

User response: Correct the erroneous start value.

RMU0-44,12 SYNTAX UNSUPPORTED FOR CSV FORMAT

Explanation: An object or a style name was used as source in Assign statement for CSV document.

User response: CSV documents cannot be decorated with fonts and images. Remove the statement.

RMU0-45,12 </&tag> TAG IS MISSING

Explanation: No matching end tag was located for `<&tag>` section.

User response: Insert the correct `</&tag>` to complete the `<&tag>` section.

RMU0-46,12 LITERAL FOUND IN CALL PARAMETERS

Explanation: Alphanumeric (quoted) or numeric literal was detected in the call parameters. Literal is not allowed in the CALL parameters.

User response: Remove erroneous parameter. Define a field in the library section with appropriate value and use the field name in the parameter list.

RMU0-47,12 PROCESS STRING EXCEEDS 64 CHARS

Explanation: Parameters on the PROCESS statement span beyond column 64.

User response: Limit PROCESS statement to less than 65 characters. Code multiple PROCESS statements back to back to accommodate your options.

RMU0-42,12 "TURF" IS ILLEGAL IN THIS CONTEXT

Explanation: `.turf` is being assigned to a LINE text.

User response: `.turf` is a special style that can be declared on the PARM statement. When coded, the option is applied to the entire document. Remove/correct improper statement.

RMU0-43,12 ZERO START IN SUBSTRING IS ILLEGAL

Explanation: Zero was used for substring start position.

User response: Code the correct start position.

RMU0-44,12 SYNTAX UNSUPPORTED FOR CSV FORMAT

Explanation: A style or and object was coded in assign statement.

User response: Style and objects cannot be assigned to text in CSV files. Remove erroneous statements.

RMU0-45,12 </XXXX-XXX> TAG IS MISSING

Explanation: A matching end tag is not coded for the tag option in effect.

User response: Code the end tag in the appropriate place.

RMU0-46,12 LITERAL FOUND IN CALL PARAMETERS

Explanation: Literal was coded on CALL statement.

User response: Define a field in Library section with the needed value and use the field name instead.

RMU0-47,12 PROCESS STRING EXCEEDS 64 CHARS

Explanation: COBOL PROCESS exceeds 64 characters.

User response: Code options using multiple PROCESS statement back to back.

RMU0-48,12 EXCEEDS EIGHT(8) EVALUATE NESTS

Explanation: Maximum nested EVALUATE statements exceeded.

User response: Reduce the number of nested EVALUATE statements. If you need to code more than 8 nested EVALUATE statements, write a procedure and use PERFORM to invoke the procedure name.

RMU0-49,12 UNPAIRED END-EVALUATE STATEMENT

Explanation: END-EVALUATE was not coded.

User response: Add END-EVALUATE to appropriate place.

RMU0-50,12 DUPLICATE PROC NAME

Explanation: Procedure name was previously defined.

User response: Use a unique procedure name.

RMU0-51,12 "&proc" UNDEFINED PROC NAME

Explanation: The "&proc" procedure name is not defined.

User response: Correct the spelling of your proc name.

RMU0-52,12 INVALID PROC NAME

Explanation: Procedure name contains invalid characters.

User response: Correct the name. You can use letters, numbers and hyphens. The first character and the last character must be a letter or a number.

RMU0-53,12 END-PROC IS OUT OF SEQUENCE

Explanation: END-PROC was placed without the PROC statement before it, or END-PROC was placed in the middle of a statement that requires a scope terminator, i.e., IF/DO or EVALUATE.

User response: Correct the problem.

RMU0-54,12 PROC NAME EXCEEDS 30 CHARACTERS

Explanation: Procedure name is more than 30 characters long.

User response: Reduce the name to 30 characters or less.

RMU0-55,12 PROC PERFORM WOULD CAUSE A LOOP

Explanation: perform &procname was placed in a proc where &procname is the procedure name where PERFORM was placed.

User response: Correct &procname or remove PERFORM statement in error.

RMU0-56,12 END-PROC IS MISSING

Explanation: End of script program is reached with a proc without a matching END-PROC statement.

User response: Add END-PROC as required.

RMU0-57,12 ILLEGAL CHARACTER AFTER END-STRING

Explanation: The END-STRING statement is followed by extraneous characters.

User response: Remove the extraneous characters.

RMU0-58,12 "DELIMITED" OPTION IS MISSING

Explanation: Improper STRING statement syntax.

User response: Refer to STRING statement for the correct syntax in this manual.

Notices

This information was developed for products and services offered in the USA.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
USA

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

IBM World Trade Asia Corporation
Licensing
2-31 Roppongi 3-chome, Minato-ku
Tokyo 106, Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
Mail Station P300
2455 South Road
Poughkeepsie, NY 12601-5400
USA

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this information and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement, or any equivalent agreement between us.

If you are viewing this information softcopy, the photographs and color illustrations may not appear.

Trademarks

A current list of IBM trademarks is available on the Web at "Copyright and trademark information", <http://www.ibm.com/legal/copytrade.shtml>.

Index

Special characters

.ENUM1, parameter, assignment statement 40
.ETEXT, parameter, assignment statement 40
<docs_end> statement 37
<docs> statement 36
<object> statement 35
<page_end> statement 38
<page_top> statement 37
<style> statement 35
&char, parameter
 PARM statement 33
 STRING statement 50
&color, parameter, <style> statement 36
&condition, parameter
 DO statement 45
 EVALUATE statement 46
&count, parameter, DO statement 45
&css parameter 3, 4
¤cy, parameter, PARM statement 33
&decimal, parameter, PARM statement 33
&expression, parameter, IF statement 47
&field, parameter
 CALL statement 42
 CONTROL statement 43
 DEFINE statement 34
 DISPLAY statement 44
 EVALUATE statement 46
 STRING statement 50
&format, parameter, PARM statement 33
&formula, parameter, assignment statement 39
&image, parameter
 <object> statement 35
 assignment statement 41
&length, parameter
 assignment statement 39, 40
 DEFINE statement 34
 DISPLAY statement 44
 EVALUATE statement 46
&line, parameter, assignment statement 40
&LINEn, parameter, BYPASS statement 41
&literal, parameter, STRING statement 50
&mod, parameter, <object> statement 35
&n, parameter, <style> statement 36
&name, parameter
 PARM statement 33
&option, parameter, PROCESS statement 49
&pointer, parameter, STRING statement 50
&procname, parameter
 PERFORM statement 48
 PROC statement 48
&program, parameter, CALL statement 42
&recfield, parameter, assignment statement 39
&sendfield, parameter, assignment statement 39
&size, parameter, <style> statement 36
&start, parameter
 assignment statement 39, 40
 DISPLAY statement 44
 EVALUATE statement 46
&style, parameter, assignment statement 40
&svc99, FJSVC99 file 7, 14
&sys1 symbol 14
&SYS1.SFZHAMAC library 11, 16
&SYS1.SFZHASRC library 11, 14, 16
&SYS1.SFZHDOCS library 7, 9, 11, 16, 30, 35
&SYS1.SFZHJCLS library 3, 4, 5, 11, 12, 13, 14, 15, 18, 19, 21, 24, 26, 29
&SYS1.SFZHLOAD library 11, 14
&SYS1.SFZHPROC library 11, 15
&target, parameter, STRING statement 50
&type, parameter, DEFINE statement 34
&value, parameter, DEFINE statement 34
#BASE, sequence number type 30
#EOF, sequence number type 31
#nnnnn, sequence number type 30
= (equal sign), assignment statement 39, 40

Numerics

1403 paper 1, 19, 26, 30
1403-paper option 3, 13, 36
1403-paper parameter, PARM statement 36
1403-paper, parameter, PARM statement 33

A

A, parameter, DEFINE statement 34
ABEND-MESSAGE
 See RMU Script, invalid field names
ABEND-REQUEST
 See RMU Script, invalid field names
ABENDs 31
ACCEPT
 See RMU Script, invalid field names
ACCESS
 See RMU Script, invalid field names
ACCUM
 See RMU Script, invalid field names
ACQUIRE
 See RMU Script, invalid field names
ADD
 See RMU Script, invalid field names
ADDRESS
 See RMU Script, invalid field names
ADVANCING
 See RMU Script, invalid field names
AFTER
 See RMU Script, invalid field names
ALL
 See RMU Script, invalid field names
ALLOWING
 See RMU Script, invalid field names
ALPHABET
 See RMU Script, invalid field names
ALPHABETIC
 See RMU Script, invalid field names
ALPHABETIC-HIGHER
 See RMU Script, invalid field names
ALPHABETIC-LOWER
 See RMU Script, invalid field names
ALPHANUMERIC
 See RMU Script, invalid field names
ALPHANUMERIC-EDITED
 See RMU Script, invalid field names
ALSO
 See RMU Script, invalid field names
ALTER
 See RMU Script, invalid field names
ALTERNATE
 See RMU Script, invalid field names
AND
 See RMU Script, invalid field names
ANY
 See RMU Script, invalid field names
APPLY
 See RMU Script, invalid field names
ARE
 See RMU Script, invalid field names
AREA
 See RMU Script, invalid field names
AREA-VALUE
 See RMU Script, invalid field names
AREAS
 See RMU Script, invalid field names
ARITHMETIC
 See RMU Script, invalid field names
ASCENDING
 See RMU Script, invalid field names
ASCII 4, 5, 7, 15, 16
ASSIGN
 See RMU Script, invalid field names
assignment statement 38
AT
 See RMU Script, invalid field names
AUTHOR
 See RMU Script, invalid field names
AUTO
 See RMU Script, invalid field names
AUTO-SKIP
 See RMU Script, invalid field names

AUTOMATIC
See RMU Script, invalid field names

B

B-AND
See RMU Script, invalid field names
B-EXOR
See RMU Script, invalid field names
B-LESS
See RMU Script, invalid field names
B-NOT
See RMU Script, invalid field names
B-OR
See RMU Script, invalid field names
B, parameter, DEFINE statement 34
background color
defining 3, 30
overriding 30
BACKGROUND-COLOR
See RMU Script, invalid field names
BACKGROUND-COLOUR
See RMU Script, invalid field names
BACKWARD
See RMU Script, invalid field names
BASIS
See RMU Script, invalid field names
BEEP
See RMU Script, invalid field names
BEFORE
See RMU Script, invalid field names
BEGINNING
See RMU Script, invalid field names
BELL
See RMU Script, invalid field names
BINARY
See RMU Script, invalid field names
BIT
See RMU Script, invalid field names
BITS
See RMU Script, invalid field names
BLANK
See RMU Script, invalid field names
BLINK
See RMU Script, invalid field names
BLOCK
See RMU Script, invalid field names
BOOLEAN
See RMU Script, invalid field names
BOTTOM
See RMU Script, invalid field names
BY
See RMU Script, invalid field names
BYPASS statement 21, 24, 26, 41

C

CALL
See also RMU Script, invalid field names
field name 52, 53
statement 42
CANCEL
See RMU Script, invalid field names
Cascaded Style Sheets
See CSS

CBL
See RMU Script, invalid field names
CD
See RMU Script, invalid field names
CF
See RMU Script, invalid field names
CH
See RMU Script, invalid field names
CH1
See RMU Script, invalid field names
CH10
See RMU Script, invalid field names
CH11
See RMU Script, invalid field names
CH12
See RMU Script, invalid field names
CH2
See RMU Script, invalid field names
CH3
See RMU Script, invalid field names
CH4
See RMU Script, invalid field names
CH5
See RMU Script, invalid field names
CH6
See RMU Script, invalid field names
CH7
See RMU Script, invalid field names
CH8
See RMU Script, invalid field names
CH9
See RMU Script, invalid field names
CHAIN
See RMU Script, invalid field names
CHAINING
See RMU Script, invalid field names
CHANGED
See RMU Script, invalid field names
CHARACTER
See RMU Script, invalid field names
Character Separated Values
See CSV
CHARACTERS
See RMU Script, invalid field names
characters, control 18
CLASS
See RMU Script, invalid field names
CLOCK-UNITS
See RMU Script, invalid field names
CLOSE
See RMU Script, invalid field names
COBLIB parameter 14
COBLIST
file, description 7
file, required when compiling 5
link and go mode 6
COBOL
See also RMU Script, invalid field names
#BASE statement 30
compiler
generated messages 59
options 49
PROCESS (CBL) option 49
requirement for 17
currency symbol 13
debugger 31

COBOL (continued)
default
compiler LIST option 12
printer 14
FZHRMUS1 utility 13
listings, redirecting 14
option, COBLIST file 7
reserved
fields 52
words 16
runtime problems 30, 31
skeleton 16
statement sequence numbers 30
statements 52
verbs 52
CODE
See RMU Script, invalid field names
code set (ASCII or EBCDIC) 15
CODE-SET
See RMU Script, invalid field names
coding, RMU Script 18
COL
See RMU Script, invalid field names
COLLATING
See RMU Script, invalid field names
COLOR
See RMU Script, invalid field names
color, background 3
COLUMN
See RMU Script, invalid field names
column values, formatting 21
COM-REG
See RMU Script, invalid field names
COMMA
See RMU Script, invalid field names
COMMA, parameter, PARM
statement 33
COMMAND-LINE
See RMU Script, invalid field names
commands
reading syntax diagrams xi
COMMIT
See RMU Script, invalid field names
COMMITMENT
See RMU Script, invalid field names
COMMON
See RMU Script, invalid field names
COMMUNICATION
See RMU Script, invalid field names
COMP
See RMU Script, invalid field names
COMP-0
See RMU Script, invalid field names
COMP-1
See RMU Script, invalid field names
COMP-2
See RMU Script, invalid field names
COMP-3
See RMU Script, invalid field names
COMP-4
See RMU Script, invalid field names
COMP-5
See RMU Script, invalid field names
COMP-6
See RMU Script, invalid field names
COMP-7
See RMU Script, invalid field names

COMP-8
 See RMU Script, invalid field names
 COMP-9
 See RMU Script, invalid field names
 COMP-X
 See RMU Script, invalid field names
 COMPUTATIONAL
 See RMU Script, invalid field names
 COMPUTATIONAL-0
 See RMU Script, invalid field names
 COMPUTATIONAL-1
 See RMU Script, invalid field names
 COMPUTATIONAL-2
 See RMU Script, invalid field names
 COMPUTATIONAL-3
 See RMU Script, invalid field names
 COMPUTATIONAL-4
 See RMU Script, invalid field names
 COMPUTATIONAL-5
 See RMU Script, invalid field names
 COMPUTATIONAL-6
 See RMU Script, invalid field names
 COMPUTATIONAL-7
 See RMU Script, invalid field names
 COMPUTATIONAL-8
 See RMU Script, invalid field names
 COMPUTATIONAL-9
 See RMU Script, invalid field names
 COMPUTATIONAL-X
 See RMU Script, invalid field names
 COMPUTE
 See RMU Script, invalid field names
 CON
 See RMU Script, invalid field names
 CONFIGURATION
 See RMU Script, invalid field names
 CONNECT
 See RMU Script, invalid field names
 CONSOLE
 See RMU Script, invalid field names
 constants
 PROCLIB0 14
 PRODUCT0 14
 CONTAINED
 See RMU Script, invalid field names
 CONTAINS
 See RMU Script, invalid field names
 CONTENT
 See RMU Script, invalid field names
 CONTINUE
 See also RMU Script, invalid field names
 field name 53
 statement 42
 control
 break
 annotations, removing 21
 fields, populating 26
 selection tree 26
 characters 18
 CONTROL
 See also RMU Script, invalid field names
 field name 53
 statement 43
 CONTROL statement 26

CONTROL-AREA
 See RMU Script, invalid field names
 CONTROLS
 See RMU Script, invalid field names
 CONVERTING
 See RMU Script, invalid field names
 COPY
 See RMU Script, invalid field names
 CORR
 See RMU Script, invalid field names
 CORRESPONDING
 See RMU Script, invalid field names
 COUNT
 See RMU Script, invalid field names
 CREATE
 See RMU Script, invalid field names
 CRT
 See RMU Script, invalid field names
 CRT-UNDER
 See RMU Script, invalid field names
 CSS
 <style> tag 35
 &css parameter 3
 &SYS1.SFZHD0CS library 11
 applying to CSV file 21
 assignment statement 39
 base templates 16
 FJIDOC0 file 7
 FZHBPARS parser utility 8
 PARM statement 3
 style section 30
 tree templates 16
 CSV
 applying CSS, images 21
 assignment statement 39
 BYPASS statement 41
 CSVCHAR parameter 13
 default separator character 13
 distributing output documents 4
 document, creating 21
 example, RMU script program 22
 files 5
 FJCONFG
 file description 7
 not in JCL 15
 FJORPT0, file description 7
 FZHCSV00, I/O module 16
 introduction to RMU 1
 parameter, PARM statement 33
 CSVCHAR parameter 13
 CTLFOOT
 See RMU Script, invalid field names
 CURRENCY
 parameter 11
 currency symbol 13
 CURRENT
 See RMU Script, invalid field names
 CURSOR
 See RMU Script, invalid field names
 custom jobs, publishing to z/OS
 UNIX 15
 CWORK parameter 14
 CYCLE
 See RMU Script, invalid field names

D

DATA
 See RMU Script, invalid field names
 DATE
 See RMU Script, invalid field names
 DATE-COMPILED
 See RMU Script, invalid field names
 DATE-WRITTEN
 See RMU Script, invalid field names
 DAY
 See RMU Script, invalid field names
 DAY-OF-WEEK
 See RMU Script, invalid field names
 DB
 See RMU Script, invalid field names
 DB-ACCESS-CONTROL-KEY
 See RMU Script, invalid field names
 DB-DATA-NAME
 See RMU Script, invalid field names
 DB-EXCEPTION
 See RMU Script, invalid field names
 DB-FORMAT-NAME
 See RMU Script, invalid field names
 DB-RECORD-NAME
 See RMU Script, invalid field names
 DB-SET-NAME
 See RMU Script, invalid field names
 DB-STATUS
 See RMU Script, invalid field names
 DBCS
 See RMU Script, invalid field names
 DD names
 FJCONFG 5, 15
 FJSYSPR 14
 FJUNIX0 4, 14
 summary 5
 DE
 See RMU Script, invalid field names
 DEBUG-CONTENTS
 See RMU Script, invalid field names
 DEBUG-ITEM
 See RMU Script, invalid field names
 DEBUG-LINE
 See RMU Script, invalid field names
 DEBUG-NAME
 See RMU Script, invalid field names
 DEBUG-SUB-1
 See RMU Script, invalid field names
 DEBUG-SUB-2
 See RMU Script, invalid field names
 DEBUG-SUB3
 See RMU Script, invalid field names
 debugger, COBOL 31
 DEBUGGING
 See RMU Script, invalid field names
 debugging, RMU Script programs 30
 DECIMAL parameter 11
 DECIMAL-POINT
 See RMU Script, invalid field names
 DECLARATIVES
 See RMU Script, invalid field names
 decorating
 file types 29
 HTML document 29
 HTML-format document 24
 HTML1-format document 26

default
 library locator table 13
 options table 11
 DEFAULT
 See RMU Script, invalid field names
 DEFINE statement 26, 34
 DELETE
 See RMU Script, invalid field names
 DELIMITED
 See RMU Script, invalid field names
 DELIMITER
 See RMU Script, invalid field names
 DEPENDING
 See RMU Script, invalid field names
 DESCENDING
 See RMU Script, invalid field names
 DESTINATION
 See RMU Script, invalid field names
 DETAIL
 See RMU Script, invalid field names
 directories, UNIX 5
 DISABLE
 See RMU Script, invalid field names
 DISCONNECT
 See RMU Script, invalid field names
 DISK
 See RMU Script, invalid field names
 DISPLAY
 See RMU Script, invalid field names
 DISPLAY statement 44
 DISPLAY-1
 See RMU Script, invalid field names
 DISPLAY-2
 See RMU Script, invalid field names
 DISPLAY-3
 See RMU Script, invalid field names
 DISPLAY-4
 See RMU Script, invalid field names
 DISPLAY-5
 See RMU Script, invalid field names
 DISPLAY-6
 See RMU Script, invalid field names
 DISPLAY-7
 See RMU Script, invalid field names
 DISPLAY-8
 See RMU Script, invalid field names
 DISPLAY-9
 See RMU Script, invalid field names
 distributing, output documents 4
 DIVIDE
 See RMU Script, invalid field names
 DIVISION
 See RMU Script, invalid field names
 DO
 loop, controlling 21
 statement 44
 docs statement 36
 docs_end statement 37
 DOWN
 See RMU Script, invalid field names
 downloading to a PC 5
 DROP
 See RMU Script, invalid field names
 DUPLICATE
 See RMU Script, invalid field names
 DUPLICATES
 See RMU Script, invalid field names
 DYNAMIC
 See RMU Script, invalid field names

E

EBCDIC 5, 15, 16
 EGCS
 See RMU Script, invalid field names
 EGI
 See RMU Script, invalid field names
 EJECT
 See RMU Script, invalid field names
 ELSE
 See RMU Script, invalid field names
 ELSE statement 47
 EMI
 See RMU Script, invalid field names
 EMPTY
 See RMU Script, invalid field names
 EMPTY-CHECK
 See RMU Script, invalid field names
 ENABLE
 See RMU Script, invalid field names
 END
 See RMU Script, invalid field names
 END-ACCEPT
 See RMU Script, invalid field names
 END-ADD
 See RMU Script, invalid field names
 END-CALL
 See RMU Script, invalid field names
 END-COMPUTE
 See RMU Script, invalid field names
 END-DELETE
 See RMU Script, invalid field names
 END-DISABLE
 See RMU Script, invalid field names
 END-DIVIDE
 See RMU Script, invalid field names
 END-DO statement 44
 END-ENABLE
 See RMU Script, invalid field names
 END-EVALUATE
 See RMU Script, invalid field names
 END-EVALUATE statement 45
 END-IF
 See also RMU Script, invalid field
 names
 field name 54
 statement 47
 END-MULTIPLY
 See RMU Script, invalid field names
 END-OF-PAGE
 See RMU Script, invalid field names
 END-PERFORM
 See RMU Script, invalid field names
 END-PROC statement 48
 END-READ
 See RMU Script, invalid field names
 END-RECEIVE
 See RMU Script, invalid field names
 END-RECORD
 See RMU Script, invalid field names
 END-RETURN
 See RMU Script, invalid field names
 END-REWRITE
 See RMU Script, invalid field names
 END-SEARCH
 See RMU Script, invalid field names
 END-SEND
 See RMU Script, invalid field names
 END-START
 See RMU Script, invalid field names
 END-STRING
 See RMU Script, invalid field names
 END-SUBTRACT
 See RMU Script, invalid field names
 END-TRANSCIBE
 See RMU Script, invalid field names
 END-UNSTRING
 See RMU Script, invalid field names
 END-WRITE
 See RMU Script, invalid field names
 ENDG
 See RMU Script, invalid field names
 ENDING
 See RMU Script, invalid field names
 ENTER
 See RMU Script, invalid field names
 ENTRY
 See RMU Script, invalid field names
 ENUM1, formatting column values 21
 ENVIRONMENT
 See RMU Script, invalid field names
 environmental errors 31
 environments, UNIX 4
 EOP
 See RMU Script, invalid field names
 EQ
 See RMU Script, invalid field names
 EQUAL
 See RMU Script, invalid field names
 EQUALS
 See RMU Script, invalid field names
 ERASE
 See RMU Script, invalid field names
 ERROR
 See RMU Script, invalid field names
 ESCAPE
 See RMU Script, invalid field names
 ESI
 See RMU Script, invalid field names
 ETEXT, formatting column values 21
 EVALUATE
 See also RMU Script, invalid field
 names
 field name 54
 statement 24
 EVALUATE statement 26, 45
 EVERY
 See RMU Script, invalid field names
 EXACT
 See RMU Script, invalid field names
 example, RMU Script 19
 EXCEEDS
 See RMU Script, invalid field names
 EXCEPTION
 See RMU Script, invalid field names
 EXCESS-3
 See RMU Script, invalid field names
 EXCLUSIVE
 See RMU Script, invalid field names
 EXEC
 See RMU Script, invalid field names

EXECUTE
See RMU Script, invalid field names
 EXHIBIT
See RMU Script, invalid field names
 EXIT
See RMU Script, invalid field names
 EXTEND
See RMU Script, invalid field names
 EXTERNAL
See RMU Script, invalid field names
 EXTERNALLY-DESCRIBED-KEY
See RMU Script, invalid field names

F

FALSE
See RMU Script, invalid field names
 FD
See RMU Script, invalid field names
 features, RMU 1
 FETCH
See RMU Script, invalid field names
 field headings, removing 21
 FILE
See RMU Script, invalid field names
 file I/O errors 31
 FILE-CONTROL
See RMU Script, invalid field names
 FILE-ID
See RMU Script, invalid field names
 files
 COBLIST 5, 6
 CSV 5
 descriptions 7
 FJCONFIG 6
 FJDMAP0 6
 FJIDOC0 5, 6
 FJIRPT0 5, 6
 FJORPT0 5, 6
 FJSVC99 6
 FJUNIX0 6
 gif 5, 7, 8, 15, 16, 19, 26, 29, 35, 37, 38
 LKEDMAP 6
 required
 compiling RMU Script 5
 publishing to z/OS UNIX 6
 running RMU in "link and go"
 mode 6
 running RMU with compiled RMU
 Script 6
 running RMU without RMU Script
 program 5
 RMUERR1 6
 RMULIST 6
 STDERR 6
 STDOUT 6
 SYSIN 6
 SYSLMOD 6
 SYSOUT 5, 6
 UNIX 4
 FILLER
See RMU Script, invalid field names
 FINAL
See RMU Script, invalid field names
 FIND
See RMU Script, invalid field names

FINISH
See RMU Script, invalid field names
 FIRST
See RMU Script, invalid field names
 FIXED
See RMU Script, invalid field names
 FJCONFIG
 file description 7
 publishing to z/OS UNIX 6
 FJCONFIG DD 15
 FJCONFIG, pointing to httpd.conf file 5
 FJDMAP0 6
 FJDMAP0, file description 7
 FJIDOC0
 file description 7
 library 26
 link and go mode 4, 6
 running RMU 3
 running with compiled RMU
 Script 3, 6
 running without RMU Script 5
 FJIRPT0
 file description 7
 link and go mode 6
 running with compiled RMU
 Script 6
 running without RMU Script 5
 FJORPT0
 file description 7
 link and go mode 6
 running with compiled RMU
 Script 6
 running without RMU Script 5
 FJSVC99
 file description 7
 link and go mode 6
 required when compiling 6
 running with compiled RMU
 Script 6
 FJSYSR, DD name 14
 FJUNIX0
 file description 8
 publishing to z/OS UNIX 6
 sending output 4, 14
 FJUNIX1, file description 8
 float characters, removing 21
 font size, changing 30
 FOOTING
See RMU Script, invalid field names
 FOR
See RMU Script, invalid field names
 FOREGROUND-COLOR
See RMU Script, invalid field names
 FOREGROUND-COLOUR
See RMU Script, invalid field names
 FORM
See RMU Script, invalid field names
 FORMAT
See RMU Script, invalid field names
 formats
 HTML 4
 HTML1 4
 formatting column values 21
 fragments, syntax diagrams xi
 FREE
See RMU Script, invalid field names

FROM
See RMU Script, invalid field names
 FULL
See RMU Script, invalid field names
 FUNCTION
See RMU Script, invalid field names
 FZH#PROC
 locating 14
 tailoring 13
 FZH#PROC, &SYS1.SFZHJCLS
 library 15
 FZH#READ, &SYS1.SFZHJCLS
 library 15
 FZHASMOJ 12
 FZHASMPJ 14
 FZHBPARS 4, 8
 FZHDELCJ 11, 18
 FZHEBCSS 30
 FZHLINKJ 3, 5, 11
 FZHOPTAB 11, 12
 FZHPROCS 13, 14
 FZHRMU00 3
 FZHRMU00 program 3, 4, 13
 FZHRMU01 3
 FZHRMU01 program 5, 13
 FZHRMUJ0 3, 5, 11, 24
 FZHRMUJ1 3, 5, 11
 FZHRMUJ2 4, 5, 11
 FZHRMUS1 13
 FZHRMUX0 3, 5, 11, 15
 FZHRMUX1 3, 5, 11, 15
 FZHRMUX2 4, 5, 11, 15
 FZHUNIX1 4, 15

G

GENERATE
See RMU Script, invalid field names
 GET
See RMU Script, invalid field names
 gif files 5, 7, 8, 15, 16, 19, 26, 29, 35, 37, 38
 GIVING
See RMU Script, invalid field names
 GLOBAL
See RMU Script, invalid field names
 GO
See RMU Script, invalid field names
 GOBACK
See RMU Script, invalid field names
 GREATER
See RMU Script, invalid field names
 GROUP
See RMU Script, invalid field names

H

HDR
See RMU Script, invalid field names
 HEADER
See RMU Script, invalid field names
 HIGH-VALUE
See also RMU Script, invalid field
 names
 field name 54
 parameter, DEFINE statement 34

HIGH-VALUES
 See also RMU Script, invalid field names
 field name 54
 parameter, DEFINE statement 34
 HIGHLIGHT
 See RMU Script, invalid field names
 how RMU works 1
 HTML
 document
 creating 24
 decorating 29
 format 4
 HTML0, parameter, PARM statement 33
 HTML1
 document, creating 26
 format 4
 option 8
 parameter, PARM statement 33
 httpd.conf 5

I

I-O
 See RMU Script, invalid field names
 I-O-CONTROL
 See RMU Script, invalid field names
 I, system-defined field, description 51
 I/O, RMU Script 17
 I2, system-defined field, description 51
 ID
 See RMU Script, invalid field names
 IDENTIFICATION
 See RMU Script, invalid field names
 IDW01
 See RMU Script, invalid field names
 IDW02
 See RMU Script, invalid field names
 IDW03
 See RMU Script, invalid field names
 IDW04
 See RMU Script, invalid field names
 IDW05
 See RMU Script, invalid field names
 IDW06
 See RMU Script, invalid field names
 IDW07
 See RMU Script, invalid field names
 IDW08
 See RMU Script, invalid field names
 IDX
 subscript
 BYPASS statement 41
 control breaks selection tree 26
 creating CSV documents 21
 creating simple HTML documents 24
 description 51
 EVALUATE statement 46
 I/O handling 18
 system-defined field, description 51
 IDX2, system-defined field, description 51
 IF
 See also RMU Script, invalid field names
 field name 55

IF (*continued*)
 statement 47
 IN
 See RMU Script, invalid field names
 INDEX
 See RMU Script, invalid field names
 INDEX-1
 See RMU Script, invalid field names
 INDEX-2
 See RMU Script, invalid field names
 INDEX-3
 See RMU Script, invalid field names
 INDEX-4
 See RMU Script, invalid field names
 INDEX-5
 See RMU Script, invalid field names
 INDEX-6
 See RMU Script, invalid field names
 INDEX-7
 See RMU Script, invalid field names
 INDEX-8
 See RMU Script, invalid field names
 INDEX-9
 See RMU Script, invalid field names
 INDEXED
 See RMU Script, invalid field names
 INDIC
 See RMU Script, invalid field names
 INDICATE
 See RMU Script, invalid field names
 INDICATOR
 See RMU Script, invalid field names
 INDICATORS
 See RMU Script, invalid field names
 INITIAL
 See RMU Script, invalid field names
 INITIALIZE
 See RMU Script, invalid field names
 INITIATE
 See RMU Script, invalid field names
 INPUT
 See RMU Script, invalid field names
 INPUT-OUTPUT
 See RMU Script, invalid field names
 INSERT
 See RMU Script, invalid field names
 INSPECT
 See RMU Script, invalid field names
 INSTALLATION
 See RMU Script, invalid field names
 installation, RMU 11
 INTO
 See RMU Script, invalid field names
 introduction, RMU 1
 INVALID
 See RMU Script, invalid field names
 IS
 See RMU Script, invalid field names
 IW-FAKE-INDEX
 See RMU Script, invalid field names
 IW-PENGI-PAGE
 See RMU Script, invalid field names
 IW-RETURN-CODE
 See RMU Script, invalid field names
 IW-WORK-INDEX
 See RMU Script, invalid field names

J

JAPANESE
 See RMU Script, invalid field names
 Java 4, 8, 9, 16
 JCL, supplied with RMU 3
 jobs
 available 5
 FZHASMOJ 12
 FZHASMPJ 14
 FZHLINKJ 3
 FZHRMUJ0 3, 5
 FZHRMUJ1 3, 5
 FZHRMUJ2 4, 5
 FZHRMUX0 3, 15
 FZHRMUX1 3, 15
 FZHRMUX2 4, 15
 JUST
 See RMU Script, invalid field names
 JUSTIFIED
 See RMU Script, invalid field names

K

KANJI
 See RMU Script, invalid field names
 KEEP
 See RMU Script, invalid field names
 KEPT
 See RMU Script, invalid field names
 KEY
 See RMU Script, invalid field names
 KEYBOARD
 See RMU Script, invalid field names
 keywords, syntax diagrams xi

L

LAST
 See RMU Script, invalid field names
 LBEL
 See RMU Script, invalid field names
 LD
 See RMU Script, invalid field names
 LEADING
 See RMU Script, invalid field names
 LEFT
 See RMU Script, invalid field names
 LEFT-JUSTIFY
 See RMU Script, invalid field names
 LENGTH
 See RMU Script, invalid field names
 LENGTH-CHECK
 See RMU Script, invalid field names
 LESS
 See RMU Script, invalid field names
 libraries
 &SYS1.SFZHAMAC 16
 &SYS1.SFZHASRC 11, 14, 16
 &SYS1.SFZHDOCS 7, 9, 16, 30, 35
 &SYS1.SFZHJCLS 3, 4, 5, 11, 12, 13, 14, 15, 18, 19, 21, 24, 26, 29
 &SYS1.SFZHLOAD 14
 &SYS1.SFZHPROC 15
 FJIDOC0 26
 library
 jobs 15

library (continued)
 locator table, default 13
 LIKE
 See RMU Script, invalid field names
 LIMIT
 See RMU Script, invalid field names
 LIMITS
 See RMU Script, invalid field names
 LINAGE
 See RMU Script, invalid field names
 LINAGE-COUNTER
 See RMU Script, invalid field names
 LINE
 parameter, BYPASS statement 41
 system-defined field, description 51
 line number 18
 LINE-COUNT
 determining page properties 21
 EVALUATE statement 46
 parameter 24, 26
 system-defined field, description 51
 LINE-COUNTER
 See RMU Script, invalid field names
 LINE1 thru LINE66, system-defined field,
 description 51
 LINES
 See RMU Script, invalid field names
 linex, parameter, EVALUATE
 statement 46
 link and go
 FZHRMU00 16
 FZHRMU00 program 13
 FZHRMU00 utility 15
 FZHRMUJ2 5
 FZHRMUJ2 job 11
 FZHRMUJ2, FZHRMUX2 jobs 4
 FZHRMUX2 job 5, 11
 FZHTEST0 15
 FZHTEST1 15
 FZHTEST2 15
 FZHTEST3 15
 FZHTEST4 15
 required files 6
 RMU default library locator table
 (FZHPROCS) 13
 RMU Script, basic concepts 17
 running RMU 4
 LINKAGE
 See RMU Script, invalid field names
 LIST option 12
 LIT
 See RMU Script, invalid field names
 LKED option 8
 LKEDMAP
 file 6
 file description 8
 required when compiling 6
 LOCALLY
 See RMU Script, invalid field names
 locating statement in error 31
 LOCK
 See RMU Script, invalid field names
 LOW-VALUE
 See also RMU Script, invalid field
 names
 field name 55
 parameter, DEFINE statement 34

LOW-VALUES
 See also RMU Script, invalid field
 names
 field name 55
 parameter, DEFINE statement 34

M

MANUAL
 See RMU Script, invalid field names
 manual, structure ix
 MASK
 See RMU Script, invalid field names
 MEMBER
 See RMU Script, invalid field names
 members
 FZH#PROC 14
 FZHEBCSS 30
 MEMORY
 See RMU Script, invalid field names
 MERGE
 See RMU Script, invalid field names
 MESSAGE
 See RMU Script, invalid field names
 messages 59
 Migration Utility
 DD name, FJSYSPR 14
 libraries 14
 MODE
 See RMU Script, invalid field names
 MODEL parameter 14
 MODIFIED
 See RMU Script, invalid field names
 MODIFY
 See RMU Script, invalid field names
 MODULES
 See RMU Script, invalid field names
 MORE-LABELS
 See RMU Script, invalid field names
 MOVE
 See RMU Script, invalid field names
 MSGALL option 14
 MSGOFF option 14
 MSGON option 14
 MSGSER option 14
 MSGTXT option 14
 MULTIPLE
 See RMU Script, invalid field names
 MULTIPLY
 See RMU Script, invalid field names

N

N, parameter, DEFINE statement 34
 NATIVE
 See RMU Script, invalid field names
 NEGATIVE
 See RMU Script, invalid field names
 NEXT
 See RMU Script, invalid field names
 NIX
 directory 5
 environment 4
 files 4

NO
 See also RMU Script, invalid field
 names
 parameter, PARM statement 33
 TURF option 3
 NO-ECHO
 See RMU Script, invalid field names
 NONAME, default value, PARM
 statement 33
 NONE
 See RMU Script, invalid field names
 NORMAL
 See RMU Script, invalid field names
 NOT
 See RMU Script, invalid field names
 Notices 65
 NULL
 See RMU Script, invalid field names
 NULLS
 See RMU Script, invalid field names
 NUMBER
 See RMU Script, invalid field names
 NUMERIC
 See RMU Script, invalid field names
 NUMERIC-EDITED
 See RMU Script, invalid field names

O

OBJECT
 See RMU Script, invalid field names
 object statement 35
 OBJECT-COMPUTER
 See RMU Script, invalid field names
 OCCURS
 See RMU Script, invalid field names
 OF
 See RMU Script, invalid field names
 OFF
 See RMU Script, invalid field names
 OMITTED
 See RMU Script, invalid field names
 ON
 See RMU Script, invalid field names
 ONLY
 See RMU Script, invalid field names
 OPEN
 See RMU Script, invalid field names
 OPTIONAL
 See RMU Script, invalid field names
 options
 1403-paper 3, 33, 36
 COBOL 7
 COBOL compiler PROCESS (CBL) 49
 HTML1 8
 LIST 12
 LKED 8
 MSGALL 14
 MSGOFF 14
 MSGON 14
 MSGSER 14
 MSGTXT 14
 NO (TURF option) 3
 STYLE 3
 SYSPRDD=&DDname 14
 table, RMU 11
 TURF 3

OR
 See RMU Script, invalid field names
 ORDER
 See RMU Script, invalid field names
 ORGANIZATION
 See RMU Script, invalid field names
 OTHER
 See also RMU Script, invalid field names
 field name 55
 parameter, EVALUATE statement 46
 OUTPUT
 See RMU Script, invalid field names
 output documents, distributing 4
 OVERFLOW
 See RMU Script, invalid field names
 OWNER
 See RMU Script, invalid field names

P

P, parameter, DEFINE statement 34
 PACKED-DECIMAL
 See RMU Script, invalid field names
 PADDING
 See RMU Script, invalid field names
 page
 properties, determining 21
 titles, removing 21
 PAGE
 See RMU Script, invalid field names
 page_end statement 38
 page_top statement 37
 PAGE-COUNT
 determining page properties 21
 parameter 24, 26
 system-defined field, description 51
 PAGE-COUNTER
 See RMU Script, invalid field names
 PAGEFOOT
 See RMU Script, invalid field names
 PALETTE
 See RMU Script, invalid field names
 PARAGRAPH
 See RMU Script, invalid field names
 parameters
 .ENUM1 40
 .ETEXT 40
 &char 33, 50
 &color 36
 &condition 45, 46
 &count 45
 &css 3, 4
 ¤cy 33
 &decimal 33
 &expression 47
 &field 34, 42, 43, 44, 46, 50
 &format 33
 &formula 39
 &HTML0 33
 &image 35, 41
 &length 34, 39, 40, 44, 46
 &line 40
 &LINEn 41
 &literal 50
 &mod 35
 &n 36

parameters (*continued*)
 &name 33
 &option 49
 &pointer 50
 &procname 48
 &program 42
 &recfield 39
 &sendfield 39
 &size 36
 &start 39, 40, 44, 46
 &style 40
 &target 50
 &type 34
 &value 34
 1403-paper 33, 36
 A 34
 B 34
 COBLIB 14
 COMMA 33
 CSVCHAR 13
 CURRENCY 11
 CWORK 14
 DECIMAL 11
 HIGH-VALUE 34
 HIGH-VALUES 34
 HTML1 33
 LINE 41
 LINE-COUNT 24, 26
 linux 46
 LOW-VALUE 34
 LOW-VALUES 34
 MODEL 14
 N 34
 NO 33
 OTHER 46
 P 34
 PAGE-COUNT 24, 26
 PATH 14
 PERIOD 33
 SPACE 34
 SPACES 34
 statements_1 47
 statements_2 47
 SVC99 14
 TURF NO 30
 TWORK 14
 UNTIL 45
 WHILE 45
 ZERO 34
 ZEROS 34
 PARM statement 24, 26, 33
 PARM-LENGTH
 See RMU Script, invalid field names
 PARM-REGISTER
 See RMU Script, invalid field names
 PARM-REGISTER-9
 See RMU Script, invalid field names
 PASSWORD
 See RMU Script, invalid field names
 PATH parameter 14
 PCs, downloading to 5
 PDS
 FJIDOC0 3, 4
 PENGICODE0
 See RMU Script, invalid field names
 PENGICODES
 See RMU Script, invalid field names

PENGICSTATUS
 See RMU Script, invalid field names
 PERFORM
 See also RMU Script, invalid field names
 field name 56
 statement 47
 PERIOD, parameter, PARM statement 33
 PF
 See RMU Script, invalid field names
 PH
 See RMU Script, invalid field names
 PIC
 See RMU Script, invalid field names
 PICTURE
 See RMU Script, invalid field names
 PLUS
 See RMU Script, invalid field names
 POINTER
 See RMU Script, invalid field names
 POS
 See RMU Script, invalid field names
 POSITION
 See RMU Script, invalid field names
 POSITIVE
 See RMU Script, invalid field names
 PRESENT
 See RMU Script, invalid field names
 PREVIOUS
 See RMU Script, invalid field names
 print control character 18
 PRINT-SWITCH
 See RMU Script, invalid field names
 PRINTER
 See RMU Script, invalid field names
 PRINTER-1
 See RMU Script, invalid field names
 printer, internal 14
 PRINTING
 See RMU Script, invalid field names
 PRIOR
 See RMU Script, invalid field names
 problems, runtime 31
 PROC statement 48
 PROCEDURE
 See RMU Script, invalid field names
 PROCEDURES
 See RMU Script, invalid field names
 PROCEED
 See RMU Script, invalid field names
 PROCESS
 See RMU Script, invalid field names
 PROCESS statement 49
 PROCESSING
 See RMU Script, invalid field names
 PROCLIB0 constant 14
 PRODUCT0 constant 14
 PROGRAM
 See RMU Script, invalid field names
 program check interrupts 31
 Program Directory 11
 PROGRAM-DATE
 See RMU Script, invalid field names
 PROGRAM-ID
 See RMU Script, invalid field names
 PROGRAM-INFO-TABLE
 See RMU Script, invalid field names

PROGRAM-NAME
See RMU Script, invalid field names
PROGRAM-OPSY
See RMU Script, invalid field names
PROGRAM-TIME
See RMU Script, invalid field names
PROGRAM-TYPE
See RMU Script, invalid field names
programs
FZHBPARS 8
FZHLINKJ 5
FZHPROCS 14
FZHRMU00 3, 4, 13
FZHRMU01 3, 5, 13
FZHUNIX1 4, 15
PROMPT
See RMU Script, invalid field names
PROTECTED
See RMU Script, invalid field names
PURGE
See RMU Script, invalid field names

Q

QUEUE
See RMU Script, invalid field names
QUOTE
See RMU Script, invalid field names
QUOTES
See RMU Script, invalid field names

R

RANDOM
See RMU Script, invalid field names
RANGE
See RMU Script, invalid field names
RC
See RMU Script, invalid field names
RC-ABEND00
See RMU Script, invalid field names
RC-ABRCODE
See RMU Script, invalid field names
RC-BOOLEAN
See RMU Script, invalid field names
RC-CHKOVF0
See RMU Script, invalid field names
RC-COBSAT
See RMU Script, invalid field names
RC-DATESWP
See RMU Script, invalid field names
RC-HEXSTRO
See RMU Script, invalid field names
RC-HEXSTR1
See RMU Script, invalid field names
RC-REPCHR0
See RMU Script, invalid field names
RD
See RMU Script, invalid field names
READ
See RMU Script, invalid field names
READY
See RMU Script, invalid field names
REALM
See RMU Script, invalid field names

RECEIVE
See RMU Script, invalid field names
RECONNECT
See RMU Script, invalid field names
RECORD
See RMU Script, invalid field names
RECORD-NAME
See RMU Script, invalid field names
RECORDING
See RMU Script, invalid field names
RECORDS
See RMU Script, invalid field names
REDEFINES
See RMU Script, invalid field names
REEL
See RMU Script, invalid field names
REFERENCE
See RMU Script, invalid field names
REFERENCES
See RMU Script, invalid field names
RELATION
See RMU Script, invalid field names
RELATIVE
See RMU Script, invalid field names
RELEASE
See RMU Script, invalid field names
RELOAD
See RMU Script, invalid field names
REMAINDER
See RMU Script, invalid field names
REMOVAL
See RMU Script, invalid field names
removing lines 21
RENAMES
See RMU Script, invalid field names
repeatable items, syntax diagrams xi
REPEATED
See RMU Script, invalid field names
REPLACE
See RMU Script, invalid field names
REPLACING
See RMU Script, invalid field names
REPORT
See RMU Script, invalid field names
REPORTING
See RMU Script, invalid field names
REPORTS
See RMU Script, invalid field names
REQUIRED
See RMU Script, invalid field names
RERUN
See RMU Script, invalid field names
RESERVE
See RMU Script, invalid field names
reserved
fields, COBOL 52
RESET
See RMU Script, invalid field names
RETAINING
See RMU Script, invalid field names
RETRIEVAL
See RMU Script, invalid field names
RETURN
See RMU Script, invalid field names
RETURN-CODE
STOP statement 49
system-defined field, description 51

REVERSE-VIDEO
See RMU Script, invalid field names
REVERSED
See RMU Script, invalid field names
REWIND
See RMU Script, invalid field names
REWRITE
See RMU Script, invalid field names
RF
See RMU Script, invalid field names
RH
See RMU Script, invalid field names
RIGHT
See RMU Script, invalid field names
RIGHT-JUSTIFY
See RMU Script, invalid field names
RMU
compiler generated messages 59
default
library locator table 13
options table 11
features 1
how it works 1
installation 11
introduction 1
libraries 11
messages
compiler generated 59
runtime, error 59
reserved words 16
running
in link and go mode 6
JCL, supplied with RMU 3
with compiled RMU Script 6
without RMU Script program 5
runtime error messages 59
sections, description 17
ways of running 3
working with 3
RMU Script
available jobs 5
coding rules 18
compile and link 5
compiler jobs 5
compiling, required files 5
concepts 17
CSV document 21
debugging 30
example 19
HTML document
creating simple 24
creating with control breaks
selection tree 26
HTML document, decorating 29
I/O 17
invalid field names 52
language instruction reference 33
working with 17
RMUERR1
file description 8
link and go 6
required when compiling 6
RMULIST
description 8
link and go 6
required when compiling 6

ROLLBACK
 See RMU Script, invalid field names
 ROLLING
 See RMU Script, invalid field names
 ROUNDED
 See RMU Script, invalid field names
 RUN
 See RMU Script, invalid field names
 runtime problems 31

S

SAME
 See RMU Script, invalid field names
 SCREEN
 See RMU Script, invalid field names
 SD
 See RMU Script, invalid field names
 SEARCH
 See RMU Script, invalid field names
 SECTION
 See RMU Script, invalid field names
 sections, RMU 17
 SECURE
 See RMU Script, invalid field names
 SECURITY
 See RMU Script, invalid field names
 SEGMENT
 See RMU Script, invalid field names
 SEGMENT-LIMIT
 See RMU Script, invalid field names
 SEL
 See RMU Script, invalid field names
 SELECT
 See RMU Script, invalid field names
 SEND
 See RMU Script, invalid field names
 SENTENCE
 See RMU Script, invalid field names
 SEPARATE
 See RMU Script, invalid field names
 SEQUENCE
 See RMU Script, invalid field names
 sequence numbers, types 30
 SEQUENTIAL
 See RMU Script, invalid field names
 SERVICE
 See RMU Script, invalid field names
 SESSION-ID
 See RMU Script, invalid field names
 SET
 See RMU Script, invalid field names
 SHARED
 See RMU Script, invalid field names
 SHIFT-IN
 See RMU Script, invalid field names
 SHIFT-OUT
 See RMU Script, invalid field names
 SIGN
 See RMU Script, invalid field names
 SIZE
 See RMU Script, invalid field names
 SKIP1
 See RMU Script, invalid field names
 SKIP2
 See RMU Script, invalid field names

SKIP3
 See RMU Script, invalid field names
 SMP/E 11
 SORT
 See RMU Script, invalid field names
 SORT-CONTROL
 See RMU Script, invalid field names
 SORT-CORE-SIZE
 See RMU Script, invalid field names
 SORT-FILE-SIZE
 See RMU Script, invalid field names
 SORT-MERGE
 See RMU Script, invalid field names
 SORT-MESSAGE
 See RMU Script, invalid field names
 SORT-MODE-SIZE
 See RMU Script, invalid field names
 SORT-RETURN
 See RMU Script, invalid field names
 SOURCE
 See RMU Script, invalid field names
 SOURCE-COMPUTER
 See RMU Script, invalid field names
 SPACE
 See also RMU Script, invalid field names
 field name 57
 parameter, DEFINE statement 34
 SPACE-FILL
 See RMU Script, invalid field names
 SPACES
 See also RMU Script, invalid field names
 field name 57
 parameter, DEFINE statement 34
 SPECIAL-NAMES
 See RMU Script, invalid field names
 STANDARD
 See RMU Script, invalid field names
 STANDARD-1
 See RMU Script, invalid field names
 STANDARD-2
 See RMU Script, invalid field names
 STANDARD-3
 See RMU Script, invalid field names
 STANDARD-4
 See RMU Script, invalid field names
 START
 See RMU Script, invalid field names
 STARTING
 See RMU Script, invalid field names
 statement sequence numbers 30
 statements
 <docs> 36
 <object> 35
 <page_end> 38
 <page_top> 37
 <style> 35
 assignment 38
 BYPASS 21, 24, 26, 41
 CALL 42
 COBOL 52
 CONTINUE 42
 CONTROL 26, 43
 DEFINE 26, 34
 DISPLAY 44
 DO 44

statements (*continued*)
 docs_end 37
 ELSE 47
 END-DO 44
 END-EVALUATE 45
 END-IF 47
 END-PROC 48
 EVALUATE 24, 26, 45
 IF 47
 PARAM 24, 26, 33
 PERFORM 47
 PROC 48
 PROCESS 49
 STOP 49
 STRING 50
 statements_1, parameter, IF statement 47
 statements_2, parameter, IF statement 47
 STATUS
 See RMU Script, invalid field names
 STDERR
 file description 8
 publishing to z/OS UNIX 6
 STDOUT
 file description 8
 publishing to z/OS UNIX 6
 STOP
 See RMU Script, invalid field names
 STOP statement 49
 STORE
 See RMU Script, invalid field names
 STRING
 See also RMU Script, invalid field names
 field name 57
 statement 50
 STYLE
 See also RMU Script, invalid field names
 field name 57
 option 3
 style statement 35
 SUB-QUEUE-1
 See RMU Script, invalid field names
 SUB-QUEUE-2
 See RMU Script, invalid field names
 SUB-QUEUE-3
 See RMU Script, invalid field names
 SUB-SCHEMA
 See RMU Script, invalid field names
 SUBFILE
 See RMU Script, invalid field names
 SUBPROGRAM
 See RMU Script, invalid field names
 SUBTRACT
 See RMU Script, invalid field names
 SUM
 See RMU Script, invalid field names
 SUPPRESS
 See RMU Script, invalid field names
 SVC99 parameter 14
 SWITCH
 See RMU Script, invalid field names
 SWITCH-1
 See RMU Script, invalid field names
 SWITCH-2
 See RMU Script, invalid field names

SWITCH-3
See RMU Script, invalid field names
 SWITCH-4
See RMU Script, invalid field names
 SWITCH-5
See RMU Script, invalid field names
 SWITCH-6
See RMU Script, invalid field names
 SWITCH-7
See RMU Script, invalid field names
 SWITCH-8
See RMU Script, invalid field names
 symbol, &sys1 14
 SYMBOLIC
See RMU Script, invalid field names
 SYNC
See RMU Script, invalid field names
 SYNCHRONIZED
See RMU Script, invalid field names
 syntax diagrams, how to read xi
 SYSDATE or SYSDATE-E, system-defined
 field, description 51
 SYSDATE-9, system-defined field,
 description 51
 SYSDATE-LONG or SYSDATE-LONG-E,
 system-defined field, description 52
 SYSDATE-LONG-9, system-defined field,
 description 52
 SYSIN
 compiling RMU Script 6
 file description 8
 link and go 6
 link and go mode 4
 not coding in JCL 3
 SYSLMOD, required when compiling 6
 SYSOUT
 DISPLAY statement 44
 file description 8
 link and go 6
 running with compiled RMU
 Script 6
 running without RMU Script 5
 SYSPRDD=&DDname option 14
 system
 defined fields 51
 information 15
 SYSTIME-9, system-defined field,
 description 52
 SYSTIME, system-defined field,
 description 52

T

TABLE
See RMU Script, invalid field names
 table, FZHPROCS 14
 TALLY
See RMU Script, invalid field names
 TALLYING
See RMU Script, invalid field names
 TAPE
See RMU Script, invalid field names
 TENANT
See RMU Script, invalid field names
 TERMINAL
See RMU Script, invalid field names

TERMINATE
See RMU Script, invalid field names
 TEST
See RMU Script, invalid field names
 TEXT
See RMU Script, invalid field names
 text, highlighting 30
 THAN
See RMU Script, invalid field names
 THEN
See RMU Script, invalid field names
 THROUGH
See RMU Script, invalid field names
 THRU
See RMU Script, invalid field names
 TIME
See RMU Script, invalid field names
 TIMEOUT
See RMU Script, invalid field names
 TIMES
See RMU Script, invalid field names
 TITLE
See RMU Script, invalid field names
 TO
See RMU Script, invalid field names
 TOP
See RMU Script, invalid field names
 TRACE
See RMU Script, invalid field names
 trademarks 66
 TRAILING
See RMU Script, invalid field names
 TRAILING-SIGN
See RMU Script, invalid field names
 TRANSACTION
See RMU Script, invalid field names
 TRANSCEIVE
See RMU Script, invalid field names
 TRUE
See RMU Script, invalid field names
 TURF option 3, 13, 30, 36
 TWORk parameter 14
 TYPE
See RMU Script, invalid field names

U

UNDERLINE
See RMU Script, invalid field names
 UNEQUAL
See RMU Script, invalid field names
 UNIT
See RMU Script, invalid field names
 UNIX, setting up environment 14
 UNLOCK
See RMU Script, invalid field names
 UNSTRING
See RMU Script, invalid field names
 UNTIL
See also RMU Script, invalid field
 names
 field name 57
 parameter, DO statement 45
 UP
See RMU Script, invalid field names
 UPDATE
See RMU Script, invalid field names

UPON
See RMU Script, invalid field names
 USAGE
See RMU Script, invalid field names
 USAGE-MODE
See RMU Script, invalid field names
 USE
See RMU Script, invalid field names
 USER
See RMU Script, invalid field names
 USING
See RMU Script, invalid field names

V

VAL
See RMU Script, invalid field names
 VALID
See RMU Script, invalid field names
 VALIDATE
See RMU Script, invalid field names
 VALUE
See RMU Script, invalid field names
 VALUES
See RMU Script, invalid field names
 VARCHAR
See RMU Script, invalid field names
 VARIABLE
See RMU Script, invalid field names
 variables, syntax diagrams xi
 VARYING
See RMU Script, invalid field names
 verbs, COBOL 52

W

WAIT
See RMU Script, invalid field names
 WHEN
See RMU Script, invalid field names
 WHEN-COMPILED
See RMU Script, invalid field names
 WHILE, parameter, DO statement 45
 WITH
See RMU Script, invalid field names
 WITHIN
See RMU Script, invalid field names
 WORDS
See RMU Script, invalid field names
 working with RMU 3
 WORKING-STORAGE
See RMU Script, invalid field names
 WRITE
See RMU Script, invalid field names
 WRITE-ONLY
See RMU Script, invalid field names

Z

z/OS Enterprise COBOL 13
 z/OS server
 publishing to 14
 setting up environment 14
 ZERO
See also RMU Script, invalid field
 names

ZERO (*continued*)
 parameter, DEFINE statement 34
ZERO-FILL
 See RMU Script, invalid field names
ZEROES
 See also RMU Script, invalid field
 names
 field name 58
 parameter, DEFINE statement 34
ZEROS
 See also RMU Script, invalid field
 names
 field name 58

Readers' Comments — We'd Like to Hear from You

Report Modernization Utility for z/OS and OS/390
User's Guide and Reference
Version 1 Release 1

Publication No. SC19-2726-00

We appreciate your comments about this publication. Please comment on specific errors or omissions, accuracy, organization, subject matter, or completeness of this book. The comments you send should pertain to only the information in this manual or product and the way in which the information is presented.

For technical questions and information about products and prices, please contact your IBM branch office, your IBM business partner, or your authorized remarketer.

When you send comments to IBM, you grant IBM a nonexclusive right to use or distribute your comments in any way it believes appropriate without incurring any obligation to you. IBM or any other organizations will only use the personal information that you supply to contact you about the issues that you state on this form.

Comments:

Thank you for your support.

Send your comments to the address on the reverse side of this form.

If you would like a response from IBM, please fill in the following information:

Name

Address

Company or Organization

Phone No.

E-mail address



Cut or Fold
Along Line

Fold and Tape

Please do not staple

Fold and Tape




NO POSTAGE
NECESSARY
IF MAILED IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST-CLASS MAIL PERMIT NO. 40 ARMONK, NEW YORK

POSTAGE WILL BE PAID BY ADDRESSEE

IBM Corporation
Reader Comments
DTX/E269
555 Bailey Avenue
San Jose, CA
U.S.A. 95141-9989



Fold and Tape

Please do not staple

Fold and Tape

Cut or Fold
Along Line



Program Number: 5697-P33

Printed in USA

SC19-2726-00



Spine information:



Report Modernization Utility for
z/OS and OS/390

Report Modernization Utility for z/OS and OS/390
V1R1 User's Guide

Version 1
Release 1