

IBM Spectrum Protect Plus
Version 10.1.2

REST API Developer Guide



Note:

Before you use this information and the product it supports, read the information in "Notices" at the end of this publication.

This edition applies to version 10, release 1, modification 2 of IBM Spectrum Protect Plus (product number 5737-F11) and to all subsequent releases and modifications until otherwise indicated in new editions.

© Copyright IBM Corporation 2017, 2018.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Table of Contents

- 1. Welcome 2
- 2. Quick Start 3
- 3. Conventions 4
 - 3.1. JSON 4
 - 3.2. HATEOAS 4
 - 3.3. Discoverability Links 4
 - 3.4. Predefined Name Links 4
 - 3.5. Headers 5
 - 3.6. Verbs 6
 - 3.7. Status Codes 6
 - 3.8. Pagination 7
 - 3.9. Sorting 7
 - 3.10. Filtering 7
 - 3.11. Embedded Objects 8
 - 3.12. Actions 8
- 4. Examples 9
 - 4.1. Getting a Session ID 9
 - 4.2. Assign VM to a Policy 13
 - 4.3. Create an SLA Policy 15
 - 4.4. Delete an SLA Policy 21
 - 4.5. Get Job Sessions 22
 - 4.6. Start a Job 27
 - 4.7. Cancel a Job 39
 - 4.8. Register a Hypervisor 45
 - 4.9. Register an Application 50
 - 4.10. Delete a vCenter 54
 - 4.11. Restore a Virtual Machine 55
 - 4.12. Generate Reports 69
 - 4.13. Generate VM Backup History Report: Successful 78
 - 4.14. Generate VM Backup History Report: Unsuccessful 91



This document presents API usage guidelines. The examples are for illustration only and should not be explicitly used for production.

Chapter 1. Welcome

The documentation in this Developer Guide provides information for the IBM Spectrum Protect™ Plus API based on the RESTful framework. Use this RESTful API to connect your applications to product components in order to query information about objects and to perform basic operations by using HTTP protocols and the principles of RESTful API.

This application programming interface uses RESTful architecture designed to work with web-based applications in a simplified way, by using four basic HTTP methods for applications to interact with: GET, POST, PUT, and DELETE.

This Developer Guide contains several RESTful API interaction examples that demonstrate basic functions such as getting a session ID, assigning a VM, and starting a job. Additionally, this guide discusses RESTful API conventions and security concepts.



The material in the Developer Guide or any accompanying publication has not been submitted to any formal IBM test and is published AS IS. It has not been the subject of rigorous review. IBM assumes no responsibility for its accuracy or completeness. The use of this information or the implementation of any of these techniques is a client responsibility and depends upon the client's ability to evaluate and integrate them into the client's operational environment.



To keep the text in the examples brief, some of the error checking has been omitted.

Chapter 2. Quick Start

This is a simple example of interacting with the API using curl to retrieve a session ID.

```
curl -X POST -i -H 'Accept:application/json' -H 'Content-type:application/json' --user  
"username:password" https://<hostname|IP>/api/endeavour/session
```

Chapter 3. Conventions

The following are conventions that cover HATEOAS, Pagination, Filtering, etc.

3.1. JSON

RESTful API requests and responses are in JSON format.

3.2. HATEOAS

Responses also support Hypermedia as the Engine of Application State. The main component of HATEOAS is the notion of discoverability. The client application must discover, via Hypermedia or response links, resources that are accessible within the response. This means the client does not require up front knowledge of methods of resource interaction.

HATEOAS is primarily driven by the response's link format. The examples in this document offer a sense of how the RESTful API is designed and what responses are expected.

3.3. Discoverability Links

```
{
  "links": {
    "<namedLink>": {
      "rel": "self|up|create|update|delete|related|action"
    }
  }
}
```

3.4. Predefined Name Links

This example assumes that users are configured within the system. By default, there is a user predefined. Consult the documentation for user credential specifics.

3.4.1. self

```
{
  "self": {
    "rel": "self",
    "href": "https://<hostname|IP>/api/endeavour/policy/1001"
  }
}
```

3.4.2. up

Returns one level up on directory path.

```
{
  "up": {
    "rel": "up",
    "href": "https://<hostname|IP>/api/endeavour/policy"
  }
}
```

3.4.3. create

```
{
  "create": {
    "rel": "create",
    "href": "https://<hostname|IP>/api/endeavour/policy"
  }
}
```

3.4.4. edit

```
{
  "edit": {
    "rel": "edit",
    "href": "https://<hostname|IP>/api/endeavour/policy/1001"
  }
}
```

3.4.5. delete

```
{
  "delete": {
    "rel": "delete",
    "href": "https://<hostname|IP>/api/endeavour/policy/1001"
  }
}
```

3.5. Headers

The following headers are required for every RESTful API operation:

Header	Description
x-endeavour-sessionid	with a valid sessionid value.
x-endeavour-auditrequest	with the value set to true or false; true indicates that the call is tracked in the audit log.
Content-Type	with the value set to application/json.
Accept	with the value set to application/json.

3.6. Verbs

This product tries to adhere as closely as possible to standard HTTP and REST conventions in its use of HTTP verbs.

Verb	Description
GET	Used to retrieve a resource
POST	Used to create a new resource
PUT	Used to update an existing resource, including partial updates
DELETE	Used to delete an existing resource

3.7. Status Codes

This product tries to adhere as closely as possible to standard HTTP and REST conventions in its use of HTTP status codes.

Status code	Usage
200 OK	The request completed successfully
201 Created	A new resource has been created successfully. The resource's URI is available from the response's Location header
204 No Content	An update to an existing resource has been applied successfully
400 Bad Request	The request was malformed. The response body will include an error providing further information
401 Unauthorized	Login attempt with invalid credentials
403 Forbidden	Generally related to permissioning through Role Base Access Control

Status code	Usage
404 Not Found	The requested resource did not exist
405 Method Not Allowed	URL is unsupported
500 Unrecoverable Error	Diagnosed in Virgo log
503 Service Unavailable	This status is returned when too many requests are going to the same controller

For additional information, visit https://en.wikipedia.org/wiki/List_of_HTTP_status_codes.

3.8. Pagination

Many GET RESTful APIs support pagination using the following syntax:

GET

```
https://<hostname|IP>/api/endeavour/trigger?pageSize=25&pageStartIndex=50
```

3.9. Sorting

Many GET RESTful APIs support sorting using the following syntax, without the line breaks:

GET

```
https://<hostname|IP>/api/endeavour/trigger?sort=[{"property":"name","direction":"ASC"},{"property":"date","direction":"DESC"}]
```

3.10. Filtering

Filtering of results is supported. The following is an example of filtering schedules, without the line breaks:

GET

```
https://<hostname|IP>/api/endeavour/trigger?filterType=all&filter=[{"property":"name","op":"=","value":"Daily"},{"property":"creationDate","op":"<","value":"1234567890"}]
```



filterType can either be all or any. All must match all criteria, any must match any criteria. Also, operator is a SQL operator, such as <, <=, =, !=, >=, >, <>, IN. If operator is not specified, = is the default value.

3.11. Embedded Objects

You can embed a related link in the response. To do this, add the embed query parameter. Following is the parameter format:

GET

```
https://<hostname|IP>/api/endeavour/job?embed=(policy)
```



This eliminates round trips to the server when retrieving job resources that are tied to specific policies. An embedded policy object can be returned for each job within the response of a job list request.

3.12. Actions

RESTful API leverages HTTP verbs to perform resource-based operations. See [Verbs](#) in this document. The "POST" verb along with a JSON request body manages the execution of various actions. The action is specified as a query parameter called action on the URI. The following is an example of performing an action:

POST

```
https://<hostname|IP>/api/hypervisor/{hypervisorId}/vm/{vmid}?action=createSnapshot
```

3.12.1. Action Request Body

```
{  
  "name": "snapshot.1"  
}
```



An Action Request Body is not required for all action calls. A "schema" link can be used to provide action context.

Chapter 4. Examples

The following sections walk through the APIs used to accomplish implementing various operations. All APIs, except a POST to the session endpoint, require a session id passed in the header, so we start with getting a session id. The next example shows how to perform search operations with the session id. This is followed by a set of examples that show how to programmatically register a resource provider, create a policy with it, use the policy to create a job, run the job and then monitor it.

4.1. Getting a Session ID

This example assumes that users have been configured within the system. By default there is a user predefined within IBM Spectrum Protect Plus. Consult the IBM Spectrum Protect Plus documentation for user credential specifics.

4.1.1. Headers

The following headers are required for every RESTful API operation:

Header	Description
x-endeavour-sessionid	with a valid sessionid value.
x-endeavour-auditrequest	with the value set to true or false; true indicates that the call is tracked in the audit log.
Content-Type	with the value set to application/json.
Accept	with the value set to application/json.

4.1.2. Endpoint

POST	/api/endeavour/session
------	------------------------

This product uses HTTP's basic authentication mechanism where the user name and password should be sent in the Authorization header. The user name and password need to be base64 encoded. When a POST operation to the endpoint above is performed which includes a valid Authorization header, the corresponding response will contain a session-id, which can then be used for subsequent API calls.

4.1.3. Request

The following example provides the steps for establishing the session-id using Google's Chrome Postman rest client. You can also refer to the **Quick Start** section at the beginning of the document to see an example using **curl**.

1) In the Basic Auth tab enter the username and password.

- 2) Click the Refresh headers button. A base encoded string will be produced.
- 3) Enter the following URL : <https://ipaddress/api/endeavour/session>
- 4) Select the POST operation
- 5) With the Authorization header set you can now hit send, which will execute a Post operation against the <https://ipaddress/api/endeavour/session> endpoint.
- 6) The following response, which includes the session-id value, is returned.

4.1.4. Response

```

{
  "sessionid": "1b78453f1256c700",
  "user": {
    "links": {
      "self": {
        "rel": "self",
        "href": "https://<hostname|IP>/api/endeavour/user/1000"
      },
      "up": {
        "rel": "up",
        "href": "https://<hostname|IP>/api/endeavour/user"
      },
      "edit": {
        "rel": "update",
        "href": "https://<hostname|IP>/api/endeavour/user/1000"
      },
      "roles": {
        "rel": "related",
        "href": "https://<hostname|IP>/api/endeavour/user/1000/role"
      },
      "changePassword": {
        "rel": "action",
        "href": "https://<hostname|IP>/api/endeavour/user/1000?action=changePassword"
      }
    },
    "name": "admin",
    "type": "NATIVE_USER",
    "roles": [
      {
        "links": {
          "self": {
            "rel": "self",
            "href": "https://<hostname|IP>/api/endeavour/role/1000"
          },
          "up": {
            "rel": "up",
            "href": "https://<hostname|IP>/api/endeavour/role"
          }
        },
        "name": "SUPERUSER",
        "id": "1000"
      }
    ],
    "id": "1000"
  }
}

```

The response contains the session id as well as the information for the logged in user. This information is exactly the same as that returned by a GET call against the following URI:

```
/api/endeavour/user/{userID}.
```

All further requests must include the session-id in the custom header x-endeavour-sessionid.

4.2. Assign VM to a Policy

4.2.1. Request

Assign VM to a Policy: Request Example

POST:

```
https://<hostname|IP>/ngp/hypervisor?action=applySLAPolicies
```

4.2.2. Request Body

Assign VM to a Policy: Request Body Parameters

Property	Sample Value	Element of	Description
"subtype"	"vmware"		Type of hypervisor either vmware or Hyper-v
"version"	"1.0"		
"resources"			
"href"	"https://<hostname>/api/hypervisor/1003?from=hello"	"resources"	Link to resource
"id"	"1003"	"resources"	ID of resource
"metadataPath"	"/MS:1003"	"resources"	
"slapolicies"			
"href"	"https://<hostname>/api/spec/storageprofile/2103"	"slapolicies"	System generated id for SLA Policy
"id"	"2103"	"slapolicies"	ID of SLA policy to be attached with
"name"	"Bronze"	"slapolicies"	Name of the SLA Policy

Assign VM to a Policy: Request Body Example

```
{
  "subtype": "vmware",
  "version": "1.0",
  "resources": [
    {
      "href": "https://<hostname|IP>/api/hypervisor/1003?from=hlo",
      "id": "1003",
      "metadataPath": "/MS:1003"
    }
  ],
  "slapolicies": [
    {
      "href": "https://<hostname|IP>/api/spec/storageprofile/2103",
      "id": "2103",
      "name": "Bronze"
    }
  ]
}
```

4.2.3. Response

Assign VM to a Policy: Response Example

```
{"statusCode":201,"response":null}
```

4.3. Create an SLA Policy

4.3.1. Request

Create an SLA Policy: Request Example

```
POST:  
https://<hostname|IP>/ngp/slapolicy
```

4.3.2. Request Body

Create an SLA Policy: Request Body Parameters

Property	Sample Value	Element of	Description
"name"	"jltest"		Name of SLA
"version"	"1.0"		
"spec"			Specifications list of json type
"simple"	true	"spec"	
"subpolicy"		"spec"	
"type"	"REPLICATION"	"subpolicy"	Describes the type of operation for SLA
"software"	true	"subpolicy"	If set to true: (which is default), then it will perform a VMCopy, if set to false, it will perform replication.
"retention"		"subpolicy"	Parent element of age, site and software
"age"	15	"retention"	Number of backup days to retain the primary copy
"trigger"		"subpolicy"	Parent element of frequency, trigger and type
"frequency"	1	"trigger"	Number of times data has to be retained

Property	Sample Value	Element of	Description
"type"	"DAILY"	"trigger"	Describes the occurrence of trigger action
"activateDate"	1508299200000	"trigger"	Creation date for SLA Policy
"site"	"Primary"	"subpolicy"	

Create an SLA Policy: Request Body Example

```
{
  "name": "jltest",
  "version": "1.0",
  "spec": {
    "simple": true,
    "subpolicy": [
      {
        "type": "REPLICATION",
        "software": true,
        "retention": {
          "age": 15
        },
        "trigger": {
          "frequency": 1,
          "type": "DAILY",
          "activateDate": 1508299200000
        },
        "site": "Primary"
      }
    ]
  }
}
```

4.3.3. Response

Create an SLA Policy: Response Body Parameters

Property	Sample Value	Element of	Description
"statusCode"	201		Indicates if SLA was created or not
"response"			Contains all the information about SLA

Property	Sample Value	Element of	Description
"spec"		"response"	json array of simple and subpolicy array
"simple"	true	"spec"	
"subpolicy"			Parent element of retention and trigger
"name"	"VM Replication0"	"subpolicy"	Name of SLA
"description"	"VM Replication0"	"subpolicy"	
"type"	"VMCOPY"	"subpolicy"	Type can be either VMcopy or replication.
"spec"		"subpolicy"	Parent element of subpolicy
"source"		"spec"	Describes the where SLA policy has been applied
"primarysource"	true	"source"	
"name"	""	"source"	
"option"		"subpolicy"	
"retention"		"option"	Describes the age
"age"	15	"retention"	Number of backup days to retain the primary copy
"maxquotasize"	0	"option"	For future use
"maxquotanumber"	0	"option"	For future use
"subpolicylabel"	"VM Replication0"	"option"	For future use
"disablesystemsnapshot policy"	false	"option"	For future use
"skipreadonlydatastores"	true	"option"	For future use
"label"	""	"option"	For future use
"targetDatastoreType"	"NFS"	"option"	For future use
"vmcopytargetvolumeprefix"	""	"option"	For future use
"fullcopymethod"	"clone"	"option"	For future use

Property	Sample Value	Element of	Description
"destination"		"subpolicy"	Parent element of target
"target"		"destination"	Parent element of href, resource type and id
"href"	"https://<hostname>/api/site/1000"	"target"	Link where the snapshot or copy is stored
"resourceType"	"site"	"target"	
"id"	"1000"	"target"	System generated value
"trigger"		"spec"	Parent element of frequency, trigger and type
"frequency"	1	"trigger"	Number of times data has to be retained
"type"	"DAILY"	"trigger"	Describes the occurrence of trigger action
"activateDate"	1508299200000	"trigger"	Creation date for SLA Policy
"id"	"2107"	"spec"	
"description"	null	"response"	
"id"	"2104"	"response"	ID of SLA
"name"	"jlttest"	"response"	Name of the SLA
"type"	null	"response"	
"subType"	null	"response"	
"rbacPath"	"root:0/storageprofile:0/storageprofiletype:dummy/storageprofile:2104"	"response"	

Create an SLA Policy: Response Example

```
{
  "statusCode": 201,
  "response": {
    "links": {
      "self": {
        "rel": "self",
        "href": "https://<hostname|IP>/api/spec/storageprofile/2104"
      }
    }
  }
}
```

```

    },
    "up": {
      "rel": "up",
      "href": "https://<hostname|IP>/api/spec/storageprofile"
    },
    "edit": {
      "rel": "edit",
      "href": "https://<hostname|IP>/api/spec/storageprofile/2104"
    },
    "delete": {
      "rel": "delete",
      "href": "https://<hostname|IP>/api/spec/storageprofile/2104"
    }
  },
  "spec": {
    "simple": true,
    "subpolicy": [
      {
        "name": "VM Replication0",
        "description": "VM Replication0",
        "type": "VMCOPY",
        "spec": {
          "source": {
            "primarysource": true,
            "name": ""
          },
          "option": {
            "retention": {
              "age": 15
            },
            "maxquotasize": 0,
            "maxquotanumber": 0,
            "subpolicylabel": "VM Replication0",
            "disablesystemsnapshotpolicy": false,
            "skipreadonlydatastores": true,
            "label": "",
            "targetDatastoreType": "NFS",
            "vmcopytargetvolumeprefix": "",
            "fullcopymethod": "clone"
          },
          "destination": {
            "target": {
              "href": "https://<hostname|IP>/api/site/1000",
              "resourceType": "site",
              "id": "1000"
            }
          }
        }
      }
    ]
  },
},

```

```
    "trigger": {
      "frequency": 1,
      "type": "DAILY",
      "activateDate": 1508299200000
    },
    "id": "2107"
  }
]
},
"description": null,
"id": "2104",
"name": "jlttest",
"type": null,
"subType": null,
"rbacPath": "root:0/storageprofile:0/storageprofiletype:dummy/storageprofile:2104"
}
}
```

4.4. Delete an SLA Policy

4.4.1. Request

Delete an SLA Policy: Request Example

```
DELETE:  
https://<hostname|IP>/ngp/slapolicy/JLTEST3
```

4.5. Get Job Sessions

4.5.1. Request

Get Job Sessions: Request Example

```
GET:  
https://<hostname|IP>/api/endeavour/job
```

4.5.2. Response

Get Job Sessions: Response Example

```
{  
  "links": {  
    "self": {  
      "rel": "self",  
      "href": "https://<hostname|IP>/api/endeavour/job"  
    },  
    "up": {  
      "rel": "up",  
      "href": "https://<hostname|IP>/api/endeavour/job"  
    },  
    "create": {  
      "rel": "create",  
      "href": "https://<hostname|IP>/api/endeavour/job"  
    },  
    "stats": {  
      "rel": "stats",  
      "href": "https://<hostname|IP>/api/endeavour/job/stats"  
    }  
  },  
  "jobs": [  
    {  
      "links": {  
        "self": {  
          "rel": "self",  
          "href": "https://<hostname|IP>/api/endeavour/job/1007"  
        },  
        "up": {  
          "rel": "up",  
          "href": "https://<hostname|IP>/api/endeavour/job"  
        },  
        "delete": {  
          "rel": "delete",
```

```

    "href": "https://<hostname|IP>/api/endeavour/job/1007"
  },
  "policyedit": {
    "rel": "update",
    "href": "https://<hostname|IP>/api/endeavour/policy/1007"
  },
  "policydelete": {
    "rel": "delete",
    "href": "https://<hostname|IP>/api/endeavour/policy/1007"
  },
  "edit": {
    "rel": "update",
    "href": "https://<hostname|IP>/api/endeavour/job/1007"
  },
  "policy": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/endeavour/policy/1007"
  },
  "triggers": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/endeavour/job/1007/trigger"
  },
  "jobsessions": {
    "rel": "related",
    "href":
    "https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22jobId%22,%
    22value%22:%221007%22%7D%5D"
  },
  "activejobsessions": {
    "rel": "related",
    "href":
    "https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%
    22op%22:%22%3D%22,%22value%22:%22active%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22
    %3D%22,%22value%22:%221007%22%7D%5D"
  },
  "pendingjobsessions": {
    "rel": "related",
    "href":
    "https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%
    22op%22:%22%3D%22,%22value%22:%22pending%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22
    %3D%22,%22value%22:%221007%22%7D%5D"
  },
  "historicaljobsessions": {
    "rel": "related",
    "href":
    "https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%
    22op%22:%22%3D%22,%22value%22:%22history%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22
    %3D%22,%22value%22:%221007%22%7D%5D"
  }

```

```

    },
    "livejobsessions": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%22op%22:%22%3D%22,%22value%22:%22live%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22%3D%22,%22value%22:%221007%22%7D%5D"
    },
    "stats": {
      "rel": "related",
      "href": "https://<hostname|IP>/api/endeavour/jobsession/stats/jobid/1007"
    },
    "firetimes": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/firetime?filter=%5B%7B%22property%22:%22jobId%22,%22value%22:%221007%22%7D%5D"
    },
    "start": {
      "schema":
"https://<hostname|IP>/api/endeavour/job/1007/schema?actionname=start",
      "title": "Start",
      "rel": "action",
      "href":
"https://<hostname|IP>/api/endeavour/job/1007?action=start&actionname=start"
    },
    "hold Schedule": {
      "rel": "action",
      "href": "https://<hostname|IP>/api/endeavour/job/1007?action=hold"
    },
    "status": {
      "rel": "related",
      "href": "https://<hostname|IP>/api/endeavour/job/1007/status"
    },
    "lastrun": {
      "rel": "related",
      "href": "https://<hostname|IP>/api/endeavour/jobsession/1519534800056"
    },
    "lastrunlog": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/log/job?filter=%5B%7B%22property%22:%22jobsessionId%22,%22value%22:%221519534800056%22%7D%5D"
    }
  },
  "name": "vmware_Gold",
  "description": "",
  "policyId": "1007",

```

```

"policyName": "vmware_Gold",
"type": "protection",
"subType": "vmware",
"serviceId": "serviceprovider.protection.hypervisor",
"displayName": "Hypervisor Backup",
"status": "IDLE",
"lastSessionStatus": "FAILED",
"triggerIds": [
  "1017",
  "1018"
],
"triggerData": [
  {
    "triggerId": "1017",
    "triggerInfo": {
      "subpolicy_id": "VM Replication0(2103)"
    }
  },
  {
    "triggerId": "1018",
    "triggerInfo": {
      "subpolicy_id": "Backup Storage Replication(2103)"
    }
  }
],
"lastRunTime": 1519534802983,
"nextFireTime": 1519621200000,
"lastSessionDuration": 30782,
"tenantId": 1000,
"actions": null,
"statistics": null,
"lastrun": {
  "sessionId": "1519534800056",
  "jobName": "vmware_Gold",
  "type": "protection",
  "subType": "vmware",
  "serviceId": "serviceprovider.protection.hypervisor",
  "start": 1519534802983,
  "end": 1519534833765,
  "duration": 30782,
  "status": "FAILED",
  "results": null,
  "properties": {
    "statistics": [
      {
        "resourceType": "vm",
        "total": 1,
        "success": 0,

```

```
    "failed": 1
  },
  {
    "resourceType": "datastore",
    "total": 1,
    "success": 0,
    "failed": 0
  }
]
},
"numTasks": 2,
"lastUpdate": 1519534833775,
"percent": 60,
"policySnapshot": null
},
"id": "1007"
},
...
],
"total": 12,
"page": 1
}
```

4.6. Start a Job

4.6.1. Attaining the Job ID

The POST request shown later in this topic requires a job id as an input parameter. To retrieve the job id and other job information given only a policy name, such as "vmware_Gold" in this example, use this GET request:

```
GET:
https://<hostname|IP>/api/endeavour/job?filter=[{"property":"name","op":"="
,"value":"vmware_Gold"}]
```

The associated response follows. The response reports job specific details including job id.

```
{
  "links": {
    "self": {
      "rel": "self",
      "href":
"https://<hostname|IP>/api/endeavour/job?pageSize=50&pageStartIndex=0&filter=%5B%7B%22pro
perty%22:%22name%22,%22op%22:%22%3D%22,%22value%22:%22vmware_Gold%22%7D%5D"
    },
    "up": {
      "rel": "up",
      "href": "https://<hostname|IP>/api/endeavour/job"
    },
    "create": {
      "rel": "create",
      "href": "https://<hostname|IP>/api/endeavour/job"
    },
    "stats": {
      "rel": "stats",
      "href": "https://<hostname|IP>/api/endeavour/job/stats"
    }
  },
  "jobs": [
    {
      "links": {
        "self": {
          "rel": "self",
          "href": "https://<hostname|IP>/api/endeavour/job/1343"
        },
        "up": {
          "rel": "up",
          "href": "https://<hostname|IP>/api/endeavour/job"
        }
      }
    }
  ]
}
```

```

    },
    "delete": {
      "rel": "delete",
      "href": "https://<hostname|IP>/api/endeavour/job/1343"
    },
    "policyedit": {
      "rel": "update",
      "href": "https://<hostname|IP>/api/endeavour/policy/1347"
    },
    "policydelete": {
      "rel": "delete",
      "href": "https://<hostname|IP>/api/endeavour/policy/1347"
    },
    "edit": {
      "rel": "update",
      "href": "https://<hostname|IP>/api/endeavour/job/1343"
    },
    "policy": {
      "rel": "related",
      "href": "https://<hostname|IP>/api/endeavour/policy/1347"
    },
    "triggers": {
      "rel": "related",
      "href": "https://<hostname|IP>/api/endeavour/job/1343/trigger"
    },
    "jobsessions": {
      "rel": "related",
      "href":
        "https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22jobId%22,%
        22value%22:%221343%22%7D%5D"
    },
    "activejobsessions": {
      "rel": "related",
      "href":
        "https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%
        22op%22:%22%3D%22,%22value%22:%22active%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%2
        %3D%22,%22value%22:%221343%22%7D%5D"
    },
    "pendingjobsessions": {
      "rel": "related",
      "href":
        "https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%
        22op%22:%22%3D%22,%22value%22:%22pending%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%2
        2%3D%22,%22value%22:%221343%22%7D%5D"
    },
    "historicaljobsessions": {
      "rel": "related",
      "href":

```

```

"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%22op%22:%22%3D%22,%22value%22:%22history%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22%3D%22,%22value%22:%221343%22%7D%5D"
  },
  "livejobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%22op%22:%22%3D%22,%22value%22:%22live%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22%3D%22,%22value%22:%221343%22%7D%5D"
  },
  "stats": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/endeavour/jobsession/stats/jobid/1343"
  },
  "firetimes": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/firetime?filter=%5B%7B%22property%22:%22jobId%22,%22value%22:%221343%22%7D%5D"
  },
  "start": {
    "schema":
"https://<hostname|IP>/api/endeavour/job/1343/schema?actionname=start",
    "title": "Start",
    "rel": "action",
    "href":
"https://<hostname|IP>/api/endeavour/job/1343?action=start&actionname=start"
  },
  "hold Schedule": {
    "rel": "action",
    "href": "https://<hostname|IP>/api/endeavour/job/1343?action=hold"
  },
  "status": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/endeavour/job/1343/status"
  },
  "lastrun": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/endeavour/jobsession/1510154602082"
  },
  "lastrunlog": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/log/job?filter=%5B%7B%22property%22:%22jobsessionId%22,%22value%22:%221510154602082%22%7D%5D"
  }
},

```

```

"name": "vmware_Gold",
"description": "Auto-generated job for Policy vmware_Gold",
"policyId": "1347",
"policyName": "vmware_Gold",
"type": "protection",
"subType": "vmware",
"serviceId": "serviceprovider.protection.hypervisor",
"displayName": "Hypervisor Backup",
"status": "IDLE",
"lastSessionStatus": "FAILED",
"triggerIds": [
  "1006"
],
"triggerData": [
  {
    "triggerId": "1006",
    "triggerInfo": {
      "storageworkflowid": "6",
      "storageworkflowname": "VADP"
    }
  }
],
"lastRunTime": 1510154608322,
"nextFireTime": 1510241002000,
"lastSessionDuration": 909,
"tenantId": 1000,
"actions": null,
"statistics": null,
"lastrun": {
  "sessionId": "1510154602082",
  "jobName": "vmware_Gold",
  "type": "protection",
  "subType": "vmware",
  "serviceId": "serviceprovider.protection.hypervisor",
  "start": 1510154608322,
  "end": 1510154609231,
  "duration": 909,
  "status": "FAILED",
  "results": null,
  "properties": {
    "statistics": []
  },
  "numTasks": 2,
  "lastUpdate": 1510154609241,
  "percent": 0,
  "policySnapshot": null
},
"id": "1343"

```

```

    }
  ],
  "total": 1,
  "page": 1

```

The following request and response pertain to starting a job.

4.6.2. Request

Start a Job: Request Example

```

POST:
https://<hostname|IP>/api/endeavour/job/1343?action=start&actionname=start

```

4.6.3. Response

Start a Job: Response Body Parameters

Property	Sample Value	Element of	Description
"name"	"vmware_for_vm_admin"		Name of the job
"description"	"Auto-generated job for Policy vmware_for_vm_admin"		Describes what the particular job does
"policyId"	"1011"		Policy associated with the job
"policyName"	"vmware_for_vm_admin"		Name of the policy
"type"		"protection"	
"subType"	"vmware"		Type of the resource
"serviceId"	"serviceprovider.protection.hypervisor"		
"displayName"	"Hypervisor Backup"		Targeted resource and Targeted job on which policy is applied
"status"	"RUNNING"		Indicates the status of the resource; it can be active or running

Property	Sample Value	Element of	Description
"lastSessionStatus"	null		Describes if the job was successful or failed
"triggerIds"	[]		
"triggerData"	[]		Trigger operation associated
"lastRunTime"	0		Time it was started
"nextFireTime"	null		Next scheduled time when policy should run
"lastSessionDuration"	null		Total time spent on a job
"tenantId"	1000		Identify the users uniquely; for future use
"actions"	null		Lifecycle triggers of the job / state of the job
"statistics"	null		Stats about the policy
"policy"			
"spec"		"response"	
"source"	[]	"spec"	
"storageworkflow"		"spec"	
"id"	"2102"	"storageworkflow"	Policy ID
"name"	"for_vm_admin"	"storageworkflow"	value of property name for a specific job
"href"	"//<hostname>/api/spec/storageprofile/2102"	"storageworkflow"	HATEOS link
"type"	Null	"storageworkflow"	
"option"		"spec"	
"maxtasks"	0	"option"	For future use
"vmsnapshot"		"option"	For future use
"takesnapshot"	false	"vmsnapshot"	For future use
"concurrentsnapshots on esx"	3	"vmsnapshot"	For future use
"includememory"	false	"vmsnapshot"	For future use
"consistency"	false	"vmsnapshot"	For future use

Property	Sample Value	Element of	Description
"consistencyvms"	[]	"vmsnapshot"	For future use
"scriptvms"	[]	"vmsnapshot"	For future use
"truncateapplicationlogs"	false	"vmsnapshot"	For future use
"skipreadonlydatastores"	true	"option"	
"notification"	[]	"spec"	
"lastrun"			Time the job ran last time
"sessionId"	"1508340858096"	"lastrun"	Uniquely identifies the session
"jobName"	"vmware_for_vm_admin"	"lastrun"	Name of the job
"type"	"protection"	"lastrun"	Type of the policy (protection , restore , inventory)
"subType"	"vmware"	"lastrun"	Type of the resource
"serviceId"	"serviceprovider.protection.hypervisor"	"lastrun"	
"start"	1508340858824	"lastrun"	Start time of the job
"end"	null	"lastrun"	End time of the job
"duration"	125141	"lastrun"	Total time to perform the job
"status"	"RUNNING"	"lastrun"	Progress of the job
"results"	null	"lastrun"	"properties"
null	"lastrun"	Statistic analysis of the job	"numTasks"
2	"lastrun"	Numbers of tasks inside a policy	"lastUpdate"
1508340859409	"lastrun"		"percent"
0	"lastrun"		"policySnapshot"
null	"lastrun"	Metadata about the policy	"id"

Start a Job: Response Example

```
{
  "links": {
    "self": {
      "rel": "self",
      "href": "https://<hostname|IP>/api/endeavour/job/1343"
    },
    "up": {
      "rel": "up",
      "href": "https://<hostname|IP>/api/endeavour/job"
    },
    "delete": {
      "rel": "delete",
      "href": "https://<hostname|IP>/api/endeavour/job/1343"
    },
    "policyedit": {
      "rel": "update",
      "href": "https://<hostname|IP>/api/endeavour/policy/1343"
    },
    "policydelete": {
      "rel": "delete",
      "href": "https://<hostname|IP>/api/endeavour/policy/1343"
    },
    "edit": {
      "rel": "update",
      "href": "https://<hostname|IP>/api/endeavour/job/1343"
    },
    "policy": {
      "rel": "related",
      "href": "https://<hostname|IP>/api/endeavour/policy/1343"
    },
    "triggers": {
      "rel": "related",
      "href": "https://<hostname|IP>/api/endeavour/job/1343/trigger"
    },
    "jobsessions": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22jobId%22,%
22value%22:%221343%22%7D%5D"
    },
    "activejobsessions": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%
22op%22:%22%3D%22,%22value%22:%22active%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22"
    }
  }
}
```

```

%3D%22,%22value%22:%221343%22%7D%5D"
  },
  "pendingjobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%22op%22:%22%3D%22,%22value%22:%22pending%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22%3D%22,%22value%22:%221343%22%7D%5D"
  },
  "historicaljobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%22op%22:%22%3D%22,%22value%22:%22history%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22%3D%22,%22value%22:%221343%22%7D%5D"
  },
  "livejobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%22op%22:%22%3D%22,%22value%22:%22live%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22%3D%22,%22value%22:%221343%22%7D%5D"
  },
  "stats": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/endeavour/jobsession/stats/jobid/1343"
  },
  "firetimes": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/firetime?filter=%5B%7B%22property%22:%22jobId%22,%22value%22:%221343%22%7D%5D"
  },
  "start": {
    "rel": "action",
    "href":
"https://<hostname|IP>/api/endeavour/job/1343?action=start&actionname=start"
  },
  "cancel": {
    "schema": "https://<hostname|IP>/api/endeavour/job/1343/schema?actionname=cancel",
    "title": "Cancel",
    "rel": "action",
    "href":
"https://<hostname|IP>/api/endeavour/job/1343?action=cancel&actionname=cancel"
  },
  "hold Schedule": {
    "rel": "action",
    "href": "https://<hostname|IP>/api/endeavour/job/1343?action=hold"
  }

```

```

    },
    "status": {
      "rel": "related",
      "href": "https://<hostname|IP>/api/endeavour/job/1343/status"
    },
    "lastrun": {
      "rel": "related",
      "href": "https://<hostname|IP>/api/endeavour/jobsession/1508340858096"
    },
    "lastrunlog": {
      "rel": "related",
      "href":
        "https://<hostname|IP>/api/endeavour/log/job?filter=%5B%7B%22property%22:%22jobsessionId%
        22,%22value%22:%221508340858096%22%7D%5D"
    }
  },
  "name": "vmware_for_vm_admin",
  "description": "Auto-generated job for Policy vmware_for_vm_admin",
  "policyId": "1343",
  "policyName": "vmware_for_vm_admin",
  "type": "protection",
  "subType": "vmware",
  "serviceId": "serviceprovider.protection.hypervisor",
  "displayName": "Hypervisor Backup",
  "status": "RESOURCE ACTIVE",
  "lastSessionStatus": null,
  "triggerIds": [],
  "triggerData": [],
  "lastRunTime": 0,
  "nextFireTime": null,
  "lastSessionDuration": null,
  "tenantId": 1000,
  "actions": null,
  "statistics": null,
  "policy": {
    "links": {
      "self": {
        "rel": "self",
        "href": "https://<hostname|IP>/api/endeavour/policy/1343"
      },
      "up": {
        "rel": "up",
        "href": "https://<hostname|IP>/api/endeavour/policy"
      },
      "edit": {
        "rel": "update",
        "href": "https://<hostname|IP>/api/endeavour/policy/1343"
      }
    }
  },

```

```

    "delete": {
      "rel": "delete",
      "href": "https://<hostname|IP>/api/endeavour/policy/1343"
    },
    "jobs": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/job?filter=%5B%7B%22property%22%3A%22policyId%22%2C%
22value%22%3A%221343%22%7D%5D"
    }
  },
  "name": "vmware_for_vm_admin",
  "type": "protection",
  "subType": "vmware",
  "serviceId": "serviceprovider.protection.hypervisor",
  "description": "",
  "version": "3.0",
  "rbacPath":
"root:0/policy:0/policytype:serviceprovider.protection.hypervisor/policy:1343",
  "tenantId": 1000,
  "creationTime": 1508178551618,
  "lastUpdated": 1508179076216,
  "spec": {
    "source": [],
    "storageworkflow": [
      {
        "id": "2102",
        "name": "for_vm_admin",
        "href": "://<hostname|IP>/api/spec/storageprofile/2102",
        "type": null
      }
    ],
    "option": {
      "maxtasks": 0,
      "vmsnapshot": {
        "takesnapshot": false,
        "concurrentsnapshotsonesx": 3,
        "includememory": false,
        "consistency": false,
        "consistencyvms": [],
        "scriptvms": [],
        "truncateapplicationlogs": false
      },
      "skipreadonlydatastores": true
    },
    "notification": []
  },
  "logicalDelete": false,

```

```
"script": {
  "preScript": null,
  "postScript": null,
  "preSnap": null,
  "postSnap": null,
  "preGuest": null,
  "postGuest": null,
  "preGuestSnap": null,
  "postGuestSnap": null,
  "continueScriptsOnError": false
},
"id": "1343"
},
"triggers": [],
"lastrun": {
  "sessionId": "1508340858096",
  "jobName": "vmware_for_vm_admin",
  "type": "protection",
  "subType": "vmware",
  "serviceId": "serviceprovider.protection.hypervisor",
  "start": null,
  "end": null,
  "duration": null,
  "status": "WAITING",
  "results": null,
  "properties": null,
  "numTasks": 0,
  "lastUpdate": 1508340858196,
  "percent": null,
  "policySnapshot": null
},
"id": "1343"
}
```

4.7. Cancel a Job

4.7.1. Request

Cancel a Job: Request Example

```
POST:  
https://<hostname|IP>/api/endeavour/job/1011?action=cancel&actionname=cancel
```

4.7.2. Response

Cancel a Job: Response Parameters

Property	Sample Value	Element of	Description
"name"	"vmware_for_vm_admin"		Name of the cancelled job
"description"	"Auto-generated job for Policy vmware_for_vm_admin"		Describes what the particular cancelled job did
"policyId"	"1011"		Policy associated with the cancelled job
"policyName"	"vmware_for_vm_admin"		Name of the policy
"type"	"protection"		
"subType"	"vmware"		Type of the resource
"serviceId"	"serviceprovider.protection.hypervisor"		
"displayName"	"Hypervisor Backup"		Targeted resource and Targeted job on which cancelled policy is applied
"status"	"RUNNING"		Indicates the status of the resource; it can be active or running
"lastSessionStatus"	null		Status of the canceled job(failed / completed)
"triggerIds"	[]		Trigger related to a particular job

Property	Sample Value	Element of	Description
"triggerData"	[]		Trigger information related to a job
"lastRunTime"	0		Time the cancelled job was started
"nextFireTime"	null		Next scheduled time when policy should run
"lastSessionDuration"	null		Total time spent on a job
"tenantId"	1000		Identify the users uniquely; for future use
"actions"	null		Lifecycle triggers of the job /state of the job
"statistics"	null		Stats about the policy
"lastrun"	"lastrun"		Time job was started
"sessionId"	"1508340858096"	"lastrun"	Uniquely identifies the session
"jobName"	"vmware_for_vm_admin"	"lastrun"	Name of the job
"type"	"protection"	"lastrun"	
"subType"	"vmware"	"lastrun"	Type of hypervisor where the job last ran
"serviceId"	"serviceprovider.protection.hypervisor"	"lastrun"	
"start"	1508340858824	"lastrun"	
"end"	null	"lastrun"	
"duration"	125141	"lastrun"	
"status"	"RUNNING"	"lastrun"	Indicates the status of the resource; it can be active or running
"results"	null	"lastrun"	Stats about the job
"properties"	null	"lastrun"	
"numTasks"	2	"lastrun"	Numbers of tasks inside a policy
"lastUpdate"	1508340859409	"lastrun"	
"percent"	0	"lastrun"	

Property	Sample Value	Element of	Description
"policySnapshot"	null	"lastrun"	Metadata about the policy
"id"	"1011"		Id of the cancelled job

Cancel a Job: Response Example

```
{
  "links": {
    "self": {
      "rel": "self",
      "href": "https://<hostname|IP>/api/endeavour/job/1011"
    },
    "up": {
      "rel": "up",
      "href": "https://<hostname|IP>/api/endeavour/job"
    },
    "delete": {
      "rel": "delete",
      "href": "https://<hostname|IP>/api/endeavour/job/1011"
    },
    "policyedit": {
      "rel": "update",
      "href": "https://<hostname|IP>/api/endeavour/policy/1011"
    },
    "policydelete": {
      "rel": "delete",
      "href": "https://<hostname|IP>/api/endeavour/policy/1011"
    },
    "edit": {
      "rel": "update",
      "href": "https://<hostname|IP>/api/endeavour/job/1011"
    },
    "policy": {
      "rel": "related",
      "href": "https://<hostname|IP>/api/endeavour/policy/1011"
    },
    "triggers": {
      "rel": "related",
      "href": "https://<hostname|IP>/api/endeavour/job/1011/trigger"
    },
    "jobsessions": {
      "rel": "related",
      "href":
        "https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22jobId%22,%22%22%7D%5D"
    }
  }
}
```

```

22value%22:%221011%22%7D%5D"
  },
  "activejobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%22op%22:%22%3D%22,%22value%22:%22active%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22%3D%22,%22value%22:%221011%22%7D%5D"
  },
  "pendingjobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%22op%22:%22%3D%22,%22value%22:%22pending%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22%3D%22,%22value%22:%221011%22%7D%5D"
  },
  "historicaljobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%22op%22:%22%3D%22,%22value%22:%22history%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22%3D%22,%22value%22:%221011%22%7D%5D"
  },
  "livejobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,%22op%22:%22%3D%22,%22value%22:%22live%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22%3D%22,%22value%22:%221011%22%7D%5D"
  },
  "stats": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/endeavour/jobsession/stats/jobid/1011"
  },
  "firetimes": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/firetime?filter=%5B%7B%22property%22:%22jobId%22,%22value%22:%221011%22%7D%5D"
  },
  "start": {
    "rel": "action",
    "href": "://<hostname|IP>/api/endeavour/job/1011?action=start&actionname=start"
  },
  "hold Schedule": {
    "rel": "action",
    "href": "https://<hostname|IP>/api/endeavour/job/1011?action=hold"
  },
}

```

```

"status": {
  "rel": "related",
  "href": "https://<hostname|IP>/api/endeavour/job/1011/status"
},
"lastrun": {
  "rel": "related",
  "href": "https://<hostname|IP>/api/endeavour/jobsession/1508340858096"
},
"lastrunlog": {
  "rel": "related",
  "href":
"https://<hostname|IP>/api/endeavour/log/job?filter=%5B%7B%22property%22:%22jobsessionId%
22,%22value%22:%221508340858096%22%7D%5D"
}
},
"name": "vmware_for_vm_admin",
"description": "Auto-generated job for Policy vmware_for_vm_admin",
"policyId": "1011",
"policyName": "vmware_for_vm_admin",
"type": "protection",
"subType": "vmware",
"serviceId": "serviceprovider.protection.hypervisor",
"displayName": "Hypervisor Backup",
"status": "RUNNING",
"lastSessionStatus": null,
"triggerIds": [],
"triggerData": [],
"lastRunTime": 0,
"nextFireTime": null,
"lastSessionDuration": null,
"tenantId": 1000,
"actions": null,
"statistics": null,
"lastrun": {
  "sessionId": "1508340858096",
  "jobName": "vmware_for_vm_admin",
  "type": "protection",
  "subType": "vmware",
  "serviceId": "serviceprovider.protection.hypervisor",
  "start": 1508340858824,
  "end": null,
  "duration": 125141,
  "status": "RUNNING",
  "results": null,
  "properties": null,
  "numTasks": 2,
  "lastUpdate": 1508340859409,
  "percent": 0,

```

```
"policySnapshot": null  
},  
"id": "1011"  
}
```

4.8. Register a Hypervisor

4.8.1. Request

Register a Hypervisor: Request Example

```
POST:
https://<hostname|IP>/ngp/hypervisor
```

4.8.2. Request Body

Register a Hypervisor: Request Body Example

```
{"hostAddress":"<IP>","portNumber":443,"username":"ad.xyz.us\\tester","password":"abcd","sslConnection":true,"type":"vmware","opProperties":{"snapshotConcurrency":3}}
```

4.8.3. Response

Register a Hypervisor: Response Example

```
{
  "statusCode": 201,
  "response": {
    "links": {
      "self": {
        "rel": "self",
        "href": "https://<hostname|IP>/api/hypervisor/1002",
        "hreflang": null,
        "media": null,
        "title": null,
        "type": null,
        "deprecation": null
      },
      "up": {
        "rel": "up",
        "href": "https://<hostname|IP>/api/hypervisor",
        "hreflang": null,
        "media": null,
        "title": null,
        "type": null,
        "deprecation": null
      },
      "edit": {
```

```

    "rel": "edit",
    "href": "https://<hostname|IP>/api/hypervisor/1002",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "delete": {
    "rel": "delete",
    "href": "https://<hostname|IP>/api/hypervisor/1002",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "usedby": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/association/resource/hypervisor/1002?action=listUsingResources",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "clusters": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/hypervisor/1002/cluster",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "hosts": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/hypervisor/1002/host",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "vms": {
    "rel": "related",

```

```
"href": "https://<hostname|IP>/api/hypervisor/1002/vm",
"hreflang": null,
"media": null,
"title": null,
"type": null,
"deprecation": null
},
"vmgroups": {
  "rel": "related",
  "href": "https://<hostname|IP>/api/hypervisor/1002/vmgroup",
  "hreflang": null,
  "media": null,
  "title": null,
  "type": null,
  "deprecation": null
},
"volumes": {
  "rel": "related",
  "href": "https://<hostname|IP>/api/hypervisor/1002/volume",
  "hreflang": null,
  "media": null,
  "title": null,
  "type": null,
  "deprecation": null
},
"tags": {
  "rel": "related",
  "href": "https://<hostname|IP>/api/hypervisor/1002/tag",
  "hreflang": null,
  "media": null,
  "title": null,
  "type": null,
  "deprecation": null
},
"tagCategories": {
  "rel": "related",
  "href": "https://<hostname|IP>/api/hypervisor/1002/tagcategory",
  "hreflang": null,
  "media": null,
  "title": null,
  "type": null,
  "deprecation": null
},
"tagview": {
  "rel": "related",
  "href": "https://<hostname|IP>/api/hypervisor/1002/tagcontent",
  "hreflang": null,
  "media": null,
```

```

    "title": null,
    "type": null,
    "deprecation": null
  },
  "vmview": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/hypervisor/1002/vmcontent",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "storageview": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/hypervisor/1002/storagecontent",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "hostview": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/hypervisor/1002/hostcontent",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "inventory": {
    "rel": "action",
    "href": "https://<hostname|IP>/api/hypervisor/1002?action=inventory",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  }
},
"name": "<IP>",
"hostAddress": "<IP>",
"user": {
  "href": "https://<hostname|IP>:-1/api/identity/user/2102"
},
"sslConnection": true,
"portNumber": 443,

```

```
"type": "vmware",
"id": "1002",
"uniqueId": "955db7e5-0042-4ead-b373-c4c5e71c7b2e",
"properties": {},
"logicalDelete": false,
"opProperties": {
  "snapshotConcurrency": 3,
  "veServerInfo": {
    "name": null,
    "hostAddress": null,
    "portNumber": 0,
    "osType": null,
    "useKeyAuthentication": false,
    "osuser": null,
    "oskey": null
  }
},
"rbacPath": "root:0/hypervisor.all:0/hypervisor.type:vmware/hypervisor:1002",
"resourceType": "hypervisor"
}
}
```

4.9. Register an Application

4.9.1. Request

Register an Application: Request Example

```
POST:
https://<hostname|IP>/ngp/appserver
```

4.9.2. Request Body

Register an Application: Request Body Example

```
{"hostAddress":"<IP>","username":"<username>","password":"1234","osType":"linux","addToCa
tJob":true,"script":false,"application":true,"opProperties":{"maxConcurrency":10}}
```

4.9.3. Response

Register an Application: Response Example

```
{
  "statusCode": 201,
  "response": {
    "links": {
      "self": {
        "rel": "self",
        "href": "https://<hostname|IP>/api/appserver/1001",
        "hreflang": null,
        "media": null,
        "title": null,
        "type": null,
        "deprecation": null
      },
      "up": {
        "rel": "up",
        "href": "https://<hostname|IP>/api/appserver",
        "hreflang": null,
        "media": null,
        "title": null,
        "type": null,
        "deprecation": null
      },
      "edit": {
```

```

    "rel": "update",
    "href": "https://<hostname|IP>/api/appserver/1001",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "delete": {
    "rel": "delete",
    "href": "https://<hostname|IP>/api/appserver/1001",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "usedby": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/association/resource/appserver/1001?action=listUsing
Resources",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "credentials": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/appserver/1001/credential",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "volumes": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/appserver/1001/volume?from=hlo",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "disks": {
    "rel": "related",

```

```

    "href": "https://<hostname|IP>/api/appserver/1001/disk?from=hlo",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "test": {
    "rel": "action",
    "href": "https://<hostname|IP>/api/appserver/1001?action=test",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  },
  "inventory": {
    "rel": "action",
    "href": "https://<hostname|IP>/api/appserver/1001?action=inventory",
    "hreflang": null,
    "media": null,
    "title": null,
    "type": null,
    "deprecation": null
  }
},
"id": "1001",
"name": "172.20.46.45",
"hostAddress": "172.20.46.45",
"comment": null,
"catalogEligible": null,
"serverType": null,
"vsphereId": null,
"applicationType": null,
"osType": "linux",
"useKeyAuthentication": null,
"logicalDelete": false,
"applicationTypes": null,
"oskey": null,
"osuser": {
  "href": "https://<hostname|IP>/api/identity/user/2103"
},
"appCredentials": [],
"portNumber": 0,
"opProperties": {
  "maxConcurrency": 10
},
"application": true,

```

```
"script": false,  
"metadataPath": null,  
"resourceType": "appserver",  
"rbacPath": "root:0/appserver.all:0/appserver:1001"  
}  
}
```

4.10. Delete a vCenter

4.10.1. Request

Delete a vCenter: Request Example

```
DELETE:  
https://<hostname|IP>/api/hypervisor/1003
```

4.11. Restore a Virtual Machine

4.11.1. Request

Restore a VM: Request Example

```
POST:  
https://<hostname|IP>/ngp/hypervisor?action=restore
```

4.11.2. Request Body

Restore a VM: Request Body Parameters

Property	Sample Value	Element of	Description
"spec"			
"source"		"spec"	
"metadata"		"source"	
"name"	"AXADummy3"	"metadata"	Name of restore action
"resourceType"	"vm"	"source"	Type of the resource that needs to be associated. Resource can be either vm, vapp, datastore, vdisk, folder
"id"	"51e62d3f751e3efe0b1ac26c1948c1cc"	"source"	ID of VM
"include"	true	"source"	"version"
	"source"	Version of the resource to be recovered	
"metadata"		"version"	Metadata of VM
"useLatest"	false	"metadata"	Use the latest version of the resource for restore
"protectionTime"	"1508094130464"	"metadata"	
"subpolicy"		"spec"	
"type"	"IV"	"subpolicy"	RECOVERY Policy can either be IA(instant access) or IV (instant virtualization)

Property	Sample Value	Element of	Description
"destination"		"subpolicy"	
"systemDefined"	true	"destination"	Use whatever system defined subnet/IP address for destination after restoring to target location
"option"		"subpolicy"	
"protocolpriority"	"iSCSI"	"option"	Can either be FC or iSCI. The default is iSCI
"poweron"	false	"option"	
"continueonerror"	true	"option"	Continue restore operation even if some resources are failed to be restored
"autocleanup"	true	"option"	Automatically clean up resources on failure
"allowsessooverwrite"	true	"option"	If new scheduled session allowed to overwrite and force cleanup of pending old session
"mode"	"test"	"option"	Disk mode for vmdk, default is persistent
"vmscripts"	false	"option"	Scripts to run before/after restore operation

Restore a VM: Request Body Example

```

{
  "subType": "vmware",
  "spec": {
    "source": [
      {
        "href":
"https://<hostname|IP>/api/hypervisor/1001/vm/51e62d3f751e3efe0b1ac26c1948c1cc?from=recov
ery",
        "metadata": {
          "name": "AXADummy3"
        },
        "resourceType": "vm",
        "id": "51e62d3f751e3efe0b1ac26c1948c1cc",
        "include": true,
        "version": {
          "href":
"https://<hostname|IP>/api/hypervisor/1001/version/vm.51e62d3f751e3efe0b1ac26c1948c1cc.15
0809400071</version/latest>?from=recovery",
          "metadata": {
            "useLatest": <true|false>,
            "protectionTime": "1508094130464"
          }
        }
      }
    ],
    "subpolicy": [
      {
        "type": "IV",
        "destination": {
          "systemDefined": true
        },
        "option": {
          "protocolpriority": "iSCSI",
          "poweron": false,
          "continueonerror": true,
          "autocleanup": true,
          "allowsessoverwrite": true,
          "mode": "test",
          "vmscripts": false
        }
      }
    ]
  }
}

```

4.11.3. Response

Restore a VM: Response Parameters

Property	Sample Value	Element of	Description
"statusCode"	201		Indicates if the request was successful or not.
"response"		"response"	Contains all the information about the resource
"name"	"onDemandRestore_1508341891370"	"response"	Name of the user defined policy name
"description"	"Auto-generated job for Policy onDemandRestore_1508341891370"	"response"	User defined policy description
"policyId"	"1022"	"response"	Policy id number
"policyName"	"onDemandRestore_1508341891370"	"response"	User defined name
"type"	"recovery"	"response"	Policy type
"subType"	"vmware"	"response"	Type of hypervisor
"serviceId"	"serviceprovider.recovery.hypervisor"	"response"	
"displayName"	"Hypervisor Recovery"	"response"	Targeted resource and targeted job
"status"	"RESOURCE ACTIVE"	"response"	Indicates the status of the resource
"lastSessionStatus"	null	"response"	
"triggerIds"	[]	"response"	Trigger related to a job
"triggerData"	[]	"response"	Data of the particular trigger
"lastRunTime"	0	"response"	time when the last job ran
"nextFireTime"	null	"response"	Next scheduled time when policy should run
"lastSessionDuration"	null	"response"	Total time spent on a job

Property	Sample Value	Element of	Description
"tenantId"	1000	"response"	Identify the users uniquely; for future use
"actions"	null	"response"	Lifecycle triggers of the job /state of the job
"statistics"	null	"response"	Stats about the policy
"policy"		"response"	
"links"			
"self"		"links"	
"rel"	"self"	"self"	
"href"	"//<hostname>/api/endeavour/policy/1022"	"self"	
"up"		"links"	
"rel"	"up"	"up"	
"href"	"https://<hostname>/api/endeavour/policy"	"up"	
"edit"		"links"	
"rel"	"update"	"edit"	
"href"	"https://<hostname>/api/endeavour/policy/1022"	"edit"	
"delete"		"links"	
"rel"	"delete"	"delete"	
"href"	<a href="https://<hostname>/api/endeavour/policy/1022">https://<hostname>/api/endeavour/policy/1022		
"delete"			
"jobs"		"links"	
"rel"	"related"	"jobs"	
"name"	"onDemandRestore_1508341891370"	"policy"	
"type"	"recovery"	"policy"	
"subtype"	"vmware"	"policy"	
"serviceId"	"serviceprovider.recovery.hypervisor"	"policy"	

Property	Sample Value	Element of	Description
"description"	""	"policy"	
"version"	"3.1"	"policy"	Describes the version of policy of the resource
"rbacPath"	"root:0/policy:0/policytype:serviceprovider.recovery.hypervisor/policy:1022"	"policy"	
"tenantId"	1000	"policy"	Identify the users uniquely; for future use
"creationTime"	1508341891415	"policy"	Time describing the creation time
"lastUpdated"	0	"policy"	
"spec"		"policy"	
"source"		"spec"	
"metadata"		"source"	
"name"	"AXADummy3"	"metadata"	Name of restore action
"resourceType"	"vm"	"source"	Type of the resource that needs to be associated. Resource can be either vm, vapp, datastore, vdisk, folder
"id"	"51e62d3f751e3efe0b1ac26c1948c1cc"	"source"	Id of VM
"include"	true	"source"	
"version"		"source"	Version of the resource to be recovered
"metadata"		"version"	
"useLatest"	false	"metadata"	Use the latest version of the resource for restore
"protectionTime"	"1508094130464"	"metadata"	
"subpolicy"		"spec"	

Property	Sample Value	Element of	Description
"type"	"IV"	"subpolicy"	RECOVERY Policy can either be IA(instant access) or IV (instant virtualization)
"destination"		"subpolicy"	
"systemDefined"	true	"subpolicy"	Use whatever system defined subnet/IP address for destination after restoring to target location
"option"			
"protocolpriority"	"iSCSI"	"option"	Can either be FC or iSCI. The default is iSCI
"poweron"	false	"option"	
"continueonerror"	true	"option"	Continue restore operation even if some resources are failed to be restored
"autocleanup"	true	"option"	Automatically clean up resources on failure
"allowsessooverwrite"	true	"option"	If new scheduled session allowed to overwrite and force cleanup of pending old session - default is true
"mode"	"test"	"option"	Disk mode for vmdk, default is persistent
"vmscripts"	false	"option"	Scripts to run before/after restore operation
"name"	"onDemandRestore_1508341891370"	"subpolicy"	
"logicalDelete"	false	"policy"	
"script"		"policy"	
"preScript"	null	"script"	Scripts description to run the restore operation

Property	Sample Value	Element of	Description
"postScript"	null	"script"	Script to run after the restore operation
"preSnap"	null	"script"	
"postSnap"	null	"script"	
"preGuest"		"script"	
"appserver"	null	"preGuest"	
"identity"	null	"preGuest"	
"script"	null	"preGuest"	
"postGuest"		"script"	
"appserver"	null	"postGuest"	
"identity"	null	"postGuest"	
"script"	null	"postGuest"	
"preGuestSnap"	null	"script"	
"postGuestSnap"	null	"script"	
"continueScriptsOnError"	false	"script"	
"id"	"1022"	"policy"	
"triggers"	[]	"response"	
"lastrun"		"response"	
"sessionId"	"1508341891139"	"lastrun"	Uniquely identifying the session
"jobName"	"onDemandRestore_1508341891370"	"lastrun"	Job last ran on the Hypervisor
"type"	"recovery"	"lastrun"	Type of job last run
"subType"	"vmware"	"lastrun"	Type of hypervisor
"serviceId"	"serviceprovider.recovery.hypervisor"	"lastrun"	
"start"	null	"lastrun"	Start time of the job last ran
"end"	null	"lastrun"	End time of the job
"duration"	null	"lastrun"	Total time to perform the job

Property	Sample Value	Element of	Description
"status"	"WAITING"	"lastrun"	Indicates the status of the resource; it can be active or running
"results"	null	"lastrun"	
"properties"	null	"lastrun"	Statistics analysis of the job
"numTasks"	0	"lastrun"	Number of tasks inside the policy
"lastUpdate"	1508341891721	"lastrun"	
"percent"	null	"lastrun"	
"policySnapshot"	null	"lastrun"	Metadata about the policy
"id"	"1021"	"response"	ID of the job

Restore a VM: Response Example

```
{
  "statusCode": 201,
  "response": {
    "links": {
      "self": {
        "rel": "self",
        "href": "https://<hostname|IP>/api/endeavour/job/1021"
      },
      "up": {
        "rel": "up",
        "href": "https://<hostname|IP>/api/endeavour/job"
      },
      "delete": {
        "rel": "delete",
        "href": "https://<hostname|IP>/api/endeavour/job/1021"
      },
      "policyedit": {
        "rel": "update",
        "href": "https://<hostname|IP>/api/endeavour/policy/1022"
      },
      "policydelete": {
        "rel": "delete",
        "href": "https://<hostname|IP>/api/endeavour/policy/1022"
      },
      "edit": {
```

```

    "rel": "update",
    "href": "https://<hostname|IP>/api/endeavour/job/1021"
  },
  "policy": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/endeavour/policy/1022"
  },
  "triggers": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/endeavour/job/1021/trigger"
  },
  "jobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22jobId%22,%
22value%22:%221021%22%7D%5D"
  },
  "activejobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,
%22op%22:%22%3D%22,%22value%22:%22active%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22
%3D%22,%22value%22:%221021%22%7D%5D"
  },
  "pendingjobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,
%22op%22:%22%3D%22,%22value%22:%22pending%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%2
2%3D%22,%22value%22:%221021%22%7D%5D"
  },
  "historicaljobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,
%22op%22:%22%3D%22,%22value%22:%22history%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%2
2%3D%22,%22value%22:%221021%22%7D%5D"
  },
  "livejobsessions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/jobsession?filter=%5B%7B%22property%22:%22status%22,
%22op%22:%22%3D%22,%22value%22:%22live%22%7D,%7B%22property%22:%22jobId%22,%22op%22:%22%3
D%22,%22value%22:%221021%22%7D%5D"
  },
  "stats": {
    "rel": "related",
    "href": "https://<hostname|IP>/api/endeavour/jobsession/stats/jobid/1021"
  }

```

```

    },
    "firetimes": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/firetime?filter=%5B%7B%22property%22:%22jobId%22,%22
value%22:%221021%22%7D%5D"
    },
    "start": {
      "schema": "https://<hostname|IP>/api/endeavour/job/1021/schema?actionname=start",
      "title": "Start",
      "rel": "action",
      "href":
"https://<hostname|IP>/api/endeavour/job/1021?action=start&actionname=start"
    },
    "hold Schedule": {
      "rel": "action",
      "href": "https://<hostname|IP>/api/endeavour/job/1021?action=hold"
    },
    "status": {
      "rel": "related",
      "href": "://<hostname|IP>/api/endeavour/job/1021/status"
    },
    "lastrun": {
      "rel": "related",
      "href": "://<hostname|IP>/api/endeavour/jobsession/1508341891139"
    },
    "lastrunlog": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/log/job?filter=%5B%7B%22property%22:%22jobsessionId%
22,%22value%22:%221508341891139%22%7D%5D"
    }
  },
  "name": "onDemandRestore_1508341891370",
  "description": "Auto-generated job for Policy onDemandRestore_1508341891370",
  "policyId": "1022",
  "policyName": "onDemandRestore_1508341891370",
  "type": "recovery",
  "subType": "vmware",
  "serviceId": "serviceprovider.recovery.hypervisor",
  "displayName": "Hypervisor Recovery",
  "status": "RESOURCE ACTIVE",
  "lastSessionStatus": null,
  "triggerIds": [],
  "triggerData": [],
  "lastRunTime": 0,
  "nextFireTime": null,
  "lastSessionDuration": null,

```

```

"tenantId": 1000,
"actions": null,
"statistics": null,
"policy": {
  "links": {
    "self": {
      "rel": "self",
      "href": "://<hostname|IP>/api/endeavour/policy/1022"
    },
    "up": {
      "rel": "up",
      "href": "https://<hostname|IP>/api/endeavour/policy"
    },
    "edit": {
      "rel": "update",
      "href": "https://<hostname|IP>/api/endeavour/policy/1022"
    },
    "delete": {
      "rel": "delete",
      "href": "https://<hostname|IP>/api/endeavour/policy/1022"
    },
    "jobs": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/job?filter=%5B%7B%22property%22%3A%22policyId%22%2C%
22value%22%3A%221022%22%7D%5D"
    }
  },
  "name": "onDemandRestore_1508341891370",
  "type": "recovery",
  "subType": "vmware",
  "serviceId": "serviceprovider.recovery.hypervisor",
  "description": "",
  "version": "3.1",
  "rbacPath":
"root:0/policy:0/policytype:serviceprovider.recovery.hypervisor/policy:1022",
  "tenantId": 1000,
  "creationTime": 1508341891415,
  "lastUpdated": 0,
  "spec": {
    "source": [
      {
        "href":
"https://<hostname|IP>/api/hypervisor/1001/vm/51e62d3f751e3efe0b1ac26c1948c1cc?from=recov
ery",
        "metadata": {
          "name": "AXADummy3"
        }
      }
    ]
  }
}

```

```

    "resourceType": "vm",
    "id": "51e62d3f751e3efe0b1ac26c1948c1cc",
    "include": true,
    "version": {
      "href":
"https://<hostname|IP>/api/hypervisor/1001/version/vm.51e62d3f751e3efe0b1ac26c1948c1cc.15
08094000071?from=recovery",
      "metadata": {
        "useLatest": false,
        "protectionTime": "1508094130464"
      }
    }
  },
  "subpolicy": [
    {
      "type": "IV",
      "destination": {
        "systemDefined": true
      },
      "option": {
        "protocolpriority": "iSCSI",
        "poweron": false,
        "continueonerror": true,
        "autocleanup": true,
        "allowsesoverwrite": true,
        "mode": "test",
        "vmscripts": false
      },
      "name": "onDemandRestore_1508341891370"
    }
  ]
},
"logicalDelete": false,
"script": {
  "preScript": null,
  "postScript": null,
  "preSnap": null,
  "postSnap": null,
  "preGuest": {
    "appserver": null,
    "identity": null,
    "script": null
  },
  "postGuest": {
    "appserver": null,
    "identity": null,
    "script": null
  }
}

```

```
    },
    "preGuestSnap": null,
    "postGuestSnap": null,
    "continueScriptsOnError": false
  },
  "id": "1022"
},
"triggers": [],
"lastrun": {
  "sessionId": "1508341891139",
  "jobName": "onDemandRestore_1508341891370",
  "type": "recovery",
  "subType": "vmware",
  "serviceId": "serviceprovider.recovery.hypervisor",
  "start": null,
  "end": null,
  "duration": null,
  "status": "WAITING",
  "results": null,
  "properties": null,
  "numTasks": 0,
  "lastUpdate": 1508341891721,
  "percent": null,
  "policySnapshot": null
},
"id": "1021"
}}
```

4.12. Generate Reports

4.12.1. Run a Report Request

Run a Report: Request Example

```
POST:  
http://<hostname|IP>/api/endeavour/report/1009?action=run
```

4.12.2. Run a Report Response

Run a Report: Response Example

```
202 Accepted  
  
{  
  "location": "http://<hostname|IP>/api/endeavour/task/1009"  
}
```

4.12.3. Create a Report Request

Create a Report: Request Example

Required permissions: "report.create"

```
POST:  
http://<hostname|IP>/api/endeavour/report
```

Create a Report: Request Body Example

```
{  
  "description": "An example custom report",  
  "name": "testreport",  
  "paramValues": {  
    "ApplicationType": [  
      "Oracle"  
    ]  
  },  
  "parentId": "1021"  
}
```

4.12.4. Create a Report Response

Create a Report: Response Example

201 Created

```
{
  "links": {
    "self": {
      "title": "testreport",
      "rel": "self",
      "href": "http://<hostname|IP>/api/endeavour/report/1069"
    },
    "up": {
      "rel": "up",
      "href": "http://<hostname|IP>/api/endeavour/report"
    },
    "parent": {
      "title": "Application Configuration",
      "rel": "parent",
      "href": "http://<hostname|IP>/api/endeavour/report/1021"
    },
    "edit": {
      "rel": "update",
      "href": "http://<hostname|IP>/api/endeavour/report/1069"
    },
    "delete": {
      "rel": "delete",
      "href": "http://<hostname|IP>/api/endeavour/report/1069"
    },
    "parameters": {
      "rel": "related",
      "href": "http://<hostname|IP>/api/endeavour/report/1069/parameter"
    },
    "schema": {
      "title": "schema",
      "rel": "related",
      "href": "http://<hostname|IP>/api/endeavour/report/1069/schema"
    },
    "run": {
      "schema": "http://<hostname|IP>/api/endeavour/report/1069/schema?action=run",
      "title": "Run report",
      "rel": "action",
      "href": "http://<hostname|IP>/api/endeavour/report/1069?action=run"
    }
  },
  "id": "1069",
```

```

"name": "testreport",
"description": "An example custom report",
"category": "Application",
"custom": true,
"creationTime": 1500380383830,
"paramValues": {
  "ApplicationType": [
    "Oracle"
  ]
},
"parentId": "1021",
"rbacPath": "root:0/report:0/reportcategory:ApplicationCategoryName/report:1069"
}

```

4.12.5. Get a Report Request

Get a Report: Request Example

```

GET:
http://<hostname|IP>/api/endeavour/report/1001

```

4.12.6. Get a Report Response

Get a Report: Response Example

```

200 OK

{
  "links": {
    "self": {
      "title": "File Usage by Owner",
      "rel": "self",
      "href": "http://<hostname|IP>/api/endeavour/report/1001"
    },
    "up": {
      "rel": "up",
      "href": "http://<hostname|IP>/api/endeavour/report"
    },
    "customReports": {
      "rel": "related",
      "href":
"http://<hostname|IP>/api/endeavour/report?filter=[{"property":"parentId","value":"1001"}]"
    },
    "parameters": {

```

```

        "rel": "related",
        "href": "http://<hostname|IP>/api/endeavour/report/1001/parameter"
    },
    "schema": {
        "title": "schema",
        "rel": "related",
        "href": "http://<hostname|IP>/api/endeavour/report/1001/schema"
    },
    "run": {
        "schema": "http://<hostname|IP>/api/endeavour/report/1001/schema?action=run",
        "title": "Run report",
        "rel": "action",
        "href": "http://<hostname|IP>/api/endeavour/report/1001?action=run"
    }
},
"id": "1001",
"name": "File Usage by Owner",
"description": "Review the usage of files on your NetApp nodes based on the owner.",
"category": "File Analytics",
"custom": false,
"creationTime": 1500380388532,
"paramValues": {
    "ParentType": "Yes",
    "exportdateformat": "epoch",
    "NodeVolumeCascadingParameterGroup-NodeParameter": "(All)",
    "NodeVolumeCascadingParameterGroup-VolumeParameter": [
        "(All)"
    ],
    "report_limit": 10
},
"rbacPath": "root:0/report:0/reportcategory:FileReportCategory/report:1001"
}

```

4.12.7. Get Reports Request

Get Reports: Request Example

```

GET:
http://<hostname|IP>/api/endeavour/report?pageSize=2

```

4.12.8. Get Reports Response

Get Reports: Response Example

```

200 OK

```

```

{
  "links": {
    "self": {
      "rel": "self",
      "href":
"http://<hostname|IP>/api/endeavour/report?pageSize=2&pageStartIndex=0"
    },
    "create": {
      "rel": "create",
      "href": "http://<hostname|IP>/api/endeavour/report"
    },
    "nextPage": {
      "rel": "next",
      "href":
"http://<hostname|IP>/api/endeavour/report?pageSize=2&pageStartIndex=2"
    },
    "lastPage": {
      "rel": "last",
      "href":
"http://<hostname|IP>/api/endeavour/report?pageSize=2&pageStartIndex=66"
    }
  },
  "reports": [
    {
      "links": {
        "self": {
          "title": "File Usage by Owner",
          "rel": "self",
          "href": "http://<hostname|IP>/api/endeavour/report/1001"
        },
        "up": {
          "rel": "up",
          "href": "http://<hostname|IP>/api/endeavour/report"
        },
        "customReports": {
          "rel": "related",
          "href":
"http://<hostname|IP>/api/endeavour/report?filter=[{"property":"parentId","value":"1001"}]"
        },
        "parameters": {
          "rel": "related",
          "href": "http://<hostname|IP>/api/endeavour/report/1001/parameter"
        },
        "schema": {
          "title": "schema",
          "rel": "related",

```

```

        "href": "http://<hostname|IP>/api/endeavour/report/1001/schema"
    },
    "run": {
        "schema":
"http://<hostname|IP>/api/endeavour/report/1001/schema?action=run",
        "title": "Run report",
        "rel": "action",
        "href": "http://<hostname|IP>/api/endeavour/report/1001?action=run"
    }
},
"id": "1001",
"name": "File Usage by Owner",
"description": "Review the usage of files on your NetApp nodes based on the
owner.",
"category": "File Analytics",
"custom": false,
"creationTime": 1500380389066,
"rbacPath": "root:0/report:0/reportcategory:FileReportCategory/report:1001"
},
{
    "links": {
        "self": {
            "title": "Files by Age",
            "rel": "self",
            "href": "http://<hostname|IP>/api/endeavour/report/1002"
        },
        "up": {
            "rel": "up",
            "href": "http://<hostname|IP>/api/endeavour/report"
        },
        "customReports": {
            "rel": "related",
            "href":
"http://<hostname|IP>/api/endeavour/report?filter=[{"property":"parentId","value":"\
1002"}]"
        },
        "parameters": {
            "rel": "related",
            "href": "http://<hostname|IP>/api/endeavour/report/1002/parameter"
        },
        "schema": {
            "title": "schema",
            "rel": "related",
            "href": "http://<hostname|IP>/api/endeavour/report/1002/schema"
        },
        "run": {
            "schema":
"http://<hostname|IP>/api/endeavour/report/1002/schema?action=run",

```

```

        "title": "Run report",
        "rel": "action",
        "href": "http://<hostname|IP>/api/endeavour/report/1002?action=run"
    }
},
"id": "1002",
"name": "Files by Age",
"description": "Review the age of files on your NetApp nodes based on the
creation date and the last time modified.",
"category": "File Analytics",
"custom": false,
"creationTime": 1500380389066,
"helpURL": "report/report_reportdetails_fileanalytics_filebyage.htm",
"rbacPath": "root:0/report:0/reportcategory:FileReportCategory/report:1002"
}
],
"total": 68,
"page": 1
}

```

4.12.9. Update Report Request

Update Report: Request Example

```

PUT:
http://<hostname|IP>/api/endeavour/report/1071

```

Update Report: Request Body Example

```

{
  "paramValues": {
    "ApplicationType": [
      "Oracle",
      "Microsoft Sharepoint"
    ]
  }
}

```

4.12.10. Update Report Response

Update Report: Response Example

```

200 OK

```

```

{
  "links": {
    "self": {
      "title": "testreport",
      "rel": "self",
      "href": "http://<hostname|IP>/api/endeavour/report/1071"
    },
    "up": {
      "rel": "up",
      "href": "http://<hostname|IP>/api/endeavour/report"
    },
    "parent": {
      "title": "Application Configuration",
      "rel": "parent",
      "href": "http://<hostname|IP>/api/endeavour/report/1021"
    },
    "edit": {
      "rel": "update",
      "href": "http://<hostname|IP>/api/endeavour/report/1071"
    },
    "delete": {
      "rel": "delete",
      "href": "http://<hostname|IP>/api/endeavour/report/1071"
    },
    "parameters": {
      "rel": "related",
      "href": "http://<hostname|IP>/api/endeavour/report/1071/parameter"
    },
    "schema": {
      "title": "schema",
      "rel": "related",
      "href": "http://<hostname|IP>/api/endeavour/report/1071/schema"
    },
    "run": {
      "schema": "http://<hostname|IP>/api/endeavour/report/1071/schema?action=run",
      "title": "Run report",
      "rel": "action",
      "href": "http://<hostname|IP>/api/endeavour/report/1071?action=run"
    }
  },
  "id": "1071",
  "name": "testreport",
  "description": "An example custom report",
  "category": "Application",
  "custom": true,
  "creationTime": 1500380403600,
  "paramValues": {

```

```
    "ApplicationType": [
      "Oracle",
      "Microsoft Sharepoint"
    ]
  },
  "parentId": "1021",
  "rbacPath": "root:0/report:0/reportcategory:ApplicationCategoryName/report:1071"
}
```

4.12.11. Delete Report Request

Delete Report: Request Example

```
DELETE:
http://<hostname|IP>/api/endeavour/report/1070
```

4.12.12. Delete Report Response

Delete Report: Response Example

```
204 No Content
```

4.13. Generate VM Backup History Report: Successful

4.13.1. Run a Report of VMs Successfully Backed Up

Request Example

```
GET:
https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm?embed=(children(properties))&pageSize=200&filter=[{"property":"sessionId","op":">":"value":"<value>"}]
```

4.13.2. Run a Report of VMs Successfully Backed Up Response

Response Example

```
{
  "links": {
    "self": {
      "rel": "self",
      "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm?pageSize=200&pageStartIndex=0&filter=%5B%7B%22property%22:%22sessionId%22,%22op%22:%22%3E%22,%22value%22:%221531334855938%22%7D%5D&embed=(children(properties))"
    },
    "up": {
      "rel": "up",
      "href": "https://<hostname|IP>/api/endeavour/catalog/recovery"
    },
    "children": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm?filter=%5B%7B%22property%22:%22sessionId%22,%22op%22:%22%3E%22,%22value%22:%221531334855938%22%7D%5D&pageStartIndex=0&pageSize=200&embed=(children)"
    },
    "schema": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm?embed=(schema)"
    }
  },
  "queryElapsedTime": 21,
  "id": "hypervisorvm",
  "name": "hypervisorvm",
  "type": "folder",
  "catalogTime": null,
```

```

"catalogProvider": "recovery",
"comment": null,
"tags": null,
"documentType": null,
"page": 1,
"properties": {},
"children": [
  {
    "links": {
      "self": {
        "rel": "self",
        "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm/5b48dbdcc2dc7188911c7b
93"
      },
      "up": {
        "rel": "up",
        "href": "https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm"
      },
      "noSchema": {
        "rel": "related",
        "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm/5b48dbdcc2dc7188911c7b
93?exclude=(schema)"
      },
      "versions": {
        "rel": "related",
        "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm/pk.01f827f8cf42e2a294f
db8f7c858bc1f/versions"
      }
    },
    "id": "5b48dbdcc2dc7188911c7b93",
    "name": "Test14",
    "type": "document",
    "catalogTime": 1531501407204,
    "catalogProvider": "recovery",
    "comment": null,
    "tags": null,
    "documentType": "vm",
    "metadataPath":
"/MS:1001/DC:9a71511fe869feaaddc30ef246b30500/VM:01f827f8cf42e2a294fdb8f7c858bc1f",
    "properties": {
      "id": null,
      "name": "Test14",
      "comment": null,
      "creatorId": 0,
      "creationTime": null,

```

```

"type": "vm",
"flags": 0,
"pk": "01f827f8cf42e2a294fdb8f7c858bc1f",
"sessionId": 1531501407204,
"objType": null,
"jobId": "1005",
"host": null,
"protectionInfo": {
  "policyName": "vmware_Backup2vSnap",
  "subPolicyName": "VM Replication0(2101)",
  "subPolicyId": "2101",
  "storageProfileId": 2101,
  "storageProfileName": "Backup2vSnap",
  "subPolicyLabel": null,
  "subPolicyType": "BACKUP",
  "subPolicySubType": null,
  "originalSubPolicyType": null,
  "protectionTime": 1531501437565,
  "lastErrorMessage": null,
  "recoveryPoint": "3e212376-cf66-4924-aac4-41f25875be90",
  "mirrorLabel": null,
  "snapLabels": null,
  "snapshotName": null,
  "protectedVolumePks": [],
  "flashCopyIds": null,
  "emcVnxSnapshotIds": null,
  "cloudSnapshotIds": null,
  "storageSnapshots": [
    {
      "storageType": "vsnap",
      "storageSnapshotId": "2101.snapshot.13622",
      "snapshotReplicationId": null,
      "snapshotVersionId": "4662397561756236964",
      "storageId": "2101",
      "storageVolumeId": "2101.volume.3899"
    }
  ],
  "maskSnapshotIds": null,
  "storageSiteIds": [
    "1000"
  ],
  "primary": null,
  "retentionInfo": {
    "type": "days",
    "count": 10,
    "expiration": 1532365519565
  },
  "skippedVolumePks": [],

```

```

"protectionMethod": "VMWARE_CBT",
"resourceType": null,
"destinationPk": null,
"destinationInfo": {
  "destinationFileName": null,
  "vmx": null,
  "vmxf": null,
  "vmxBackup": null,
  "vmxfBackup": null,
  "configFile": "[G_TMcluster_lun0] Test14/Test14.vmx",
  "extendedConfigFile": null,
  "configFileBackup": null,
  "extendedConfigFileBackup": null,
  "backupPath": null,
  "destinationVolumeKey": null
},
"storageType": [
  "VSNAP"
],
"backupMetadata": null,
"backupDocumentKey": null,
"rmanTag": null,
"recoveryTransactionId": null,
"masked": false,
"dbServerTime": null,
"incrementalSnapshot": false,
"isCGCreatedByXYZ": false,
"transferDuration": 59,
"transferSize": 0,
"storageInfo":
"{\"<hostname|IP>\": [\"spp_1005_2101_16494991242__164949943cf_23_G_TMcluster_lun0\"]},
  "sppoFromVSNap": false,
  "excludedFromBackup": false,
  "dummyObject": false
},
"parentPk": "9a71511fe869feaaddc30ef246b30500",
"providerNodeId": "1001",
"providerUniqueId": null,
"siteId": null,
"autoProvisionedsubPolicyName": null,
"rbacPath":
"root:0/hypervisor.all:0/hypervisor.type:vmware/hypervisor:1001/vdc:9a71511fe869feaaddc30
ef246b30500/vm:01f827f8cf42e2a294fdb8f7c858bc1f",
  "rbacPathId": 576,
  "location": "/vcqa2.ad.XYZ.us/TM Cluster",
  "metadataPath":
"/MS:1001/DC:9a71511fe869feaaddc30ef246b30500/VM:01f827f8cf42e2a294fdb8f7c858bc1f",
  "nativeObject": {

```

```

"resourcePool": {
  "val": "resgroup-46456",
  "type": "ResourcePool"
},
"config_version": "vmx-13",
"summary_storage": {
  "committed": 0,
  "uncommitted": 5557092937,
  "unshared": 0,
  "timestamp": 1531501505745
},
"name": "Test14",
"mor": {
  "val": "vm-188890",
  "type": "VirtualMachine"
},
"config_hardware_numCoresPerSocket": 1,
"config_instanceUuid": "0123be8b-5733-a5e8-ea15-68086831d891",
"runtime": {
  "device": [
    {
      "runtimeState": {
        "vmDirectPathGen2Active": false,
        "vmDirectPathGen2InactiveReasonVm": [
          "vmNptIncompatibleAdapterType",
          "vmNptDisabledOrDisconnectedAdapter"
        ],
        "vmDirectPathGen2InactiveReasonOther": [
          "vmNptIncompatibleHost"
        ]
      },
      "key": 4000
    }
  ],
  "host": {
    "val": "host-45243",
    "type": "HostSystem"
  },
  "connectionState": "connected",
  "powerState": "poweredOff",
  "faultToleranceState": "notConfigured",
  "toolsInstallerMounted": false,
  "suspendInterval": 0,
  "numMksConnections": 0,
  "recordReplayState": "inactive",
  "onlineStandby": false,
  "consolidationNeeded": false,
  "offlineFeatureRequirement": [

```

```

    {
      "key": "cpuid.lm",
      "featureName": "cpuid.lm",
      "value": "Bool:Min:1"
    }
  ],
  "paused": false,
  "snapshotInBackground": false
},
"config_uuid": "01238cde-90cc-b9b5-fcb0-7b74ffae399a",
"config_hardware_numCPU": 1,
"parent": {
  "val": "group-v22",
  "type": "Folder"
},
"config_files_vmPathName": "[G_TMcluster_lun0] Test14/Test14.vmx",
"config_template": false,
"config_hardware_memoryMB": 4096,
"layoutEx_file": [
  {
    "key": 0,
    "name": "[G_TMcluster_lun0] Test14/Test14.vmx",
    "type": "config",
    "size": 0,
    "uniqueSize": 0,
    "accessible": true
  },
  {
    "key": 1,
    "name": "[G_TMcluster_lun0] Test14/Test14.vmsd",
    "type": "snapshotList",
    "size": 0,
    "uniqueSize": 0,
    "accessible": true
  },
  {
    "key": 2,
    "name": "[G_TMcluster_lun0] Test14/Test14.vmdk",
    "type": "diskDescriptor",
    "size": 0,
    "uniqueSize": 0,
    "accessible": true
  },
  {
    "key": 3,
    "name": "[G_TMcluster_lun0] Test14/Test14-flat.vmdk",
    "type": "diskExtent",
    "size": 0,

```

```

        "uniqueSize": 0,
        "accessible": true
    }
]
},
"hypervisorType": "vmware",
"hypervisorKey": "1001",
"hypervisorManagementServerID": "1001",
"nativeKey": "vm-188890",
"tags": [],
"tagCategories": [],
"isTemplate": false,
"isEncrypted": false,
"powerSummary": {
    "powerState": "OFF",
    "lastPowerOnTime": null,
    "lastPowerOffTime": null,
    "lastSuspendTime": null
},
"storageSummary": {
    "committed": 0,
    "uncommitted": 5557092937,
    "shared": 0
},
"hypervisorHostKey": "72adf270c8f30fb059e136fd36c8ace2",
"hypervisorHostName": "r610esx-5.devad.XYZ.us",
"volumes": [
    {
        "name": "G_TMcluster_lun0",
        "key": "e0a4b6e55e2c8c6740ae13c9902a4e0d",
        "isConfigVolume": true
    }
],
"hypervisorFolderKey": "1e17d0f05937d34958706dba11e7dceb",
"hypervisorFolderPath": "",
"uniqueId": "01238cde-90cc-b9b5-fcb0-7b74ffae399a:5032be8b-5733-a5e8-ea15-68086831d891",
"profileId": null,
"keyId": null,
"keyProviderId": null,
"configFilePath": "[G_TMcluster_lun0] Test14/Test14.vmx",
"fileDirPath": null,
"datacenter": {
    "name": "TM Cluster",
    "key": "9a71511fe869feaaddc30ef246b30500"
},
"cluster": {
    "name": "XYZCluster",

```

```

    "key": "77aab164b2cb59aa6fa30ee96149b436"
  },
  "vmGroup": null,
  "resourcePool": {
    "name": "STest",
    "key": "95583e5f117e533c16f327798d8341f9"
  },
  "cpu": 1,
  "coresPerCpu": 1,
  "memory": 4294967296,
  "vmVersion": "vmx-13"
}
},
{
  "links": {
    "self": {
      "rel": "self",
      "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm/5b48dbdcc2dc7188911c7b97"
    },
    "up": {
      "rel": "up",
      "href": "https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm"
    },
    "noSchema": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm/5b48dbdcc2dc7188911c7b97?exclude=(schema)"
    },
    "versions": {
      "rel": "related",
      "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/hypervisorvm/pk.17ab2711d371730b065f1632b1072eed/versions"
    }
  },
  "id": "5b48dbdcc2dc7188911c7b97",
  "name": "Test17R2_",
  "type": "document",
  "catalogTime": 1531501407204,
  "catalogProvider": "recovery",
  "comment": null,
  "tags": null,
  "documentType": "vm",
  "metadataPath":
"/MS:1001/DC:9a71511fe869feaaddc30ef246b30500/VM:17ab2711d371730b065f1632b1072eed",

```

```

"properties": {
  "id": null,
  "name": "Test17R2_",
  "comment": null,
  "creatorId": 0,
  "creationTime": null,
  "type": "vm",
  "flags": 0,
  "pk": "17ab2711d371730b065f1632b1072eed",
  "sessionId": 1531501407204,
  "objType": null,
  "jobId": "1005",
  "host": null,
  "protectionInfo": {
    "policyName": "vmware_Backup2vSnap",
    "subPolicyName": "VM Replication0(2101)",
    "subPolicyId": "2101",
    "storageProfileId": 2101,
    "storageProfileName": "Backup2vSnap",
    "subPolicyLabel": null,
    "subPolicyType": "BACKUP",
    "subPolicySubType": null,
    "originalSubPolicyType": null,
    "protectionTime": 1531501437647,
    "lastErrorMessage": null,
    "recoveryPoint": "3e212376-cf66-4924-aac4-41f25875be90",
    "mirrorLabel": null,
    "snapLabels": null,
    "snapShotName": null,
    "protectedVolumePks": [],
    "flashCopyIds": null,
    "emcVnxSnapshotIds": null,
    "cloudSnapshotIds": null,
    "storageSnapshots": [
      {
        "storageType": "vsnap",
        "storageSnapshotId": "2101.snapshot.13622",
        "snapshotReplicationId": null,
        "snapshotVersionId": "4662397561756236964",
        "storageId": "2101",
        "storageVolumeId": "2101.volume.3899"
      }
    ],
    "maskSnapshotIds": null,
    "storageSiteIds": [
      "1000"
    ],
    "primary": null,

```

```

    "retentionInfo": {
      "type": "days",
      "count": 10,
      "expiration": 1532365519565
    },
    "skippedVolumePks": [],
    "protectionMethod": "VMWARE_CBT",
    "resourceType": null,
    "destinationPk": null,
    "destinationInfo": {
      "destinationFileName": null,
      "vmx": null,
      "vmxf": null,
      "vmxBackup": null,
      "vmxfBackup": null,
      "configFile": "[G_TMcluster_lun0] Test17/Test17.vmx",
      "extendedConfigFile": null,
      "configFileBackup": null,
      "extendedConfigFileBackup": null,
      "backupPath": null,
      "destinationVolumeKey": null
    },
    "storageType": [
      "VSNAP"
    ],
    "backupMetadata": null,
    "backupDocumentKey": null,
    "rmanTag": null,
    "recoveryTransactionId": null,
    "masked": false,
    "dbServerTime": null,
    "incrementalSnapshot": false,
    "isCGCreatedByXYZ": false,
    "transferDuration": 70,
    "transferSize": 0,
    "storageInfo":
    "{ \"<hostname|IP>\": [\"spp_1005_2101_16494991242__164949943cf_23_G_TMcluster_lun0\"] }",
      "sppoFromVSNAP": false,
      "excludedFromBackup": false,
      "dummyObject": false
    },
    "parentPk": "9a71511fe869feaaddc30ef246b30500",
    "providerNodeId": "1001",
    "providerUniqueId": null,
    "siteId": null,
    "autoProvisionedsubPolicyName": null,
    "rbacPath":
    "root:0/hypervisor.all:0/hypervisor.type:vmware/hypervisor:1001/vdc:9a71511fe869feaaddc30

```

```

ef246b30500/vm:17ab2711d371730b065f1632b1072eed",
  "rbacPathId": 581,
  "location": "/vcqa2.ad.XYZ.us/TM Cluster",
  "metadataPath":
"/MS:1001/DC:9a71511fe869feaddc30ef246b30500/VM:17ab2711d371730b065f1632b1072eed",
  "nativeObject": {
    "resourcePool": {
      "val": "resgroup-46456",
      "type": "ResourcePool"
    },
    "config_version": "vmx-13",
    "summary_storage": {
      "committed": 1073741824,
      "uncommitted": 4483351087,
      "unshared": 1073741824,
      "timestamp": 1531501511309
    },
    "name": "Test17R2_",
    "mor": {
      "val": "vm-188893",
      "type": "VirtualMachine"
    },
    "config_hardware_numCoresPerSocket": 1,
    "config_instanceUuid": "01239a52-4088-da36-8483-e86e05adc096",
    "runtime": {
      "device": [
        {
          "runtimeState": {
            "vmDirectPathGen2Active": false,
            "vmDirectPathGen2InactiveReasonVm": [
              "vmNptIncompatibleAdapterType",
              "vmNptDisabledOrDisconnectedAdapter"
            ],
            "vmDirectPathGen2InactiveReasonOther": [
              "vmNptIncompatibleHost"
            ]
          },
          "key": 4000
        }
      ],
      "host": {
        "val": "host-45245",
        "type": "HostSystem"
      },
      "connectionState": "connected",
      "powerState": "poweredOff",
      "faultToleranceState": "notConfigured",
      "toolsInstallerMounted": false,

```

```

"suspendInterval": 0,
"numMksConnections": 0,
"recordReplayState": "inactive",
"onlineStandby": false,
"consolidationNeeded": false,
"offlineFeatureRequirement": [
  {
    "key": "cpuid.lm",
    "featureName": "cpuid.lm",
    "value": "Bool:Min:1"
  }
],
"paused": false,
"snapshotInBackground": false
},
"config_uuid": "0123a16c-99e0-6f94-0e9a-df73119c68b7",
"config_hardware_numCPU": 1,
"parent": {
  "val": "group-v22",
  "type": "Folder"
},
"config_files_vmPathName": "[G_TMcluster_lun0] Test17/Test17.vmx",
"config_template": false,
"config_hardware_memoryMB": 4096,
"layoutEx_file": [
  {
    "key": 0,
    "name": "[G_TMcluster_lun0] Test17/Test17.vmx",
    "type": "config",
    "size": 0,
    "uniqueSize": 0,
    "accessible": true
  },
  {
    "key": 1,
    "name": "[G_TMcluster_lun0] Test17/Test17.vmsd",
    "type": "snapshotList",
    "size": 0,
    "uniqueSize": 0,
    "accessible": true
  },
  {
    "key": 2,
    "name": "[G_TMcluster_lun0] Test17/Test17.vmdk",
    "type": "diskDescriptor",
    "size": 0,
    "uniqueSize": 0,
    "accessible": true
  }
]

```

```

    },
    {
      "key": 3,
      "name": "[G_TMcluster_lun0] Test17/Test17-flat.vmdk",
      "type": "diskExtent",
      "size": 1073741824,
      "uniqueSize": 1073741824,
      "accessible": true
    }
  ]
},
"hypervisorType": "vmware",
"hypervisorKey": "1001",
"hypervisorManagementServerID": "1001",
"nativeKey": "vm-188893",
"tags": [],
"tagCategories": [],
"isTemplate": false,
"isEncrypted": false,
"powerSummary": {
  "powerState": "OFF",
  "lastPowerOnTime": null,
  "lastPowerOffTime": null,
  "lastSuspendTime": null
},
"storageSummary": {
  "committed": 1073741824,
  "uncommitted": 4483351087,
  "shared": 1073741824
},
"hypervisorHostKey": "d7f0a112ef682d0a6570a26398bc4690",
"hypervisorHostName": "r610esx-6.devad.XYZ.us",
"volumes": [
  {
    "name": "G_TMcluster_lun0",
    "key": "e0a4b6e55e2c8c6740ae13c9902a4e0d",
    "isConfigVolume": true
  }
],
"hypervisorFolderKey": "1e17d0f05937d34958706dba11e7dceb",
"hypervisorFolderPath": "",
"uniqueId": "0123a16c-99e0-6f94-0e9a-df73119c68b7:50329a52-4088-da36-8483-
e86e05adc096",
"profileId": null,
"keyId": null,
"keyProviderId": null,
"configFilePath": "[G_TMcluster_lun0] Test17/Test17.vmx",
"fileDirPath": null,

```

```

    "datacenter": {
      "name": "TM Cluster",
      "key": "9a71511fe869feaaddc30ef246b30500"
    },
    "cluster": {
      "name": "XYZCluster",
      "key": "77aab164b2cb59aa6fa30ee96149b436"
    },
    "vmGroup": null,
    "resourcePool": {
      "name": "STest",
      "key": "95583e5f117e533c16f327798d8341f9"
    },
    "cpu": 1,
    "coresPerCpu": 1,
    "memory": 4294967296,
    "vmVersion": "vmx-13"
  }
}
]
}

```

4.14. Generate VM Backup History Report: Unsuccessful

4.14.1. Run a Report of VMs Unsuccessfully Backed Up

The following API lists the VMs for which the backup failed for any reason. Be aware that if at a later time the backup succeeds, the list of VMs from the call to this API might not hold true to the current status of the VM run.

Request Example

```

GET:
https://<hostname|IP>/api/endeavour/catalog/recovery/recoverypointerror?embed=(children(properties))&pageSize=200&filter=[{"property":"sessionId","op": ">": "value": "<value>"}: {"property":"errObjType", "op": "=", "value": "vm"}]

```

4.14.2. Run a Report of VMs Unsuccessfully Backed Up Response

Response Example

```

{
  "links": {
    "self": {

```

```

    "rel": "self",
    "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/recoverypointerror?pageSize=200&pag
eStartIndex=0&filter=%5B%7B%22property%22:%22sessionId%22,%22op%22:%22%3E%22,%22value%22:
%221531334856043%22%7D,%7B%22property%22:%22errObjType%22,%22op%22:%22%3D%22,%22value%22:
%22vm%22%7D%5D&embed=(children(properties))"
  },
  "up": {
    "rel": "up",
    "href": "https://<hostname|IP>/api/endeavour/catalog/recovery"
  },
  "children": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/recoverypointerror?filter=%5B%7B%22
property%22:%22sessionId%22,%22op%22:%22%3E%22,%22value%22:%221531334856043%22%7D,%7B%22p
roperty%22:%22errObjType%22,%22op%22:%22%3D%22,%22value%22:%22vm%22%7D%5D&pageStartIndex=
0&pageSize=200&embed=(children)"
  },
  "schema": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/recoverypointerror?embed=(schema)"
  }
},
"queryElapsedTime": 5,
"id": "recoverypointerror",
"name": "recoverypointerror",
"type": "folder",
"catalogTime": null,
"catalogProvider": "recovery",
"comment": null,
"tags": null,
"documentType": null,
"page": 1,
"properties": {},
"children": [
  {
    "links": {
      "self": {
        "rel": "self",
        "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/recoverypointerror/5b46aa81c2dced70
70d3e7cd"
      },
      "up": {
        "rel": "up",
        "href":

```

```

"https://<hostname|IP>/api/endeavour/catalog/recovery/recoverypointerror"
  },
  "noSchema": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/recoverypointerror/5b46aa81c2dced70
70d3e7cd?exclude=(schema)"
  },
  "versions": {
    "rel": "related",
    "href":
"https://<hostname|IP>/api/endeavour/catalog/recovery/recoverypointerror/pk.c740bdd58651d
9cb9ccefff98b87f50b/versions"
  }
},
"id": "5b46aa81c2dced7070d3e7cd",
"name": "taggedVm1",
"type": "document",
"catalogTime": 1531357683156,
"catalogProvider": "recovery",
"comment": null,
"tags": null,
"documentType": "RecoveryPointError",
"metadataPath": null,
"properties": {
  "id": null,
  "name": "taggedVm1",
  "comment": null,
  "creatorId": 0,
  "creationTime": null,
  "type": "RecoveryPointError",
  "flags": 0,
  "pk": "c740bdd58651d9cb9ccefff98b87f50b",
  "sessionId": 1531357683156,
  "objType": null,
  "jobId": null,
  "host": null,
  "providerNodeId": "1001",
  "providerUniqueId": null,
  "siteId": null,
  "autoProvisionedsubPolicyName": null,
  "errObj": {
    "_id": null,
    "isTemplate": false,
    "isEncrypted": false,
    "powerSummary": {
      "powerState": "OFF",
      "lastPowerOnTime": 1530297799548,

```

```

    "lastPowerOffTime": 1530297809653
  },
  "storageSummary": {
    "committed": 2147669939,
    "uncommitted": 2366161449,
    "shared": 2147483648
  },
  "hypervisorHostKey": "6bdc8d1402597de3c65c286826969247",
  "hypervisorHostName": "grest-esx1.devad.XYZ.us",
  "volumes": [
    {
      "isConfigVolume": true,
      "name": "JCGRFN1",
      "key": "c9dd8303710f4ec5990f22936e55880f"
    }
  ],
  "hypervisorFolderKey": "d392ee49b8831088e72c54d47bb532b1",
  "hypervisorFolderPath": "JC",
  "uniqueId": "0123d2ab-2abf-01cd-a0e9-414ec5ed4369:5015d475-fe1f-a10e-9e99-
dbc0e5cac6c0",
  "configFilePath": "[JCGRFN1] taggedVm1/taggedVm1.vmx",
  "datacenter": {
    "name": "Grest",
    "key": "cb9e77170ef70396fc85a8566c478582"
  },
  "cluster": {
    "name": "Grest Cluster",
    "key": "0dacd6b3a061e0c400440158f2aae2fa"
  },
  "resourcePool": {
    "name": "automation infrastructure products",
    "key": "4f4a4a3f0c5caf0be85d5c641b6425fd"
  },
  "cpu": 1,
  "coresPerCpu": 1,
  "memory": 2147483648,
  "vmVersion": "vmx-13",
  "nativeObject": {
    "resourcePool": {
      "val": "resgroup-303",
      "type": "ResourcePool"
    }
  },
  "config_version": "vmx-13",
  "summary_storage": {
    "dynamicType": null,
    "dynamicProperty": null,
    "committed": 2147669939,
    "uncommitted": 2366161449,

```

```
"unshared": 2147483648,
  "timestamp": 1531314329310
},
"name": "taggedVm1",
"mor": {
  "val": "vm-532",
  "type": "VirtualMachine"
},
"config_hardware_numCoresPerSocket": 1,
"config_instanceUuid": "0123d475-fe1f-a10e-9e99-dbc0e5cac6c0",
"runtime": {
  "dynamicType": null,
  "dynamicProperty": null,
  "device": null,
  "host": {
    "val": "host-85",
    "type": "HostSystem"
  },
  "connectionState": "inaccessible",
  "powerState": "poweredOff",
  "faultToleranceState": "notConfigured",
  "dasVmProtection": null,
  "toolsInstallerMounted": false,
  "suspendTime": null,
  "bootTime": null,
  "suspendInterval": null,
  "question": null,
  "memoryOverhead": null,
  "maxCpuUsage": null,
  "maxMemoryUsage": null,
  "numMksConnections": 0,
  "recordReplayState": "inactive",
  "cleanPowerOff": null,
  "needSecondaryReason": null,
  "onlineStandby": false,
  "minRequiredEVCMODEKey": null,
  "consolidationNeeded": false,
  "offlineFeatureRequirement": null,
  "featureRequirement": null,
  "featureMask": null,
  "vFlashCacheAllocation": null,
  "paused": false,
  "snapshotInBackground": false,
  "quiescedForkParent": null
},
"config_uuid": "0123d2ab-2abf-01cd-a0e9-414ec5ed4369",
"config_hardware_numCPU": 1,
"parent": {
```

```

    "val": "group-v203",
    "type": "Folder"
  },
  "config_files_vmPathName": "[JCGRFN1] taggedVm1/taggedVm1.vmx",
  "config_template": false,
  "config_hardware_memoryMB": 2048,
  "layoutEx_file": [
    {
      "dynamicType": null,
      "dynamicProperty": null,
      "key": 0,
      "name": "[JCGRFN1] taggedVm1/taggedVm1.vmx",
      "type": "config",
      "size": 0,
      "uniqueSize": null,
      "backingObjectId": null,
      "accessible": false
    }
  ]
},
"hypervisorType": "vmware",
"hypervisorKey": "1001",
"hypervisorManagementServerID": "1001",
"nativeKey": "vm-532",
"tags": [],
"tagCategories": [],
"sessionId": 1531357683156,
"jobId": "1013",
"protectionInfo": {
  "policyName": "vmware_Pytest_SLA_1",
  "subPolicyName": "VM Replication0(2106)",
  "subPolicyId": "2106",
  "storageProfileId": 2106,
  "storageProfileName": "Pytest_SLA_1",
  "subPolicyType": "BACKUP",
  "protectionTime": 1531357821363,
  "lastErrorMessage": "[com.vmware.vim25.InvalidState The operation is not
allowed in the current state. Error in creating snapshot (SPP-20180712-010816-615) of VM
(taggedVm1)]",
  "storageSiteIds": [
    "1000"
  ],
  "retentionInfo": {
    "type": "days",
    "count": 15,
    "expiration": 1532653821363
  }
},
"masked": false,

```

```

    "incrementalSnapshot": false,
    "isCGCreatedByXYZ": false,
    "transferDuration": 0,
    "transferSize": 0,
    "storageInfo":
"{\"localhost\":[\"spp_1013_2106_1648c07f2dc__1648c08080c_88_JCGRFN1\"]}\",
    "sppoFromVSNap": false,
    "excludedFromBackup": false,
    "dummyObject": false
  },
  "parentPk": "d392ee49b8831088e72c54d47bb532b1",
  "providerNodeId": "1001",
  "rbacPath":
"root:0/hypervisor.all:0/hypervisor.type:vmware/hypervisor:1001/vdc:cb9e77170ef70396fc85a
8566c478582/vfld:d392ee49b8831088e72c54d47bb532b1/vm:c740bdd58651d9cb9c9cefff98b87f50b",
    "rbacPathId": 40,
    "location": "/dev8vcenter.ad.XYZ.us/Grest/JC",
    "metadataPath":
"/MS:1001/DC:cb9e77170ef70396fc85a8566c478582/FLDR:d392ee49b8831088e72c54d47bb532b1/VM:c7
40bdd58651d9cb9c9cefff98b87f50b",
    "name": "taggedVm1",
    "creatorId": 0,
    "type": "vm",
    "flags": 0,
    "pk": "c740bdd58651d9cb9c9cefff98b87f50b"
  },
  "errObjType": "vm"
}
]
}

```

Notices

This information was developed for products and services offered in the US. This material might be available from IBM in other languages. However, you may be required to own a copy of the product or product version in that language in order to access it.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing
IBM Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
US*

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
19-21, Nihonbashi-Hakozakicho, Chuo-ku
Tokyo 103-8510, Japan*

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those

websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*IBM Director of Licensing
IBM Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
US*

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

The performance data discussed herein is presented as derived under specific operating conditions. Actual results may vary.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Each copy or any portion of these sample programs or any derivative work must include a copyright notice as follows: © (your company name) (year). Portions of this code are derived from IBM Corp. Sample Programs. © Copyright IBM Corp. _enter the year or years_.

Trademarks

IBM, the IBM logo, and ibm.com[®] are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

Adobe is a registered trademark of Adobe Systems Incorporated in the United States, and/or other countries.

Linear Tape-Open, LTO, and Ultrium are trademarks of HP, IBM Corp. and Quantum in the U.S. and other countries.

Intel and Itanium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, and Windows NT are trademarks of Microsoft Corporation in the United States, other countries, or both.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

SoftLayer[®] is a registered trademark of SoftLayer, Inc., an IBM Company.

UNIX is a registered trademark of The Open Group in the United States and other countries.

VMware, VMware vCenter Server, and VMware vSphere are registered trademarks or trademarks of VMware, Inc. or its subsidiaries in the United States and/or other jurisdictions.

Terms and conditions for product documentation

Permissions for the use of these publications are granted subject to the following terms and conditions.

Applicability

These terms and conditions are in addition to any terms of use for the IBM website.

Personal use

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of IBM.

Commercial use

You may reproduce, distribute and display these publications solely within

your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

Rights Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

Privacy policy considerations

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user, or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

This Software Offering does not use cookies or other technologies to collect personally identifiable information.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at <http://www.ibm.com/privacy> and IBM's Online Privacy Statement at <http://www.ibm.com/privacy/details> in the section entitled "Cookies, Web Beacons and Other Technologies," and the "IBM Software Products and Software-as-a-Service Privacy Statement" at <http://www.ibm.com/software/info/product-privacy>.



Product Number: 5737-F11

Printed in USA