

IBM Storage Protect for Databases

Oracle Installation and User's Guide for Windows

8.2.0



Contents

Who should read this guide	5
Publications	5
What's new	5
Protection for Oracle Server databases	6
Overview of Data Protection for Oracle	6
RMAN and Data Protection for Oracle	6
LAN-free data transfer	6
Migration and coexistence with Data Protection for Oracle	6
Automated failover for data recovery	7
Data Protection for Oracle installation.....	9
Installing Data Protection for Oracle	9
Installation prerequisites	9
Installing for Windows™	10
Installing in silent mode	10
Configuring Data Protection for Oracle	15
Configuration with default settings	15
Configuring Data Protection for Oracle.....	16
Define Data Protection for Oracle options in the tdpo . opt file	16
Register the Data Protection for Oracle node to an IBM® Storage Protect server	18
Define IBM® Storage Protect options in the client options file.....	19
Define IBM® Storage Protect policy requirements.....	22
Initialize the password with an IBM® Storage Protect server	23
Protecting Oracle Server data.....	24
RMAN and Data Protection for Oracle	24
Starting RMAN	24
Editing RMAN scripts	25
The Duplex Copy function	27
Removing old backups	28
Setting up a schedule example.....	28
Setting up a schedule on the IBM® Storage Protect server.....	29
Setting up a schedule on the workstation with the Oracle Server	29
Querying backup objects	33
Data deduplication with Data Protection for Oracle.....	33
Overview of data deduplication	33
Setting up for client-side data deduplication	33
Determining total data reduction	35
Commands and utilities for Data Protection for Oracle	36
tdpoconf and tdposync utilities.....	36
Command line syntax and characteristics	36
tdpoconf utility	36
tdposync utility	38
Accessibility features for the IBM® Storage Protect product family.....	46
Overview	46
Keyboard navigation	46
Interface information	46
Vendor software	46
Related accessibility information.....	46
Notices.....	47
Trademarks.....	48
Terms and conditions for product documentation	48
Privacy policy considerations	49
Glossary	50
Index	51

Note:

Before you use this information and the product it supports, read the information in “Notices” on page 47.

This edition applies to version 8, release 2 of IBM® Storage Protect for Databases: Data Protection for Oracle for Windows™ (product number 5725-X01) and to all subsequent releases and modifications until otherwise indicated in new editions.

About this publication

This publication contains information about installing, configuring, administering, and using IBM® Storage Protect for Databases: Data Protection for Oracle.

Data Protection for Oracle runs online or offline backups of Oracle 11g databases to IBM® Storage Protect storage. This integration with the RMAN Media Management API maximizes the protection of data, and provides a comprehensive storage management solution.

IBM® Storage Protect is a client/server licensed product that provides storage management services in a multiplatform computer environment.

Who should read this guide

The target audience for this publication includes system installers, system users, Oracle database administrators, IBM® Storage Protect administrators, and system administrators.

It is assumed that you have an understanding of the following applications:

- Oracle server
- IBM® Storage Protect server
- IBM® Storage Protect backup-archive client
- IBM® Storage Protect application programming interface

It is assumed that you have an understanding of the Windows™ Server operating system on which your Oracle database is hosted.

Publications

The IBM® Storage Protect product family includes IBM® Storage Protect Plus, , , and several other storage management products from IBM®.

To view IBM® product documentation, see [IBM® Documentation](#).

Data Protection for Oracle updates V8.1.23

This document provides information about what's new or what has changed in Data Protection for Oracle version 8.1.23.

What's new

The official product name IBM Storage® Protect for Databases - Data Protection for Oracle is now changed also in the user interfaces, command output, and other code-related messages.

Protection for Oracle Server databases

A brief overview of IBM® Storage Protect for Databases: Data Protection for Oracle is provided.

Overview of Data Protection for Oracle

Data Protection for Oracle interfaces with the Oracle Recovery Manager (RMAN) to send backup versions of Oracle databases to the IBM® Storage Protect server.

Data Protection for Oracle currently supports Oracle 11g databases with the Oracle Recovery Manager. See [“Data Protection for Oracle installation” on page 9](#) for specific levels of supported Oracle databases.

RMAN and Data Protection for Oracle

Oracle Recovery Manager (RMAN) provides consistent and secure backup, restore, and recovery performance for Oracle databases. While the Oracle RMAN initiates a backup or restore, Data Protection for Oracle acts as the interface to the IBM® Storage Protect server. The IBM® Storage Protect server then applies administrator-defined storage management policies to the data. Data Protection for Oracle implements the Oracle defined Media Management application programming interface (SBTAPI) 2.0. This SBTAPI communicates with RMAN and translates Oracle commands into IBM® Storage Protect API calls to the IBM® Storage Protect server.

You can use RMAN Data Protection for Oracle to run backup and restore functions that are listed.

- Full and incremental backup functions online or offline for:
 - Databases
 - Table spaces
 - Data files
 - Archive log files
 - Control files
- Full database restores while offline.
- Table space and data file restore online or offline.

LAN-free data transfer

Data Protection for Oracle supports backup and restore operations in a LAN-free environment. This environment shifts the movement of data from the communications network to a storage area network (SAN). Data moves over the SAN to a SAN-attached storage device by the IBM® Storage Protect Storage Agent. Running Data Protection for Oracle in a LAN-free environment avoids constraints of the network. The load on the IBM® Storage Protect server is decreased, allowing the server to support a greater number of simultaneous connections.

Data Protection for Oracle can be installed on a client with the Storage Agent (STA). The agents can be installed on a non-STA client. The backup data is sent over the LAN (TCP/IP) to the STA client. The STA client sends the data over the SAN LAN-free, directly to tape or disk.

In addition to specific LAN-free requirements, you must specify the following option:

lanfreetcpserveraddress

Specifies the TCP/IP address for an IBM® Storage Protect Storage Agent.

Migration and coexistence with Data Protection for Oracle

The migration considerations to the new version of Data Protection for Oracle are provided.

- Existing backups that are created with a previous version of Data Protection for Oracle are restorable with Data Protection for Oracle 7.1.

- Backups that are created with Data Protection for Oracle 7.1 cannot be restored with previous versions of Data Protection for Oracle.

Related information

[Configuring Data Protection for Oracle](#)

[Editing RMAN scripts](#)

Automated failover for data recovery

When there is an outage on the IBM Storage® Protect server, Data Protection for Oracle can fail over to a secondary server for data recovery operations.

The IBM Storage® Protect server that Data Protection for Oracle connects to for backup operations is called the *primary server*. When the primary server and the Data Protection for Oracle node are set up for node replication on the primary server, the node can be replicated to another IBM Storage® Protect server, called the *secondary server*.

During normal operations, connection information for the secondary server is automatically sent to Data Protection for Oracle from the primary server. The secondary server information is saved to the client options file (dsm.opt) on the Data Protection for Oracle node. No manual intervention is required by you to add the information for the secondary server.

Each time Data Protection for Oracle logs on to the server for backup services, it attempts to contact the primary server. If the primary server is unavailable, Data Protection for Oracle automatically fails over to the secondary server. In failover mode, you can restore data that was replicated to the secondary server. When the primary server is online again, Data Protection for Oracle automatically fails back to the primary server the next time it connects to the server.

You can confirm that Data Protection for Oracle has failed over by looking for entries about the secondary server in the `dsierror.log` file.

Requirements: To ensure that automated client failover can occur, Data Protection for Oracle must meet the following requirements:

- Data Protection for Oracle must be at the V7.1 level.
- The primary server and secondary server must be at the V7.1 level.
- The primary and secondary servers must be set up for node replication.
- The Data Protection for Oracle node must be configured for replication with the `replstate=enabled` option in the node definition on the server.
- Before the connection information for the secondary server can be sent to IBM Storage® Protect Snapshot, the following processes must occur:
 - You must back up data at least one time to the primary server.
 - The Data Protection for Oracle node on the primary server must be replicated at least one time to the secondary server.

Restriction: The following restrictions apply to Data Protection for Oracle during failover:

- Any operation that requires data to be stored on the IBM Storage® Protect server, such as backup operations, are not available. You can use only data recovery functions, such as restore or query operations.
- Schedules are not replicated to the secondary server. Therefore, schedules are not run while the primary server is unavailable.
- If the primary server goes down before or during node replication, the most recent backup data is not successfully replicated to the secondary server. The replication status of the file space is not current. If you attempt to restore data in failover mode and the replication status is not current, the

recovered data might not be usable. You must wait until the primary server comes back online before you can restore the data.

Data Protection for Oracle installation

Install IBM® Storage Protect for Databases: Data Protection for Oracle to protect your Oracle server databases.

Installing Data Protection for Oracle

Verify installation prerequisites and follow the instructions to install Data Protection for Oracle for Windows™.

Before you begin

Hardware, software, and operating system requirements must be met before you attempt to install Data Protection for Oracle.

Installation prerequisites

Before you install Data Protection for Oracle, ensure that your system meets the minimum hardware, software, and operating system requirements.

The minimum hardware and software requirements for the Data Protection for Oracle release are available in the hardware and software requirements technote for each particular release. For current requirements, review the Hardware and Software Requirements technote for your version of Data Protection for Oracle. This technote is available in the *IBM Storage Protect™ for Databases - All Requirements Documents* website at <http://www.ibm.com/support/docview.wss?uid=swg21218747>. From the page, follow the link to the requirements technote for your specific release or update level.

Note:

- You cannot install the 32-bit version of Data Protection for Oracle on a 64-bit operating system.
- You must have administrative authority to install Data Protection for Oracle on a Windows™ server where the target database is stored.
- If Data Protection for Oracle was not previously installed on your system, you can install it to the IBM Storage Protect™ base directory. For best results, install all IBM Storage Protect™ products and components into the same base directory.
- The installation process does not overwrite the existing `dsm.opt` options file, `tdpo.opt` configuration file, or log files.

Minimum hardware requirements

Your system must meet the minimum hardware requirements for installing or operating Data Protection for Oracle in a Windows™ environment.

The minimum hardware requirements for the Data Protection for Oracle release are available in the hardware and software requirements technote for each particular release. For current requirements, review the Hardware and Software Requirements technote for your version of Data Protection for Oracle. This technote is available in the *TSM for Databases - All Requirements Documents* website at <http://www.ibm.com/support/docview.wss?uid=swg21218747>. From the page, follow the link to the requirements technote for your specific release or update level.

Minimum software and operating system requirements

Your system must meet the minimum software and operating requirements for using Data Protection for Oracle in a Windows™ environment.

The minimum hardware and software requirements for the Data Protection for Oracle release are available in the hardware and software requirements technote for each particular release. For current requirements, review the *Hardware and Software Requirements* technote for your version of Data Protection for Oracle. This technote is available in the *TSM for Databases - All Requirements Documents* website at <http://www.ibm.com/support/docview.wss?uid=swg21218747>. From the page, follow the link to the requirements technote for your specific release or update level.

Virtualization support

Information about the virtualization environments that can be used with Data Protection for Oracle is available in the *IBM® Tivoli® Storage Manager guest support for virtual machines and virtualization* website at: <http://www.ibm.com/support/docview.wss?uid=swg21239546>.

Installing for Windows™

Use these instructions to install Data Protection for Oracle.

Procedure

With the Data Protection for Oracle DVD in the DVD drive, Windows™ automatically starts the **InstallShield** wizard. If the wizard is not enabled, complete the following steps.

1. Run one of the following commands, where *x* is the DVD drive letter:
 - (x86): *x*:\\oracle\\windows\\x32\\client\\setup\\spinstall.exe
 - (x86_64): *x*:\\oracle\\windows\\x64\\client\\setup\\spinstall.exe

Click **OK** to start the installation program.

2. Accept the License Agreement and click **Finish** to complete the installation.

Installing in silent mode

You can install Data Protection for Oracle in silent mode. A silent installation runs independently without any intervention so that you are not required to monitor, or provide input.

About this task

This method is useful when you must install Data Protection for Oracle on a number of different computers with identical hardware. For example, a company might have 25 Oracle servers that are installed across 25 different sites. You can create an unattended installation package and make it available to the 25 sites. This method ensures a consistent configuration and avoids different people all entering Data Protection for Oracle parameters. The installation package can be placed on a DVD and sent to each site, or it can be placed on a file server for distribution.

You can install in silent mode with one of the following methods:

Setup Program

Use the **setup** command and specify silent installation options.

Microsoft™ Installer (MSI)

Use **msiexec.exe** to install the package.

The following options can be used with either silent installation method.

Table 1: Silent installation options	
Option	Description
/i	Specifies the program to install the product.
/l*v	Specifies verbose logging.
/qn	Runs the installation quietly, without displaying windows.
/s	Specifies silent mode.

Option	Description
/v	<p>The setup passes the parameter string to the MSI executable program (msiexec.exe). The following syntax is required when you use the /v option:</p> <ul style="list-style-type: none"> • Use a backslash (\) before quotation marks (" ") that are contained within existing quotation marks. • Do not include a space between the /v command-line option and its arguments. • Separate parameters that are entered with the /v command-line option with a space. • Create a log file by specifying the directory and file name after the command. The directory must exist before you start the installation process.
/x	Specifies that the program is to uninstall the product.
addlocal	Specifies features to install.
allusers	Specifies which users can use the installation package.
installdir	Specifies the directory where Data Protection for Oracle is to be installed.
reboot	<p>Specifies whether to prompt the user to restart the system after silent installation.</p> <p>Force</p> <p>Always prompts user to restart after an installation.</p> <p>Suppress</p> <p>Suppresses prompt to restart after an installation.</p> <p>ReallySuppress</p> <p>Suppresses all restart operations, and prompts the user to restart after an installation.</p>
rebootyesno	Specifies whether to restart the system after silent installation.

The following components are used in this procedure and are case-sensitive.

Table 2: Silent installation components (base client only)	
Component	Description
Client	Data Protection for Oracle code
License_Paid	License file is used when paid versions of Data Protection for Oracle are installed

Installing in silent mode with the setup executable file

Use the setup program, by running the `setup.exe` file, to install Data Protection for Oracle in silent mode. When you install in silent mode, you do not need to monitor the process or provide input.

Before you begin

Install Data Protection for Oracle from an account that is a member of the local Administrators group for the computer where the Oracle server is running.

About this task

The following commands can be used for installing Data Protection for Oracle in silent mode.

- Run the following command to install Data Protection for Oracle in silent mode to the default installation directory:

```
setup.exe /s/v/qn
```

- Install Data Protection for Oracle in silent mode to the default installation directory with custom features by running the following command:

```
spinstall.exe /s /v"INSTALLDIR=\"c:\program files\tivoli\tsm\"  
ADDLOCAL=\"Client,License_Paid\"  
TRANSFORM=1033.mst /qn /l*v \"c:\temp\log.txt\""
```

In a custom installation, list all features after the **addlocal** option.

Installing in silent mode with MSI

You can install Data Protection for Oracle in silent mode by using the Microsoft™ Installer program (MSI), and the `msiexec.exe` file.

Before you begin

Prepare to install Data Protection for Oracle from an account that is a member of the local Administrator group for the computer where the Oracle server is running.

About this task

Important: Data Protection for Oracle installs the Microsoft™ Visual C++ 2012 Redistributable Package as a setup prerequisite. If you are installing the product with the `msiexec.exe` file, you must separately install the Microsoft™ Visual C++ 2012 Redistributable Package. The files are included in the installable packages:

- For Windows™ 64 bit, install the following file:
In the path to the Data Protection for Oracle files: `\ISSetupPrerequisites\{3A3AF437-A9CD-472f-9BC9-8EEDD7505A02} \vc_redist_x64.exe`

- The following example silently installs to a directory other than the default installation directory and includes custom features:

```
msiexec /i<path to msi file>\\"IBM Tivoli Storage Manager for Databases - Oracle.msi"  
RebootYesNo="No" Reboot="Suppress" ALLUSERS=1  
INSTALLDIR="c:\program files\tivoli\tsm"  
ADDLOCAL="Client,License_Paid"  
TRANSFORM=1033.mst /norestart /qn /l*v "c:\temp\log.txt"
```

Capturing a log of the installation

Capture a log of the installation of Data Protection for Oracle using the following procedure.

About this task

The following environmental information can be helpful:

Gather a detailed log of the installation procedure in a file called `setup.log`. To gather the information, run the setup program as follows:

```
setup /v"/l*v setup.log"
```

Creating an installation package

You have a choice of making the Data Protection for Oracle installation package available for distribution on a DVD or on a server.

About this task

You can burn a DVD or place the package in a shared directory on a server. The package contains the Data Protection for Oracle code distribution files for installing the product.

Creating a package for installing in silent mode

Use these instructions to create a silent installation package.

Before you begin

Before you create the package, decide where you are going to store the package. If you are burning a DVD, use a staging directory. If you are placing the package on a file server, you can use a staging directory or you can build the package directly on the file server.

Procedure

1. Run the following command to create the `tdpdpkg` staging directory:

```
mkdir c:\tdpdpkg
```

2. From the command line, navigate to the staging directory `cd /d c:\tdpdpkg`
3. Copy the Data Protection for Oracle DVD distribution files to the staging directory:
`xcopy g:*. * . /s`
4. Replace the existing `setup.bat` with the one created in the previous step: `copy c:\setup.bat`

What to do next

The installation package can be placed on a DVD or made available from a shared directory.

Playing back the installation package in silent mode

You can run an installation package from a DVD or a shared directory. This process is called *playing back* the installation.

About this task

No visual cues exist to inform you when the installation finishes, although you can add visual cues to the batch file. Therefore, ensure that you allow enough time for the installation to complete.

- If autostart is enabled, the silent installation begins as soon as the DVD is inserted into the drive.
- If the installation package is in a shared directory, a user can run the command as follows:
From a staging directory that is called `tdpdpkg` at `\\machine1\d$`, the command `net use x: \\machine1\d$` can be run from a different computer to share the drive as drive `x`.

Creating batch files for installing in silent mode

You can create a batch file to install Data Protection for Oracle in silent mode, with the parameters that you want.

About this task

The following example shows a sample script that includes specific installation options.

```
@echo off
rem =====
rem sample silent install script
```

```
rem
setup /s /v"INSTALLDIR=\"X:\Install Path\" /qn"
rem =====
rem Code can be added after the
rem installation completes to
rem customize the dsm.opt files
rem if needed.
rem =====
```

Configuring Data Protection for Oracle

Use these instructions to configure Data Protection for Oracle for backup and restore operations.

Before you begin

Data Protection for Oracle must be installed on your system and an IBM Storage Protect™ server must be available to communicate with Data Protection for Oracle.

About this task

Review all configuration information before you run any configuration tasks.

Configuration with default settings

Use the Data Protection for Oracle quick configuration option to quickly configure with default settings and minimal configuration tasks. Setup time is minimized and you proceed quickly to a state where you can begin backing up your Oracle databases.

Before you begin

Install Data Protection for Oracle. For detailed installation instructions, see [“Data Protection for Oracle installation” on page 9](#).

About this task

Use the instructions to configure Data Protection for Oracle. Change the listed installation paths and library extensions according to the operating system you are using.

See [“Configuring Data Protection for Oracle” on page 16](#) for detailed instructions on how to customize Data Protection for Oracle for your environment and processing needs.

Procedure

1. Depending on your operating system, change to one of the following directories:
 - AIX® 64-bit operating system: /usr/tivoli/tsm/client/oracle/bin64
 - Linux operating system: /opt/tivoli/tsm/client/oracle/bin64
 - Windows™ 64-bit Server system: C:\Program Files\Tivoli\TSM\Agent0BA64
2. Copy the `tdpo.opt.smp` file to `tdpo.opt`.
3. For Windows, these instructions use a 64-bit Windows™ Server system as the example operating system.

```
dsmi_orc_config C:\Program Files\Tivoli\TSM\Agent0BA64\dsm.opt  
dsmi_log C:\Program Files\Tivoli\TSM\Agent0BA64
```

For more information about these options, see [“Available Data Protection for Oracle options” on page 17](#).

4. Register the node to the IBM® Storage Protect server with the following command:

```
REG nodename NodeA1 hostname_oracle password maxnummp=n
```

Where *hostname* is the name of the system that Data Protection for Oracle is installed, *password* is the password for this node, and *n* is equal to the number of channels that you are planning to use.

5. Make sure that the `<oracle user>` has the following permissions:
 - Read and Write permissions to the following directories:
 - C:\Program Files\Tivoli\TSM\Agent0BA64 directory
 - `tdpoerror.log` and the directory where it is stored
6. Run the **tdpoconf password** command as the `<oracle user>` to generate the password file. For more information about this command, see [“password command” on page 36](#).

Enter the password from Step [“4” on page 15](#) three times.

7. Run the **tdpoconf showenvironment** command to view and confirm your configuration. For more information about this command, see [“showenvironment command” on page 37](#).
8. As <oracle user>, run the RMAN backup script with the **ENV=(TDPO_OPTFILE=C:\Program Files\Tivoli\TSM\Agent0BA64\tdpo.opt)** parameter specified. For example:

```
run
{
  allocate channel t1 type 'sbt_tape' parms
    'ENV=(TDPO_OPTFILE=C:\Program Files\Tivoli\TSM\Agent0BA64\tdpo.opt)';

  backup
    filesperset 5
    format 'df_%t_%s_%p'
    (database);
}
```

Note, the `allocate channel` entry is divided on two lines after the `parms` option is specified to accommodate page formatting.

For more information about RMAN backup scripts, see [“RMAN and Data Protection for Oracle” on page 24](#).

Configuring Data Protection for Oracle

After Data Protection for Oracle is successfully installed, you must complete the configuration tasks.

Procedure

1. Define Data Protection for Oracle options in the `tdpo.opt` file.
2. Register the Data Protection for Oracle node to an IBM® Storage Protect server.
3. Define IBM® Storage Protect options in the `dsm.opt` file.
4. Define IBM® Storage Protect policy requirements.
5. Initialize the password with an IBM® Storage Protect server.

Result

If you would like to configure Data Protection for Oracle using default settings, see [“Configuration with default settings” on page 15](#) for instructions.

Define Data Protection for Oracle options in the `tdpo.opt` file

You must define options to control the way Data Protection for Oracle backs up and restores data.

About this task

The Data Protection for Oracle options file, `tdpo.opt`, contains options that determine the behavior and performance of Data Protection for Oracle. The only environment variable Data Protection for Oracle recognizes within an RMAN script is the fully qualified path name to the `tdpo.opt` file. Therefore, some RMAN scripts must be edited to use **TDPO_OPTFILE**=fully qualified path and file name of options file variable in place of other environment variables. For example:

```
allocate channel t1 type 'sbt_tape' parms
  'ENV=(TDPO_OPTFILE=C:\RMAN\scripts\tdpo.opt)'
```

For further information about RMAN scripts, see [“Editing RMAN scripts” on page 25](#) for further information. Note, the `allocate channel` entry is divided on two lines after the `parms` option to accommodate page formatting.

If the **TDPO_OPTFILE** variable is not provided, Data Protection for Oracle uses the `tdpo.opt` file in the Data Protection for Oracle default installation directory. If this file does not exist, Data Protection for Oracle fails.

Though it is possible to change values in the options file, you cannot change the `dsmi` options until you restart Data Protection for Oracle. Data Protection for Oracle loads these values from the default `tdpo.opt` file into the default installation directory when the Oracle service is started.

Note:

- For best results, use the `tdpo.opt` file exclusively instead of default parameters.
- RMAN and the `tdpoconf` and `tdposync` utilities use the options that are defined in the `tdpo.opt` file.
- By default, the `tdpo.opt` file is in the directory where Data Protection for Oracle is installed.
- You can specify options in the `tdpo.opt` file in both uppercase or lowercase type.

Available Data Protection for Oracle options

The options that can be set in the `tdpo.opt` file for Data Protection for Oracle are described.

The following options can be set in the `tdpo.opt` file:

dsmi_log

Specify the directory that contains the Data Protection for Oracle error log file `tdpoerror.log`.

dsmi_orc_config

Specify the complete path to the IBM® Storage Protect client user options file `dsm.opt` used during the Data Protection for Oracle session. If you do not specify this option, Data Protection for Oracle looks for the options file in the Data Protection for Oracle installation directory. You must specify this option if your IBM® Storage Protect client user options file is in a directory other than the Data Protection for Oracle installation directory.

tdpo_enablescriptinput

You can automate the maintenance of IBM® Storage Protect Data Protection for Oracle without the need for user interaction. You can set the `tdpo_enablescriptinput` option to allow the **tdposync** utility to receive input from a script or batch file.

You can specify the following options:

Yes

The **tdposync** utility can receive redirected input that allows the utility to run in batch mode.

No

The **tdposync** utility must be run in interactive mode and requires user input to complete its run. This option is the default.

Attention: If you run the **tdposync** command interactively and the `tdpo_enablescriptinput` is set to **Yes**, the input for the Oracle password is shown in plain text. To obfuscate the password, set the `tdpo_enablescriptinput` to **No**.

tdpo_fs

Specify a file space name on the IBM® Storage Protect server for Data Protection for Oracle backup, delete, and restore operations. The file space name can contain a string of 1-1024 characters.

- The default file space name is `adsmorc`.
- When you have more than one Oracle database, use this option to back up each Oracle target database to its own file space on the IBM® Storage Protect server.
- The file space name in the `include/exclude` statement must match the file space name that is specified in the `tdpo_fs` option for `include/exclude` processing to function correctly.

tdpo_date_fmt

This option specifies the format that you want to use to display dates.
You can specify a number, 1 - 5. The default value is 1.

- 1 MM/DD/YYYY (Default value)
- 2 DD-MM-YYYY
- 3 YYYY-MM-DD
- 4 DD.MM.YYYY
- 5 YYYY.MM.DD

tdpo_num_fmt

This option specifies the format that you want to use to display numbers. You can specify a number, 1 - 6.
The default value is 1.

- 1 1,000.00 (Default value)
- 2 1,000,00
- 3 1 000,00
- 4 1 000.00
- 5 1.000,00
- 6 1'000,00

tdpo_time_fmt

This option specifies the format that you want to use to display time.
You can specify a number, 1 - 4. The default value is 1.

- 1 23:00:00 (Default value)
- 2 23,00,00
- 3 23.00.00
- 4 12:00:00 A/P

tdpo_mgmt_class_2

This option specifies the second management class that is used for copy 2 in the RMAN duplex copy command.

tdpo_mgmt_class_3

This option specifies the third management class that is used for copy 3 in the RMAN duplex copy command.

tdpo_mgmt_class_4

This option specifies the fourth management class that is used for copy 4 in the RMAN duplex copy command. Four copies is the maximum that is allowed by RMAN.

Note: See [“The Duplex Copy function” on page 27](#) for specific details on using management class options.

Register the Data Protection for Oracle node to an IBM® Storage Protect server

The Data Protection for Oracle node name and password when required must be registered to the IBM® Storage Protect server before you can begin requesting backup and restore services. The process of setting up a node name and password with the IBM® Storage Protect server is called registration.

About this task

The following information is needed to register Data Protection for Oracle with the IBM® Storage Protect server:

- Data Protection for Oracle node name:
The node name identifies the instance on which Data Protection for Oracle is installed. Use a separate and unique node name for Data Protection for Oracle. This prevents any confusion with an existing IBM® Storage Protect backup-archive client on the same workstation.
- Initial password:
Specify the password that you want to use, if a password is required.

The following information is defined by the IBM® Storage Protect administrator:

- The policy domain to which your client node belongs.
A policy domain contains policy sets and management classes that control how IBM® Storage Protect manages the objects you back up. Rather than binding Data Protection for Oracle backups to a different management class, define a unique policy domain for Data Protection for Oracle node names. These backups can be bound to the default management class within this unique policy domain. Rather than binding a different management class for Oracle backups, specify a different domain for the backups with a separate management class.
- The authority to enable compression.
The IBM® Storage Protect administrator can specify the server to compress files. If the IBM® Storage Protect administrator specifies that the compression decision belongs to the client **compressionclient**, you must specify **compressionyes** in the client user options file `dsm.opt` so that the Data Protection for Oracle node is able to compress objects before it sends them to the IBM® Storage Protect server.
- The authority to delete backup data from IBM® Storage Protect storage.
The Data Protection for Oracle node can only delete backed up data from IBM® Storage Protect storage if the IBM® Storage Protect administrator registers the node with `backdeleteauthority`. Specify the following option to allow `backdeleteauthority`:
`backdelete yes`
Note, when `backdelete no` is specified and a deletion request is made, the request fails and an error message displays. Therefore, specify `backdelete yes` for the object to be immediately removed from the IBM® Storage Protect server when the next inventory expiration occurs. This expiration also makes the previously used storage space available for new use.

Define IBM® Storage Protect options in the client options file

You must define some IBM® Storage Protect options after the Data Protection for Oracle node is registered to the IBM® Storage Protect server:

About this task

- These options are defined in the IBM® Storage Protect client user options file `dsm.opt` by default.
- Note, the IBM® Storage Protect client user options file `dsm.opt` by default, that you must edit for Data Protection for Oracle is in the directory that is specified by the `thedsmi_orc_config` option. If this option is not specified, Data Protection for Oracle looks for this options file in the Data Protection for Oracle installation directory.
- Data Protection for Oracle provides sample IBM® Storage Protect options files that you can modify for this purpose. These sample files are in the Data Protection for Oracle installation directory.
- The IBM® Storage Protect administrator can provide you with the TCP server address **tcpserveraddress** and communication method **commmethod** for connecting Data Protection for Oracle to the IBM® Storage Protect server.

Required options

You must set required IBM® Storage Protect client options to operate Data Protection for Oracle.

Specify the required options in the IBM® Storage Protect client user options file `dsm.opt` by default, in the directory that is specified by the `thedsmi_orc_config` option.

nodename

Specify the Data Protection for Oracle node name that is used during operations with the IBM® Storage Protect server. The node name can contain a string of 1 - 64 characters.

To restore data from one Oracle server to another with Data Protection for Oracle, make sure that the value of the `nodename` option in the `dsm.opt` file on the target Oracle server equals the value of the `nodename` option in the `dsm.opt` file on the source Oracle server. Data Protection for Oracle, the IBM® Storage Protect backup-archive client, and the IBM® Storage Protect API must be at the same levels on both the source Oracle server and the target Oracle server. If there is a password that is associated with the `nodename` option in the `dsm.opt` file on the target Oracle server, use the `tdpoconfutility` to generate the local password file when the value of the `nodename` option changes.

passwordaccess

Specify `passwordaccess generate`. This option allows the IBM Storage Protect™ API to manage all password actions after the password is created with the `tdpoconf password` command. The IBM® Storage Protect API saves the current encrypted password in the Windows™ registry and automatically generates a new password when the current password expires. This method of password management is useful when you are running unattended scheduled backups because it ensures that the backup never fails with an expired password.

tcpserveraddress

Specify the TCP/IP address for the IBM® Storage Protect server to be used for Oracle backups.

commethod

Specify the communication method for Data Protection for Oracle to communicate with the IBM® Storage Protect server. Note, this option requires other IBM® Storage Protect options, depending on the communication method you specify.

Other configuration options to consider

There are other IBM® Storage Protect client options that you can use when you are configuring Data Protection for Oracle.

You can specify other options in the IBM® Storage Protect client user options file `dsm.opt`.

compression

Specify whether the IBM® Storage Protect API compresses data before it sends it to the IBM® Storage Protect server. You can specify `yes` or `no`. The default value is `No`. The value of the compression option for Data Protection for Oracle is allowed only if the IBM® Storage Protect administrator leaves the compression decision to the node. Enabling compression affects performance in three ways:

- Processor usage is higher on the system on which Data Protection for Oracle is running.
- Network bandwidth usage is reduced because fewer bytes are transmitted.
- Storage usage on the IBM® Storage Protect server is reduced.

When any of the following conditions exist, you should specify `yes`:

- The network adapter has a data overload.
- Communications between Data Protection for Oracle and the IBM® Storage Protect server are over a low-bandwidth connection.
- There is heavy network traffic.

When any of the following conditions exist, you should specify `no`:

- The system that is running Data Protection for Oracle has a processor overload. The added processor usage as a result of enabling compression can impact other applications, including the Oracle server. You can monitor processor and network resource usage with the Performance Monitor program that is shipped with Windows™.
- You are not constrained by network bandwidth. In this case, you can achieve the best performance by specifying `compressionno` and enabling hardware compaction on the tape drive, which also reduces storage requirements.
- Hardware compression is in use for the media where Data Protection for Oracle data is stored.

After a completed backup operation, view the throughput rate and the compression status for a backup object in the IBM® Storage Protect server activity log file. Run the IBM® Storage Protect server **QUERY ACTLOG** command in the IBM® Storage Protect server administrative client window. The throughput rate and the compression status are not written to the activity log when activity logging is disabled on the IBM® Storage Protect server. See the **SET ACTLOGRETENTION** command in the *IBM® Storage Protect Administrator's Reference* for complete activity logging information.

You can also determine whether objects were compressed by running the `tdposync query` command.

deduplication

Specify whether the IBM® Storage Protect API deduplicates data before it sends it to the IBM® Storage Protect server. You can specify `Yes` or `No`. The default value is `No`. The value of the deduplication option for

Data Protection for Oracle applies only if the IBM Storage Protect™ administrator allows client-side data deduplication.

You can determine if objects are deduplicated by running the **tdposync query** command or by examining the IBM® Storage Protect server activity log file.

The **deduplication** and **enablelanfree** options are mutually exclusive. Therefore, you must use either one option or the other, but not both options together.

The **deduplication** and **enableclientencryptkey** options are also mutually exclusive. Therefore, you must use either one option or the other, but not both options together.

enablelanfree

Specify whether you run backup or restore operations in a LAN-free environment if you are equipped to do so. You can specify yes or no. The default value is no. You can avoid network constraints by shifting the movement of data to a storage area network (SAN). After a completed backup operation, view the LAN-free status for a backup object in the IBM® Storage Protect server activity log file. For more information, see the appropriate Storage Agent User's Guide.

The **enablelanfree** and **deduplication** options are mutually exclusive. Therefore, you must use either one option or the other, but not both options together.

include

When a management class other than the default management class is defined within an existing policy domain, add an include statement to the client options file that is used by the Oracle node. You must add an include statement to the `dsm.opt` file.

This include statement binds the Oracle backup objects to the management class that is defined for managing these objects. The include statement uses the following naming convention:

```
\FilespaceName\orcnt\ObjectName
```

The **FORMAT** parameter in the RMAN script can also be used to assist with object naming. For example, if the **FORMAT** parameters (in the RMAN script) specified the following values for databases and logs:

```
format 'DB_%u_%p_%c'  
format 'LOG_%u_%p_%c'
```

The include statement in the `dsm.opt` file, which is used by the Oracle node, would be as follows:

```
INCLUDE \FilespaceName\orcnt\DB* mgmtclassname  
INCLUDE \FilespaceName\orcnt\LOG* mgmtclassname
```

Make sure that the **FORMAT** parameter specifies a unique name for the backup. If the object name exists on the IBM® Storage Protect server, the backup might fail with an RC=8 error that is recorded in the `sbtio.log` file.

enableclientencryptkey

When **enableclientencryptkey** is set to yes, Data Protection for Oracle provides 128-bit transparent encryption of Oracle databases during backup and restore processing. One random encryption key is generated per session and is stored on the IBM® Storage Protect server with the object in the server database. Although IBM Storage Protect™ manages the key, a valid database must be available to restore an encrypted object.

Important: The **enableclientencryptkey** and **deduplication** options are mutually exclusive because encrypted files cannot be deduplicated. Therefore, you can use only one or the other option, but not both options together.

You can specify the databases that you want encrypted by adding an include statement with the `include.encryptoption` in the client user options file `dsm.opt`.

For example, to enable transparent encryption, do the following steps:

1. Edit the client user options file, `dsm.opt`.
2. Specify **enableclientencryptkey** yes.
3. Specify **encryptiontype** AES128, or AES256.

4. Specify the objects to encrypt. This example encrypts all data:

```
include.encrypt          \adsmorc\...\*
```

Thus, the encryption options would be as follows in this client user options file, `dsm.opt`:

```
enableclientencryptkey yes
encryptiontype aes128
include.encrypt          \adsmorc\...\*
```

See *IBM® Storage Protect Using the Application Programming Interface* for more details about the `enableclientencryptkey` option.

You can determine whether objects were encrypted by running the **tdposync query** command.

Related information

[LAN-free data transfer](#)

Define IBM® Storage Protect policy requirements

Data Protection for Oracle requires special IBM® Storage Protect policy domain settings.

About this task

RMAN uses the **format** parameter in the RMAN script to generate unique backup file names. Because all backup objects inserted into the IBM® Storage Protect backup storage pool have unique file names, they never expire on the IBM® Storage Protect server. As a result, Data Protection for Oracle requires the following IBM® Storage Protect policy domain settings:

Backup copy group values

Data Protection for Oracle provides the `tdposync` utility to remove unwanted backup objects from the IBM® Storage Protect server. Set the following IBM® Storage Protect backup copy group options:

- `verdeleted 0`
- `retonly 0`

When Data Protection for Oracle marks a backup object inactive, that object is deleted from the IBM® Storage Protect server the next time expiration processing occurs. A backup object is marked for immediate expiration when you delete it through RMAN with the Data Protection for Oracle interface or with the `tdposync` utility. Note, an inactive backup object cannot be restored through RMAN with the Data Protection for Oracle interface.

Note:

1. The IBM® Storage Protect administrator must also register your node by specifying `backdelete yes` in order for backup objects to be deleted. However, be aware that a backup object is marked for immediate expiration when `backdelete yes` and you delete it through RMAN with the Data Protection for Oracle interface or with the `tdposync` utility. Note, when `backdelete no` is specified and a deletion request is made, the request fails and an error message displays.
2. The following backup copy group options are not applicable to Data Protection for Oracle:
 - `frequency`
 - `verexists`
 - `retextra`
 - `mode`
 - `serialization`

Data Protection for Oracle accepts default values for these options.

3. An archive copy group is not required (although it can exist) because Data Protection for Oracle stores all objects as backup objects on IBM® Storage Protect.

Management class

IBM® Storage Protect uses management classes to manage backups on the IBM® Storage Protect server. When you back up a database, the default management class for your node is used. Because the policy requirements for Data Protection for Oracle might be different from the wanted settings for the regular IBM® Storage Protect backup-archive clients, you must have a different management class that is defined for Data Protection for Oracle. You must define a separate policy domain where the default management class has the required settings. Then, register all Data Protection for Oracle nodes to that domain.

If you choose to define a new management class within an existing policy domain, not the default management class for that domain, then you must add an `include` statement to the Data Protection for Oracle options file to bind all objects to that management class.

The following steps assign a management class name `orcbackup` to all Oracle backups with a default file space name `adsmorc`:

1. Add this `inclexcl` entry under the server stanza you use in the `dsm.opt` file:

```
inclexcl C:\myfile\include.def
```

2. Add the following `include` entry to the `C:\myfile\include.def` file:

```
include \adsmorc\...\* orcbackup
```

Note: The file space name in the `include/exclude` statement must match the file space name that is defined with `thetdpo_fsoption`. If a file space name other than the default value `adsmorc` is used:

- a. You must specify the file space name with `thetdpo_fsoption`.
- b. You must specify the file space name that is defined in `thetdpo_fsoption` in the `include/exclude` statement.

All the files that are backed up with a default file space name of `adsmorc` are assigned to management class `orcbackup`.

Note: Data Protection for Oracle stores all objects as backup objects on IBM® Storage Protect storage, so an archive copy group is not required, although it can exist.

See your IBM® Storage Protect administrator or see the *IBM® Storage Protect Administrator's Guide* for more information about defining or updating IBM® Storage Protect policy domains and copy groups.

Initialize the password with an IBM® Storage Protect server

The administrator must run the `tdpoconf` utility program to set the password before you use Data Protection for Oracle.

Related information

[tdpoconf utility](#)

Protecting Oracle Server data

Use Data Protection for Oracle to back up and restore Oracle Server data.

Before you begin

Data Protection for Oracle must be installed and configured on your system and an Oracle Server must be available.

RMAN and Data Protection for Oracle

You can run full or partial, offline, or online backups with Oracle. When you identify which database to back up, Oracle locates all necessary files and sends them to the IBM® Storage Protect server through Data Protection for Oracle.

About this task

Data Protection for Oracle provides an interface between Oracle Media Management API calls and IBM® Storage Protect API routines.

Starting RMAN

Use RMAN to back up and restore an Oracle database.

About this task

In this example, the catalog database contains a registered target database. Start an RMAN session with this command:

```
$> rman target xxx/yyy@target rcvcat aaa/bbb@catalog  
cmdfile bkdb.scr msglog bkdb.log
```

RMAN starts in the sequence shown.

```
target xxx/yyy@target: connect to target database  
using user xxx and password yyy with connect string target  
rcvcat aaa/bbb@catalog: connect to catalog database  
using user aaa and password bbb with connect string catalog  
cmdfile bkdb.scr: run bkdb.scr script  
msglog bkdb.log: log the output messages in bkdb.log
```

Tip: In the example, RMAN creates a log file, `bkdb.log`, in the current working directory. If an error occurs, the error stack is logged to the log file.

After a completed backup or restore operation, view the throughput rate and encryption status for a backup object in the IBM® Storage Protect server activity log file. Run the IBM® Storage Protect server **QUERY ACTLOG** command in the IBM® Storage Protect server administrative client window. A message similar to the following is displayed:

```
08/03/11  
16:23:08  
ANE4991I (Session: 67, Node: MACHINE_ORC) DP Oracle Win64 ANU0599 TDP for Oracle:  
(5508): =>()  
ANU2526I Backup details for backup piece \adsmorc\orcnt\df_727444762_116_1  
(database "orcl").  
Total bytes processed: 9961472. Deduplicated: Yes. Bytes after deduplication: 2272805.  
Deduplication reduction: 77.18%. Compressed: Yes. Bytes after compression: 52253.  
Compressed by: 97.70%. Encryption: None. LAN-Free: No. Total bytes sent: 52253.  
Total data reduction: 99.48%. Total processing time: 00:00:01.
```


Editing RMAN scripts

You must edit existing RMAN scripts to use **TDPO_OPTFILE**=*fully qualified path and file name of options file* variable in place of other environment variables.

About this task

Sending options with the send command

Use the Oracle RMAN **send** command in an RMAN script to pass IBM Storage Protect™ options to the IBM Storage Protect™ API.

Before you begin

To send options from the IBM Storage Protect™ to the IBM Storage Protect™ API, you must specify the **send** command in an RMAN script.

About this task

Use the **send** command to set IBM Storage Protect™ options such as **TCPServeraddress** and **TCPport** to the IBM Storage Protect™ API. You can customize the actions that the script takes without updating the existing Data Protection for Oracle or IBM Storage Protect™ API options files. Any option that is sent through the **send** command overrides the option that is specified in the Data Protection for Oracle or IBM Storage Protect™ API options files.

- You can specify multiple IBM Storage Protect™ API options in the same **send** command.
- The **ENABLELANFREE** and **DEDUPLICATION** options are mutually exclusive. If both options are defined, client-side data deduplication does not occur.
- The **ENABLECLIENTENCRYPTKEY** and **DEDUPLICATION** options are also mutually exclusive. If both options are defined, client-side data deduplication does not occur.
- You can specify any IBM Storage Protect™ API option with the **send** command.
- Specify the **send** command in an RMAN script. You can specify one or more IBM Storage Protect™ options in a **send** command string. The **send** command string can contain up to 512 bytes.
To back up an Oracle database to the IBM® Storage Protect server named **halley** at TCP/IP port 1601, and to enable the cache for client-side data deduplication for only channel **t1**, specify the following statements in an RMAN script:

```
allocate channel t1 type 'SBT_TAPE';  
SEND channel 't1' '-TCPSEVER=halley -TCPPOINT=1601 -ENABLEDEDUPCACHE=YES';
```

Result

Data Protection for Oracle passes the command string to the IBM Storage Protect™ API. The IBM Storage Protect™ API validates the contents of the string. If an invalid entry is detected, the API issues an **ANS****E** message to Data Protection for Oracle. The message returns an error condition to Oracle RMAN and stops processing.

Related information

[RMAN script examples](#)

RMAN script examples

Sample RMAN scripts illustrate how to create parallel backup streams to IBM® Storage Protect server storage.

Example

In these examples, to back up to IBM® Storage Protect by using Data Protection for Oracle, you must specify type 'sbt_tape' in the RMAN script or within the global RMAN configuration settings.

Example 1:

When the IBM® Storage Protect server and Oracle system have multiple network cards, you can back up your data with multiple network paths to improve network throughput. Your environment is set up as follows:

- The Oracle system has two network cards with two addresses, A and B.
- The IBM® Storage Protect server also has two network cards with two addresses, C and D.
- Paths exist between A and C, B and D, but not between A and D or B and C.

Create two backup streams or Oracle channels, without using two separate options files to point to different two different addresses. Channel t1 goes to address C, channel t2 goes to address D. Be careful not to send parts of your backup to two different IBM® Storage Protect servers because it cannot be restored.

You can maintain one Data Protection for Oracle options file and change the IBM Storage Protect™ server specification in an RMAN script in the following manner:

```
run
{
  allocate channel t1 type 'sbt_tape';
    SEND channel t1 '-TCPSEVER=<C>';
  allocate channel t2 type 'sbt_tape';
    SEND channel t2 '-TCPSEVER=<D>';

  backup
    filesperset 5
    format 'df_%t_%s_%p'
      (database);
  release channel t2;
  release channel t1;
}
```

Example 2:

This backup script allocates two parallel connections to the IBM® Storage Protect server. The IBM® Storage Protect server views these connections as two separate sessions:

```
run
{
  allocate channel t1 type 'sbt_tape' parms
    'ENV=(TDPO_OPTFILE=C:\oracle\scripts\tdpo.opt)';
  allocate channel t2 type 'sbt_tape' parms
    'ENV=(TDPO_OPTFILE=C:\oracle\scripts\tdpo.opt)';

  backup
    filesperset 5
    format 'df_%t_%s_%p'
      (database);
}
```

Example 3:

This restore script allocates one parallel connection to the IBM® Storage Protect server:

```
run
{
  allocate channel t1 type 'sbt_tape' parms
    'ENV=(TDPO_OPTFILE=C:\oracle\scripts\tdpo.opt)';
  restore database;
  recover database;
  alter database open;
}
```

Note:

1. The `allocate channel` entry is divided on two lines after the `parms` option to accommodate page formatting.
2. The Oracle database must be in mount mode for the restore to succeed.

The Duplex Copy function

With Data Protection for Oracle, you can use the Oracle Server Duplex backup feature to make up to four exact duplicate copies of a backup. The backup can then be stored on different backup media.

About this task

A different management class is required for each backup copy. By default, the primary management class is the default management class on the policy domain that is defined for the Data Protection for Oracle node.

Note: It might be necessary to define the Oracle parameter value (`BACKUP_TAPE_IO_SLAVES=TRUE`) in the `init.ora` file of the target database for Data Protection for Oracle to use the duplex copy feature. Refer to your Oracle documentation about the use of this Oracle parameter.

For example, to create four backup copies:

Procedure

1. Specify the following option in the RMAN backup script:

```
set duplex=4
```

2. Define the following options in the `tdpo.opt` file:
 - `tdpo_mgmt_class_2`
 - `tdpo_mgmt_class_3`
 - `tdpo_mgmt_class_4`
3. Run the RMAN backup script.

Result

The following backup behavior occurs:

- The first backup copy is bound to the default management class to which the node is registered.
- The second backup copy is bound to the management class defined by the `tdpo_mgmt_class_2` option.
- The third backup copy is bound to the management class defined by the `tdpo_mgmt_class_3` option.
- The fourth backup copy is bound to the management class defined by the `tdpo_mgmt_class_4` option.

Note: Take note of the considerations provided:

- The duplex copy feature does not use `include` statements. It uses the management classes that are specified in the `tdpo.opt` file.
- You receive an error message if you specify **set duplex =4** in the RMAN backup script and do not define enough `tdpo_mgmt_class` options in the `tdpo.opt` file.
- To place duplicate copies on different media:
 - Make sure that the storage pool information for each backup copy group within the management classes is not the same.

- Make sure that backups from these different storage pools are not moved to the same storage pool later.
- Duplicate data is sent across the network.
- If you specify **set duplex =4** and allocate one channel in the RMAN backup script, RMAN will start four sessions to the IBM® Storage Protect server. Likewise, if you specify **set duplex =4** and allocate two channels in the RMAN backup script, RMAN will start eight sessions to the IBM® Storage Protect server.
- The duplex copy feature sends the backup copies simultaneously. If the backup destination is tape, the number of sessions is a multiple of the duplex value. As a result, make sure that RMAN does not start more sessions than the maximum mount points allowed by the IBM® Storage Protect server. The node definition option on the IBM® Storage Protect server **maxnummp** determines the maximum number of mount points a client node can use on the IBM® Storage Protect server during a backup operation. View the maximum mount points that are allowed by the IBM® Storage Protect server for a particular node by entering the **query node** command from an IBM® Storage Protect Administrative Client prompt:

```
q node f=d
```

See the appropriate *IBM® Storage Protect Administrator's Reference* for more information about this option.

Review your current Oracle documentation about the duplex backup function.

Removing old backups

Data Protection for Oracle uses the IBM® Storage Protect backup repository. Each database backup creates an object with a unique name. Since these objects have unique names, they always remain active and never expire. The database administrator (DBA) can control and coordinate copies that are removed from the IBM® Storage Protect server with RMAN.

Before you begin

Ensure that **backdelete=yes** is specified by the IBM® Storage Protect administrator during registration of your node. Specifying this parameter gives you permissions to delete backup objects.

About this task

Note: Make sure to use the same `tdpo.opt` file that was used for the original backup. Using this file enables the backup objects to be found on the IBM® Storage Protect server.

Removing a backup example

A sample script for removing an old backup is provided.

About this task

To remove an old backup, issue this command from the RMAN prompt:

```
run
{
  allocate channel for delete type 'sbt_tape' parms
    'ENV=(TDPO_OPTFILE=C:\oracle\scripts\tdpo.opt)';

  change backupset backupset number delete;
}
```

Refer to the Oracle RMAN manual for more information about the **change** command and its options.

Setting up a schedule example

This example illustrates how to set up a schedule to automatically back up Oracle server databases.

About this task

For consistency, this procedure uses specific information. However, you can define a command file with any set of commands you choose. You can then use the same command file to define schedules on other IBM® Storage Protect servers. All command information is presented as command-line interface entries.

This schedule in this procedure contains the following settings:

- The Data Protection for Oracle node name is NodeA1.
- The password for node name NodeA1 is PasswordA1.
- The policy domain to which node name NodeA1 is registered is PolicyA1.
- The schedule is a daily backup of an online Oracle database.
- The scheduled backup begins between 9:00 and 9:15 PM.

Setting up a schedule on the IBM® Storage Protect server

Define a schedule on the IBM® Storage Protect server to automatically run online backups of Oracle server databases.

Before you begin

Ensure that your system meets the minimum hardware, software, and operating system requirements. For more information, see [“Data Protection for Oracle installation” on page 9](#)

Procedure

To set up a schedule on the IBM® Storage Protect server:

1. Define the following schedule on the IBM® Storage Protect server. You can enter the command on the IBM® Storage Protect server console or on an administrative client. The administrative client does not have to be running on the same system as the IBM® Storage Protect server.

```
define schedule PolicyA1 daily_orcbkup description="07Daily Online DB Backup"
action=command objects="C:\Program Files\Tivoli\TSM\Agent0BA64\sched
\orcsched.cmd"
starttime=21:00 duration=15 durunits=minutes period=1 perunits=day
dayofweek=any
```

The following message must display before you proceed to the next step:

```
ANR2500I Schedule daily_orcbkup defined in policy domain PolicyA1.
```

2. Issue the following command to associate the Data Protection for Oracle node to the backup schedule defined in step [“1” on page 29](#):

```
define association PolicyA1 daily_orcbkup NodeA1
```

Result

- A backup schedule is now defined on the IBM® Storage Protect server.
- The backup schedule runs the command file `orcsched.cmd`, in the `C:\Program Files\Tivoli\TSM\Agent0BA64\sched\` or `c:\progra~1\tivoli\tsm\agentoba64\sched\` directory.
- The backup runs daily around 9:00 PM.
- The backup schedule can start on any day of the week.
- You can run the IBM® Storage Protect **query schedule** and **query association** commands to confirm that the schedule and node association are set correctly.

Setting up a schedule on the workstation with the Oracle Server

Use this procedure to define a schedule on the workstation with the Oracle Server.

About this task

This example assumes the following setup:

- The IBM® Storage Protect backup archive client is installed on the Oracle Server in the following directory:

```
C:\Program Files\Tivoli\TSM\baclient
```

- The Data Protection for Oracle for the Oracle server is installed in the following directory:

```
C:\Program Files\Tivoli\TSM\Agent0BA64
```

- The options files in each of these directories are updated so that the communication parameters point to the IBM® Storage Protect server.

Procedure

To set up a schedule on the workstation with the Oracle Server:

1. Log in with a Windows™ account that has administrative privileges.
2. Change to the backup archive client installation directory with this command: `C:\>cd \Program Files\Tivoli\TSM\baclient`
3. Use the IBM® Storage Protect Client Service Configuration Utility `dsmcutil` to install the IBM® Storage Protect Scheduler Service. Type in the command from your current location in the backup archive client installation directory.

For example:

```
dsmcutil inst /name:"TSM Oracle Bkup Scheduler"  
/node:nodea1 /password:passworda1 /autostart:yes  
/clientdir:"C:\Program Files\Tivoli\TSM\baclient"  
/optfile:"C:\Program Files\Tivoli\TSM\Agent0BA64\dsm.opt"  
/validate:yes
```

You can modify the command to contain options specific to your schedule.

This example shows the output:

```
TSM Windows NT Client Service Configuration Utility  
Command Line Interface - Version 8, Release 1, Level 0  
(C) Copyright IBM Corporation, 1990, 2016, All Rights Reserved.
```

```
TSM Api Version 8.1.23
```

```
Command: Install TSM Client Service  
Machine: ABC-ARTXNC(Local Machine)
```

```
Installing TSM Client Service:
```

```
Machine           : ABC-ARTXNC  
Service Name      : TSM Oracle Bkup Scheduler  
Client Directory  : C:\Program Files\Tivoli\TSM\baclient  
Automatic Start   : yes  
Logon Account     : LocalSystem
```

```
The service was successfully installed.
```

```
Creating Registry Keys ...
```

```
Updated registry value 'ImagePath' .  
Updated registry value 'EventMessageFile' .  
Updated registry value 'TypesSupported' .  
Updated registry value 'TSM Oracle Bkup Scheduler' .  
Updated registry value 'ADSMClientKey' .  
Updated registry value 'OptionsFile' .  
Updated registry value 'EventLogging' .  
Updated registry value 'ClientNodeName' .
```

```
Generating registry password ...
```

```
Authenticating TSM password for node NODEA1 ...
```

```

Connecting to TSM Server via client options file
'C:\Program Files\Tivoli\TSM\Agent0BA64\dsm.opt' ...

Password authentication successful.

The registry password for TSM node NODEA1 has been updated.

Starting the 'TSM Oracle Bkup Scheduler' service .....
The service was successfully started.

```

The options file that is defined for Data Protection for Oracle is used by the scheduler when it validates the node and password. The options file is also used when contacting the IBM® Storage Protect server for schedule information. This example assumes that the `dsm.opt` file is updated so that the communication parameters point to the IBM® Storage Protect server to which the Oracle databases are to be backed up.

If this message displays:

```

A communications error occurred connecting to the IBM® Storage Protect
server

```

Ensure that the `dsm.opt` file contains entries that point to the correct IBM® Storage Protect server. Also, ensure that the IBM® Storage Protect server is running. If you must make a correction, enter the following command:

```
dsmcutil remove /name:"TSM Oracle Bkup Scheduler"
```

Then enter the command that is given at the beginning of this step.

4. Ensure that Data Protection for Oracle is running under the Oracle Site Services account so that it can access the Oracle backup API. The Data Protection for Oracle scheduler service must log on with that account. The scheduler service account information can be specified through the services applet in the control panel.
5. Create a batch file that is called `orcsched.cmd` and place it in the following location:

```
C:\Program Files\Tivoli\TSM\Agent0BA64\sched\orcsched.cmd
```

Note: The scheduler service runs from the Windows™ system directory, so it is important that complete paths are specified for all file names and non-system commands. The scheduler service checks the Windows™ system directory for input and produces its output by default.

The following is an example of the `orcsched.cmd` file:

```

rem orcsched.cmd
rem =====

rem =====
rem setting oracle sid
rem =====
set oracle_sid=ilr

rem =====
rem set orc executable binary
rem =====
set ora_exe=c:\oracle\bin\rman.exe

%ora_exe% cmdfile 'C:\rman\bkdb.rmn'

```

The following is an example of the `bkdb.rmn` file:

```

connect target agnttest/agttest
run
{
allocate channel ch1 type 'SBT_TAPE' parms

```

```
'ENV=(TDPO_OPTFILE=C:\oracle\tdpo.opt)';
allocate channel ch2 type 'SBT_TAPE' parms
'ENV=(TDPO_OPTFILE=C:\oracle\tdpo.opt)';
allocate channel ch3 type 'SBT_TAPE' parms
'ENV=(TDPO_OPTFILE=C:\oracle\tdpo.opt)';
allocate channel ch4 type 'SBT_TAPE' parms
'ENV=(TDPO_OPTFILE=C:\oracle\tdpo.opt)';
backup (database);
release channel ch1;
release channel ch2;
release channel ch3;
release channel ch4;
}
```

Note: The `allocate channel` entry for each channel is divided on two lines after the `parms` option to accommodate page formatting. The `bkdb.rmn` file must have the `allocate channel` entry for each channel specified on one line of text.

6. The scheduler service is now installed, but is not yet started. To start the service, issue the following command:

```
net start "TSM Oracle Bkup Scheduler"
```

A message is displayed indicating that the Scheduler is starting up.

Note, because **autostart**=yes is specified, the IBM® Storage Protect scheduling service is automatically started each time the Windows™ system is restarted.

Your system is now ready to run automatic daily online database backups.

Result

Note: If you want to use the IBM® Storage Protect server scheduling mode:

1. Ensure that the Data Protection for Oracle options file has the **tcpclientaddress** and **tcpclientport** options specified. If you want to run more than one scheduler service, use the same **tcpclientaddress**. However, you must use different values for **tcpclientport** in addition to the different node names. Scheduling Data Protection for Oracle with the regular Windows™ backup archive client is an example of running more than one scheduler service. Server-prompted scheduling is supported only when TCP/IP communication is being used. By default, Data Protection for Oracle uses the polling schedule mode.
2. If any changes that affect the scheduler service are made to the Data Protection for Oracle options file, the scheduler service must be restarted to pick up the changes. For example, changes to the IBM® Storage Protect server address, schedule mode, or the TCP/IP address or port. The restart is done by entering these commands:

```
net stop "TSM Oracle Bkup Scheduler"
net start "TSM Oracle Bkup Scheduler"
```

3. The file named `dsmsched.log` contains status information for the IBM® Storage Protect scheduler service. Though the default directory is `\Tivoli\TSM\baclient\sched\dsmsched.log`, you can specify a different directory, such as `\Tivoli\TSM\Agent0BA64\sched\dsmsched.log` with the **schedlogname** option in the Data Protection for Oracle options file.
4. If an IBM® Storage Protect scheduler service is already installed on your workstation for the regular backups of the Windows™ system, you must install another with a unique name to run the schedules that are defined for Data Protection for Oracle. The IBM® Storage Protect scheduler service needs a different node name than the regular IBM® Storage Protect backup archive client. If the path you want to use has a space in it, for example `C:\Program Files\Tivoli\TSM\baclient`, you can place quotation marks around the section of the path name that contains a space `C:\"Program Files"`. You can also use the short form of the path name. The short form of a path name is made up of the first six characters in the path, followed by a tilde

(~) and the unique identifier. The following is an example of the short form of the path name: C:\Progr~1\Tivoli\TSM\baclient

The `orcsched.cmd` file must contain these variables with the following values:

oracle_sid

Specify the Oracle system identifier for the instance to be used in the scheduled backup. A value of `filr` is used in the example.

ora_exe

Specify the complete path and file name of the Oracle RMAN executable file. A value of `c:\oracle\ora91\bin\rman.exe` is used in the example.

cmdfile

Specify the complete path and file name of the Oracle command file. A value of `C:\rman\bkdb.rmn` is used in the example.

Querying backup objects

Use the **tdposync query** command to query the IBM® Storage Protect server for information about objects that are backed up.

About this task

When you issue the **tdposync query** command, information about a backup object is displayed. Information is listed including the size and date of the backup, and whether the object is compressed, encrypted, or deduplicated by the IBM® Storage Protect during the backup operation.

Related information

[Query command](#)

[Data deduplication with Data Protection for Oracle](#)

Data deduplication with Data Protection for Oracle

You can use data deduplication with Data Protection for Oracle to reduce the amount of redundant data that is backed up to the IBM® Storage Protect server.

Overview of data deduplication

Data deduplication is a method of reducing storage needs by eliminating redundant data

Two types of data deduplication are available with IBM Storage Protect™: client-side data deduplication and server side data deduplication.

Client-side data deduplication is a data deduplication technique that is used on the IBM Storage Protect™ API to remove redundant data during backup processing before the data is transferred to the IBM® Storage Protect server. Using client-side data deduplication can reduce the amount of data that is sent over a local area network.

Server side data deduplication is a data deduplication technique that is done by the server. The IBM® Storage Protect server administrator can specify the data deduplication location on either the client or server to use with the **DEDUP** parameter on the **REGISTER NODE**, or **UPDATE NODE** server command.

Setting up for client-side data deduplication

You must edit the client options file before Data Protection for Oracle can use client-side data deduplication through the IBM Storage Protect™ API.

About this task

You can turn on client-side data deduplication by adding `DEDUPLICATION YES` to the `dsm.opt` file and by making sure that the deduplication prerequisites are met.

The IBM® Storage Protect server administrator must enable data deduplication for the Data Protection for Oracle with the appropriate server command. For example:

```
UPDATE NODE ORACLE_NODE DEDUPLICATION=CLIENTORSERVER
```

The IBM® Storage Protect server administrator must enable data deduplication on the storage pool where the Oracle data is stored with the following server command:

```
UPDATE STGPPOOL BACKUP_POOL DEDUPLICATION=YES
```

Result

After you created backups with client-side data deduplication enabled, you can use the **tdposync query** command to verify that client deduplication occurred during the backup operation. For detailed statistics, you can also query the IBM Storage Protect™ server activity log for the total data reduction.

You can also use the performance monitor feature in the IBM Storage Protect™ server to verify the percentage of data that has been deduplicated. The performance monitor feature is part of the IBM Storage Protect™ Administration Center. The data deduplication statistics are displayed graphically in the Performance GUI in the Administration Center.

Considerations:

- The **deduplication** and **enablelanfree** options are mutually exclusive. Therefore, you can use either one option or the other, but not both options together.
- The **deduplication** and **enableclientencryptkey** options are also mutually exclusive. Therefore, you can use either one option or the other, but not both options together.
- A local deduplication cache is an optimization that can reduce network traffic between the IBM® Storage Protect server and the client. Client-side data deduplication can occur with or without it. Do not use the deduplication cache with Data Protection for Oracle for the following reasons:
 - The cache cannot be used when multiple processes, such as concurrent backups or IBM Storage Protect™ API applications, transfer content concurrently. Data Protection for Oracle backup operations that use multiple channels use multiple processes.
 - It is possible that the client deduplication cache can become out of sync with the server-deduplicated disk storage pool. This state can be the result of object expiration, file space deletion, and overflow to an associated tape storage pool. When the client cache contains entries that are no longer in the IBM® Storage Protect server deduplicated pool, the cache is reset and the backup operations fails. The IBM Storage Protect™ API does not attempt the backup again.
- When IBM® Storage Protect server expiration or a similar process that removes deduplicated data extents runs concurrently with a deduplicated backup, the backup might fail. Backup operations with client-side deduplication enabled fails with the following messages:
 - Return code=254
 - Error message: ANS7899E The client referenced a deduplicated extent that does not exist on the TSM server.

Related information

[Query command](#)

[Determining total data reduction](#)

Determining total data reduction

You can determine the percentage of total data reduction by querying the IBM Storage Protect™ server activity log.

About this task

Look for message number ANU2526I, which displays the data deduplication statistics, as shown in the following example:

```
ANE4991I (Session: 67, Node: HALLEY_ORC) DP Oracle Win64 ANU0599 TDP for Oracle: (5508):
=>()
  ANU2526I Backup details for backup piece \adsmorc\orc\df_727444762_116_1 (database
  "orcl").
    Total bytes processed: 9961472. Deduplicated: Yes. Bytes after deduplication: 2272805.
    Deduplication reduction: 77.18%. Compressed: Yes. Bytes after compression: 52253.
    Compressed by: 97.70%.
    Encryption: None. LAN-Free: No. Total bytes sent: 52253. Total data reduction: 99.48%.
    Total processing time: 00:00:01. Throughput rate: 9728.00Kb/Sec. (SESSION: 67)
```

In the following example, the Oracle database backup piece size is 9,961,472 bytes. Then, it was deduplicated and the number of bytes after deduplication is 2,272,805.

The total data reduction is calculated as follows:

- The percentage of data that is deduplicated is as follows:

```
Deduplication reduction = (1 - 2272805 / 9961472 ) = 0.7718
```

- After data deduplication, the object was compressed. The number of bytes before compression is the number of bytes after deduplication. The data was compressed to 52,253 bytes. Therefore,

```
Compressed by = (1 - 52253 / 2272805) = 0.9770
```

- The total bytes sent to the server equals the number of bytes after compression. The formula for total data reduction is as follows:

```
Total data reduction = (1 - bytes after compression / bytes processed)
= (1 - 52253 / 9961472) = 0.9948
```

Result

If there is no deduplication, the number of bytes after deduplication equals the number of bytes processed. If there is no compression, the number of bytes after compression equals the number of bytes after deduplication. If you want to find out data reduction across multiple backup pieces, you can add up the numbers and calculate the ratios.

You can also use the performance monitor feature in the IBM Storage Protect™ server to verify the percentage of data that has been deduplicated. The performance monitor feature is part of the IBM Storage Protect™ Administration Center. The data deduplication statistics are displayed graphically in the Performance GUI in the Administration Center.

Commands and utilities for Data Protection for Oracle

The Data Protection for Oracle commands and utilities are used to protect Oracle Server data.

tdpoconf and tdposync utilities

Set up and maintain Data Protection for Oracle with the tdpoconf and tdposync utilities. Find the utilities in the directory where Data Protection for Oracle is installed.

Use the Data Protection for Oracle utilities to do the following tasks:

- Set up and maintain Data Protection for Oracle with the tdpoconf utility. The utility is also used for password maintenance.
- Synchronize the RMAN catalog and Oracle control file by using tdposync. The utility is used to delete Oracle backups that are stored on the IBM® Storage Protect.
- Query objects that are backed up on the IBM® Storage Protect by using the tdposync utility.

Command line syntax and characteristics

Guidelines for the command line syntax for the Data Protection for Oracle utilities.

The Data Protection for Oracle utilities use the following command line syntax:

```
tdpoconf command 0 or more optional parameters
```

```
tdposync command 0 or more optional parameters
```

The command-line parameters have the following characteristics:

- Minimum abbreviations for keywords are indicated in uppercase.
- Optional parameters begin with a dash (-).
- Optional parameters can display in any order.
- Some keyword parameters require a value that is separated by the equal sign (=).
- If a parameter requires more than one value, the values are separated with commas.
- A space separates the invocation from the command and the command from any optional parameters.
- Each parameter is separated from others by a space.
- If a parameter value includes spaces, the entire parameter must be enclosed in double quotation marks.

tdpoconf utility

The tdpoconf utility provides setup tasks for configuring Data Protection for Oracle. The utility uses the `tdpo.opt` file that is stored in the installation directory to centralize information for setup purposes.

Use the following commands with the tdpoconf utility:


- **PASSWord**
- **SHOWENVironment**

password command

Use the **password** command to create a password or change an existing password on the IBM® Storage Protect server.

You are prompted to enter both the old and new passwords, if you do not provide them, when you use this utility to change the password.

Syntax



Optional parameters

oldnodepassword

Specifies the current (old) password you want to change.

newnodepassword

Specifies the new password.

The password is not case-sensitive and can be composed of 1 to 63 of the following characters:

```
a b c d e f g h i j k l m n o p q r s t u v w x y z
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
0 1 2 3 4 5 6 7 8 9
~ ! @ # $ % ^ & * _ - + = ` | ( ) { } [ ] : ; < > , . ? /
```

Enclose all parameters that contain one or more special characters in quotation marks. Without quotation marks, the special characters can be interpreted as shell escape characters, file redirection characters, or other characters that have significance to the operating system.

-TDPO_OPTFILE=pathname

This parameter specifies the fully qualified path name to the `tdpo.opt` file. If you choose not to specify this option, the default path is used.

Example

Example

An output example of the **tdpoconf password oldnodepassword newnodepassword** command is provided:

```
*****
*   IBM Protect for Databases Utility                               *
*   Password file initialization/update program                     *
*                                                                 *
*****
ANU0260I Password successfully changed.
```


showenvironment command

Use the **showenvironment** command to query the IBM® Storage Protect server with the options that are set in `-TDPO_OPTFILE`, the `tdpo.opt` file in the default installation directory, or the default values set by Data Protection for Oracle.

The screen output displays information about the IBM® Storage Protect API and IBM® Storage Protect server. This command is useful if you are troubleshooting setup errors for Data Protection for Oracle. If the password file is not initialized properly, the output of the `tdpoconf showenvironment` command reports the error.

Tip: To ensure that the environment is set up correctly before you use RMAN, direct the setup output to a file with the `outfile` option.

Syntax



Optional parameters

-TDPO_OPTFILE=*pathname*

This parameter specifies the fully qualified path name to the `tdpo.opt` file. The options file is used by the utilities and the Data Protection for Oracle library.

-OUTfile=*pathname*

This parameter specifies the fully qualified path name to the output file. The formatted text of this file is the same content that in the output on screen.

Example

Example

The following example shows the output of the **tdpoconf showenvironment** command:

```

IBM Protect for Databases:
Data Protection for Oracle
Version 8, Release 1, Level 0
(C) Copyright IBM Corporation 1997, 2016. All rights reserved.

Data Protection for Oracle Information
Version:            8
Release:            1
Level:              0
Sublevel:           0
Platform:           64bit TDP Oracle SUN

IBM Protect Server Information
Server Name:         TSMSEVER_ORACLE
Server Address:      TSMSEVER
Server Type:         Windows
Server Port:         1500
Communication Method: TCP/IP

Session Information
Node Name:           NODE_oracle
Node Type:           TDP Oracle SUN
DSMI_DIR:            /opt/tivoli/tsm/client/api/bin64
DSMI_ORC_CONFIG:     /opt/tivoli/tsm/client/oracle/bin64/dsm.opt
TDPO_OPTFILE:        /opt/tivoli/tsm/client/oracle/bin64/tdpo.opt
Password Directory:  /opt/tivoli/tsm/client/oracle/bin64
Compression:         FALSE
License Information:  License file exists and contains valid license data.

```

tdposync utility

The **tdposync** utility checks for items on the IBM® Storage Protect server that are not in the RMAN catalog or Oracle control file. With this utility, you can repair these discrepancies by removing unwanted objects from the IBM® Storage Protect, and reclaim space on the server.

Attention: Deleted files and inactive files cannot be restored.

When you are using this utility to delete files, ensure that you do not log in to the wrong node name. You might query a different database than intended, and delete files in error. Ensure that the node name in the **PICK** window is the one you need. See [“Optional parameters” on page 41](#) and [“PICK window” on page 43](#) for further details.

When you run an RMAN deletion script, entries are deleted in the RMAN recovery catalog or Oracle control file before confirmation from the IBM® Storage Protect server. In cases where objects are not found on the IBM® Storage Protect server, RMAN tries to delete backup sets from the IBM® Storage Protect server and fails. However, the entries in the RMAN catalog or control file for these objects are still removed. When they are deleted, RMAN can no longer identify these backups through the catalog or control file even though the file exists on the IBM® Storage Protect server. Therefore, this utility synchronizes the contents of the servers.

When the RMAN catalog or control file contains backups that are marked as expired, RMAN still considers these objects as existing. If you run the **tdposync** utility against these objects, it recognizes these objects in the RMAN catalog or control file and on the IBM® Storage Protect server and considers them to be in sync. Therefore, you must delete these objects from the RMAN catalog or control file for them to be deleted from the IBM® Storage Protect server. Use the Oracle **crosscheck** command to verify whether the backups exist. Then, use the Oracle **delete expired** command to remove their record from the RMAN catalog or control file.

When you start **tdposync**, the following processing takes place:

1. Prompts you for the RMAN catalog owner ID or the Oracle database user name, password, and connect string.
2. Gathers information for the Oracle servers.
3. Queries the Oracle backup catalog and the IBM® Storage Protect server.
4. Displays a list of files that exist on the IBM® Storage Protect server but not in the RMAN catalog or Oracle control file.
5. Prompts you to take one of the following actions:
 - Delete any files found causing the discrepancy.
 - Delete all files.
 - Exit the program without deleting files from the IBM® Storage Protect server.

You can automate the maintenance of IBM® Storage Protect Data Protection for Oracle without the need for user interaction. You can use an input file to allow the **tdposync** utility to receive input from a script or batch file.

Example

For example, `tdposync syncdb < input.txt`

The `input.txt` file contains the required responses to the prompts for information as in the following example:

```
06/01/2016
06/07/2016
rman
rman
orcl
+
o
y
```

The description of each line of the `input.txt` file is listed in the following table:

06/01/2016	# from date
06/07/2016	# to date
rman	# RMAN user
rman	# RMAN password
orcl	# Oracle connection string

+	# pick windows selection, + selects all objects
o	# proceed with the operation
y	# confirm

tdposync considerations

To run the **tdposync** utility successfully, resynchronize the Oracle catalogs with the target databases. If you are using multiple Oracle catalogs, use the **numcatalogs** parameter. Each Oracle database must be backed up to the IBM® Storage Protect server.

The following information must be considered before you use the **tdposync** command:

- Resynchronize Oracle catalogs with the target databases before you run the **tdposync syncdb** command. First, connect to the target database and the catalog database. The following is an example:

```
$ rman target xxx/yyy@targetdb rcvcat xxx/yyy@catalogdb
```

When you are connected to both databases, type **resync catalog** at the RMAN prompt.

- By default, Data Protection for Oracle prompts you to synchronize with one Oracle catalog at a time. If you use multiple Oracle catalogs to back up multiple target databases to the same file space, the same node name, and the same owner name on the same IBM® Storage Protect server, you must use **-numcatalogs=number**. This action is necessary so that **tdposync** has all the information to correctly query both Oracle and the IBM Storage Protect™.

Similarly, if you use Oracle control files to back up multiple target databases to the same file space, the same node name, and the same owner name on the same, you must use **-numinstances=number**.

If, for example, you back up only one target database by using two catalogs, do not specify this option. However, if you back up two target databases by using two catalogs, one catalog for each, to the same under the same file space, node name, and owner name, you must specify **numcatalogs**. If you fail to provide information for the second target database by not specifying two catalogs, that database is displayed as eligible for deletion.

Restriction: Failure to provide all pertinent and correct information can result in erroneous output. To prevent the erroneous output, see the next consideration.

- If you have more than one Oracle database, back up each Oracle target database to its own file space on the IBM® Storage Protect server. To back up each Oracle target database to its own file space, use the **tdpo_fsoption** in the **tdpo.opt** file. For best results, use a separate Data Protection for Oracle options file for each database that you back up to IBM® Storage Protect. In this way, it is only necessary to synchronize one catalog at a time, one for each target database. The possibility of showing wrong information in the **PICK** window is minimized.

Tip: Make sure to use the same **tdpo.opt** file that was used for the original backup.

- If the information for **sqlplus** that you provide to **tdposync** is incorrect, such as logon, password, or connect string information, **sqlplus** stops at its logon screen. You must log on again at the prompt by using the RMAN catalog owner ID, password, and connect string. For example:


```
login/password@connectstring
```

where **connectstring** represents the Oracle database in which to connect. The **connectstring** is also sometimes referred to as the Transparent Network Substrate (TNS) alias. When the correct input is entered, **tdposync** proceeds.

syncdb command

The **syncdb** command synchronizes Oracle catalog databases or the Oracle control file with the IBM® Storage Protect server.

Syntax



Optional parameters

-TDPO_OPTFILE=pathname

This parameter specifies the fully qualified path name to the `tdpo.opt` file. This file is the options file that is used by the utilities and the Data Protection for Oracle library. This file contains the information for the IBM® Storage Protect server name and address that **tdposync** needs for synchronizing.

Note: For **syncdb TDPO_OPTFILE**, you must specify the same options file values that were used to do the original backup operations.

-NUMCATalogs=number

This parameter specifies the number of Oracle catalog databases that you want to synchronize and prompts you for information for each catalog.

Specify this option only when you use multiple Oracle catalogs to back up multiple target databases to the same IBM® Storage Protect server under the same file space, node name, and owner name.

According to the number you specify for **-numcatalogs**, you are prompted for the user name, password, and connect string for each. If you do not specify **-numcatalogs**, the default is 1, and you are prompted only once.

You are prompted for start and end dates for your query. Then you are prompted for the following information for each catalog:

- Catalog # User Name:
- Catalog # Password:
- Catalog # Connect String:

You are also prompted for the following date information to narrow your search:

- From Date: MM/DD/YYYY
- To Date: MM/DD/YYYY

If no dates are specified, Data Protection for Oracle displays all objects that are not in sync.

-NOCATalog

This parameter specifies that the **tdposync** utility uses the backup history information that is stored in the Oracle control file rather than a catalog database to reconcile the IBM Storage Protect™ database with the RMAN backup history.

-NUMORCINSTances=number

This parameter specifies the number of Oracle instances that you want to synchronize and prompts you for information for each instance.

Specify this option only when you use multiple Oracle instances to back up multiple target databases to the same IBM® Storage Protect server under the same file space, node name, and owner name.

According to the number you specify for **-numorcinstances**, you are prompted for the user name, password, and connect string for each instance. If you do not specify a value for **-numorcinstances**, the default is 1, and you are prompted only once.

For each Oracle instance, the following information is requested:

- Oracle Database # User Name
- Oracle Database # Password
- Oracle Database # Connect String

You are also prompted for the following date information to narrow your search:

- From Date: MM/DD/YYYY
- To Date: MM/DD/YYYY

If no dates are specified, Data Protection for Oracle shows all objects that are not in sync.

Example

Example

Synchronize the IBM Storage Protect™ database with the RMAN backup history and the Oracle control file using the **tdposync syncdb** command. The following output is displayed:

```
Command: TDPOSYNC syncdb -nocatalog -numorcinstances=2

Output:
IBM Protect for Databases:
Data Protection for Oracle
Version 8, Release 1, Level 0.0
(C) Copyright IBM Corporation 1997, 2016. All rights reserved.
From Date (01/01/1990): 10/20/2016
To Date (10/28/2016): 10/28/2016

Oracle Database 1 User Name: OrcUser1
Oracle database 1 Password: OrcUser1pw
Oracle database 1 Connect String: Oracle_DB_A

Oracle Database 2 User Name: OrcYser2
Oracle database 2 Password: OrcUser2pw
Oracle database 2 Connect String: Oracle_DB_B
```

When you specify the **syncdb -numcatalogs** parameter, you are prompted for input for each catalog on the node. This example assumes two separate RMAN catalogs, **rman** and **rman2**:

```
C:\Tivoli\Tsm\Agent0ba>tdposync syncdb -numcatalogs=2 -TDPO_OPTFILE=c:\RMAN\
scripts\tdpo.opt

Output:
IBM Protect for Databases:
Data Protection for Oracle
Version 8, Release 1, Level 0
(C) Copyright IBM Corporation 1997, 2014. All rights reserved.

From Date (01/01/1990): 10/20/2016
To Date (10/28/2016): 10/28/2016
```

```
Catalog 2 User Name: rman2
Catalog 2 Password: rman2
Catalog 2 Connect String: rman2
```

PICK window

The following information is provided:

- Attention:** Use caution when you are selecting files for deletion. If you are unsure that the files in question are out of synchronization, do further research before you delete them. Deleted files cannot be restored.

Example

Example

```

Synchronize utility PICK Window
Node Name:                AGENT_NODE

Backup Date                Size                Backup Name
-----
1. | 01/09/2014  09:19:59                50.35MB                \adsmorc\orcnt\1kc2cnfv_1_1
2. | 01/02/2014  11:36:20                427.08MB                \adsmorc\orcnt\4kc3cnfv_1_1
3. | 01/02/2014  07:14:30                508.00MB                \adsmorc\orcnt\4qcgdhfr_1_1
4. | 01/02/2014  07:21:38                763.94MB                \adsmorc\orcnt\4ocf8999_1_1
5. | 01/09/2014  11:00:11                69.12MB                \adsmorc\orcnt\4ocf8999_1_2
6. | 01/09/2014  11:00:12                950.09MB                \adsmorc\orcnt\4ocf8999_1_3
7. | 01/09/2014  11:00:13                656.69MB                \adsmorc\orcnt\4rch25jk_1_1
8. | 01/09/2014  11:00:14                135.36MB                \adsmorc\orcnt\4rch25jk_1_2
9. | 01/09/2014  11:00:15                298.01MB                \adsmorc\orcnt\4rch25jk_1_30
|
0-----10-----20-----30-----40-----50-----60-----70
<U>=Up   <D>=Down  <T>=Top   <B>=Bottom  <R#>=Right  <L#>=Left
<G#>=Goto Line #  <#>=Toggle Entry  <+>=Select All <->=Deselect All
<#:#+>=Select A Range <#:#->=Deselect A Range  <O>=Ok   <C>=Cancel
pick>

```

1. Enter **OK** at the PICK prompt.
A warning message is shown confirming the deletion of the selected files.

2. Enter **Yes** to delete the selected files from the IBM® Storage Protect server.


Query command

Use this command to query the IBM® Storage Protect server for information about objects that are backed up. You can obtain information such as whether an object is compressed, encrypted, or deduplicated by the client during a backup operation.

The **query** command uses the options that are set in the **-TDPO_OPTFILE** parameter, the `tdpo.opt` file in the default installation directory, or the default values set by Data Protection for Oracle to query the IBM® Storage Protect server.

When you issue the **tdposync query** command, you are prompted to enter date range for the query. The screen output displays information about the objects that were backed up to the IBM® Storage Protect server between the start and end dates that you specified.

Syntax



Optional parameters

-TDPO_OPTFILE =pathname

This parameter specifies the fully qualified path name to the `tdpo.opt` file. This file is the options file that is used by the utilities and the Data Protection for Oracle library. The file contains the information for the IBM® Storage Protect server and the server address that **tdposync** command must use for synchronizing. When you specify the **query TDPO_OPTFILE** command, you must specify the same options file values that were used for the original backup operations. If you do not specify the **TDPO_OPTFILE** path, the default value in the default Oracle installation path (`/Program Files/Tivoli/TSM/Agent0BA64/tdpo.opt`) is used.

Description of the output fields

Name

Object name on the IBM® Storage Protect server; for instance, `/fs/h1/l1`.

Owner

The name of the user who backed up the object.

Size

The size of the object size on the IBM® Storage Protect server.

Creation Date / Time

The date and time the object was backed up.

Compressed

Lists whether an object was compressed during the backup operation.

Encryption Type

Lists the type of encryption that was used during the backup operation. The possible values are as follows:

None

The object was not encrypted.

AES-128

The object was encrypted by using AES-128 encryption.

AES-256

The object was encrypted by using AES-256 encryption.

Client-deduplicated

Lists whether an object underwent client-side data deduplication.

Examples

Use the `tdposync query` command to find information about backed up objects, encryption type and data deduplication.

Query the IBM® Storage Protect server for information about objects that are backed up

The command to be run is `tdposync query`.
The following output is displayed:

```
IBM Protect for Databases:
Data Protection for Oracle
Version 8, Release 1, Level 0
(C) Copyright IBM Corporation 1997, 2016. All rights reserved.

From Date (01/01/2016):

To Date (07/02/2016):

Backup Object Information
-----

Name ..... \adsmorc\orcnt\df_722435657_35_1
Owner.....
Size ..... 2,010 KB
Creation Date / Time ..... 07/02/2014 10:08:20
Compressed ..... Yes
Encryption Type ..... None
Client-deduplicated ..... No

Backup Object Information
-----

...
```

Finding the encryption type

When you issue the **tdposync query** command, the entire list of backup object information is printed to the command prompt window without page separators, scrolling, or canceling capability. Redirect the output of the query to a file and find out the encryption type that was used for the backups from the previous week.

Command: `echo from_date > in.txt & echo to_date >> in.txt & tdposync query < in.txt > out.txt`

Open the file `out.txt` with a text editor and search for `Encryption Type` to determine the type of encryption that was used.

Finding data deduplication information

Determine the data deduplication reduction for a particular node by querying the IBM Storage Protect™ server activity log for the ANU2526I message.

Accessibility features for the IBM® Storage Protect product family

Accessibility features assist users who have a disability, such as restricted mobility or limited vision, to use information technology content successfully.

Overview

The IBM® Storage Protect family of products includes the following major accessibility features:

- Keyboard-only operation
- Operations that use a screen reader

The IBM® Storage Protect family of products uses the latest W3C Standard, [WAI-ARIA 1.0](#), to ensure compliance with US Section 508 and [Web Content Accessibility Guidelines \(WCAG\) 2.0](#). To take advantage of accessibility features, use the latest release of your screen reader and the latest web browser that is supported by the product.

The product documentation in IBM® Documentation is enabled for accessibility.

Keyboard navigation

This product uses standard navigation keys.

Interface information

User interfaces do not have content that flashes 2 - 55 times per second.

Web user interfaces rely on cascading style sheets to render content properly and to provide a usable experience. The application provides an equivalent way for low-vision users to use system display settings, including high-contrast mode. You can control font size by using the device or web browser settings.

Web user interfaces include WAI-ARIA navigational landmarks that you can use to quickly navigate to functional areas in the application.

Vendor software

The IBM® Storage Protect product family includes certain vendor software that is not covered under the IBM license agreement. IBM makes no representation about the accessibility features of these products. Contact the vendor for accessibility information about its products.

Related accessibility information

In addition to standard IBM help desk and support websites, IBM has a TTY telephone service for use by deaf or hard of hearing customers to access sales and support services:

TTY service
800-IBM-3383 (800-426-3383)
(within North America)

For more information about the commitment that IBM has to accessibility, see [IBM Accessibility](#).

Notices

This information was developed for products and services offered in the US. This material might be available from IBM® in other languages. However, you may be required to own a copy of the product or product version in that language in order to access it.

IBM® may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM® representative for information on the products and services currently available in your area. Any reference to an IBM® product, program, or service is not intended to state or imply that only that IBM® product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM® intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM® product, program, or service.

IBM® may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM® Director of Licensing
IBM® Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
US

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM® Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing
Legal and Intellectual Property Law
IBM® Japan Ltd.
19-21, Nihonbashi-Hakozakicho, Chuo-ku
Tokyo 103-8510, Japan

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM® may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM® websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM® product and use of those websites is at your own risk.

IBM® may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM® Director of Licensing
IBM® Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
US

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM® under terms of the IBM® Customer Agreement, IBM® International Program License Agreement or any equivalent agreement between us.

The performance data discussed herein is presented as derived under specific operating conditions. Actual results may vary.

Information concerning non-IBM® products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM® has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM® products. Questions on the capabilities of non-IBM® products should be addressed to the suppliers of those products.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM®, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM®, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM® shall not be liable for any damages arising out of your use of the sample programs.

Each copy or any portion of these sample programs or any derivative work must include a copyright notice as follows: © (your company name) (year). Portions of this code are derived from IBM® Corp. Sample Programs. © Copyright IBM® Corp. _enter the year or years_.

Trademarks

IBM®, the IBM® logo, and ibm.com® are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM® or other companies. A current list of IBM® trademarks is available on the Web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

Adobe™ is a registered trademark of Adobe™ Systems Incorporated in the United States, and/or other countries.

Linear Tape-Open™, LTO™, and Ultrium™ are trademarks of HP, IBM® Corp. and Quantum in the U.S. and other countries.

Intel™ and Itanium™ are trademarks or registered trademarks of Intel™ Corporation or its subsidiaries in the United States and other countries.

The registered trademark Linux® is used pursuant to a sublicense from the Linux® Foundation, the exclusive licensee of Linus Torvalds, owner of the mark on a worldwide basis.

Microsoft™, Windows™, and Windows NT™ are trademarks of Microsoft™ Corporation in the United States, other countries, or both.

Java™ and all Java™-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Red Hat®, OpenShift®, Ansible®, and Ceph® are trademarks or registered trademarks of Red Hat®, Inc. or its subsidiaries in the United States and other countries.

UNIX® is a registered trademark of The Open Group in the United States and other countries.

VMware, VMware vCenter Server™, and VMware vSphere™ are registered trademarks or trademarks of VMware, Inc. or its subsidiaries in the United States and/or other jurisdictions.

Terms and conditions for product documentation

Permissions for the use of these publications are granted subject to the following terms and conditions.

Applicability

These terms and conditions are in addition to any terms of use for the IBM® website.

Personal use

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of IBM®.

Commercial use

You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM®.

Rights

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM® reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM®, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM® MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

Privacy policy considerations

IBM® Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user, or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

This Software Offering does not use cookies or other technologies to collect personally identifiable information.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM®'s Privacy Policy at <http://www.ibm.com/privacy> and IBM®'s Online Privacy Statement at <http://www.ibm.com/privacy/details> in the section entitled "Cookies, Web Beacons and Other Technologies," and the "IBM® Software Products and Software-as-a-Service Privacy Statement" at <http://www.ibm.com/software/info/product-privacy>.

Glossary

Index

40

- and Oracle databases 24
- configuring 19
- creating an installation package 13
- creating an installation package on DVD or file server 13
- installing 9, 10
- management class 22
- overview 6, 6
- policy requirements 22, 22
- Recovery Manager (RMAN) 6
- silent installation 10
- silent installation with batch file 13
- silent installation with msixec.exe 12
- silent installation with setup.exe 11
- supported Oracle versions 6
- updates 5
- version migration 6

A

- About this publication 5
- accessibility features 46
- archive copy group 22
- automated 7
- autostart 29

B

- backdelete**
 - and node 18
 - and policy 22
- backup copy group values 22
- backups**
 - removing 28
- bkdb.log 24
- bkdb.scr
 - and the scheduler 29

C

- command line syntax**
 - characteristics 36
- commands**
 - query association 29
 - query node 27
 - query schedule 29
- Oracle**
 - change 28
- tdpoconf password 36
- tdpoconf showenvironment 37
- tdposync**
 - query 44
 - syncdb 41
- commmethod**
 - description 19

- compression 20
- configure**
 - Quick configuration 15
 - with default settings 15
- configuring 16
- configuring**
 - Data Protection for Oracle 15
- control file 38, 41

D

- data deduplication**
 - overview 33
 - using 33
- data deduplication reduction**
 - determining 35
- Data Protection for Oracle**
 - configuring 15
 - installing 9
 - protecting data 24
 - reference 36
- deduplication**
 - using 33
- defining a schedule**
 - on the 29
 - on the workstation with the Oracle Server 29
- disability 46
- dsm.opt**
 - description 19
 - recommended options 20
 - required options 19
- dsmi_log 17
- dsmi_orc_config 17
- dsmsched.log 29
- duplex copy**
 - considerations 27
 - overview 27

E

- enablelanfree 20
- example**
 - tdposync query command 44
- examples**
 - duplex copy 27
 - include/exclude 22
 - invoking RMAN 24
 - removing backups 28
- RMAN script**
 - send command 25
- RMAN scripts 25
- scheduler 28
- tdpoconf password command 36
- tdpoconf showenvironment command 37
- tdposync syncdb command 41
- tdposync syncdb command**

pick window [43](#)
expiration of objects [22](#)

F

failover
[7](#)
overview [7](#)

I

IBM Knowledge Center [5](#)
inclexcl
and policy [22](#)
include
and policy [22](#)
and duplex copy [27](#)
description [20](#)
installation
instructions
node name registration [18](#)
prerequisites [9](#)
installing [10](#)
installing
creating an installation package [13](#)
creating an installation package on DVD or file server [13](#)
Data Protection for Oracle [9](#)
silently [10](#)
silently with batch file [13](#)
silently with msixec.exe [12](#)
silently with setup.exe [11](#)
installing in silent mode
installation
capturing a log of the installation [12](#)
installing
capturing a log [12](#)

K

keyboard [46](#)
Knowledge Center [5](#)

L

LAN-free data transfer
options [20](#)

M

management class
for automatic expiration [22](#)
maxnummp [27](#)
migration considerations [6](#)
Minimum software requirements [9](#)

N

New in this version [5](#)
nocatalog
and tdposync syncdb command [41](#)
node name
registration [18](#)
nodename [19](#)

numcatalogs
and tdposync syncdb command [41](#)
numorcintstances
and tdposync syncdb command [41](#)

O

operating system requirements [9](#)
options [17](#)
Oracle RMAN send command
using [25](#)
orcsched.cmd file [29](#)
outfile
and tdpoconf showenvironment command [37](#)
overview
[6](#)
data deduplication [33](#)

P

passwordaccess [19](#)
pick window [43](#)
policy domain [22](#)
prerequisites [9](#)
protecting data
Data Protection for Oracle [24](#)
publications [5](#)

Q

querying backup objects [33](#)

R

reference
Data Protection for Oracle [36](#)
reonly
and policy [22](#)
RMAN
description [6](#)
invoking [24](#)
scripts [25](#)
scripts
send command [25](#)

S

schedlogname [29](#)
scripts [25](#)
send command
in an RMAN script [25](#)
sample script [25](#)
using [25](#)
set duplex [27](#)
silent installation
playing back the installation [13](#)

T

tcpclientaddress [29](#)
tcpclientport [29](#)
tcpserveraddress [19](#)
tdpo.opt

- and version migration [6](#)
- description [16](#)
- tdpo_date_fmt [17](#)
- tdpo_enablescriptinput [17](#)
- tdpo_fs [17](#)
- tdpo_mgmt_class_2 [17](#)
- tdpo_mgmt_class_3 [17](#)
- tdpo_mgmt_class_4 [17](#)
- tdpo_num_fmt [17](#)
- TDPO_OPTFILE**
 - and tdpoconf password command [36](#)
 - and tdpoconf showenvironment command [37](#)
 - and tdposync syncdb command [44](#), [41](#)
 - example [16](#)
- tdpo_time_fmt [17](#)
- tdpoconf [36](#)
- tdpoconf**
 - and password initialization [23](#)
 - and tdpo.opt [16](#)
 - description [36](#)
 - password command [36](#)
 - password command**
 - example [36](#)
 - syntax diagram [36](#)
 - TDPO_OPTFILE [36](#)
 - showenvironment command [37](#)
 - showenvironment command**
 - example [37](#)
 - outfile [37](#)
 - syntax diagram [37](#)
 - TDPO_OPTFILE [37](#)
 - tdpoconf utility [36](#)
- tdpoerror.log**
 - how to specify [17](#)
- tdposync [36](#)

- tdposync**
 - and tdpo.opt [16](#)
 - considerations [40](#)
 - description [38](#)
 - query command [44](#)
 - query command**
 - example [44](#)
 - syntax diagram [44](#)
 - TDPO_OPTFILE [44](#)
 - syncdb command [41](#)
 - syncdb command**
 - example [41](#)
 - nocatalog [41](#)
 - numcatalogs [41](#)
 - numorcintstances [41](#)
 - pick window [43](#)
 - syntax diagram [41](#)
 - TDPO_OPTFILE [41](#)
- tdposync syncdb command**
 - pick window [43](#)

U

- using data deduplication [33](#)
- utilities**
 - using [36](#)

V

- verdeleted**
 - and policy [22](#)
- Virtualization support [9](#)

W

- Windows x86**
 - hardware [9](#)
- Windows x86_64**
 - hardware [9](#)

© Copyright International Business Machines Corporation 1998, 2025

US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp

