

IBM Rational Developer for System z
Version 8.0.3

*RSE Server Installation Guide: AIX and
Linux on IBM Power Systems*



IBM Rational Developer for System z
Version 8.0.3

*RSE Server Installation Guide: AIX and
Linux on IBM Power Systems*



Note

Before using this information, be sure to read the general information under “Notices” on page 15.

(October 2011)

This edition applies to IBM Rational Developer for System z Version 8.0.3 (program number 5724-T07) and to all subsequent releases and modifications until otherwise indicated in new editions.

Order publications by phone or fax. IBM Software Manufacturing Solutions takes publication orders between 8 a.m. and 7:00 p.m. eastern standard time (EST). The phone number is (800) 879-2755. The fax number is (800) 445-9269. Send faxes Attn: Publications, 3rd floor.

You can also order publications through your IBM representative or the IBM branch office serving your locality. Publications are not stocked at the address below.

IBM welcomes your comments. You can send your comments by mail to the following address:

IBM Corporation
Attn: Information Development Department 53NA
Building 501 P.O. Box 12195
Research Triangle Park NC 27709-2195.
USA

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

Note to U.S. Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

© **Copyright IBM Corporation 2000, 2011.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

About this document

This document describes how to install the RSE server option of IBM® Rational® Developer for System z® Version 8.0.3 on AIX® or Linux on IBM Power Systems™.

From here on, the following names are used in this manual:

- *IBM Rational Developer for System z Version 8.0.3* is called *Developer for System z*.
- *IBM Rational Developer for zEnterprise™ Version 8.0.3* is called *Developer for zEnterprise*.

For earlier releases, including IBM Rational Developer for System z, WebSphere® Developer for zSeries® and IBM WebSphere Enterprise Developer, use the installation information found in the documentation included in those releases.

The information in this document applies to all IBM Rational Developer for System z Version 8.0.3 packages including Developer for zEnterprise.

Chapter 1. Who should use this document

This document is intended for system programmers installing and configuring IBM Rational Developer for System z Version 8.0.3 on AIX or Linux on IBM Power Systems.

This document lists in detail the different steps needed to install the RSE server component of Developer for System z. To use this document, you need to be familiar with AIX or Linux on IBM Power Systems.

Chapter 2. Introduction

The Remote System Explorer communications server (RSE server) is installed on AIX or Linux running on IBM Power Systems.

The RSE server allows a workstation running Developer for System z to perform the following types of tasks on the connected remote host system:

- Copy, edit, create, or delete remote files; search for files on the remote system.
- Download and upload files between workstation and server; transfer files between remote systems.
- Use remote command shells; execute commands on the remote system; work with remote processes.
- Run integrated builds of remote source code; develop and debug remote programs.

This document describes how to install, use, and uninstall the RSE server on AIX or Linux running on IBM Power Systems.

Chapter 3. AIX host requisites

General information

The products listed in this section are all available at the time of publication for this manual. See the IBM Software Lifecycle Web site (<http://www.ibm.com/software/support/lifecycle/>) to see whether a selected IBM product is still available at the time that you want to use the related Developer for System z function.

The most current listing of prerequisites and corequisites is available in the *Developer for System z Prerequisites Guide* (SC23-7659). This document is available on the IBM Rational Developer for System z Web site Library page (<http://www.ibm.com/software/rational/products/developer/systemz/library/>) and supersedes the requirements listed in this document.

AIX

One of the following levels must be installed:

Program Number	Product Name
5765-G98	AIX 7.1
5765-G62	AIX 6.1
5765-G03	AIX version 5.3, TL 7 or higher

The related product Web site is:

<http://www.ibm.com/developerworks/java/jdk/aix/>

SDK for AIX, Java 2 Technology Edition

To use Remote Systems Explorer (RSE) on AIX, one of the following levels must be installed:

Program Number	Product Name
6207-001	IBM 32-bit Runtime Environment for AIX, Java 2 Technology Edition, Version 6
6205-001	IBM 32-bit Runtime Environment for AIX, Java 2 Technology Edition, Version 5

The related product Web site is:

<http://www.ibm.com/developerworks/java/jdk/aix/>

Attention: The 64-bit version is not supported.

Chapter 4. Intel host requisites

General information

The products listed in this section are all available at the time of publication for this manual. See the IBM Software Lifecycle Web site (<http://www.ibm.com/software/support/lifecycle/>) to see whether a selected IBM product is still available at the time that you want to use the related Developer for System z function.

The most current listing of prerequisites and corequisites is available in the *Developer for System z Prerequisites Guide* (SC23-7659). This document is available on the IBM Rational Developer for System z Web site Library page (<http://www.ibm.com/software/rational/products/developer/systemz/library/>) and supersedes the requirements listed in this document.

Linux

One of the following levels must be installed:

Product Name
Red Hat Enterprise Linux Server 6 for IBM Power Systems
Red Hat Enterprise Linux Server 5 (Update 5 or higher) for IBM Power Systems
SUSE Linux Enterprise Server 11 (SP1 or higher) for IBM Power Systems
SUSE Linux Enterprise Server 10 (SP3 or higher) for IBM Power Systems

SDK for Linux, Java 2 Technology Edition

To use Remote Systems Explorer (RSE) on Linux, one of the following levels must be installed:

Program Number	Product Name
6207-001	IBM 32-bit Runtime Environment for Linux on System i® and System p®, Java Technology Edition, Version 6
6205-001	IBM 32-bit Runtime Environment for Linux on System i and System p, Java Technology Edition, Version 5

The related product Web site is:

<http://www.ibm.com/developerworks/java/jdk/linux/>

Attention: The 64-bit version is not supported.

Chapter 5. RSE server installation and configuration

The supported functions of the RSE server on AIX or Linux on Power Systems are the following:

- RSE access to including SSL connections.
- Command shell use in RSE except vi or similar programs.
- Connection by the Host Emulator with full shell access.

Installing the RSE server on IBM Power Systems

This topic describes how to install the RSE server on AIX or Linux for IBM Power Systems.

Note: You must have root access privileges when you perform these install operations.

Installing on AIX

On AIX, install the RSE server from the RSE server filesets stored in the product image.

- If you have physical media, the filesets are located on the "IBM Rational Developer for zEnterprise Server for z/OS and Multiplatforms Server Installation disk" in the AIXServerRuntime directory.
- If you have an electronic image, the filesets are located in the \RDz803Ent_RSE\AIXServerRuntime directory.

Install with the AIX command **installp**. For example:

```
installp -agXd ./ all
```

Installing on Linux

On Linux, install the RSE server from the RSE server RPM packages stored in the product image.

- If you have physical media, the RPM packages are located on the "IBM Rational Developer for zEnterprise Server for z/OS and Multiplatforms Server Installation disk" in the PowerLinuxServerRuntime directory.
- If you have an electronic image, the RPM packages are located in the \RDz803Ent_RSE\PowerLinuxServerRuntime directory.

Install with the Linux utility **rpm**. For example:

```
rpm -ivh *.rpm
```

Note: If you plan to use the Java JDK rather than the Java JRE to run the RPM server, add the nodeps option to rpm to disable the dependency check. For example:

```
rpm -ivh *.rpm --nodeps
```

RSE directory configuration

Important: After the RSE server has been installed on a host system, only the root user can log in to the host system.

To allow other users to log in to the system, the system administrator must grant read and execute permissions on the directory where the RSE server is installed and on all the files and subdirectories within that directory.

To grant permissions to the owning user (root) and to all users in the root group, enter the following command at the command line:

```
chmod -R ug+xr rse_directory
```

where *rse_directory* is the path of the directory where the RSE server is installed. The default path is /opt/IBM/RDPower/8.0.

Note: This example assumes that the RSE server is the only product installed in the directory.

To grant permissions to every user on the system, enter the following command at the command line:

```
chmod -R ugo+xr rse_directory
```

where *rse_directory* is the path of the directory where the RSE server is installed. The default path is /opt/IBM/RDPower/8.0.

Note: This example assumes that the RSE server is the only product installed in the directory.

Starting the RSE server on IBM Power Systems

In both AIX and Linux on Power Systems, the RSE server daemon is started automatically when the system is started. The default port is 8050.

To configure the RSE server to use a different port:

1. Kill the RSE server daemon if it is running.
2. Set the new port number in the `$portvariable` variable in the script file `/opt/IBM/RDPower/8.0/rse/daemon.pl`
3. Restart the RSE server daemon using the `telinit q` command.

Configuring the RSE server to use SSL

You can configure the RSE server to use SSL authentication to provide secure connections between the server and its clients. To configure the RSE server to use SSL authentication follow these steps:

1. Create a Java keystore file on the system where the RSE server is installed.

Use the `keytool` program provided with the Java SDK to generate a key pair (public key and associated private key). For example:

```
keytool -genkey -alias alias_name -validity 3650 -keystore keystore_name
-storepass keystore_password -keypass key_password
```

where:

- *alias_name* is the name of the keystore.
 - *keystore_password* is the password for the keystore.
 - *key_password* is the password for the key.
2. In the RSE server install directory, update the `ssl.properties` file:
 - a. Open the `ssl.properties` file with a text editor.
 - b. Specify the location of the Java keystore file and the password:

```
daemon_keystore_file=jks_file
daemon_keystore_password=jks_password
```

where:

- *jks_file* is the path of the Java keystore file that you created, and
- *jks_password* is the password for the Java keystore file.

- c. Set the following two properties to enable SSL authentication:

```
enable_ssl=true
disable_server_ssl=false
```

- d. Close the `ssl.properties` file.

3. Start the SSL Server in the usual way.

Example: RSE server start with SSL

The following example shows what the command line interface looks like when the RSE server with SSL is started successfully. The first line is the command to start the server and the subsequent lines are output from that command:

Secure and nonsecure sessions

If you want to concurrently run both secure sessions and nonsecure sessions, you must install a second instance of the RSE server and configure the `ssl.properties` file in the new installation directory. You cannot use a single instance of the server to run both secure sessions and nonsecure sessions concurrently.

For example, suppose that you have installed the RSE server in the default directory and you have configured it to run nonsecure sessions using the default port. Follow these steps:

1. Install a second instance of the RSE server into a new installation directory, such as `/opt/IBM/RDPower/8.0/rsessl`.
2. In the installation directory, modify the `ssl.properties` file as described in the topic “Configuring the RSE server to use SSL” on page 12:

```
daemon_keystore_file=jks_file
daemon_keystore_password=jks_password
```

```
enable_ssl=true
disable_server_ssl=false
```

3. Start the server, using a different port than the port used for nonsecure connections:

Notices

© Copyright IBM Corporation 2000, 2011.

U.S. Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Programming interfaces: Intended programming interfaces allow the customer to write programs to obtain the services of IBM Rational Developer for System z.

*IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
U.S.A.*

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan, Ltd.
3-2-12, Roppongi, Minato-ku, Tokyo 106-8711 Japan*

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*Intellectual Property Dept. for Rational Software
IBM Corporation
20 Maguire Road
Lexington, Massachusetts 02421-3112
U.S.A.*

Such information may be available, subject to appropriate terms and conditions, including in some cases payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement, or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements, or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice and represent goals and objectives only.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

Copyright license

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Each copy or any portion of these sample programs or any derivative work must include a copyright notice as follows: "© (your company name) (year). © Copyright

IBM Corporation 2000, 2011. Portions of this code are derived from IBM Corp. Sample Programs. Copyright IBM Corp. 2000, 2011".

Trademark acknowledgments

IBM, the IBM logo, and `ibm.com`[®] are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at Copyright and trademark information [www.ibm.com/legal/copytrade.shtml].

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other product and service names might be trademarks of IBM or other companies.



Printed in USA

SC14-7496-00

