

IBM Security Identity Manager

Reference Topics



Contents

Tables.....	xi
Chapter 1. Application extensions.....	1
WorkflowApplication interface.....	1
Application extension methods.....	1
Registering extensions.....	2
Chapter 2. Application programming interfaces.....	3
Applications API.....	3
Self registration API.....	4
Access control information list (ACI) API.....	4
IBM Security Identity Manager group API.....	4
Provisioning policy API.....	4
Recertification policy API.....	4
Reconciliation API.....	5
Authentication API.....	5
Data services API.....	6
IBM Directory Integration API.....	6
JavaScript API.....	6
Mail API.....	6
Password rules API.....	7
Policy analysis API.....	7
Service provider API.....	7
Single sign-on API.....	8
Web services API.....	8
Updates to the web services application interface programming (API).....	11
Workflow API.....	11
Chapter 3. Dictionary for a password policy.....	13
Chapter 4. Dataservices attributes for recertification.....	15
Chapter 5. Date range customization.....	17
Chapter 6. Workflow extensions.....	19
Policy enforcement extension.....	19
Recertification extensions.....	19
Wait extension.....	22
Chapter 7. REST APIs.....	25
REST API code samples.....	25
Invoking REST APIs in a domain different from the originating web page.....	25
Configuring REST APIs for OAuth authentication.....	26
Filter configuration for REST search services.....	27
Chapter 8. Dynamic tags in mail templates.....	31
Mail templates.....	36
Manual service default messages.....	36
Recertification default messages.....	38

Workflow default messages.....	43
Chapter 9. JavaScript extensions overview.....	55
Packaged extensions.....	56
AttributesExtension.....	56
DelegateExtension.....	57
EmailContextExtension.....	57
EnroleExtension.....	57
IdentityPolicyExtension.....	57
LoopCountExtension.....	58
Model extensions package.....	58
PersonPlacementRulesExtension.....	59
PostOfficeExtension.....	60
ProvisioningPolicyExtension.....	60
ReminderExtension.....	60
ServiceExtension.....	60
SubjectExtension.....	61
WorkflowExtension.....	61
Registering JavaScript extensions.....	62
Configuring scriptframework.properties.....	63
Migration of custom FESI extensions to the IBM JSEngine.....	64
Best practice in handling function returns.....	64
Plain Old Java Object (POJO) example.....	64
Conversion to a script extension.....	66
Creation of a constructor.....	67
Download of fes.jar from a non-IBM source (deprecated).....	68
Chapter 10. JavaScript extension reference.....	69
How to read the reference pages.....	70
Account.....	71
Account.getAndDecryptPassword().....	72
Account.setAndEncryptPassword().....	72
AccountSearch.....	73
AccountSearch.searchByOwner().....	73
AccountSearch.searchByUid().....	74
AccountSearch.searchByUidAndService().....	74
AccountSearch.searchByURI().....	75
Activity.....	75
Activity.auditEvent().....	77
Activity.description.....	77
Activity.duedate.....	77
Activity.getSubProcesses().....	78
Activity.guid.....	78
Activity.id.....	78
Activity.index.....	79
Activity.name.....	79
Activity.participant.....	79
Activity.resultDetail.....	79
Activity.resultSummary.....	80
Activity.setResult().....	80
Activity.started.....	80
Activity.state.....	81
Activity.subtype.....	81
Activity.type.....	81
AttributeChangeOperation.....	82
AttributeChangeOperation.attr.....	82
AttributeChangeOperation.op.....	82

AttributeChangeOperation.values[].....	83
ContainerSearch.....	83
ContainerSearch.searchByFilter().....	83
ContainerSearch.searchByURI().....	84
Context.....	84
Context.getAccountParameter().....	86
Context.getActivityResult().....	86
Context.getActivityResultById().....	86
Context.getLoopCount().....	87
Context.getLoopCountById().....	87
Context.getProcessType().....	87
Context.getRequestee().....	88
Context.getService().....	88
Context.isAccountDataChanged().....	88
Credential.....	89
Credential.getAccessMode().....	90
Credential.getCheckoutDuration().....	90
Credential.getNotifyOption().....	90
Credential.getNotificationRecipient().....	90
Credential.isCheckoutSearchEnable().....	91
Credential.isNotifyOnly().....	91
Credential.isPasswordViewable().....	91
Credential.isResetPasswordAtCheckin().....	92
Delegate.....	92
DirectoryObject.....	93
DirectoryObject.addProperty().....	94
DirectoryObject.dn.....	94
DirectoryObject.getChanges().....	95
DirectoryObject.getProperty().....	95
DirectoryObject.getPropertyAsDate().....	96
DirectoryObject.getPropertyAsString().....	96
DirectoryObject.getPropertyNames().....	97
DirectoryObject.name.....	97
DirectoryObject.profileName.....	97
DirectoryObject.removeProperty(name).....	98
DirectoryObject.removeProperty(name,value).....	98
DirectoryObject.setProperty().....	99
EmailContext.....	99
Enrole.....	101
Enrole.generatePassword().....	102
Enrole.getAttributeValue().....	103
Enrole.getAttributeValues().....	103
Enrole.localize().....	103
Enrole.log().....	104
Enrole.logError().....	104
Enrole.logInfo().....	105
Enrole.logWarning().....	105
Enrole.toGeneralizedTime().....	106
Enrole.toMilliseconds().....	106
Enrole.traceMax().....	107
Enrole.traceMid().....	107
Enrole.traceMin().....	108
Error.....	108
Error.setMessage().....	109
Error.getMessage().....	109
Error.setErrorCode().....	109
Error.getErrorCode().....	110
ExtendedPerson.....	110

ExtendedPerson.getOwnershipType().....	111
ExtendedPerson.setOwnershipType().....	111
IdentityPolicy.....	112
IdentityPolicy.getNextCount().....	112
IdentityPolicy.userIDExists().....	113
PackagedApprovalDocument.....	113
PackagedApprovalItem.....	115
Participant.....	116
Participant.implementation.....	117
Participant.name.....	117
Participant.type.....	117
ParticipantType.....	118
Person.....	119
Person.getAllAssignmentAttributes().....	121
Person.getAndDecryptSynchPassword().....	121
Person.getAndDecryptPersonPassword().....	122
Person.getRoleAssignmentData().....	122
Person.getRoleAssignmentData(String roleAssignedDN).....	123
Person.getRoles().....	123
Person.getNewRoles().....	124
Person.getNewRoles(boolean convertReplaceToAddDelete).....	124
Person.getRemovedRoles().....	124
Person.getRemovedRoles(boolean convertReplaceToAddDelete).....	125
Person.isInRole().....	125
Person.removeRole().....	126
Person.removeRoleAssignmentData().....	126
Person.updateRoleAssignmentData().....	127
PersonSearch.....	127
PersonSearch.searchByFilter().....	128
PersonSearch.searchByURI().....	128
PostOffice.....	129
PostOffice.getAllEmailMessages().....	129
PostOffice.getEmailAddress().....	130
PostOffice.getPersonByEmailAddress().....	130
PostOffice.getTopic().....	130
Process.....	130
Process.auditEvent().....	132
Process.comment.....	132
Process.description.....	133
Process.getActivity().....	133
Process.getParent().....	133
Process.getRootProcess().....	134
Process.getRootRequesterName().....	134
Process.guid.....	134
Process.getSubProcesses().....	135
Process.id.....	135
Process.name.....	135
Process.parentId.....	136
Process.requesteeDN.....	136
Process.requestorDN.....	136
Process.requesteeName.....	136
Process.requestorName.....	137
Process.requestorId.....	137
Process.requestorType.....	137
Process.resultDetail.....	138
Process.resultSummary.....	138
Process.setRequesteeData().....	138
Process.setResult().....	139

Process.setSubjectData()	139
Process.started	139
Process.state	140
Process.subject	140
Process.type	140
ProcessData	141
ProcessData.get()	141
ProcessData.set()	141
RecertificationWorkflow	142
Reminder	142
Role	143
Role.getAscendantRoles()	144
Role.getAssignmentAttributes()	144
Role.getChildRoles()	145
Role.getDescendantRoles()	145
Role.getOwner()	146
Role.getParentRoles()	146
Role.setAssignmentAttributes()	147
RoleAssignmentAttribute	147
RoleAssignmentAttribute.getName()	147
RoleAssignmentAttribute.getRoleName()	148
RoleAssignmentAttribute.getRoleDN	148
RoleAssignmentObject	149
RoleAssignmentObject.getAssignedRoleDN()	150
RoleAssignmentObject.getDefinedRoleDN()	150
RoleAssignmentObject.addProperty()	150
RoleAssignmentObject.getChanges()	151
RoleAssignmentObject.getProperty()	152
RoleAssignmentObject.getPropertyNames()	152
RoleAssignmentObject.removeProperty()	152
RoleAssignmentObject.setProperty()	153
RoleSearch	153
RoleSearch.searchByName()	153
RoleSearch.searchByURI()	154
SeparationOfDutyRuleViolation	154
Service	155
ServiceSearch	155
ServiceSearch.searchByFilter()	156
ServiceSearch.searchByName()	156
ServiceSearch.searchByURI()	157
ServiceSearch.searchForClosestToPerson()	157
UserAccess	158
AccessRequestBatch	158
AccessRequestBatch.getSubmittedAccessProvisioningList()	159
AccessRequestBatch.getSubmittedAccessDeprovisioningList()	160
AccessRequestBatch.getSubmittedAccessUpdateList()	160
AccessRequestBatch.getAccessProvisioningStatusList()	161
AccessRequestBatch.getAccessDeprovisioningStatusList()	161
AccessRequestBatch.getAccessUpdateStatusList()	162

Chapter 11. Provisioning policy parameter usage scenarios..... 163

Chapter 12. Provisioning policy entitlement parameters..... 165

Provisioning policy constant	165
Provisioning policy Null types	165
Provisioning policy JavaScript functions	165
Provisioning policy regular expressions	168

Chapter 13. Service selection policy JavaScript.....	169
Service selection policy JavaScript objects.....	169
Service selection policy script example.....	169
Chapter 14. SubForm control type.....	171
SubForm contextual parameters.....	171
HTTP request parameter naming convention.....	172
Process to write a SubForm.....	173
Chapter 15. Supplemental property files.....	175
Properties files.....	175
Modifiable property files.....	175
Non-modifiable properties files.....	178
adhocreporting.properties.....	180
CustomLabels.properties.....	187
DataBaseFunctions.conf.....	188
enroleAuditing.properties.....	189
enRoleAuthentication.properties.....	192
enRoleDatabase.properties.....	194
enRoleLDAPConnection.properties.....	197
enRoleLogging.properties.....	201
enRoleMail.properties.....	214
enrolepolicies.properties.....	218
enroleStartup.properties.....	223
enroleworkflow.properties.....	224
fesiextensions.properties (deprecated).....	225
helpmappings.properties.....	227
reportingLabels.properties.....	228
reporttabledeny.properties.....	228
rest.properties.....	229
scriptframework.properties (Suggested).....	231
SelfServiceHelp.properties.....	233
SelfServiceHomePage.properties.....	233
SelfServiceScreenText.properties.....	234
SelfServiceUI.properties.....	234
ui.properties.....	237
UIConfig.properties.....	247
Chapter 16. Select accounts to exclude from reconciliations.....	253
Chapter 17. System property configuration in enRole.properties.....	255
Properties files.....	255
WebSphere Application Server properties.....	255
Remote services properties.....	259
Web services properties.....	260
Application server properties.....	261
Organization properties.....	263
LDAP server properties.....	264
Search and LDAP control properties.....	265
Person profile properties.....	268
Profile and schema cache properties.....	269
LDAP connection pool properties.....	270
Mail properties.....	272
Messaging properties.....	273
Password encryption properties.....	275
Password synchronization properties.....	277

Password transaction monitor properties.....	277
Product name properties.....	278
Reconciliation properties.....	278
Scheduling properties.....	282
Shared secret properties.....	283
System listening port properties.....	284
XML and DTD properties.....	285
Challenge response encoding properties.....	285
Workflow properties.....	285
Lifecycle rule properties.....	292
Application client request properties.....	293
Reverse password synchronization properties.....	293
Post office properties.....	294
Database resource bundle properties.....	295
Database cleanup properties.....	296
Create password check box properties.....	296
Access catalog properties.....	296
Identity feed properties.....	297
Upgrade properties.....	298
Multiple password-synch agent properties.....	299
Concurrency properties.....	299
Required field properties.....	300

Index..... 301

Tables

1. Filters and their supported values.....	27
2. Syntax and example of using JavaScript code to replace message content.....	31
3. Syntax and examples of using a RE tag to replace message content.....	33
4. Syntax and example of using tags to replace message content.....	33
5. Syntax and examples of ITIMURL.....	34
6. Escape characters.....	34
7. Host components and script extensions.....	55
8. Script class keys.....	63
9. Script extensions.....	69
10. Provisioning policy examples.....	163
11. Sample provisioning policies.....	163
12. SubForm parameters.....	171
13. SubForm parameters.....	171
14. Properties files.....	175
15. Non-modifiable properties files.....	178
16. adhocreporting.properties properties.....	180
17. DataBaseFunctions.conf.....	188
18. enroleAuditing.properties properties.....	190
19. enRoleAuthentication.properties properties.....	192
20. enRoleDatabase.properties properties.....	194
21. enRoleLDAPConnection.properties properties.....	197
22. enRoleLogging.properties properties.....	201
23. enRoleMail.properties file properties.....	214

24. enrolepolicies.properties properties.....	219
25. enroleStartup.properties properties.....	223
26. enroleworkflow.properties properties.....	225
27. fesiextensions.properties properties (deprecated).....	226
28. helpmappings.properties properties.....	227
29. reporttabledeny.properties.....	228
30. rest. properties.....	229
31. SelfServiceHelp properties.....	233
32. SelfServiceUI. properties.....	234
33. ui.properties properties.....	238
34. UIConfig.properties.....	247
35. WebSphere application server properties.....	255
36. Remote services properties.....	259
37. Web services properties.....	260
38. Application server properties.....	261
39. Organization properties.....	263
40. LDAP server properties.....	264
41. Search and LDAP control properties.....	265
42. Person profile property.....	268
43. Profile and schema cache properties.....	269
44. LDAP connection pool properties.....	270
45. Mail services properties.....	273
46. Messaging properties.....	273
47. Encryption properties.....	275
48. Password transaction monitor properties.....	278

49. Product property.....	278
50. Reconciliation properties.....	278
51. Scheduling properties.....	283
52. Shared secret hashing properties.....	283
53. System configuration properties.....	284
54. XML and DTD properties.....	285
55. Challenge response encoding properties.....	285
56. Workflow configuration properties.....	286
57. Lifecycle rule properties.....	292
58. Application client request properties.....	293
59. Reverse password synchronization properties.....	293
60. Post office properties.....	294
61. Database resource bundle properties.....	295
62. Database cleanup properties.....	296
63. Create password check box default properties.....	296
64. Access catalog properties.....	297
65. Default identity feed properties.....	297
66. Default upgrade properties.....	298
67. Multiple password-synch agent properties.....	299
68. Account concurrency properties.....	299
69. Required field properties.....	300

Chapter 1. Application extensions

Application extensions can be defined in Java™ class files and run from a workflow.

Application extensions are typically defined in one or more Java class files. They are used when a set of functions needs to be run from a workflow. The functions can be implemented to receive input parameters from a workflow and return parameters back to the workflow.

WorkflowApplication interface

Application extensions that require access to the current workflow context information must implement the `WorkflowApplication` interface.

If the extension does not require any workflow context information, implementing this interface is not required. The following example is a code snippet for implementing the `WorkflowApplication` interface. For a complete example, see the information in the extensions directory.

```
public class CustomEmail implements WorkflowApplication {
    public CustomEmail() {
    }
}
```

When you implement the `WorkflowApplication` interface you must define a `setContext` method that accepts a `WorkflowExecutionContext` object. Store this object in a member variable in the implementing class.

```
// The context of the workflow. Passed in from the workflow engine
protected WorkflowExecutionContext ctx;
/**
 * Passes the workflow execution context to the application.
 *
 * @param context WorkflowExecutionContext holding information about the
 * currently executing activity.
 */
public void setContext(WorkflowExecutionContext ctx) {
    this.ctx = ctx;
}
```

Application extension methods

The application can contain whatever processing is required to accomplish the task. An extension can contain any number of methods that can be exposed to the workflow.

The following example is a code snippet of a method that is available in the workflow for the extension node. For a complete example, see the information in the `extensions.zip` file.

```
/**
 * Method sendMailByProperty.
 * This method is called to send an e-mail to an e-mail address specified by
 the
 * "recipient" property in the specified property file.
 * @param person - the requestee's person object
 * @param mailTag - the mailtag for this message. Used to look up properties
 * @param propertyFileName - the name of the property file that contains
 * this message's data
 * @param attrList - an optional list of tag/value pairs
 * @return ActivityResult - a workflow activity result object
 */
public ActivityResult sendMailByProperty(Person person,
String mailTag,
String propertyFileName,
String attrs) {
    String recipient_email = "";
    try {
        processSendMail(person, mailTag, propertyFileName, recipient_email,
            attrs);
    }
}
```

```

return new ActivityResult(ActivityResult.STATUS_COMPLETE,
    ActivityResult.SUCCESS,
    "Sent Mail",
    null);
} catch (CustomEMailDataException e) {
return new ActivityResult(ActivityResult.STATUS_COMPLETE,
    ActivityResult.FAILED,
    e.getMessage(),
    null);
}
}
}

```

Application Extension methods can receive inputs from the workflow. The inputs defined in the workflow extension window maps to the method arguments (ensure that the types match). The `sendMailByProperty` method returns an `ActivityResult` object. This method allows the application to communicate back to the caller a status and a return value, if necessary. The `ActivityResult` object has member variables for status (int), summary, (String), detail (List), and description (String). Return values are in the detail list. The order of the values in the list must correspond to the order of the output parameters as defined in the extension window. See the IBM® Security Identity Manager API documentation for a complete description of the `ActivityResult` class.

Registering extensions

For the workflow to make the extension available with the extension node, it must first be registered in the `ISIM_HOME/data/workflowextensions.xml` file.

Each method requires an activity entry in the XML file. The activity entry includes these aspects:

Activity ID

An activity ID is required and must be unique in the workflow. This name is in the extension window activity type menu.

Implementation type

The implementation type contains the class name and the method name that is started by this extension.

Parameters sections

The parameters sections list the input and out parameters and their data types. These parameters are in the extension window Input/Out Parameters.

Transition restriction

The transition restriction defines the join type. Split type can also be defined. For more information, see the information in the extensions directory.

```

<ACTIVITY ACTIVITYID="SendMailByProperty" LIMIT="600000">
  <IMPLEMENTATION_TYPE>
<APPLICATION
  CLASS_NAME="com.ibm.itim.CustomWorkflowExtensions.CustomEmail"
  METHOD_NAME="sendMailByProperty"/>
  </IMPLEMENTATION_TYPE>
  <PARAMETERS>
<IN_PARAMETERS PARAM_ID="inperson" TYPE="Person"/>
<IN_PARAMETERS PARAM_ID="mailtag" TYPE="String"/>
<IN_PARAMETERS PARAM_ID="propertyfilename" TYPE="String"/>
<IN_PARAMETERS PARAM_ID="attributelist" TYPE="String"/>
  </PARAMETERS>
  <TRANSITION_RESTRICTION JOIN="XOR"/>
</ACTIVITY>

```

The Application Extension class file must be in a JAR file, which must be in the IBM Security Identity Manager class path. After these changes are completed, you must restart the server before the extensions are available in the workflow.

Chapter 2. Application programming interfaces

Application programming interfaces (APIs) are part of a plug-in model that you can use to add applications without disrupting existing applications.

Remote application programs run outside of the IBM Security Identity Manager server Java virtual machine (JVM). Classes outside of the application packages are not intended to be started by a remote application. Classes in remote applications are documented under the IBM Security Identity Manager application packages. Server extensions, which run in the IBM Security Identity Manager server JVM, can use any of the classes listed in the published API documentation (Javadoc). They are Java classes that run in the same JVM of the caller. These APIs are used to develop IBM Security Identity Manager customization and extensions that can plug into IBM Security Identity Manager.

Several application APIs can be started by a remote application. A few server extension APIs in the `dataservices` package are included also. The following application APIs are intended to be started by a remote application:

Provisioning Policy API

Can search, add, modify, and delete provisioning policies in IBM Security Identity Manager from a remote application.

Group API

Can search, add, modify, and delete an IBM Security Identity Manager group.

ACI API

Can search, add, modify, and delete an access control information list (access right), but it does not verify authorization.

Reconciliation API

Can get, add, modify, and delete a reconciliation schedule for a particular service and triggers reconciliation.

The following server extension APIs are included:

- `com.ibm.itim.common.ComplexAttributeValue`
- `com.ibm.itim.dataservices.model.ComplexAttributeHandler`
- `com.ibm.itim.dataservices.model.domain.access.Access`
- `com.ibm.itim.dataservices.model.domain.access.ProvisioningConfiguration`
- `com.ibm.itim.dataservices.model.domain.access.NotificationOption`

Applications API

Use the applications API to create customized or alternative user interfaces. This API provides an interface to the IBM Security Identity Manager provisioning platform.

The applications API provides a set of Java classes that abstract the more frequently used functions of the provisioning platform. Examples are identity management, password management, and account management. The classes that make up this API are the same classes that IBM Security Identity Manager uses for its user interface.

For more information, see the documentation provided with the Applications API in the `ISIM_HOME/extensions/version number/doc/applications` directory. For sample codes, see the `ISIM_HOME/extensions/version number/examples/apps` directory.

Version number represents the version of IBM Security Identity Manager. For example:

```
ISIM_HOME/extensions/6.0/doc/applications
ISIM_HOME/extensions/6.0/examples/apps
```

Self registration API

Part of the applications API, the self registration API provides an interface to create a person in the provisioning platform without a user context.

The self registration API can be called without a user context. It is set up to start without accessing the system with an IBM Security Identity Manager account login and password. The Self Registration API is part of a customizable process. The process provides an example JavaServer Pages (JSP) page as a product extension based on the default `inetOrgPerson` class. The JSP calls the Self Registration API to create a user.

Access control information list (ACI) API

The ACI API provides an interface for managing the IBM Security Identity Manager access control list, container-by-container.

A remote client can use basic add, list, modify, and delete operations for managing the access control list. However, the ACI API cannot verify authorization to the user.

This API exists in the `com.ibm.itim.apps.acl.AccessControlListManager` class.

IBM Security Identity Manager group API

The IBM Security Identity Manager group API provides system group management capabilities, namely APIs to manage groups on the IBM Security Identity Manager service and groups on managed services. The APIs also provide search capabilities for these groups.

The IBM Security Identity Manager group API provides an interface for managing the groups on either the IBM Security Identity Manager service or on other managed services. You can search, add, modify, or delete these groups. You can also add and remove users in a group on either the IBM Security Identity Manager service or on a managed service.

For groups on the IBM Security Identity Manager service, the API exists in the following classes:

- `com.ibm.itim.apps.system.SystemRoleManager`
- `com.ibm.itim.apps.system.SystemRoleMO`
- `com.ibm.itim.apps.system.SystemUserMO`

For groups on a managed service, the API exists in the following classes:

- `com.ibm.itim.apps.provisioning.GroupManager`
- `com.ibm.itim.apps.provisioning.GroupMO`

Provisioning policy API

The IBM Security Identity Manager provisioning policy API provides an interface to manage provisioning policies that are defined in IBM Security Identity Manager.

This API can search, add, modify, and delete provisioning policy. The API exists in the following classes:

- `com.ibm.itim.apps.policy.ProvisioningPolicyManager`
- `com.ibm.itim.apps.policy.ProvisioningPolicyMO`

Recertification policy API

The IBM Security Identity Manager recertification policy API provides an interface to manage recertification policies that are defined in Security Identity Manager.

This API provides capabilities to search, add, modify, delete, and run recertification policies.

The following classes or interfaces are exposed to provide recertification policy management capabilities through APIs.

1. Core classes:

- `com.ibm.itim.apps.policy.RecertificationPolicyManager`
- `com.ibm.itim.apps.policy.RecertificationPolicyMO`
- `com.ibm.itim.dataservices.model.policy.recert.RecertificationPolicy`

2. Dependent classes:

- `com.ibm.itim.dataservices.model.policy.recert.RecertificationParticipant`
- `com.ibm.itim.dataservices.model.policy.RoleTarget`
- `com.ibm.itim.dataservices.model.policy.GroupTarget`
- `com.ibm.itim.dataservices.model.policy.ServiceTarget`
- `com.ibm.itim.scheduling.RecurringTimeSchedule`

3. Abstract classes extended by recertification policy directly or indirectly:

- `com.ibm.itim.dataservices.model.policy.DirectoryPolicy`
- `com.ibm.itim.dataservices.model.policy.ScopedPolicy`
- `com.ibm.itim.dataservices.model.policy.ServicePolicy`

4. Interface implemented by recertification policy or dependent classes directly or indirectly:

- `com.ibm.itim.dataservices.model.policy.Policy`
- `com.ibm.itim.dataservices.model.policy.IPolicyTarget`
- `com.ibm.itim.scheduling.Schedulable`

Reconciliation API

The reconciliation API can create and query reconciliations and reconciliation parameters.

The Reconciliation API provides an interface to manage reconciliation schedules of services. You can:

- Get and set reconciliation schedules to a service.
- Modify the reconciliation schedules collection, which includes additions and deletions.
- Set the new collection.
- Trigger a specific reconciliation schedule to run.

The API exists in the following classes:

- `com.ibm.itim.apps.recon.ReconManager`
- `com.ibm.itim.apps.recon.ReconUnitData`

Authentication API

Use the authentication API for working with different trusted identity stores such as identity information. This information can be stored on a Windows domain server or an LDAP directory. It includes the use of different types of keys, typically passwords, to unlock the application for a user.

The authentication API contains the authentication client API, which makes authentication requests, and the authentication provider API, which implements authentication requests.

Data services API

The data services API provides an interface to the IBM Security Identity Manager data model.

This API abstracts the more commonly used data model entities such as identities, accounts, access, and services in the provisioning process. It includes a generic interface to handle complex attributes. Data synchronization depends on Data Services APIs. Furthermore, the data services API provides the data model that the Applications API uses.

Although the ability to change the data model is provided in this API, this ability is not its focus. The Data Services API is low level. It abstracts the physical layout of the data store (directory structure). It does not provide the business logic that the provisioning applications with the platform provide.

IBM Directory Integration API

With this API, IBM Security Directory Integrator can import identity information into IBM Security Identity Manager. It manages accounts in the IBM Security Identity Manager data store on external resources that use IBM Security Directory Integrator.

The following features are included in this API:

Note: Directory Service Markup Language version 2 (DSMLv2) was deprecated.

- A Directory Service Markup Language version 2 (DSMLv2) `ServiceProvider`. You can use it to import data. IBM Security Identity Manager acts as a DSMLv2 client. IBM Security Directory Integrator acts as a DSMLv2 server.
- A DSMLv2 event handler. You can use it to import data into IBM Security Identity Manager. IBM Security Identity Manager acts as a DSMLv2 server. IBM Security Directory Integrator acts as a DSMLv2 client.
- Ready-to-use schema support for communicating with IBM Security Directory Integrator. You can use IBM Security Directory Integrator as an endpoint and define it as a service instance in the IBM Security Identity Manager user interface for identity feed.

JavaScript API

The JavaScript API extends the scripting components that are specific to the scripting language that is configured with the product.

IBM Security Identity Manager provides a method to register new JavaScript extensions with the server. You can use the JavaScript API to add additional objects and functions to the interpreter's glossary. A client can create and register additional objects and functions with the interpreter to run at run time.

The JavaScript API provides information about access participants, such as participant type, workflow participants, group access management, and access notification context.

Mail API

Use the mail API to customize mail content, format, and notification recipients.

Clients who use this API can make notification requests and extend construction of notification messages. The Mail API contains the Mail Client API, which makes notification requests, and the Mail Provider API, which implements notification requests.

The mail API also contains a function that is called Post Office that prevents workflow participants from receiving multiple email notifications that have similar content. Similar emails are stored, combined into a single email notification, and forwarded to a user.

Password rules API

The password rules API provides an interface to customize the standard password rule set and random password generation process.

You can use the password rules framework to customize the mechanism of generating passwords by the IBM Security Identity Manager server. Use one of the following ways to add custom logic to the password framework:

- A custom rule
- A custom generator
- Custom rules and a custom generator

Policy analysis API

The policy analysis API provides an interface to information about policies that are defined in the IBM Security Identity Manager Server. It is an interface to the access granted to a specific individual.

The API contains a set of Java classes that retrieve and abstract the provisioning policy information that controls access to managed resources. The Provisioning Policy API reports the provisioning policy enforcement in the system, but it does not support client modification of the policy. A client can use the policy information for auditing or deciding about potential policy enforcement changes.

Service provider API

The service provider API provides custom connectors. The connectors can be used from the IBM Security Identity Manager provisioning platform or any other Java-based provisioning platform that supports the same interface.

Service provider APIs define the interface that the IBM Security Identity Manager adapter needs to implement and communicate to remote adapter agents. The adapter agent implementation does not rely on IBM Security Identity Manager APIs except for the set of asynchronous notification APIs provided under Service Provider APIs.

The following operations are included in the interface between the provisioning platform and the connector:

- Add
- Change password
- Delete
- Modify
- Restore
- Search
- Suspend
- Test

The provisioning platform performs all of the operations needed to determine the actions and their parameters that are to be run against resources. The connector runs those operations on the resource within requirements that are related to the resource.

Single sign-on API

The single sign-on API provides a single sign-on interface to accessible resources.

Some IBM Security Identity Manager installations might require integration with third party, single sign-on providers. Typically, such single sign-on providers protect a set of web-based resources with an authentication data store that is managed separately from IBM Security Identity Manager. The first time a client attempts to access any protected resource, the single sign-on provider provides authentication. If access is granted, the provider passes a token that indicates the identity of the authenticated user to all resources that are accessed later.

Web services API

This API consists of multiple web services, which are grouped by function. The services are listed alphabetically except the `WSSessionService`. This service is listed first since it is the first service that is called by any application. The session object that is returned by its login method is used as a parameter in all subsequent services.

WSSessionService

The `WSSessionService` web service provides authentication, session creation, and password challenge authentication. A client calls `WSSessionService` before you start any other web services.

`WSSessionService` returns a session (handle) object that must be passed to the other web service calls to maintain a threaded conversation. The service provides the following operations:

- Login.
- Logout.

You can also use the `WSUnauthService` web service for other operations.

WSAccessService

The `WSAccessService` web service provides the following operations:

- Create a user access.
- Retrieve existing user access of a person.
- Remove user access.
- Search access entitlements available to a person.

The service provides following operations:

- Create and modify accesses.
- Do access searches.

WSAccountService

The `WSAccountService` web service provides the following operations to do account-related tasks:

- Create, modify, and other simple account operations.
- Retrieve default account attributes for a new account as specified by the provisioning policy.
- Retrieve the account profile name for a service.

WSExtensionService

The `WSExtensionService` web service provides a framework to extend the existing web services that are used by users. The service provides the users to create an operation to show a new Security Identity Manager API. The detailed steps to create an extension service are specified in the `ITIMWS.odt` file,

which is in the *ISIM_INSTALL_DIR/extensions/6.0/doc/ws* directory. *ISIM_INSTALL_DIR* is the directory where Security Identity Manager is installed.

WSGroupService

The `WSGroupService` web service provides group management functions. The service provides the following operations:

- Create and remove groups.
- Search groups.
- Manage group membership.

WSOrganizationalContainerService

The `WSOrganizationalContainerService` web service provides Security Identity Manager organization tree traversal and retrieval methods.

WSPasswordService

The `WSPasswordService` web service provides password management functions. The service provides the following operations:

- Validates the password as per the password policy rules.
- Enables change or generate password.

WSPersonService

The `WSPersonService` web service provides person-object related methods. The service provides the following operations:

- Create, modify, suspend, restore, delete, and other simple person operations.
- Retrieve the services to which a person is entitled in Security Identity Manager or accounts.
- Do person searches.
- Retrieve the person object of the Principal.

WSProvisioningPolicyService

The `WSProvisioningPolicyService` web service deals with the provisioning policy. The service provides the following operations:

- Search provisioning policies.
- Create, modify, and delete provisioning policies.

WSRequestService

The `WSRequestService` web service provides the Security Identity Manager request related functions. The service provides the following operations:

- Search for completed requests.
- Retrieve pending requests.
- Retrieve the request object that is based on the process ID or request ID.

WSRoleService

The `WSRoleService` web service provides role-based capabilities in the Security Identity Manager. The service provides the following operations:

- Create and modify roles.
- Do role searches.

- Manage role hierarchy.

WSSearchDataService

The `WSSearchDataService` web service provides functions to search various Security Identity Manager directory objects. The search method does not enforce the Security Identity Manager ACIs, but a valid Security Identity Manager session is required to call these methods. The service provides the following operations:

- Search for persons from root container.
- Search for persons that are having an Security Identity Manager account.
- Search for the possible delegates within Security Identity Manager for the logged-in user.
- Retrieve the searchable attributes of an entity in Security Identity Manager.
- Retrieve common searchable attributes for the Security Identity Manager entity.

WSServiceService

The `WSServiceService` web service provides Security Identity Manager-based managed services (end-point configuration) functions. The service provides the following operations:

- Retrieve support data. For example, group data for UNIX, Linux, or Microsoft Windows services.
- Determine whether a password is required when provisioning on a service.
- Retrieve services that are configured on Security Identity Manager.

WSSharedAccessService

The `WSSharedAccessService` web service provides many functions for the shared access module that is introduced in Security Identity Manager Version 6.0/Version 7.0. The web service clients must call the login method before it calls any other web services. The service provides the following operations:

- Retrieve authorized shared accesses.
- Retrieve the credentials.
- Check in or checkout credentials.

Note: You must install and enable the shared access module in order to use the `WSSharedAccessService` API.

For more information, see [Shared access web services API](#).

WSSystemUserService

The `WSSystemUserService` web service provides the functions that are related to system users. The service provides the following operations:

- Manage delegates, that is, add, modify, or delete delegates.
- Retrieve all the system roles.
- Configure challenge response.
- Search for system users who have an Security Identity Manager account.

WSToDoService

The `WSToDoService` web service provides the functions to manage the different activities available in Security Identity Manager. The service provides the following operations:

- Approve or reject activities.
- Retrieve or Submit Request for information activity details.
- Retrieve the pending activities of the logged-in user.

WSUnauthService

The WSUnauthService web service provides an interface for all the web service APIs that do not require the Security Identity Manager authentication. The service provides the following operations:

- Version information.
- Reset password by using the challenge responses.
- Password policies.

Updates to the web services application interface programming (API)

There are updates available for IBM Security Identity Manager web services APIs in any fix pack that is later than IBM Security Identity Manager 6.0.0.6.

Web services APIs for the person search, which belongs to the WSPersonService and WSSearchDataService services are updated to enable the search person functionality for any person category, such as Person, BPPerson, or Custom person.

The new web service WSRoleService deletes an organizational role.

Note: For detailed information about web services APIs, go to *ITIM_HOME/extensions/doc/ws/ITIMWS.odt*. For information about migrating existing APIs to IBM Security Identity Manager web services, go to *ITIM_HOME/extensions/doc/ws/migration/OPALWebServicesMigrationGuidelines.doc*.

Workflow API

Use the workflow API for custom code that can be called from a workflow process as a custom Java application or a JavaScript function. This custom code can then do special business logic, query external data stores, or provide integration with other workflow engines.

The Workflow API consists of a set of Java classes. The classes abstract the more commonly used concepts of the workflow environment, such as processes, activities, and relevant data.

The Workflow API supports new access request types. The access owner is a participant type.

The Workflow API provides methods for updating the recertification state and provides audit information for recertification. Audit records contain information about the recertification configuration and the *who*, *what*, and *when* of recertification tasks. These audits provide more useful reports about recertification compliance of users, accounts, and accesses. Consumers of the recertification policies can also have their recertification process audited in a reportable way.

Chapter 3. Dictionary for a password policy

You can create a dictionary for a password policy rule that rejects certain terms as passwords.

To use a dictionary for a password policy rule, you must first create and load a `dictionary.ldif` file to the IBM Security Identity Manager Server. To create a dictionary for a password policy rule:

1. Using an ASCII or other plain text editor, create a dictionary that contains the list of terms in an LDAP Data Interchange Format (LDIF) file.

For example, create a file similar to this `dictionary.ldif` file, which specifies the domain as `dc=com`:

```
dn: erword=test,erdictionaryname=password, ou=itim, dc=com
erWord: test
objectclass: top
objectclass: erDictionaryItem

dn: erword=secret,erdictionaryname=password, ou=itim, dc=com
erWord: secret
objectclass: top
objectclass: erDictionaryItem

dn: erword=password,erdictionaryname=password, ou=itim, dc=com
erWord: password
objectclass: top
objectclass: erDictionaryItem
```

2. Load the `dictionary.ldif` file on to the IBM Security Directory Server with one of these procedures:

- Use an LDAP browser to import the `dictionary.ldif` file.
- On the command prompt of the LDAP server, enter this command on one line.

```
ITDS_HOME/bin/ldapadd.exe -h hostname -D cn=adminuser
-w adminpwd -V 3 -f dictionary.ldif
```

-h *hostname*

Specifies the host name of the computer on which the LDAP server is running.

-D cn=*adminuser*

Specifies the administrator's distinguished name to bind to the LDAP directory.

-w *adminpwd*

Specifies the administrator's distinguished name password, for simple authentication.

-V *ldap_version*

Specifies the version of the LDAP protocol to use. The default value is 3, for the LDAP v3 protocol. A value of 2 uses the LDAP v2 protocol.

-f *file*

Reads the entry modification information from a file such as `dictionary.ldif`, instead of from standard input.

The dictionary file can now be used in the password strength rule.

Chapter 4. Dataservices attributes for recertification

IBM Security Identity Manager provides optional attributes in the `erAccountItem` object class to represent different values for recertification.

Overview

The `dataservices` attributes for recertification are relevant only if recertification is enabled for specific accounts or accesses.

The following optional attributes are provided:

- `erLastCertifiedDate`
- `erRecertificationLastAction`
- `erAccessLastCertifiedDate`
- `erAccessRecertificationLastAction`

`erLastCertifiedDate`

The `erLastCertifiedDate` attribute is updated by the account recertification process only, but not for accesses. An optional attribute for the timestamp of the last time the account was marked as recertified. This attribute is updated on approved recertifications regardless of recertification policy schedule type, whether rolling or calendar style.

This attribute is updated for both approvals during normal recertification cycle and through the `recertificationOverride` option outside of the normal recertification policy run. The absence of a value means that recertification was never approved for this account. The Account data services object from the `com.ibm.itim.dataservices.model.domain` package defines the `setLastCertifiedDate()` and `getLastCertifiedDate()` methods for accessing this attribute. When an account is *certified*, this attribute must be updated along with `reRecertificationLastAction`.

`erRecertificationLastAction`

The `erRecertificationLastAction` attribute is updated by the account recertification process only, but not for accesses. This attribute requires a getter and setter method defined on the Account data services object class `com.ibm.itim.dataservices.model.domain` package:

```
public void setRecertificationLastAction(String recertificationAction)
public String getRecertificationLastAction()
```

This optional attribute describes the action taken the last time recertification was run. The following values are valid:

- `com.ibm.itim.dataservices.model.domain.Account.CERTIFIED = 'CERTIFIED'`
- `com.ibm.itim.dataservices.model.domain.Account.CERTIFIED_ADMIN = 'CERTIFIED_ADMIN'`
- `com.ibm.itim.dataservices.model.domain.Account.REJECTED_MARK = 'REJECTED_MARK'`
- `com.ibm.itim.dataservices.model.domain.Account.REJECTED_SUSPEND = 'REJECTED_SUSPEND'`

`erAccessLastCertifiedDate`

The `erAccessLastCertifiedDate` attribute is specific to accesses that are defined on an account. This multivalued attribute holds the access group definition distinguished name and timestamp that shows when that access was last certified as a delimited string.

Example

```
eraccesslastcertifieddate: ertlocalname=users,  
erglobalid=7281584268561021074,ou=services,  
erglobalid=00000000000000000000,ou=hawk,o=ibm,  
c=us;;200711202115Z
```

This example shows the last recertification date for the access that is associated with the access defined for the group specified by the distinguished name. Only one value for this attribute per access is defined for the account.

erAccessRecertificationLastAction

The `erAccessRecertificationLastAction` attribute is specific to recertification state of accesses that are defined on an account. This multivalued attribute holds the access group definition distinguished name and recertification last action taken as a delimited string. It serves the same purpose for accesses as `erRecertificationLastAction` does for accounts.

Example

```
eraccessrecertificationlastaction: ertlocalname=users,  
erglobalid=7281584268561021074,  
ou=services,erglobalid=00000000000000000000,  
ou=hawk,o=ibm,c=us;;CERTIFIED
```

This example shows the last recertification action for the access that is associated with the group definition distinguished name. The values for the action are the same as described for the `erRecertificationLastAction` attribute. Only one value for this attribute per access is defined for the account.

Chapter 5. Date range customization

IBM Security Identity Manager provides additional date range customization, which is not available through the standard Form Designer applet.

With these options, you can control the years available to users when they customize a date. The following options must be configured manually on the following form template that is stored in the directory server:

```
erformname=inetOrgPerson,ou=formTemplates,ou=itim,ou=tivsys,dc=com
```

You can specify options that define the range of years to be displayed. You also can specify the standard range of years, a special extended max year such as 9999, or special minimum value such as 1900. You have options to display all years between the standard range and extended dates.

The options are:

minYear

Minimum year to display.

spanMinYearRange

When set to a value of false, displays all years between minYear and minRangeYear.

minRangeYear

Starting year for the standard range of years. The default is 1990.

maxRangeYear

Ending year for the standard range of years. The default is 2010.

spanYearRange

When the value is false, displays all years between maxRangeYear and maxYear.

maxYear

Maximum year to display.

Chapter 6. Workflow extensions

Workflow extensions provide a means to alter or extend workflow functions.

Policy enforcement extension

The policy enforcement extension assesses the accounts that are associated with a Person or BPPerson and enforces the policies in place for that person.

Overview

A policy enforcement extension is code that can be called directly from a workflow. Workflows that change a person object typically use this extension.

The extension is implemented in `com.ibm.itim.workflowextensions.PersonExtensions`.

The following extensions are provided:

- `enforcePolicyForPerson(Person, skipNonEntitledAccountsEvaluation)`
- `enforcePolicyForPerson(BPPerson, skipNonEntitledAccountsEvaluation)`

The extensions work identically on the specified Person or BPPerson.

`skipNonEntitledAccountsEvaluation` is a string, either `true` or `false`.

- If `false`, then all accounts applicable to the person are evaluated. All accounts that the person owns are considered when the extension enforces provisioning policies.
- If `true`, then policy enforcement proceeds as follows:
 1. Identify all services applicable for the person store them in a collection.
 2. Check for removed roles in the change list of the specified person.
 3. Merge the list of services that are identified in step 1 and step 2.

This process specifies that only accounts calculated from the person's role change are considered for policy enforcement. No other accounts are considered.

Therefore, some accounts are not considered: accounts where the person's role is removed, and accounts that are already provisioned for those roles.

For examples of how the extensions are used, see the Add, Modify, and Transfer operations in [Operations management](#).

Recertification extensions

The recertification extensions track the recertification state in a workflow.

Overview

A recertification extension is code that can be called directly from a workflow. An extension defined for accounts also handles the recertification state for accesses, and uses `dataservices` to update attributes stored on the account object in data services. These extension methods are integrated into the `AccountExtensions` class from the `com.ibm.itim.workflowextensions` package.

Because the recertification extensions provided are considered activities by the workflow engine, any failure in those extensions is returned as a failure when the activity completes. This result causes the recertification workflow to fail, and its failure is audited in the `RECERTIFICATIONLOG` audit table as well.

The following extensions are provided:

- `constructApprovalDocument`
- `recertificationMark`
- `recertificationMarkAccess`
- `recertificationSuspend`
- `recertificationCertify`
- `recertificationCertifyAccess`
- `recertificationAdminCertify`
- `recertificationAdminCertifyAccess`
- `remediateAccountsAndGroups`
- `remediateRoleMemberships`
- `updateRecertificationStatusAllApproved`
- `updateRecertificationStatusEmptyDocument`

recertificationMark

The public `ProcessResult recertificationMark(Account)` extension updates `erLastRecertificationAction` for the target type, updating the `erLastRecertificationAction` attribute to:

```
com.ibm.itim.dataservices.model.domain.Account.REJECTED_MARK = 'REJECTED_MARK'
```

The recertification action is audited in `RECERTIFICATIONLOG` table for use by reports.

constructApprovalDocument

The public `ProcessResult constructApprovalDocument(Person, RecertificationPolicy)` extension constructs the `PackagedApprovalDocument` that is required for user-based recertification. This document contains all of the static roles, accounts, and groups for the specified person.

If there are no recertification targets for the person, this method returns a `ProcessResult` with a `WARNING` summary and an embedded message. In this case, it contains an output parameter list with an empty document. Otherwise, if successful, the `ProcessResult` contains a populated document for this particular person.

recertificationMarkAccess

The public `ProcessResult recertificationMark(UserAccessAccount)` extension has the same function for accesses as `recertificationMark()` has for users and accounts. It updates the `erAccessLastRecertificationAction` attribute specific to the `UserAccess` passed in to:

```
com.ibm.itim.dataservices.model.domain.Account.REJECTED_MARK = 'REJECTED_MARK'
```

The recertification action is audited in `RECERTIFICATIONLOG` table for use by reports.

Note: This method is for suspending accounts only. No method for suspending access is provided.

recertificationSuspend

The public `ProcessResult recertificationSuspend(Account)` extension updates `erLastRecertificationAction` for the account. It updates the `erLastRecertificationAction` attribute to:

```
com.ibm.itim.dataservices.model.domain.Account.REJECTED_SUSPEND = 'REJECTED_SUSPEND'
```

The recertification action is audited in `RECERTIFICATIONLOG` table for use by reports.

Note: This method is for suspending accounts only. No method for suspending access is provided.

recertificationCertify

The public `ProcessResult recertificationCertify(Account)` extension updates `erLastRecertificationAction` for the target type. It updates the `erLastRecertificationAction` attribute to:

```
com.ibm.itim.dataservices.model.domain.Account.CERTIFIED = 'CERTIFIED'
```

The recertification action is audited in `RECERTIFICATIONLOG` table for use by reports. This extension also updates the `erLastCertifiedDate` attribute with the current timestamp.

recertificationCertifyAccess

The public `ProcessResult recertificationCertify(UserAccessAccount)` extension updates `erLastAccessRecertificationAction` for the access. It updates the `erLastRecertificationAction` attribute for the specified `UserAccess` to:

```
com.ibm.itim.dataservices.model.domain.Account.CERTIFIED = 'CERTIFIED'
```

The recertification action is audited in `RECERTIFICATIONLOG` table for use by reports. This extension also updates the `erAccessLastCertifiedDate` attribute for the `accessAttribute` with the current timestamp.

Note: This method is the access version of `recertificationCertify` for users and accounts.

recertificationAdminCertify

The public `ProcessResult recertificationAdminCertify(Account)` extension updates `erLastRecertificationAction` for the target type. It updates the `erLastRecertificationAction` attribute to:

```
com.ibm.itim.dataservices.model.domain.Account.CERTIFIED_ADMIN = 'CERTIFIED_ADMIN'
```

The recertification action is audited in `RECERTIFICATIONLOG` table for use by reports. This extension also updates the `erLastCertifiedDate` attribute with the current timestamp.

recertificationAdminCertifyAccess

The public `ProcessResult recertificationAdminCertify(UserAccessAccount)` extension updates `erLastRecertificationAction` for the access. It updates the `erAccessLastRecertificationAction` attribute for the `UserAccess` passed in to:

```
com.ibm.itim.dataservices.model.domain.Account.CERTIFIED_ADMIN = 'CERTIFIED_ADMIN'
```

The recertification action is audited in `RECERTIFICATIONLOG` table for use by reports. This extension also updates the `erAccessLastCertifiedDate` attribute for the `accessAttribute` with the current timestamp.

Note: This method is the access version of `recertificationAdminCertify` for users and accounts.

remediateAccountsAndGroups

The public `ProcessResult remediateAccountsAndGroups(PackagedApprovalDocument, Person, RecertificationPolicy, String)` extension runs user recertification remediation on all of the accounts, groups, and accesses in the approval document. Each entry is processed based on the responses in the document and the enforcement action of the policy. Any recertification status updates are performed directly through data services. Any removals of accounts, groups, or accesses are handled by launching the appropriate workflow operation as a subprocess.

remediateRoleMemberships

The public `ProcessResult remediateRoleMemberships(PackagedApprovalDocument, Person, RecertificationPolicy, String)` extension runs user recertification remediation on all role memberships in the approval document. Each entry is processed based on the responses in the document and the enforcement action of the policy. If any roles are removed, this extension launches the person modify operation to process the removal and corresponding policy enforcement actions. If no role are removed, this activity directly invokes policy enforcement to make sure that the recertification is performed on every person.

updateRecertificationStatusAllApproved

The public `ProcessResult updateRecertificationStatusAllApproved(PackagedApprovalDocument, Person, RecertificationPolicy)` extension processes the approval document, and updates the recertification status of each entry. The entries include accounts, groups, and role memberships. This extension is only invoked when all choices in the document are approved. Different extensions are used for remediation. Any recertification status updates are performed directly through data services.

updateRecertificationStatusEmptyDocument

The public `ProcessResult updateRecertificationStatusEmptyDocument(PackagedApprovalDocument, Person, RecertificationPolicy)` extension updates the required recertification status on the person being recertified. It is the only action required in the case that the document does not contain any resources. The recertification status updates are performed directly through data services.

Wait extension

The wait extension pauses the workflow until a specified time.

Overview

A wait extension is code that can be called directly from a workflow. It is implemented in the `WaitExtension` class in the `com.ibm.itim.workflowextensions` package.

The following extension is provided:

- `scheduleTimeout`

scheduleTimeout

The public `ProcessResult scheduleTimeout(Date)` extension suspends the workflow until the time specified by `Date`, which is the standard `Date` object in JavaScript. When the specified time is reached, the extension activity is complete and the workflow continues.

Embed the wait extension in a loop in the workflow if you want the workflow to check a condition and continue only when the condition is no longer met. The loop requires the following logic:

- Check the condition.
- Calculate the target date for the wait extension from the current date. Use JavaScript.
- Run the wait extension. Use the calculated target date for `scheduleTimeout(Date)`.

For more information about `Date`, see a JavaScript reference like the following: [JavaScript Date Reference](#). Another possible reference is the [ECMAScript\(r\) Language Specification](#), published by ECMA International, which now administers the standards that are the basis for JavaScript and other scripting languages.

Examples

- A workflow loop checks CPU load and continues only when CPU load falls below the desired level.

1. Check CPU load.
 - If CPU load is below the desired threshold: Exit the loop.
 - If CPU load is above the desired threshold: Calculate the target DATE and then run the wait extension.
2. When the wait extension is complete, loop to check CPU load again.
- Enforce dynamically calculated timeouts for long-running workflow activities. For example, implement an approval that is pending for *two working days*.
 1. Calculate the target DATE. Use JavaScript. The calculation needs to account for workflows that are triggered near a weekend. For example, consider the desired period of two working days. If the workflow is triggered on a Friday, the target date is Tuesday (four elapsed days). If the workflow is triggered on a Monday, then the target date is Wednesday (two elapsed days).
 2. Branch workflow execution that uses a fork type of AND. Put the approval on one branch and the wait extension with the target DATE on the other branch.
 3. Merge the two branches with a join type of OR.

The workflow continues when either branch is complete: an approval is submitted or the wait extension times out.

Chapter 7. REST APIs

You can develop custom applications by using the REST application programming interfaces (APIs) that come with the IBM Security Identity Manager. The REST APIs are available so that you can administer the tasks outside of the IBM Security Identity Manager user interface. The topic provides information about the functions that REST APIs support.

Note: The REST API documentation is available in the following location:

ISIM_HOME/extensions/6.0/doc/rest/index.html

The REST APIs are segregated into a set of functional components of IBM Security Identity Manager that are listed in the following section.

Person Management

View or edit user profiles.

System User Management

Search capability for the IBM Security Identity Manager system users based on unique identifiers.

Password Management

Change or reset the password, and recover the forgotten password.

Access Management

Request, view, edit, or delete the access.

Activity Management

View and act on your activities.

Delegation Management

Delegate activities, view, edit, and delete the delegation schedule.

Generic Search APIs

Assorted set of search capabilities that are provided by the REST APIs.

REST API code samples

The REST API code samples are annotated. The annotations provide information about how to use the samples in your test environment.

The REST API annotated code samples are available in *ISIM_HOME*/extensions/6.0/examples.

Invoking REST APIs in a domain different from the originating web page

IBM Security Identity Manager REST APIs support cross-origin resource sharing (CORS). CORS describes a mechanism for supporting requests that a web page sends to a server that is not in the same domain as the originating web page. You can configure CORS to control which origins can work with the IBM Security Identity Manager REST APIs.

About this task

You can modify a list of trusted domains that can access Identity Service Center REST APIs. Complete the steps.

Procedure

1. Open the *ISIM_HOME*/data/rest.properties file.
2. In the ui.CORSOrigin property, set the trusted domains.
You can add multiple domains that are separated by white space.

Results

The domains that are listed in the `ui.CORSOrigin` property can only access the IBM Security Identity Manager REST APIs.

Configuring REST APIs for OAuth authentication

IBM Security Identity Manager REST APIs support OAuth authentication. OAuth provides a method for client applications to access server resources on behalf of a resource owner. A resource owner might be a different client or a user. It specifies a process for resource owners to authorize third-party access to their server resources without sharing their credentials.

Before you begin

Complete the OAuth configuration. See http://www.ibm.com/support/knowledgecenter/SSEQTP_8.5.5/com.ibm.websphere.base.doc/ae/cwbs_oauthintroduction.html?cp=SSEQTP_8.5.5%2F1-8-2-31-3-9. You can also refer to the developer works article as an example for the OAuth configuration at http://www.ibm.com/developerworks/websphere/techjournal/1305_odonnell1/1305_odonnell1.html.

About this task

The OAuth third-party client uses the user credentials to request an access token from the WebSphere® Application Server. It is one time activity. The access token is placed in the client repository. The third-party client can access the IBM Security Identity Manager REST APIs by providing the access token as a credential to REST APIs.

After you complete the OAuth configuration, you must enable OAuth Trust Association Interceptor (TAI) and start the components for IBM Security Identity Manager.

Procedure

1. Enable OAuth TAI for the IBM Security Identity Manager domain that is already configured in WebSphere Application Server.
 - a) In the WebSphere Application Server administrative console, click **Security > Global Security > Security Domains > ISIMSecurity Domain**.
 - b) Under **Security Attributes**, expand **Trust Association**.
 - c) Select the option **Customize for this domain**.
 - d) Select **Enable trust association**.
 - e) Click **Interceptors**.
 - f) Click **New**.
 - g) Create the interceptor with an interceptor class name of `com.ibm.ws.security.oauth20.tai.OAuthTAI`.
2. Start the components to enable OAuth.
 - a) In the WebSphere Application Server administrative console, click **Servers > Server Types > Websphere Application Servers**, add your server name.
 - b) Under **Configuration** tab, select **Start components as needed**.
 - c) Restart the WebSphere Application Server.

Results

After you enable OAuth in WebSphere Application Server successfully, a token is generated for the Identity Service Center user. You can use the generated token and do not require to authenticate to access REST APIs.

Filter configuration for REST search services

Use the following information to learn how the IBM Security Identity Manager REST search services create the search filter expression.

You can configure the filters and the HTTP request URL query parameters to control the data that the REST search services return.

Note:

To use a specific filter configuration for a request, the REST client can supply 'filterId' as a URL query parameter and its value must be the filter identifier that is configured in the custom/rest/searchfilter.json file. See "Examples" on page 28.

For more information about how to define the filter identifier, see [Defining the filter identifier for REST search service](#). The REST service uses the corresponding filter configuration in the following table to create the filter expression.

Filters	Description
"filterTemplate"	<p>A template string for the filter expression. For example,</p> <ul style="list-style-type: none"> "(&(&(date>=\${fromDate})(date<=\${toDate}))\${filterExpression})". <i>fromDate</i> and <i>toDate</i> are the URL parameter names and their values are placed in the template. \${filterExpression} is replaced with the expression that is created with remaining URL parameters as described in the table. <p>Note: filterTemplate is an optional configuration for a filter. If the filterTemplate is not specified, then it is equivalent to "filterTemplate": "\${filterExpression}".</p>
"joinOperator"	An operator that is applied to join the logical expressions. Supported values are & and .
"multivalueJoinOperator"	An operator that is applied to join the logical expressions that are created for the multiple value URL parameters. Supported values are & and .
"comparisonOperator"	An operator that is applied for an attribute and its value comparison. Supported values are =, !=, ~, >=, <=, >, <.
"baseFilter"	<p>You can substitute attributes of the current Identity Service Center account or the owner of the account into the base search filter. These attributes are used when the filter is evaluated. The notation \${xxx} is used to specify where the substitution is made, and xxxx specifies what attribute value is to be substituted. The special string systemUser represents the user account of the current Identity Service Center user. You can qualify systemUser to specify an account attribute, such as \${systemUser.eruid}. You can also reference attributes of the owner of the account, such as \${systemUser.owner.cn}. Only attributes of the current account or the owner of the account can be used as substitutions into the base search filter. If a substitution cannot be evaluated or is evaluated to an empty string, a substitution value of <code>_undefined_</code> is used instead.</p> <p>For example,</p> <pre>"baseFilter": "(! (uid=\${systemUser.owner.uid}))"</pre>
"allowWildcard"	Specifies whether to use * as wildcard in the final filter expression or escape it. Supported values are true and false .

Rules that apply to populate the filterTemplate

- If a parameter in the template is not supplied as URL query parameter in the HTTP request, it is removed from the expression. For example,

The filterTemplate is "(&(cn=xyz)(sn=\${sn}))" and the request URL is "/rest/people"

The resultant expression is (cn=xyz).

- String `filterExpression` in the `filterTemplate` is replaced by the filter expression that is created by using the filter configuration and URL parameters that are not provided in the filter template. For example,

The `filterTemplate` is `"(&(cn=xyz)(sn=${sn})${filterExpression})"` and the request URL is `"/rest/people?sn=abc&email=pqr@site.com"`

The resultant expression is `(&(cn=xyz)(sn=abc)(email=pqr@site.com))`. In this example, `sn`, `email` are two URL query parameters but `email` is used to create `filterExpression` because `sn` is already used in the template.

Conditions in the `filterExpression` for `joinOperator`, `multivalueJoinOperator`, `comparisonOperator`, `allowWildcard`

- If a URL parameter contains multiple values, then the template expression for that parameter is constructed by using `multivalueJoinOperator`.

The `filterTemplate` is `"(&(cn=pqr)(sn=${sn}))"` and the request url is `"/rest/people?sn=abc&sn=xyz"` and the `multivalueJoinOperator` is `|`

The resultant expression is `(&(cn=pqr)(|(sn=abc)(sn=xyz)))`.

- If a URL parameter contains single value, then that value is placed in the template.

The `filterTemplate` is `"(&(cn=abc)(sn=${sn}))"` and the request url is `"/rest/people?sn=xyz"`

The resultant expression is `(&(cn=abc)(sn=xyz))`.

Examples

Example 1 - Person search without using the filter identifier

The `PERSON_SEARCH` is the REST service endpoint key for the person search capability. You must set a value for the `PERSON_SEARCH` that you can use as a filter identifier for person search capability when you create a request URL. You might not know the REST service endpoint keys for all the supported functions. You can use the dictionary service to know about all the supported REST service endpoint keys. Access <http://hostname:port/itim/rest/dictionary> to find the REST service endpoint keys.

You want to search for a person. Example 1 explains how to use the REST service, without providing any explicit filter identifier. Complete the following steps:

1. Set the value for the `PERSON_SEARCH` in the `isim/data/rest.propertiesrest.properties` file. For example, `PERSON_SEARCH=customPersonSearch`.
2. Define the `customPersonSearch` filter in the `custom/rest/searchfilter.json` file. For example,

```
"customPersonSearch": {
  "joinOperator": "&",
  "multivalueJoinOperator": "|",
  "comparisonOperator": "=",
  "baseFilter": "(! (uid=${systemUser.owner.uid}))",
  "allowWildcard": "false"
}
```

If the request URL is:

```
/itim/rest/people?cn=abc&sn=pqr&sn=xyz*
```

and you log in as a user `user1`

Then, the filter expression is:

```
(&(&(cn=abc)(|(sn=pqr)(sn=xyz\2a)))(!(uid=user1)))
```

Example 2 - Request search by using the filter identifier

You want to search for the requests. Example 2 explains how to use the REST service with the filter identifier. Complete the following steps.

1. Assume that the filter identifier `requestSearch` is already defined for the request search REST service endpoint key.
2. Define the `requestSearch` filter in the `custom/rest/searchfilter.json` file. For example,

```
"requestSearch": {
  "filterTemplate":
    "(&(&(date>=${fromDate})(date<=${toDate}))${filterExpression})",
  "comparisonOperator": "=",
  "joinOperator": "|",
  "multivalueJoinOperator": "|",
  "allowWildcard": "true"
}
```

If the request URL is:

```
/itim/rest/requests/quicksearches?filterId=requestSearch&fromDate=1425061800000
&toDate=1427826513600&accessName=*finance*&justification=*payroll*&limit=5
```

Then, the filter expression is:

```
(&(&(date>=1425061800000)(date<=1427826513600))(|(justification=*payroll*)
(accessName=*finance*)))
```


Chapter 8. Dynamic tags in mail templates

IBM Security Identity Manager mail templates allow dynamic retrieval, substitution, and decision making in creating a message.

Dynamic content tags and examples

Security Identity Manager provides dynamic content tags to allow text substitution and enable translation. The tags are used for the emails that are generated by these tasks:

- Designing workflows
- Specifying mail activity
- Manual service notification
- Recertification notification
- Post office
- Reminder template
- Default system notifications
- Delegation notifications

These tags are associated with dynamic content:

JavaScript code

Handles JavaScript and runs the JavaScript content that is contained between the open and close tags. This tag contains child tags unless they return a string. JavaScript code is called in `<JS>MyJavaScriptCode</JS>` delimiters.

Syntax	Example
<code><JS>text or JavaScript tag</JS></code>	Enter each <code><JS></JS></code> statement as a single line: <pre>An account request has been initiated for <JS>process.requesteeName;</JS> <JS>if (var x=process.getParent() !=null) return x </JS></pre>
<code><JS escapeentities="false">text or JavaScript tag</JS></code>	When specified as "false", any text that is returned by the JavaScript execution does not have its HTML entity tags escaped. For instance, the <code><</code> character does not return as <code>&lt;</code> ; . This option might be useful when the execution of the JavaScript code returns XML. For example, embedding XHTML body notifications inside the XHTML body of the post office template. The default for this attribute is "true", so not specifying the tag escapes the characters.

Table 2. Syntax and example of using JavaScript code to replace message content. (continued)

Syntax	Example
<pre data-bbox="167 254 781 302"><JS removexhtmlheader="false">text or JavaScript tag</JS></pre>	<p data-bbox="907 243 1461 464">If <code>removexhtmlheader="true"</code> is in the JS tag, any text that is returned from the JavaScript does not have the DTD statement in the XHTML content. The text that is returned from the JavaScript has the DTD statement in the XHTML content when either of the following conditions exist:</p> <ul data-bbox="907 485 1344 554" style="list-style-type: none"> • <code>removexhtmlheader="false"</code> . • It is not placed in the JS tag. <p data-bbox="907 575 1453 663">The default value of this attribute is <code>false</code>. Not specifying the flag in the tag puts the DTD statement in the XHTML content.</p>

Replace tag

Formats the message that is represented by the key to allow string replacement. The formatted string can have zero or more parameters. Parameters can contain strings, activity IDs, or JavaScript. The string inside the key must exist in the `CustomLabels.properties` file. Strings are sourced from a `CustomLabels.properties` resource bundle file or from the `Labels.properties` file.

The key of the string replacement can be specified with the `key` attribute or by adding a **KEY** tag between **RE** tags. Specifying a key that uses both the attribute and tag at the same time results in an exception.

The tag has these parameters:

Key

Represents the resource bundle key for a **RE** tag. For example:

```
<RE key="key">
</RE>
```

PARAM

Represents the parameters for a **RE** tag. For example:

```
<RE key="key">
<PARAM>with plain text</PARAM>
</RE>
```

Table 3. Syntax and examples of using a RE tag to replace message content.	
Syntax	Example
<pre><RE key="message key"> <PARM>text or JavaScript tag</PARM> </RE></pre> <p>or enter each <KEY></KEY> statement as a single line:</p> <pre><RE><KEY>message key or JavaScript tag to return a key </KEY> <PARM>text or JavaScript tag</PARM> </RE></pre> <p>The KEY can be specified by either an attribute on the RE tag, or as a subelement of the RE tag by using the tag KEY.</p>	<pre><RE key="message key"> <PARM>with plain text</PARM> <PARM><JS>process.requesteeName; </JS></PARM></RE></pre> <p>Output:</p> <p>This is a formatted string replacement example with plain text and JavaScript code for requestee name John Smith.</p>
<p>To enable string replacement for translation, specify a custom label in a CustomLabels.properties file to overwrite a Labels.properties key.</p> <p>For example, the Labels.properties file contains this key/value pair.</p> <pre>readOnlyDateFormat=MMM dd, yy hh:mm:ss z</pre> <p>To override this format, add the same key to the CustomLabels.properties file.</p>	<pre><RE key="readOnlyDateFormat"> <PARM><JS>if (process.scheduled !=null) return process.scheduled.getTime(); else return "";</JS></PARM></RE></pre> <p>Output:</p> <p>Apr 18, 2005 05:20:52 EDT</p>

Non-compliant message tag

Represents a message that describes the noncompliant attributes of an account. For example:

```
<CAMessage/>
```

Dynamic content message tags

Tags are delimited in <TAG/> syntax, such as the following examples:

Table 4. Syntax and example of using tags to replace message content.	
Syntax	Example
<TagName/>	<pre><CAMessage/></pre> <p>Returns a string that describes the non-compliant attributes of an account.</p>
	<pre><ManualServiceAddAccount/></pre> <p>Returns a string that contains the text body for manual service email notification.</p>
	<pre><rfiActivityHasBeenSubmitted/></pre> <p>Returns a string that contains the text body of an RFI activity that was submitted in an account request workflow.</p>

ID tag

Represents the activity ID in the form: `Process.ActivityId`. For example:

```
<ID/>
```

ITIMURL tag

Based on group membership of the person. It represents the URL of the IBM Security Identity Manager Server. A forced URL can be applied by using the `forcedurl` attribute of the tag. This attribute contains constant values such as the value `console`, `enduser`, or `ISC`.

Syntax	Example
<code><ITIMURL/></code>	Based on group membership of the person. It represents the URL of the IBM Security Identity Manager Server.
<code><ITIMURL forcedurl="enduser"/></code>	Represents the URL of the graphical user interface on the IBM Security Identity Manager Server. If the <code>forcedurl</code> attribute is used, the URL is not generated based on the group membership of the person. These values are associated with this attribute: enduser The URL points at the self-service graphical user interface. console The URL points at the administrator graphical user interface. servicecenter The URL points at the service center graphical user interface.
<code><ITIMURL forcedurl="console"/></code>	
<code><ITIMURL forcedurl="servicecenter"/></code>	

Properties file values

To change templates, you can add the `key=value` statements in the `CustomLabels.properties` file or create your own properties and values.

Required escape characters and JavaScript

The following characters must be escaped by using the appropriate HTML entity form that has the format `&entity;`. This action ensures that the notification template XML is well-formed.

Escape character	Character
<code>&lt;</code>	Less Than (<)
<code>&gt;</code>	Greater Than (>)
<code>&quot;</code>	Quotation (")
<code>&apos;</code>	Apostrophe (')
<code>&amp;</code>	Ampersand (&)

For example, to use the following JavaScript

```
if (i<4) return "less than four";
```


the dynamic content tag is

```
<JS> if (i<4) return &quote;less than four&quote;;</JS>
```

Common formatting patterns in the XHTML body

Default messages are formatted with a common pattern in the XHTML body and also contain message-unique statements.

For example, the XHTML for the to-do reminder template calls a common style sheet (the `imperatives.css` file) and logos. Message-unique statements are similar to the following ones:

```
<!-- Start of notification body -->
      <textBody/>
      <RE key="escalation_note"/> <escalationTime/>
    </td>
  </tr>
<!-- End of notification body -->
```

The following example shows a complete set of statements in an XHTML body:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE html
  PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
  "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
<head>
<title>${TITLE}</title>
<meta content="text/html; charset=UTF-8" http-equiv="Content-Type" />
<link type="text/css" title="Styles" rel="stylesheet"
  href="`${BASE_URL}/console/css/imperative.css" />
</head>

<!-- Put Next statement on one line -->

<body topmargin="0" marginheight="0" leftmargin="0" marginwidth="0"
  bgcolor="ffffff">

<!-- Block for the Template Header part -->
<table width="100%" border="0" cellpadding="0" cellspacing="0">
  <tbody>
    <tr>
      <!-- Security logo -->
      <td width="186" background="`${BASE_URL}/console/html/images/mid-part-1.gif">
        </td>
      <!-- Middle part -->
      <td background="`${BASE_URL}/console/html/images/mid-part-1.gif" width="692"></td>
      <!-- IBM logo -->
      <td background="`${BASE_URL}/console/html/images/ibm_banner.gif" width="96"></td>
    </tr>
  </tbody>
</table>

<!-- Title Bar -->
<table width="100%" border="0" cellpadding="0" cellspacing="0">
  <tbody>
    <tr>
      <td background="`${BASE_URL}/console/html/images/titlebar_middle.gif"
        height="23" width="8">
        </td>
      <!-- ISIM Notification Lable -->
      <td background="`${BASE_URL}/console/html/images/titlebar_middle.gif"
        height="23" classpath="portfolio-header" width="979">${TITLE}</td>
      <td background="`${BASE_URL}/console/html/images/titlebar_middle.gif"
        height="23" width="5"></td>
    </tr>
  </tbody>
</table>

<table width="100%" border="0" cellpadding="0" cellspacing="0">
  <tbody>
    <tr>
```

```

<!-- Background for the template body -->
<td background="$BASE_URL/console/html/images/portfolio_background.gif"
height="148">
<table border="0" cellspacing="0" cellpadding="0" width="100%">
  <tr>
    <td align="left" class="text-description" height="65">
      <!-- Start of notification body -->
      <textBody/>
      <RE key="escalation_note"/> <escalationTime/>
    </td>
  </tr>
</table>
</td>
</tr>
</tbody>
</table>
<!-- Copy Right Table -->
<table width="100%" border="0" cellpadding="0" cellspacing="0">
  <tbody>
    <tr bgcolor="#9d9d9d" align="center" valign="middle">
      <td class="text-description"><span class="cont1" id="W57ea57ea"><span
class="txt" id="text">IBM Copyright 2007</span></span></td>
    </tr>
  </tbody>
</table>
</body>
</html>

```

Mail templates

You define mail templates to deliver customized message notifications. The templates use several customization functions.

Templates have these main parts:

Subject

Describes an activity to a recipient of the notification. The subject can consist of plain text and dynamic content tags. If no subject is specified for manual service activities, no email is sent.

Text body

Describes the outcome of an activity, such as an account approval. The content can consist of plain text, dynamic content tags, and JavaScript code.

XHTML body

Provides the content of the email as an HTML message.

Dynamic content can include dynamic content message tags, JavaScript code, and tags that replace variables with other values or reference a property that allows translation with the `CustomLabels.properties` file.

Manual service default messages

IBM Security Identity Manager provides default notification templates for messages that participants that are service owners receive when changes occur to accounts or passwords for manual services that they own.

Default notification templates

IBM Security Identity Manager provides these default notification templates:

<ManualServiceAddAccount/>

Provides default text sent to a participant when an account is added for the user of a manual service.

<ManualServiceModifyAccount/>

Provides default text sent to a participant when an account is modified for the user of a manual service.

<ManualServiceDeleteAccount/>

Provides default text sent to a participant when an account is deleted for the user of a manual service.

<ManualServiceRestoreAccount/>

Provides default text sent to a participant when an account is restored for the user of a manual service.

<ManualServiceSuspendAccount/>

Provides default text sent to a participant when an account is suspended for the user of a manual service.

<ManualServiceChangePassword/>

Provides default text sent to a participant when a password change occurs for the user of a manual service.

Properties used for translation

If the properties exist in the CustomLabels.properties file, their value is used. Otherwise, the values of the properties in Labels.properties file are used. These properties contain the translated versions of the messages (with parameter substitution) that make up the dynamic tags. Change their values in the CustomLabels.properties file if you want different text. Do not change the defaults in the Labels.properties file.

The properties include these items:

```
manualServiceWorkOrderAddOperationMessage
manualServiceAttributeName
manualServiceAttributeValue
manualServiceAttributeAction
manualServiceAddAction
manualServiceRemoveAction
manualServiceReplaceAction
manualServiceWorkOrderChangePwdOperationMessage
manualServiceWorkOrderPwdValueMessage
manualServiceWorkOrderDeleteOperationMessage
manualServiceWorkOrderModifyOperationMessage
manualServiceWorkOrderRestoreOperationMessage
manualServiceWorkOrderSuspendOperationMessage
manualServiceUnknownPerson
```

Notification script example

A default notification script for a manual service provides a message that is sent to a participant. For example, the ManualServiceAddAccount notification output is similar to this example:

```
Attribute Name: Attribute Value
myattr: TT
Password: secret
Owner: Auditor
User ID: auditor1

Description: manual service operation
Requestee: Auditor
Subject: auditor1
Request Initiated: Jun 28, 2007 05:11:05 IST

Requested by process:
Process Name: Account Add
Description: Account Add Process
Requester: System Administrator
Requestee: Auditor
Subject: auditor1
```

Output example

The `<ManualServiceAddAccount/>` template provides a message that uses some of the values in the `Labels.properties` file:

```
manualServiceWorkOrderAddOperationMessage
manualServiceAttributeName : manualServiceAttributeValue
{insert real attribute names here} : {insert real attribute values here}
```

The `<ManualServiceModifyAccount/>` tag generates:

```
manualServiceWorkOrderModifyOperationMessage
{Place the following attributes on one line:}
manualServiceAttributeName : manualServiceAttributeValue
  : manualServiceAttributeAction
{insert real attribute names here} : {insert real attribute values here} :
{depending on what needs to be done, one of the following: }
{Place the following attributes on one line:}
{manualServiceAddAction,manualServiceReplaceAction,
  manualServiceRemoveAction}
```

Recertification default messages

IBM Security Identity Manager provides default message templates for recertification messages.

Default recertification templates

IBM Security Identity Manager provides default message templates for recertification messages. You cannot change the following templates:

Suspend Account

Provides default text that requests a participant to recertify use of an account. Declining the request suspends the account.

For example, the participant receives this message:

```
Recertification required for account myaccount on service shortword-linux

You have received a recertificaton request for account myaccount on service
shortword-linux owned by firstname lastname.

Rejection of this recertification request will result in the suspension of
account myaccount on shortword-linux.

Activity:Recertification of Account/Access
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:Recertification
Requested for:firstname lastname
Requested by:SYSTEM
Access/Account:myaccount
Description:

Due date:Apr 27, 2007 10:34:57 IST
```

Delete Account

Provides default text that requests a participant to recertify use of an account. Declining the request deletes the account.

For example, the participant receives this message:

```
Recertification required for account myaccount on service shortword-linux

You have received a recertificaton request for account myaccount
on service shortword-linux owned by firstname lastname.

Rejection of this recertification request will result in the deletion
of account myaccount on shortword-linux.

Activity:Recertification of Account/Access
Date submitted:Apr 26, 2007 10:34:51 IST
```

```
Request type:Recertification
Requested for:firstname lastname
Requested by:SYSTEM
Access/Account:myaccount
Description:
Due date:Apr 27, 2007 10:34:57 IST
```

Mark Account

Provides default text that is sent to a participant to recertify use of an account. Declining the request marks the account for a subsequent action on the account.

For example, the participant receives this message:

```
Recertification required for account myaccount on
service shortword-linux.

You have received a recertificaton request for account myaccount on service
shortword-linux owned by firstname lastname.

Rejection of this recertification request will result in
account myaccount on shortword-linux being marked as rejected
for recertification.

Activity:Recertification of Account/Access
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:Recertification
Requested for:firstname lastname
Requested by:SYSTEM
Access/Account:myaccount
Description:
Due date:Apr 27, 2007 10:34:57 IST
```

Mark Access

Provides default text that is sent to a participant to recertify use of an account on an access. Declining the request marks the access for a subsequent action on the account.

For example, the participant receives this message:

```
Recertification required for account myaccount on access myaccess.

You have received a recertificaton request for account myaccount on
access myaccess owned by firstname lastname.

Rejection of this recertification request will result in
access myaccess being marked as rejected for recertification.

Activity:
Date submitted:Apr 26, 2007 10:34:51 IST    /* Need to fill this data */
Request type:
Requested for:
Requested by:
Access/Account:
Description:
Due date:Apr 27, 2007 10:34:57 IST
```

Delete Access

Provides default text that requests a participant to recertify use of an account on an access. Declining the request deletes the account on the access.

For example, the participant receives this message:

```
Recertification required for account myaccount on access myaccess.

You have received a recertificaton request for account myaccount on
access myaccess owned by firstname lastname.

Rejection of this recertification request will result in the deletion
of access myaccess.

Activity:
Date submitted:Apr 26, 2007 10:34:51 IST    /* Need to fill this data */
Request type:
Requested for:
Requested by:
Access/Account:
```

Description:
Due date:Apr 27, 2007 10:34:57 IST

Account Suspended

Provides default text that is sent to a participant, confirming suspension of an account, after a participant declines a recertification request.

For example, the participant receives this message:

```
Account myaccount on service shortword-linux has been suspended due
to rejection of a recertification request

The account myaccount on service shortword-linux owned by
firstname lastname has been suspended due to rejection of
a recertification request.

Activity:Recertification of Account/Access
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:Recertification
Requested for:firstname lastname
Requested by:SYSTEM
Access/Account:myaccount
Description:
```

Account Deleted

Provides default text that is sent to a participant, confirming deletion of an account, after a participant declines a recertification request.

For example, the participant receives this message:

```
Account myaccount on service shortword-linux has been deleted due to
rejection of a recertification request

The account myaccount on service shortword-linux owned by
firstname lastname has been deleted due to rejection
of a recertification request.

Activity:Recertification of Account/Access
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:Recertification
Requested for:firstname lastname
Requested by:SYSTEM
Access/Account:myaccount
Description:
Due date:Apr 27, 2007 10:34:57 IST
```

Account Marked

Provides default text that is sent to a participant, confirming that an account is marked for suspension, after a participant declines a recertification request.

For example, the participant receives this message:

```
Account myaccount on service shrotword-linux has been marked as rejected
for recertification due to rejection of a recertification request

The account myaccount on service shortword-linux owned by
firstname lastname has been marked as rejected for recertification
due to rejection of a recertification request.

Activity:Recertification of Account/Access
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:Recertification
Requested for:firstname lastname
Requested by:SYSTEM
Access/Account:myaccount
Description:
Due date:Apr 27, 2007 10:34:57 IS
```

Access Marked

Provides default text that is sent to a participant. It confirms that an account on an access is marked for subsequent action after a participant declines a recertification request.

The template contains these statements:

```
Account myaccount on access myaccess has been deleted
due to rejection of a recertification request.

The account myaccount on access myaccess owned by firstname lastname
has been marked as rejected for recertification due to rejection of
a recertification request.

Activity:
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:
Requested for:
Requested by:
Access/Account:
Description:
Due date:Apr 27, 2007 10:34:57 IST
```

Access Removed

Provides default text that is sent to a participant, confirming deletion of an account on an access, after a participant declines a recertification request.

For example, the participant receives this message:

```
Account myaccount on access myaccess has been deleted due to
rejection of a recertification request.

The account myaccount on access myaccess owned by firstname
lastname has been deleted due to rejection of a recertification request.

Activity:
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:
Requested for:
Requested by:
Access/Account:
Description:
Due date:Apr 27, 2007 10:34:57 IST
```

User Recertification Pending

Provides default text that is sent to a participant, confirming that a user recertification is pending, after a recertification request is initiated.

For example, the participant receives this message:

```
You have received a recertification request for user firstname lastname.
The recertification includes their membership in X role(s) and ownership
of Y account(s). Please indicate whether the user still requires these
resources:

The account myaccount on access myaccess owned by firstname
lastname has been deleted due to rejection of a recertification request.

Activity: Recertification of Account/Access/User
Date submitted: Sep 08, 2008 04:10:32 EDT
Request type: Recertification
Requested for: firstname lastname
Requested by: System
Due date: Sep 18, 2008 04:10:34 EDT
```

User Recertification Rejected

Provides default text that is sent to a participant, confirming that one or more resources were declined in a user recertification request.

For example, the participant receives this message:

```
One or more resources for user firstname lastname have been rejected
during recertification.

The account myaccount on access myaccess owned by firstname
lastname has been deleted due to rejection of a recertification request.

Activity: Recertification of Account/Access/User
Date submitted: Sep 08, 2008 06:30:07 EDT
Request type: Recertification
```

```
Requested for: firstname lastname
Requested by: System
```

```
The following roles were rejected:
rolename
```

```
The following accounts were rejected, along with all groups associated
with the accounts:
Account "uid" on service "servicename"
```

```
The following groups were rejected, but the account was accepted:
Group "groupname" for account "uid" on service "servicename"
```

Properties file values

To change templates, you can use all of the `key=value` statements in the `CustomLabels.properties` file, or create your own properties and values.

The properties include these items on one line:

```
recertOn={0} on {1}
recertTemplateSubject=Recertification required
    for account {0} on service {1}
recertTemplateAccessSubject=Recertification required
    for account {0} on access {1}
recertTemplateBody=You have received a recertificaton request
    for account {0} on service {1} owned by {2}.
recertTemplateAccessBody=You have received a recertificaton request
    for account {0} on access {1} owned by {2}.
recertDeclineSuspendBody=Rejection of this recertification request
    will result in the suspension of account {0} on {1}.
recertDeclineDeletesBody=Rejection of this recertification request
    will result in the deletion of account {0} on {1}.
recertDeclineMarksBody=Rejection of this recertification request
    will result in account {0} on {1} being marked as rejected for recertification.
recertDeclineDeletesAccessBody=Rejection of this recertification request
    will result in the deletion of access {0}.
recertDeclineMarksAccessBody=Rejection of this recertification request
    will result in access {0} being marked as rejected for recertification.
recertDeclinedAcctSuspendedSubj=Account {0} on service {1} has
    been suspended due to rejection of a recertification request
recertDeclinedAcctDeletedSubj=Account {0} on service {1} has
    been deleted due to rejection of a recertification request
recertDeclinedAcctMarkedSubj=Account {0} on service {1} has
    been marked as rejected for recertification due to rejection
    of a recertification request
recertDeclinedAccessDeletedSubj=Account {0} on access {1} has
    been deleted due to rejection of a recertification request
recertDeclinedAccessMarkedSubj=Account {0} on access {1} has
    been marked as rejected for recertification due to rejection
    of a recertification request
recertDeclinedAcctSuspendedBody=The account {0} on
    service {1} owned by {2} has been suspended due to rejection
    of a recertification request.
recertDeclinedAcctDeletedBody=The account {0} on service {1}
    owned by {2} has been deleted due to rejection of a recertification request.
recertDeclinedAcctMarkedBody=The account {0} on service {1}
    owned by {2} has been marked as rejected for recertification
    due to rejection of a recertification request.
recertDeclinedAccessDeletedBody=The account {0} on access {1}
    owned by {2} has been deleted due to rejection of a recertification request.
recertDeclinedAccessMarkedBody=The account {0} on access {1}
    owned by {2} has been marked as rejected for recertification
    due to rejection of a recertification request.
userRecertTemplateSubject=Recertification required for user {0}
userRecertTemplateBody=You have received a recertificaton request
    for user {0}. The recertification includes their membership in {1} role(s)
    and ownership of {2} account(s). Please indicate whether the user still
    requires these resources.
userRecertDeclinedSubj=Recertification request rejected for user {0}
userRecertDeclinedBody=One or more resources for user {0} have been
    rejected during recertification.
userRecertRolesRejectedLabel=The following roles were rejected:
userRecertAccountsRejectedLabel=The following accounts were rejected,
    along with all groups associated with the accounts:
userRecertGroupsRejectedLabel=The following groups were rejected,
    but the account was accepted:
```



```
userRecertAcctLabel=Account "{0}" on service "{1}"
userRecertGroupLabel=Group "{0}" for account "{1}" on service "{2}"
```

Recertification template key definitions

Recertification templates use the following key definitions:

```
name=Activity
timeScheduled=Date submitted
recertRequestType=Request type
recertRequestedFor=Requested for
recertRequestedBy=Requested by
recertAccountAccess=Access/Account
recertDueDate=Due date
recertRequestTypeName=Recertification
readOnlyDateFormat=MMM dd, yyyy hh:mm:ss z
```

Workflow default messages

IBM Security Identity Manager provides default workflow messages.

Default workflow templates

All the workflow notice templates can be customized. IBM Security Identity Manager provides these default workflow notice templates:

Activity Timeout Template

Provides information that the workflow activity is timed out and terminated. By default, this template is enabled.

For example, the template provides this message:

```
Workflow activity is being timed out and will be terminated
by the workflow system.
```

```
The following activity has timed out.The activity will be terminated
by the workflow system and the result set to Terminated.
```

```
Activity Information
```

```
View Changes: http://localhost:9090/itim/console
Activity ID: ADApproval
Activity: AD Account Approval
Time Started: Jun 09, 2007 12:28:45 IST
Time Completed:
Result Summary: Escalated
State: Running
Activity Type: Manual Approval/Reject
```

```
Process Information
```

```
Process ID: 1099575082113388748
Activity: Default AD Account Approval Workflow
Description:
State:Running
Date submitted: Jun 09, 2007 12:23:41 IST
Time Completed:
Result Summary:
Requester: 1099572462907357646
Requestee: firstname lastname
Subject:
Comment:
Detail:
```

The subject statement is:

```
<RE key="activity_timeout_subject" />
```

The plain text is:

```
<RE key="activity_timeout_message" />
<RE key="activity_timeout_detail" />
<RE key="activityInformation" />
<ITIMURL/>
<RE key="activityID"/>: <JS>activity.id;</JS>
<RE key="name"/>: <JS>activity.name;</JS>
<RE key="timeStarted"/>: <RE key="readOnlyDateFormat"><PARM>
  <JS>if (activity.started != null)
    return activity.started.getTime();
  else return '';</JS></PARM></RE>
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>
  <JS>if (activity.completed != null)
    return activity.completed.getTime();
  else return '';</JS></PARM></RE>
<RE key="resultSummary"/>: <RE><KEY>
  <JS>process.STATE_PREFIX + activity.resultSummary;
</JS></KEY></RE>
<RE key="state"/>: <RE><KEY><JS>process.STATE_PREFIX+activity.state;
</JS></KEY></RE>
<RE key="activityType"/>: <RE><KEY>
  <JS>activity.TYPE_PREFIX + activity.type;</JS>
</KEY></RE>
<RE><KEY><JS>activity.TYPE_PREFIX + activity.subtype;</JS></KEY></RE>
<RE key="processInformation" />
<RE key="processID"/>: <JS>process.id;</JS>
<RE key="name"/>: <RE><KEY><JS>process.name;</JS></KEY></RE>
<RE key="description"/>: <RE><KEY>
  <JS>process.description;</JS></KEY></RE>
<RE key="state"/>: <RE><KEY><JS>process.STATE_PREFIX + process.state;
</JS></KEY></RE>
<RE key="timeScheduled"/>: <RE key="readOnlyDateFormat"><PARM>
  <JS>if (process.scheduled != null) return process.scheduled.getTime();
  else return '';</JS></PARM></RE>
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>
  <JS>if (process.completed != null) return process.completed.getTime();
  else return '';</JS></PARM></RE>
<RE key="resultSummary"/>: <RE><KEY>
  <JS>process.STATE_PREFIX + process.resultSummary;
</JS></KEY></RE>
<RE key="requester"/>: <JS>process.requestorName;</JS>
<RE key="requestedFor"/>: <JS>process.requesteeName;</JS>
<RE key="subject"/>: <JS>process.subject;</JS>
<RE key="comment"/>: <JS>process.comment;</JS>
<RE key="detail"/>: <JS>process.resultDetail;</JS>
```

Change Account Template

Provides information that the workflow activity has modified account information. By default, this template is disabled.

For example, the template provides this message:

```
Modified Account Information from IBM Security Identity Manager
The following ITIM Service [ITIM] account has been modified:
View Changes: http://localhost:9090/itim/console
Process Reference: 875016861865594505
Account ID: myaccount
```

Owner Name: firstname lastname
Time Completed: Jun 08, 2007 09:52:24 IST

The subject statement is:

```
<RE key="change_account_subject"/>
```

The plain text is:

```
<RE key="account_changed"><PARM>
  <RE key="service_name_with_profile_name"><PARM>
    <JS>EmailContext.getAccountServiceName();</JS></PARM>
    <PARM><RE><KEY><JS>EmailContext.getAccountServiceProfileName();
    </JS></KEY></RE></PARM></RE></PARM></RE>
  <ITIMURL/>
  <RE key="processRef"/>: <JS>process.id;</JS>
  <JS>if (EmailContext.getTransactionId() != '0')
    { '<RE key="TRANSACTION_ID_LABEL"/>: ' +
  EmailContext.getTransactionId(); }
  </JS>
  <RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>
  <RE key="accountOwnerName"/>: <JS>EmailContext.getAccountOwnerName();</JS>
  <RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>
    <JS>(new Date()).getTime();</JS></PARM></RE>
  <JS>if (EmailContext.hasNewAccess()) { '<RE key="accountNewAccess"/>:
    <JS>EmailContext.getAccountNewAccessAsString();</JS>\n'; }</JS>
  <JS>if (EmailContext.hasRemovedAccess()) { '<RE
  key="accountRemovedAccess"/>:
    <JS>EmailContext.getAccountRemovedAccessAsString();</JS>\n'; }</JS>
  <JS>if (EmailContext.getTransactionId() != '0')
    { '<RE key="RETRIEVE_PASSWORD_TITLE"/>: ' +
    EmailContext.getPasswordRetrievalUrl(); }
  </JS>
  <JS>if (EmailContext.getTransactionId() != '0')
    { '<RE key="passwordExpireLabel"/>:
  <JS>if (EmailContext.getPasswordExpirePeriod() == 0)
    { '<RE key="passwordneverexpire"/>'; }
    else { EmailContext.getPasswordExpirePeriod(); }</JS>'; }</JS>
  <JS>if (EmailContext.getTransactionId() != '0')
    { '<JS>if (EmailContext.getPasswordExpirePeriod() == 0)
    { '<RE key="additionalMsgForPwdRetrieval"/>'; }</JS>'; }</JS>
```

Compliance Template

Provides information that an account is not compliant with a provisioning policy. By default, this template is enabled.

For example, the template provides this message:

```
Compliance Alert for winlocal
Account [helpdesk35] is not compliant with the provisioning policy.
The value [Performance Log Users] of attribute [Local Groups]
should be [removed].
View Changes: http://99.99.999.99:80/itim/console
```

The subject statement is:

```
<RE key="compliance_alert_subject" >
  <PARM><JS>var service = context.getService();
  return service.getProperty("erservicename")[0];</JS>
</PARM>
</RE>
```

The plain text is:

```
<CAMessage/>
<RE key="itimUrl"/>:<ITIMURL/>
```

Delegation Template

Provides the default template for delegation, which includes the new delegation information. By default, this template is enabled and cannot be disabled. If any exception is thrown while evaluating JavaScript in the notification template or parsing the notification template, then the default delegation notification is sent.

For example, the template provides this message:

```
You have been selected to be the delegate:

For: John Doe

From: Tue Jul 03 08:00:13 IST 2012

To: Fri Jul 06 20:00:13 IST 2012

The subject statement is:
<RE key="delegationMailSubject"/>

The plain text is:
<RE key="delegationMailContent"/>

<RE key="delegationMailDelegator"/>:<JS>Delegate.getDelegator().name;</JS>

<RE key="delegationMailFrom"/>:<JS>Delegate.getStartDate();</JS>

<RE key="delegationMailTo"/>:<JS>Delegate.getEndDate();</JS>
```

Deprovision Account Template

Provides information that the workflow activity has removed an account. By default, this template is enabled.

For example, the template provides this message:

```
Your account has been removed by IBM Security Identity Manager.

The following Odessa Service [ADProfile] account has been deprovisioned.

View Changes: http://host:9080/itim/self
Process Reference: 5870349043636872731
Account ID: myaccount
Owner Name: myname
Reason: Policy Enforcement
Time completed: May 03, 2007 03:54:22 IST
```

The subject statement is:

```
<RE key="remove_account_subject" />
```

The plain text is:

```
<RE key="account_deprovisioned">
  <PARAM><RE key="service_name_with_profile_name">
    <PARAM><JS>EmailContext.getAccountServiceName();</JS></PARAM>
    <PARAM><RE><KEY><JS>EmailContext.getAccountServiceProfileName();
    </JS></KEY></RE></PARAM></RE></PARAM></RE>
  <ITIMURL/>
  <RE key="processRef"/>: <JS>process.id;</JS>
  <RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>
  <RE key="accountOwnerName"/>: <JS>EmailContext.getAccountOwnerName();</JS>
  <RE key="reason"/>: <JS>EmailContext.getReason();</JS>
  <RE key="deprovisionCompleted"/>: <RE key="readOnlyDateFormat">
    <PARAM><JS>(new Date()).getTime();</JS></PARAM></RE>
```

Manual Activity Approval Template

Provides information that the user should provide information for a request. By default, this template is enabled.

For example, the template provides this message:

```
Pending workflow action: Case 884088984804067042.884090864796694775

You have been requested to submit information for the following request

View Changes: http://localhost:9090/itim/console
Description:
Requestee: firstname lastname
Subject: subject
Request Initiated: Jun 08, 2007 10:27:29 IST
Process Reference: 884088984804067042

Requested by process:
Process ID: 884066904196868932
Process Name: Provision Account
Description: Provisioning Account Process
Requester: System Administrator
Requestee: firstname lastname
Subject: subject
```

The subject statement is:

```
<RE key="pending_workitem_subject"><PARAM><ID /></PARAM></RE>
```

The plain text is:

```
<RE key="wiApproval_message" />
<ITIMURL/>
<RE key="description"/>: <RE><KEY><JS>process.description;</JS></KEY></RE>
<RE key="requestedFor"/>: <JS>process.requesteeName;</JS>
<RE key="subject"/>: <JS>process.subject;</JS>
<JS>if (process.subjectAccess!=null) if (process.subjectAccess.length>0)
  { '<RE key="accessName"/>: <JS>process.subjectAccess;</JS>\n'; }</JS>
<RE key="requestInit"/>: <RE key="readOnlyDateFormat"><PARAM>
<JS>if (process.started != null) return process.started.getTime();
else return '';</JS></PARAM></RE>
<RE key="processRef"/>: <JS>process.id;</JS>
<JS>if (process.parentId == '0') { '<RE key="requestedBy"/>:
  <JS>process.requestorName;</JS>'; }</JS>

<JS>if (process.parentId != '0') { '<RE key="parent_process"/>'; }</JS>
  <JS>if (process.parentId != '0')
    { '<RE key="processID"/>: ' + process.parentId; }</JS>
  <JS>if (process.parentId != '0') { '<RE key="processName"/>:
    <RE><KEY><JS>if (process.parentId != '0')
  { process.getParent().name; }
  </JS></KEY></RE>'; }</JS>
  <JS>if (process.parentId != '0') { '<RE key="description"/>:
    <RE><KEY><JS>if (process.parentId != '0')
  { process.getParent().description; } </JS></KEY></RE>'; }</JS>
  <JS>if (process.parentId != '0')
    { '<RE key="requester"/>: ' + process.getParent().requestorName; }
  </JS>
  <JS>if (process.parentId != '0')
    { '<RE key="requestedFor"/>: ' +
process.getParent().requesteeName; }
  </JS>
  <JS>if (process.parentId != '0')
    { '<RE key="subject"/>: ' + process.getParent().subject; }</JS>
```

Manual Activity RFI Template

Provides the default template for request for information workflow activities. By default, this template is enabled

For example, the template provides this message:

```
You have been requested to submit information for the following request
http://localhost:9080/itim/self/ReviewActivities.do?
```

```
activity=3053543743245419023
Description:
Requestee: Shoe Flower
Subject: shoe1
Request Initiated: Aug 03, 2007 11:48:52 IST
Process Reference: 3053543339468639238
```

```
Requested by process:
Process ID: 3053541330639294422
Process Name: Provision Account
Description: Provision Account Process
Requester: System Administrator
Requestee: Shoe Flower
Subject: shoe1
```

The subject statement is:

```
<RE key="pending_workitem_subject"><PARM><ID /></PARM></RE>
```

The plain text is:

```
<RE key="wiRFI_message" />
<ITIMURL/>
<RE key="description"/>: <RE><KEY>
  <JS>process.description;</JS></KEY></RE>
<RE key="requestedFor"/>: <JS>process.requesteeName;</JS>
<RE key="subject"/>: <JS>process.subject;</JS>
<JS>if (process.subjectAccess!=null)
  if (process.subjectAccess.length>0)
    { '<RE key="accessName"/>:
      <JS>process.subjectAccess;</JS>\n'; }</JS>
  <RE key="requestInit"/>: <RE key="readOnlyDateFormat"><PARM>
    <JS>if (process.started != null) return process.started.getTime();
    else return '';</JS></PARM></RE>
  <RE key="processRef"/>: <JS>process.id;</JS>
  <JS>if (process.parentId == '0') { '<RE key="requestedBy"/>:
    <JS>process.requestorName;</JS>'; }</JS>

  <JS>if (process.parentId != '0') { '<RE key="parent_process"/>'; }
  </JS>
  <JS>if (process.parentId != '0')
    { '<RE key="processID"/>: ' + process.parentId; }</JS>
  <JS>if (process.parentId != '0') { '<RE key="processName"/>:
    <RE><KEY><JS>if (process.parentId != '0')
      { process.getParent().name; }
    </JS></KEY></RE>'; }</JS>
  <JS>if (process.parentId != '0') { '<RE key="description"/>:
    <RE><KEY><JS>if (process.parentId != '0')
      { process.getParent().description; }
    </JS></KEY></RE>'; }</JS>
  <JS>if (process.parentId != '0')
    { '<RE key="requester"/>: ' + process.getParent().requestorName; }
  </JS>
  <JS>if (process.parentId != '0')
    { '<RE key="requestedFor"/>: ' +
    process.getParent().requesteeName; }
  </JS>
  <JS>if (process.parentId != '0')
    { '<RE key="subject"/>: ' + process.getParent().subject; }</JS>
```

Manual Activity Work Order Template

Provides default template for the work order workflow manual activity. By default, this template is enabled.

For example, the template provides this message:

```
Pending workflow action:
Case 1401993364658803275.1402011582339065124
```

You have received a Work Order request

The subject statement is:

```
<RE key="pending_workitem_subject"><PARM><ID /></PARM></RE>
```

The plain text is:

```
<RE key="wiWorkOrder_message" />
```

New Account Template

Provides information that the workflow activity has created a new account. By default, this template is enabled.

For example, the template provides this message:

```
New Account Information from IBM Security Identity Manager
The following new ITIM Service [ITIM] account has been created for you:

View Changes: http://localhost:80/itim/console
Process Reference: 8498649245880216244
Password: bAMI#gai
Account ID: myaccount
Owner Name: firstname lastname
Time of service provision: Jun 29, 2007 10:55:58 IST
```

The subject statement is:

```
<RE key="new_account_subject"/>
```

The plain text is:

```
<RE key="account_created"><PARM>
  <RE key="service_name_with_profile_name">
    <PARM><JS>EmailContext.getAccountServiceName();</JS></PARM>
  <PARM><RE><KEY><JS>EmailContext.getAccountServiceProfileName();
  </JS></KEY></RE></PARM></RE></PARM></RE>
<ITIMURL/>
<RE key="processRef"/>: <JS>process.id;</JS>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="TRANSACTION_ID_LABEL"/>: '
  + EmailContext.getTransactionId(); } </JS>
<RE key="password"/>: <JS>EmailContext.getAccountPassword();</JS>
<RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>
<RE key="accountOwnerName"/>:
  <JS>EmailContext.getAccountOwnerName();</JS>
<RE key="timeofprovision"/>: <RE key="readOnlyDateFormat">
  <PARM><JS>(new Date()).getTime();</JS></PARM></RE>
<JS>if (EmailContext.hasNewAccess()) { '<RE key="accountNewAccess"/>:
  <JS>EmailContext.getAccountNewAccessAsString();</JS>\n'; }</JS>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="RETRIEVE_PASSWORD_TITLE"/>: '
  + EmailContext.getPasswordRetrievalUrl(); }</JS>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="passwordExpireLabel"/>:
  <JS>if (EmailContext.getPasswordExpirePeriod() == 0)
  { '<RE key="passwordneverexpire"/>'; }
  else { EmailContext.getPasswordExpirePeriod(); }</JS>'; }</JS>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<JS>if (EmailContext.getPasswordExpirePeriod() == 0)
  { '<RE key="additionalMsgForPwdRetrieval"/>'; }</JS>'; }</JS>
```

New Password Template

Provides information that there is a new password for an account. By default, this template is enabled.

For example, the template provides this message:

```
Account new password information

The following is your new password for account myaccount:

View Changes: http://localhost:9090/itim/console
Process Reference: 2855285841498421007
New Password: secret
Account ID: myaccount
Account Service: ITIM Service
Account Service Profile: ITIM
Owner Name: firstname lastname
Time of service provision: Apr 25, 2007 12:54:05 IST
```

The subject statement is:

```
<RE key="password_change_subject"/>
```

The plain text is:

```
<RE><KEY><JS>if (EmailContext.getTransactionId() == '0')
  { 'newAccountPassword' } else { 'newAccountPasswordPickUp'; }
</JS></KEY>
<PARAM><JS>process.subject;</JS></PARAM></RE>
<ITIMURL/>
<RE key="processRef"/>: <JS>process.id;</JS>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="TRANSACTION_ID_LABEL"/>: ' +
    EmailContext.getTransactionId(); }
</JS>
<RE key="newPassword"/>: <JS>EmailContext.getAccountPassword();</JS>
<RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>
<RE key="accountService"/>:
  <JS>EmailContext.getAccountServiceName();</JS>
<RE key="accountServiceProfile"/>: <RE><KEY>
  <JS>EmailContext.getAccountServiceProfileName();</JS></KEY></RE>
<RE key="accountOwnerName"/>:
  <JS>EmailContext.getAccountOwnerName();</JS>
<RE key="timeofprovision"/>: <RE key="readOnlyDateFormat">
  <PARAM><JS>(new Date()).getTime();</JS></PARAM></RE>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="RETRIEVE_PASSWORD_TITLE"/>: '
    + EmailContext.getPasswordRetrievalUrl(); }</JS>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="passwordExpireLabel"/>:
    <JS>if (EmailContext.getPasswordExpirePeriod() == 0)
      { '<RE key="passwordneverexpire"/>'; }
    else { EmailContext.getPasswordExpirePeriod(); }</JS>'; }</JS>

<JS>if (EmailContext.getTransactionId() != '0')
  { '<JS>if (EmailContext.getPasswordExpirePeriod() == 0)
    { '<RE key="additionalMsgForPwdRetrieval"/>'; }</JS>'; }</JS>
```

Process Completion Template

Provides information that the workflow activity has completed. By default, this template is enabled.

For example, the template provides this message when an activity is completed without being canceled:

```
A workflow process, 1416721862784240178, has completed.
Result Summary: Success
The following process has completed

Process Information

View Changes: http://localhost:9090/itim/console
Process ID: 1416721862784240178
Activity:
```


Description: Modify Provisioning Policy Process
State: Completed
Date submitted: May 16, 2007 12:22:58 IST
Time Completed: May 16, 2007 01:44:17 IST
Result Summary: Success
Requester: System Administrator
Requestee:
Subject: Default Provisioning Policy for service Win Local Profile
Comment:
Detail:

For example, the template provides this message when an activity is canceled:

Subject: A workflow process, 6690130336188564930, has completed.
Result Summary: Failed
The following process has completed

Process Information

View Changes: <http://localhost:80/itim/console>
Process ID: 6690130336188564930
Activity: Person Add
Description: Person Add Process
State: Canceled
Date submitted: Jan 30, 2014 01:13:59 CST
Time Completed: Jan 29, 2014 01:13:22 CST
Result Summary: Failed
Requester: System Administrator
Requestee: firstname lastname
Subject:
Comment:
Detail:
Canceled By: System Administrator
Date Canceled: Jan 29, 2014 01:13:22 CST
Canceled Justification: No longer needed

The subject statement is:

```
<RE key="processCompletedSubject"><PARM><JS>process.id;</JS></PARM>  
<PARM><RE key="resultSummaryValue"><PARM><RE><KEY>  
<JS>process.STATE_PREFIX + process.resultSummary;  
</JS></KEY></RE></PARM></RE></PARM></RE>
```

The plain text is:

```
<RE key="process_completed_message" />  
  
<RE key="processInformation" />  
<ITIMURL/>  
<RE key="processID"/>: <JS>process.id;</JS>  
<RE key="name"/>: <RE><KEY><JS>process.name;</JS></KEY></RE>  
<RE key="description"/>: <RE><KEY><JS>process.description;</JS>  
</KEY></RE>  
<RE key="state"/>: <RE><KEY>  
<JS>process.STATE_PREFIX + process.state;</JS></KEY></RE>  
<RE key="timeScheduled"/>: <RE key="readOnlyDateFormat"><PARM>  
<JS>if (process.scheduled != null)  
return process.scheduled.getTime();  
else return '';</JS></PARM></RE>  
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>  
<JS>if (process.completed != null)  
return process.completed.getTime();  
else return '';</JS></PARM></RE>  
<RE key="resultSummary"/>: <RE><KEY>  
<JS>process.STATE_PREFIX + process.resultSummary;</JS>  
</KEY></RE>  
<RE key="requester"/>: <JS>process.requestorName;</JS>  
<RE key="requestedFor"/>: <JS>process.requesteeName;</JS>  
<RE key="subject"/>: <JS>process.subject;</JS>  
<RE key="comment"/>: <JS>process.comment;</JS>
```

```

    <RE key="detail"/>: <JS>process.resultDetail;</JS>
<JS>if (process.cancelor_name != null)
    { '<RE key="CanceledBy"/>: ' + process.cancelor_name; }</JS>
<JS>if (process.cancelor_name != null)
    { '<RE key="DateCanceled"/>: '; }</JS>
<RE key="readOnlyDateFormat"><PARM>
<JS>if (process.canceled_date != null) return process.canceled_date.getTime();
    else return '';</JS>
</PARM></RE>
<JS>if (process.cancelor_name != null) { '<RE key="CanceledReason"/>:
<JS>if (process.canceled_justification == null) { return ' '; }
    else { return process.canceled_justification;}
</JS>'; }</JS>

```

Process Timeout Template

Provides information that the workflow process has timed out. By default, this template is enabled.

For example, the template provides this message:

```

Workflow activity is being timed out and will be
    terminated by the workflow system

```

```

Activity Information
View Changes: http://localhost:9080/itim/console
Activity ID: RECERTAPPROVAL
Activity: $ITIM_RECERTIFY
Time Started: Aug 02, 2007 03:18:54 IST
Time Completed:
Result Summary: Pending
State: Running
Activity Type: Manual Approval/Reject

```

Process Information

```

Process ID: 8566433417513336819
Activity: Recertification of Account/Access
Description: Recertification of Account/Access
State: Running
Date submitted: Aug 02, 2007 03:18:54 IST
Time Completed:
Result Summary:
Requester: org
Requestee: Person B
Subject: personb
Comment:
Detail:

```

The subject statement is:

```
<RE key="process_timeout_subject" />
```

The plain text is:

```

<RE key="process_timeout_message" />

<RE key="processInformation" />
<ITIMURL/>
<RE key="processID"/>: <JS>process.id;</JS>
<RE key="name"/>: <RE><KEY><JS>process.name;</JS></KEY></RE>
<RE key="description"/>: <RE><KEY><JS>process.description;</JS></KEY></RE>
<RE key="state"/>: <RE><KEY>
    <JS>process.STATE_PREFIX + process.TIMEOUT;</JS></KEY></RE>
<RE key="timeScheduled"/>: <RE key="readOnlyDateFormat"><PARM>
    <JS>if (process.scheduled != null) return process.scheduled.getTime();
    else return '';</JS></PARM></RE>
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>
    <JS>if (process.completed != null) return process.completed.getTime();
    else return '';</JS></PARM></RE>
<RE key="resultSummary"/>: <RE><KEY>

```

```

    <JS>process.STATE_PREFIX + process.resultSummary;</JS></KEY></RE>
<RE key="requester"/>: <JS>process.requestorName;</JS>
<RE key="requestedFor"/>: <JS>process.requesteeName;</JS>
<RE key="subject"/>: <JS>process.subject;</JS>
<RE key="comment"/>: <JS>process.comment;</JS>

<RE key="detail"/>: <JS>process.resultDetail;</JS>

```

Restore Account Template

Provides information that an account has been restored. By default, this template is enabled.

For example, the template provides this message:

```

Restored Account Information from IBM Security Identity Manager

The following ITIM Service [ITIM] account has been restored:

View Changes: http://localhost:9090/itim/console
Process Reference: 2857890686820910405
New Password: secret
Account ID: myaccount
Owner Name: firstname lastname
Time Completed: Apr 25, 2007 01:04:08 IST

```

The subject statement is:

```
<RE key="restore_account_subject"/>
```

The plain text is:

```

<RE key="restore_account"><PARM>
<RE key="service_name_with_profile_name"><PARM>
<JS>EmailContext.getAccountServiceName();</JS></PARM>
<PARM><RE><KEY>
<JS>EmailContext.getAccountServiceProfileName();
</JS></KEY></RE></PARM></RE></PARM></RE>
<ITIMURL/>
<RE key="processRef"/>: <JS>process.id;</JS>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="TRANSACTION_ID_LABEL"/>: '
  + EmailContext.getTransactionId(); } </JS>
<RE key="newPassword"/>: <JS>EmailContext.getAccountPassword();</JS>
<RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>
<RE key="accountOwnerName"/>:
  <JS>EmailContext.getAccountOwnerName();</JS>
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat">
<PARM>
  <JS>(new Date()).getTime();</JS></PARM></RE>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="RETRIEVE_PASSWORD_TITLE"/>: '
  + EmailContext.getPasswordRetrievalUrl(); }</JS>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="passwordExpireLabel"/>: '
  + EmailContext.getPasswordExpirePeriod(); }</JS>'; }
<JS>if (EmailContext.getPasswordExpirePeriod() == 0)
  { '<RE key="passwordneverexpire"/>'; }
  else { EmailContext.getPasswordExpirePeriod(); }</JS>'; }
</JS>

<JS>if (EmailContext.getTransactionId() != '0')
  { '<JS>if (EmailContext.getPasswordExpirePeriod() == 0)
  { '<RE key="additionalMsgForPwdRetrieval"/>'; }</JS>'; }</JS>

```

Suspend Account Template

Provides information that an account is suspended. By default, this template is enabled.

For example, the template provides this message:

```
Your account has been suspended by IBM Security Identity Manager
```

The following AD Service (RFI) [ADProfile] account has been suspended:

View Changes: <http://localhost:9090/itim/console>
Process Reference: 2857497715286893521
Account ID: myaccount
Owner Name: firstname lastname
Time Completed: Apr 25, 2007 01:02:43 IST

The subject statement is:

```
<RE key="suspend_account_subject" />
```

The plain text is:

```
<RE key="account_suspended"><PARM>  
  <RE key="service_name_with_profile_name">  
    <PARM><JS>EmailContext.getAccountServiceName();</JS></PARM>  
    <PARM><RE><KEY><JS>EmailContext.getAccountServiceProfileName();  
  </JS></KEY></RE></PARM></RE></PARM></RE>  
<ITIMURL/>  
<RE key="processRef"/>: <JS>process.id;</JS>  
<RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>  
<RE key="accountOwnerName"/>:  
  <JS>EmailContext.getAccountOwnerName();</JS>  
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>  
  <JS>(new Date()).getTime();</JS></PARM></RE>
```

To-Do Reminder Template

Provides the default template for workflow reminders, which are email messages that remind users about pending activities to which they not responded. By default, this template is disabled.

For example, the template provides this message:

```
Subject: Pending workflow action:  
Case 6167063972298972180.6167064647650050990  
  
The following request has been submitted for your approval  
View Changes: http://localhost:9080/itim/console  
Description: ApprovalWorkflow  
Requestee: firstname lastname  
Subject: subject  
Request Initiated: Sep 05, 2007 05:42:18 IST  
Process Reference: 6167063972298972180  
  
Requested by process:  
Process ID: 6167052766519381908  
Process Name: Provision Account  
Description: Provision Account Process  
Requester: System Administrator  
Requestee: firstname lastname  
Subject: subject  
  
This WorkItem will be escalated on: Saturday, September 8, 2007.
```

The subject statement is:

```
<originalSubject/>
```

The plain text is:

```
<textBody/>  
<RE key="escalation_note"/> <escalationTime/>
```

Chapter 9. JavaScript extensions overview

JavaScript is used in IBM Security Identity Manager to specify identity policies, provisioning policy parameters, service selection policies, placement rules for identity feeds, and orphan account adoption.

In addition, JavaScript is used in workflows to specify transition conditions, loop conditions, JavaScript activities, activity postscripts, and workflow notification. Various scripting extensions are provided by IBM Security Identity Manager to expose useful data and services to each of these scripts. In addition to these extensions, system administrators can configure IBM Security Identity Manager to load custom JavaScript extensions. For more information about custom JavaScript extensions, see the *ISIM_HOME/data/scriptframework.properties* file.

IBM Security Identity Manager supports two Java Script interpreters: IBM JSEngine and Free EcmaScript Interpreter (FESI, now deprecated). Both of these interpreters support the third edition (December 1999) of the ECMA-262 specification.

Table 7 on page 55 lists the supported host components and script extensions.

Host Component	Supported Script Extension	Description
AccountTemplate	ProvisioningPolicyExtension	Extensions registered with this key are loaded by Account Default Template parameters.
	ServiceExtension	
	SubjectExtension	
Delegate	DelegateExtension	Extensions registered with this key are loaded by Delegation notifications.
	Model Extensions Package	
HostSelection	ServiceModelExtension	Extensions registered with this key are loaded by Service Selection Policies.
	SubjectExtension	
IdentityPolicy	IdentityPolicyExtension	Extensions registered with this key are loaded by Identity Policies.
	AttributesExtension	
	ServiceExtension	
	SubjectExtension	
OrphanAdoption	Model Extensions Package	Extensions registered with this key are loaded by adoption scripts.
	ServiceExtension	
	SubjectExtension	
PersonPlacementRules	PersonPlacementRulesExtension	Extensions registered with this key are loaded by placement rules during identity feeds.
	ServiceExtension	
	AttributesExtension	
PostOffice	PostOfficeExtension	Extensions registered with this key are loaded by Post Office templates.

<i>Table 7. Host components and script extensions (continued)</i>		
Host Component	Supported Script Extension	Description
ProvisioningPolicy	ProvisioningPolicyExtension	Extensions registered with this key are loaded by Provisioning Policy parameters.
	Model Extensions Package	
	ServiceExtension	
	SubjectExtension	
	AttributesExtension (deprecated)	
Reminder	ReminderExtension	Extensions registered with this key are loaded by email reminder templates.
	SubjectExtension	
Workflow	WorkflowExtension	Extensions registered with this key are loaded by workflow scripts that include Workflow TODO Notifications.
	Model Extensions Package	
	LoopCountExtension	
Workflow Notification	WorkflowExtension	The extensions loaded are hardcoded and all supported extensions are loaded.
	EmailContextExtension	
	PersonModelExtension	
TODO Notification (Approval/RFI/ComplianceAlert/WorkOrder)	WorkflowExtension	The extensions loaded are the same as Workflow.
	Model Extensions Package	
	LoopCountExtension	

Packaged extensions

The section describes the scripting extensions provided by IBM Security Identity Manager, the JavaScript objects they expose, and the scripts to which these extensions are applicable.

Do not remove these extensions from the properties file that you configure, because they are necessary for standard product operation. All of the extensions are configured for new installations.

AttributesExtension

The full extension name is `com.ibm.itim.script.extensions.AttributesExtension`.

This extension is responsible for making the ATTRIBUTES object available to scripts. ATTRIBUTES is a Map type object and is used internally to implement the deprecated `Enrole.getAttributeValue()` and `Enrole.getAttributeValues()` methods.

AttributesExtension and the ATTRIBUTES script object are deprecated. Do not use them in any new scripts.

Availability

```
IdentityPolicy
PersonPlacementRules
ProvisioningPolicy
```

JavaScript Objects

ATTRIBUTES

DelegateExtension

The full extension name is `com.ibm.itim.script.extensions.DelegateExtension`.

This extension is responsible for making the Delegate object available to delegation notification scripts.

Availability

Delegation Notification

JavaScript Objects

Delegate

EmailContextExtension

The full extension name is `com.ibm.itim.workflow.script.EmailContextExtension`.

The `EmailContextExtension` provides the `EmailContext` object that provides information about the workflow activity and process that is making the notification. `EmailContext` is of type `WorkflowRuntimeContext`, although it might be a more specific subtype, depending on what type of change triggered the notification.

Availability

Notification

JavaScript Objects

EmailContext

EnroleExtension

The full extension name is `com.ibm.itim.script.extensions.EnroleExtension`.

This extension is automatically loaded for all scripts. It is not in the `scriptframework.properties` file.

This extension exposes the `Enrole` object to scripts. This object provides the following miscellaneous functions:

- Converting to and from the generalized time format.
- Logging and tracing facilities to write to the Security Identity Manager logs.

Availability

All scripts

JavaScript Objects

Enrole
Error

IdentityPolicyExtension

The full extension name is `com.ibm.itim.policy.script.IdentityPolicyExtension`.

This extension exposes the `IdentityPolicy` object to identity policy scripts. This object provides a method to test for the existence of a user ID.

Availability

Identity Policy

JavaScript Objects

IdentityPolicy

LoopCountExtension

The full extension name is `com.ibm.itim.workflow.script.LoopCountExtension`.

This extension provides the `loopcount` script object. The object is an integer that tells a script how many times a loop ran.

Availability

Workflow

JavaScript Objects

`loopcount`

Model extensions package

The model extensions expose JavaScript objects that can be used to search for people, accounts, services, and organizational units such as organizations, business units, and locations.

Important: The objects exposed by these extensions allow access to identity and service data without regard to specified access control rules for these data. The objects are considered privileged. Define access control items that manage access to IBM Security Identity Manager scripts.

All of the model extensions have the same availability and can be used with the following extension points:

- `AccountTemplate`
- `ProvisioningPolicy`
- `HostSelection`
- `OrphanAdoption`
- `Workflow`
- `Notification`

AccountModelExtension

The full extension name is `com.ibm.itim.script.extensions.model.AccountModelExtension`.

This extension exposes the `Account` constructor and `AccountSearch` constructor to applicable scripts. After it is constructed, an `Account` object represents an Account Directory Object in scripts. The `AccountSearch` object provides methods to search for existing accounts based on several parameters, which include **uid**, **owner**, and **service**.

JavaScript Objects

- `AccountSearch`
- `Account`

CredentialModelExtension

The full extension name is `com.ibm.itim.script.extensions.model.CredentialModelExtension`.

This extension exposes the `Credential` constructor to applicable scripts when Shared Access Module is activated. When it is constructed, a `Credential` object represents a Credential Directory Object in scripts.

Note: You must install and enable the shared access module in order to use `com.ibm.itim.script.extensions.model.CredentialModelExtension`.

JavaScript Objects

`Credential`

PersonModelExtension

The full extension name is `com.ibm.itim.script.extensions.model.PersonModelExtension`.

This extension exposes the `Person` constructor, `PersonSearch` constructor, and `ExtendedPerson` constructor to applicable scripts. After it is constructed, a `Person` object represents a `Person Directory Object` in script. A `ExtendedPerson` object extends `Person` with ownership type information. The `PersonSearch` object provides methods to search for existing people based on a provided LDAP filter.

JavaScript Objects

- `PersonSearch`
- `Person`
- `ExtendedPerson`

OrganizationModelExtension

The full extension name is `com.ibm.itim.script.extensions.model.OrganizationModelExtension`.

This extension exposes the `ContainerSearch` constructor to applicable scripts. The `ContainerSearch` object provides methods to search of Organizational containers based on LDAP filters.

JavaScript Objects

`ContainerSearch`

RoleModelExtension

The full extension name is `com.ibm.itim.script.extensions.model.RoleModelExtension`.

This extension exposes the `Role` constructor and `RoleSearch` constructor to applicable scripts. After it is constructed, the `Role` object represents a `Role Directory Object` in scripts. The `RoleSearch` object provides a method to search for Roles based on role name.

JavaScript Objects

- `RoleSearch`
- `Role`

ServiceModelExtension

The full extension name is `com.ibm.itim.script.extensions.model.ServiceModelExtension`.

This extension exposes the `Service` constructor and `ServiceSearch` constructor to applicable scripts. After it is constructed the `Service` object represents a `Service Directory Object` in scripts. The `ServiceSearch` object provides methods to search for Service based on several parameters, which include LDAP filter and service name.

JavaScript Objects

- `ServiceSearch`
- `Service`

PersonPlacementRulesExtension

The full extension name is `com.ibm.itim.remoteservices.script.PersonPlacementRulesExtension`.

This extension provides the entry object to the scripting environment. The entry object is of type `Map` and contains the attribute values for the `Person` that is placed.

Availability

`PersonPlacementRules`

JavaScript Objects

`entry`

PostOfficeExtension

The full extension name is `com.ibm.itim.mail.postoffice.script.PostOfficeExtension`.

The Post Office capability reduces the number of email messages received by workflow participants by combining similar notifications into a single email. The emails are combined with a template specified in the system configuration pages. This extension exposes a JavaScript object, `PostOffice`, to JavaScript snippets in these templates. This object provides methods for accessing all the distinct emails, the email address of the recipient, the email topic, and the recipient data.

Availability

Post Office Template

JavaScript Objects

`PostOffice`

ProvisioningPolicyExtension

The full extension name is `com.ibm.itim.policy.script.ProvisioningPolicyExtension`.

This extension provides the scripting objects `reason` and `parameters` to the scripting environment. The `reason` object is an integer that informs a script of the reason the evaluation is happening: 0 if a new account or 1 if an existing account. The `parameters` object is a map that contains the information about the account that is being evaluated. Currently, only the **uid** field is supported.

Availability

AccountTemplate
ProvisioningPolicy

JavaScript Objects

`parameters`
`reason`

ReminderExtension

The full extension name is `com.ibm.itim.script.extensions.ReminderExtension`.

This extension exposes the `reminderCtx` object to JavaScript snippets contained in email reminders. This object provides methods for accessing the original email text and subject. It also provides the due date and time for the associated to-do item.

Availability

E-mail reminders

JavaScript Objects

`reminderCtx`

ServiceExtension

The full extension name is `com.ibm.itim.script.extensions.ServiceExtension`.

This extension exports the `service` object to the scripting environment. The `service` object is a `DirectoryObject` type and represents the Service associated with a provisioning operation.

Availability

```
IdentityPolicy
OrphanAdoption
PersonPlacementRules
AccountTemplate
ProvisioningPolicy
```

JavaScript Objects

`service`

SubjectExtension

The full extension name is `com.ibm.itim.script.extensions.SubjectExtension`.

This extension provides the subject scripting object. In all of the scripting contexts except for OrphanAdoption, subject is a DirectoryObject. In the OrphanAdoption context, subject is a Map of the attributes returned by a reconciliation.

Availability

HostSelection
IdentityPolicy
OrphanAdoption
Reminder
AccountTemplate
ProvisioningPolicy

JavaScript Objects

subject

WorkflowExtension

The full extension name is `com.ibm.itim.workflow.script.WorkflowExtension`.

This extension exposes JavaScript objects that can be used to access data from a workflow process in progress. In addition, it exposes objects that can be used to get or set the status, state, and result of a workflow process or activity.

Availability

Workflows

JavaScript Objects

- process
- activity
- participant
- Relevant Data

Note: Relevant Data are objects defined by the workflow designer. Check with system administrator to find the names of specific Relevant Data objects.

Relevant data JavaScript objects

Each process has a set of relevant data, or process specific parameters, which can be read or changed from in a workflow script.

The name and syntax of these parameters, or relevant data items, are defined in the workflow designer and are typically specific to the workflow process purpose. For example when you add a user, an object that holds all the attributes of the new user can be a relevant data item. However, when you delete a user, the only required relevant data item can be the distinguished name of the user to delete.

Each relevant data item is represented in the workflow script as a variable with the same relevant data ID as defined in the workflow designer. These relevant data items all have the following functions:

get()

This function returns a JavaScript object that represents the value of the relevant data item. There is a variable present for each relevant data item in the context of the script. For performance reasons, however, the values are not retrieved from the workflow engine until the script specifically requests it with this call. The returned JavaScript object is in the same syntax as defined in the workflow designer.

Usage:

```
dn = subjectDN.get();
```

where `subjectDN` is defined as a relevant data item for the current process.

set(Object value)

The `set(Object value)` function changes the value of the relevant data item. It not only updates the relevant data item in the script, but also in the workflow engine. The new value is a parameter to the function. The new value must be compatible with the syntax of the relevant data item as defined in the workflow designer. For example, if the relevant data item is an integer, the value `cat` is not a valid parameter to this function.

Usage:

```
ou.set("engineering");
```

where `ou` is defined as a relevant data item for the current process.

Registering JavaScript extensions

JavaScript extensions might not be useful or applicable to every scriptable function that IBM Security Identity Manager provides. For example, an extension used by Post Office templates might not be applicable to provisioning policy parameters. An extension designed for one class of script might not load or behave appropriately when loaded into another class of script.

Security Identity Manager has the classes of script that are listed in [Table 8 on page 63](#). JavaScript extensions might be registered to load and run with any combination of these script classes.

JavaScript extensions are configured in these files:

scriptframework.properties (suggested)

For *all* new extensions. Use this file to configure script extensions and other scripting functions.

JavaScript extensions are registered in the `ISIM_HOME/data/scriptframework.properties` file. This file is formatted with the standard Java Properties `key[.subkey]=value` format.

- The `key` is the name assigned to the target script class, described in [Table 8 on page 63](#).
- The `value` is the full class name of the `ScriptExtension` interface.
- (Optional) The `subkey` is used when more than one extension is registered for a script class.

Note:

1. Security Identity Manager is installed with a set of extensions for each script class already registered in the `scriptframework.properties` file. Do not remove these extensions from the file as they are necessary for the product to function correctly.
2. To prevent the possibility of a code injection attack, do not use the JavaScript function `eval()`.
3. By default, only the set of extensions registered in the `scriptframework.properties` file is available for the particular script. You can configure any supported extension for the script by registering JavaScript extensions in the `scriptframework.properties` file. For information about supported script extensions, see [Table 7 on page 55](#). For information about the properties and methods available for each JavaScript extension object, see [Chapter 10, “JavaScript extension reference,” on page 69](#).

fesiextensions.properties (deprecated)

Provides support for Free ECMAScript Interpreter (FESI) JavaScript extensions before Version 5.0 of IBM Tivoli® Identity Manager. Do not author *new* extensions with this deprecated architecture.

If you continue to use the deprecated `fesiextensions.properties` file, save the `fesi.jar` library in the `ITIM_HOME/lib` directory *before* you upgrade Tivoli Identity Manager to Version 5.0 or later versions. Replace the newly installed file with the custom `fesi.jar` file after the upgrade completes.

The following line registers a single extension for use in Security Identity Manager scripts:

```
ITIM.extension.IdentityPolicy=com.ibm.itim.policy.script.IdentityPolicyExtension
```

These example lines register multiple extensions for use in Security Identity Manager scripts:

```
ITIM.extension.IdentityPolicy.1=com.ibm.itim.policy.script.IdentityPolicyExtension
ITIM.extension.IdentityPolicy.2=com.yourcompany.script.YourCustomExtension
```

Host Component	Script Class Key
AccountTemplate	ITIM.extension.AccountTemplate
Delegate	ITIM.extension.Delegate
HostSelection	ITIM.extension.HostSelection
IdentityPolicy	ITIM.extension.IdentityPolicy
OrphanAdoption	ITIM.extension.OrphanAdoption
PersonPlacementRules	ITIM.extension.PersonPlacementRules
PostOffice	ITIM.extension.PostOffice
ProvisioningPolicy	ITIM.extension.ProvisioningPolicy
Reminder	ITIM.extension.Reminder
Workflow	ITIM.extension.Workflow
Workflow Notification	ITIM.extension.Notification
TODO Notification (Approval/RFI/ ComplianceAlert/WorkOrder)	ITIM.extension.Notification

Configuring scriptframework.properties

Use the `ISIM_HOME/data/scriptframework.properties` file, which provides extended documentation for these tasks, to configure major scripting functions.

Following are the major scripting functions:

Extensions

Specifies which extensions to load for each host component. To load more than a single extension for any host component, add a suffix to the properties key (each key must be unique). For example:

```
ITIM.extension.IdentityPolicy=com.ibm.itim.policy.script.IdentityPolicyExtension
ITIM.extension.IdentityPolicy.service=com.ibm.itim.script.extensions.ServiceExtension
```

Interpreters

Configures the interpreter to use for each host component. The default is the IBM JSEngine.

The other option is FESI, which can be used only if the `fesi.jar` file exists in `ISIM_HOME/lib/`. It is only to be used by customers of IBM Tivoli Identity Manager Version 4.6 and earlier who wrote their own custom FESI extensions.

Wrappers

All objects available to scripts are really Java objects that are used by IBM Security Identity Manager. To prevent security issues, IBM Security Identity Manager wraps these objects in wrappers. Use this area of the `scriptframework.properties` file to change the default wrappers that are used by IBM Security Identity Manager. Default scripts that are provided by IBM Security Identity Manager assume the use of default wrappers. If you change the scripts, functions might stop working. This area is for advanced use only.

Miscellaneous

Determines whether profiling information is collected and included in the trace log and whether plain text passwords can be accessed from Person and Account objects.

Migration of custom FESI extensions to the IBM JSEngine

Migration of a custom FESI extension to a script extension makes your code shorter, easier to read, and easier to understand.

Note: Support for FESI is deprecated in IBM Security Identity Manager Version 6.0.

For detailed information and examples about how to write new extensions, see the documentation in *ISIM_HOME/extensions/doc/javascript/javascript.html*.

The following example illustrates the migration steps.

Best practice in handling function returns

You can minimize problems that might occur due to differences in how FESI and IBM JSEngine handle JavaScript. The differences involve implicit return values from functions.

For example, given these statements:

```
function sumValue() {
  var a = 3;
  var b = 2;
  a + b;
}
```

With FESI, the function `sumValue()` returns 5 because 5 is the result of the last statement run in the function. Using IBM JSEngine, the expression `sumValue()` returns null because there is no explicit return. The correct code for IBM JSEngine includes an explicit return statement:

```
function sumValue() {
  var a = 3;
  var b = 2;
  return a + b;
}
```

To keep JavaScript code consistent, always use an explicit return value in functions. In the previous release, some of the service selection script examples did not use an explicit return value. Update any JavaScript code that is based on these examples to have an explicit return value, to ensure that the code continues to work after an upgrade to use IBM JSEngine.

Plain Old Java Object (POJO) example

Start with a Plain Old Java Object (POJO, in this example) that contains all of the business logic for your extension.

For example:

```
public class Extension {
  public static void log(String msg) {
    System.out.println(msg);
  }
}
```

In this case, the POJO contains a single method. Your typical extension contains more logic. For example:

```
static class FESIExtension implements JSExtension {
  public void initializeExtension(JSGlobalObject go) throws JSEException {
    // Create the prototype
    final JSObject prototype = go.makeJSObject();

    prototype.setMember("log", new JSFunctionAdapter() {
      public Object doCall(JSObject thisObject, Object[] args)
        throws JSEException {

```

```

        if (args.length >= 1) {
            Extension.log(args[0].toString());
        }

        return null;
    }
});

final JSObject obj = go.makeJSObject(prototype);

// This is the name of the object to be used in JavaScript Code
go.setMember("CustomExtension", obj);

go.setMember("log", new JSFunctionAdapter() {
    public Object doCall(JSObject thisObject, Object[] args)
        throws JSEException {
        if (args.length >= 1) {
            Extension.log(args[0].toString());
        }

        return null;
    }
});

go.setMember("Logger", new JSFunctionAdapter() {
    public Object doNew(JSObject thisObject, Object[] args)
        throws JSEException {
        JSGlobalObject go = thisObject.getGlobalObject();
        JSObject proto = go.makeJSObject();

        proto.setMember("log", new JSFunctionAdapter() {
            public Object doCall(JSObject thisObject, Object[] args)
                throws JSEException {
                if (args.length >= 1) {
                    Extension.log(args[0].toString());
                }

                return null;
            }
        });
        final JSObject obj = go.makeJSObject(proto);
        return obj;
    }
});
}

```

This FESI extension has three main parts:

1. First, the extension makes a JSObject named prototype and adds the method “log” to prototype:

```

final JSObject prototype = go.makeJSObject();

prototype.setMember("log", new JSFunctionAdapter() {
    public Object doCall(JSObject thisObject, Object[] args)
        throws JSEException {
        if (args.length >= 1) {
            Extension.log(args[0].toString());
        }

        return null;
    }
});

go.setMember("CustomExtension", obj);

```

The prototype JSObject is then added to the JSGlobalObject with the name CustomExtension. This addition allows scripts to call:

```

CustomExtension.log("message");

```

2. The second part of the extension creates a global function named log.

```

go.setMember("log", new JSFunctionAdapter() {
    public Object doCall(JSObject thisObject, Object[] args)
        throws JSEException {
        if (args.length >= 1) {
            Extension.log(args[0].toString());
        }
    }
});

```

```

    }
    return null;
  }
});

```

Now, a script can call:

```
log("message");
```

3. The third part of the extension creates a constructor that can be called from scripts. For example:

```

go.setMember("Logger", new JSFunctionAdapter() {
    public Object doNew(JSObject thisObject, Object[] args)
        throws JSEException {
        JSGlobalObject go = thisObject.getGlobalObject();
        JSObject proto = go.makeJSObject();

        proto.setMember("log", new JSFunctionAdapter() {
            public Object doCall(JSObject thisObject, Object[] args)
                throws JSEException {
                if (args.length >= 1) {
                    Extension.log(args[0].toString());
                }

                return null;
            }
        });
        final JSObject obj = go.makeJSObject(proto);
        return obj;
    }
});

```

With this constructor, scripts can do the following:

```

var logger = new Logger();
logger.log("message");

```

Conversion to a script extension

When you convert a FESI extension to a script extension, the root of a script extension is the `ScriptExtension` interface.

You must implement this interface to create script extension.

```

public class ITIMEExtension implements ScriptExtension {
    public List getContextItems() {
    }

    public void initialize(ScriptInterface si, ScriptContextDAO dao)
        throws ScriptException, IllegalArgumentException {
    }
}

```

To create object that can be used in scripts, create a POJO class that contains all of the business logic, and implements the marker interface `ExtensionBean`. A marker interface means that `ExtensionBean` does not require you to implement any methods and it does add any new data to your class. A POJO that implements `ExtensionBean` is treated specially by the IBM Security Identity Manager scripting components.

If your class does not implement `ExtensionBean`, then scripts cannot use the methods provided by the POJO. For example:

```

public class Extension implements ExtensionBean {
    public static void log(String msg) {
        System.out.println(msg);
    }
}

```


In the initialize method of your extension, create `ContextItem` that contains an instance of your extension and add that `ContextItem` to a List.

```
ContextItem custom = ContextItem.createItem("CustomExtension",
    new Extension());
items.add(custom);
```

To create global function, use `ContextItem`, but this time call `createGlobalFunction`. For example:

```
ContextItem func = ContextItem.createGlobalFunction("log",
    new GlobalFunction() {
        public Object call(Object[] parameters)
            throws ScriptEvaluationException {
            if (parameters.length >= 1) {
                Extension.log(parameters[0].toString());
            }
            return null;
        }
    });
items.add(func);
```

The second argument to `createGlobalFunction` is a `GlobalFunction` object. `GlobalFunction` has a single method that you must implement and call. It is similar to the `doCall` method from the `FESI JSFunctionAdapter`. `GlobalFunctions` are not suggested because, like the `doCall` method, they pass an array of parameters. You must check that all of the parameters exist and are the right types, which can be difficult to maintain over the life of your extension.

Creation of a constructor

To create a constructor, use `ContextItem` and the `createConstructor` method.

For example:

```
ContextItem logger = ContextItem.createConstructor("Logger",
    Extension.class);
items.add(logger);
```

The second parameter to `createConstructor` is the `Class` object for the object that you want to construct. It is usually a POJO that implements `ExtensionBean`.

In each of these examples, you add the `ContextItem` to a List. In the `getContextItems` method of `ScriptExtension`, you return that List. For example, the full code is:

```
public class ITIMEExtension implements ScriptExtension {

    private List<ContextItem> items;

    public List getContextItems() {
        return items;
    }

    public void initialize(ScriptInterface si, ScriptContextDAO dao)
        throws ScriptException, IllegalArgumentException {

        items = new ArrayList<ContextItem>();

        ContextItem custom = ContextItem.createItem("CustomExtension",
            new Extension());
        items.add(custom);

        ContextItem func = ContextItem.createGlobalFunction("log",
            new GlobalFunction() {
                public Object call(Object[] parameters)
                    throws ScriptEvaluationException {
                    if (parameters.length >= 1) {
                        Extension.log(parameters[0].toString());
                    }
                    return null;
                }
            });
        items.add(func);

        ContextItem logger = ContextItem.createConstructor("Logger",
```

```
        Extension.class);
    items.add(logger);
}
}
```

Download of fesi.jar from a non-IBM source (deprecated)

If you want to use FESI, but do not have the required libraries, you can download and enable the libraries.

Note: Support for FESI is deprecated in IBM Security Identity Manager Version 6.0.

If you upgrade from IBM Tivoli Identity Manager Version 4.6, do not follow these steps. The correct version of the FESI library is maintained during the upgrade.

1. Download FESI version 1.1.8 from <http://www.lugrin.ch/fesi/>. At the time of this writing, 1.1.8 is the latest version
 - a. Follow the link to download the current version, which displays the license page.
 - b. Accept the license to continue.
 - c. Access a download page.
 - d. Download the `install-fesi-1.1.8.jar` file.
2. After the file downloads successfully, start the installer by typing this command from the command line:

```
java -jar install-fesi-1.1.8.jar
```

- a. Follow the remaining steps that the installer provides to install FESI.

Note: Because IBM Security Identity Manager needs only a JAR file from the installation, you can install FESI to a temporary location that you can delete later.
 - b. After the installation completes, go to `$FESI_INSTALL_DIR/lib` and locate the `fesi.jar` file.
 - c. Copy the `fesi.jar` file to the `ISIM_HOME/lib` directory.
3. Specify where IBM Security Identity Manager accesses `fesi.jar`.
 - a. Log on to the WebSphere Application Server administrative console, which is typically at `http://hostname:9060/ibm/console`, where `hostname` is specific to your computer.
 - b. Go to **Environment > Shared Libraries > ITIM_LIB**.
 - c. At the bottom of the **Classpath** text box, add the line `${ISIM_HOME}/lib/fesi.jar`.
 4. Restart the WebSphere Application Server to put the changes into effect.
 5. Edit the `scriptframework.properties` file to use the FESI interpreter.

When you are using FESI, the script framework looks for the `fesiextensions.properties` file to determine which FESI extensions to load. If this file does not exist, a message is written to the `trace.log` file for every script that is run by FESI.

Chapter 10. JavaScript extension reference

The reference section is arranged alphabetically.

There are a number of IBM Security Identity Manager specific objects available for use. IBM Security Identity Manager uses JavaScript extensions to package JavaScript objects and APIs. An extension can also be a package of other extensions (for example, ModelExtension).

After an extension is defined, it can be registered in the *ISIM_HOME/data/scriptframework.properties* file to be used in a specific JavaScript context. In some cases, an environment needs to be created for an extension.

Table 9 on page 69 shows these script extensions.

<i>Table 9. Script extensions</i>		
Script Extension	Object Name	Object Type
AttributesExtension (deprecated)	ATTRIBUTES	Map
EmailContextExtension	EmailContext	EmailContext
EnroleExtension	Enrole error	Enrole Error
IdentityPolicyExtension	IdentityPolicy	IdentityPolicy
LoopCountExtension	loopcount	int
PersonPlacementRulesExtension	entry	Map
PostOfficeExtension	PostOffice	PostOffice
ProvisioningPolicyExtension	parameters reason	Map int (0: New Account, 1: Existing Account)
AccountModelExtension	Account constructor AccountSearch constructor	Account AccountSearch
CredentialModelExtension	Credential	Credential
OrganizationModelExtension	ContainerSearch constructor	ContainerSearch
PersonModelExtension	Person constructor ExtendedPerson constructor PersonSearch constructor	Person ExtendedPerson PersonSearch
RoleModelExtension	Role constructor RoleSearch constructor	Role RoleSearch
ServiceModelExtension	Service constructor ServiceSearch	Service ServiceSearch
ReminderExtension	reminderCtx	Reminder

<i>Table 9. Script extensions (continued)</i>		
Script Extension	Object Name	Object Type
ServiceExtension	service	DirectoryObject
SubjectExtension	subject	Person Note: For Orphan Adoption Rule JavaScript, the subject is a Map, which contains the account attributes returned from reconciliation. The entries in the map are referred by the name of the account attributes, which might vary based on the service type.
WorkflowExtension	process activity Participant constructor ParticipantType \$RelevantDataName	Activity Participant ParticipantType ProcessDataProcess

Finding methods and properties for a specific JavaScript object

This example demonstrates how to find methods and properties for a specific JavaScript object.

If you are writing a workflow script, look in the `scriptframework.properties` file to see which extensions are available. By default, workflow loads the model extensions, the `WorkflowExtension`, and the `LoopCountExtension`.

Table 9 on page 69 shows that `WorkflowExtension` defines scripting objects that include `process`, `activity`, a `Participant` constructor, an object named `ParticipantType`, and a series of workflow-specific pieces of data.

In another column in the table, notice that the `process` object is of type `Process`. Now, locate `Process` in this reference to see that `Process` type has a property called `name`, and a method called `getParent()`.

To understand how to use maps, notice that objects, such as `parameters` from **ProvisioningPolicyExtension**, have a type of `Map`. A `Map`, also known as a dictionary, is a named JavaScript object that can hold many other objects which can be accessed by name. The `parameters` object holds another object named `uid`. To access `uid`, you can type `parameters.uid[0]`. (In this case `uid` is an array, so you must type `[0]` to get the first element of the array.) The values that a map holds will vary between each map. For more information, locate the specific map in the JavaScript reference.

How to read the reference pages

This section explains the structure of each reference item.

Title and Description

Every reference entry begins with a title and a one line description. The entries are alphabetized by title. The one-line description gives a quick summary of the item documented in the entry.

Availability

The IBM Security Identity Manager JavaScript extensions change over time. Unless otherwise noted, anything available in one version of the IBM Security Identity Manager extensions is also available in later versions. This section also specifies whether an existing item was enhanced with a later version of the extensions and when an item is deprecated. Deprecated items are no longer supported and can be removed from future versions of the IBM Security Identity Manager extensions. Do not use deprecated items in new IBM Security Identity Manager JavaScript code.

Provided by

At installation, IBM Security Identity Manager provides this initial set of registered extensions:

- **EnroleExtension**
- **ProvisioningPolicyExtension**
- **PostOfficeExtension**
- **IdentityPolicyExtension**
- **PersonPlacementRulesExtension**
- **WorkflowExtension**
- **ReminderExtension**
- **ServiceExtension**
- **SubjectExtension**
- **AttributesExtension**
- **LoopCountExtension**
- **EmailContextExtension**
- **Model extensions package**

Inherits From

JavaScript classes can inherit properties and methods from other classes. When it occurs, an Inherits From section appears in the reference entry. The inherited fields and methods are in the listed superclasses. For example, the subject object inherits all of its fields and properties from the **DirectoryObject** class.

Synopsis

This section is a synopsis of how to use the object, method, property, or function.

Arguments

If the reference page describes a function or method that has arguments, the Synopsis is followed by an Arguments subsection that describes the arguments to the function or method. For some objects, the Synopsis section is replaced by a Constructor section which is also followed by an Arguments subsection.

Returns

If a function or a method has a return value, the Arguments subsection is followed by a Returns subsection that explains the return value of the function, method or constructor.

Properties

If the reference page documents an object, the Properties section lists the properties the object supports and provides short explanations of each.

Methods

The reference page for an object that defines methods includes a Methods section.

Description

Most reference entities contain a Description section, which is a basic description of whatever is documented. For some simple methods, the Arguments and Returns sections document the method sufficiently by themselves, so the Description section is omitted.

Usage

This section describes common techniques for using the item, or it contains cautionary information.

Account

Represents an account that is associated with a provisioning operation.

Availability

IBM Tivoli Identity Manager 4.x.

Inherits From
DirectoryObject

Provided by
com.ibm.itim.script.extensions.model.AccountModelExtension

Constructor
new Account(dn)

Returns
The newly created Account object that represents the account with the specified DN, which is a String.

Methods
getAndDecryptPassword()

Decrypts and returns
The decrypted password of the account entity in plain text.

Note: This method is available in the scripting context of Security Identity Manager only if the javascript.password.access.enabled property is set to true in the <ISIM_HOME>/data/scriptframework.properties file.

setAndEncryptPassword()

Encrypts
The given plaintext password and sets it on the account object.

Note: This method is available in the scripting context of Security Identity Manager only if the javascript.password.access.enabled property is set to true in the <ISIM_HOME>/data/scriptframework.properties file.

Account.getAndDecryptPassword()

The method decrypts and returns the decrypted password of the account entity in plain text.

Availability
IBM Tivoli Identity Manager 4.x.

Synopsis
account.getAndDecryptPassword()

Returns
String representing plain text password set in the account object.

Description

This method can be used in the scripting context of Security Identity Manager if the **javascript.password.access.enabled** property is set to true in the <ISIM_HOME>/data/scriptframework.properties file. It decrypts and returns the decrypted password set in the account object. This function will return null if the password is not present.

Note: This method does not decrypt the password of the Security Identity Manager account, which is hashed and stored in LDAP.

Usage

```
var password = account.getAndDecryptPassword();  
</page_ Account.getAndDecryptPassword()>
```

Account.setAndEncryptPassword()

The method encrypts the given plaintext password and sets it on account object.

Availability
IBM Tivoli Identity Manager 4.x.

Synopsis
account.setAndEncryptPassword(String password)

Arguments

password

Plain text password string.

Description

This method can be used in the scripting context to set a given plain text password to an account object if the **javascript.password.access.enabled** property is set to true in the <ISIM_HOME>/data/scriptframework.properties file. Internally, the function encrypts the password and sets the same on the account entity.

Usage

```
account.setAndEncryptPassword("secret");  
</page_Account.setAndEncryptPassword(>
```

AccountSearch

You can search for an account with the AccountSearch object.

Availability

IBM Tivoli Identity Manager 4.x.

Provided by

com.ibm.itim.script.extensions.model.AccountModelExtension

Constructor

new AccountSearch()

Returns

The newly created and initialized account search object.

Methods

searchByOwner()

Search for an account by owner.

searchByUid()

Search for an account by user ID.

searchByUidAndService()

Search for an account by user ID and service.

searchByURI()

Search for an account by URI within an organizational container.

Description

The entity implements the IBM Security Identity Manager Account Search class.

AccountSearch.searchByOwner()

The method finds an account entity by the distinguished name of the owner.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

AccountSearch.searchByOwner(personDN)

Arguments

personDN

String representing the distinguished name of the account owner.

Description

Given the distinguished name of the person, find the account entities owned by that person. This function will return null if the person is not found.

Usage

```
var account = (new AccountSearch()).searchByOwner(person.dn);
if (account!=null) {
  Enrole.log("script", "Found " + account.length + " accounts");}
}
```

AccountSearch.searchByUid()

The method finds an account entity by user ID and distinguished name of a service.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
AccountSearch.searchByUid(uid, serviceDN)
```

Arguments

uid

String representing the user ID of the account.

serviceDN

String representing the distinguished name of the account.

Description

Given the user ID of the account and the distinguished name of the service, find the account entity.

This function returns null if there is not exactly one matching account, or if the service is not found.

Usage

```
var account = (new AccountSearch()).searchByUid("pallen",
service.dn);
if (account!=null) {
  Enrole.log("script", "Found account pallen");
}
```

AccountSearch.searchByUidAndService()

The method finds an account entity by user ID, service name, and service profile name.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
AccountSearch.searchByUidAndService(uid, serviceName)
```

Arguments

uid

String representing the user ID of the account.

serviceName

String representing the name of the service.

Description

Given the user ID of the account and the name of the service that has the same service profile as the script context service profile, find the account entity. This function returns null if:

- More than one matching account exists.
- The service is not found.
- More than one service with the given name exists.

Usage

```
var account = (new AccountSearch()).searchByUidAndService
("pallen", "Domain Controller");
if (account!=null) {
  Enrole.log("script", "Found account pallen"); }
}
```


Synopsis

```
AccountSearch.searchByUidAndService(uid, serviceName, serviceProfileName)
```

Arguments

uid

String representing the user ID of the account.

serviceName

String representing the name of the service.

serviceProfileName

String representing the name of the service profile of the serviceName service.

AccountSearch.searchByURI()

The method finds an account by URI in an organizational container.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
AccountSearch.searchByURI(containerDN, uri)
```

Arguments

Container DN

String representing the distinguished name of the organizational container.

uri

String representing the URI of the account.

Returns

An Account object.

Description

Given the distinguished name of an organizational container and the account URI, this method finds the account. If the account is not found, this function returns null. If more than one account is found, this function throws a scripting exception.

Usage

```
var account = (new AccountSearch()).searchByURI(container.dn, uri);
if (account != null) {
  Enrole.log("script", "Found " + account.getProperty("eruid") );}
}
```

Activity

Activity is used to reference any activity in a IBM Security Identity Manager workflow.

Availability

IBM Tivoli Identity Manager 4.x

Provided by

The activity JavaScript object in the `WorkflowExtension` returns an `Activity` object that represents the current workflow activity. The workflow activity can be used in the context of a workflow activity `PostScript`, or in a transition script, to reference the current activity. For a transition script, this object represents the activity whose completion has lead to the evaluation of the transition script.

`Process.getActivity()` can return any `Activity` object in the context of a workflow process. For more information, see the description of this method.

Activity Result Summary Code

APPROVED

Approved process summary code. Result code is AA.

ESCALATED

Escalated process summary code. Result code is ES.

FAILED

Failed process summary code. Result code is SF.

PARTICIPANT_RESOLVE_FAILED

Participant resolved failure process summary code. Result code is PF.

PENDING

Pending process summary code. Result code is PE.

REJECTED

Rejected process summary code. Result code is AR.

SUBMITTED

Submitted process summary code. Result code is RS.

SUCCESS

Success process summary code. Result code is SS.

TIMEOUT

Time out process summary code. Result code is ST.

WARNING

Warning process summary code. Result code is SW.

Properties**description**

Describes the purpose of the activity given when defined in the workflow designer.

duedate

Indicates the time in milliseconds by when the activity is due.

id

Assigned by the workflow designer to uniquely identify the workflow activity within the workflow engine.

index

Index of the instance of the activity.

name

Label given this activity when defined in the workflow designer.

participant

The activity participant, as defined in the workflow designer.

resultDetail

An application-specific string that provides more detail about the result of the activity.

resultSummary

An application-specific string that represents the summary result of the activity.

started

Indicates when the activity started.

state

Code that represents the current state of the activity.

subtype

Code that further categorizes the activity beyond the type of the activity, such as approval or request for information.

type

Code that categorizes the activity given when defined in the workflow designer, such as manual or application.

Methods**auditEvent()**

Create an event in the audit trail specific to the activity.

setResult()

Change the result member of the activity in the current activity.

Description

This entity represents the current workflow activity that is being run. Within the context of a workflow transition script, this entity represents the activity whose completion has led to the evaluation of the transition script. No constructor is available to create this object in any IBM Security Identity Manager context.

Activity.auditEvent()

The method creates an event in the audit trail.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
activity.auditEvent(event)
```

Arguments**event**

String representing the event to be audited.

Description

This method creates an event in the audit trail specific to the activity. The function takes in one parameter that can be any JavaScript object that can be translated into a String for storage. In the audit trail, the event is automatically time stamped.

Usage

```
activity.auditEvent("Task completed");
```

Activity.description

The field provides information about the purpose of the activity.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
activity.description
```

Description

This read-only field is a String that describes the purpose of the activity given when defined in the workflow designer.

Usage

```
x = activity.description;
```

Activity.duedate

The field represents the time in milliseconds by when the activity is due.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
activity.duedate
```

Description

This read-only field is a long number of milliseconds by when this activity is due.

Usage

```
x = activity.duedate;
```

Activity.getSubProcesses()

The method returns the subordinate processes (if any) of the activity.

Availability

IBM Security Identity Manager 6.0.0.3.

Synopsis

```
activity.getSubProcesses()
```

Returns

The subordinate processes. If there are no subordinate processes, an empty array is returned.

Description

This method returns the subordinate processes (if any) of this activity.

Usage

```
var out = "subprocesses of the activity: \n";
var subProcesses = activity.getSubProcesses();
for (var i = 0; i < subProcesses.length; i++) {
    out += subProcesses[i].id + " type: " + subProcesses[i].type + " resultSummary: " +
    subProcesses[i].resultSummary + "\n";
}
activity.auditEvent(out);
```

Activity.guid

The generated unique identifier assigned to the activity at runtime.

Availability

IBM Tivoli Identity Manager 5.x

Synopsis

```
activity.guid
```

Description

This read-only field is a String of the generated unique identifier for the workflow activity within the workflow engine.

Usage

```
x = activity.guid;
```

Activity.id

The field is the unique identifier assigned to the activity.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
activity.id
```

Description

This read-only field is a String assigned by the workflow designer to uniquely identify the workflow activity within the workflow engine.

Usage

```
x = activity.id;
```

Activity.index

The field is an index of the instance of the activity.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

activity.index

Description

This field is a read-only and a number. If there is more than one instance of this activity, such as in the case where the activity of the ID is called multiple times in a loop in the workflow process, the value starts at one. If there is only one instance of this activity, the index value is zero.

Usage

```
x = activity.index;
```

Activity.name

The field is the label that is assigned to the activity.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

activity.name

Description

This read-only field is a String assigned by the workflow designer to label this activity.

Usage

```
x = activity.name;
```

Activity.participant

The field represents the activity participant.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

activity.participant

Description

This read-only field is a Participant that represents the activity participant. Not all activities have a participant. If there is no participant associated with the activity, this member is empty.

Usage

```
x = activity.participant;
```

Activity.resultDetail

You can get the details about the result of the activity with this field.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

activity.resultDetail

Description

This read-only field is an application-specific string that provides more detail about the result of the activity.

Usage

```
x = activity.resultDetail;
```

Activity.resultSummary

The field helps you view the summary of the result of the activity.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

`activity.resultSummary`

Summary

This read-only field is an application-specific string that provides a summary of the result of the activity. It can represent a success or failure.

Usage

```
x = activity.resultSummary;
```

Activity.setResult()

The method changes the result member of the activity.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
activity.setResult(summary)
```

```
activity.setResult(summary, detail)
```

Arguments

summary

String code that represents the result summary.

detail

String representing the result details.

Description

This method changes the result member of the activity in the current activity. It is supported for current activities in the current workflow process. The result is composed by an application-specific summary code, and optional more detailed application-specific description. The summary code can indicate a success or failure. This summary code is stored as the `resultSummary` member locally and updated in the relevant data in the workflow engine. The detail is stored as the `resultDetail` member locally and updated in the relevant data in the workflow engine.

Usage

```
activity.setResult(activity.FAILED);
```

```
activity.setResult(activity.FAILED, "Unable to connect to resource");
```

Activity.started

The field represents the date that indicates when the activity started.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

`activity.started`

Description

This read-only field is a string that represents the date that indicates when the activity started.

Usage

```
x = activity.started;
```

Activity.state

The field represents the current state of the activity.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

activity.state

Description

This read-only field is a code string that represents the current state of the activity. The state can have the following values:

- **R** for running
- **I** for not started
- **T** for terminated
- **A** for aborted
- **S** for suspended
- **C** for completed
- **B** for bypassed

Usage

```
if (activity.state == "S") {  
  ...  
}
```

Activity.subtype

The field represents the subtype of the activity.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

activity.subtype

Description

This read-only field is a code string that further categorizes the activity beyond the type of the activity, such as approval or request for information. This is defined in the workflow designer. Not all activities have a subtype. If there is no subtype associated with the activity, this member is empty. The currently supported subtypes are:

- **AP** for approval
- **RI** for request for input
- **WO** for work order

Usage

```
x = activity.subtype;
```

Activity.type

The field represents the type of the activity.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

activity.type

Description

This read-only field is code string that categorizes the activity given when defined in the workflow designer, such as manual or application. The currently supported types are:

- **S** for subprocess
- **L** for loop
- **A** for application
- **R** for route
- **M** for manual
- **O** for operation

Usage

```
x = activity.type;
```

AttributeChangeOperation

The object represents an entity about the attribute change operation.

Availability

IBM Tivoli Identity Manager 4.x.

Provided by

AttributeChangeOperation objects are returned from the method **DirectoryObject.getChanges()** and are therefore not provided by any specific extension.

Properties

attr

Name of the attribute that is being changed.

op

An integer that identifies the type of change that is being made.

values[]

An array of objects that must be either added, removed, or replaced.

Description

This entity represents the changes made to a IBM Security Identity Manager object.

AttributeChangeOperation.attr

Represents the name of an attribute that is being changed.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
attributeChangeOperation.attr
```

Description

Value is the attribute that is being changed.

Usage

```
x = attributeChangeOperation.attr;
```

AttributeChangeOperation.op

The field represents the type of change that is being made.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
attributeChangeOperation.op
```

Description

This read-only field is a number that identifies the type of change that is being made. The values are:

- **1** for add
- **2** for replace

- 3 for remove

Usage

```
x = attributeChangeOperation.op;
```

AttributeChangeOperation.values[]

The field represents the name of attribute that is being changed.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
attributeChangeOperation.values[]
```

Description

This read-only field is an array of objects that must be added, removed, or replaced.

Usage

```
x = attributeChangeOperation.values[1];
```

ContainerSearch

The object represents the search for an organizational container.

Availability

IBM Tivoli Identity Manager 4.x.

Provided by

```
com.ibm.itim.script.extensions.model.OrganizationModelExtension
```

Constructor

```
new ContainerSearch()
```

Returns

The newly created and initialized container search object.

Methods**searchByFilter()**

Search for a container with a filter.

searchByURI()

Search for an organizational container by URI within a parent organizational container.

Description

Implements the IBM Security Identity Manager **OrganizationalContainerSearch** class.

ContainerSearch.searchByFilter()

The method represents the search for a container with a filter.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
containerSearch.searchByFilter(profileName, filter, scope)
```

Arguments**profileName**

The String name of the organizational container profile to use.

filter

LDAP search filter String that defines the criteria for returned containers to meet. The filter must be in the format defined by RFC2254.

scope

Optional Int search scope. Use 1 for One Level Scope and 2 for SubTree Scope. One Level Scope is the default scope.

Returns

An array of **DirectoryObjects** representing the results of the search.

Description

This method searches for a container with a filter.

Usage

```
var locationContainer = new ContainerSearch();
// use subtree scope
var thisLocation = locationContainer.searchByFilter("Location",
    "(l=Raleigh)", 2);

// use default one level scope
var otherLocation = locationContainer.searchByFilter("Location",
    "(l=Raleigh)");
```

ContainerSearch.searchByURI()

The method finds an organizational container by URI in a parent organizational container.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
ContainerSearch.searchByURI(containerDN, uri)
```

Arguments**Container DN**

String representing the distinguished name of the parent organizational container.

uri

String representing the URI of the organizational container.

Returns

A **DirectoryObject** representing the container.

Description

Given the distinguished name of the parent organizational container and the container URI, this method finds the container. If the container is not found, this function returns null. If more than one container is found, this function throws a scripting exception.

Usage

```
var container = (new ContainerSearch()).searchByURI(parentContainer.dn,
    uri);
if (container != null) {
    Enrole.log("script", "Found " + container.getProperty("ou") );}
```

Context

The object represents the context of the currently running workflow process (for example, requestor or subject). Only used for entitlement workflows.

Note: This object type is deprecated. Use workflow JavaScript objects, such as **Process**, **Activity**, and **Relevant Data**.

Some account-specific functions of the context JavaScript extension, including **getService()**, **isAccountDataChanged()**, and **getAccountParameter()** cannot be applicable to operation workflows that are not account related. The context JavaScript extension is not suggested for custom workflows.

Availability

IBM Tivoli Identity Manager 4.x.

Provided by

com.ibm.itim.workflow.script.WorkflowExtension

Context Constants**APPROVED**

This constant is used to describe the result of an activity. The member applies only to Approval types of activities.

Usage

```
if (context.getActivityResult() == context.APPROVED) {...
```

REJECTED

This constant is used to describe the result of an activity. This member applies only to Approval types of activities.

Usage

```
if (context.getActivityResult() == context.REJECTED) {...
```

NEWACCOUNT

This constant is used to identify the type of request that triggers the custom workflow run time.

Usage

```
if (context.getProcessType() ==  
    context.NEWACCOUNT) {...
```

ACCOUNTDATACHANGE

This constant is used to identify the type of request that triggers the custom workflow in run time.

Usage

```
if (context.getProcessType() ==  
    context.ACCOUNTDATACHANGE) {...
```

Methods**getAccountParameter()**

Returns the value of an account attribute.

getActivityResult()

Returns the activity result for the current activity.

getActivityResultByID()

Returns the activity result for a specific activity.

getLoopCount()

Returns the loop count for the current loop activity.

getLoopCountByID()

Returns the current loop count for a specific loop activity.

getProcessType()

Returns the type of the request that triggers the custom workflow process.

getRequestee()

Returns the requestee associated with the request as a Person object.

getService()

Returns the target service as a Service entity object.

isAccountDataChanged()

Identifies whether a specific account attribute was changed in the request that triggers the custom workflow process.

Description

The context of the currently running workflow process (for example, requestor or subject) is represented within the JavaScript as an object named context.

Context.getAccountParameter()

The method returns the value of an account attribute.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
context.getAccountParameter(String attributeName)
```

Arguments**attributeName**

String representing the attribute name.

Returns

String value of an account attribute.

Description

This member function returns the value of an account attribute as a string.

Usage

```
parameter=context.getAccountParameter("group");
```

Context.getActivityResult()

The method returns the activity result for the current activity.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
context.getActivityResult()
```

Returns

String

Description

This member function returns the activity result for the current activity. The function returns APPROVED or REJECTED. If this function is used to specify a transition condition, the function refers to the activity from which the transition is coming.

Usage

```
if (context.getActivityResult() == context.APPROVED) {...
```

Context.getActivityResultById()

The method returns the activity result for a specific activity.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
context.getActivityResultById(String activityDefinitionID)
```

Arguments**activityDefinitionID**

String ID of the activity definition.

Returns

String

Description

This member function returns the activity result for a specific activity. The function returns APPROVED or REJECTED.

Usage

```
if (context.getActivityResultByID("1234567890") == context.APPROVED) {...
```

Context.getLoopCount()

The method returns the loop count for the current loop activity.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
getLoopCount()
```

Returns

Integer of loop count.

Description

This member function returns the loop count for the current loop activity. If this function is called before a loop is started, the loop count is 0. If this activity is called while the loop activity is in process, the loop count is the number of times the loop ran. If this function is called after the loop is completed, the loop count is the total number of times the loop is defined to run.

Usage

```
currentiteration = context.getLoopCount();
```

Context.getLoopCountByID()

The method returns the current loop count for a specific loop activity.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
context.getLoopCountByID(String activityDefinitionID)
```

Arguments**activityDefinitionID**

ID of the activity definition.

Returns

Integer

Description

This member function returns the current loop count for a specific loop activity. If this function is called before the loop is started, the loop count is 0. If this function is called while the loop activity is in process, the loop count is the number of times the loop ran. If this function is called after the loop is completed, the loop count is the total number of times the loop is defined to run.

Usage

```
currentiteration = context.getLoopCount("1234567890");
```

Context.getProcessType()

The method returns the type of the request that triggers the custom workflow process.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
context.getProcessType()
```

Returns

String

Description

This member function returns the type of the request that triggers the custom workflow process. The function returns NEWACCOUNT or ACCOUNTDATACHANGE.

Usage

```
if (context.getProcessType() == context.NEWACCOUNT) {...
```

Context.getRequestee()

The method returns the requestee associated with the request as a person object.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
context.getRequestee();
```

Returns

A `DirectoryObject` that represents a Person.

Description

This member function returns the requestee associated with the request as a Person object. The requestee is the user who owns the associated, provisioned account.

Usage

```
requestee = context.getRequestee();
```

Context.getService()

The method returns the target service as a service entity object.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
context.getService()
```

Returns

`DirectoryObject`

Description

This member function returns the target service as a Service entity object. The service entity is the service associated with the provisioned account.

Usage

```
service = context.getService();
```

Context.isAccountDataChanged()

The method identifies whether a specific account attribute was changed in the request that triggers the custom workflow process.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
isAccountDataChanged(String attributeName)
```

Description

This member function identifies whether a specific account attribute was changed in the request that triggers the custom workflow process. If the request that triggers the custom workflow is NEWACCOUNT and the attribute is in the new account parameters, this function returns TRUE. Otherwise, this function returns FALSE. If the request that triggers the custom workflow is ACCOUNTDATACHANGE and the specified attribute is changed, this function returns TRUE. Otherwise, this function returns FALSE.

Usage

```
if (context.isAccountDataChanged("group")) {...
```

Credential

Credentials are associated with a shared access module operation, such as `addCredentialToVault`, `checkin`, or `checkout`.

Availability

Security Identity Manager 6.0

Inherits from

`DirectoryObject`

Provided by

`com.ibm.itim.script.extensions.model.CredentialModelExtension`

Access mode

EXCLUSIVE

Indicates that an authorized user must access the credential through the checkout process.

NON_EXCLUSIVE

Indicates that an authorized user can access the credential without the checkout process.

NON_SHARED

Indicates that the credential is not intended for sharing.

Notification option

NOTIFY_ONLY

When the credential lease expires, a notification email is sent.

NOTIFY_AND_CHECKIN

When the credential lease expires, the credential is checked in automatically, and a notification email is sent.

Constructor

```
new Credential(dn)
```

Returns

The newly created `Credential` object that represents the credential with the specified DN, which is a `String`.

Methods

getAccessMode()

Returns an integer constant to represent the access mode, which can be `EXCLUSIVE`, `NON_EXCLUSIVE`, or `NON_SHARED`.

getCheckoutDuration()

Returns the maximum checkout time in hours.

getNotificationRecipient()

Returns the `Participant` object.

getNotifyOption()

Returns integer constant `NOTIFY_ONLY`, or `NOTIFY_AND_CHECKIN`.

isCheckoutSearchEnable

Returns true if the credential is enabled for search during checkout; returns false, otherwise.

isNotifyOnly()

Returns true if the system is configured to send only a notification when a lease is expired; returns false, otherwise.

isPasswordViewable()

Returns true if the credential password can be displayed to an authorized user; returns false, otherwise.

isResetPasswordAtCheckin()

Returns true if the credential password needs to be reset during the checkin process; returns false, otherwise.

Credential.getAccessMode()

The method returns the access mode of the credential.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
Credential.getAccessMode()
```

Returns

Integer

Description

This function returns EXCLUSIVE, NON_EXCLUSIVE, or NON_SHARED.

Usage

```
var accessMode = credential.getAccessMode();
if (accessMode == Credential.EXCLUSIVE) {
    ...;
}
```

Credential.getCheckoutDuration()

The method returns the maximum checkout time for the credential in hours.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
Credential.getCheckoutDuration()
```

Returns

Integer

Description

This function returns an integer value in hours.

Usage

```
var checkoutDuration = credential.getCheckoutDuration();
```

Credential.getNotifyOption()

The method returns the notification option when a credential lease is expired.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
Credential.getNotifyOption()
```

Returns

Integer

Description

This function returns NOTIFY_ONLY or NOTIFY_AND_CHECKIN.

Usage

```
var notifyOption = credential.getNotifyOption();
if (notifyOption == Credential.NOTIFY_ONLY) {
    ...;
}
```

Credential.getNotificationRecipient()

The method returns the notification recipient when a credential lease is expired.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
Credential.getNotificationRecipient()
```

Returns

Participant

Description

This function returns Participant object to whom the lease expiration email is sent.

Note: The person who checked out the credential always gets a notification when the lease is expired.

Usage

```
var participant = credential.getNotificationRecipient();
```

Credential.isCheckoutSearchEnable()

The method returns whether the credential is enabled for a checkout search.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
Credential.isCheckoutSearchEnable()
```

Returns

Boolean

Description

This function returns true if the credential is enabled for a checkout search; returns false otherwise.

Usage

```
var isSearchable = credential.isCheckoutSearchEnable();
if (isSearchable) {
    ...;
}
```

Credential.isNotifyOnly()

The method returns whether the system must send only a notification email when a credential lease is expired or not.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
Credential.isNotifyOnly()
```

Returns

Boolean

Description

This function returns true if the notification option is NOTIFY_ONLY; returns false if the notification option is NOTIFY_AND_CHECKIN.

Usage

```
var isNotifyOnly = credential.isNotifyOnly();
if (isNotifyOnly) {
    ...;
}
```

Credential.isPasswordViewable()

The method returns whether the credential password can be displayed to an authorized user or not.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
Credential.isPasswordViewable()
```

Returns

Boolean

Description

This function returns true if the credential password can be displayed to an authorized user; returns false, otherwise.

Usage

```
var isDisplayPwd = credential.isPasswordViewable();
if (isDisplayPwd) {
    ...;
}
```

Credential.isResetPasswordAtCheckin()

The method returns whether to reset the credential password during the checkin process or not.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
Credential.isResetPasswordAtCheckin()
```

Returns

Boolean

Description

This function returns true if the credential password needs to be reset during the checkin process; returns false, otherwise.

Usage

```
var isResetPwd = credential.isResetPasswordAtCheckin();
if (isResetPwd) {
    ...;
}
```

Delegate

The object provides the Delegate JavaScript object for use in the JavaScript environment of delegation notification. The Delegate JavaScript object and their use is described in this section.

Delegate

The Delegate object contains all the information associated with the current delegation operation.

Availability

IBM Tivoli Identity Manager 5.1.0.11

Delegation Notification context

Provided by

com.ibm.itim.script.extensions.DelegateExtension

Methods**Delegate.getDelegator()**

Returns the DirectoryObject that represents a system user such as the IBM Security Identity Manager account, whose activities are delegated.

Delegate.getDelegatee()

Returns the DirectoryObject that represents a system user such as the IBM Security Identity Manager account, who is selected to be the delegate for the activities of the delegator.

Delegate.getStartDate()

Returns a Date that contains the date and time when the delegation starts.

Delegate.getEndDate()

Returns a Date that contains the date and time when the delegation ends.

Delegate.getRequester()

Returns the `DirectoryObject` that represents a system user such as the IBM Security Identity Manager account, who initiated the delegation.

Description

The `Delegator` object is available in the context of a delegation notification. The object retrieves the delegation information in the delegation notification template. The model script extensions are also available in the delegation notification context.

DirectoryObject

The object represents any IBM Security Identity Manager directory object or entity.

Availability

IBM Tivoli Identity Manager 4.x

Constructor

There is no specific constructor for this object. Specific constructors for `Account`, `Person`, `Role`, and `Service` return `DirectoryObject`.

For example, `new Service()` returns a `DirectoryObject`.

Properties**dn**

String representing the distinguished name of the entity.

name

String representing the logical name of the entity.

profileName

String representing the profile name of the entity.

Methods**addProperty()**

Changes the value of the specified property, or adds the specified property if it does not exist. For multivalued objects, `addProperty()` adds the values to the specified property in the directory object and does not replace them.

getChanges()

Returns the changes made to the entity.

getProperty()

Returns the values of the property specified by the given name.

getPropertyNames()

Returns a list of properties (attributes and relationships).

removeProperty()

Removes the specified property.

setProperty()

Changes the value of the specified property, or adds the specified property if it does not exist.

getPropertyAsDate()

Returns the value of the specified property as a `Date`.

getPropertyAsString()

Returns the value of the specified property as a `String`.

Description

This Object represents a Security Identity Manager entity in the JavaScript environment. Each Security Identity Manager entity is wrapped in one of these object classes.

DirectoryObject.addProperty()

The method adds or updates the value for the specified property.

Availability

IBM Tivoli Identity Manager 5.x

Synopsis

```
directoryObject.addProperty(name, value)
```

Arguments

name

String representing the name of the property to be created or modified.

value

The value to add to the property.

Description

This method changes the value of the specified property or adds the specified property if it does not exist. This change is made locally to the script environment, not to the data store. The value can be a single value object or an array of objects. For multivalued objects, `addProperty()` adds the values to the specified property in the directory object and does not replace them. The value type (syntax) of object must be compatible with the syntax of the specified property. This method is available for the following data types:

- `void addProperty(String name, Collection value);`
- `void addProperty(String name, Date value);`
- `void addProperty(String name, Map value);`
- `void addProperty(String name, boolean value);`
- `void addProperty(String name, byte value);`
- `void addProperty(String name, String value);`
- `void addProperty(String name, number value);`
- `void addProperty(String name, char value);`

Usage

```
directoryObject.addProperty("eruid", "jdoe");
```

The `getProperty` method returns a Java array of objects that is stored in a JavaScript `JSONArray` object. Unlike a standard JavaScript array, `JSONArray` objects are used to access members of a Java array. Because Java arrays cannot be resized, the size of a `JSONArray` object cannot be changed. Also, `JSONArray` objects are typed. Setting a `JSONArray` element to the wrong type throws a JavaScript error.

In Security Identity Manager, a `JSONArray` object cannot be passed directly back into a `addProperty` method. The `JSONArray` array might be converted into a standard JavaScript array as follows:

```
jsAliases = new Array();
myPerson = person.get();
aliases = myPerson.getProperty("eraliases");
for (i=0; i < aliases.length; i++) {
  jsAliases[i] = aliases[i];
}
jsAliases[aliases.length] = "myNewAlias";
myPerson.addProperty("eraliases", jsAliases);
person.set(myPerson);
```

DirectoryObject.dn

The field represents the distinguished name of the object.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

directoryObject.dn

Description

This read-only field is a string that provides the distinguished name of the object. If the object holds information that was not created, there is no value.

Usage

x = directoryObject.dn;

DirectoryObject.getChanges()

The method returns the changes made to the entity.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

directoryObject.getChanges()

Returns

An array of change objects. If there are no changes, an empty array is returned. Each element in the array is an `AttributeChangeOperation`.

Description

This method returns the changes made to the entity. These changes are represented by change objects with the following members:

attr

String name of the attribute that is being changed.

op

An integer that identifies the type of change that is being made. The enumerated values are 1 for add, 2 for replace, and 3 for remove.

values

An array of objects that must be either added, removed, or replaced.

The changes are returned as an array of these change objects. If there are no changes, an empty array is returned.

Usage

```
changes = directoryObject.getChanges();
for (i = 0; i < changes.length; i++) {
  name = changes[i].attr;
  if (changes[i].op == 1) {
    ...
  } else if (changes[i].op == 2) {
    ...
  } else {
    ...
  }
};
```

DirectoryObject.getProperty()

The method returns the values of the property specified by the given name.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

directoryObject.getProperty(name)

Arguments**name**

String representing the name of the property to return.

Returns

Either a `String` or a `DirectoryObject`. The type of object returned depends on the property obtained. If the specified property does not exist, an empty array is returned.

Description

This method returns the values of the property specified by the given name. The type of object returned depends on the property obtained. If the specified property does not exist, an empty array is returned.

The property name can be either an attribute name or a relationship name. For an attribute name, the return is a `String[]`; for a relationship name, an array of `DirectoryObjects` is returned. If an attribute and a relationship have the same name, then the attribute is returned. For example, an `Account` entity has both an `owner` attribute and an `owner` relationship.

Usage

When operating on an account, for example, the user ID property can return a `String`, where the owner property can return another entity (`DirectoryObject`). The owner entity can then be operated on with the `getProperty()` member to obtain information about it.

```
userids = directoryObject.getProperty("eruid");
if (userids.length > 0)
    userid = userids[0];
owner = directoryObject.getProperty("owner");
if (owner.length > 0)
    ownerName = owner.getProperty("name")[0];
```

Note: These statements assume there is at least one value returned. If no values are returned, an array indexing violation occurs.

The `getProperty` method returns a Java array of objects that is stored in a JavaScript `JavaArray` object. Unlike a standard JavaScript array, `JavaArray` objects are used to access members of a Java array. Since Java arrays cannot be resized, the size of a `JavaArray` object cannot be changed. Also, `JavaArray` objects are typed. Setting a `JavaArray` element to the wrong type throws a JavaScript error.

DirectoryObject.getPropertyAsDate()

The method returns the value of the property specified by the given name as a date object.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
directoryObject.getPropertyAsDate(name)
```

Arguments

name

String representing the name of the property to return.

Returns

A `Date` object. If the specified property does not exist, current date is returned.

Description

This method returns the value of the property specified by the given name as a date object. If the specified property does not exist, current date is returned.

Usage

```
var createDate = directotyObject. getPropertyAsDate("ercreatedate");
```

DirectoryObject.getPropertyAsString()

The method returns the value of the property specified by the given name as a string.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
directoryObject.getPropertyAsString(name)
```

Arguments**name**

String representing the name of the property to return.

Returns

A `String` object. If the specified property does not exist, empty is returned. If the specified property has multiple values, only the first value is returned.

Description

This method returns the value of the property specified by the given name as a `String` object. If the specified property does not exist, empty string is returned. If the specified property has multiple values, only the first value is returned.

Usage

```
var name = directotyObject.getPropertyAsString("erservicename");
```

DirectoryObject.getPropertyNames()

The method returns a list of properties, such as attributes and relationships.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
directoryObject.getPropertyNames()
```

Returns

An array of `Strings`.

Description

This method returns a list of properties as an array of `Strings`. A property can be either an attribute or a relationship.

Usage

```
properties = directoryObject.getPropertyNames();
```

DirectoryObject.name

The field represents the logical name of the object.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
directoryObject.name
```

Description

This read-only field is a string that provides the logical name of the object, represented as a `String`. The physical attribute used as the name can be different for each type of object.

Usage

```
x = directoryObject.name;
```

DirectoryObject.profileName

The field returns the object profile name.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
directoryObject.profileName()
```

Description

This read-only field is a string that provides the profile name of the object, represented as a `String`.

Usage

```
x = directoryObject.profileName;
```

DirectoryObject.removeProperty(name)

The method removes the property specified by the given name.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
directoryObject.removeProperty(name)
```

Arguments

name

String representing the name of the property to remove.

Description

This method removes the specified property. This change is made locally to the script environment, not to the data store. The property name can be either an attribute name or a relationship name.

Usage

```
directoryObject.removeProperty("eruid");
```

DirectoryObject.removeProperty(name,value)

The method removes the value from the specified property.

Availability

IBM Security Identity Manager 6.0.0.3

Synopsis

```
directoryObject.removeProperty(name,value)
```

Arguments

name

String representing the name of the property to be modified.

value

The value to remove from the property.

Description

This method removes the specified value from property if it exists. This change is made locally to the script environment, not to the data store. The value can be a single value object or an array of objects. For multivalued objects, removeProperty(name,value) removes the values from the specified property in the directory object. The object type of the value (syntax) must be compatible with the syntax of the specified property. This method is available for the following data types:

- void removeProperty(String name, Collection value);
- void removeProperty(String name, Date value);
- void removeProperty(String name, Map value);
- void removeProperty(String name, boolean value);
- void removeProperty(String name, byte value);
- void removeProperty(String name, String value);
- void removeProperty(String name, Number value);

Usage

```
var directoryObject = Entity.get();
directoryObject.removeProperty("eraliases", "jdoe");
Entity.set(directoryObject);
```


DirectoryObject.setProperty()

The method sets the value of the specified property.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
directoryObject.setProperty(name, value)
```

Arguments

name

String representing the name of the property to be created or modified.

value

The value to set the property to.

Description

This method changes the value of the specified property, or adds the specified property if it does not exist. This change is made locally to the script environment, not to the data store. The value can be a single value object or an array of objects. The value type (syntax) of object must be compatible with the syntax of the specified property. This method is available for the following data types:

- `void setProperty(String name, Collection value);`
- `void setProperty(String name, Date value);`
- `void setProperty(String name, Map value);`
- `void setProperty(String name, boolean value);`
- `void setProperty(String name, byte value);`
- `void setProperty(String name, String value);`
- `void setProperty(String name, number value);`
- `void setProperty(String name, char value);`

Usage

```
directoryObject.setProperty("eruid", "jdoe");
```

The `getProperty` method returns a Java array of objects that is stored in a JavaScript `JSONArray` object. Unlike a standard JavaScript array, `JSONArray` objects are used to access members of a Java array. Since Java arrays cannot be resized, the size of a `JSONArray` object cannot be changed. Also, `JSONArray` objects are typed. Setting a `JSONArray` element to the wrong type throws a JavaScript error.

In IBM Security Identity Manager, a `JSONArray` object cannot be passed directly back into a `setProperty` method. The `JSONArray` array into a standard JavaScript array as follows:

```
jsAliases = new Array();
myPerson = person.get();
aliases = myPerson.getProperty("eraliases");
for (i=0; i < aliases.length; i++) {
    jsAliases[i] = aliases[i];
}
jsAliases[aliases.length] = "myNewAlias";

myPerson.setProperty("eraliases", jsAliases);
person.set(myPerson);
```

EmailContext

The object provides access to contextual information specific to a type of notification that is sent.

Some methods for accessing information change are based upon the listed notification types. (The Reminder/Approval/RFI/WorkOrder/ComplianceAlert Notification does not support this.)

- Activity Timeout Template

- Change Account Template
- Compliance Template
- New Account Template
- New Password Template
- Process Completion Template
- Process Timeout Template
- Restore Account Template
- Suspend Account Template

Availability

IBM Tivoli Identity Manager 4.6

Provided by

`com.ibm.itim.workflow.script.EmailContextExtension`

Synopsis

Call methods documented in this section as an `EmailContext` object. For example:

```
notificationActivity=EmailContext.getActivity();
owner=EmailContext.getAccountOwnerName()
```

Common methods

These methods are available for all types of notifications:

getActivity()

Returns information about the most recent running activity. (Returns the `ActivityInfoOC` Java Object. To get the activity information in JavaScript object, use the object, 'activity'.

getActivity(java.lang.String actDefID)

Returns information about the activity with the specified definition ID. (Returns the `ActivityInfoOC` Java Object.) This obtains information by using the `Process.$dataName.get()` workflow process. To get the activity information in JavaScript object, use 'process.getActivity(java.lang.String actDefID)'.

getParentProcess()

Returns information about the parent process of the currently running process. (Returns the `ProcessInfoOC` Java object.) To get the process information of the parent process in JavaScript object, use 'process.getParent()'.

getProcess()

Returns the information about the currently running process. (Returns the `ProcessInfoOC` Java object.) To get the process information of the parent process in JavaScript object, use the object, 'process'.

getRootProcess()

Returns information about the root process of the current running process. (Returns the `ProcessInfoOC` Java object.) To get the process information of the parent process in JavaScript object, use 'process.getRootProcess ()').

Account notification methods

These methods are available for all types of account notifications:

getAccountOwnerName()

Returns the account owner name for the account.

getAccountServiceName()

Returns the account service name for the account.

getAccountServiceProfileName()

Returns the account service profile name for the account.

getAccountUserId()

Returns the account user ID for the account.

hasNewAccess()

Returns true if the account has new access and false otherwise.

hasRemovedAccess()

Returns true if the account removed access and false otherwise.

getAccountNewAccessAsString()

Returns String that contains list of new access separated by commas.

getAccountNewAccessList()

Returns Array of String that contains the new access.

getAccountRemovedAccessAsString()

Returns a string that contains the list of removed access separated by commas.

getAccountRemovedAccessList()

Returns Array of String that contains the list of removed access.

Account Suspend/Deprovisioning Notification Methods:

These methods are only available for all types of account suspend/deprovision notifications:

getAction()

Returns the action taken against the service (resource) itself.

getReason()

Returns a descriptive reason for the deprovision.

Account New/Modify/Restore Notification Methods:

These methods are only available for all types of notifications for new, modified, and restored accounts:

showPassword()

Returns whether to display the password when the user is notified of their new account.

getAccountPassword()

Returns the account password for the account. .

getPasswordExpirePeriod()

Returns the password delivery expiration period.

getPasswordRetrievalUrl()

Returns the password delivery URL in order to retrieve the password with the accounts shared secret.

getTransactionId()

Returns the password delivery transaction ID for picking up the password created for this account.

Account Password Change Notification Methods:

These methods are available for all types of account password change notifications:

getAccountPassword()

Returns the account password for the account.

getPasswordExpirePeriod()

Returns the password delivery expiration period.

getPasswordRetrievalUrl()

Returns the password delivery URL in order to retrieve the password with the accounts shared secret.

getTransactionId()

Returns the password delivery transaction ID for picking up the password created for this account.

Enrole

The object contains the general methods.

Availability

- All JavaScript contexts

- IBM Security Identity Manager Version 6.0
- IBM Tivoli Identity Manager Version 4.x

Provided by

`com.ibm.itim.script.extensions.EnroleExtension`

Methods

generatePassword()

Generates a password for a specific service.

getAttributeValue()

Get a single value attribute value.

getAttributeValues()

Get a multi-valued attribute value.

localize()

Localized message specified in <Message> XML format.

log()

Logs a message to the IBM Security Identity Manager log at ERROR level.

logError()

Logs the specified text to the IBM Security Identity Manager message log (`msg.log`) at ERROR level.

logInfo()

Logs the specified text to the IBM Security Identity Manager message log (`msg.log`) at INFO level.

logWarning()

Logs the specified text to the IBM Security Identity Manager message log (`msg.log`) at WARN level.

toGeneralizedTime()

Converts a time or date to generalized time format.

toMilliseconds()

Converts a String in generalized time format to an integer value in milliseconds.

traceMax()

Logs the specified text to the IBM Security Identity Manager trace log (`trace.log`) at DEBUG_MAX level.

traceMid()

Logs the specified text to the IBM Security Identity Manager trace log (`trace.log`) at DEBUG_MID level.

traceMin()

Logs the specified text to the IBM Security Identity Manager trace log (`trace.log`) at DEBUG_MIN level.

Description

Provides some common utilities for use in many different scripting contexts.

Enrole.generatePassword()

The method generates a new valid password for an account.

Availability

`generatePassword()` requires a service to work, so `generatePassword()` is only available when the `ServiceExtension` is used.

Synopsis

`Enrole.generatePassword()`

Returns

A String that is a valid password for the `ServiceDirectoryObject` stored in the "service" variable.

Description

This method generates a new valid password for a service.

Enrole.getAttributeValue()

The method retrieves the attribute's value.

Availability

Deprecated as of IBM Tivoli Identity Manager 4.3. Replace with `DirectoryObject.getProperty()`

Synopsis

```
Enrole.getAttributeValue(name, defaultValue)
```

Arguments**name**

String representing the name of the property to return.

defaultValue

Default value to return if there is no value to return.

Returns

An Object. The type of object returned depends on the property obtained. If the specified property does not exist, the default value is returned.

Description

This method retrieves the value of the specified property.

Enrole.getAttributeValues()

The method retrieves a multi-valued attribute value.

Availability

Deprecated as of IBM Tivoli Identity Manager 4.3. Replace with `DirectoryObject.getProperty()`

Synopsis

```
Enrole.getAttributeValues(name)
```

Arguments**name**

String representing the name of the property to return.

Returns

An array of objects. The type of object returned depends on the property obtained. If the specified property does not exist, an empty array is returned.

Description

This method retrieves the value of the specified property.

Enrole.localize()

The method localizes a message specified in <Message> XML format.

Availability

IBM Tivoli Identity Manager 5.0

Synopsis

```
Enrole.localize(String xmlMsg, String localStr)
```

Arguments**xmlMsg**

A message specified in XML.

localStr

A String that represents the locale to be used for globalization.

Returns

AA localized message.

Description

This method globalizes an XML message to the specified locale.

Enrole.log()

The method logs messages to the IBM Security Identity Manager message log (`msg.log`).

Availability

IBM Tivoli Identity Manager 4.6

Synopsis

```
Enrole.log(category, message);
```

Arguments**category**

The category of the log entry, entered as a String. The category argument can be used or it can be left empty, but the argument must not be null.

message

The message to be logged, entered as a String.

Description

Logs a message to the IBM Security Identity Manager log at error level.

Usage

```
var roleDN = ..;(DN of role)
var role = new Role(roleDN);

// Put next statement on one line

Enrole.log("script", "The role name is
"+ role.getProperty("errolename")[0]);
```

Use the following new methods in IBM Security Identity Manager Version 6.0 to provide greater adaptability, control, or flexibility over the `Enrole.log()` method:

- [logError\(\)](#)
- [logInfo\(\)](#)
- [logWarning\(\)](#)
- [traceMax\(\)](#)
- [traceMid\(\)](#)
- [traceMin\(\)](#)

Enrole.logError()

The method logs text messages to the IBM Security Identity Manager message log (`msg.log`) with a message severity level of ERROR.

Availability

IBM Security Identity Manager Version 6.0

Synopsis

```
Enrole.logError(component, method, message);
```

Arguments**component**

The component of the log entry, entered as a String. The component can be any string. Logging can be controlled for components by setting specific log levels in the `enRoleLogging.properties` file.

method

The string to display in the "Method" record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the message log to be written to the log file.

Description

Writes an error message to the IBM Security Identity Manager message log (`msg.log`).

Usage

An example to write a `msg.log` message at ERROR level with the component name `com.ibm.myExtension` and the method name `postScriptOfAccountCreate`:

```
var userName = "Joe";
// below is a single line
Enrole.logError("com.ibm.myExtension","postScriptOfAccountCreate",
"Recording error message after unsuccessful account creation for user "
+ userName + ".");
```

Enrole.logInfo()

The method logs text messages to the IBM Security Identity Manager message log (`msg.log`) with a message severity level of INFO.

Availability

IBM Security Identity Manager Version 6.0

Synopsis

```
Enrole.logInfo((component, method, message));
```

Arguments**component**

The component of the log entry, entered as a String. The component can be any string. Logging can be controlled for components by setting specific log levels in the `enRoleLogging.properties` file.

method

The string to display in the "Method" record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the message log to be written to the log file.

Description

Writes an error message to the IBM Security Identity Manager message log (`msg.log`).

Usage

An example to write a `msg.log` message at INFO level with the component name `com.ibm.myExtension` and the method name `postScriptOfAccountCreate`:

```
var userName = "Joe";
// below is a single line
Enrole.logInfo("com.ibm.myExtension","postScriptOfAccountCreate",
"Recording information message after account creation for user " + userName +
".");
```

Enrole.logWarning()

The method logs text messages to the IBM Security Identity Manager message log (`msg.log`) with a message severity level of WARN.

Availability

IBM Security Identity Manager Version 6.0

Synopsis

```
Enrole.logWarning((component, method, message));
```

Arguments

component

The component of the log entry, entered as a String. The component can be any string. Logging can be controlled for components by setting specific log levels in the `enRoleLogging.properties` file.

method

The string to display in the "Method" record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the message log to be written to the log file.

Description

Writes a warning message to the IBM Security Identity Manager message log (`msg.log`).

Usage

An example to write a `msg.log` message at WARN level with the component name `com.ibm.myExtension` and the method name `postScriptOfAccountCreate`:

```
var userName = "Joe";  
    // below is a single line  
    Enrole.logWarning("com.ibm.myExtension","postScriptOfAccountCreate",  
"Recording warning message after account creation for user " + userName + ".");
```

Enrole.toGeneralizedTime()

The method converts a time or date to generalized time format.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

`Enrole.toGeneralizedTime(time)`

Arguments

time

Integer time in milliseconds or a Date object.

Description

This method converts a time or date to generalized time format. Can be used in either Identity Policies or in default entitlements.

Usage

```
genTime = Enrole.toGeneralizedTime(seconds);
```

Enrole.toMilliseconds()

The method converts a string in generalized time format to an integer value in milliseconds.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

`Enrole.toMilliseconds(genTime)`

Arguments

genTime

String in generalized time format.

Description

This method converts a String in generalized time format to an integer value in milliseconds.

Usage

```
seconds = Enrole.toMilliseconds(genTime);
```


Enrole.traceMax()

The method logs text messages to the IBM Security Identity Manager trace log (`trace.log`) with a message severity level of `DEBUG_MAX`.

Availability

IBM Security Identity Manager Version 6.0

Synopsis

```
Enrole.traceMax((component, method, message));
```

Arguments

component

The component of the log entry, entered as a String. The component can be any string. Logging can be controlled for components by setting specific log levels in the `enRoleLogging.properties` file.

method

The string to display in the "Method" record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the trace message to be written to the log file.

Description

Writes a `DEBUG_MAX` message to the IBM Security Identity Manager trace log (`trace.log`).

Usage

An example to write a `trace.log` message at `DEBUG_MAX` level with the component name `com.ibm.myExtension` and the method name `postScriptOfAccountCreate`:

```
var userName = "Joe";  
    // below is a single line  
    Enrole.traceMax("com.ibm.myExtension","postScriptOfAccountCreate",  
"Recording DEBUG_MAX trace message after account creation for user " + userName +  
".");
```

Enrole.traceMid()

Logs text messages to the IBM Security Identity Manager trace log (`trace.log`) with a message severity level of `DEBUG_MID`.

Availability

IBM Security Identity Manager Version 6.0

Synopsis

```
Enrole.traceMid((component, method, message));
```

Arguments

component

The component of the log entry, entered as a String. The component can be any string. Logging can be controlled for components by setting specific log levels in the `enRoleLogging.properties` file.

method

The string to display in the "Method" record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the trace message to be written to the log file.

Description

Writes a `DEBUG_MID` message to the IBM Security Identity Manager trace log (`trace.log`).

Usage

An example to write a `trace.log` message at `DEBUG_MID` level with the component name `com.ibm.myExtension` and the method name `postScriptOfAccountCreate`:

```
var userName = "Joe";  
    // below is a single line  
    Enrole.traceMid("com.ibm.myExtension","postScriptOfAccountCreate",  
"Recording DEBUG_MID trace message after account creation for user " + userName +  
".");
```

Enrole.traceMin()

The method logs text messages to the IBM Security Identity Manager trace log (`trace.log`) with a message severity level of `DEBUG_MIN`.

Availability

IBM Security Identity Manager Version 6.0

Synopsis

```
Enrole.traceMin((component, method, message);
```

Arguments

component

The component of the log entry, entered as a `String`. The component can be any string. Logging can be controlled for components by setting specific log levels in the `enRoleLogging.properties` file.

method

The string to display in the "Method" record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the trace message to be written to the log file.

Description

Writes a `DEBUG_MIN` message to the IBM Security Identity Manager trace log (`trace.log`).

Usage

An example to write a `trace.log` message at `DEBUG_MIN` level with the component name `com.ibm.myExtension` and the method name `postScriptOfAccountCreate`:

```
var userName = "Joe";  
    // below is a single line  
    Enrole.traceMin("com.ibm.myExtension","postScriptOfAccountCreate",  
"Recording DEBUG_MIN trace message after account creation for user " + userName +  
".");
```

Error

This object contains a script error description to notify the calling code of an exceptional runtime condition.

When an error is returned from a script evaluation, it is converted to a Java exception and thrown from the script evaluator class.

Availability

IBM Tivoli Identity Manager 4.6.x

Provided by

`com.ibm.itim.script.extensions.EnroleExtension`

Methods

setMessage()

Sets the message for the error.

getMessage()

Retrieves the error message for the error.

setErrorCode()

Sets the error code for the error.

getErrorCode()

Retrieves the error code for the error.

Usage

```
var sn = subject.getProperty("sn");
if(sn == null || sn.length == 0) {
    error.setMessage("sn was missing");
    return error;
} else {
    return sn[0];
}
```

Error.setMessage()

The method sets the message for the error.

Availability

IBM Tivoli Identity Manager 4.6.x

Synopsis

```
error.setMessage(String msg)
```

Arguments**msg**

String representing the message to be set.

Description

This method sets the text for an error message. The function takes in one String parameter.

Usage

```
error.setMessage("sn was missing");
```

Error.getMessage()

The method retrieves the message set for an error.

Availability

IBM Tivoli Identity Manager 4.6.x.

Synopsis

```
error.getMessage()
```

Returns

String message for an error.

Description

This method retrieves the text of an error message.

Usage

```
messageValue = error.getMessage();
```

Error.setErrorCode()

The method sets the error code for the error.

Availability

IBM Tivoli Identity Manager 4.6.x.

Synopsis

```
error.setErrorCode(int code)
```

Arguments

code

Integer representing the error code.

Description

This method sets the error code for an error message. The function takes in one **Int** parameter.

Usage

```
error.setErrorCode(1);
```

Error.getErrorCode()

The method retrieves the error code set for an error.

Availability

IBM Tivoli Identity Manager 4.6.x.

Synopsis

```
error.getErrorCode()
```

Returns

Integer value for an error code.

Description

This method retrieves the error code of an error message.

Usage

```
errorCodeValue = error.getErrorCode();
```

ExtendedPerson

This object extends the Person object with the ownership type information for account adoption.

Availability

IBM Security Identity Manager Version 6.0.

Inherited from

Person.

Provided by

```
com.ibm.itim.script.extensions.model.PersonModelExtension
```

Ownership type

INDIVIDUAL

String constant represents the default ownership type.

Constructor

```
new ExtendedPerson(dn)
```

Arguments

DN

DN string of a specific person entity.

Returns

The new ExtendedPerson object that represents a person with the DN and INDIVIDUAL ownership type.

```
new ExtendedPerson(dn, ownershipType)
```

Arguments

DN

DN string of a specific person entity.

ownershipType

String representing one of the ownership types configured in IBM Security Identity Manager.

Returns

The new `ExtendedPerson` object that represents a person with the DN and ownership type. If the ownership type is invalid, it throws `ScriptException`.

```
new ExtendedPerson(person)
```

Arguments**person**

Person object.

Returns

The new `ExtendedPerson` object that represents the person with the `INDIVIDUAL` ownership type.

```
new ExtendedPerson(person, ownershipType)
```

Arguments**person**

Person object.

ownershipType

String representing one of the ownership types configured in IBM Security Identity Manager.

Returns

The new `ExtendedPerson` object that represents the person with the ownership type. If the ownership type is invalid, it throws `ScriptException`.

Methods**getOwnershipType()**

Returns the ownership type.

setOwnershipType()

Sets the ownership type.

ExtendedPerson.getOwnershipType()

The method return the ownership type as a string.

Availability

IBM Security Identity Manager Version 6.0.

Synopsis

```
ExtendedPerson.getOwnershipType()
```

Returns

String.

Description

This method returns the ownership type.

Usage

```
var ownershipType = extendedPerson.getOwnershipType();
```

ExtendedPerson.setOwnershipType()

The method sets the value of the ownership type.

Availability

IBM Security Identity Manager Version 6.0.

Synopsis

```
ExtendedPerson.setOwnershipType(value)
```

Arguments

value

A string represents one of the ownership types configured in IBM Security Identity Manager.

Description

This method updates the ownership type. If the ownership type is invalid, it throws `ScriptException`.

Usage

```
var extendedPerson.setOwnershipType("System");
```

IdentityPolicy

The object represents the identity policy entity.

Availability

IBM Tivoli Identity Manager 4.x
Identity Policy context

Provided by

`com.ibm.itim.policy.script.IdentityPolicyExtension`

Methods

getNextCount()

Returns a number that can be appended to the end of a user name to make that user name unique.

userIDExists()

Checks if requested UID is already in use.

Description

This object represents a IBM Security Identity Manager Policy entity.

IdentityPolicy.getNextCount()

The method gets a number that can be appended to the end of a user name to make that user name unique. `ServiceExtension` must be loaded for `getNextCount()` to work.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
IdentityPolicy.getNextCount(baseId)
```

Arguments

baseId

The base user name.

Returns

A number that can be appended to the end of a user name to make the user name unique. Returns -1 if the user name is already unique and -2 if an error occurs.

Description

This method checks whether requested UID is already in use.

Usage

```
num = IdentityPolicy.getNextCount(baseId);  
return baseId + num;
```

IdentityPolicy.userIDExists()

The method checks if the requested UID is in use.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

```
IdentityPolicy.userIDExists(uid, checkAllServices, checkRecycleBin)
```

Arguments

uid

User identity.

checkAllServices

If set to true, all service instances are checked to see whether the uid is used on an account of any service type. If set to false, only the target service instance is checked. This argument is optional. Default value is false.

checkRecycleBin

If set to true, the recycle bin is checked for any deleted accounts. This parameter is intended to work in conjunction with the **checkAllServices** parameter. Set this parameter true only when the **checkAllServices** parameter is also set to true. This argument is optional. Default value is false.

Returns

True if the user ID exists, false otherwise.

Description

This method checks whether the requested UID is in use.

Usage

```
// To create a user ID without checking for it in the recycle bin but
// checking it against all services.
tf = IdentityPolicy.userIDExists("jason_jones", true, false);
```

PackagedApprovalDocument

A relevant data object used in multi-item approval, used exclusively in user recertification workflows. This object is made up of multiple PackagedApprovalItem objects from the user recertification approval and allows for searching and retrieving recertification items.

Availability

IBM Tivoli Identity Manager 5.1.

Constructor

```
new PackagedApprovalDocument()
```

Constructs an empty approval document object. Instances might also be obtained in user recertification workflow and notifications by accessing the relevant data item "ApprovalDocument." For example, ApprovalDocument.get() returns a PackagedApprovalDocument in a user recertification workflow.

Properties

TYPE_ACCOUNT

A constant for approval items that are accounts.

TYPE_GROUP

A constant for approval items that are groups on other services but are not defined as an access.

TYPE_GROUP_ACCESS

A constant for approval items that are groups and also defined as accesses.

TYPE_ITIM_GROUP

A constant for approval items that are groups on services of type ITIM Service.

TYPE_ROLE

A constant for approval items that are roles.

Methods

addItem(PackagedApprovalItem item)

Returns a Boolean flag that indicates that a `PackagedApprovalItem` item is added in this approval document.

containsDecisionCode(decisionCode)

Returns a Boolean flag that indicates whether any of the items in this document that allow for decisions contain the specified decision code string. Valid decision codes are `activity.APPROVED` and `activity.REJECTED`.

getDecisionItemCountByType(type)

Returns the number of items in this document that support decisions and have the specified type. The types are defined as constants on this object, such as `TYPE_ROLE` or `TYPE_ACCOUNT`. This method considers all approval items in the document that supports decisions, including children of top-level items.

getDecisionItemCountByType(type, includeChildren)

Returns the number of items in this document that support decisions and have the specified type. The types are defined as constants on this object, such as `TYPE_ROLE` or `TYPE_ACCOUNT`. Depending on the value the `includeChildren` flag, this method might also count all items in this document, including any items that are children of the top-level items.

getItemCountByType(type)

Returns the number of items in this document that are of the specified type. The types are defined as constants on this object, such as `TYPE_ROLE` or `TYPE_ACCOUNT`. This method considers all approval items in the document, including children of top-level items.

getItemCountByType(type, includeChildren)

Returns the number of items in this document that are of the specified type. The types are defined as constants on this object, such as `TYPE_ROLE` or `TYPE_ACCOUNT`. Depending on the value of the `includeChildren` flag, this method might also count all items in this document, including any items that are children of the top-level items.

getItemCountByTypeAndDecision(type, decisionCode)

Returns the number of items in this document that are of the specified type and that allow for decisions and contain the specified decision code string. The types are defined as constants on this object, such as `TYPE_ROLE` or `TYPE_ACCOUNT`. Valid decision codes are `activity.APPROVED` and `activity.REJECTED`. This method considers only top-level approval items and does not count the children of those items.

getItemsByType(type)

Returns the top-level items in this approval document that have the specified type as an array of `PackagedApprovalItem` objects. The types are defined as constants on this object, such as `TYPE_ROLE` or `TYPE_ACCOUNT`.

getItemsByTypeAndDecision(type, decisionCode)

Returns the top-level items in this approval document that have the specified type. If decisions are allowed, it contains the specified decision code string as an array of `PackagedApprovalItem` objects. The types are defined as constants on this object, such as `TYPE_ROLE` or `TYPE_ACCOUNT`. Valid decision codes are `activity.APPROVED` and `activity.REJECTED`.

removeItem(String identifier)

Returns a Boolean flag that indicates that a `PackagedApprovalItem` that corresponds to the `identifier` is removed from this approval document.

setDecisionCodeForAllItems(decisionCode)

Sets the specified `decisionCode` on all items in this document, including any children of top-level items. Any items that do not support decisions are skipped. Valid decision codes are `activity.APPROVED` and `activity.REJECTED`.

Description

The object represents the multi-item approval document in the JavaScript environment.

PackagedApprovalItem

A relevant data object used in IBM Security Identity Manager multi-item approval, used exclusively in user recertification workflows. This object represents the individual roles, accounts, and groups that are presented to the user during the recertification process. Some items might contain a decision code that indicates the choice of the approvers for that item. Each item also contains a list of children that is used to represent relationships between accounts and groups.

Availability

IBM Tivoli Identity Manager 5.1.

Constructor

`new PackagedApprovalItem(itemType, value)`

Constructs a `PackagedApprovalItem` object that does not support decisions and is read-only during the recertification approval activity. The parameters are an item type constant and `value`, where the `value` is a `DirectoryObject` that matches the type, such as `Role` or `Account`.

`new PackagedApprovalItem(itemType, value, decisionCode)`

Constructs a `PackagedApprovalItem` object that supports decisions. The **`decisionCode`** parameter is either `activity.APPROVED`, `activity.REJECTED`, or `null`, where `null` indicates that a decision is required but not yet specified.

For example:

```
new PackagedApprovalItem(PackagedApprovalDocument.TYPE_ACCOUNT, acctObj)

new PackagedApprovalItem(PackagedApprovalDocument.TYPE_ROLE, roleObj,
activity.APPROVED)
```

Properties

DECISION_NOT_APPLICABLE

A constant for approval items that do not support decisions and are read-only during the recertification.

Methods

getItemTypeString()

Returns the type of the item, where the constant values are defined on the `PackagedApprovalDocument` object (`TYPE_ROLE`, `TYPE_ACCOUNT`, `TYPE_GROUP`, `TYPE_GROUP_ACCESS`).

getDecisionCode()

Returns the decision code for this item, where the possible values are `activity.APPROVED` and `activity.REJECTED`. This method might also return `PackagedApprovalItem.DECISION_NOT_APPLICABLE` if this item is for informational purposes only, or `null` if the decision is not yet specified.

getValue()

Returns a `DirectoryObject` for the role, account, or group of this item.

getChildItems()

Returns an array of `PackagedApprovalItem` objects that are the children of this item. For example, account items can have groups as their children.

getChildItemsByDecision(decisionCode)

Returns an array of `PackagedApprovalItem` objects that are the children of this item and have the specified decision code, such as `activity.APPROVED` or `activity.REJECTED`.

Description

The Object represents the Security Identity Manager multi-item approval element in the JavaScript environment.

Participant

Workflow participant entity, which specifies an activity participant. In a mail node, this entity specifies the mail recipient.

Participant applies only to manual activity types, including `Approval`, `RFI`, `WorkOrder`, and `Mail`.

The participant of an activity can be specified during workflow design as Custom Defined Participant. In this case, the Participant JavaScript object can be used to construct the appropriate participant based on the process context.

Availability

IBM Tivoli Identity Manager 4.x

Provided by

`com.ibm.itim.workflow.script.WorkflowExtension`

Constructor

`new Participant(type, dn)`

Arguments**type**

Code that categorizes the participant type.

dn

Optional DN of a specific entity.

Returns

The newly created and initialized participant object.

Constructor for custom self approval

`new Participant(type, boolean)`

Arguments**type**

Type is either `REQUESTEE` or `REQUESTOR`.

boolean

Self approval values. `true` enables the custom self approval workflow. `false` disables the custom self approval workflow.

Returns

The newly created and initialized participant object.

Properties**implementation**

This property contains JavaScript that returns participant when the participant type is Custom.

name

Identifies the participant.

type

Code that categorizes the participant type.

Description

The participant specifies an activity participant. Participant applies only to manual activity types, including `Approval`, `RFI`, `Work Order` and `Mail` activities. The participant of an activity or recipient of a mail activity can be specified during workflow design as Custom Defined Participant. In this case,

the Participant JavaScript object can be used to construct the appropriate participant based on the process context.

Usage

```
//assume person is one of the relevant data in the workflow
//process for the target user involved
if( person.get().getProperty("title")[0]=="Manager" )
    return new Participant(ParticipantType.SYSTEM_ADMIN);
else
    return new Participant(ParticipantType.SUPERVISOR);

//assume person is one of the relevant data in the workflow
//process for the target user involved
if( person.get().getProperty("title")[0]=="Manager")
    return new Participant(ParticipantType.USER, person.get().dn);
else
    ...
```

Participant.implementation

The field represents the custom defined participant.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

participant.implementation

Description

This read-only field is a string that provides the custom-defined participant, which contains the JavaScript code to return the participant.

Usage

x = participant.implementation;

Participant.name

The field represents the DN of the participant.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

participant.name

Description

This read-only field is a Distinguished Name that identifies the participant. It is only applicable to participant types of ROLE and USER.

Usage

x = participant.name;

Participant.type

the field represents the code that categorizes the participant type.

Availability

IBM Tivoli Identity Manager 4.x.

Synopsis

participant.type

Description

This read-only field is a string that represents a code that categorizes the participant type.

Usage

x = participant.type;

ParticipantType

An entity that represents the workflow participant type constants.

Availability

IBM Tivoli Identity Manager 4.x.

Provided by

com.ibm.itim.workflow.script.WorkflowExtension

Properties

DOMAIN_ADMIN

Participant type for the domain administrator of the organizational container. It is associated with the Subject account service (as specified by the Subject context in the workflow properties window).

```
participant = new Participant(ParticipantType.DOMAIN_ADMIN);
```

REQUESTOR

Participant type for the person that initiated the request. If a person initiates a change request for a person that triggers policy enforcement, the participant is the person that requests the change. For data loads, the participant is the system user. By setting the following property in `$ISIM_HOME/data/enRole.properties` to **true**, an approval request that has the requester as the participant is automatically approved by the system:

```
participant = new Participant(ParticipantType.REQUESTOR);
```

Enables the self approval by requester for specific workflow even though the global configuration is set to disable the self approval. By setting the value of boolean to `true`, self approval for specific workflow is enabled.

```
participant = new Participant(ParticipantType.REQUESTOR, boolean);
```

REQUESTEE

Participant type for the person designated as the requestee in the owner field of the relevant data.

```
participant = new Participant(ParticipantType.REQUESTEE);
```

Enables the self approval by requestee for specific workflow even though the global configuration is set to disable the self approval. By setting the value of boolean to `true`, self approval for specific workflow is enabled.

```
participant = new Participant(ParticipantType.REQUESTEE, boolean);
```

ROLE

Participant type for a specific organizational role. All user members of the role and its child roles are notified and are eligible to respond, the first response triggers the workflow to continue. In other words, specifying a role cannot be used to require multiple participants to approve the request.

```
participant = new Participant(ParticipantType.ROLE, roleDN);
```

ROLE_OWNER

Participant type for the owner of the role (if specified). The Role is resolved based on the owners specified in the `OrgRole` listed as an input parameter for the operational workflow operation. If there is no `OrgRole` specified as an input parameter in the workflow, the participant is not resolved.

```
participant = new Participant(ParticipantType.ROLE_OWNER);
```

SERVICE_OWNER

Participant type for the owner of the service (if specified). The Service is resolved based on the account object from the workflow relevant data that is marked as "Subject" in the properties window.

```
participant = new Participant(ParticipantType.SERVICE_OWNER);
```

SOD_POLICY_OWNER

Participant type for the owners of the separation of duty policy (if specified). The owners are resolved based on the SeparationOfDutyRuleViolation object from the workflow relevant data that is marked as "Subject" in the properties window. If there is no SeparationOfDutyRuleViolation specified as the Subject of the workflow, the participant is not resolved.

The SOD_POLICY_OWNER participant type is used only in the approveSoDViolation global operation.

```
participant = new Participant(ParticipantType.SOD_POLICY_OWNER);
```

SPONSOR

Participant type for the person designated as the sponsor with the sponsor relationship for the requestee (as marked in relevant data).

```
participant = new Participant(ParticipantType.SPONSOR);
```

SUPERVISOR

Participant type for the supervisor or manager of the requestee. If none is specified for the requestee, then the supervisor designated on the organizational container of the requestee becomes the participant. If no supervisor is specified for the organizational container of the requestee, then the next level up is checked for a supervisor. The search continues up the tree until the top of the organization is reached. If no supervisor is found, the participant is unresolved.

```
participant = new Participant(ParticipantType.SUPERVISOR);
```

SYSTEM_ADMIN

Participant type for a member of the Security Identity Manager System Administrator group.

```
participant = new Participant(ParticipantType.SYSTEM_ADMIN);
```

USER

Participant type for a specific person to respond to the request. The person must have a Security Identity Manager account.

```
participant = new Participant(ParticipantType.USER, userDN);
```

ITIM GROUP

Participant type for a specific ITIM group. Though all members of the group are notified, and all are eligible to respond, the first response triggers the workflow to continue. Specifying a group cannot be used to require multiple participants to approve the request.

```
participant = new Participant(ParticipantType.GROUP, groupDN);
```

Description

This entity represents the workflow participant type constants.

Person

The object represents the person entity.

Availability

IBM Tivoli Identity Manager 4.x.

Provided by

com.ibm.itim.script.extensions.model.PersonModelExtension

Inherits From

DirectoryObject

Constructors**new Person(String dn)**

Arguments:

dn

The distinguished name of a specific person entry in the directory server.

Returns: A new Person object that represents the person with the given DN.

new Person(DirectoryObject directoryObject)

Arguments:

directoryObject

DirectoryObject to be contained in the person

new Person(DirectoryObjectEntity directoryObjectEntity)

Arguments:

directoryObjectEntity

DirectoryObjectEntity to be contained in the person

Methods**getAllAssignmentAttributes()**

Returns an array of the RoleAssignmentAttribute objects that are defined in all of authorized roles for this person. The authorized roles consist of both the direct roles for this person and also all of the parent roles of the direct roles.

getAndDecryptSynchPassword()

Decrypts and returns the decrypted synch password of the person entity in plain text.

Note: This method is available in the scripting context of IBM Security Identity Manager only if the **javascript.password.access.enabled** property is set to true in the *ISIM_HOME/data/scriptframework.properties* file.

getAndDecryptPersonPassword()

Decrypts and returns the decrypted person password of the person entity in plain text.

Note: This method is available in the scripting context of Security Identity Manager only if the **javascript.password.access.enabled** property is set to true in the *ISIM_HOME/data/scriptframework.properties* file.

getRoleAssignmentData()

Returns all role assignment data for the person.

getRoleAssignmentData(String roleAssignedDN)

Returns all role assignment data for the person for the specified role.

getRoles()

Returns an array of DirectoryObjects, each representing a role.

getNewRoles()

Returns an array of newly added roles for the person.

getNewRoles(boolean convertReplaceToAddDelete)

Returns an array of newly added static roles for the person.

getRemovedRoles()

Returns an array of removed roles for the person.

getRemovedRoles(boolean convertReplaceToAddDelete)

Returns an array of removed static roles for the person.

isInRole(String roleName)

Determines whether the person belongs to the role. Returns Boolean.

removeRole()

Removes the person from the specified role.

removeRoleAssignmentData(String roleAssignedDN)

Removes all role assignment data for the person from the specified role.

updateRoleAssignmentData(RoleAssignmentObject[] roleAssignmentObject)

Updates a person with the role assignment attribute value changes that are defined in the set of RoleAssignmentObjects.

Person.getAllAssignmentAttributes()

The method returns an array of the RoleAssignmentAttribute objects that are defined for all of authorized roles for this person. The authorized roles consist of both the direct roles for this person and also all the parent roles of the direct roles.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
person.getAllAssignmentAttributes()
```

Arguments

None

Description

This method is defined on the Person object. It returns an array of the RoleAssignmentAttribute objects that are defined in all of authorized roles for this person. The authorized roles consist of both the direct roles for this person and also all the parent roles of the direct roles. The method returns an empty array if no assignment attribute exists. RoleAssignmentAttribute objects contains role assignment attribute name, role name, and role DN.

Usage

```
//The script is used in a workflow, in which Entity is a person object.
var person = Entity.get();

//get assignment attributes of the person
var attributeList = person.getAllAssignmentAttributes();
if (attributeList.length == 0) {
    Enrole.log("script", "No assignment attribute for this role: "
        + role.name);
    return;
}

// print out the role assignment attribute name.
for (var i=0; i < attributeList.length; i++) {
    var roleAtr = attributeList[i];
    Enrole.log("script","attribute name-----: "+ roleAtr.getName());
}
```

Person.getAndDecryptSynchPassword()

The method decrypts and returns the decrypted sync password of the person entity in plain text.

Availability

IBM Tivoli Identity Manager 5.0.

Synopsis

```
person.getAndDecryptSynchPassword()
```

Arguments

None

Description

This method is defined on the Person object. It returns a string that represents the plain text sync password for the person that is used for synchronization. It decrypts and returns the decrypted sync password set in the person object. This function returns null if the sync password is not present. This method can be used in IBM Security Identity Manager scripting context if the

javascript.password.access.enabled property is set to true in the *ISIM_HOME/data/scriptframework.properties* file.

Usage

```
//The script is used in a workflow, in which Entity is a person object.
var person = Entity.get();
//get sync password set on the person
var synchPassword = person.getAndDecryptSynchPassword();
```

Person.getAndDecryptPersonPassword()

The method decrypts and returns the decrypted password of the person entity in plain text.

Availability

IBM Tivoli Identity Manager 5.0.

Synopsis

```
person.getAndDecryptPersonPassword()
```

Arguments

None

Description

This method is defined on the Person object. It returns a string that represents the plain text password for the person. It decrypts and returns the decrypted password set in the person object. This function returns null if the password is not present. This method can be used in IBM Security Identity Manager scripting context if the **javascript.password.access.enabled** property is set to true in the *ISIM_HOME/data/scriptframework.properties* file.

Usage

```
//The script is used in a workflow, in which Entity is a person object.
var person = Entity.get();
//get person password set on the person
var personPassword = person.getAndDecryptPersonPassword();
```

Person.getRoleAssignmentData()

The method returns all the role assignment data for the person, as an array of RoleAssignmentObject objects that contain the role assignment values, defined Role DN and assigned Role DN.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
person.getRoleAssignmentData()
```

Arguments

none

Description

This method is defined on the Person object. It returns an array of RoleAssignmentObject objects, containing the role assignment values, defined Role DN, and assigned Role DN. The method returns an empty array if no assignment data exists.

Usage

```
//The script is used in a workflow, in which Entity is a person object.
var person = Entity.get();
var assignmentObjects = person.getRoleAssignmentData();
if (assignmentObjects.length == 0) {
    Enrole.log("script", "There is no assignment values for " + person.name);
    return;
}
var str = "The number of role assignment objects returned from
person.getRoleAssignmentData(): " +
assignmentObjects.length + "\n";
for(var i=0; i<assignmentObjects.length; i++) {
    var obj = assignmentObjects[i];
    str += obj.toString() + "\n";
}
```



```
Enrole.log("script", "The assignment attribute data for person:"+
    person.name+" is:"+ str);
```

Person.getRoleAssignmentData(String roleAssignedDN)

The method returns all the role assignment data for the person. The data is an array of RoleAssignmentObject objects that contain the role assignment values, defined Role DN, and assigned Role DN for the specified assigned role.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
person.getRoleAssignmentData(String roleAssignedDN)
```

Arguments

roleAssignedDN

The distinguished name of the assigned role

Description

This method is defined on the Person object. It returns an array of RoleAssignmentObject objects, containing the role assignment values, defined Role DN, and assigned Role DN for a specified assigned role. The method returns an empty array if no assignment data exists.

Usage

```
//The script is used in a workflow, in which Entity is a person object.
var person = Entity.get();
var roleDNs = person.getProperty("erroles");
if(roleDNs.length == 0) {
    Enrole.log("script", person.name + " does not have any role");
    return;
}
// Get role assignment data for the first role.
var roleDN = roleDNs[0];
var role = new Role(roleDN);
var assignmentObjects = person.getRoleAssignmentData(roleDNs[0]);
if (assignmentObjects.length == 0) {
    Enrole.log("script", person.name + " does not have any assignment
objects for role: " + role.name);
    return;
}
var str = "The number of role assignment objects returned from
person.getRoleAssignmentData() for "
+ role.name + " : " + assignmentObjects.length + "\n";
for(var i=0; i<assignmentObjects.length; i++) {
    var obj = assignmentObjects[i];
    str += obj.toString() + "\n";
}
Enrole.log("script", str);
```

Person.getRoles()

The method returns roles assigned to a Person.

Availability

IBM Tivoli Identity Manager 4.6

Synopsis

```
person.getRoles()
```

Description

This method defined on the Person object returns an array of roles that the person belongs to. The return type is an array of entities, which are instances of role directory entity objects. The properties available on the Entity Objects are name and description.

Usage

```
// logs the names of all roles that a person belongs to
var per = person.get();
var rolesArray = per.getRoles();
if(rolesArray.length>0){
```

```

    Enrole.log("script", per.getProperty("cn")[0] +
        " belongs to following roles: ");

    for( var i=0; i<rolesArray.length;i++) {
        Enrole.log("script",
            rolesArray[i].getProperty("errolename")[0]);
    }
} else {
    Enrole.log("script", per.getProperty("cn")[0] +
        "does not belong to any roles");
}

```

Person.getNewRoles()

The method returns an array of newly added static roles for a Person.

Availability

IBM Tivoli Identity Manager 5.0

Synopsis

```
person.getNewRoles()
```

Description

This method defined on the person object returns an array of new static roles associated with the person. The return type is an array of `DirectoryObjects`,

Note: The person object is often a runtime object in memory, and these new static roles were not added to the directory.

Usage

```
var newRoles = per.getNewRoles();
```

Person.getNewRoles(boolean convertReplaceToAddDelete)

The method returns an array of newly added static roles for a Person.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
person.getNewRoles(boolean convertReplaceToAddDelete)
```

Description

This method defined on the person object returns an array of new static roles associated with the person. The return type is an array of `DirectoryObjects`.

Depending on how the person modification is triggered, the role changes get stored as REPLACE operation or ADD/DELETE operation.

When the method is invoked with a true parameter, the REPLACE operation is evaluated as ADD/DELETE and the method will return only the newly added roles.

When the method is invoked with a false parameter, if role changes are stored as REPLACE operation, the method will return the complete set of new roles. This will include the existing roles too.

Note: The person object is often a runtime object in memory, and these new static roles were not added to the directory.

Usage

```
var newRoles = per.getNewRoles(true);
```

Person.getRemovedRoles()

The method returns an array of removed static roles for the Person.

Availability

IBM Tivoli Identity Manager 5.0

Synopsis

```
person.getRemovedRoles()
```

Description

This method defined on the person object returns an array of static roles from which the person was removed. The return type is an array of `DirectoryObjects`.

Note: The person object is often a runtime object in memory, and these static roles were not removed from the directory.

Usage

```
var removedRoles = per.getRemovedRoles();
```

Person.getRemovedRoles(boolean convertReplaceToAddDelete)

The method returns an array of removed static roles for the `Person`.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
person.getRemovedRoles(boolean convertReplaceToAddDelete)
```

Description

This method defined on the person object returns an array of static roles from which the person was removed. The return type is an array of `DirectoryObjects`.

Depending on how the person modification is triggered, the role changes get stored as REPLACE operation or ADD/DELETE operation.

When the method is invoked with a true parameter, the REPLACE operation is evaluated as ADD/DELETE and the method will return only the removed roles.

When the method is invoked with a false parameter, if role changes are stored as REPLACE operation, the method will return the complete set of existing roles. This return includes the existing roles, which are not deleted.

Note: The person object is often a runtime object in memory, and these static roles were not removed from the directory.

Usage

```
var removedRoles = per.getRemovedRoles(true);
```

Person.isInRole()

The method evaluates whether a `Person` belongs to a role.

Availability

IBM Tivoli Identity Manager 4.6

Synopsis

```
person.isInRole(roleName)
```

Arguments

roleName

The name of the role to check.

Description

Given a person object and the name of the role, determine whether the person belongs to the role. If the role is not uniquely determined by the `roleName` parameter or if the person cannot be found, then return an error object.

Usage

```
// Check whether the person is in the role Manager and log a  
// message  
var per=person.get();
```

```

if(!per.isInRole("Manager")) {
    Enrole.log("script",per.getProperty("cn")[0] +
        "does not belong to role Manager");
} else {
    Enrole.log("script",per.getProperty("cn")[0] +
        "belong to role Manager");
}

```

Person.removeRole()

The method removes the person from the specified role.

Availability

IBM Tivoli Identity Manager 5.0

Synopsis

```
person.removeRole(role)
```

Arguments

role

Role object that represents the role from which the person is removed.

Description

Removes the person from the role.

Note: This operation removes only the role from the Person object in run time, and it does not remove the role from the directory.

Usage

```

//Remove the first role in the Person object
var roles = person.getRoles();
if (roles.length > 0) {
    person.removeRole(roles[0]);
}

```

Person.removeRoleAssignmentData()

The method removes all role assignment data of the person for an array of assigned Roles. It does not directly change data in the data source, but removes from memory the data inside the person object.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
person.removeRoleAssignmentData(String [] roleAssignedDNs)
```

Arguments

roleAssignedDNs

An array of distinguished names of the assigned role.

Description

This method is defined on the Person object. It removes all role assignment data of the person for an array of assigned roles.

Usage

```

//The script is used in a workflow, in which Entity is a person object.
var person = Entity.get();
var roleDNs = person.getProperty("erroles");
if(roleDNs.length == 0) {
    Enrole.log("script", person.name + " does not have any roles");
    return;
}

//remove the role assignment attribute.
person.removeRoleAssignmentData(roleDNs);

```

Person.updateRoleAssignmentData()

The method updates a person with the role assignment attribute value changes that are defined in the set of RoleAssignmentObjects. It does not directly change data in the data source, but updates (in memory) the data inside the person object.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
person.updateRoleAssignmentData(RoleAssignmentObject []  
roleAssignmentObject)
```

Arguments

roleAssignmentObject

A list of roleAssignmentObjects that contains the role assignment attribute value change set to be applied.

Description

This method is defined on the Person object. It updates a person with the role assignment attribute value changes that are defined in the set of RoleAssignmentObjects.

Usage

```
//The script is used in a workflow, in which Entity is a person object.  
var person = Entity.get();  
var roleDNs = person.getProperty("erroles");  
if(roleDNs.length == 0) {  
    Enrole.log("script", person.name + " does not have any role");  
    return;  
}  
  
//construct a new RoleAssignmentObject  
var assignmentObj = new RoleAssignmentObject(roleDNs[0], roleDNs[0]);  
assignmentObj.addProperty("attr_3", ["newv1", "newv2"]);  
person.updateRoleAssignmentData([assignmentObj]);
```

PersonSearch

The object searches for a person.

Availability

IBM Tivoli Identity Manager 4.x
Provisioning Policy context
Service Selection Policy context

Provided by

com.ibm.itim.script.extensions.model.PersonModelExtension

Constructor

```
new PersonSearch()
```

Returns

The newly created and initialized person search object.

Methods

searchByFilter()

Search for a person by a filter.

searchByURI()

Search for a person by URI in an organizational container.

Description

The entity implements the IBM Security Identity Manager PersonSearch class. The API Javadoc for this class is in the following directory:

```
$ISIM_HOME/extensions/version_number/api/com/ibm/itim/dataservices/model/domain/
```

PersonSearch.searchByFilter()

The method searches for a person by a filter.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
personSearch.searchByFilter(profileName, filter, scope)
```

Arguments

profileName

The name of the person profile to use.

filter

LDAP search filter that defines the criteria for returned containers to meet. The filter must be in the format defined by RFC2254.

scope

Optional search scope. Use **1** for One Level Scope and **2** for SubTree Scope. One Level Scope is the default scope.

Returns

An array of DirectoryObjects representing the results of the search.

Description

This method searches for a person by a filter.

Usage

```
var personSearch = new PersonSearch();
var searchResult1 = personSearch.searchByFilter("Person",
    "(sn=Smith)", 2);

// use default one level scope
var searchResult2 = personSearch.searchByFilter("Person",
    "(sn=Smith)");
```

PersonSearch.searchByURI()

The method finds a person by URI within an organizational container.

Availability

IBM Security Identity Manager 6.0

Synopsis

```
PersonSearch.searchByURI(containerDN, uri)
```

Arguments

Container DN

String representing the distinguished name of the parent organizational container.

uri

String representing the URI of the person.

Returns

A Person object.

Description

Given the distinguished name of the parent organizational container and the person URI, this method finds the person. If the person is not found, this function returns null. If more than one persons found, this function throws a scripting exception.

Usage

```
var person= (new PersonSearch()).searchByURI(container.dn, uri);
if (person != null) {
  Enrole.log("script", "Found " + person.getProperty("cn") );}
```

PostOffice

The object post office object that consolidates notifications.

Availability

IBM Tivoli Identity Manager 4.6.x

Provided by

com.ibm.itim.mail.postoffice.script.PostOfficeExtension

Methods

getAllEmailMessages()

Obtains the Subject, Text Body, and HTML Body of each individual message contained in an aggregate message.

getEmailAddress()

Contains the email address that is the destination of the aggregate email message.

getPersonByEmailAddress()

Returns the Person that corresponds to the email address specified.

getTopic()

Returns the topic of the aggregated email message.

The `getAllEmailMessages()` extension allows access to the `NotificationMessage` object. Do not call the `getHtmlMessage()` method from a template. This call returns an XHTML version of the notification text. It is not possible to embed XML documents, so a call to this method results in a template execution failure. Use the text body of the original notifications by calling `getMessage()` instead.

PostOffice.getAllEmailMessages()

The message returns an array of `NotificationMessage` objects.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
PostOffice.getAllEmailMessages()
```

Description

This JavaScript extension returns an array of `NotificationMessage` objects for obtaining the Subject, Text Body, and HTML Body of each message in an aggregate message.

Usage

An example of how to iterate through the returned array in JavaScript is as follows:

```
Here are the email text bodies fetched using the JavaScript extension:
<JS>
  var msgListIterator =
    PostOffice.getAllEmailMessages().iterator();
  var returnString = "<br />";
  while (msgListIterator.hasNext()) {
    returnString = returnString +
      msgListIterator.next().getMessage() + "<br />";
  }
  return returnString;
</JS>
```

PostOffice.getEmailAddress()

The method returns email address of aggregate email destination.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
PostOffice.getEmailAddress()
```

Description

This JavaScript extension returns a String containing the email address that is the destination of the aggregate email message.

Usage

```
destinationAddress = PostOffice.getEmailAddress();
```

PostOffice.getPersonByEmailAddress()

The method returns the Person object that corresponds to this email address.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
PostOffice.getPersonByEmailAddress(String email)
```

Description

This JavaScript extension returns the Person object that corresponds to the email address specified.

Usage

```
targetPerson = PostOffice.getPersonByEmailAddress()
```

Examples:

```
targetPerson = PostOffice.getPersonByEmailAddress("user@itim.com");
targetPerson =
    PostOffice.getPersonByEmailAddress(PostOffice.getEmailAddress());
```

PostOffice.getTopic()

The method returns the topic string of the aggregate email.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
PostOffice.getTopic()
```

Description

This JavaScript extension returns a string containing the topic of the aggregated email message.

Usage

```
topicString = PostOffice.getTopic();
```

Process

Represents the IBM Security Identity Manager workflow process.

Availability

IBM Tivoli Identity Manager 4.x

Provided by

The Process JavaScript Object in the WorkflowExtension returns a Process object. The object represents the current workflow process. The parent processes of the current workflow can be returned by calling `Process.getParent()` recursively, and the parent process is also a Process object.

Properties

Note: Custom result codes are supported in the workflow designer for approval activities.

APPROVED

Approved process summary code. Result code is AA.

ESCALATED

Escalated process summary code. Result code is ES.

FAILED

Failed process summary code. Result code is SF.

PARTICIPANT_RESOLVE_FAILED

Participant resolved failure process summary code. Result code is PF.

PENDING

Pending process summary code. Result code is PE.

REJECTED

Rejected process summary code. Result code is AR.

SUBMITTED

Submitted process summary code. Result code is RS.

SUCCESS

Success process summary code. Result code is SS.

TIMEOUT

Time out process summary code. Result code is ST.

WARNING

Warning process summary code. Result code is SW.

comment

Provides additional information about the process given when defined in the workflow designer.

description

Describes the purpose of the process given when defined in the workflow designer.

id

Assigned by the workflow designer to uniquely identify the workflow process within the workflow engine.

name

Label given this activity when defined in the workflow designer.

parentId

Uniquely identifies the parent process (if any) that started this process.

requesteeDN

Uniquely identifies the requestee if the requestee is a user in the IBM Security Identity Manager data store.

requesteeName

Name of the process requestee.

requestorId

Id of the process requestor.

requestorName

The name of the process requestor if the requestor is a user.

requestorType

Categorize the requestor

resultDetail

An application-specific string that provides more detail about the result of the process.

resultSummary

An application-specific string that represents the summary result of the process.

started

Indicates when the process started.

state

Code that represents the current state of the process.

subject

Describes the object that is the focal point of the workflow process.

type

Code that categorizes the process given when defined in the workflow designer.

Methods**auditEvent()**

Create an event in the audit trail specific to the activity.

getActivity()

Returns an activity with the ID and index.

getParent()

Get the parent process (if any) that started this process.

getRootProcess()

Returns the JavaScript Process object that contains information about the root process.

getRootRequesterName()

Returns String of requester name of the root process.

setRequesteeData()

Change the requestee data for the current process.

setResult()

Change the result member of the activity in the current activity.

setSubjectData()

Change the subject data for the current process.

Description

This entity represents the current workflow process is running.

Process.auditEvent()

The method creates an event in the audit trail.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.auditEvent(event)
```

Arguments**event**

String representing the event to be audited.

Description

This method creates an event in the audit trail specific to the process. The function takes in one parameter that can be any JavaScript object that can be translated into a string for storage. In the audit trail, the event is automatically time stamped.

Usage

```
process.auditEvent("Task completed");
```

Process.comment

The field provides additional information about the process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

process.comment

Description

This read-only field is a string that provides additional information about the process given when defined in the workflow designer.

Usage

```
x = process.comment;
```

Process.description

The field represents the purpose of the process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

process.description

Description

This read-only field is a string that describes the purpose of the process when defined in the workflow designer.

Usage

```
x = process.description;
```

Process.getActivity()

The method returns an activity with the ID and index.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.getActivity(id, index)
```

Arguments**id**

Activity ID assigned by the workflow designer.

index

Optionally identifies specific activity if there is more than one activity with the ID.

Returns

The associated Activity.

Description

This method returns an activity with the ID and index in the event that there is more than one activity with the ID. This might occur if the activity of the given ID is called multiple times in a loop in the workflow process. If there is no activity with the ID and index, this function returns null. If the optional index is not specified and if there is more than one activity with the ID, the first activity with the ID is returned.

Usage

```
theFirstActivity = process.getActivity("id1", 3);
theActivityName = theFirstActivity.name;

theSecondActivity = process.getActivity("id2");
theActivityName = theSecondActivity.name;
```

Process.getParent()

The method returns the parent process (if any) that started this process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.getParent()
```

Returns

The parent Process. If there is no parent, a null is returned.

Description

This method returns the parent process (if any) that started this process.

Usage

```
parent = process.getParent();  
parentName = parent.name;
```

Process.getRootProcess()

The method returns the root process (if any) that started this process.

Availability

IBM Tivoli Identity Manager 5.0

Synopsis

```
process.getRootProcess()
```

Returns

The root process. If there is no root process, a null is returned.

Description

This method returns the root process (if any) of this process.

Usage

```
root = process.getRootProcess();  
rootName = root.name;
```

Process.getRootRequesterName()

The method returns the root requester name.

Availability

IBM Tivoli Identity Manager 4.6

Synopsis

```
process.getRootRequesterName()
```

Description

This method returns the root requester name of the workflow process initiator.

Usage

```
rootRequester = process.getRootRequesterName();
```

Process.guid

The generated unique identifier assigned to the process at runtime.

Availability

IBM Tivoli Identity Manager 5.x

Synopsis

```
process.guid
```

Description

This read-only field is a String of the generated unique identifier for the workflow process in the workflow engine.

Usage

```
x = process.guid;
```

Process.getSubProcesses()

The method returns the subordinate processes (if any) of the process.

Availability

IBM Security Identity Manager 6.0.0.3

Synopsis

```
process.getSubProcesses()
```

Returns

The subordinate processes. If there are no subordinate processes, an empty array is returned.

Description

This method returns the subordinate processes (if any) of this process.

Usage

```
var out = "subprocesses of the process: \n";

function traverse(p, prefix) {
  var subProcesses = p.getSubProcesses();
  prefix += "/" + p.name;
  out += prefix + ": " + p.id + " type: " + p.type + " resultSummary: " + p.resultSummary +
  "\n";
  for (var i = 0; i < subProcesses.length; i++) {
    traverse(subProcesses[i], prefix);
  }
}

traverse(process, "");
activity.auditEvent(out);
```

Process.id

The generated unique identifier assigned to the process at runtime.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.id
```

Description

This read-only field is a string of the generated unique identifier for the workflow process in the workflow engine.

Usage

```
x = process.id;
```

Process.name

The label assigned to the process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.name
```

Description

This read-only field is a string assigned by the workflow designer to label this process.

Usage

```
x = process.name;
```

Process.parentId

The field uniquely identifies the parent process that started this process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.parentId
```

Description

This read-only field is a string representation of the long integer that uniquely identifies the parent process (if any) that started this process.

Usage

```
x = process.parentId;
```

Process.requesteeDN

The field uniquely identifies the requestee if the requestee is a user in the IBM Security Identity Manager data store.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.requesteeDN
```

Description

This read-only field is a string that uniquely identifies the requestee if the requestee is a user in the IBM Security Identity Manager data store. Not all requestees are users (that is, the process can act on a policy, not a user directly), so this member can be empty.

Usage

```
x = process.requesteeDN;
```

Process.requestorDN

The field specifies the distinguished name of the process requester, if the requester is a user in the IBM Security Identity Manager data store.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.requestorDN
```

Description

This read-only field is a string that represents the distinguished name of the process requester. This string is displayed only if the requester is a user in the IBM Security Identity Manager data store. Not all requesters are users (that is, the process can act on a policy, not a user directly), so this member can be empty.

Usage

```
if (process.requestorType == "U")  
x = process.requestorDN;
```

Process.requesteeName

The field represents the name of the process requestee as a string.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.requesteeName
```

Description

This read-only field is a string that provides the name the requestee if the requestee is a user in the IBM Security Identity Manager data store. Not all requestees are users (that is, the process can act on a policy, not a user directly), so this member can be empty.

Usage

```
x = process.requesteeName;
```

Process.requestorName

The field represents the name of the process requester if the requester is a user.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.requestorName
```

Description

This read-only field is a string that represents the name of the process requester if the requester is a user.

Usage

```
if (process.requestorType == "U")  
  x = process.requestorName;
```

Process.requestorId

The field identifies the party who requested the process to be executed.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.requestorId
```

Description

This read-only field is a String that identifies the party who requested the process to be executed. The value is not guaranteed to be unique across different workflow processes.

Usage

```
processRequestorId = process.requestorId;
```

Note: If the requestor is system (`process.requestorType == P`) then `process.requestorId` returns NULL.

Process.requestorType

The field categorize the requestor.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.requestorType
```

Description

This read-only field is a string that categorizes the requestor. The potential categories, or types, are:

- **U** for user
- **S** for the workflow engine
- **P** for the system

Usage

```
x = process.requestorType;
if (x == "U")
...
else if (x == "S")
...
else if (x == "P")
...
...
```

Process.resultDetail

The field details about the result of the process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

process.resultDetail

Description

This read-only field is an application-specific string that provides more detail about the result of the process.

Usage

x = process.resultDetail;

Process.resultSummary

The field represents the summary of the result of the process.

Availability

IBM Tivoli Identity Manager 4.x

Description

This read-only field is an application-specific string that provides a summary of the result of the process.

Usage

x = process.resultSummary;

Process.setRequesteeData()

The method changes the requestee data for the current process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

process.setRequesteeData(person)

Arguments

person

DirectoryObject representing the new requestee.

Description

This method changes the requestee data for the current process. It is not supported for a process that is not the current process. It not only updates the current process in the script, but also in the workflow engine. The `requesteeData` argument contains a person distinguished name or a collection of strings from which the requestee data can be extracted.

Usage

process.setRequesteeData(person);

Process.setResult()

The method changes the result member of the process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.setResult(summary, detail)
```

Arguments

summary

String code that represents the result summary.

detail

String representing the result details.

Description

This method changes the result member of the process in the current process. It is supported for current activities in the current workflow process. The result is composed by an application-specific summary code, and optional more detailed application-specific description. The summary code can indicate a success or failure. This summary code is stored as the `resultSummary` member locally and updated in the relevant data in the workflow engine. The detail is stored as the `resultDetail` member locally and updated in the relevant data in the workflow engine.

Usage

```
process.setResult(process.FAILED, "Unable to connect to resource");
```

Process.setSubjectData()

The method changes the subject data for the current process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.setSubjectData(person)
```

Arguments

person

DirectoryObject representing the new subject.

Description

This method changes the subject data for the current process. It is not supported for a process that is not the current process. It not only updates the current process in the script, but also in the workflow engine. The `subjectData` argument contains a person distinguished name or a collection of strings from which the subject data can be extracted.

Usage

```
process.setSubjectData(person);
```

Process.started

The field represents the JavaScript date that indicates when the process started.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.started
```

Description

This read-only field is code string that represents the JavaScript Date that indicates when the process started.

Usage

```
x = process.started;
```

Process.state

The field represents the current state of the process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

process.state

Description

This read-only field is code string that represents the current state of the process. The state can have the following values:

- R for running
- I for not started
- T for terminated
- A for aborted
- S for suspended
- C for completed
- B for bypassed

Usage

```
if (process.state == "S") {  
  ...  
}
```

Process.subject

The field represents the object that is the focal point of the workflow process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

process.subject

Description

This read-only field is code string that describes the object that is the focal point of the workflow process. This string can be an identity in the system, an account, a policy, or another object.

Usage

```
x = process.subject;
```

Process.type

The field represents the type of process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
process.type
```

Description

This read-only field is code string that categorizes the process when defined in the workflow designer.

Usage

```
x = process.type;
```

ProcessData

The object represents the workflow process data entity.

Availability

IBM Tivoli Identity Manager 4.x
Workflow context

Provided by

com.ibm.itim.workflow.script.WorkflowExtension

Methods

get()

Returns a JavaScript object that represents the value of the relevant data item.

set()

Changes the value of the relevant data item.

Description

Each workflow process has a set of relevant data, or process specific parameters, which can be read or changed from within a workflow script. The name and syntax of these parameters, or relevant data items, are defined in the workflow designer, and are typically specific to the workflow process purpose. For example, when adding a user, an object that holds all the attributes of the new user can be a relevant data item. However, when deleting a user, the only needed relevant data item can be the distinguished name of the user to delete.

Each relevant data item will be represented in the workflow script as a variable with the same relevant data ID as defined in the workflow designer.

ProcessData.get()

The method changes the subject data for the current process.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
processData.get()
```

Returns

Returns a JavaScript object that represents the value of the relevant data item.

Description

This method returns a JavaScript object that represents the value of the relevant data item. There is a variable present for each relevant data item in the context of script. For performance reasons, the values are not retrieved from the workflow engine until the script specifically requests the values with this call. The returned JavaScript object is in the same syntax as defined in the workflow designer.

Usage

```
dn = subjectDN.get();
```

ProcessData.set()

The method changes the value of the relevant data item.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
processData.set(value)
```

Arguments

value

Value to use to update the relevant data item.

Description

This method changes the value of the relevant data item. It not only updates the relevant data item in the script, but also in the workflow engine. The new value is a parameter to the function. The new value must be compatible with the syntax of the relevant data item as defined in the workflow designer. For example, if the relevant data item is an integer, the value cat would not be a valid parameter to this function.

Usage

```
processData.set("engineering");
```

RecertificationWorkflow

Provides extended capabilities to user recertification workflows, including audit support for the reporting and view requests functions.

Availability

IBM Tivoli Identity Manager 5.1.

Methods

auditCompletion(person, recertPolicy, approvalDoc)

Performs a full audit of the decisions made during a user recertification packaged approval activity, including data for reporting and view requests.

auditTimeout(person, recertPolicy, approvalDoc)

Perform full audit of the decisions set during a user recertification packaged approval activity timeout, including data for reporting and view requests.

auditCompletion(person, recertPolicy, approvalDoc, auditForReports, auditForViewRequests)

Performs an audit of the decisions made during a user recertification packaged approval activity. The value of the Boolean flag `auditForReports` determines whether an audit entry is created for reporting. The value of the Boolean flag `auditForViewRequests` determines whether an audit entry is created for view requests.

RecertificationWorkflow.auditTimeout(person, recertPolicy, approvalDoc, auditForReports, auditForViewRequests)

Performs an audit of the decisions set during a user recertification packaged approval activity timeout. The value of the Boolean flag `auditForReports` determines whether an audit entry is created for reporting. The value of the Boolean flag `auditForViewRequests` determines whether an audit entry is created for view requests.

Usage

```
RecertificationWorkflow.auditCompletion(Entity.get(), Policy.get(),  
ApprovalDocument.get())
```

```
RecertificationWorkflow.auditTimeout(Entity.get(), Policy.get(),  
ApprovalDocument.get(), false, true)
```

Reminder

An activity to-do item reminder informs the participant that the IBM Security Identity Manager requires user action.

Availability

IBM Tivoli Identity Manager 4.x
Reminder context

Provided by

```
com.ibm.itim.script.extensions.ReminderExtension
```

Methods

Reminder.getOriginalSubject()

This method returns the subject of the original notification sent when the work item was first assigned.

Reminder.getXhtmlBody()

This method returns the XHTML body of the original notification sent when the work item was first assigned.

Reminder.getTextBody()

This method returns the text body of the original notification sent when the work item was first assigned.

Reminder.getRemindersSent()

This method returns the number of reminders previously sent.

Reminder.getEscalationTime()

This method returns a string that contains the date and time when the work item is escalated unless acted upon.

Reminder.getEscalationDate()

This method returns a Date containing the date and time when the work item is escalated unless acted upon.

Description

An activity to-do item reminder informs the participant that IBM Security Identity Manager requires user action.

Role

The object represents the role associated with a provisioning operation.

Availability

IBM Tivoli Identity Manager 4.x

Provided by

`com.ibm.itim.script.extensions.model.RoleModelExtension`

Constructor

`new Role(dn)`

Returns

A new Role object that represents the Role with the given DN.

Methods

getAssignmentAttributes()

Returns an array of assignment attribute names. Returns an empty array if no assignment attribute exists.

getAllAssignmentAttributes()

Returns an array of RoleAssignmentAttribute objects containing assignment attribute name, role name, and role DN. Returns an empty array if no assignment attribute exists. Returns the role assignment attributes of the whole role hierarchy.

getOwner()

Returns an array of DirectoryObjects that represent any Person that has an Owner relationship with this role.

getChildRoles()

Returns an array of roles. The array contains the immediate member roles, that is, child roles of the role. The method returns an empty array if no child role exists.

getParentRoles()

Returns an array of roles. The array contains the immediate parent roles of the role. The method returns an empty array if no parent role exists.

getAscendantRoles()

Returns an array of roles. The array contains all ancestor roles of the role, transitively. The method returns an empty array if no ascendant role exists.

getDecendantRoles()

Returns an array of roles. The array contains all member roles of the role, transitively, based on the role hierarchy. The method returns an empty array if no member role exists.

setAssignmentAttributes()

Sets role assignment attributes of the role.

Inherits from

DirectoryObject

Synopsis

```
role.dn;
```

Description

The role object is available in the context of a provisioning policy.

Note: For more information on role assignment attributes, see [Defining assignment attributes when creating a role](#).

Role.getAscendantRoles()

This method returns all the ascendant roles, transitively. Ascendant roles are ancestors, that is, parent roles, grandparent roles, and more remote ancestor roles.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
Role.getAscendantRoles()
```

Arguments

None

Description

This method is defined on the Role object and returns an array of roles. The array contains all ancestor roles of the role, transitively. The method returns an empty array if no ascendant role exists.

Usage

```
var role = new Role(roleDN);
//get ascendant roles
var roleList = role.getAscendantRoles();
if (roleList.length == 0) {
    Enrole.log("script", "There are no ascendant roles of role: " + role.name);
    return;
}

// print out role names.
for (var i=0; i < roleList.length; i++) {
    var r = roleList[i];
    Enrole.log("script", "role name: " + r.name);
}
```

Role.getAssignmentAttributes()

The method returns an array of assignment attribute names. Returns an empty array if no assignment attribute exists.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
Role.getAssignmentAttributes()
```

Arguments

None

Description

This method is defined on the Role object and returns an array of assignment attribute names. The method returns an empty array if no assignment attribute exists.

Usage

```
var role = new Role(roleDN);

//get assignment attributes of the role
var attributeList = role.getAssignmentAttributes();
if (attributeList.length == 0) {
    Enrole.log("script", "No assignment attribute for this role: "
        + role.name);
    return;
}

// print out role assignment attribute name.
for (var i=0; i < attributeList.length; i++) {
    var attrName = attributeList[i];
    Enrole.log("script", "attribute name-----: "+ attrName);
}
```

Role.getChildRoles()

The method returns all the immediate member roles.

Availability

IBM Security Identity Manager 6.0.

Synopsis

Role.getChildRoles()

Arguments

None

Description

This method is defined on the Role object and returns an array of roles. The array contains the immediate member roles, that is, child roles of the role. The method returns an empty array if no child role exists.

Usage

```
var role = new Role(roleDN);
//get child roles
var roleList = role.getChildRoles();
if (roleList.length == 0) {
    Enrole.log("script", "There are no child roles of role: " + role.name);
    return;
}

// print out role names.
for (var i=0; i < roleList.length; i++) {
    var r = roleList[i];
    Enrole.log("script", "role name: "+ r.name);
}
```

Role.getDescendantRoles()

This method returns all the member roles, transitively.

Availability

IBM Security Identity Manager 6.0.

Synopsis

Role.getDescendantRoles()

Arguments

None

Description

This method is defined on the Role object and returns an array of roles. The array contains all member roles of the role, transitively, based on the role hierarchy. The method returns an empty array if no member role exists.

Usage

```
var role = new Role(roleDN);
//get child roles
var roleList = role.getDescendantRoles();
if (roleList.length == 0) {
    Enrole.log("script", "There are no descendant roles of role: " + role.name);
    return;
}

// print out role names.
for (var i=0; i < roleList.length; i++) {
    var r = roleList[i];
    Enrole.log("script", "role name: "+ r.name);
}
}
```

Role.getOwner()

The method returns an array of DirectoryObjects that represents any Person that has an Owner relationship with this role.

Availability

IBM Tivoli Identity Manager 5.0

Synopsis

```
Role.getOwner()
```

Returns

Array of DirectoryObjects that represents the owners of this Role or null if there are no owners.

Usage

```
var owners = role.getOwner();
```

Role.getParentRoles()

The method returns all the immediate parent roles.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
Role.getParentRoles()
```

Arguments

None

Description

This method is defined on the Role object and returns an array of roles. The array contains the immediate parent roles of the role. The method returns an empty array if no parent role exists.

Usage

```
var role = new Role(roleDN);
//get parent roles
var roleList = role.getParentRoles();
if (roleList.length == 0) {
    Enrole.log("script", "There is no parent role of role: " + role.name);
    return;
}

// print out role names.
for (var i=0; i < roleList.length; i++) {
    var r = roleList[i];
    Enrole.log("script", "role name: "+ r.name);
}
}
```


Role.setAssignmentAttributes()

The method sets role assignment attributes of the role.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
Role.setAssignmentAttributes(String[] attributeNames)
```

Arguments

attributeNames

The array of assignment attribute names of the role. If an empty array is specified, all assignment attributes for the role are removed.

Description

This method is defined on the Role object and sets the role assignment attributes for a role.

Usage

```
var roleDN = roles[0];
var role = new Role(roleDN);
var roleAtr = new Array();
roleAtr[0] = "creditlimit";
//set assignment attribute names
role.setAssignmentAttributes(roleAtr);
```

RoleAssignmentAttribute

The object represents the role assignment attribute associated with a role.

Availability

IBM Security Identity Manager 6.0.

Methods

getName()

Returns the attribute name associated with the role assignment attribute object.

getRoleName()

Returns the name of the role. Returns an empty string if there is no name associated with the role assignment attribute object.

getRoleDN()

Returns the DN of the role. Returns an empty string if there is no DN associated with the role assignment attribute object.

Description

The RoleAssignmentAttribute object associated with the role assignment attribute.

RoleAssignmentAttribute.getName()

The method returns the name of the assignment attribute.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
RoleAssignmentAttribute.getName()
```

Arguments

None

Returns

The name of the assignment attribute.

Description

Returns the name of the assignment attribute that is defined on the role.

Usage

```
var role = new Role(roleDN);
//get assignment attributes of the role
var attributeList = role.getAllAssignmentAttributes();
if (attributeList.length == 0) {
    Enrole.log("script", "No assignment attribute for this role: "
        + role.name);
    return;
}

// print out role assignment attribute name.
for (var i=0; i < attributeList.length; i++) {
    var roleAtr = attributeList[i];
    Enrole.log("script", "attribute name-----: "+ roleAtr.getName());
}
```

RoleAssignmentAttribute.getRoleName()

The method returns the name of the role that has the assignment attribute defined.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
RoleAssignmentAttribute.getRoleName()
```

Arguments

None

Returns

The name of the role that has the assignment attribute defined.

Description

Returns the name of the role that has the assignment attribute defined.

Usage

```
var role = new Role(roleDN);
//get assignment attributes of the role
var attributeList = role.getAllAssignmentAttributes();
if (attributeList.length == 0) {
    Enrole.log("script", "No assignment attribute for this role: "
        + role.name);
    return;
}

// print out all role names.
for (var i=0; i < attributeList.length; i++) {
    var roleAtr = attributeList[i];
    Enrole.log("script", "role name-----: "+ roleAtr.getRoleName());
}
```

RoleAssignmentAttribute.getRoleDN

The method returns the distinguished name of the role that defines the assignment attributes.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
RoleAssignmentAttribute.getRoleDN()
```

Arguments

None

Returns

The distinguished name of the role that defines the assignment attributes.

Description

Returns the distinguished name of the role that defines the assignment attributes.

Usage

```
var role = new Role(roleDN);
//get assignment attributes of the role
var attributeList = role.getAllAssignmentAttributes();
if (attributeList.length == 0) {
    Enrole.log("script", "No assignment attribute for this role: "
        + role.name);
    return;
}

// print out the distinguished name of the role that defines
// assignment attributes.
for (var i=0; i < attributeList.length; i++) {
    var roleAtr = attributeList[i];
    Enrole.log("script", "define role DN-----: "+ roleAtr.getRoleDN());
}
```

RoleAssignmentObject

The `RoleAssignmentObject` class is a `DataObject` class for role assignment data.

This class holds the assignment data that are associated with the defined role and the assigned role. The defined role is the role that holds a list of assignment attributes. The assigned role is the role to which the person is assigned.

Availability

IBM Security Identity Manager 6.0

Provided by

`com.ibm.itim.script.extensions.model.RAObjectModelExtension`

Constructors

new RoleAssignmentObject(RoleAssignmentObject assignmentObject)

Arguments:

assignmentObject

`RoleAssignmentObject` that is wrapped inside the `RoleAssignmentObject`.

new RoleAssignmentObject(String assignedRoleDN, String definedRoleDN)

Arguments:

assignedRoleDN

The String format of the distinguished name for the assigned role.

definedRoleDN

The String format of the distinguished name for the defined role.

Methods

addProperty()

Adds the values for specified assignment attribute.

getAssignedRoleDN()

Returns the distinguished name string for the role to which the person is assigned.

getDefinedRoleDN()

Returns the distinguished name string for the role in which the assignment attribute is defined.

getChanges()

Returns the changes made to this `RoleAssignmentObject`.

getProperty()

Returns the values of the property specified by the assignment attribute name.

getPropertyNames()

Returns a list of role assignment attribute names.

removeProperty()

Removes the values for the specified assignment attribute name.

setProperty()

Sets the values for a specified assignment attribute.

Description

RoleAssignmentObject contains the role assignment data, including the assigned role DN, the defined role DN and attribute values.

RoleAssignmentObject.getAssignedRoleDN()

The method returns the distinguished name string for the role to which a person is assigned.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
roleAssignmentObject.getAssignedRoleDN()
```

Arguments

None

Returns

The distinguished name string for the role to which a person is assigned.

Description

This method returns the distinguished name string for the role to which a person is assigned.

Usage

```
var assignedRoleDN = "globalid=111";  
var definedRoleDN = "globalid=222";  
var assignmentObj = new RoleAssignmentObject(assignedRoleDN, definedRoleDN);  
  
var assignedRoleDN2 = assignmentObj.getAssignedRoleDN();
```

RoleAssignmentObject.getDefinedRoleDN()

The method returns the distinguished name string for the role in which the assignment attribute is defined.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
roleAssignmentObject.getDefinedRoleDN()
```

Arguments

None

Returns

Returns the distinguished name string for the role in which the assignment attribute is defined.

Description

This method returns the distinguished name string for the role to which the person is assigned.

Usage

```
var assignedRoleDN = "globalid=111";  
var definedRoleDN = "globalid=222";  
var assignmentObj = new RoleAssignmentObject(assignedRoleDN, definedRoleDN);  
  
var definedRoleDN2 = assignmentObj.getDefinedRoleDN();
```

RoleAssignmentObject.addProperty()

Use this method to add the values for specified assignment attribute.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
RoleAssignmentObject.addProperty(name, value)
```

Arguments

name

String representing the name of the assignment attribute to be added.

value

The value to be added.

Description

This method changes the value of the specified assignment attribute or adds the specified assignment attribute if it does not exist. This change is made locally to the script environment, not to the data store.

Usage

```
// Create assignment object with assigned role dn and defined role dn.
var assignmentObj = new RoleAssignmentObject("eruid=1111,dc=com",
    "eruid=2222,dc=com");
// Add some assignment attribute with values.
assignmentObj.addProperty("attr1", ["attr1val1", "attr2val1"]);
assignmentObj.addProperty("attr2", ["attr2val1"]);
assignmentObj.addProperty("attr2", ["attr2val2"]);
```

RoleAssignmentObject.getChanges()

The method returns the changes made to an entity.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
RoleAssignmentObject.getChanges()
```

Returns

An array of change objects. If there are no changes, an empty array is returned. Each element in the array is an *AttributeChangeOperation*.

Description

This method returns the changes made to the entity. These changes are represented by change objects with the following members:

attr

String name of the attribute that is being changed.

op

An integer that identifies the type of change that is being made. The enumerated values are 1 for add, 2 for replace, and 3 for remove.

values

An array of objects that can be either added, removed, or replaced.

The changes are returned as an array of these change objects. If there are no changes, an empty array is returned.

Usage

```
changes = assignmentObject.getChanges();
for (i = 0; i < changes.length; i++) {
    name = changes[i].attr;
    if (changes[i].op == 1) {
        ...
    } else if (changes[i].op == 2) {
        ...
    } else {
        ...
    }
};
```

RoleAssignmentObject.getProperty()

The method returns the values of the assignment attribute specified by the given name.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
RoleAssignmentObject.getProperty(name)
```

Arguments

name

String representing the name of the assignment attribute to return.

Returns

The array of strings that represents the values for an assignment attribute. If the specified assignment attribute does not exist, an empty array is returned.

Description

This method returns the values of the assignment attribute specified by the given name. If the specified assignment attribute does not exist, an empty array is returned.

Usage

```
// create assignment object with assigned role dn and defined role dn.
var assignmentObj = new RoleAssignmentObject("eruid=1111,dc=com",
    "eruid=2222,dc=com");
assignmentObj.addProperty("attr1", ["attr1val1", "attr1val2"]);

// get assignment attribute values for attr1.
var attrValues = assignmentObj.getProperty("attr1");
var attrValuesStr = "";
for (var j=0; j<attrValues.length; j++) {
    attrValuesStr += attrValues[j] + ", ";
}
Enrole.log("script", "The values for attr1:" + attrValuesStr);
```

RoleAssignmentObject.getPropertyNames()

The method returns a list of assignment attributes.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
RoleAssignmentObject.getPropertyNames()
```

Returns

An array of strings.

Description

This method returns a list of assignment attributes as an array of strings.

Usage

```
properties = RoleAssignmentObject.getPropertyNames();
```

RoleAssignmentObject.removeProperty()

The method removes the assignment attribute specified by the given name.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
RoleAssignmentObject.removeProperty(name)
```

Arguments

name

String representing the name of the assignment attribute to remove.

Description

This method removes the specified assignment attribute. This change is made locally to the script environment, not to the data store.

Usage

```
RoleAssignmentObject.removeProperty("assignmentAttr1");
```

RoleAssignmentObject.setProperty()

The method sets the value of the specified assignment attribute.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
RoleAssignmentObject.setProperty(name, value)
```

Arguments**name**

String representing the name of the assignment attribute to be created or modified.

value

Specifies the value to which the assignment attribute is set.

Description

This method changes the value of the specified assignment attribute, or adds the specified assignment attribute if it does not exist. This change is made locally to the script environment, not to the data store.

Usage

```
RoleAssignmentObject.setProperty("attr1",["val1","val2"]);
```

RoleSearch

The object searches for a role.

Availability

IBM Tivoli Identity Manager 4.x

Provided by

com.ibm.itim.script.extensions.model.RoleModelExtension

Constructor

```
new RoleSearch()
```

Returns

The newly created and initialized role search object.

Methods**searchByName()**

Search for a role by name.

searchByURI()

Search for a role by URI within an organizational container.

RoleSearch.searchByName()

The method searches for a role by a name.

Availability

IBM Tivoli Identity Manager 4.6

Synopsis

```
RoleSearch.searchByName(name)
```

Arguments

name

The role name to use as the basis for the search.

Returns

Array of `DirectoryObjects` that represents a role.

Description

Given the name of a role, locate the Role entity. Will return `null` if there is not exactly one matching role.

Usage

```
// Given the name of a role, see if it exists and log its
// description
var roles = (new RoleSearch()).searchByName("testRole");
if (roles.length >= 1) {
    if (roles[0].getProperty("errolename")[0] == "testRole") {
        Enrole.log("script", "The Role " + roles[0].getProperty("errolename")[0] +
            "has Description :" + roles[0].getProperty("description")[0]);
    }
}
```

RoleSearch.searchByURI()

The method finds a role by URI in an organizational container.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
RoleSearch.searchByURI(containerDN, uri)
```

Arguments

Container DN

String representing the distinguished name of the organizational container.

uri

String representing the URI of the role.

Returns

A Role object

Description

Given the distinguished name of the organizational container and the role URI, this method finds the container. If the role is not found, this function returns `null`. If more than one role is found, this function throws a scripting exception.

Usage

```
var role = (new RoleSearch()).searchByURI(container.dn, uri);
if (role != null) {
    Enrole.log("script", "Found " + role.getProperty("errolename") );}
```

SeparationOfDutyRuleViolation

Object that provides information about a specific separation of duty rule violation. Use this object to get specific information about a separation of duty policy violation. This object cannot be created for use by the user. The user can work only with `SeparationOfDutyRuleViolation` objects that the system has generated as part of the *approveSoDViolation* workflow.

Availability

IBM Tivoli Identity Manager 5.1.

Provided by

`com.ibm.itim.script.wrappers.generic.IRuleResultWrapper`

Methods**getName()**

Returns the name of the separation of duty policy rule to which this violation corresponds.

getViolationString()

Provides a string that represents the list of roles in violation. It describes the roles the person has that are in violation and which role in a separation of duty rule they correspond to. The role lists might be different due to role hierarchy.

getViolationStringHTMLTable()

Returns a string version of the roles in violation for use in an HTML table or email template.

getPolicyName()

Returns the name of the separation of duty policy which contains the rule in violation.

getPolicyDescription()

Returns a description of the separation of duty policy.

getPolicyOwnerDNs()

Returns a collection of the distinguished names of one or more separation of duty policy owners.

getCardinality()

Returns string that represents the number of allowed roles in the separation of duty policy rule in violation.

Service

The object represents the service associated with a provisioning operation.

Availability

IBM Tivoli Identity Manager 4.x

Provided by

`com.ibm.itim.script.extensions.model.ServiceModelExtension`

Constructor

`new Service(dn)`

Returns

A new Service object that represents the Service with the DN.

Inherits From

DirectoryObject

Synopsis

`service.dn;`

Description

The service object is available in the context of a Provisioning Policy and Service Selection Policy.

ServiceSearch

Use the object to provide searching capability for IBM Security Identity Manager services.

Availability

IBM Tivoli Identity Manager 4.x
Provisioning Policy context
Service Selection Policy context

Provided by

com.ibm.itim.script.extensions.model.ServiceModelExtension

Methods**searchByFilter()**

Search for a service by a filter.

searchByName()

Search for a service by a name.

searchByURI()

Search for a service by URI in an organizational container.

searchForClosestToPerson()

Search for the closest Service to a person.

Description

This object is used to provide searching capability for IBM Security Identity Manager services.

ServiceSearch.searchByFilter()

The method searches for a service by a filter.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

ServiceSearch.searchByFilter(filter, scope)

Arguments**filter**

LDAP search filter that defines the criteria for returned containers to meet. The filter must be in the format defined by RFC2254.

scope

Optional search scope. Use 1 for One Level Scope and 2 for SubTree Scope. One Level Scope is the default scope.

Returns

An array of `DirectoryObjects` representing the results of the search.

Description

This method searches for a service by a filter.

Usage

```
searchResult1 =
  ServiceSearch.searchByFilter("(entlocalservername=*srv)", 2);

// use default one level scope, put statement on one line

searchResult2 =
  ServiceSearch.searchByFilter("(entlocalservername=*srv)");
```

ServiceSearch.searchByName()

The method searches for a service by name.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

ServiceSearch.searchByName(name, profileName, scope)

Arguments**name**

The service name, provided as a string, to use as the basis for the search.

profileName

Optional profile name, provided as a string. The profile name of the service to use as the basis for the search.

scope

Optional search scope, provided as an int. Use **1** for One Level Scope and **2** for Scope. One Level Scope is the default scope. When you use this method in workflow JavaScripts, set the scope parameter to SubTree because the logical search context is limited to the tenant above the default organization. In this context, setting the scope to One Level Scope returns empty results during a search because there are no services at the tenant level.

Returns

An array of `DirectoryObjects` representing the results of the search.

Description

This method searches for a service by a name.

Usage

```
searchResult1 = ServiceSearch.searchByName("US Service", 2);  
  
// use default one level scope  
searchResult2 = ServiceSearch.searchByName("US Service");
```

ServiceSearch.searchByURI()

The method finds a service by URI in an organizational container.

Availability

IBM Security Identity Manager 6.0.

Synopsis

```
ServiceSearch.searchByURI(containerDN, uri)
```

Arguments**Container DN**

String representing the distinguished name of the organizational container.

uri

String representing the URI of the service.

Returns

A Service object

Description

Given the distinguished name of the organizational container and the service URI, this method finds the service. If the service is not found, this function returns null. If more than one service is found, this function throws a scripting exception.

Usage

```
var service = (new ServiceSearch()).searchByURI(container.dn, uri);  
if (service != null) {  
  Enrole.log("script", "Found " + service.getProperty("erservicename") );  
}
```

ServiceSearch.searchForClosestToPerson()

The method searches for a service closest to a person.

Availability

IBM Tivoli Identity Manager 4.x

Synopsis

```
ServiceSearch.searchForClosestToPerson(person, profileName)
```

Arguments

person

The DirectoryObject representing a person to use as the basis for the search.

profileName

Optional service profile name.

Returns

An array of DirectoryObjects representing the results of the search.

Description

This method searches for a service closest to a person.

Usage

```
//Search for AIX service closest to the person.
searchResult1 = ServiceSearch.searchForClosestToPerson(subject,
"PosixAixProfile");

//Search for any service closest to the person.
searchResult2 = ServiceSearch.searchForClosestToPerson(subject);
```

UserAccess

The object extends the Account object and contains the data for a new account or changes to an existing account to provision the access, along with further information for the access.

Availability

IBM Security Identity Manager 6.0.

Inherits From

Account

Methods

getApprovalProcessID()

Returns the distinguished name of the approval process for gaining the access that was requested.

isNew()

Returns whether a new account is to be created by this access request, or an existing one is to be modified.

getAccessId()

Returns the identifier of the access that was requested.

getAccessName()

Returns the name of the access that was requested.

getAccessDescription()

Returns the description of the access that was requested.

getAccessOwner()

Returns the distinguished name of the owner of the access that was requested.

AccessRequestBatch

The object provides the AccessRequestBatch JavaScript object for use in the JavaScript environment of the access request batch notification templates.

The JavaScript object can be used in the ready-for-immediate-use notification templates - Access Batch Processing Start Template and Access Batch Processing Complete Template. The AccessRequestBatch object is a relevant data item in the processAccessBatch workflow definition. The workflow is not available for customization in workflow designer. To get the AccessRequestBatch JavaScript object, invoke get () on the relevant data ID accessRequestBatch.

Availability

IBM Security Identity Manager 6.0.0.17 and 7.0.1.6.

Provided by

com.ibm.itim.workflow.script.WorkflowExtension

Usage

```
var accessRequest = accessRequestBatch.get();
```

Methods**getSubmittedAccessProvisioningList()**

Returns the names of the accesses that were requested to be provisioned.

getSubmittedAccessDeprovisioningList()

Returns the names of the accesses that were requested to be deleted.

getSubmittedAccessUpdateList()

Returns the names of the accesses that were requested to be updated.

getAccessProvisioningStatusList()

Returns the access names and fulfillment status for the access provisioning requests that were made.

getAccessDeprovisioningStatusList()

Returns the access names and fulfillment status for the access deprovisioning requests that were made.

getAccessUpdateStatusList()

Returns the access names and fulfillment status for access update request made.

AccessRequestBatch.getSubmittedAccessProvisioningList()

This method returns the names of the accesses that were requested to be provisioned for a user. This method applies for access batch requests submitted from Identity Service Center only.

Availability

IBM Security Identity Manager 6.0.0.17 and 7.0.1.6.

Synopsis

```
AccessRequestBatch.getSubmittedAccessProvisioningList()
```

Returns

An array of access names that were requested to be provisioned for a user.

Description

This method returns the names of the accesses that were requested to be provisioned for a user. This method applies for access batch requests submitted from Identity Service Center only.

Usage

The following JavaScript is added in Access Batch Processing Start Template.

```
<RE key="Access Provisioning Request Submitted"/>:
<JS>
var result = '';
var accessList = accessRequestBatch.get().getSubmittedAccessProvisioningList();
for (var i = 0; i < accessList.length; i++)
{
    var accessName = accessList[i];
    if (i == (accessList.length - 1)){
        result += accessName;
    }else{
        result += accessName + ', ';
    }
}
return result;
</JS>
```

AccessRequestBatch.getSubmittedAccessDeprovisioningList()

This method returns the names of the accesses that were requested to be deleted for a user. This method applies for access batch requests submitted from Identity Service Center only.

Availability

IBM Security Identity Manager 6.0.0.17 and 7.0.1.6.

Synopsis

AccessRequestBatch.getSubmittedAccessDeprovisioningList()

Returns

An array of access names that were requested to be deleted for a user.

Description

This method returns the names of the accesses that were requested to be deleted for a user. This method applies for access batch requests submitted from Identity Service Center only.

Usage

The following JavaScript is added in Access Batch Processing Start Template.

```
<JS>
var result = '';
var accessList = accessRequestBatch.get().getSubmittedAccessDeprovisioningList();
for (var i = 0; i < accessList.length; i++)
{
    var accessName = accessList[i];
    if (i == (accessList.length - 1)){
        result += accessName;
    }else{
        result += accessName + ', ';
    }
}
return result;
</JS>
```

AccessRequestBatch.getSubmittedAccessUpdateList()

This method returns the names of the accesses that were requested to be updated for a user. This method applies for access batch requests submitted from Identity Service Center only.

Availability

IBM Security Identity Manager 6.0.0.17 and 7.0.1.6.

Synopsis

AccessRequestBatch.getSubmittedAccessUpdateList()

Returns

An array of access names that were requested to be updated for a user.

Description

This method returns the names of the accesses that were requested to be updated for a user. This method applies for access batch requests submitted from Identity Service Center only.

Usage

The following JavaScript is added in Access Batch Processing Start Template.

```
<JS>
var result = '';
var accessList = accessRequestBatch.get().getSubmittedAccessUpdateList();
for (var i = 0; i < accessList.length; i++)
{
    var accessName = accessList[i];
    if (i == (accessList.length - 1)){
        result += accessName;
    }else{
        result += accessName + ', ';
    }
}
return result;
</JS>
```

AccessRequestBatch.getAccessProvisioningStatusList()

This method returns an array of access names and the fulfillment status for access provisioning requests. The status can be Fulfilled, Not Fulfilled, Pending, or Unknown.

Availability

IBM Security Identity Manager 6.0.0.17 and 7.0.1.6.

Synopsis

AccessRequestBatch.getAccessProvisioningStatusList(String processId)

Arguments

The process ID of the access batch request process.

Returns

An array of access names and their statuses in the following format.

```
access name-access status
```

Description

This method returns an array of access names and the fulfillment status for access provisioning requests. The status can be Fulfilled, Not Fulfilled, Pending, or Unknown.

Usage

The following JavaScript is added in Access Batch Processing Complete Template.

```
</JS>
<RE key="Access Provisioning Status"/>: <JS>
  var result = '';
  var accessStatusList =
accessRequestBatch.get().getAccessProvisioningStatusList(process.id);
  for (var i = 0; i < accessStatusList.length; i++)
  {
    var accessNameStatus = accessStatusList[i];
    if (i == (accessStatusList.length - 1)){
      result += accessNameStatus;
    }else{
      result += accessNameStatus + ', \n      ';
    }
  }
  return result;
</JS>
```

AccessRequestBatch.getAccessDeprovisioningStatusList()

This method returns an array of access names and the fulfillment status for access removal requests. The status can be Fulfilled, Not Fulfilled, Pending, or Unknown.

Availability

IBM Security Identity Manager 6.0.0.17 and 7.0.1.6.

Synopsis

AccessRequestBatch.getAccessDeprovisioningStatusList(String processId)

Arguments

The process ID of the access batch request process.

Returns

An array of access names and their statuses in the following format.

```
access name-access status
```

Description

This method returns an array of access names and the fulfillment status for access removal requests. The status can be Fulfilled, Not Fulfilled, Pending, or Unknown.

Usage

The following JavaScript is added in Access Batch Processing Complete Template.

```
<JS>
var result = '';
var accessStatusList =
accessRequestBatch.get().getAccessDeprovisioningStatusList(process.id);
for (var i = 0; i <&lt; accessStatusList.length; i++)
{
    var accessNameStatus = accessStatusList[i];
    if (i == (accessStatusList.length - 1)){
        result += accessNameStatus;
    }else{
        result += accessNameStatus + ', \n          ';
    }
}
return result;
</JS>
```

AccessRequestBatch.getAccessUpdateStatusList()

This method returns an array of access names and the fulfillment status for access update requests. The status can be Fulfilled, Not Fulfilled, Pending, or Unknown.

Availability

IBM Security Identity Manager 6.0.0.17 and 7.0.1.6.

Synopsis

```
AccessRequestBatch.getAccessUpdateStatusList(String processId)
```

Arguments

The process ID of the access batch request process.

Returns

An array of access names and their statuses in the following format.

```
access name-access status
```

Description

This method returns an array of access names and the fulfillment status for access update requests. The status can be Fulfilled, Not Fulfilled, Pending, or Unknown.

Usage

The following JavaScript is added in Access Batch Processing Complete Template.

```
<JS>
var result = '';
var accessStatusList = accessRequestBatch.get().getAccessUpdateStatusList(process.id);
for (var i = 0; i <&lt; accessStatusList.length; i++)
{
    var accessNameStatus = accessStatusList[i];
    if (i == (accessStatusList.length - 1)){
        result += accessNameStatus;
    }else{
        result += accessNameStatus + ', \n          ';
    }
}
return result;
</JS>
```


Chapter 11. Provisioning policy parameter usage scenarios

The following scenarios illustrate usage of provisioning policy parameters.

Scenario 1: No attributes defined

If no parameter values are selected for a multi-valued attribute, all values are valid for this attribute.

If a parameter is added for a multi-valued attribute with the parameter type as Allowed (valid), all other values for this attribute are implicitly excluded for this policy.

If an attribute value is added to a policy as valid, all other values are implicitly excluded for that parameter for the policy.

For multiple applicable entitlements, a valid attribute value is determined by the join directive for the attribute. See the following scenarios.

Scenario 2: Priority-based provisioning policy join directive

The following table identifies two examples of provisioning policies:

Policy	Description
Policy 1	Priority = 1 Attribute: erdivision = divisionA, enforcement = DEFAULT
Policy 2	Priority = 2 Attribute: erdivision = divisionB, enforcement = MANDATORY

Because Policy 1 has a higher priority, only Policy 1's definition for the `erdivision` attribute is used. Policy 2's definition for the `erdivision` attribute is ignored.

During policy validation, including reconciliation with policy check option turned on, `divisionA` might exist on the `erdivision` attribute. All other values are valid, because the only policy that is being considered in a priority join is Policy 1, which has DEFAULT enforcement on `erdivision`. DEFAULT enforcement by itself is interpreted as valid for all values, but the default value is the value specified on the new account.

Note: A priority join directive is the default join directive for all single-valued and string-typed attributes.

Scenario 3: Union-based provisioning policy join directive

The following table identifies two example provisioning policies:

Policy	Description
Policy 1	Priority = 1 Attribute: localgroup = groupA, enforcement = DEFAULT
Policy 2	Priority = 2 Attribute: localgroup = groupB, enforcement = MANDATORY

Because the join directive is defined as UNION, the resulting policy uses the following definitions for the policies:

- During account creation, `localgroup` is defined as `groupA` and `groupB`.
- During reconciliations, `localgroup` is defined as `groupB` if the attribute is undefined or incorrectly defined.

Note: A union join directive is the default join directive for multi-valued attributes.

Chapter 12. Provisioning policy entitlement parameters

Provisioning policy parameters help system administrators define the attribute values that are required and the values that are allowed.

The following parameter types are valid:

- Constant value
- Null
- JavaScript
- Regular expression

The provisioning parameters in an entitlement can be statically or dynamically defined. Parameters are defined statically by selecting the constant parameter type and specifying literal values, such as strings or integers. For example, an attribute can be defined as Domain Users or Power® Users. A dynamically defined parameter value can be based on a JavaScript function. A range of values can be defined that use a regular expression.

Parameters can also be specified as Null, indicating that the parameter does not have a value. This situation is equivalent to having a JavaScript parameter type with a value of `return null;`

Provisioning parameters for single-valued attributes can be based only on JavaScript code or a constant. The provisioning parameters of a multi-valued attribute can use a constant, JavaScript code, or regular expression for their values.

However, a regular expression can be used only for provisioning parameter enforcement of the Allowed or Excluded type.

Provisioning policy constant

A static, constant value can be assigned to an entitlement parameter for a single or multivalued attribute with the provisioning policy Constant parameter type. You can define a provisioning parameter with a literal static value. You can enter the value or select a value based on the field widget.

Provisioning policy Null types

The null parameter type can be used to specify a null value for an account attribute. If the value of a parameter is specified as null with mandatory enforcement, no value is valid for that attribute. You can specifically define null value for the provisioning parameter, which is equivalent to specifying empty for the value.

Provisioning policy JavaScript functions

You can use a script to define provisioning parameters.

The provisioning parameters of an entitlement within a provisioning policy can be defined by a script. The context of the script is

- The person for whom the entitlement is being enforced.
- The service the entitlement is protecting.
- The `eruid` attribute of the target account.

The context of the script includes the following elements:

Subject

Owner of the account.

Service

Service on which the account exists or to be created.

uid

User ID of the account.

Context

Information about the parameter evaluation, which can be validation of a new account or validation of existing account.

A special object named *parameters* is available for *eruid* to evaluate the script in the context of provisioning policy parameters. To obtain its value, use the following syntax:

```
parameters.eruid[0]
```

The value of zero in this syntax returns the first value of the array object.

A JavaScript object named *subject* represents a user for whom the entitlement is being enforced. The service is represented by another JavaScript data model entity named *service*. The script author uses both the subject and service object to access attributes of these objects.

The values of attributes of objects that are part of the evaluation context can also be retrieved with the IBM Security Identity Manager custom JavaScript functions.

To use JavaScript to define the value of an attribute, the JavaScript parameter type must be selected. Select **JavaScript/Constant** in the **Expression Type** field.

The following examples demonstrate the use of IBM Security Identity Manager custom JavaScript functions within provisioning policies. For a complete reference to all custom JavaScript functions, see the JavaScript Extension Reference.

Person attributes

Syntax:

```
subject.getProperty(String rowAttrName)
```

Example:

```
subject.getProperty("sn")[0];
```

Example:

```
# Concatenates user's given name and family name with space in between.
# Resulting string value may be used to on account attribute such as
# Description.
{subject.getProperty("givenname")[0] + " " + subject.getProperty("sn")[0];}
```

Example:

```
# Set a user's Password attribute to the user's Shared Secret Attribute
# (if the account is automatically provisioned)
{
  function passInit()
  {var password = subject.getProperty("ersharedsecret");
   if (password.length > 0){
     return password[0];
   } else {
     return ""
   }
  }
  return
  passInit();
}
```

Search for person

Syntax:

```
PersonSearch.searchByFilter(String profileName, String filter, [int scope])
```

where scope =1 is a single level search and scope =2 is a subtree search.

Example:

```
PersonSearch.searchByFilter("Person", "(sn=Smith)", 1);
```

Search for service

Syntax:

```
ServiceSearch.searchByFilter(String filter, [int scope])
```

where scope=1 is a single level search and scope=2 is a subtree search.

Example:

```
ServiceSearch.searchByFilter("(erntllocalservername=*srv)", 1);
```

Service closest to the person

Syntax:

```
ServiceSearch.searchForClosestToPerson(Person person, [int scope])
```

where scope=1 is a single level search and scope=2 is a subtree search.

Example:

```
ServiceSearch.searchForClosestToPerson(subject);
```

Name of the business unit in which the person is located

Syntax:

```
subject.getProperty(String propertyName)
```

Example:

```
subject.getProperty("Parent")[0].name;
```

Specifying the current account Uid

Syntax:

```
uid = parameters.eruid[0];
```

Example:

```
var accountId = parameters.eruid[0];
```

Enrole.toGeneralizedTime statement

Syntax:

```
Enrole.toGeneralizedTime(Date date)
```

Examples:

Using the function to return today's date string:

```
var gt = Enrole.toGeneralizedTime(new Date());
```

Using the function to return today's date string as a default attribute:

```
{Enrole.toGeneralizedTime(new Date())}
```

Enrole.toMilliseconds statement

Syntax:

```
Enrole.toMilliseconds(String generalizedTime)
```

Examples:

```
var millis = Enrole.toMilliseconds("200101012004Z");  
var date = new Date(millis);
```

Provisioning policy regular expressions

Regular expressions are used to define a matching pattern that is checked against given text. Within IBM Security Identity Manager, regular expressions define allowed and excluded parameter values.

Within IBM Security Identity Manager, regular expressions define allowed and excluded parameter values. Parameter values with regular expressions are used against existing attribute values to determine which ones are valid.

To use a regular expression for a provisioning parameter value, select **Regular Expression** in the Expression Type menu.

Note: Regular Expression can be used only with excluded or allowed attributes. See the `regexp` Java library for a syntax reference.

Chapter 13. Service selection policy JavaScript

A service selection policy identifies the service type for the service returned, and the JavaScript specifies the service. For example, the service definition can be based on attributes of an account owner.

Service selection policy JavaScript objects

The service selection policy JavaScript returns an object that represents a IBM Security Identity Manager service entity.

The "subject" JavaScript object is a Person object that represents the account owner. Attributes of the Person can be used to construct filters to search and return the service. The ServiceModelExtension is available for Service Selection policy by default.

The following list includes APIs for the ServiceSearch JavaScript object that can be used to return the service:

- ServiceSearch.searchByName
- ServiceSearch.searchByFilter
- ServiceSearch.searchForClosestToPerson

See a JavaScript API reference guide for detailed information for these APIs.

Service selection policy script example

This section includes examples of Service Selection policy scripts.

Service selection based on family name

The following script returns a service instance based on the family name of the account owner. Other person attributes such as job title and location can be used to select service, as in this example.

```
function selectService() {
  var sn = subject.getProperty("sn")[0];
  var serviceInstance = null;
  if(sn=="Jones") {
    serviceInstanceArr = ServiceSearch.searchByFilter(
      "(erservicename=NT40X)", 1);

    if (serviceInstanceArr != null && serviceInstanceArr.length > 0)
      serviceInstance = serviceInstanceArr[0];
  } else {
    serviceInstanceArr = ServiceSearch.searchByFilter(
      "(erservicename=NT40Y)", 1);

    if (serviceInstanceArr != null && serviceInstanceArr.length > 0)
      serviceInstance = serviceInstanceArr[0];
  }
  return serviceInstance;
}
return selectService();
```

Searching for the closest service to the person

The following example searches for the service closest to the level of the person, based on the organization tree structure.

```
function selectService() {
  var services = ServiceSearch.searchForClosestToPerson(subject);

  if (services != null && services.length > 0) {
    return services[0];
  }
}
```

```
}  
}  
return selectService();
```


Chapter 14. SubForm control type

The SubForm control type provides a means to use custom user interfaces for complex multi-valued attributes.

This control type is used infrequently by some IBM Security Identity Manager adapters.

SubForm is a special control type used to start a servlet, JSP, or static HTML page from a window that opens from a custom IBM Security Identity Manager form. Use subforms to submit an arbitrary number of parameter names and values to a custom servlet or JSP. They are used to create custom user interfaces for complex multi-valued attributes.

Parameter	Description	Value
customServletURI	The URI to the servlet, JSP, or static HTML page to be started from the main form. If a servlet is implemented and deployed in the default web application for IBM Security Identity Manager, the value for this parameter is the same as the <i>URL-pattern</i> value defined by <code>web.xml</code> in the <i>servlet-mapping</i> tag, without the slash (/). If a JSP is implemented, the value for this parameter is the JSP file name that includes the jsp file extension. This parameter is required on all subforms.	Servlet name or JSP file name such as <code>sample.jsp</code>
<i>Parameter Name</i>	Arbitrary parameter name and value that is included in the HTTP request that starts the resource at <code>customServletURI</code> . For example: <code>objectClass=erracgrp</code>	<i>Parameter Value</i>

For more information, see the subform example and other information in the `ISIM_HOME/extensions/examples/` subdirectory that IBM Security Identity Manager provides.

SubForm contextual parameters

As a child element of a main form, a SubForm is passed contextual parameters that help identify the context from which it is started.

These contextual parameters are included in the HTTP Request that brings up the SubForm:

HTTP (contextual) Parameter Name	Person Create	Person Modify	Account Create	Account Modify
target_dn	empty	DN of Person	DN of account owner	DN of the account

Table 13. SubForm parameters (continued)

HTTP (contextual) Parameter Name	Person Create	Person Modify	Account Create	Account Modify
container_dn	DN of the organization tree container where the Person is created.	DN of the organization tree container where the person is located.	DN of account owner	DN of the account owner
search_base	empty	empty	DN of service	DN of the service instance on which an account is provisioned

To assign the `target_dn` HTTP parameter value to a String declared inside a servlet:

```
String targetDN = request.getParameter("target_dn");
```

Account Modify example

For example, for Account Modify, the value of contextual parameters are:

target_dn

Is the DN of the entity whose attributes are displayed on the main form. If the SubForm is placed on a RACF® account form, this parameter value is the DistinguishedName of the RACF account.

container_dn

Is the entity container or parent. For example, if the SubForm is placed on a Person form, this parameter value is the DistinguishedName of the parent or container of the person. The container can be an organization, organizational unit, admin domain, or location.

search_base

For example, if the SubForm is placed on a RACF account form, this parameter value is the DistinguishedName for the RACF service instance on which the account is provisioned.

HTTP request parameter naming convention

A naming convention used on SubForm parameters prevents collisions with other parameters (such as contextual parameters).

The naming convention for SubForm parameters is:

```
[prefix].[attributename].[parametername]
```

where:

prefix

property.data

attributename

Name of the attribute on which the SubForm is placed on the main form.

parametername

Name used in the SubForm Editor dialog. For example, an HTTP parameter named `property.erracfcconnectgroup.objectClass` would contain the value defined in the SubForm editor dialog assigned to `objectClass`.

To assign this value to a string declared inside a servlet:

```
String objectClass =  
request.getParameter("property.data.erracfconnectgroup.objectClass");
```

Process to write a SubForm

To write a custom SubForm, create a servlet that generates the HTML user interface to manage the value of the attribute.

To save the value, create an instance of `com.ibm.itim.common.AttributeValue` and bind it to a user's `HttpSession` with the key defined in `com.ibm.itim.webclient.util.FormData` (on one line):

```
AttributeValue av = new AttributeValue("attributename", "customValue");  
HttpSession session = request.getSession(false);  
session.setAttribute("subFormAttrValue", av);
```

This ensures that the value gets picked up and added to the form data collected from the fields when the main form is submitted.

Chapter 15. Supplemental property files

The following section provides detailed information about the property keys and values contained in the IBM Security Identity Manager supplemental property files.

Properties files

Java properties files define attributes that allow customizing and control of the Java software.

Standard system properties files and custom properties files are used to configure user preferences and user customization. A Java properties file defines the values of named resources that can specify program options such as database access information, environment settings, and special features and functions.

A properties file defines named resources with a property key and value pair format:

```
property-key-name=value
```

The *property-key-name* is an identifier for the resource. The *value* is usually the name of the actual Java object that provides the resource, or a String representing the value of the property key, such as `database.name=itimdb`. The statement syntax allows spaces before and after the equal (=) sign, and can span multiple lines if you place a line continuation character \ (a backslash) at the end of the line. For more information about statement syntax, see Java language references.

IBM Security Identity Manager uses a number of properties files to control the program and to allow user customization of special features.

Modifiable property files

This table lists the IBM Security Identity Manager properties files that you can modify.

Table 14 on page 175 lists the IBM Security Identity Manager properties files. Most files are in the `ISIM_HOME\data\` directory.

Additional properties files are not configurable. Do not modify them.

Property file name	Description
adhocreporting	The <code>adhocreporting.properties</code> file supports the custom reporting module.
<code>com_ibm_itim_isimm</code>	The <code>com_ibm_itim_isimm.properties</code> file contains properties that are required for configuring the IBM Security Identity Manager mobile app that is deployed on WebSphere Application Server.
CustomLabels	The property key and value pairs in the <code>CustomLabels.properties</code> file are used by the Security Identity Manager user interface to display the label text for forms.
DataBaseFunctions.conf	The custom reporting feature of Security Identity Manager allows you to use database functions when designing custom report templates.
enRole	The <code>enRole.properties</code> system configuration file contains many of the properties that are used to configure IBM Security Identity Manager. See Chapter 17, “System property configuration in <code>enRole.properties</code> ,” on page 255.

Table 14. Properties files (continued)

Property file name	Description
enroleAuditing	The property key and value pairs in the <code>enroleAuditing.properties</code> file are used to enable or disable the tracking of changes made by a Security Identity Manager user to business objects such as person, location, service, and other objects, or configuration of the system.
enRoleAuthentication	The <code>enRoleAuthentication.properties</code> file specifies the type of method that is used by the Security Identity Manager Server to authenticate users and identifies the Java object that provides the specified authentication mechanism.
enRoleDatabase	The <code>enRoleDatabase.properties</code> file specifies attributes that support the relational database used by Security Identity Manager.
enroleExtensionAttributes	The <code>enroleExtensionAttributes.properties</code> file contains properties to configure an image to show in the user cards that are shown in request access wizard associated with each user. The IBM Security Identity Manager provides a plug-in that can be used to dynamically generate the location (URI) of a user image. It is based on one or more attributes of the user.
enRoleFonts	The <code>enRoleFonts.properties</code> file specifies font names for locale languages.
enRoleHiddenAttributes	The <code>enRoleHiddenAttributes.properties</code> file contains the attributes of each object class (for example, person, service, account, organization unit) that are invisible to the IBM Security Identity Manager Console. This hidden attribute list contains mostly attributes used by the system.
enRoleLDAPConnection	The <code>enRoleLDAPConnections.properties</code> file provides standard configuration settings that allow successful communication between Security Identity Manager and the LDAP directory server.
enRoleLogging	The <code>enRoleLogging.properties</code> file specifies attributes that govern the operation of the jlog logging and tracing API that is bundled with Security Identity Manager.
enRoleMail	The <code>enRoleMail.properties</code> file contains attributes that specify the mail transport protocol that is used by the JavaMail API and other Security Identity Manager application-specific properties. You must provide the values for the application-specific properties.
enrolepolicies	The <code>enrolepolicies.properties</code> file provides standard and custom settings that support the functions of the provisioning policy.
enroleStartup	The <code>enroleStartup</code> file is used to specify startup activities in the WebSphere Application Server environment.
enroleworkflow	The <code>enroleworkflow.properties</code> file specifies the XML file mappings for system-defined workflows.
fesiextensions	The <code>fesiextensions.properties</code> file (deprecated) provides support for Free EcmaScript Interpreter (FESI) JavaScript extensions before Version 5.0 of Security Identity Manager. Do not author <i>new</i> extensions using this deprecated architecture.

Table 14. Properties files (continued)

Property file name	Description
helpmappings	The <code>helpmappings.properties</code> file allows a customer to replace the installed Security Identity Manager help system with an alternative help system.
<code>passwordrules</code>	The <code>passwordrules.properties</code> file is used to specify the custom class for generating passwords. IBM Security Identity Manager provides a default password generator.
<code>ReportDataSynchronization</code>	The <code>ReportDataSynchronization.properties</code> file contains properties to customize report data synchronization behavior.
reportingLabels	This properties file is like other labels-related properties files such as <code>labels.properties</code> , or <code>customLabels.properties</code> , and holds labels that are used by Reports.
reporttabledeny	By default, this property holds a list of Security Identity Manager tables that are used by various Security Identity Manager components to store internal or configuration data that is inappropriate for a report.
<code>rest</code>	The properties of the <code>rest.properties</code> file control the behavior of the REST interfaces that are included in IBM Security Identity Manager.
scriptframework	For <i>all</i> new JavaScript extensions, use the <code>scriptframework.properties</code> file to configure script extensions and other scripting functions.
SelfServiceHelp	The <code>SelfServiceHelp.properties</code> file can be used to redirect help to a custom location for customers who want to have their own help content for the self-service user interface.
SelfServiceHomePage	The <code>SelfServiceHomePage.properties</code> file is used to configure the sections of the initially installed home page for the self-service user interface. You can add or remove tasks, and update icon URLs and labels of the home page from this file.
<code>SelfServiceScreenText</code>	The <code>SelfServiceScreenText.properties</code> file is a resource bundle containing the labels for the self-service user interface.
SelfServiceUI	The <code>SelfServiceUI.properties</code> file controls miscellaneous properties of the self-service user interface.
ui	The <code>ui.properties</code> file specifies attributes that affect the operation and display of the Security Identity Manager graphical user interface.
UIConfig	The <code>UIconfig.properties</code> file contains the several properties that affect the Identity Service Center interface.
<code>wsExtensions</code>	The <code>wsExtensions.properties</code> file contains properties to register new classes for use by the <code>WSExtensionService</code> to extend the existing web services.

Non-modifiable properties files

Some property files are not configurable. Do not modify them.

Table 15 on page 178 lists the remaining property files that are used by IBM Security Identity Manager. In all cases, these files are not configurable. Do not modify them.

Property file name	Description
ConfigErrorMessages	This file is used by the runConfig utility and contains configuration error messages in English. Do not modify.
ConfigLabels	This file is used by the runConfig utility and contains IBM Security Identity Manager Console display labels in English. Do not modify.
ConfigMessages	This file is used by the runConfig utility and contains configuration instructions and normal messages in English. Do not modify.
CustomForms	This file is used for form generation, form display, and form design. Do not modify.
CustomThemes	Do not modify. This file has custom themes used by applets to support accessibility.
dataSynchronization	This file is used by the IBM Security Identity Manager Data Services component to define data replication for runtime execution optimization purpose. Do not modify.
Dsm12RootDSE	This file is used for searching a root DSE (LDAP) to return a collection of attributes about the IBM Security Identity Manager server. Do not modify.
Dsm12Schema	This file is used for searching a schema (LDAP) to return object classes and attributes specified in this file. Do not modify.
encryptionKey	This file is used to store the encryption password information in the IBM Security Identity Manager Console. Do not modify.
enRole2ldif	This file is now deprecated and was used for migration from enRole 3.x to 4.4. Do not modify.
enRoleEntityHiddenAttributes	This file is used to filter out LDAP attributes for each entity type available for mapping. For example, Organization, BPOrganization, Person, BPPerson. Do not modify.
enRoleFonts	This file specifies font names for locale languages. Do not modify.
enRoleHelp	This file contains a list of operations that are not in the workflow designer. Do not modify.

Table 15. Non-modifiable properties files (continued)

Property file name	Description
enRoleHiddenAttributes	This file contains the attributes of each object class (for example, person, service, account, organization unit) that are invisible to the IBM Security Identity Manager Console. This hidden attribute list contains mostly attributes used by the system. Do not modify.
enRoleHiddenOperations	Do not modify.
enRoleHiddenSearchAttributes	Attributes listed in this file are not in search activities or in any pending and completed request details. This file is used to filter out process data attributes that must not be displayed in the user interface. Do not remove the existing entries in this file, otherwise the search function on these attributes fails. Do not modify.
enRoleUnchangedAttributes	This file is used by the directory server upgrade utility. Do not modify.
enRoleValidateAttributes	This file is used internally by the IBM Tivoli Identity Manager Express® Server for entity schema attribute mapping. Do not modify.
entitlementHiddenAttributes	This file is used by the Tivoli Identity Manager Express Server for filtering out system managed attributes from displaying on the available entitlement parameter selection. Do not modify.
expressHiddenAttributes	This file was used by the Tivoli Identity Manager Express Server at Version 4.6.x. Do not modify.
HighContrastBigFontTheme	This file is used to specify the appearance of a high contrast, large font for applet accessibility. Do not modify.
<u>HighContrastTheme</u>	This file is used to specify high contrast display values for applet accessibility. Do not modify.
ibmSchemaSyntax	This file is used by LDAP configuration during IBM Security Identity Manager installation. Do not modify.
iplanetSchemaSyntax	This file is used by LDAP configuration during IBM Security Identity Manager installation. Do not modify.
itiminstaller	This file is during IBM Security Identity Manager installation. Do not modify.
Labels	This file contains English labels for the UI display. Do not modify.
Messages	This file contains all normal messages that IBM Security Identity Manager uses to communicate with users. Do not modify.

<i>Table 15. Non-modifiable properties files (continued)</i>	
Property file name	Description
passwordrules	This file is used to specify the custom class for generating passwords. IBM Security Identity Manager provides a default password generator. In the sample passwordrules.properties, the first line contains the class name. The second line defines the input requires by the class defined in line 1. Your site might require additional rules for use in production. Do not modify.
pimDataSync	This file is used by the IBM Security Identity Manager Data Services component to define shared access data replication for shared access runtime execution optimization purpose. Do not modify.
pimWorkflowDataSyntax	This files defines workflow data syntax for the Shared Access Module. Do not modify.
pimWorkflowextensions	This files defines workflow extensions for Shared Access Module. Do not modify.
platformcontext	This file specifies provisioning platform context information. Do not modify.
Properties	This file is the top-level properties file that indicates the actual properties file path. Do not modify.
subform	This file is used by the IBM Security Identity Manager server for subforms. Do not modify.
tenant	This file used for the creation of a new tenant. Do not modify.
tmsMessages	This file contains all error messages. Do not modify.
TungstenTheme	This file sets display values for applet accessibility. Do not modify.

adhocreporing.properties

The adhocreporing.properties file supports the custom reporting module.

Table 16 on page 180 defines the properties used to configure reporting.

<i>Table 16. adhocreporing.properties properties</i>	
Report Generation	
reportPageSize	

Table 16. *adhocreporting.properties* properties (continued)

	<p>Indicates the number of rows that are displayed on each page of a PDF report. The maximum number of rows on a page must not exceed 45.</p> <p>Example (default):</p> <pre>reportPageSize=45</pre>
<pre>reportColWidth</pre>	
	<p>Indicates the width, in centimeters (cm), of the report column in a PDF report output. You can adjust the size of all columns by modifying this value.</p> <p>Note: 2.54 cm equals 1 inch.</p> <p>Example (default):</p> <pre>reportColWidth=20</pre>
<p>Access Control Item Enforcement on Report Data Generated</p>	
<pre>availableForNonAdministrators</pre>	
	<p>Specifies whether to synchronize access control item-related information during data synchronization.</p> <p>Set this value to <code>true</code> to enable non-administrators to run reports.</p> <p>Set this value to <code>false</code> to disable all functions related to non-administrator execution of reports, such as access control item data synchronization and setting report access control items on reports.</p> <p>Example:</p> <pre>availableForNonAdministrators=true</pre>
<p>Incremental schema Enforcement using Incremental Data Synchronizer</p>	
<pre>enableDeltaSchemaEnforcer</pre>	
	<p>Specifies whether to synchronize any schema changes in reporting.</p> <p>Schema changes include new mappings that were created or existing mappings that were removed with the Schema Designer.</p> <p>When set to <code>true</code>, the Incremental Data Synchronizer manages the attributes that are mapped (changed) in the Schema Designer since the last full data synchronization was run.</p> <p>When set to <code>false</code>, the Incremental Data Synchronizer does not synchronize the attributes which are mapped (changed) since the last full data synchronization was run.</p> <p>Example (default):</p> <pre>enableDeltaSchemaEnforcer=false</pre>
<p>Data Synchronization</p>	

Table 16. *adhocreporting.properties* properties (continued)

<code>changeLogEnabled</code>	
	<p>Specifies whether the Incremental Data Synchronizer is used. Values include:</p> <ul style="list-style-type: none"> • true – Incremental Data Synchronizer is configured • false – Incremental Data Synchronizer is not configured <p>Example (default):</p> <pre style="background-color: #f2f2f2; padding: 5px;">changeLogEnabled=false</pre>
<code>changeLogBaseDN</code>	
	<p>Specifies the DN in the directory where the change log is configured.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2; padding: 5px;">changeLogBaseDN=cn=changeLog</pre>
<code>changeLogFetchSize</code>	
	<p>Specifies the number of change logs to be fetched at one time from the directory server.</p> <p>A value of 0, or a negative value, results in no fetch restriction. Fetch restriction is useful when the directory server cannot be heavily loaded for a time. For example, retrieving 100,000 change log entries at a time can delay the directory server response time for a few minutes.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2; padding: 5px;">changeLogFetchSize=200</pre>
<code>maximumChangeLogsToSynchronize</code>	
	<p>Specifies the maximum number of change logs to be synchronized in a single use of the Incremental Data Synchronizer.</p> <p>Consider the available system memory and CPU utilization that is required for other processes in the system when you set this property. If the value is set to zero or a negative value, the Incremental Data Synchronizer synchronizes all change log entries.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2; padding: 5px;">maximumChangeLogsToSynchronize=10000</pre>
<code>changeLogsToAnalyzeBeforeSynchronization</code>	

Table 16. *adhocreporting.properties* properties (continued)

	<p>Specifies the number of fetched change log entries to be analyzed before all analyzed entries are synchronized to the database.</p> <p>For example, consider the following values:</p> <pre>changeLogFetchSize=500 changeLogsToAnalyzeBeforeSynchronization=20000 maximumChangeLogsToSynchronize=100000</pre> <p>500 change log entries are considered one batch. After 20,000 change log entries (40 batches) are analyzed, data synchronization occurs. This process repeats until 100,000 entries are analyzed (5 synchronizations).</p> <p>Setting this value to 0 or a negative value results in synchronization of all fetched change log entries.</p> <p>Example (default):</p> <pre>changeLogsToAnalyzeBeforeSynchronization=5000</pre>
<pre>enableChangelogPruning</pre>	
	<p>Specifies whether changelog entries need to be pruned after they are successfully synchronized. This property takes effect only for the SunOne Version 5.2 directory server. For the IBM Security Directory Server, see its documentation about pruning changelog entries.</p> <p>Example (default):</p> <pre>enableChangelogPruning=false</pre>
<pre>itimAdminID</pre>	
	<p>Specifies the administrator ID required to run the Incremental Data Synchronizer in a z/OS® environment.</p> <p>For example:</p> <pre>itimAdminID=myadminid</pre>
<pre>itimAdminCredential</pre>	
	<p>Specifies the Security Identity Manager password required to run the Incremental Data Synchronizer in a z/OS environment.</p> <p>For example:</p> <pre>itimAdminCredential=myadmincredential</pre>
<pre>createIndex</pre>	

Table 16. *adhocreporting.properties* properties (continued)

	<p>Specifies whether to create database indexes for frequently used database columns. If this property is set to <code>true</code>, reports are generated more quickly.</p> <p>Valid values for this property are:</p> <ul style="list-style-type: none"> • true – Creates indexes for columns that are used by reporting. Enabling this value might increase the data synchronization time. • false – Does not create indexes during data synchronization. Disabling this value might increase the time that is needed to generate reports. <p>Example (default):</p> <pre>createIndex=true</pre>
<pre>reportIndexes</pre>	
	<p>Specifies a set of a set of <code><ENTITY: (ATTR1 ORDER1, ATTR2 ORDER2, ...)></code> values on which indexes are created.</p> <p>Both single and compound indexes can be created with this property. If you are creating a single index, use the name of entity that you see in the report designer or schema mapping.</p> <p>If you are defining a compound index, specify the exact table name, such as <code>Account</code> or <code>Person_cn</code>, instead of the entity name. You can specify an optional order <code>asc</code> or <code>desc</code> for an index. Observe the usage of a semi-colon as the delimiter between indexes. You must maintain the syntax of this property correctly, or indexes might not get created successfully.</p> <p>If you add additional indexes, follow the syntax for these default indexes:</p> <pre>reportIndexes=Person:cn asc;Account:eraccountcompliance; Account:(eraccountstatus asc);Account:erlastaccessdate asc; Account:eruid asc;Service:(servicetype asc); Service:erservicename asc;ProvisioningPolicy:erpolicyitemname asc; ProvisioningPolicy:erpolicytarget asc; ProvisioningPolicy:erpolicymembership asc;Role:errolename asc; Account:(eraccountstatus asc, erservice asc); Person_cn:(dn, cn);Account_owner:(dn asc, owner asc)</pre>
<pre>sqlBatchSize</pre>	
	<p>Indicates the size of batch updates that are processed during data synchronization. To improve performance, set this value to a larger number. This value is affected by the specific database settings for the transaction log file size, a database property. Setting the value too high might cause data synchronization to fail. Always use the default value of 50 to avoid data synchronization failure.</p> <p>A value of 0, or a negative value, causes all SQL updates to be processed as a single batch.</p> <p>Example (default):</p> <pre>sqlBatchSize=50</pre>
<pre>attribsSkippedInSchema</pre>	

Table 16. *adhocreporting.properties* properties (continued)

	<p>These attributes contain XMLs as data. The reporting engine currently does not support reporting on these attributes.</p> <p>Example (on one line):</p> <pre>attribsSkippedInSchema=erEntitlements erAcl erHistoricalPassword erJavascript erLostPasswordAnswer erPassword erPlacementRule erxforms erXML</pre>
<pre>reportsAllowedAttributes</pre>	
	<p>A set of attributes on which reporting engine does not enforce attribute-level access control.</p> <p>Example (default):</p> <pre>reportsAllowedAttributes=servicetype</pre>
<pre>reportsAllowedEntities</pre>	
	<p>A set of entities on which reporting engine does not enforce attribute-level access control.</p> <p>Example (default):</p> <pre>reportsAllowedEntities=RecertificationPolicy,Group</pre>
<pre>reservedWords</pre>	
	<p>Database reserved words. These words are not used as table/column names during Schema Mapping and Data Synchronization.</p> <p>Example (on one line):</p> <pre>reservedWords=ALL ADD ALTER BACKUP BEGIN BY BULK CASCADE CHECK CHECKPOINT CLUSTORED COLUMN CREATE CURRENT DUMMY DOMAIN DELETE DEFAULT DISTINCT DROP FOREIGN FROM GROUP IDENTITY IDENTITY_INSERT IDENTITYCOL INSERT IN LIKE SET SELECT TABLE VALUES ORDER UID WHERE</pre>
<pre>disallowedChars</pre>	
	<p>Characters that are not part of Table/Column name in database. If the entity/attribute name contains one or more of these characters, the characters are removed from the table or column name. In the following example, the double backslashes (//) are used as escape characters.</p> <p>Example (default):</p> <pre>disallowedChars=~!@#%&*()+{} :/"<>? -=[]//;' ,./</pre>
<pre>disallowedCharsForStart</pre>	
	<p>Characters are not used as the starting character of table or column name. In the following example, the double backslashes (//) are used as escape characters.</p> <p>Example (default):</p> <pre>disallowedCharsForStart=~!@#%&*()_+{} :/"<>? -=[]//;' ,./0123456789</pre>

Table 16. *adhocreporting.properties* properties (continued)

<code>maxTableNameLength</code>	
	<p>Default maximum length for a table name.</p> <p>Example (default):</p> <pre>maxTableNameLength=30</pre>
<code>maxColumnNameLength</code>	
	<p>Default maximum length for a column name.</p> <p>Example (default):</p> <pre>maxColumnNameLength=30</pre>
<code>maxTableNameLength_DB2</code>	
	<p>Maximum name length for a table name in DB2®.</p> <p>Example (default):</p> <pre>maxTableNameLength_DB2=128</pre>
<code>maxColumnNameLength_DB2</code>	
	<p>Maximum name length for a column name in DB2.</p> <p>Example (default):</p> <pre>maxColumnNameLength_DB2=30</pre>
<code>maxTableNameLength_ZDB2</code>	
	<p>Maximum name length for a table name in DB2 z/OS.</p> <p>Example (default):</p> <pre>maxTableNameLength_ZDB2=128</pre>
<code>maxColumnNameLength_ZDB2</code>	
	<p>Maximum name length for a column name in DB2 z/OS.</p> <p>Example (default):</p> <pre>maxColumnNameLength_ZDB2=30</pre>
<code>maxTableNameLength_ORACLE=30</code>	

Table 16. *adhocreporting.properties* properties (continued)

	<p>Maximum name length for a table name in Oracle.</p> <p>Example (default):</p> <pre>maxTableNameLength_ORACLE=30</pre>
<pre>maxColumnNameLength_ORACLE</pre>	
	<p>Maximum name length for a column name in Oracle.</p> <p>Example (default):</p> <pre>maxColumnNameLength_ORACLE=30</pre>
<pre>maxTableNameLength_MS_SQL_SERVER</pre>	
	<p>Maximum name length for a table name in Microsoft SQL Server.</p> <p>Example (default):</p> <pre>maxTableNameLength_MS_SQL_SERVER=128</pre>
<pre>maxColumnNameLength_MS_SQL_SERVER</pre>	
	<p>Maximum name length for a column name in Microsoft SQL Server.</p> <p>Example (default):</p> <pre>maxColumnNameLength_MS_SQL_SERVER=128</pre>
<pre>populateGroupMembers</pre>	
	<p>Specifies whether Service group membership changes need to be synchronized during incremental synchronization. Service group membership information is stored in the GROUPMEMBERS table.</p> <p>Valid values for this property are:</p> <ul style="list-style-type: none"> • true – Synchronizes membership changes to service groups and accesses (for example, because of a new access request). • false – Does not synchronize group membership changes, since this type of synchronization is performance intensive. <p>Example (default):</p> <pre>populateGroupMembers=false</pre>

CustomLabels.properties

The property key and value pairs in the `CustomLabels.properties` file are used by the IBM Security Identity Manager user interface to display the label text for forms.

The key name must be entirely lowercase in each property key and value pair.

A separate `CustomLabels.properties` file exists for each individual language supported by IBM Security Identity Manager.

This file is used to provide localized versions of graphical user interface elements when IBM Security Identity Manager is installed in international environments.

Add the property key and value pairs in the `CustomLabels.properties` file to display any labels.

For example, to display a two word access type - **Business Applications**,

1. Specify the access key as **businessApplications**. The access type key cannot contain a space.
2. Specify the value as **Business Applications**.

The entry in the `CustomLabels.properties` file to have "Business Applications" displayed in the user interface as the access type is **businessApplications=Business Applications**.

Access types that are part of a hierarchy of types have a special notation that you must use in the `CustomLabels.properties` file. Each node of the hierarchy must be in the key and separated by a period (.). For example, an access type that is called **Applications** has a child **businessApplications**. You want **businessApplications** to display as "Business Applications". The entry that you define in the `CustomLabels.properties` file is **Applications.businessApplications=Business Applications**.

A file name extension identifies the specific language. For example:

English

`CustomLabels_en.properties`

Japanese

`CustomLabels_ja.properties`

DataBaseFunctions.conf

The custom reporting feature of Security Identity Manager allows you to use database functions when designing custom report templates.

This file is in the `ISIM_HOME/data` directory.

You can use the database functions with the Report Designer component of IBM Security Identity Manager by defining the functions in the `DataBaseFunctions.conf` file.

Pre-defined database function properties use the following format in the `DataBaseFunctions.conf` file:

```
<function_name> - <number_of_arguments>
```

Database users can also create and define functions for their custom use. Custom functions are called user-defined functions in Microsoft SQL and IBM DB2. Functions created as stored procedures in DB2 can also be used for reporting. Functions must be created with the database utilities that are provided by the respective database vendor.

User-defined database function properties use the following format in the `DataBaseFunctions.conf` file:

```
user:<function_name> - <number_of_arguments>
```

Only functions with a single argument are supported in the IBM Security Identity Manager Report Designer.

<i>Table 17. DataBaseFunctions.conf</i>
Upper

Table 17. *DataBaseFunctions.conf* (continued)

	<p>Converts the argument to uppercase.</p> <p>Example:</p> <pre>Upper - 1</pre>
<pre>Lower</pre>	
	<p>Converts the argument to lowercase.</p> <p>Example:</p> <pre>Lower - 1</pre>

enroleAuditing.properties

The property key and value pairs in the `enroleAuditing.properties` file are used to enable or disable the tracking of changes made by a Security Identity Manager user to business objects such as person, location, service, and other objects, or configuration of the system.

Any user request to change the IBM Security Identity Manager directory store or database can be audited and published in a report.

The following is a comprehensive list of events audited:

- ACI Management (**Add, Add Authorization Owner, Delete, Delete Authorization Owner, Modify**)
- Account Management (**Add, Adopt, Change Password, Delete, Modify, Orphan, Password Pickup, Restore, Suspend, Synchronize Password**)
- Access Management (**Add, Remove**)
- Access Configuration (**Add, Remove, Modify**)
- Authentication (**Authenticate ITIM user**)
- Container Management (**Add, Delete, Modify**)
- Delegate Authority (**Add, Delete, Modify**)
- Entitlement Workflow Management (**Add, Delete, Modify**)
- Entity Operation Management (**Add, Delete, Modify**)
- IBM Security Identity Manager Configuration (**Add, Delete, Enforce, Install Profile, Modify, Uninstall Profile**)
- Group Management (**Add, Add Member, Delete, Modify, Remove Member**)
- Migration (**Agent Profile Install, Start Export, Start Import, Stop Export, Stop Import**)
- Role Management (**Add, Add Member, Delete, Modify, Remove Member**)
- Person Management (**Add, Delete, Modify, Restore, Self Register, Suspend, Transfer**)
- Policy Management (**Add, Commit Draft, Delete, Enforce Entire Policy, Modify, Save as Draft, Add Account Template, Change Account Template, Remove Account Template**)
- Reconciliation (**Run Recon, Set Recon Unit, Set Service Recon Parameters**)
- Runtime Events (**Start IBM Security Identity Manager, Stop IBM Security Identity Manager**)
- Self Password Change (**Change Password, Reset Password**)
- Service Management (**Add, Add Adoption Rule, Delete, Delete Adoption Rule, Modify, ModifyAdoption Rule**)

- Service Policy Enforcement (**Correct Non-Compliant, Mark Non-Compliant, Suspend Non-Compliant, Use Global Setting, Use Workflow For Non-Compliant**)

Audited information specifically includes:

- The identity of the user who takes the action.
- The time the action was taken.
- The type of action taken.
- The data effected by the action.

Table 18 on page 190 defines the properties used to configure how the auditing feature behaves.

<i>Table 18. enroleAuditing.properties properties</i>	
IBM Security Identity Manager audit configuration settings	
<code>itim.auditing</code>	
	<p>Specifies whether to enable or disable auditing for IBM Security Identity Manager events.</p> <p>Valid values include:</p> <ul style="list-style-type: none"> • true – IBM Security Identity Manager events are audited • false – IBM Security Identity Manager events are not audited, regardless of the settings of individual events or categories <p>Example (default):</p> <pre>itim.auditing=true</pre>
<code>itim.auditing.retrycount</code>	
	<p>The number of times auditing is tried again in case of failure.</p> <p>Valid values include any integer.</p> <p>Example (default):</p> <pre>itim.auditing.retrycount=1</pre>
<code>itim.auditing.retrydelay</code>	
	<p>The wait time in milliseconds before trying again.</p> <p>Example (default):</p> <pre>itim.auditing.retrydelay=5000</pre>
<code>enrole.auditing.errorpopup.enabled</code>	
	<p>Enables or disables the process failure display.</p> <p>Example (default):</p> <pre>enrole.auditing.errorpopup.enabled=false</pre>

Table 18. *enroleAuditing.properties* properties (continued)

<code>enrole.auditing.errorpopup.fields</code>	
	<p>The process failure display always contains these attributes and their values:</p> <pre>{name, subject, type, result_summary}</pre> <p>You can additionally specify one or more of these attributes:</p> <pre>{subject, comments, name, type, requester_type, requester_name, description, scheduled, started, completed, lastmodified, submitted, state, notify, requestee_name, subject_profile, subject_service, result_summary, result_detail}</pre> <p>Example:</p> <pre>enrole.auditing.errorpopup.fields=subject, comments</pre>
<code>enrole.auditing.errorpopup.textwrap</code>	
	<p>Specifies whether the text wraps at the end of the display.</p> <p>Example (default):</p> <pre>enrole.auditing.errorpopup.textwrap=false</pre>
<code>enrole.auditing.pageSize</code>	
	<p>Specifies the page size in lines that displaying unsuccessful processes or activities on the failed activity popup.</p> <p>Example (default):</p> <pre>enrole.auditing.pageSize=10</pre>
<code>enrole.auditing.pageLinkMax</code>	
	<p>Specifies the number of page links for multi-page result sets on the failed activity.</p> <p>Example (default):</p> <pre>enrole.auditing.pageLinkMax=10</pre>
<code>enrole.auditing.viewRequests.skipServiceLookup.customProcessTypes</code>	

Table 18. *enroleAuditing.properties* properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the custom process type that does not have a service or an account as subject data in the input parameters of its corresponding workflow operation.</p> <p>To use this property, add it to the <code>\$ISIM_HOME/data/enroleAuditing.properties</code> file with a custom process type value.</p> <p>Valid values: A comma-separated custom process type value.</p> <p>Example (default):</p> <pre>enrole.auditing.viewRequests.skipServiceLookup.customProcessTypes=CP</pre>
--	---

enRoleAuthentication.properties

The `enRoleAuthentication.properties` file specifies the type of method that is used by the Security Identity Manager Server to authenticate users and identifies the Java object that provides the specified authentication mechanism.

Additionally, the file specifies objects that support IBM Security Access Manager WebSEAL single sign-on and administration of IBM Security Identity Manager to managed remote services.

Authentication properties are specified with a property key and value pair format:

```
property-key-name=value
```

The *property-key-name* is an identifier for the authentication mechanism or resource. The *value* is the name of the Java object that provides the authentication service, expressed also as a key and value pair.

```
factory=value
```

The **factory** key name represents a special category for authentication support within the IBM Security Identity Manager software. The *value* is the actual name of the Java object.

For example (entered on one line):

```
enrole.authentication.provider.service=
factory=com.ibm.enrole.authentication.service.
ServiceAuthenticationProviderFactory
```

Table 19 on page 192 defines the properties used to configure IBM Security Identity Manager authentication.

Table 19. *enRoleAuthentication.properties* properties

Authentication method
<pre>enrole.authentication.requiredCredentials={simple}</pre>

Table 19. *enRoleAuthentication.properties* properties (continued)

	<p>Specifies the required authentication method for users who log in to the IBM Security Identity Manager Server.</p> <p>The valid value for this property is:</p> <ul style="list-style-type: none"> • simple - User name and password. <p>Example (default):</p> <pre>enrole.authentication.requiredCredentials=simple</pre>
Authentication providers (factories)	
<pre>enrole.authentication.provider.simple</pre>	
	<p>Specifies the Java object that handles authentication with user name and password. Custom authentication providers are not supported in the IBM Security Identity Manager Server virtual appliance.</p> <p>Example (entered on a single line):</p> <pre>enrole.authentication.provider.simple=\ factory=com.ibm.itim.authentication.simple. SimpleAuthenticationProviderFactory</pre>
Authentication service provider	
<pre>enrole.authentication.provider.service</pre>	
	<p>Specifies the Java object that transparently handles IBM Security Identity Manager access to managed remote services and to manage changes in the accounts to these remote services.</p> <p>These changes include addition, deletion, suspension, restoration, and modification of accounts on the remote service. When you log in to IBM Security Identity Manager, you can change the login and password information for an account on the managed remote service.</p> <p>The <code>ServiceAuthenticationProviderFactory</code> mechanism works with the agent for a given remote service and processes the changed information.</p> <p>Example (entered on a single line):</p> <pre>enrole.authentication.provider.service=\ factory=com.ibm.itim.authentication.service. ServiceAuthenticationProviderFactory</pre>
WebSEAL single sign-on	
<pre>enrole.authentication.provider.webseal</pre>	
	<p>Specifies the Java object that allows single sign-on in a WebSEAL environment.</p> <p>Example (entered on a single line):</p> <pre>enrole.authentication.provider.webseal=\ factory=com.ibm.itim.authentication.webseal.WebsealProviderFactory</pre>
<pre>enrole.authentication.idsEqual</pre>	

Table 19. *enRoleAuthentication.properties* properties (continued)

	<p>Indicates the appropriate algorithm for mapping the IBM Security Access Manager user ID to an IBM Security Identity Manager user ID. An internal identity mapping algorithm is used to ensure the success of the single sign-on operation.</p> <p>Valid values for this property are:</p> <ul style="list-style-type: none"> • true – The Security Access Manager user ID is the same as the IBM Security Identity Manager user ID. • false – The Security Access Manager user ID is not the same as the IBM Security Identity Manager user ID. <p>Example:</p> <pre>enrole.authentication.idsEqual=true</pre>
--	---

enRoleDatabase.properties

The `enRoleDatabase.properties` file specifies attributes that support the relational database used by Security Identity Manager.

The property key values contained in this file are synchronized with values in the appropriate application server configuration file. Most values in this file are supplied during initial installation of IBM Security Identity Manager and the configuration of the database. You can make subsequent changes to some values. However, you must use the **runConfig** utility to synchronize the property file values with the values in the application server configuration file.

IBM Security Identity Manager uses Java Database Connectivity (JDBC) to access the relational database. With the JDBC API, you can access virtually any tabular data source from the Java programming language.

Table 20 on page 194 defines the properties used to configure database properties.

Table 20. *enRoleDatabase.properties* properties

Database information	
<code>database.db.type</code>	
	<p>Do not modify this property key. The value is supplied during the initial installation of IBM Security Identity Manager.</p> <p>Specifies the database type that is used by IBM Security Identity Manager.</p> <p>Example:</p> <pre>database.db.type=DB2</pre>
<code>database.db.server</code>	

Table 20. *enRoleDatabase.properties* properties (continued)

	<p>This value is supplied during the installation of IBM Security Identity Manager and the configuration of the database.</p> <p>Specifies the name or local alias name of the remote database.</p> <p>To change this value for a new database, use the database configuration utility to set up the database. The database configuration utility supplies the new database name to this properties file.</p> <p>To change this value for another existing database, use the runConfig utility to supply the new database name to this properties file.</p> <p>The value for <code>database.db.server</code> is stored in following format: <code>db_host_name:port:database_name</code></p> <p>Examples:</p> <ul style="list-style-type: none"> • DB2 <pre>10.77.214.35:50000:itimdb</pre> • Oracle <pre>tivsun13:1521:itimdb</pre> • Microsoft SQL <pre>tivsun13:1433:itimdb</pre>
<pre>database.db.owner</pre>	
	<p>Do not modify this property key. The value is built in to the system.</p> <p>Specifies the name of the database schema owner for IBM Security Identity Manager.</p> <p>Example (default):</p> <pre>database.db.owner=itimuser</pre>
<pre>database.db.user</pre>	
	<p>Do not modify this property key. The value is built in to the system.</p> <p>Specifies a default database user for IBM Security Identity Manager.</p> <p>Example (default):</p> <pre>database.db.user=itimuser</pre>
<pre>database.db.password</pre>	

Table 20. *enRoleDatabase.properties* properties (continued)

	<p>Do not modify this property key. The value is supplied during database configuration.</p> <p>Specifies the password for the database user.</p> <p>Encryption of this value is specified by the <code>enrole.password.database.encrypted</code> property in <code>enRole.properties</code>.</p> <p>The password value is encrypted by default unless the encryption setting was deactivated with the runConfig utility.</p> <p>Example:</p> <pre>database.db.password=secret</pre>
<p>Connection pool properties</p>	
<pre>database.jdbc.connectionPool.initialCapacity</pre>	
	<p>Do not manually edit this file to modify this property key value. Use the runConfig utility to change this value.</p> <p>Specifies the initial number of physical database connections to create for the connection pool. This value must be less than or equal to the <code>database.jdbc.connectionPool.maxCapacity</code> value.</p> <p>Example:</p> <pre>database.jdbc.connectionPool.initialCapacity=5</pre>
<pre>database.jdbc.connectionPool.maxCapacity</pre>	
	<p>Do not manually edit this file to modify this property key value. Use the runConfig utility to change this value.</p> <p>Specifies the maximum number of physical database connections that can be created. This value is used to manage system performance tuning.</p> <p>Example (default):</p> <pre>database.jdbc.connectionPool.maxCapacity=50</pre>
<p>JDBC driver</p>	
<pre>database.jdbc.driverurl</pre>	

Table 20. *enRoleDatabase.properties* properties (continued)

<p>Do not remove or modify this property key and value.</p> <p>Specifies the URL of the JDBC driver. The default value is <code>jdbc:db2://db_host_name:port/database_name</code>.</p> <p>Examples:</p> <ul style="list-style-type: none">• DB2 <pre>jdbc:db2://10.77.214.31:50000/itimdb</pre> <ul style="list-style-type: none">• Oracle <pre>jdbc:oracle:thin:@host_name:1521:itimdb</pre> <ul style="list-style-type: none">• Microsoft SQL Server <pre>jdbc:sqlserver://;server=9.72.121.180;port=1433;database=itimdb</pre>
<pre>database.jdbc.driver</pre>
<p>Do not remove or modify this property key and value.</p> <p>Specifies the JDBC driver name.</p> <p>Examples:</p> <ul style="list-style-type: none">• DB2 <pre>database.jdbc.driver=com.ibm.db2.jcc.DB2Driver</pre> <ul style="list-style-type: none">• Oracle <pre>database.jdbc.driver=oracle.jdbc.driver.OracleDriver</pre> <ul style="list-style-type: none">• Microsoft SQL Server <pre>com.microsoft.sqlserver.jdbc.SQLServerDriver</pre>

enRoleLDAPConnection.properties

The `enRoleLDAPConnections.properties` file provides standard configuration settings that allow successful communication between Security Identity Manager and the LDAP directory server.

Table 21 on page 197 defines the properties used to configure LDAP directory server properties.

Table 21. *enRoleLDAPConnection.properties* properties

<pre>java.naming.factory.initial</pre>
--

Table 21. *enRoleLDAPConnection.properties* properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies the built-in Java class file that provides the communication interface between IBM Security Identity Manager and the LDAP directory server. The Java Naming and Directory Interface (JNDI) protocol is used.</p> <p>Example:</p> <pre>java.naming.factory.initial=com.sun.jndi.ldap.LdapCtxFactory</pre> <p>LDAP context: <code>Context.INITIAL_CONTEXT_FACTORY</code></p>
<pre>java.naming.provider.url</pre>	
	<p>Specifies the URL of the LDAP directory server. The LDAP server is on:</p> <ul style="list-style-type: none"> • The local IBM Security Identity Manager Server. In this case, use <code>localhost</code>. • A remote computer. In this case, use the short or fully qualified host name or the IP address. <p>The value for this property is initially configured during IBM Security Identity Manager installation. You can also provide this value with the ldapconfig utility or runConfig utility.</p> <p>Example:</p> <pre>java.naming.provider.url=ldap://localhost:389</pre> <p>LDAP context: <code>Context.PROVIDER_URL</code></p>
<pre>java.naming.security.principal</pre>	
	<p>Specifies the distinguished name (DN) of the LDAP administration account on the LDAP directory server.</p> <p>The value for this key is initially configured during IBM Security Identity Manager installation. You can also provide this value with the ldapconfig utility or runConfig utility.</p> <p>Example:</p> <pre>java.naming.security.principal=cn=root</pre> <p>Example for Sun Open Net Environment (ONE) Directory Server:</p> <pre>java.naming.security.principal=cn=directory manager</pre> <p>LDAP context: <code>Context.SECURITY_PRINCIPAL</code></p>
<pre>java.naming.security.credentials</pre>	

Table 21. *enRoleLDAPConnection.properties* properties (continued)

	<p>Specifies the password for the LDAP administration account on the LDAP directory server.</p> <p>The value for this key is initially configured during IBM Security Identity Manager installation. You can also provide this value with the ldapconfig utility or runConfig utility.</p> <p>Encryption of this value is specified by the <code>enrole.password.ldap.encrypted</code> property in the <code>enRole.properties</code> file.</p> <p>The encryption type is initially configured during IBM Security Identity Manager installation.</p> <p>Example:</p> <pre>java.naming.security.credentials=ibmldap</pre> <p>LDAP context: <code>Context.SECURITY_CREDENTIALS</code></p>
<pre>java.naming.security.protocol</pre>	
	<p>By default, this property is commented out.</p> <p>Specifies the protocol that is used for communication between IBM Security Identity Manager and the LDAP directory server. For example, to enable SSL, uncomment the line and change it to <code>java.naming.security.protocol=ssl</code>.</p> <p>LDAP context: <code>Context.SECURITY_PROTOCOL</code></p>
<pre>java.naming.security.authentication</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the authentication type that is used by the LDAP directory server. Valid types include:</p> <ul style="list-style-type: none"> • none - The anonymous: user becomes a member of an unauthenticated group. • simple - The user supplies a user name and password. • strong - A stronger authentication mechanism that you provide. <p>Example:</p> <pre>java.naming.security.authentication=simple</pre> <p>LDAP context: <code>Context.SECURITY_AUTHENTICATION</code></p>
<pre>java.naming.referral</pre>	

Table 21. *enRoleLDAPConnection.properties* properties (continued)

	<p>Do not modify this property key and value.</p> <p>If multiple LDAP directory servers are linked in the IBM Security Identity Manager environment, this property specifies whether to use links when a referral is needed to complete a request for LDAP information.</p> <p>Valid values include:</p> <ul style="list-style-type: none"> • follow --- Use links to complete an LDAP information request. • ignore --- Do not use links to complete an LDAP information request. • throw --- Do not use links to complete an LDAP information request. and return an error message. <p>Example:</p> <pre>java.naming.referral=follow</pre> <p>LDAP context: Context.REFERRAL</p>
<pre>java.naming.batchsize</pre>	
	<p>Do not modify this property key and value.</p> <p>A JNDI property that specifies the number of data elements returned at one time during a request (query) to the LDAP directory server. A larger number reduces the number of LDAP fetches, which might improve performance.</p> <p>A value of 0 blocks any control by the client (IBM Security Identity Manager) until all requested elements are returned.</p> <p>Example:</p> <pre>java.naming.batchsize=100</pre> <p>LDAP context: Context.BATCHSIZE</p>
<pre>java.naming.ldap.derefAliases</pre>	
	<p>Specifies that look up for an object by using the alias dereferences the alias so that what is returned is the object pointed to by the DN of the alias</p> <p>Valid values include:</p> <ul style="list-style-type: none"> • never --- Do not dereference an alias during object lookup. • always --- Dereference an alias during object lookup. • finding --- Dereference an alias during object lookup (only during name resolution). • searching --- Dereference an alias during object lookup (only after name resolution). <p>Example:</p> <pre>java.naming.ldap.derefAliases=never</pre>
<pre>java.naming.ldap.attributes.binary</pre>	

Table 21. *enRoleLDAPConnection.properties* properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies IBM Security Identity Manager attributes that are treated as binary data type. Multiple attribute values are separated by a single space.</p> <p>Example (on a single line):</p> <pre>java.naming.ldap.attributes.binary=erPassword erHistoricalPassword erSynchPassword erServicePassword erPersonPassword</pre> <p>LDAP context: <code>attribute.binary</code></p>
<pre>com.sun.jndi.ldap.connect.pool</pre>	
	<p>Activates the LDAP connection pool.</p> <p>Valid values include:</p> <ul style="list-style-type: none"> • true - Use the LDAP connection pool. • false - Do not use the LDAP connection pool. <p>Example (default):</p> <pre>com.sun.jndi.ldap.connect.pool=true</pre>
<pre>com.sun.jndi.ldap.connect.timeout</pre>	
	<p>Specifies the number of milliseconds that a client waits for a pooled connection to become available. If the property is not specified, the client waits indefinitely.</p> <p>Example:</p> <pre>#com.sun.jndi.ldap.connect.timeout=</pre>

enRoleLogging.properties

The `enRoleLogging.properties` file specifies attributes that govern the operation of the **jlog** logging and tracing API that is bundled with Security Identity Manager.

`jlog` is a logging package for Java. With this package, you can log messages by message type and priority. At run time, you also can control how these messages are formatted and where they are reported.

Table 22 on page 201 defines the properties that are used to configure IBM Security Identity Manager logging properties and which are available for modification.

Table 22. *enRoleLogging.properties* properties

<p>General settings</p>
<pre>logger.refreshInterval</pre>

Table 22. *enRoleLogging.properties* properties (continued)

	<p>Specifies the refresh interval [in milliseconds] of the logging properties.</p> <p>Example:</p> <pre>logger.refreshInterval=300000</pre>
<pre>logger.msg.com.ibm.itim.security.logChoice</pre>	
	<p>Specifies the type of authentication attempts to log.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • failure -- Log authentication failures. • success -- Log authentication successes. • both -- Log both authentication failures and successes. <p>Example:</p> <pre>logger.msg.com.ibm.itim.security.logChoice=failure</pre>
<pre>logger.msg.com.ibm.itim.security.logging</pre>	
	<p>Specifies whether authentication attempts are logged or not.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • true -- Log authentication attempts. • false -- Do not log authentication attempts. <p>Example:</p> <pre>logger.msg.com.ibm.itim.security.logging=true</pre>
<pre>handler.file.security.maxFiles</pre>	
	<p>Specifies the maximum number of security log files.</p> <p>Example:</p> <pre>handler.file.security.maxFiles=10</pre>
<pre>logger.msg.level</pre>	
	<p>Specifies the logging level for messages.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • INFO • WARN • ERROR <p>Example:</p> <pre>logger.msg.level=INFO</pre>

Table 22. *enRoleLogging.properties* properties (continued)

<code>handler.file.msg.maxFiles</code>	
	<p>Specifies the maximum number of message log files.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;">handler.file.msg.maxFiles=5</pre>
<code>logger.trace.level</code>	
	<p>Specifies the tracing level.</p> <p>The supported trace levels are:</p> <ul style="list-style-type: none"> • DEBUG_MIN • DEBUG_MID • DEBUG_MAX <p>DEBUG_MAX is the most verbose trace level and can effect system performance. When you debug a problem, avoid setting DEBUG_MAX at <code>logger.trace</code>. Set the DEBUG_MAX at the effected components or packages.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;">logger.trace.level=DEBUG_MIN</pre>
<code>handler.file.trace.maxFiles</code>	
	<p>Specifies the maximum number of trace log files.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;">handler.file.trace.maxFiles=10</pre>
<code>handler.file.maxFileSize</code>	
	<p>Specifies the maximum log file size in kilobytes</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;">handler.file.maxFileSize=1024</pre>
Logger root properties	
<code>jlog.noLogCmd</code>	
	<p>Do not modify this property key and value.</p> <p>Disables the log command server.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;">jlog.noLogCmd=true</pre>

Table 22. *enRoleLogging.properties* properties (continued)

<code>logger.className</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the class name of the logger.</p> <p>Example:</p> <pre>logger.className=com.ibm.log.PDLogger</pre>
<code>logger.description</code>	
	<p>Specifies the description of the logger.</p> <p>Example:</p> <pre>logger.description=TIM PD Logger</pre>
<code>logger.product</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the product name.</p> <p>Example:</p> <pre>logger.product=CTGIM</pre>
<code>logger.productInstance</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the server instance name. The value is supplied during the installation of Security Identity Manager.</p> <p>Example:</p> <pre>logger.productInstance=myserver</pre>
Message logger properties	
<code>logger.msg.description</code>	
	<p>Specifies the description of the message logger.</p> <p>Example:</p> <pre>logger.msg.description=TIM PD Message Logger</pre>
<code>logger.msg.logging</code>	

Table 22. *enRoleLogging.properties* properties (continued)

	<p>Turns logging on or off for messages.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • true --- Turns logging on. • false --- Turns logging off. <p>Example:</p> <pre>logger.msg.logging=true</pre>
<pre>logger.msg.messageFile</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the resource bundle name of localizable messages.</p> <p>Example:</p> <pre>logger.msg.messageFile=tmsMessages</pre>
<pre>logger.msg.com.ibm.itim.ui.messageFile</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the resource bundle name of localizable messages.</p> <p>Example: (on a single line)</p> <pre>logger.msg.com.ibm.itim.ui.messageFile= com.ibm.itim.ui.resources.UIMessageResources</pre>
<pre>logger.msg.listenerNames</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the listener names attached to the message logger.</p> <p>Example:</p> <pre>logger.msg.listenerNames=handler.file.msg handler.ffdc.fileCopy</pre>
<p>Security logger properties</p>	
<pre>logger.msg.com.ibm.itim.security.listenerNames</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the listener names attached to the security logger.</p> <p>Example:</p> <pre>logger.msg.com.ibm.itim.security.listenerNames=handler.file.security</pre>
<p>Trace logger properties</p>	

Table 22. *enRoleLogging.properties* properties (continued)

<code>logger.trace.description</code>	
	<p>Specifies the description of the trace logger.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">logger.trace.description=TIM PD Trace Logger</pre>
<code>logger.trace.logging</code>	
	<p>Turns trace logging on or off.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • true --- Turns logging on. • false --- Turns logging off. <p>Example:</p> <pre style="background-color: #f2f2f2;">logger.trace.logging=true</pre>
<code>logger.trace.listenerNames</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the listener names attached to the trace logger.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">logger.trace.listenerNames=handler.file.trace</pre>
<code>logger.trace.com.ibm</code>	

Table 22. *enRoleLogging.properties* properties (continued)

	<p>Edit the level of these component loggers to adjust the amount of tracing information written to the trace log.</p> <p>The supported trace levels are:</p> <ul style="list-style-type: none"> • DEBUG_MIN • DEBUG_MID • DEBUG_MAX <p>Component loggers are:</p> <p>Note: The <code>logger.trace.com.ibm.itim.script.level</code> component logger is equivalent to <code>logger.trace.com.ibm.itim.fesiextensions.level</code> (deprecated).</p> <pre> logger.trace.com.ibm.itim.adhocreport.level logger.trace.com.ibm.itim.adhocreport.changelog.level logger.trace.com.ibm.itim.apps.level logger.trace.com.ibm.itim.apps.ejb.adhocreport.level logger.trace.com.ibm.itim.authentication.level logger.trace.com.ibm.itim.authorization.level logger.trace.com.ibm.itim.common.level logger.trace.com.ibm.itim.fesiextensions.level logger.trace.com.ibm.itim.script.level logger.trace.com.ibm.itim.mail.level logger.trace.com.ibm.itim.messaging.level logger.trace.com.ibm.itim.dataservices.model.level logger.trace.com.ibm.itim.passworddelivery.level logger.trace.com.ibm.itim.policy.level logger.trace.com.ibm.itim.remoteservices.level logger.trace.com.ibm.itim.remoteservices.installation.level logger.trace.com.ibm.itim.report.level logger.trace.com.ibm.itim.security.level logger.trace.com.ibm.itim.scheduling.level logger.trace.com.ibm.itim.script.level logger.trace.com.ibm.itim.systemConfig.level logger.trace.com.ibm.itim.util.level logger.trace.com.ibm.itim.webclient.level logger.trace.com.ibm.itim.workflow.level logger.trace.com.ibm.daml.level logger.trace.com.ibm.erma.level </pre>
<p>Applet tracing properties</p>	
<pre>logger.trace.com.ibm.itim.applet.logging</pre>	
	<p>Enables or disables applet trace logging.</p> <p>Example:</p> <pre>logger.trace.com.ibm.itim.applet.logging=true</pre>
<pre>logger.trace.com.ibm.itim.applet.level</pre>	

Table 22. *enRoleLogging.properties* properties (continued)

	<p>Specifies the applet tracing level.</p> <p>The supported trace levels are:</p> <ul style="list-style-type: none"> • DEBUG_MIN • DEBUG_MID • DEBUG_MAX <p>Example:</p> <pre>logger.trace.com.ibm.itim.applet.level=DEBUG_MIN</pre>
File handler properties	
<code>handler.file.className</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the class name of the file handler.</p> <p>Example:</p> <pre>handler.file.className=com.ibm.log.FileHandler</pre>
<code>handler.file.description</code>	
	<p>Specifies the description of the file handler.</p> <p>Example:</p> <pre>handler.file.description=TIM File Handler</pre>
<code>handler.file.fileDir</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the base directory of the file handler. This value is supplied during installation.</p> <p>Example:</p> <pre>handler.file.fileDir=c:/tivoli_comm_dir/CTGIM/logs</pre>
<code>handler.file.formatterName</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the formatter of the file handler.</p> <p>Example:</p> <pre>handler.file.formatterName=formatter.PDXML</pre>
Message logging file handler properties	
<code>handler.file.msg.fileName</code>	

Table 22. *enRoleLogging.properties* properties (continued)

	<p>Specifies the message log file.</p> <p>Example:</p> <pre>handler.file.msg.fileName=msg.log</pre>
<pre>handler.file.msg.formatterName</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the formatter of the message file handler.</p> <p>Example:</p> <pre>handler.file.msg.formatterName=formatter.PDXML.msg</pre>
<p>Security logging file handler properties</p>	
<pre>handler.file.security.fileDir</pre>	
	<p>Specifies the security log directory.</p> <p>Example:</p> <pre>handler.file.security.fileDir=c:/tivoli_comm_dir/CTGIM/logs</pre>
<pre>handler.file.security.fileName</pre>	
	<p>Specifies the security log file.</p> <p>Example:</p> <pre>handler.file.security.fileName=access.log</pre>
<pre>handler.file.security.formatterName</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the formatter of the security file handler.</p> <p>Example:</p> <pre>handler.file.security.formatterName=formatter.PDXML.security</pre>
<p>Trace file handler properties</p>	
<pre>handler.file.trace.fileName</pre>	
	<p>Specifies the trace file name.</p> <p>Example:</p> <pre>handler.file.trace.fileName=trace.log</pre>

Table 22. *enRoleLogging.properties* properties (continued)

<code>handler.file.trace.formatterName</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the formatter of the trace file handler.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">handler.file.trace.formatterName=formatter.PDXML.trace</pre>
FFDC (First-Failure Data Capture) file copy handler properties	
<code>handler.ffdc.baseDir</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the ffdc base directory.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">handler.ffdc.baseDir=c:/tivoli_comm_dir/CTGIM/ffdc</pre>
<code>handler.ffdc.triggerRepeatTime</code>	
	<p>Specifies the minimum time [in milliseconds] after an initial triggering that the handler responds to subsequent triggering events.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">handler.ffdc.triggerRepeatTime=300000</pre>
<code>handler.ffdc.fileCopy.className</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the handler class name.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">handler.ffdc.fileCopy.className=com.tivoli.log.FileCopyHandler</pre>
<code>handler.ffdc.fileCopy.triggerFilter</code>	
	<p>Specifies the filter to control which events trigger an FFDC action.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">handler.ffdc.fileCopy.triggerFilter=filter.msgId</pre>
<code>handler.ffdc.fileCopy.fileTimestampFormat</code>	

Table 22. *enRoleLogging.properties* properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies the time stamp format which is appended to the FFDC folder name and file names.</p> <p>Example:</p> <pre>handler.ffdc.fileCopy.fileTimestampFormat=yyyy.MM.dd-HH.mm.ss</pre>
<pre>handler.ffdc.fileCopy.filesToCopy</pre>	
	<p>Specifies the files to be copied to the FFDC directory when the FFDC is triggered.</p> <p>Example (on a single line):</p> <pre>handler.ffdc.fileCopy.filesToCopy= "c:/tivoli_comm_dir/CTGIM/logs/trace.log" "c:/tivoli_comm_dir/CTGIM/logs/msg.log"</pre>
<p>FFDC message id filter properties</p>	
<pre>filter.msgId.className</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the class name of the message ID filter.</p> <p>Example:</p> <pre>filter.msgId.className=com.tivoli.log.MsgIdFilter</pre>
<pre>filter.msgId.description</pre>	
	<p>Specifies the description of the message ID filter.</p> <p>Example:</p> <pre>filter.msgId.description=IBM Security Identity Manager FFDC Message Id Filter</pre>
<pre>filter.msgId.msgIds</pre>	
	<p>Specifies the TMS message IDs that trigger the FFDC action. The listed message IDs represent the most severe system errors.</p> <p>Example (on a single line):</p> <pre>filter.msgId.msgIds=CTGIMA401E CTGIMA438W CTGIME013E CTGIME035E CTGIME203E CTGIMF003E CTGIMF011E CTGIMF012E CTGIMF013E CTGIMF014E</pre>
<pre>filter.msgId.mode</pre>	

Table 22. *enRoleLogging.properties* properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies the filter mode.</p> <p>Example:</p> <pre>filter.msgId.mode=PASSTHRU</pre>
<pre>filter.msgId.msgIdRepeatTime</pre>	
	<p>Specifies the minimum time in milliseconds to wait after a log event is passed with a TMS message ID before it passes another one with the same ID.</p> <p>Example:</p> <pre>filter.msgId.msgIdRepeatTime=300000</pre>
<p>Formatter properties</p>	
<pre>formatter.className</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the class name of the formatter.</p> <p>Example:</p> <pre>formatter.className=com.ibm.log.Formatter</pre>
<pre>formatter.description</pre>	
	<p>Specifies the description of the formatter.</p> <p>Example:</p> <pre>formatter.description=formatter</pre>
<pre>formatter.dateFormat</pre>	
	<p>Specifies the Java SimpleDateFormat pattern to format event dates.</p> <p>Example:</p> <pre>formatter.dateFormat=yyyy.MM.dd</pre>
<pre>formatter.timeFormat</pre>	

Table 22. *enRoleLogging.properties* properties (continued)

	<p>Specifies the Java SimpleDateFormat pattern to format event time.</p> <p>Example:</p> <pre>formatter.timeFormat=HH:mm:ss.SSS</pre>
PDXML formatter properties	
	<pre>formatter.PDXML.className</pre>
	<p>Do not modify this property key and value.</p> <p>Specifies the formatter class name which formatting log event in LOG XML format.</p> <p>Example:</p> <pre>formatter.PDXML.className=com.ibm.itim.logging.LogXMLFormatter</pre>
	<pre>formatter.PDXML.description</pre>
	<p>Specifies the description of the formatter.</p> <p>Example:</p> <pre>formatter.PDXML.description=TIM Log XML Formatter</pre>
	<pre>formatter.PDXML.msg.forceAsMessage</pre>
	<p>Force the message formatter to format all output as message events, regardless of their contents.</p> <p>Example:</p> <pre>formatter.PDXML.msg.forceAsMessage=true</pre>

Enabling tracing for the Security Identity Manager user interface

You must set the level to FINEST in WebSphere Application Server to get the user interface trace working.

Enabling tracing for the Security Identity Manager user interface is a two-step process:

- Set the appropriate component loggers in the *enRoleLogging.properties* file.
- Enable WebSphere tracing by logging in to the WebSphere Application Server administrative console.

To enable the tracing level for the WebSphere Application Server administrative console, complete these steps:

1. Log in to the WebSphere Application Server administrative console.
2. Select **Troubleshooting -> Logs and Trace**.
3. Click the appropriate server (for example, *Server1*).
4. Select **Change log detail levels** under **General Properties**.
 - To make a static change to the configuration, click the **Configuration** tab.

A list of well-known components, packages, and groups is displayed.

- To change the configuration dynamically, click the **Runtime** tab.

The list of components, packages, and groups displays all the components that are currently registered on the running server.

5. Expand the node for `com.ibm.itim.*` under ***[All Components]**.
6. Click the node labeled `com.ibm.itim.ui.*` and select **All Messages and Traces**.
7. Click **Apply**.
8. Click **OK**.
9. Stop and then restart the WebSphere Application Server to set the static configuration changes.

You must enable the debug level for the user interface package in the following section of the `enRoleLogging.properties` file:

```
# UI-tier tracing
# logger.trace.com.ibm.itim.ui.level=DEBUG_MIN
# logger.trace.com.ibm.itim.ui.common.level=DEBUG_MIN
# logger.trace.com.ibm.itim.ui.controller.level=DEBUG_MIN
# logger.trace.com.ibm.itim.ui.customizer.level=DEBUG_MIN
# logger.trace.com.ibm.itim.ui.help.level=DEBUG_MIN
# logger.trace.com.ibm.itim.ui.impl.level=DEBUG_MIN
# logger.trace.com.ibm.itim.ui.listener.level=DEBUG_MIN
# logger.trace.com.ibm.itim.ui.tasklauncher.level=DEBUG_MIN
# logger.trace.com.ibm.itim.ui.validator.level=DEBUG_MIN
# logger.trace.com.ibm.itim.ui.view.level=DEBUG_MIN
# logger.trace.com.ibm.itim.ui.viewmodel.level=DEBUG_MIN
```

For more information about setting the trace level, see http://www.ibm.com/support/knowledgecenter/SSBJCK_7.0.0/com.ibm.btools.modeler.basic.inst.doc/configuring/settingloggingpreferences.html.

enRoleMail.properties

The `enRoleMail.properties` file contains attributes that specify the mail transport protocol that is used by the JavaMail API and other Security Identity Manager application-specific properties. You must provide the values for the application-specific properties.

Default values are provided for the **JavaMail** specific properties. They include the default mail provider and protocol. If you change the default values for the specific JavaMail properties, you must provide your own testing and verification of custom protocol and implementation.

Go to the following URL for more usage and provider information:

<http://java.sun.com/products/javamail/>

Table 23. *enRoleMail.properties* file properties

Mail attributes specific to the IBM Security Identity Manager application
mail.baseurl

Table 23. *enRoleMail.properties* file properties (continued)

	<p>Specifies the base URL for constructing the login URL in email notifications sent to new IBM Security Identity Manager users. The default value before you run the runConfig utility for the first time is <code>http://localhost:80</code>.</p> <p>This value is provided during IBM Security Identity Manager installation. You can also provide the value with the runConfig utility.</p> <p>This property is mandatory.</p> <p>Example</p> <pre>mail.baseurl=http://localhost:80</pre>
<pre>mail.itim.context</pre>	
	<p>Specifies the root context for IBM Security Identity Manager.</p> <p>Example</p> <pre>mail.itim.context=/itim</pre>
<pre>mail.context.console</pre>	
	<p>Specifies the root context for IBM Security Identity Manager console.</p> <p>This property is mandatory.</p> <p>Example</p> <pre>mail.context.console=/itim/console</pre>
<pre>mail.context.enduser</pre>	
	<p>Specifies the root context for IBM Security Identity Manager self-service console.</p> <p>This property is mandatory.</p> <p>Example</p> <pre>mail.context.enduser=/itim/self</pre>
<pre>mail.context.servicecenter</pre>	
	<p>Specifies the root context for IBM Security Identity Manager Service Center.</p> <p>This property is mandatory.</p> <p>Example</p> <pre>mail.context.servicecenter=/itim/ui</pre>

Table 23. *enRoleMail.properties* file properties (continued)

<code>mail.from</code>	
	<p>Specifies the return email address of the current user.</p> <p>This value is initially provided during IBM Security Identity Manager installation. You can also provide the value with the runConfig utility.</p> <p>This property is mandatory.</p> <p>Example</p> <pre style="background-color: #f2f2f2;">mail.from=admin@us.example.com</pre>
<code>mail.transport.protocol</code>	
	<p>Specifies the default transport protocol. The default is the Sun SMTP transport protocol.</p> <p>This property is mandatory.</p> <p>Example for the default value.</p> <pre style="background-color: #f2f2f2;">mail.transport.protocol=SMTP</pre>
<code>mail.title</code>	
	<p>This property is not used to specify the title banner of email notification in IBM Tivoli Identity Manager Version 5.0.</p> <p>The <code>mail.title</code> property of <code>Labels.properties</code> specifies title banner of email notification. You must edit this <code>properties</code> file directly to provide the value to this property.</p> <p>This property was previously mandatory.</p> <p>Example for the default value at previous releases.</p> <pre style="background-color: #f2f2f2;">mail.title=ITIM notification</pre>
Mail attributes specific to the built-in JavaMail service	
<code>mail.host</code>	
	<p>Specifies the IP address of the computer where the mail server is located.</p> <p>This value is initially provided during IBM Security Identity Manager installation. You can also provide this value with the runConfig utility.</p> <p>This property is mandatory.</p> <p>Example</p> <pre style="background-color: #f2f2f2;">mail.host=192.0.2.5</pre>

Table 23. *enRoleMail.properties* file properties (continued)

<code>mail.protocol.host</code>	
	<p>Specifies the IP address of the protocol-specific default mail server. This property key overrides the <code>mail.host</code> property key.</p> <p>By default, this property is not mandatory and no value is provided.</p>
<code>mail.protocol.user</code>	
	<p>Specifies the protocol-specific default user name for connecting to the Mail server. This property key overrides the <code>mail.user</code> property key.</p> <p>By default, this property is not mandatory and no value is provided.</p>
<code>mail.protocol.class</code>	
	<p>Specifies the Java class implementation of the mail protocol.</p> <p>Example for the default value.</p> <pre>mail.SMTP.class=com.sun.mail.smtp.SMTPTransport</pre>
<code>mail.store.protocol</code>	
	<p>Specifies the default message access protocol.</p> <p>By default, this property is not mandatory and no value is provided.</p>
<code>mail.user</code>	
	<p>Specifies a user name that is used during authentication when you connect to a mail server.</p> <p>By default, this property is not mandatory and no value is provided. In the IBM Security Identity Manager environment, the mail server is located within firewall boundaries, rendering this level of authentication unnecessary.</p>
<code>mail.protocol.user</code>	
	<p>Specifies the protocol-specific user name that is used during authentication when you connect to a mail server. This property key overrides the <code>mail.user</code> property key.</p> <p>By default, this property is not mandatory and no value is provided.</p>
<code>mail.smtp.starttls.enable</code>	
	<p>Specifies whether to enable TLS session with the mail server. Values allowed are <code>true</code> or <code>false</code>.</p> <p>Example:</p> <pre>mail.smtp.starttls.enable=true</pre>

Table 23. *enRoleMail.properties* file properties (continued)

<code>mail.smtp.auth</code>	
	Specifies whether to enable SMTP mail server authentication. Values allowed are <code>true</code> or <code>false</code> . Example: <pre>mail.smtp.auth=true</pre>
<code>mail.smtp.auth.user</code>	
	Specifies the user ID that is used by IBM Security Identity Manager to authenticate with the mail server when authentication is enabled. Example: <pre>mail.smtp.auth.user=user1</pre>
<code>mail.smtp.auth.password</code>	
	Specifies the password for <code>mail.smtp.auth.user</code> . Use runConfig utility to update the encrypted password. Example: <pre>mail.smtp.auth.password=password</pre>

enrolepolicies.properties

The `enrolepolicies.properties` file provides standard and custom settings that support the functions of the provisioning policy.

Functions supported by this properties file includes:

- Specifying Java classes to process provisioning policy conflicts with join directives
- Specifying default and non-default join directive caching timeouts
- Declaring policy attributes to be ignored during policy compliance validation

A join directive is a set of rules that is used to determine how attributes are handled when a provisioning policy conflicts with another. Join directives use logical constructs to resolve conflicts. Examples include combining all policy attributes (union), with only common attributes (intersection), and resolving conflicts with Boolean AND or OR logic.

There are 12 types of join directives that you can use. Provisioning policy join directives take effect when more than one provisioning policy is defined for the same user (or group of users) for the same target service, service instance, or service type.

Custom join directives can be defined by writing a custom Java class, adding it to your class path, and then providing the fully qualified Java class name in the policy configuration GUI. If you extend or replace one of the existing join directive classes, you must add the custom property key and value to the `enrolepolicies.properties` file. For example if you developed a new class (`com.abc.TextualEx`) to replace the existing class for textual joins, the registration line is as follows:

```
provisioning.policy.join.Textual= com.abc.TextualEx
```

Table 24 on page 219 defines the properties used to configure IBM Security Identity Manager policies.

Table 24. *enrolepolicies.properties properties*

Join directive classes

```
provisioning.policy.join.PrecedenceSequence=com.ibm.itim.policy.join.PrecedenceSequence

provisioning.policy.join.Boolean=com.ibm.itim.policy.join.Boolean
provisioning.policy.join.Bitwise=com.ibm.itim.policy.join.Bitwise
provisioning.policy.join.Numeric=com.ibm.itim.policy.join.Numeric
provisioning.policy.join.Textual=com.ibm.itim.policy.join.Textual
provisioning.policy.join.Textual.AppendSeparator=<<<>>
provisioning.policy.join.Multivalued=com.ibm.itim.policy.join.Multivalued
```

Do not modify these property keys and values.

Each property key specifies a Java class. It can be used to process the logic of a join directive that is required to resolve a provisioning policy conflict.

Append separator characters

```
provisioning.policy.join.Textual.AppendSeparator
```

Specifies the character that is used by the textual join directive Java class to separate individual values of a multi-value attribute.

Example:

```
provisioning.policy.join.Textual.AppendSeparator=<<<>>
```

Join directive cache timeouts

```
provisioning.policy.join.defaultCacheTimeout
```

Specifies the timeout interval [in seconds] between refreshes of the cache that stores default join directive cache values.

The default is 86400 seconds, which is 24 hours.

Example (default):

```
provisioning.policy.join.defaultCacheTimeout=86400
```

```
provisioning.policy.join.overridingCacheTimeout
```

Specifies the timeout interval [in seconds] between refreshes of the cache that stores non-default join directive values.

The default is 300 seconds, which is 5 minutes.

Example:

```
provisioning.policy.join.overridingCacheTimeout=300
```

Account attributes ignored by policy compliance validation

Table 24. *enrolepolicies.properties properties (continued)*

Excluded generic attributes (default value=1):

```

nonvalidateable.attribute.eraccountcompliance
nonvalidateable.attribute.eracl
nonvalidateable.attribute.eraccountstatus
nonvalidateable.attribute.erauthorizationowner
nonvalidateable.attribute.erglobalid
nonvalidateable.attribute.erhistoricalpassword
nonvalidateable.attribute.erisdeleted
nonvalidateable.attribute.erlastmodifiedtime
nonvalidateable.attribute.erlogontimes
nonvalidateable.attribute.ernumlogons
nonvalidateable.attribute.erparent
nonvalidateable.attribute.erpassword
nonvalidateable.attribute.erservice
#nonvalidateable.attribute.eruid
nonvalidateable.attribute.objectclass
nonvalidateable.attribute.owner
nonvalidateable.attribute.ercreatedate
nonvalidateable.attribute.erlaststatuschangedate
nonvalidateable.attribute.erpswdlastchanged
nonvalidateable.attribute.erlastaccessdate
nonvalidateable.attribute.ernumlogonattempt
    
```

Excluded Windows Server attributes:

```

nonvalidateable.attribute.erntpasswordexpired
nonvalidateable.attribute.erntuserbadpwdcount
nonvalidateable.attribute.erntlockedout
    
```

Declares account attributes that are to be ignored during policy compliance validation. This exclusion list reduces overhead during compliance validation. It also reduces the risk of system failure that can be caused by attributes that cannot logically be resolved during validation.

Partition size

```
policy.partition.size
```

To analyze many persons during a policy change event without incurring transaction timeouts, you must break apart or partition the total number of affected persons. It is done, not for starting the concurrent policy analysis, but strictly to avoid waiting in a single database transaction for all persons to be processed. Creating multiple transactions or quickly partitioning the total number of users diminishes the chance of any (smaller) transactions to exceed the transaction timeout value. When a WebSphere Application Server cluster is used with IBM Security Identity Manager, it is helpful to note that partitioning operation itself is not clustered. It is done on the same WebSphere Application Server node which receives the policy change request.

Specifies the number of persons or accounts to be evaluated in each thread during high volume policy analysis. High volume policy analysis occurs when a policy change or a service enforcement level change affects a large group of persons or accounts. A larger partition size results in fewer threads. A smaller partition size results in more executed threads in parallel, which requires more memory.

Example (default):

```
policy.partition.size=2500
```

```
policy.message.size
```

Table 24. *enrolepolicies.properties properties (continued)*

	<p>Specifies the number of persons that are analyzed as part of policy change within a single JMS message. Since WebSphere Application Server polled and reuses threads, the JMS mechanism queues the individual units of analysis work for all assigned WebSphere Application Server threads or message consumers. It is likely that during large policy changes that affect large numbers of people, all JMS consumer threads are busy processing policy analysis and enforcement; the queue for each thread is saturated with more messages to process.</p> <p>Example (default):</p> <pre>policy.message.size=25</pre>
<p>Additional properties</p>	
<pre>policy.analysiservicebatch.size</pre>	
	<p>Specifies the maximum number of services to be analyzed in each policy analysis message. This property is useful during policy/person analysis when a person has many accounts. To prevent system from running into OOM or hung threads this property can be tuned.</p> <p>By default, the property is commented out and an internal hardcoded value of 100 is applied. This default 100 service per batch is found to be optimal for environments that has users who own up to 50 K accounts across multiple platforms.</p> <p>Example (default):</p> <pre>policy.analysiservicebatch.size=100</pre>
<pre>policy.service.selection.maxsearch.size</pre>	
	<p>This property is used to return the specified number of Persons that are affected by the policy. It also checks whether the policy references any Person of given user class in any one of its memberships.</p> <p>The number is for person search, which is per policy, and thus additive based on the policies involved. It prevents an accidental explosion of the server's JVM with an OOM. By default, the property has an internal hardcoded value of 10000. This property is used while evaluating a collection of service move operations for persons that are affected by adding a host selection policy. It is also used while evaluating a service selection script.</p> <p>Example (default):</p> <pre>policy.service.selection.maxsearch.size=10000</pre>
<pre>policy.cleanup.commitFrequency</pre>	

Table 24. *enrolepolicies.properties properties (continued)*

	<p>Specifies the number of rows that are to be deleted as a batch from database tables while the policy analysis data is cleaned up..</p> <p>The value of this property if set to 0, commits database updates only at the end when the entire cleanup activity is completed.</p> <p>If this property value is set to any number greater than 0, the commit is done when the number of uncommitted database updates are equal to this set value. If negative or non-integer value is specified, then default value of 0 is used. The default value of the property is 0 and suggested values are multiples of 1000 (Ex: 25000).</p> <p>Example (default):</p> <pre>policy.cleanup.commitFrequency=0</pre>
<p>During a provisioning policy preview operation, IBM Security Identity Manager evaluates and joins other dependent provisioning policies that are applicable to a user. Performing a lookup for the policy and its dependent data in directory server and parsing it for each user can hamper performance. IBM Security Identity Manager caches the already parsed policies for better performance.</p> <p>Following caches are created:</p> <ul style="list-style-type: none"> • Policy Cache: Maintains a mapping of provisioning policy DNs and policy objects in cache with policy DN as the key. • RoleDN Cache: Maintains a mapping of Organizational Role DN and a set of provisioning policy DNs in cache with Organizational Role DN as the key. • ServiceDN Cache: Maintains a mapping of Service DN and a set of provisioning policy DNs in cache with Service DN as the key. <p>The greater number of data objects in the cache, the greater is the consumption of memory. The following three properties help to tune the caches by defining the maximum number of policies, service DNs, and role DNs to be cached.</p>	
<p>Provisioning policy cache size</p>	
<pre>policy.policiescache.size</pre>	
	<p>Specifies the number of provisioning policies to be cached in Policy cache for each provisioning policy preview request. For better performance, the size can be set to number of policies in the Organization.</p> <p>Example (default):</p> <pre>policy.policiescache.size=100</pre>
<p>Organizational Role DN cache size</p>	
<pre>policy.roledncache.size</pre>	

Table 24. *enrolepolicies.properties* properties (continued)

	<p>Specifies the number of role DNs to be cached in RoleDN cache for each provisioning policy preview request. For better performance, the size can be set to number of roles in the Organization.</p> <p>Example (default):</p> <pre>policy.roledncache.size=100</pre>
Service DN cache size	
<pre>policy.servicedncache.size</pre>	
	<p>Specifies the number of Service DNs to be cached in ServiceDN cache for each provisioning policy preview request. For better performance, the size can be set to number of services in the Organization.</p> <p>Example (default):</p> <pre>policy.servicedncache.size=100</pre>

enroleStartup.properties

The `enroleStartup` file is used to specify startup activities in the WebSphere Application Server environment.

Table 25 on page 223 defines the properties used to configure IBM Security Identity Manager policies.

Table 25. *enroleStartup.properties* properties

<pre>enrole.startup.names</pre>	
	<p>Lists the background services that are started during IBM Security Identity Manager startup. Do not modify this property.</p>
<pre>enrole.startup.shutdownTrigger.name</pre>	
	<p>The registered class used during shutdown of processes. Do not modify this property.</p>
<pre>enrole.startup.WAS50J2EEShutdownTrigger.attributes</pre>	
	<p>Additional parameters to be passed in to the registered shutdown class. Do not modify this property.</p>
<p>These properties define the background services startup. Do not modify these properties.</p>	

Table 25. `enroleStartup.properties` properties (continued)

	<code>enrole.startup.Scheduler.attributes</code> <code>enrole.startup.PasswordExpiration.attributes</code> <code>enrole.startup.DataServices.attributes</code> <code>enrole.startup.PostOffice.attributes</code> <code>enrole.startup.RemotePending.attributes</code> <code>enrole.startup.PolicyAnalysis.attributes</code> <code>enrole.startup.ReconcilerCleanup.attributes</code> <code>enrole.startup.PasswordSynchStore.attributes</code> <code>enrole.startup.Monitoring.attributes</code> <code>enrole.startup.WebServices.attributes</code>
	<code>enrole.startup.MessageListeners.attributes</code>
	The JMS queue endpoint listeners can be deactivated during startup for a node in a cluster with disaster recovery configuration. Do not modify this attribute in a single server setup. Deactivating endpoint listeners can cause JMS queue errors if none of the messages is being processed.
	<code>enrole.appServer.standby</code>
	Defines whether the node that is participating in a cluster setup should be a standby node. A standby node does not participate in background shared workload. Available for cluster setup. Do not modify this attribute in a single server setup.
	<code>enrole.appServer.standby.inactiveMessageListeners</code>
	Provides an override to the list of message endpoint listeners to be deactivated in a standby mode. Effective only when <code>enrole.appServer.standby</code> is true.
	<code>enrole.appServer.standby.inactiveStartupInitializer</code>
	Provides an override to the list of background services to be deactivated in a standby mode. Effective only when <code>enrole.appServer.standby</code> is true.

enroleworkflow.properties

The `enroleworkflow.properties` file specifies the XML file mappings for system-defined workflows.

A workflow is a process that specifies the flow of operations that involve business operations and human interactions. A workflow design defines the manner in which a particular business logic is processed. The XML files specified in the `enroleworkflow.properties` file implement workflow designs.

The system workflow is identified by a unique type ID and an associated XML file. The XML workflow files are in the following directory:

```
ISIM_HOME/data/workflow_systemprocess
```

Do not remove or modify the default system workflow type IDs and XML file values in the `enroleworkflow.properties` file.

The updating of the following XML files is not supported.

Table 26 on page 225 defines the properties used to configure IBM Security Identity Manager workflows.

Table 26. *enroleworkflow.properties* properties

Policy enforcement workflow
<code>enrole.workflow.PS=enforcepolicyforservice.xml</code>
Account fulfillment for noncompliant accounts workflow
<code>enrole.workflow.EN=fulfillpolicyforaccount.xml</code>
Service selection management workflow
<code>enrole.workflow.SA=addserviceselectionpolicy.xml</code> <code>enrole.workflow.SC=changeserviceselectionpolicy.xml</code> <code>enrole.workflow.SD=removeserviceselectionpolicy.xml</code>
Provisioning policy management workflow
<code>#Add policy</code> <code>enrole.workflow.PA=addpolicy.xml</code> <code>#Modify policy</code> <code>enrole.workflow.PC=changepolicy.xml</code> <code>#Delete policy</code> <code>enrole.workflow.PD=removepolicy.xml</code> <code>#User BU change</code> <code>enrole.workflow.U0=userbuchange.xml</code>
Reconciliation workflow
<code>enrole.workflow.RC=reconciliation.xml</code> <code>enrole.workflow.HR=hrfeed.xml</code>
Dynamic role workflow
<code>#Add dynamic role</code> <code>enrole.workflow.DA=adddynamicrole.xml</code> <code>#Modify dynamic role</code> <code>enrole.workflow.DC=changedynamicrole.xml</code> <code>#Delete dynamic role</code> <code>enrole.workflow.DD=removedynamicrole.xml</code> <code>#Import Policy Enforcement</code> <code>enrole.workflow.PE=importpolicyenforcement.xml</code> <code>#Process Lifecycle Rule</code> <code>enrole.workflow.LC=lifecyclerule.xml</code>

fesiextensions.properties (deprecated)

The `fesiextensions.properties` file (deprecated) provides support for Free EcmaScript Interpreter (FESI) JavaScript extensions before Version 5.0 of Security Identity Manager. Do not author *new* extensions using this deprecated architecture.

The `fesiextensions.properties` file defines built-in and custom FESI extensions required by IBM Security Identity Manager. FESI is the Free EcmaScript Interpreter, a JavaScript interpreter written in Java. The FESI interpreter reads this properties file during IBM Security Identity Manager initialization to set extensions for required Java classes.

The FESI extensions represent regions, or hooks, in IBM Security Identity Manager where the use of JavaScript code is allowed to introduce built-in or custom business logic. FESI extensions are specified with a property key and value pair format:

```
property-key-name=value
```

The *value* is a fully qualified Java class file name. The *property-key-name* includes a standard prefix (`fesi.extension`), a context, and (for custom classes) an identifier name (ID) representing the fully qualified Java class file. Typically the shorter unqualified class name is used as the identifier name (ID).

```
fesi.extension.context.class-ID=fully-qualified-class-name
```

The FESI system extensions that are used by IBM Security Identity Manager include a global context and three specific contexts.

Global context identifier:

```
Enrole
```

Specific context identifiers:

```
IdentityPolicy
HostSelection
Workflow
```

Although you *must not modify* the built-in system FESI extensions, you can add custom FESI extensions that might be required for any custom programs. When you add a custom FESI extension to this properties file, you must use one of the established global or specific contexts.

Indicate the fully qualified custom Java class file name as the *value* and provide a unique property key identifier name (ID) for the custom class. Examples:

```
fesi.extension.IdentityPolicy.custom-class-ID=custom-fully-qualified-class-name
fesi.extension.HostSelection.custom-class-ID=custom-fully-qualified-class-name
```

Table 27 on page 226 defines the deprecated properties used to configure FESI extensions (on a single line).

<i>Table 27. fesiextensions.properties properties (deprecated)</i>	
System FESI extensions	
<pre>fesi.extension.Enrole=com.ibm.itim.fesiextensions.Enrole fesi.extension.IdentityPolicy=com.ibm.itim.fesiextensions.IdentityPolicy fesi.extension.HostSelection=com.ibm.itim.fesiextensions.ModelExtension fesi.extension.OrphanAdoption.Model=com.ibm.itim.fesiextensions.ModelExtension fesi.extension.PersonPlacementRules.Model=com.ibm.itim.fesiextensions.ModelExtension fesi.extension.Workflow=com.ibm.itim.workflow.fesiextensions.WorkflowExtension fesi.extension.Workflow.Model=com.ibm.itim.fesiextensions.ModelExtension (next extension statement intended as one line) fesi.extension.PostOffice=com.ibm.itim.mail.postoffice.fesiextensions.PostOfficeExtension fesi.extension.Reminder=com.ibm.itim.fesiextensions.ReminderExtension</pre>	
	<p>The value for each system property key is a fully qualified Java class file that IBM Security Identity Manager provides.</p> <p>Do not remove or modify information in this section</p>
Custom FESI extensions	

Table 27. *fesiextensions.properties properties (deprecated) (continued)*

Example:

```
fesi.extension.enRole.custom-class-ID=custom-fully-qualified-class-name
```

You can modify the `fesiextensions.properties` files to include additional FESI extensions for required custom objects and methods.

The value for each custom property key is a fully qualified custom Java class file.

All property key names must be unique.

JavaScript password access

```
javascript.password.access.enabled
```

Determines whether plaintext passwords can be accessed from Person and Account objects. Values include:

- **true** — Password access is enabled.
- **false** — Passwords cannot be accessed with javascript.

Example (default):

```
javascript.password.access.enabled=true
```

helpmappings.properties

The `helpmappings.properties` file allows a customer to replace the installed Security Identity Manager help system with an alternative help system.

The `helpmappings.properties` file contains the following properties:

Table 28. *helpmappings.properties properties*

```
url.contexthelp
```

Specifies an external URL for help. The default is blank, which uses the URL of the IBM Security Identity Manager help system. The URL will also add the resolved locale based on the IBM Security Identity Manager language packs that are installed. For example, `http://www.example.com/help/en/ui_login.html`

Example:

```
url.contexthelp=www.example.com/help
```

Clicking on the help icon ('?') in the IBM Security Identity Manager graphical user interface will load the html file from the key mapping (`http://www.example.com/help/customerfilename.html`). For a login page, the value of `customerfilename` might be `ui_login.html`, and the full address might be `http://www.example.com/help/ui_login.html`.

reportingLabels.properties

This properties file is like other labels-related properties files such as `labels.properties`, or `customLabels.properties`, and holds labels that are used by Reports.

reporttabledeny.properties

By default, this property holds a list of Security Identity Manager tables that are used by various Security Identity Manager components to store internal or configuration data that is inappropriate for a report.

This file is used by IBM Security Identity Manager Server for Reporting Engine purposes.

The following table defines the properties that determine which information is not exposed in reports.

<i>Table 29. reporttabledeny.properties</i>	
tables	
	<p>Holds a comma-separated list of all IBM Security Identity Manager database tables that are excluded from report production.</p> <p>If a table is part of this property, the table and its columns are not in the Report Designer; a report cannot be designed on columns of this table. A user who wants to deny a specific database table from being used by the Report Designer can choose to add the table against the <code>tables</code> property.</p> <p>Example:</p> <pre>tables=JMSState, JMSStore, entity_column, column_report, report, synchronization_history, synchronization_lock, changelog, resources_synchronizations, NextValue, ListData, AUTH_KEY, ATTR_CHANGE, ACCT_CHANGE, LCR_INPROGRESS_TABLE, WORKFLOW_CALLBACK, POLICY_ANALYSIS, POLICY_ANALYSIS_ERROR, PO_TOPIC_TABLE, PO_NOTIFICATION_TABLE, BULK_DATA_SERVICE, MIGRATION_STATUS, SYNCH_POINT, COMPLIANCE_ALERT, PO_NOTIFICATION_HTMLBODY_TABLE, BULK_DATA_STORE, BULK_DATA_INDEX, MANUAL_SERVICE_RECON_ACCOUNTS, SCRIPT, ACTIVITY_LOCK</pre>
allowedRestrictedColumns	
	<p>Allows IBM Security Identity Manager administrators to explicitly allow columns of restricted data types, to be used for designing and running custom reports. Such reports however work for IBM Security Identity Manager Administrators only. If a non-administrator attempts to run such reports, the user receives an <code>AuthorizationException</code>.</p> <p>By default, columns of the following restricted data types are not available when you design or run custom reports:</p> <pre>BLOB, CLOB, BINARY, VARBINARY, LONGVARBINARY and LONGVARCHAR</pre> <p>The value of the property is a comma-separated list of <code><TABLE_NAME>.<COLUMN_NAME></code>. If this property is undefined, then none of the columns of the restricted data type is available for reporting.</p> <p>Example (on a single line):</p> <pre>allowedRestrictedColumns=ACTIVITY.RESULT_DETAIL, PROCESS.RESULT_DETAIL, PROCESSLOG.NEW_DATA</pre>

rest.properties

The properties of the `rest.properties` file control the behavior of the REST interfaces that are included in IBM Security Identity Manager. As an administrator, you can update the properties in the `rest.properties` file to modify the behavior of certain aspects of the REST interfaces.

Note: To avoid performance issues, any changes that you make to the parameters in `rest.properties` must be thoroughly tested before you apply them to a production environment.

<code>baseUri</code>	
	<p>Specifies the base for the URIs that are returned from the REST interfaces.</p> <p>If the property is not specified, the REST interfaces use the base URIs from the HTTP request.</p> <p>Example:</p> <pre>baseUri=https://server/itim/rest</pre>
<code>search.limit</code>	
	<p>Specifies the maximum number of items that are returned by the REST search APIs. The REST search APIs attempt to retrieve no more than the specified number of items plus one. Specifying a value of 0 indicates that there is no limit.</p> <p>Example:</p> <pre>search.limit=1000</pre> <p>Note: The limit of accesses that are returned by a search is determined by a separate property <code>search.limit.access</code>.</p>
<code>search.limit.access</code>	
	<p>Specifies the maximum number of accesses that are returned by the REST access search API. The REST access search API attempts to retrieve no more than the specified number of accesses plus one. Specifying a value of 0 indicates that there is no limit.</p> <p>Example:</p> <pre>search.limit.access=100</pre>
<code>search.limit.activities</code>	
	<p>Specifies the maximum number of activities that are returned by the REST activity search API. The REST activity search API attempts to retrieve no more than the specified number of activities plus one. Specifying a value of 0 indicates that there is no limit.</p> <p>Example:</p> <pre>search.limit.activities=100</pre>

Table 30. rest. properties (continued)

<code>participant.limit</code>	
	<p>Specifies the maximum number of participants that are assigned to the activity that are returned by a search or a retrieval of activities. Specifying a value of 0 indicates that there is no limit.</p> <p>Example:</p> <pre>participant.limit=0</pre>
<code>search.pagesize</code>	
	<p>Specifies the maximum number of items that are included in each page when the REST search APIs perform paged searching. Specifying a value of 0 indicates that REST search APIs do not perform paged searching.</p> <p>Example:</p> <pre>search.pagesize=100</pre>
<code>search.queryfilter.allowedHiddenAttributes</code>	
	<p>Specifies the list of hidden attributes, (specified in <code>enrolehiddenattributes.properties</code> file) that are allowed in filter query parameters. The value must be in lowercase, and separated by a comma. For example: <code>erlastmodifiedtime,ercategory</code>.</p> <p>Example:</p> <pre>search.queryfilter.allowedHiddenAttributes=erlastmodifiedtime</pre>
<code>search.cache.enabled</code>	
	<p>Specifies whether the REST search APIs cache search results to satisfy subsequent request that specify the same search criteria.</p> <p>Example:</p> <pre>search.cache.enabled=true</pre>
<code>search.cache.limit</code>	
	<p>Specifies the maximum number of searches for which results are cached for each client. Specifying a value of 0 indicates that there is no limit. This parameter is ignored if <code>search.cache.enabled=false</code> is specified.</p> <p>Example:</p> <pre>search.cache.limit=100</pre>
<code>search.cache.timeout</code>	

Table 30. *rest.properties* (continued)

	<p>Specifies the number of seconds that search results remain cached for each client since the last time the client issued a request with the same search criteria. Specifying a value of 0 indicates that the search results remain cached until the client's HTTP session times out. This parameter is ignored if <code>search.cache.enabled=false</code> is specified.</p> <p>Example:</p> <pre>search.cache.timeout=600</pre>
<pre>activity.duedate.threshold</pre>	
	<p>Specifies the time in hours. If the due date is approaching within this threshold limit, it is flagged in the activity summary and detail pages. The activity card and activity due date are flagged.</p> <p>Example:</p> <pre>activity.duedate.threshold=24</pre>

scriptframework.properties (Suggested)

For *all* new JavaScript extensions, use the `scriptframework.properties` file to configure script extensions and other scripting functions.

JavaScript is used in IBM Security Identity Manager to specify identity policies, provisioning policy parameters, service selection policies, placement rules for identity feeds, and orphan account adoption.

In addition, JavaScript is used in workflows to specify transition conditions, loop conditions, JavaScript activities, activity postscripts, and workflow notification. Various scripting extensions are provided by IBM Security Identity Manager to expose useful data and services to each of these scripts. In addition to these extensions, system administrators can configure IBM Security Identity Manager to load custom JavaScript extensions.

The file `scriptframework.properties` is used to configure all parts of scripting support in IBM Security Identity Manager. It includes which script extensions to use, which script interpreter to use, and other properties that relate to scripting.

The major parts of the `scriptframework.properties` are divided by these host components: `PostOffice`, `ProvisioningPolicy`, `AccountTemplate`, `HostSelection`, `PersonPlacementRules`, `Workflow`, `Reminder`, `IdentityPolicy`, `Notification`, and `OrphanAdoption`.

The most heavily used section of the property file is for configuring which extensions to load for each host component. To have the script framework load an extension, add a key-value line to the `scriptframework.properties` file that is similar to this example:

```
ITIM.extension.{Host Component}=com.ibm.itim.class_name
```

where `ITIM.extension.{Host Component}` is the key and `com.ibm.itim.class_name` is the value. The value of `{Host Component}` can be any of the previously listed components. If you want to load more than a single extension for a host component, you can add a suffix to host component, such as:

```
ITIM.extension.{Host Component}.suffix=com.ibm.itim.class_name
```

The only rule is that each key must be unique in the file.

The `scriptframework.properties` file comes pre-configured to load the extensions necessary to use IBM Security Identity Manager with its default scripts. Do not remove any lines in `scriptframework.properties` because removal might cause IBM Security Identity Manager to stop functioning properly.

The next section of the `scriptframework.properties` file configures which script interpreter to use for each host component. IBM Security Identity Manager currently supports two different script interpreters, the IBM JSEngine and the FESI JavaScript Interpreter.

To configure which interpreter to use for each host component, there is a line in the file that looks like:

```
ITIM.interpreter.{Host Component}={Engine}
```

The value of `{Host Component}` can be any of the previously listed components. The value of `{Engine}` can be either IBMJS or FESI. The `{Engine}` variable is not case-sensitive, so typing `fesi` works as well as typing `FESI`. IBMJS is the default scripting engine, so any value for `{Engine}` other than IBMJS or FESI, or no value, uses the IBMJS engine. The FESI engine is deprecated. Use it only if you upgraded from IBM Security Identity Manager Version 4.6 or earlier and have custom FESI extensions.

The next section in the configuration file enables configuring custom JavaScript wrappers. For security reasons, IBM Security Identity Manager does not expose all objects to the scripting environment. Instead, most objects are wrapped in a more restrictive wrapper class that exposes only certain methods. IBM Security Identity Manager has a default wrapper configuration that you can override or extend in this section. This feature is for an advanced user; in most cases do not use it. For more details on how to configure custom wrappers, see the comments in the `scriptframework.properties` file.

In the next section, you can configure direct Java access from scripts run by the IBM JSEngine interpreter. Direct Java access is powerful, but scripts can bypass some of the security built into the script framework. Consider carefully before you do so. See the comments in the `scriptframework.properties` file for more information about how to enable direct Java access.

The final section of the configuration file configures specific properties that might be useful. Each specific property is explained in comments in the `scriptframework.properties` file, including default and allowed values.

Error handling

To enable retry of an activity in the workflow, when the script evaluation fails, due to Directory Server being down, add the following new property:

```
ITIM.script.extension.retryOn=standardException.jndiCommunicationException,  
standardException.jndiServiceUnavailable
```

Additionally any custom IBMJS code, used in the workflow, which performs any LDAP operation, must be modified to throw `ScriptException`, with the exception message set to either `standardException.jndiCommunicationException`, or `standardException.jndiServiceUnavailable`.

For example:

```
...  
try {  
  //Custom Script Code performing LDAP operation  
} catch(ModelCommunicationException e) {  
  String msg = "standardException.jndiCommunicationException";  
  throw new ScriptException(msg, e);  
}  
...
```

Alternatively, the exception message that is thrown by a custom script extension, can be included as another value for `'ITIM.script.extension.retryOn'` property. Multiple values that are specified for this property must be comma separated.

SelfServiceHelp.properties

The `SelfServiceHelp.properties` file can be used to redirect help to a custom location for customers who want to have their own help content for the self-service user interface.

Table 31 on page 233 defines the properties used to redirect help to a custom location.

Table 31. SelfServiceHelp properties	
IBM Security Identity Manager SelfServiceHelp settings	
<code>helpBaseUrl</code>	
	<p>Specifies the base url to send help requests to. A blank value indicates that help goes to the URL for Self Service application help.</p> <p>Valid values include the URL of the Self Service application help.</p> <p>Example:</p> <pre>helpBaseUrl=http://myserver:80</pre>
Help Id mappings include:	
<code>helpId = relative page URL</code>	
	<p>The help mappings section maps ids from specific pages to a relative URL sent to the help server.</p> <p>For example:</p> <pre>helpBaseUrl=http://myserver:80 locale = en_US loginId/relativeURL = login_help_url=ui/ui_eui_login.html Final URL = http://myserver:80/en_US/ui/ui_eui_login.html</pre> <p>Locale is determined by resolving the <code>SelfServiceScreenText.properties</code> resource bundle for the current logged in user and with the associated locale.</p>

SelfServiceHomePage.properties

The `SelfServiceHomePage.properties` file is used to configure the sections of the initially installed home page for the self-service user interface. You can add or remove tasks, and update icon URLs and labels of the home page from this file.

The file has these types of entries:

- `Sections=ActionNeeded, Password, sectionConfigName ...`
Defines the section configuration names in the order in which they are displayed.
- Section definition
Defines the label keys, icons, and other objects for the home page section.
- Task definitions
Defines the NLS key and link for the URL, the NLS key for the task description, and other attributes that enable displaying the task.

For more information about these properties, see documentation in the properties file.

SelfServiceScreenText.properties

The `SelfServiceScreenText.properties` file is a resource bundle containing the labels for the self-service user interface.

Versions of the file might be available for the installed languages. For example: `SelfServiceScreenText_en.properties` and `SelfServiceScreenText_es.properties`, which are editable by users.

SelfServiceUI.properties

The `SelfServiceUI.properties` file controls miscellaneous properties of the self-service user interface.

[Table 32 on page 234](#) defines the properties used to configure the self-service user interface.

<i>Table 32. SelfServiceUI.properties</i>	
<code>enrole.ui.pageSize</code>	
	Specifies the page size for displaying lists. Example: <code>enrole.ui.pageSize=10</code>
<code>enrole.ui.pageLinkMax</code>	
	Specifies the number of page links to be shown for multi-page result sets. Example: <code>enrole.ui.pageLinkMax=100</code>
<code>enrole.ui.maxSearchResults</code>	
	Specifies the maximum number of items returned from a search. The results that are returned can be less than, but not larger than the values specified in <code>ui.properties</code> . Example: <code>enrole.ui.maxSearchResults=1000</code>
<code>enrole.ui.maxSearchResults.users</code>	
	Specifies the maximum displayable search results for the task Delegate Activities - Search for User . Example: <code>enrole.ui.maxSearchResults.users=100</code>

Table 32. *SelfServiceUI.properties* (continued)

<code>enrole.ui.maxNrOfIteration</code>	
	<p>Specifies the maximum number of wait iterations for RequestInfo status.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">enrole.ui.maxNrOfIteration=20</pre>
<code>enrole.ui.waitTime</code>	
	<p>Specifies the time to wait until the request is asked for next status. The product of (<code>maxNrOfIteration * waitTime</code>) is a maximum of 60 seconds. The value is interpreted in milliseconds.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">enrole.ui.waitTime=3000</pre>
<code>enrole.ui.logoffURL</code>	
	<p>Specifies the URL to forward the browser to when the user logs off.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">enrole.ui.logoffURL=myLogoffURL</pre>
<code>enrole.ui.timeoutURL</code>	
	<p>Specifies the URL to which forward the browser on timeout.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">enrole.ui.timeoutURL=myTimeoutURL</pre>
<code>ui.layout.showBanner</code>	
	<p>Specifies a change to the values of <code>ui.layout</code> properties to show or hide the banner of the self-service user interface.</p> <p>Example:</p> <pre style="background-color: #f2f2f2;">ui.layout.showBanner=true</pre>
<code>ui.layout.showFooter</code>	

Table 32. SelfServiceUI.properties (continued)

	<p>Specifies a change to the values of <code>ui.layout</code> properties to show or hide the footer of the self-service user interface.</p> <p>Example:</p> <pre>ui.layout.showFooter=true</pre>
<pre>ui.layout.showToolBar</pre>	
	<p>Specifies a change to the values of <code>ui.layout</code> properties to show or hide the toolbar of the self-service user interface.</p> <p>Example:</p> <pre>ui.layout.showToolBar=true</pre>
<pre>ui.layout.showNav</pre>	
	<p>Specifies a change to the values of <code>ui.layout</code> properties to show or hide the page navigation of the self-service user interface.</p> <p>Example:</p> <pre>ui.layout.showNav=false</pre>
<pre>ui.usersearch.attr.cn</pre>	
	<p>Specifies the attribute that is listed in the searchBy field for a user search. The attribute is prefixed with <code>ui.usersearch.attr</code>. For more information about mapping and syntax, see the documentation in the <code>SelfServiceUI.properties</code> file.</p> <p>Example:</p> <pre>ui.usersearch.attr.cn=cn</pre>
<pre>ui.usersearch.attr.sn</pre>	
	<p>Specifies the attribute that is listed in the searchBy field for a user search. The attribute is prefixed with <code>ui.usersearch.attr</code>. For more information about mapping and syntax, see the documentation in the <code>SelfServiceUI.properties</code> file.</p> <p>Example:</p> <pre>ui.usersearch.attr.sn=sn</pre>
<pre>ui.usersearch.attr.telephonenumber</pre>	

Table 32. *SelfServiceUI.properties* (continued)

	<p>Specifies the attribute that is listed in the searchBy field for a user search. The attribute is prefixed with <code>ui.usersearch.attr</code>. For more information about mapping and syntax, see the documentation in the <code>SelfServiceUI.properties</code> file.</p> <p>Example:</p> <pre>ui.usersearch.attr.telephonenumber=telephonenumber</pre>
<pre>ui.usersearch.attr.mail</pre>	
	<p>Specifies the attribute that is listed in the searchBy field for a user search. The attribute is prefixed with <code>ui.usersearch.attr</code>. For more information about mapping and syntax, see the documentation in the <code>SelfServiceUI.properties</code> file.</p> <p>Example:</p> <pre>ui.usersearch.attr.mail=mail</pre>
<pre>ui.view.accounts.expandedbydefault</pre>	
	<p>Specifies whether the accounts affected twistie state on the change password page are expanded or collapsed (<code>true</code> <code>false</code>) by default. Valid values are:</p> <ul style="list-style-type: none"> • true – Expand the accounts affected twistie state on the change password page by default • false – Do not expand the accounts affected twistie state on the change password page by default <p>Example (default):</p> <pre>ui.view.accounts.expandedbydefault=false</pre>
<pre>ui.select.all.accounts</pre>	
	<p>Specifies whether all the accounts under the account twistie are to be selected by default. Valid values are:</p> <ul style="list-style-type: none"> • all – To select all the accounts under the account twistie • none – To select none of the accounts under the account twistie • default – To retain the default behavior <p>Example (default):</p> <pre>ui.select.all.accounts=default</pre>

ui.properties

The `ui.properties` file specifies attributes that affect the operation and display of the Security Identity Manager graphical user interface.

The following table defines the properties for configuring the IBM Security Identity Manager graphical user interface.

Table 33. *ui.properties* properties

IBM Security Identity Manager GUI configuration settings

<code>enrole.ui.customerLogo.image</code>	
	<p>Specifies the file name of the graphic that is displayed on the right side of the IBM Security Identity Manager title banner. The graphic is usually a company logo. For display over the web in a browser, the format of the file must be type that the browser supports. The actual graphics file must be stored in the following location:</p> <p>WebSphere Application Server:</p> <pre style="background-color: #f2f2f2; padding: 5px;">WebSphere/AppServer/installedApps/<i>domain-name</i>/ITIM.ear/itim_console.war/html/images/</pre> <p>You can also specify a path under the console webapp, <code>/itim/console/custom/banner.gif</code> or specify the full URL as <code>http://yourhost.com/banner.gif</code>.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;">enrole.ui.customerLogo.image=ibm_banner.gif</pre>
<code>enrole.ui.customerLogo.url</code>	
	<p>Specifies the URL link that is activated when you click the custom graphic image (company logo) on the right side of the IBM Security Identity Manager banner.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;">enrole.ui.customerLogo.url=www.ibm.com</pre>
<code>enrole.ui.pageSize</code>	
	<p>Specifies the number of list items that is initially displayed on the screen. If there are more items in the list, links are at the bottom of the list view that activate continuations of the list. For example, Page 2, Page 3, Page 4.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;">enrole.ui.pageSize=50</pre>
<code>enrole.ui.maxSearchResults</code>	
	<p>Specifies the maximum number of items that are returned for a search. This property limits the number of items that are returned when a search is done on the directory server. The evaluation of the ACIs is done later on these returned items. The number of items in the directory server is greater than the value specified for this property. So, the number of items that are displayed on the IBM Security Identity Manager Console might be less than the value specified.</p> <p>The value for this property can control possible system performance degradation when a large return of items is encountered. If you modify the value for this property, you must restart the application server.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;">enrole.ui.maxSearchResults=1000</pre>

Table 33. *ui.properties* properties (continued)

<code>ui.banner.showForLogin</code>	
	<p>Specifies whether to show the console banner on the login page, rather than the default login banner. Any customization to the console banner is also on the login page when this property is in effect.</p> <p>yes Show the console banner in the login page.</p> <p>no Show the default login banner. An empty value assumes no.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2; padding: 5px;"><code>ui.banner.showForLogin=no</code></pre>
<code>ui.footer.URL</code>	
	<p>Specifies the URL for the IBM Security Identity Manager Console. Specify either the full address (<code>http://yourhost.com/footer.html</code>) or an address from the IBM Security Identity Manager web server (<code>/itim/console/custom/footer.html</code>). A blank value uses the default address of the IBM Security Identity Manager footer.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;"><code>ui.footer.URL=http://itim99.mylab.raleigh.ibm.com:9080/itim/console/main</code></pre>
<code>ui.footer.height</code>	
	<p>Specifies the height in pixels of the footer on the IBM Security Identity Manager Console.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2; padding: 5px;"><code>ui.footer.height=50</code></pre>
<code>ui.footer.isVisible</code>	
	<p>Shows or hides the footer of the IBM Security Identity Manager Console.</p> <p>Valid values are as follows:</p> <p>yes (or blank) Shows the footer.</p> <p>no Hides the footer.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2; padding: 5px;"><code>ui.footer.isVisible=yes</code></pre>
<code>ui.banner.URL</code>	

Table 33. *ui.properties* properties (continued)

	<p>Specifies the URL for the banner on the IBM Security Identity Manager Console.</p> <p>Specify either the full address (<code>http://yourhost.com/banner.html</code>) or a path from the IBM Security Identity Manager web server (<code>/itim/console/custom/banner.html</code>). A blank value uses the default address of the IBM Security Identity Manager banner.</p> <p>Example:</p> <pre>ui.banner.URL=http://itim99.mylab.raleigh.ibm.com:9080/itim/console/main</pre>
<pre>ui.banner.height</pre>	
	<p>Specifies the height in pixels of the banner on the IBM Security Identity Manager Console.</p> <p>Example (default):</p> <pre>ui.banner.height=48</pre>
<pre>ui.homepage.path</pre>	
	<p>IBM Security Identity Manager Console home page location. Specify a relative path from the IBM Security Identity Manager Console context root (<code>/itim/console</code>).</p> <p>For example, if the full path to the home page was <code>http://yourhost:9080/itim/console/custom/home.html</code>, then the following value is <code>ui.homepage.path=custom/home.html</code>.</p> <p>The custom home page must be in the IBM Security Identity Manager web application. For example: <code>path/ITIM.ear/itim_console.war/custom/home.html</code>). A blank value uses the default address of the IBM Security Identity Manager home page.</p> <p>Example:</p> <pre>ui.homepage.path=custom/home.html</pre>
<pre>ui.titlebar.text</pre>	
	<p>Specifies the text in the title bar of the browser for the IBM Security Identity Manager Console. A blank value uses the default name of the IBM Security Identity Manager product.</p> <p>Example:</p> <pre>ui.titlebar.text=Our Home Page</pre>
<pre>ui.userManagement.includeAccounts</pre>	
	<p>Specifies the default behavior for including accounts when you suspend, restore, or delete users. Valid values are as follows:</p> <p>true Accounts are included.</p> <p>false Accounts are excluded.</p> <p>Example (default):</p> <pre>ui.userManagement.includeAccounts=true</pre>

Table 33. *ui.properties* properties (continued)

<code>ui.userManagement.search.attributes</code>	
	<p>Adds a search attribute to the default list for the Manage Users page in the IBM Security Identity Manager Console.</p> <p>Provide one or more attribute names in the <code>ui.userManagement.search.attributes</code> property value that is separated by a comma. Make sure to provide valid and non-repetitive attributes. Do not specify attributes that cannot be searched by using plain text. For example, audio, photo, and other similar items.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;"><code>ui.userManagement.search.attributes=homepostaladdress,employeenumber</code></pre> <p>By default, this property value is empty.</p> <p>The property adds user attributes that display in the Search By list on the Manage Users page for the person search filter.</p>
<code>ui.challengeResponse.showAnswers</code>	
	<p>Specifies whether the answers to challenge response questions is treated as passwords or as clear text in the IBM Security Identity Manager Console of the following pages:</p> <ul style="list-style-type: none"> • Forgot Password page • Challenge response question and answer definition page <p>Valid values are as follows:</p> <p>true Answers to challenge response questions is clear text.</p> <p>false Answers to challenge response questions is treated as passwords.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2; padding: 5px;"><code>ui.challengeResponse.showAnswers=true</code></pre>
<code>ui.challengeResponse.bypassChallengeResponse</code>	
	<p>Specifies whether the challenge response questions can be bypassed when the user first logs on to the IBM Security Identity Manager Console, the self service web user interface, or the Identity Service Center. Valid values:</p> <p>true When true, the user can cancel and not answer the challenge questions.</p> <p>false When false, the user cannot cancel. The user is forced to respond to the challenge questions.</p> <p>Default value: true</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;"><code>ui.challengeResponse.bypassChallengeResponse=true</code></pre>
<code>ui.viewAllRequests.loadDefaultQueryResult</code>	

Table 33. *ui.properties* properties (continued)

	<p>Specifies whether the View All Requests page loads the default query result.</p> <p>true Loads the View All Requests page with default query result.</p> <p>false Does not load the View All Requests page with default query result.</p> <p>Default value: false</p> <p>Example:</p> <pre>ui.viewAllRequests.loadDefaultQueryResult=false</pre>
<pre>ui.allowLaunchingNewTaskWithoutWarningForActiveTask</pre>	
	<p>Specifies whether to start selected task or not, if the same task is already active in the IBM Security Identity Manager Console. The examples of the tasks are as follows: Create Service, Change Service, Create User, Change User.</p> <p>true When you try to start an already active task, the existing task is closed. Starts the new task without displaying any warning message.</p> <p>false When you try to start an already active task, a warning message is displayed. Does not start the new task.</p> <p>Default value: false</p> <p>Example:</p> <pre>ui.allowLaunchingNewTaskWithoutWarningForActiveTask=false</pre>
<pre>ui.policyManagement.manageProvisioningPolicies.create.defaultMemberType</pre>	
	<p>Controls default selection of policy membership. This property allows default member type to be selected while you create a provisioning policy. Allowed values are as follows:</p> <p>users All users in the organization.</p> <p>roles Roles that are specified later.</p> <p>others All other users who are not granted to the entitlements that are defined by this provisioning policy by way of other policies.</p> <p>Default value: users</p> <p>Example:</p> <pre>ui.policyManagement.manageProvisioningPolicies.create.defaultMemberType=users</pre>
<pre>ui.manageServices.reconcileNow.defaultSelectQuery</pre>	

Table 33. *ui.properties* properties (continued)

	<p>Specifies the default reconciliation query option. Allowed values are as follows:</p> <p>none None.</p> <p>use_query Use query from existing schedule.</p> <p>define_query Define query.</p> <p>Default value: none</p> <p>Example:</p> <pre>ui.manageServices.reconcileNow.defaultSelectQuery=none</pre>
<pre>ui.passwordManagement.defaultSelection.typePassword</pre>	
	<p>Specifies Allow me to type a password as default over the current Generate a password for me option. Allowed values are as follows:</p> <p>true Selects the Allow me to type a password option and additionally none of the accounts get selected by default.</p> <p>false Selects the Generate a password for me option if this property is set to false or not present.</p> <p>Default value: false</p> <p>Example:</p> <pre>ui.passwordManagement.defaultSelection.typePassword=false</pre>
<pre>ui.advancedUserSearch.AllTypes.defaultSearchAttribute.names ui.advancedUserSearch.AllTypes.defaultSearchAttribute.labels</pre>	
	<p>When you select User type as All types in the Select User Type page, the properties add the default search attributes and its labels on the Advanced Search page for users in the IBM Security Identity Manager Console. If the <code>ui.advancedUserSearch.AllTypes.defaultSearchAttribute.names</code> property is removed or if no value is specified, then IBM Security Identity Manager does not display any default search attribute field.</p> <p>Provide one or more attribute names in the <code>ui.advancedUserSearch.AllTypes.defaultSearchAttribute.names</code> property value, and corresponding attribute labels in the <code>ui.advancedUserSearch.AllTypes.defaultSearchAttribute.labels</code> property value.</p> <p>Make sure to provide valid, non-repetitive, and comma-separated values. Do not specify attributes that cannot be searched by using plain text. For example, audio, photo, and other similar items.</p> <p>Example (default):</p> <pre>ui.advancedUserSearch.AllTypes.defaultSearchAttribute.names=cn ui.advancedUserSearch.AllTypes.defaultSearchAttribute.labels=\$cn</pre> <p>The property adds the default search attributes and its labels on the Advanced Search page for users when you select User type as All types in the Select User Type page.</p>

Table 33. *ui.properties* properties (continued)

WfDesigner and FormDesigner applet properties

```

enrole.build.version
enrole.java.plugin
enrole.java.plugin.classid
enrole.java.pluginspage
enrole.java.plugin.jpi-version
enrole.java.plugin.version
enrole.java.entWflowHeightIE
enrole.java.entWflowWidthIE
enrole.java.entWflowHeightMZ
enrole.java.entWflowWidthMZ
enrole.java.opWflowHeightIE
enrole.java.opWflowWidthIE
enrole.java.opWflowHeightMZ
enrole.java.opWflowWidthMZ
enrole.java.joinDirHeightIE
enrole.java.joinDirWidthIE
enrole.java.joinDirHeightMZ
enrole.java.joinDirWidthMZ
enrole.java.formDesignHeightIE
enrole.java.formDesignWidthIE
enrole.java.formDesignHeightMZ
enrole.java.formDesignWidthMZ
express.java.formDesignHeightIE
express.java.formDesignWidthIE
express.java.formDesignHeightMZ
express.java.formDesignWidthMZ
#enrole.ui.logoffURL (default is commented out)
#enrole.ui.timeoutURL (default is commented out)

```

You must not modify or remove any information for these properties in the property file.

These property key and value pairs provide the necessary Java applet support required by the Java Web Start that runs the IBM Security Identity Manager Console.

Report menu properties

```
enrole.ui.report.maxRecordsInReport
```

Displays the number of records that can be displayed in a PDF report without encountering an "Out of Memory" error. The number does not ensure that PDF report generation is successful. If the report contains more records than specified by this property, PDF report generation is not attempted.

Example:

```
enrole.ui.report.maxRecordsInReport=5000
```

Enable or disable WebSEAL single sign-on (SSO)

```
enrole.ui.ssoEnabled
```

Table 33. *ui.properties* properties (continued)

	<p>The property key and value pairs do not pertain to the IBM Security Identity Manager Console. Enable or disables WebSEAL single sign-on. More configuration is required for WebSEAL single sign-on. Valid values are as follows:</p> <p>true WebSEAL single sign-on is enabled.</p> <p>false WebSEAL single sign-on is disabled.</p> <p>Example (default):</p> <pre>enrole.ui.ssoEnabled=false</pre>
<pre>enrole.ui.ssoEncoding</pre>	
	<p>Specifies the encoding that is used to decode user credentials with WebSEAL single sign-on.</p> <p>Example (default):</p> <pre>enrole.ui.ssoEncoding=UTF-8</pre>
<p>Refresh properties</p>	
<pre>enrole.ui.httpRefreshSecs</pre>	
	<p>Defines, in seconds, the refresh rate for pages within the IBM Security Identity Manager Console. This property is used during policy previews.</p> <p>Example (default):</p> <pre>enrole.ui.httpRefreshSecs=10</pre>
<p>Search class mapping for ObjectProfileCategory</p>	
	<p>The property key and value pairs do not pertain to the IBM Security Identity Manager Console and must not be modified or removed.</p>
<p>Justification field configuration properties</p>	
<pre>ui.displayJustification</pre>	
	<p>Specifies whether the Justification field is displayed in the user interface. By default, the Justification field is not displayed.</p> <p>Use in conjunction with the <code>enrole.justificationRequired</code> property in the <code>enRole.properties</code> file.</p> <p>Example (default):</p> <pre>ui.displayJustification=false</pre>
<p>Identity Service Center as the default user interface configuration property</p>	

Table 33. *ui.properties* properties (continued)

<code>ui.defaultui.redirectSelfToISC</code>	
	<p>Specifies whether the Identity Service Center user interface is set as the default user interface. If a user is already authenticated to the IBM Security Identity Manager, and starts the self-service user interface, no redirection happens.</p> <p>true If the Identity Service Center is deployed and if a user starts the self-service user interface, then the self-service user interface redirects the user to the Identity Service Center.</p> <p>false When a user starts the self-service user interface, it does not redirect a user to the Identity Service Center. The self-service user interface starts.</p> <p>Example (default):</p> <pre style="background-color: #f0f0f0; padding: 5px;"><code>ui.defaultui.redirectSelfToISC=false</code></pre>
Generate password configuration property	
<code>ui.passwordManagement.generatePassword</code>	
	<p>Specifies which change password options to enable on the Identity Service Center user interface. This property is applicable only when the Enable password editing is selected in the administrative console. The valid values are:</p> <p>true Enables both the Generate a password for me and Allow me to type a password options. The <code>ui.passwordManagement.defaultSelection.typePassword</code> property is applicable only if the property <code>ui.passwordManagement.generatePassword</code> is set to <code>true</code>.</p> <p>false Enables the Generate a password for me option and disables the Allow me to type a password option.</p> <p>Example (default):</p> <pre style="background-color: #f0f0f0; padding: 5px;"><code>ui.passwordManagement.generatePassword=true</code></pre>
Challenge response answers display configuration property	
<code>ui.challengeResponse.showAnswers</code>	
	<p>Shows or hides the challenge response answers that a user types in the text box. The valid values are:</p> <p>true Shows what a user types.</p> <p>false Hides what a user types.</p> <p>Example (default):</p> <pre style="background-color: #f0f0f0; padding: 5px;"><code>ui.challengeResponse.showAnswers=true</code></pre>

UIConfig.properties

The `config/UIconfig.properties` file contains the several properties that affect the Identity Service Center interface.

<i>Table 34. UIConfig.properties</i>	
<code>password.change.pollingTime</code>	
	<p>Specifies in milliseconds the time to wait before checking whether the expired password change request is processed. A value that is less than 0 is invalid.</p> <p>Example (default):</p> <pre>password.change.pollingTime=1000</pre>
<code>password.change.pollingIterations</code>	
	<p>Specifies the maximum number of times that the server checks whether the password change is processed. A value that is less than 1 is invalid.</p> <p>Example (default):</p> <pre>password.change.pollingIterations=5</pre>
<code>isim.ui.rtlLocales</code>	
	<p>A comma-separated list of right-to-left locales. The default values are ARABIC (ar) and HEBREW (iw).</p> <p>Example (default):</p> <pre>isim.ui.rtlLocales=ar,iw</pre>
<code>property.refresh.interval.seconds</code>	
	<p>Defines how frequently the Identity Service Center server refreshes the value of properties by reading the <code>UIconfig.properties</code> file to pick up new values for the changed properties. A user can change this property even while the Identity Service Center server is running. A user does not need to restart the server to pick up the changes.</p> <p>Example (default):</p> <pre>property.refresh.interval.seconds=300</pre>
<code>LOGO_IMAGE</code>	

Table 34. UIConfig.properties (continued)

	<p>Specifies the file name in custom/ui/images directory that displays the company logo image.</p> <p>Example:</p> <pre>LOGO_IMAGE=companyLogo.png</pre>
<pre>HEADER_LOGO_IMAGE</pre>	
	<p>Specifies the file name in custom/ui/images directory that displays the page header logo image.</p> <p>Example:</p> <pre>HEADER_LOGO_IMAGE=headerLogo.png</pre>
<pre>access.selection.maximum.number</pre>	
	<p>Specifies the maximum number of accesses that can be selected in the manage access flow. For example, in the Request Access wizard, and Edit and Delete Access wizard.</p> <p>Example (default):</p> <pre>access.selection.maximum.number=25</pre>
<pre>search.queryfilter.queryParameters.allowedMaxEntities</pre>	
	<p>Specifies the maximum limit for entities that are allowed in filter query parameter.</p> <p>Example (default):</p> <pre>search.queryfilter.queryParameters.allowedMaxEntities=1</pre>
<pre>timeout.notify</pre>	
	<p>Specifies the seconds left before the session end that the expiration notification message is sent.</p> <p>Example (default):</p> <pre>timeout.notify=20</pre>
<pre>timeouturl</pre>	
	<p>Specifies the URL to which IBM Security Identity Manager redirects on session timeout</p> <p>Example:</p> <pre>timeouturl=myTimeoutURL</pre>
<pre>ui.accessPicker.defaultCategory</pre>	

Table 34. *UIConfig.properties* (continued)

	<p>Specifies whether default search is executed for the specific access category only in view access or during an edit or delete access flow when you select a person. It does not have any impact on request access flow in Identity Service Center. The property does not support multiple values. For example, if MyExampleApp is a child access category of Application access category, then you can specify the property value as Application:MyExampleApp. It executes a default search for the MyExampleApp access category who is the child of access category of Application.</p> <p>By default, this property must be commented out.</p> <p>Example:</p> <pre>ui.accessPicker.defaultCategory=Application:MyExampleApp</pre>
<pre>ui.accessPicker.searchAccessCategoriesInLDAP</pre>	
	<p>Specifies whether access categories must be searched directly in LDAP for view access and edit or delete access flows.</p> <p>The valid values are:</p> <p>true Access categories are searched directly in LDAP for view access, and edit or delete access flows.</p> <p>false Access categories are not searched directly in LDAP for view access, and edit or delete access flows.</p> <p>By default, this property is set to 'false'.</p> <p>Example:</p> <pre>ui.accessPicker.searchAccessCategoriesInLDAP=false</pre>
<pre>ui.activities.approve.justificationRequired</pre>	
	<p>Specifies whether the justification field is mandatory while approving the activity.</p> <p>The valid values are:</p> <p>true The justification field is mandatory while approving the activity.</p> <p>false The justification field is optional while approving the activity.</p> <p>By default, this property is set to true.</p>
<pre>ui.activities.compliancealert.justificationRequired</pre>	

Table 34. UIConfig.properties (continued)

	<p>Specifies whether the justification field is mandatory while working on global alert policy enforcement activity on Manage Activities and Decisions page.</p> <p>The valid values are:</p> <p>true The justification field is mandatory.</p> <p>false The justification field is not mandatory.</p> <p>By default this property will be set to true.</p>
<pre>ui.activities.reject.justificationRequired</pre>	
	<p>Specifies whether the justification field is mandatory while rejecting the activity.</p> <p>The valid values are:</p> <p>true The justification field is mandatory while rejecting the activity.</p> <p>false The justification field is optional while rejecting the activity.</p> <p>By default, this property is set to true.</p>
<pre>ui.activities.displayJustification</pre>	
	<p>Specifies whether the justification field is displayed in the Manage Activities and Decisions page.</p> <p>true The justification field is displayed in the Manage Activities and Decisions page.</p> <p>false The justification field is not displayed in the Manage Activities and Decisions page.</p> <p>By default, this property is set to true.</p>
<pre>ui.activities.displayUserComments</pre>	
	<p>Specifies whether a user comment field is display on the Manage Activities and Decisions page.</p> <p>true Displays the user comment field.</p> <p>false Hides the user comment field.</p> <p>By default, this property is set to false.</p>
<pre>ui.activities.rfi.justificationRequired</pre>	

Table 34. *UIConfig.properties* (continued)

	<p>This property decides whether the justification field is mandatory while working on request for information activity on Manage Activities and Decisions page.</p> <p>true Specifies that the justification field is mandatory.</p> <p>false Specifies that the justification field is not mandatory.</p> <p>By default, this property is set to true.</p>
<pre>ui.activities.workorder.justificationRequired</pre>	
	<p>Specifies whether justification is a required field while working with work order activities on the Manage Activities and Decisions page.</p> <p>true The Justification field is a required field that you must complete before you can proceed ahead.</p> <p>false The Justification field is not a required field.</p> <p>By default, this property is set to true.</p>
<pre>ui.requestAccess.accessCategories.preventDefaultSearch</pre>	
	<p>Stops default access search behavior for specific access categories in the request access flow when you search for an access category by selecting an access category. Multiple values are separated by a white space character. You must define the value as an access type key which you defined while creating the access category.</p> <p>Example usage:Application AccessRole</p> <p>You can also use wildcard characters to stop default access search of specific access categories and its children. For example: Application AccessRole:AccessRole1:*</p> <p>By default, this property is commented out.</p>
<pre>ui.requestAccess.executeDefaultSearchforAllCategories</pre>	
	<p>Specifies whether a default search is started in request access flow and accesses are displayed after you select the user or when you click the All Categories option.</p> <p>true The default search behavior is enabled.</p> <p>false The default search behavior is not enabled.</p> <p>By default, this property is set to true.</p>
<pre>ui.ssoEnabled</pre>	

Table 34. *UIConfig.properties* (continued)

	<p>The property key and value pair pertain to the Identity Service Center.</p> <p>The property indicates whether WebSEAL single sign-on is enabled or disabled.</p> <p>To complete the configuration for WebSEAL single sign-on for Identity Service Center, set this property value to <code>true</code>.</p> <p>The valid values are:</p> <p>true WebSEAL single sign-on is enabled.</p> <p>false WebSEAL single sign-on is disabled.</p> <p>By default, this property is set to <code>false</code>.</p>
<code>ui.userPicker.defaultSelfSelect</code>	
	<p>This property used to specify whether the current logged in user is selected automatically for the Request Access flow and the Edit and Delete Access flow.</p> <p>The valid values are:</p> <p>true The current logged in user is selected automatically.</p> <p>false No user is selected.</p> <p>By default, this property is set to <code>false</code>.</p>

Chapter 16. Select accounts to exclude from reconciliations

Learn how to excluded selected accounts from reconciliations.

To select accounts to exclude from reconciliations, do the following steps:

1. Create an LDIF file and specify the accounts to exclude from reconciliation and the services on which these accounts exist.
2. Import the LDIF file to the LDAP Directory Server.

Exclude accounts from reconciliation

During reconciliations, all accounts are returned from the managed resource, unless otherwise specified by a query. Accounts are automatically adopted if the account is owned by a recognized user in the system or if an alias exists for any account.

However, the IBM Security Identity Manager Server can be configured to prevent automatic adoption of specified accounts. This feature can be used to prevent system accounts, such as `root`, `lp`, `sys`, and `etc` in UNIX resources, from automatically being adopted. This precaution prevents users from accidentally or maliciously adopting and modifying sensitive accounts.

Although these accounts are not automatically adopted, these accounts can still be manually adopted by an administrative user.

The accounts to exclude from reconciliations are specified in an LDIF file. The following excerpt is an example of entries in an LDIF file:

```
dn: ou=excludeAccounts, ou=itim, <TENANT_DN>
ou: excludeAccounts
objectClass: top
objectClass: organizationalunit

dn: cn=SolarisProfile, ou=excludeAccounts, ou=itim, <TENANT_DN>
erObjectProfileName: SolarisProfile
objectClass: top
objectClass: eridentityexclusion
cn: SolarisProfile
erAccountID: root
erAccountID: admin
```

The `cn` and `erObjectProfileName` is the name of the service profile. Excluded accounts are defined by the `erAccountID` attribute. The example excludes the `root` and `admin` accounts from automatically being adopted when a reconciliation is run on a Solaris service.

Chapter 17. System property configuration in enRole.properties

This section provides detailed information about the property keys and values contained in the `ISIM_HOME\data\enRole.properties` system configuration file.

The `enRole.properties` system configuration file contains many of the properties used to configure IBM Security Identity Manager. The file properties control the program functions and enable user customization of special features.

Properties files

Java properties files define attributes that allow customizing and control of the Java software. Standard system properties files and custom properties files are used to configure user preferences and user customization.

A Java properties file defines the values of named resources. It can specify program options such as database access information, environment settings, and special features and functions.

A properties file defines named resources with a property key and value pair format:

```
property-key-name=value
```

The *property-key-name* is an identifier for the resource. The *value* is typically the name of the actual Java object. It provides the resource or a String representing the value of the property key, such as `database.name=itimdb`. The statement syntax allows spaces before and after the equal (=) sign. It can span multiple lines if you place a line continuation character \ (a backslash) at the end of the line. For more information about statement syntax, see the Java language references.

WebSphere Application Server properties

WebSphere Application Server properties define values that are specific to integrating IBM Security Identity Manager with the WebSphere Application Server.

[Table 35 on page 255](#) lists these WebSphere Application Server properties.

Table 35. WebSphere application server properties	
Platform Context Factory Name	
enrole.platform.contextFactory	
	<p>Do not modify this property key and value.</p> <p>Specifies the Java class for the platform context factory that defines the integration point for IBM Security Identity Manager with the WebSphere Application Server.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.platform.contextFactory=com.ibm.itim.apps.impl.websphere. WebSpherePlatformContextFactory</pre>
Application server	

Table 35. WebSphere application server properties (continued)

<code>enrole.appServer.contextFactory</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the Java class that determines which JNDI factory to use with the WebSphere Application Server.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2; padding: 5px;">enrole.appServer.contextFactory=com.ibm.websphere.naming.WsnInitialContextFactory</pre>
<code>enrole.appServer.url</code>	
	<p>This property key and value can be changed only by a qualified administrator.</p> <p>Specifies the location of the application server naming service. This value is obtained during IBM Security Identity Manager installation.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;">enrole.appServer.url=iiop://localhost:2809</pre>
<code>enrole.appServer.usertransaction.jndiname</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the JNDI name of the JTA (Java Transaction API) User Transaction object.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2; padding: 5px;">enrole.appServer.usertransaction.jndiname=jta/usertransaction</pre>
<code>enrole.appServer.systemUser</code>	
	<p>This property key and value can be changed only by a qualified administrator. Modify with the runConfig utility only.</p> <p>Specifies the name of the administrator for the WebSphere Application Server when security is enabled. In a WebSphere Application Server environment, this value is required only when global security is enabled. The value is not set if security is not enabled.</p> <p>The value is used to start, stop, and configure the IBM Security Identity Manager Server. The value is also used by IBM Security Identity Manager installation and configuration routines to authenticate to the WebSphere Application Server.</p> <p>Example:</p> <pre style="background-color: #f2f2f2; padding: 5px;">enrole.appServer.systemUser=system</pre>
<code>enrole.appServer.systemUser.credentials</code>	

Table 35. WebSphere application server properties (continued)

	<p>This property key and value can be changed only by a qualified administrator. Modify with the runConfig utility only. This value is stored in an encrypted format that depends on the option selected with the runConfig utility.</p> <p>Specifies the password for the <code>systemUser</code>.</p> <p>Example:</p> <pre>enrole.appServer.systemUser.credentials=password</pre>
<pre>enrole.appServer.ejbuser.principal</pre>	
	<p>This property key and value can be changed only by a qualified administrator. Modify with the runConfig utility only.</p> <p>Specifies the name used by IBM Security Identity Manager to authenticate when it makes calls on Java beans.</p> <p>Example:</p> <pre>enrole.appServer.ejbuser.principal=rasweb</pre>
<pre>enrole.appServer.ejbuser.credentials</pre>	
	<p>This property key and value can be changed only by a qualified administrator. Modify with the runConfig utility only.</p> <p>Specifies the password for the principal specified.</p> <p>Encryption of this value is specified by the <code>enrole.password.appServer.encrypted</code> property in <code>enRole.properties</code>.</p> <p>Example:</p> <pre>enrole.appServer.ejbuser.credentials=password</pre>
<pre>enrole.appServer.realm</pre>	
	<p>This property key and value can be changed only by a qualified administrator.</p> <p>Specifies the target server security realm name if IBM Security Identity Manager is running on a different WebSphere Application Server instance that is configured to run with different security realm.</p> <p>Example (on a single line):</p> <pre>enrole.appServer.realm=itimCustomRealm</pre> <p>The default value is <code>itimCustomRealm</code>; it can be updated during the installation of IBM Security Identity Manager.</p>
<pre>enrole.appServer.registry</pre>	

Table 35. WebSphere application server properties (continued)

	<p>Do not modify this property key and value.</p> <p>Describes the registry to which IBM Security Identity Manager is configured.</p> <p>Example (default):</p> <pre>enrole.appServer.registry=ITIM_Custom_registry</pre>
<pre>enrole.appServer.security.domain</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the name of the Security domain created for IBM Security Identity Manager.</p> <p>Example (default):</p> <pre>enrole.appServer.security.domain=ISIMSecurityDomain</pre>
<pre>enrole.appServer.alwayssetisolevelrc</pre>	
	<p>Do not modify this property key and value.</p> <p>This property specifies that IBM Security Identity Manager must always set the transaction isolation level to Read-Committed when it acquires database connections.</p> <p>Because the WebSphere Application Server has internal support for setting the isolation level, this property must be set to false.</p> <p>Example (default):</p> <pre>enrole.appServer.alwayssetisolevelrc=false</pre>
<p>Login helper</p>	
<pre>enrole.appServer.loginHelper.class</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the Java class that is used to log each thread in to J2EE Security.</p> <p>Example (default):</p> <pre>enrole.appServer.loginHelper.class=com.ibm.itim.util.was.WAS40LoginHelper</pre>
<p>Application server servlet path separator</p>	
<pre>enrole.servlet.path.separator</pre>	

Table 35. WebSphere application server properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies the separator character used to specify path names to required resources.</p> <p>Example (default):</p> <pre>enrole.servlet.path.separator=.</pre>
Event notification system login	
SystemLoginContextFactory	
	<p>Do not modify this property key and value.</p> <p>Specifies the Java factory class for event notification system login appropriate for WebSphere Application Server.</p> <p>Example (default, entered as a single line):</p> <pre>SystemLoginContextFactory=com.ibm.itim.remoteservices.provider.itim.websphere.WSSystemLogonContextFactory</pre>

Remote services properties

The `enrole.remoteservices.assemblyline.encodeusingUTF8` property is referred whenever IBM Security Identity Manager sends the assembly line to IBM Security Directory Integrator dispatcher before running any operation. Use the UTF-8 encoding when the assembly line contains special characters such as German umlaut characters.

The value of the `enrole.remoteservices.assemblyline.encodeusingUTF8` property determines whether the assembly line sent to IBM Security Directory Integrator is encoded with the UTF-8 format or not.

Table 36. Remote services properties

<code>enrole.remoteservices.assemblyline.encodeusingUTF8</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether the UTF-8 encoding is used or not.</p> <p>Values include:</p> <ul style="list-style-type: none"> • true – Only the UTF-8 encoding is used. • false – The platform default encoding is used. <p>Example (default):</p> <pre>enrole.remoteservices.assemblyline.encodeusingUTF8=false</pre>

Web services properties

The web services properties define the properties that are used by IBM Security Identity Manager to manage the web services API.

Table 37 on page 260 determines the web services properties.

<i>Table 37. Web services properties</i>	
<code>enrole.webServices.version</code>	
	<p>Do not change this property key.</p> <p>Specifies the web services version. The value is returned by the <code>WSUnAuthService.getWebServicesVersion</code> web services API.</p> <p>Values include the version of the web services.</p> <p>Example (default):</p> <pre>enrole.webServices.version=1.0</pre>
<code>enrole.webseal.ltpa.cookie.name</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the property to identify the name of the HTTP header, which carries the LTPA token. Use this property in SSO mode only.</p> <p>The default value is <code>LtpaToken2</code>. Do not change this property unless the HTTP header name that carries the LTPA token is other than the default specified.</p> <p>Example (default):</p> <pre>enrole.webseal.ltpa.cookie.name=LtpaToken2</pre>
<code>enrole.webServices.session.cache.maxRetry</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Use this property key in cluster environment, and when the <code>enrole.webServices.session.mgmt.clientSide</code> property is set to <code>false</code>.</p> <p>Values must be a valid integer.</p> <p>Example (default):</p> <pre>enrole.webServices.session.cache.maxRetry=5</pre>
<code>enrole.webServices.session.mgmt.clientSide</code>	

Table 37. Web services properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether the session management is client side or server side.</p> <p>Values include:</p> <ul style="list-style-type: none"> • true – indicates that client side management is enabled. • false – indicates that a server-side management is expected. <p>Example (default):</p> <pre>enrole.webServices.session.mgmt.clientSide=true</pre>
<pre>authTokenTimeout</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the time in hours for how long a session can be valid. For example, even if you keep a session active by continuously using it, the session expires every two days, and you must log in again.</p> <p>Use this property key when the <code>enrole.webServices.session.mgmt.clientSide</code> property is set to false.</p> <p>Values include:</p> <p>Example (default):</p> <pre>authTokenTimeout=48</pre>
<pre>sessionInactivityTime</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the time in minutes for how long an unused session is active.</p> <p>Use this property key when the <code>enrole.webServices.session.mgmt.clientSide</code> property is set to false.</p> <p>Values include:</p> <p>Example (default):</p> <pre>sessionInactivityTime=15</pre>

Application server properties

Application server properties define properties that are specific to the application server, such as a user-selected locale.

Table 38 on page 261 defines the properties that are specific to the application server.

Table 38. Application server properties

User-selected locale

Table 38. Application server properties (continued)

locale	
	<p>Specifies the locale setting for the IBM Security Identity Manager environment.</p> <p>Example (default):</p> <pre>locale=en</pre>
Context factory name	
enrole.appServer.name	
	<p>Specifies the unique name of the application server.</p> <p>In a cluster environment, it is important that this name is unique for each member within a node in the cluster. Cluster members on different nodes can have same names.</p> <p>Example (default):</p> <pre>enrole.appServer.name=myserver</pre>
enrole.password.database.encrypted	
	<p>Use the runConfig utility to modify this property.</p> <p>Specifies whether the password for the database connection (specified by the <code>database.db.password</code> property in the <code>enroleDatabase.properties</code> file) is encrypted. Valid values are:</p> <ul style="list-style-type: none"> • true – Password is encrypted. • false – Password is not encrypted. <p>Example (default):</p> <pre>enrole.password.database.encrypted=true</pre>
enrole.password.ldap.encrypted	
	<p>Use the runConfig utility to modify this property.</p> <p>Specifies whether the LDAP password (specified by the <code>java.naming.security.credentials</code> property in the <code>enRoleLDAPConnection.properties</code> file) is encrypted. Valid values are:</p> <ul style="list-style-type: none"> • true – Password is encrypted. • false – Password is not encrypted. <p>Example (default):</p> <pre>enrole.password.ldap.encrypted=true</pre>
enrole.password.appServer.encrypted	

Table 38. Application server properties (continued)

	<p>Use the runConfig utility to modify this property.</p> <p>Specifies whether the application server password (specified by the <code>enrole.appServer.ejbuser.credentials</code> property in the <code>enRole.properties</code> file) is encrypted. Valid values are:</p> <ul style="list-style-type: none">• true – Password is encrypted.• false – Password is not encrypted. <p>Example (default):</p> <pre>enrole.password.appServer.encrypted=true</pre>
--	---

Organization properties

Organization properties define the organization name that is used by the directory server.

Table 39 on page 263 defines the properties for the organization name that is used by the directory server.

Table 39. Organization properties

	<pre>enrole.defaulttenant.id</pre>
	<p>Use the ldapConfig utility to modify this property.</p> <p>Specifies the short format of the organization name that is used by the directory server.</p> <p>This value is specified during installation of IBM Security Identity Manager or by running the ldapConfig utility.</p> <p>Example (default):</p> <pre>enrole.defaulttenant.id=org</pre> <p>In LDAP, this value is expressed as:</p> <pre>ou=org</pre>
	<pre>enrole.organization.name</pre>
	<p>Use the ldapConfig utility to modify this property.</p> <p>Specifies the long format of the organization name that is used by the directory server.</p> <p>This value is specified during installation of IBM Security Identity Manager or by running the ldapConfig utility.</p> <p>Example (default):</p> <pre>enrole.organization.name=Organization</pre>

LDAP server properties

LDAP server properties define the properties that are used by the directory server in which IBM Security Identity Manager stores data.

Table 40 on page 264 defines the properties that are used the directory server.

<i>Table 40. LDAP server properties</i>	
<code>enrole.ldapservers.root</code>	
	<p>Specifies the top-level entry node of the directory server data structure (dc=domain control). Use the ldapConfig utility to modify this value.</p> <p>This value is specified during installation of IBM Security Identity Manager.</p> <p>Example (default):</p> <pre>enrole.ldapservers.root=dc=com</pre>
<code>enrole.ldapservers.home</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the location of the system configuration information in the directory server.</p> <p>Example (default):</p> <pre>enrole.ldapservers.home=ou=itim</pre>
<code>enrole.ldapservers.agelimit</code>	
	<p>Do not change this property key and value unless you are a qualified administrator. Use the runConfig utility to modify this value.</p> <p>Specifies the number of days that an object remains in the recycle bin before it can be deleted when the cleanup script is started. The recycle bin age limit protects objects in the recycle bin from cleanup scripts for the specified length of time.</p> <p>Cleanup scripts can remove only those objects that are older than the age limit setting. If the age limit setting is 62 days (default), only objects in the recycle bin for more than 62 days can be deleted by starting the cleanup script.</p> <p>Example (default):</p> <pre>enrole.ldapservers.agelimit=62</pre>
<code>enrole.ldapservers.ditlayout</code>	

<i>Table 40. LDAP server properties (continued)</i>	
	<p>Do not modify this property key and value.</p> <p>Specifies the Java class that defines the structure of the data that is stored in the directory server.</p> <p>Example (default, flat structure):</p> <pre>enrole.ldapserver.ditlayout=com.ibm.itim.dataservices.dit.itim.FlatHashedLayout</pre>
<code>enrole.ldap.provider</code>	
	<p>Example (default):</p> <pre>enrole.ldap.provider=IBM</pre>

Search and LDAP control properties

Search and LDAP control properties are used to configure search strategy and LDAP control.

For more information about setting these parameters for your environment, see the tuning guide that is provided for IBM Security Identity Manager.

Table 41 on page 265 defines the properties used to configure search strategy and LDAP control.

<i>Table 41. Search and LDAP control properties</i>	
<code>enrole.search.sss.enable</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies whether Server Side Sorting is used for searches of the directory server. Enabling server-side sorting with this property can have a large negative impact when you view large organizational units. It is suggested that you disable this option in most environments.</p> <p>Example (default):</p> <pre>enrole.search.sss.enable=false</pre>
<code>enrole.search.vlv.enable</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies whether Virtual List View (VLV) is used for all return data from the directory server. This property can be enabled only when supported by the directory server. This option reduces the memory load on the application server but places a significant load on the LDAP server.</p> <p>Example (default):</p> <pre>enrole.search.vlv.enable=false</pre>

Table 41. Search and LDAP control properties (continued)

<code>enrole.search.paging.enable</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies whether Paged Sorting is used for searches of the directory server. This option reduces the memory load on the application server. Enabling it is not suggested because the directory server might place a limit on the number of outstanding paged searches.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2;">enrole.search.paging.enable=false</pre>
<code>enrole.search.paging.pagesize</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the page size used for paged LDAP searches when <code>enrole.search.paging.enable=true</code>.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2;">enrole.search.paging.pagesize=128</pre>
<code>enrole.search.cache.enable</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the use of cached searching to speed up LDAP searches.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2;">enrole.search.cache.enable=true</pre>
<code>enrole.search.cache.secondary.enable</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the use of secondary cached searching to speed up LDAP searches.</p> <p>Example (default):</p> <pre style="background-color: #f2f2f2;">enrole.search.cache.secondary.enable=true</pre>
<code>enrole.search.cache.secondary.filter.1</code>	

Table 41. Search and LDAP control properties (continued)

	<p>Do not modify this property key and value.</p> <p>Use a filter fragment for people to prevent LDAP search filters from getting cached. Filtered out LDAP search filters are cached in the secondary cache, if enabled.</p> <p>Example (default):</p> <pre>enrole.search.cache.secondary.filter.1=ou=people</pre>
<pre>enrole.search.cache.secondary.filter.2</pre>	
	<p>Do not modify this property key and value.</p> <p>Use a filter fragment for accounts to prevent LDAP search filters from getting cached. Filtered out LDAP search filters are cached in the secondary cache, if enabled.</p> <p>Example (default):</p> <pre>enrole.search.cache.secondary.filter.2=ou=accounts</pre>
<pre>enrole.search.cache.secondary.filter.3</pre>	
	<p>Do not modify this property key and value.</p> <p>Use a filter fragment for the <code>systemuser</code> to prevent LDAP search filters from getting cached. Filtered out LDAP search filters are cached in the secondary cache, if enabled.</p> <p>Example (default):</p> <pre>enrole.search.cache.secondary.filter.3=ou=systemuser</pre>
<pre>enrole.search.cache.secondary.filter.4</pre>	
	<p>Do not modify this property key and value.</p> <p>Use a filter fragment for orphan accounts to prevent LDAP search filters from getting cached. Filtered out LDAP search filters are cached in the secondary cache, if enabled.</p> <p>Example (default):</p> <pre>enrole.search.cache.secondary.filter.4=ou=orphans</pre>
<pre>enrole.search.clientside.filtering.enable</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the use of client-side filtering as a performance alternative on complex LDAP searches.</p> <p>Example (default):</p> <pre>enrole.search.clientside.filtering.enable=true</pre>

Table 41. Search and LDAP control properties (continued)

<code>enrole.search.strategy</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the Java class that defines the search strategy to process the return data from the directory server.</p> <p>Strategy values include:</p> <ul style="list-style-type: none">• <code>com.ibm.itim.apps.ejb.search.EnumeratedSearch</code> (process data on demand) Avoids the use of collections, if possible. Maintains a cache of the number of search links multiplied by the page size. The underlying connection is closed when the page cache is filled. Access control items are applied as results are retrieved.• <code>com.ibm.itim.apps.ejb.search.CollectedException</code> (process all data) This is the previous search mechanism, which converts the search results into a collection and sort it. Applying access control items on the collection as pages are retrieved. The underlying LDAP connection is freed as soon as the results are transformed into a collection. <p>Example (default):</p> <pre>enrole.search.strategy=com.ibm.itim.apps.ejb.search.EnumeratedSearch</pre>
<code>enrole.recyclebin.enable</code>	
	<p>Disable use of the recycle bin for a majority of objects to improve search times.</p> <p>Example (default for new installations):</p> <pre>enrole.recyclebin.enable=false</pre>

Person profile properties

Person profile properties identify a person profile.

Table 42 on page 268 defines the property used to identify a person profile. This property selects the profile by default when you create people or do advanced person searches in the administrative console.

Table 42. Person profile property

<code>enrole.personProfile</code>

Table 42. Person profile property (continued)

	<p>Searches in IBM Security Identity Manager use the default person profile <i>Person</i>. If you want to use custom person schemas, set this property to your profile.</p> <p>Example (default):</p> <pre>enrole.personProfile=Person</pre> <p>Example:</p> <pre>enrole.personProfile=your_profile</pre>
--	---

Profile and schema cache properties

Profile and schema cache properties define system cache performance.

Table 43 on page 269 defines the properties used to configure system cache performance.

Table 43. Profile and schema cache properties

<code>enrole.profile.timeout</code>	
	<p>This property key and value affects performance tuning for IBM Security Identity Manager. Do not change it unless you are a qualified administrator.</p> <p>Specifies the timeout value in minutes for information in the profile section of the cache. Information exceeding this timeout value is removed from the cache.</p> <p>Example (default):</p> <pre>enrole.profile.timeout=10</pre>
<code>enrole.schema.timeout</code>	
	<p>This property key and value affects performance tuning for IBM Security Identity Manager. Do not change it unless you are a qualified administrator.</p> <p>Specifies the timeout value in minutes for information in the schema section of the cache. Information exceeding this timeout value is removed from the cache.</p> <p>Example (default):</p> <pre>enrole.schema.timeout=10</pre>
<code>password.attributes</code>	

<i>Table 43. Profile and schema cache properties (continued)</i>	
	<p>Specifies which attribute is encrypted by the dataservices component.</p> <p>Example (default, on a single line):</p> <pre>password.attributes=ersynchpassword erServicePassword erServicePwd1 erServicePwd2 erServicePwd3 erServicePwd4 erADDomainPassword erPersonPassword erNotesPasswdAddCert eritamcred erep6umds</pre>
<code>enrole.reminder.timeout</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the cache interval (in minutes) for a workflow reminder.</p> <p>Example:</p> <pre>enrole.reminder.timeout=10</pre>
<code>signedObjectsCacheTimeout</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the cache interval (in hours) for a signed objects.</p> <p>Example:</p> <pre>signedObjectsCacheTimeout=8</pre>

LDAP connection pool properties

LDAP connection pool properties are used to configure cache connection requests to the directory server.

Table 44 on page 270 defines the properties used to configure the values that affect cache connection requests to the IBM Security Identity Manager directory server.

<i>Table 44. LDAP connection pool properties</i>	
<code>enrole.connectionpool.incrementcount</code>	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies the number of connections that are created any time the LDAP connection pool is incremented to accommodate an increasing demand.</p> <p>Example (default):</p> <pre>enrole.connectionpool.incrementcount=3</pre>
<code>enrole.connectionpool.authentication</code>	

Table 44. LDAP connection pool properties (continued)

	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies a list of space-separated authentication types of connections that can be pooled.</p> <p>Valid types are:</p> <ul style="list-style-type: none"> • none - No authentication is required. • simple • DIGEST-MD5 - <p>Example (default):</p> <pre>enrole.connectionpool.authentication=none simple</pre>
<pre>enrole.connectionpool.debug</pre>	
	<p>This property key and value specify the level of debug output. Valid values are "fine" (trace connection creation and removal) and "all" (all debugging information).</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • fine - Trace connection creation and removal. • all - All debugging information. <p>Example (default, commented out):</p> <pre>#enrole.connectionpool.debug=fine</pre>
<pre>enrole.connectionpool.initialpoolsize</pre>	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies the initial number of physical LDAP connections to create for the LDAP connection pool. This value must be less than or equal to the value of the maxpoolsize property.</p> <p>Example (default):</p> <pre>enrole.connectionpool.initialpoolsize=50</pre>
<pre>enrole.connectionpool.maxpoolsize</pre>	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies the maximum number of physical LDAP connections that can be created.</p> <p>Example (default):</p> <pre>enrole.connectionpool.maxpoolsize=100</pre>

Table 44. LDAP connection pool properties (continued)

<code>enrole.connectionpool.prefsiz</code>	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies the preferred number of physical LDAP connections that must be maintained concurrently. This number includes both in-use and idle connections. A size of zero or no value means that there is no preferred size. In that case, a request for a pooled connection results in a newly created connection if no idle ones are available.</p> <p>Example (no value):</p> <pre>enrole.connectionpool.prefsiz=</pre>
<code>enrole.connectionpool.protocol</code>	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies a list of space-separated protocol types of connections that can be pooled.</p> <p>Valid values are:</p> <ul style="list-style-type: none">• plain• ssl• plain ssl <p>Example (default):</p> <pre>enrole.connectionpool.protocol=plain ssl</pre>
<code>enrole.connectionpool.timeout</code>	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies the number of milliseconds that an idle connection can remain in the pool without being closed and removed from the pool.</p> <p>Example (default, commented out):</p> <pre>#enrole.connectionpool.timeout=10000</pre>

Mail properties

Mail properties are used to configure internal mail notification.

Table 45 on page 273 defines the properties used to configure internal mail notification.

Table 45. Mail services properties

<code>enrole.mail.notify</code>	
	<p>Specifies whether the sending of workflow internal email is synchronized or not.</p> <p>Values include:</p> <ul style="list-style-type: none"> • SYNC - Synchronized. • ASYNC - Asynchronized. <p>Example (default):</p> <div style="background-color: #f2f2f2; padding: 5px;"><code>enrole.mail.notify=ASYNC</code></div>

Messaging properties

Messaging properties configure the internal communication between components of the Java Message Service (JMS) used by IBM Security Identity Manager.

Table 46 on page 273 defines the properties used to configure the internal communication between components of the Java Message Service (JMS) used by IBM Security Identity Manager.

The adjustment of these property values is important to accurate performance tuning and scalability of the IBM Security Identity Manager product. Do not change property values in this section unless you are a qualified administrator.

Table 46. Messaging properties

Message timeout configuration	
<code>enrole.messaging.ttl</code>	
	<p>This property key and value affects performance tuning for JMS. Do not change the value unless you are a qualified administrator.</p> <p>Specifies the lifetime in minutes of a message in the queue. A value of zero specifies an unlimited lifetime.</p> <p>Example (default):</p> <div style="background-color: #f2f2f2; padding: 5px;"><code>enrole.messaging.ttl=0</code></div>
Messaging queue configuration	
<pre>enrole.messaging.managers= \ enrole.messaging.adhocSyncQueue \ enrole.messaging.workflowQueue \ enrole.messaging.sharedWorkflowQueue \ enrole.messaging.partitioningServiceQueue \ enrole.messaging.remoteServicesQueue \ enrole.messaging.remotePendingQueue \ enrole.messaging.mailServicesQueue \ enrole.messaging.policyAnalysisQueue \ enrole.messaging.policySimulationQueue \ enrole.messaging.importExportQueue</pre>	

Table 46. Messaging properties (continued)

	<p>Do not modify these property keys and values.</p> <p>Specifies the key names of supported IBM Security Identity Manager queues.</p>
<pre>enrole.messaging.adhocSyncQueue=adhocSyncQueue enrole.messaging.workflowQueue=workflowQueue enrole.messaging.sharedWorkflowQueue=sharedWorkflowQueue enrole.messaging.partitioningServiceQueue=partitioningServiceQueue enrole.messaging.remoteServicesQueue=remoteServicesQueue enrole.messaging.remotePendingQueue=remotePendingQueue enrole.messaging.mailServicesQueue=mailServicesQueue enrole.messaging.policyAnalysisQueue=policyAnalysisQueue enrole.messaging.policySimulationQueue=policySimulationQueue enrole.messaging.importExportQueue=importExportQueue</pre>	
	<p>Do not modify these property keys and values.</p> <p>Specifies the actual queue name as referenced by the application server.</p>
Queue attribute configuration	

Table 46. Messaging properties (continued)

<ul style="list-style-type: none">• SHARED <p>A Boolean value that indicates whether the queue is shared across a clustered deployment. In a cluster, a shared queue can be read and written to by all cluster members.</p> <p>Do not modify this property.</p> <p>Example (on a single line):</p> <pre>enrole.messaging.sharedWorkflowQueue.attributes=SHARED=true enrole.messaging.policyAnalysisQueue.attributes=SHARED=true enrole.messaging.policySimulationQueue.attributes=SHARED=true</pre> <p>Message processing errors detected by the messaging system cause individual messages to be redelivered and additional attempts to handle the message. Following the first indication of process failure, a retry is scheduled immediately. If the first attempt fails, another is scheduled with a delay that matches the value of the FIRST_RETRY_DELAY property. If the second attempt fails, another is scheduled with a delay that matches the value of the RETRY_DELAY property. Subsequent retries are attempted with the value of the RETRY_DELAY property until the MAX_RETRY_TIME threshold is reached.</p> <p>Set the following properties to manage how the system handles the retry attempts.</p> <ul style="list-style-type: none">• FIRST_RETRY_DELAY <p>The amount of time in milliseconds to delay before retrying after the initial immediate retry. Default value is 900000 (15 minutes).</p> <ul style="list-style-type: none">• RETRY_DELAY <p>The amount of time [in milliseconds] to delay before retrying after the immediate and first attempts fail. Default value is 3600000 (60 minutes).</p> <ul style="list-style-type: none">• MAX_RETRY_TIME <p>The maximum amount of time allowed for attempts, beginning with the first failure. Default value is 86400000 (24 hours)</p> <p>Example (on a single line):</p> <pre>enrole.messaging.workflowQueue.attributes=SHARED=false FIRST_RETRY_DELAY=300000 RETRY_DELAY=900000 MAX_RETRY_TIME=3600000</pre>

Password encryption properties

Password encryption properties are used to configure password encryption.

Table 47 on page 275 defines the properties used to configure password encryption.

<p>Table 47. Encryption properties</p>
<pre>enrole.encryption.algorithm</pre>

Table 47. Encryption properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies the cipher suite to use for encryption. For example, AES or PBEwithMD5AndDES.</p> <p>Example (default):</p> <pre>enrole.encryption.algorithm=AES</pre>
<pre>enrole.encryption.password</pre>	
	<p>Do not modify this property key and value. This value is specified during IBM Security Identity Manager installation.</p> <p>The value of the <code>enrole.encryption.password</code> property is moved into the <code>encryptionKey</code> property file. The value is encoded by default and is stored in the <code>encryptionKey</code> property file.</p> <p>For Password-Based Encryption (PBE) encryption algorithms (used for upgraded IBM Tivoli Identity Manager Version 4.6 installations), specifies the encrypted password used as an input parameter for Password-Based Encryption (PBE). PBE is a method of encrypting and decrypting data with a secret key based on a user-supplied password. For example, encrypted data includes shared secrets, service passwords, and some protected account attributes.</p> <p>Specifies the keystore password, in encrypted format, when AES is the encryption algorithm. For non-PBE based encryption algorithms (used for new IBM Tivoli Identity Manager Version 5.0 installations), the password is used to encrypt the keystore that stores the private key. For more information about this property, see the <code>enrole.encryption.keystore</code> property.</p> <p>This value is specified during IBM Security Identity Manager installation.</p>
<pre>enrole.encryption.passwordDigest</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the type of password digest used for an IBM Security Identity Manager password. Upgrading Tivoli Identity Manager from Version 4.6 continues to use the original hash algorithm until users change their passwords. This original algorithm is defined by the property <code>enrole.pre50.encryption.passwordDigest</code>. Valid values are:</p> <ul style="list-style-type: none"> • SHA-256 – Federal Information Processing Standards (FIPS)-approved hashing algorithm used by IBM Tivoli Identity Manager Version 5.0 for passwords. A random salt value is added to the data before it is hashed. • SHA-384 – Federal Information Processing Standards (FIPS)-approved hashing algorithm, providing 384 bits of security (by truncating the output of the SHA-512 algorithm). A random salt value is added to the data before it is hashed. • SHA-512 – Federal Information Processing Standards (FIPS)-approved hashing algorithm, providing 512 bits of security. A random salt value is added to the data before it is hashed. <p>Example (default):</p> <pre>enrole.encryption.passwordDigest=SHA-256</pre>
<pre>enrole.pre50.encryption.passwordDigest</pre>	

Table 47. Encryption properties (continued)

	<p>Do not modify this property key and value. Upgrading IBM Tivoli Identity Manager from Version 4.6 adds this property dynamically to this properties file.</p> <p>Specifies the type of password digest used for IBM Security Identity Manager password data from IBM Tivoli Identity Manager versions before 5.0. The lack of a ":" in an encrypted IBM Security Identity Manager password value is used to identify such migrated data.</p> <p>Note: All new passwords, including changed migrated passwords, are stored with the <code>enrole.encryption.passwordDigest</code> algorithm.</p> <p>Example (default for migrated installations, not present for new installations):</p> <pre>enrole.pre50.encryption.passwordDigest=MD5</pre>
<pre>enrole.encryption.keystore</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the keystore file name used to contain the randomly generated secret key for non-PBE based encryption algorithms, such as AES. This keystore file is protected with the <code>enrole.encryption.password</code> value. This file is in the <code>ISIM_HOME\data\keystore</code> directory.</p> <p>Example (default):</p> <pre>enrole.encryption.keystore=itimKeystore.jceks</pre>

Password synchronization properties

Password synchronization properties define the options that are used to configure password synchronization behavior.

The following properties have no effect when password synchronization is disabled.

<pre>enrole.passwordsynch.exclude.category</pre>	
	<p>Defines the account category that is excluded from password synchronization when password synch is enabled.</p>
<pre>enrole.passwordsynch.exclude.service</pre>	
	<p>Defines the service that is excluded from password synchronization when password synch is enabled. The accounts of the services, that are defined in the distinguished name will be excluded during password synchronization.</p>

Password transaction monitor properties

Password transaction monitor properties checks responses to password transactions. It expires those transactions when the user fails to respond in the specified interval.

When a password for a user is changed or automatically generated, an email notification is sent to a user. The email contains either the actual password or a link that the user can follow to obtain the new password. This activity is called a password transaction. The user must respond to the email and incorporate the new password within a specified amount of time. If the user fails to respond within the allowed time period, the password transaction expires.

The password transaction monitor is responsible for checking responses to password transactions. It expires those transactions when the user fails to respond to the email.

<i>Table 48. Password transaction monitor properties</i>	
<code>enrole.passwordtransactionmonitor.heartbeat</code>	
	<p>Specifies how often [in hours] the password transaction monitor checks for expired password transactions.</p> <p>Example (default):</p> <pre style="background-color: #f0f0f0; padding: 5px;">enrole.passwordtransactionmonitor.heartbeat=1</pre>

Product name properties

Product name properties identify this product.

Table 49 on page 278 defines the property used to identify the product.

<i>Table 49. Product property</i>	
<code>enrole.product.name</code>	
	<p>Do not change this name. This property key identifies the product name as IBM Security Identity Manager.</p> <p>Example (default):</p> <pre style="background-color: #f0f0f0; padding: 5px;">enrole.product.name=ITIM Enterprise</pre>

Reconciliation properties

Reconciliation properties are used to configure the reconciliation process where data retrieved from agents is synchronized in the IBM Security Identity Manager database.

Table 50 on page 278 defines the properties used to configure the values that affect the reconciliation process where data retrieved from agents is synchronized in the IBM Security Identity Manager database.

<i>Table 50. Reconciliation properties</i>	
Reconciliation configuration	
<code>enrole.reconciliation.accountcachesize</code>	

Table 50. Reconciliation properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the maximum size of the cache for existing accounts cache that is used for the reconciliation process. Setting a value larger than the default might cause processing of reconciliations to fail.</p> <p>Example (default):</p> <pre>enrole.reconciliation.accountcachesize=2000</pre>
<pre>enrole.reconciliation.threadcount</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the number of threads that are used to handle reconciled entries. This number of threads is created for each reconciliation process.</p> <p>Example (default):</p> <pre>enrole.reconciliation.threadcount=8</pre>
<pre>enrole.reconciliation.failurethreshold</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the maximum number of local accounts to delete at the end of reconciliation. If the value is exceeded, then no local account or supporting data entries are deleted. If the value is followed by a percent sign (%), specifies the maximum as percentage compared with total of (local accounts at reconciliation start plus the new accounts returned by reconciliation). A value of 100% specifies that there is no limit.</p> <p>Example (default, commented out):</p> <pre>#enrole.reconciliation.failurethreshold=100%</pre>
<pre>enrole.reconciliation.logTimeInterval</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the time interval in seconds for reconciliation progress trace log messages. A value of zero disables this time interval.</p> <p>Example (default, commented out):</p> <pre>#enrole.reconciliation.logTimeInterval=600</pre>
<pre>enrole.reconciliation.logEveryNResults</pre>	

Table 50. Reconciliation properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the count for reconciliation progress trace log messages. A value of zero disables this count.</p> <p>Example (default, commented out):</p> <pre>#enrole.reconciliation.logEveryNResults=5000</pre>
<p>Unsolicited notification events</p>	
<pre>account.EventProcessorFactory</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the built-in Java class for the account event processor factory.</p> <p>Example (default, entered as a single line):</p> <pre>account.EventProcessorFactory=com.ibm.itim.remoteservices.ejb.reconciliation.AccountEventProcessorFactory</pre>
<pre>person.EventProcessorFactory</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the built-in Java class for the person event processor factory.</p> <p>Example (default, entered as a single line):</p> <pre>person.EventProcessorFactory=com.ibm.itim.remoteservices.ejb.reconciliation.PersonEventProcessorFactory</pre>
<p>Reconciliation processing</p>	
<pre>account.ReconEntryHandlerFactory</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the built-in Java class for the account entry handler factory.</p> <p>Example (default, entered as a single line):</p> <pre>account.ReconEntryHandlerFactory=com.ibm.itim.remoteservices.ejb.mediation.AccountEntryHandlerFactory</pre>
<pre>person.ReconEntryHandlerFactory</pre>	

Table 50. Reconciliation properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies the built-in Java class for the person entry handler factory.</p> <p>Example (default, entered as a single line):</p> <pre>person.ReconEntryHandlerFactory=com.ibm.itim.remoteservices.ejb.mediation.PersonEntryHandlerFactory</pre>
<pre>enrole.reconciliation.accountChangeFormatter</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>When specified, this property allows you to customize how local attribute changes that are detected during reconciliation are formatted and stored. The default behavior can be overridden by specifying the fully qualified Java class name of an alternative implementation.</p> <p>Example (assuming Java class <code>com.example.custom.AccountChangeFormatter</code> is a custom implementation of interface <code>com.ibm.itim.remoteservices.ejb.mediation.IAccountChangeFormatter</code>). The example is entered as a single line:</p> <pre>enrole.reconciliation.accountChangeFormatter=com.example.custom.AccountChangeFormatter</pre>
<p>Deferring requests for failed remote resources</p>	
<pre>com.ibm.itim.remoteservices.ResourceProperties.DEFER_FAILED_RESOURCE</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies whether to defer requests to failed resources and wait for resource to restart before it sends them. Valid values are:</p> <ul style="list-style-type: none"> • true – Defers requests to failed resources and waits for the resource to restart. • false – If the resource fails, requests follows the configured workflow retry mechanism before it terminates as failed. See <code>enrole.workflow.maxretry</code> and <code>enrole.workflow.retrydelay</code>. <p>Example (default):</p> <pre>com.ibm.itim.remoteservices.ResourceProperties.DEFER_FAILED_RESOURCE=true</pre>
<pre>remoteservices.remotepending.interval</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the interval in seconds (120 minimum to 3600 maximum) to check whether failed resources restart.</p> <p>Example (default):</p> <pre>remoteservices.remotepending.interval=600</pre>

Table 50. Reconciliation properties (continued)

<code>com.ibm.itim.remoteservices.ResourceProperties.MAX_REQUEST_TIME</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the maximum time in seconds that a request to a resource can be outstanding. It includes time in pending state for asynchronous requests, or deferred requests due to a service failure or request backlog. Valid values are:</p> <ul style="list-style-type: none"> • -1 – Unlimited • 60 + (value of <code>remoteservices.remotepending.interval</code>) – Minimum time interval for outstanding requests. <p>Example (default):</p> <pre>com.ibm.itim.remoteservices.ResourceProperties.MAX_REQUEST_TIME=-1</pre>
<code>remoteservices.remotepending.restart.retry</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the time interval in minutes that pending requests generated from the restart of a failed service are given to complete. When the time interval ends, the server retries the requests.</p> <p>Example (default):</p> <pre>remoteservices.remotepending.restart.retry=1440</pre>
<code>com.ibm.itim.remoteservices.DSML2ServiceProvider.modifyAsREPLACE</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>For remote services, specifies the DSMLv2 (deprecated) provider mode of sending a modify request for attributes.</p> <p>Values include:</p> <ul style="list-style-type: none"> • true – Use the REPLACE operation. • false – Use the ADD and DELETE operations. <p>Example (default):</p> <pre>com.ibm.itim.remoteservices.DSML2ServiceProvider.modifyAsREPLACE=true</pre>

Scheduling properties

The scheduling properties are used to configure the internal scheduler that runs calendar-based and scheduled events.

Table 51 on page 283 defines the properties used to configure the internal scheduler responsible for running calendar-based scheduled events. Events and their schedules are stored in a database table.

<i>Table 51. Scheduling properties</i>	
<code>enrole.scheduling.heartbeat</code>	
	<p>This property key and value affects performance tuning for IBM Security Identity Manager. Do not change it unless you are a qualified administrator.</p> <p>Specifies the interval [in seconds] that the event monitor checks the database table for scheduled events.</p> <p>Example (default):</p> <pre>enrole.scheduling.heartbeat=30</pre>
<code>enrole.scheduling.timeout</code>	
	<p>This property key and value affects performance tuning for IBM Security Identity Manager. Do not change it unless you are a qualified administrator.</p> <p>Specifies the timeout value [in minutes] for the event processor.</p> <p>Example (default):</p> <pre>enrole.scheduling.timeout=10</pre>
<code>enrole.scheduling.fetchsize</code>	
	<p>This property key and value affects performance tuning for IBM Security Identity Manager. Do not change it unless you are a qualified administrator.</p> <p>Specifies the number of messages to retrieve at a time when in batch mode.</p> <p>Example (default):</p> <pre>enrole.scheduling.fetchsize=50</pre>

Shared secret properties

Shared secret properties are used to configure the level of protection of the shared secret code.

[Table 52 on page 283](#) defines the properties used to configure the level of protection of the shared secret code.

The shared secret is used by an account owner to retrieve a new or changed password for an account when the system is configured to not email passwords in the clear (that is, the value of `enrole.workflow.notifypassword=false`). This property determines whether the stored shared secret is hashed for additional protection.

<i>Table 52. Shared secret hashing properties</i>
<code>enrole.sharedsecret.hashed</code>

Table 52. Shared secret hashing properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether the shared secret code is hashed (secure) or not hashed (not secure).</p> <p>Values include:</p> <ul style="list-style-type: none">• true – Store the shared secret as hashed.• false – Store the shared secret as not hashed. <p>Example (default):</p> <pre>enrole.sharedsecret.hashed=false</pre>
--	---

System listening port properties

System listening port properties are used to configure the listening port settings for the IBM Security Identity Manager Server.

Table 53 on page 284 defines the properties used to configure the listening port settings for the IBM Security Identity Manager Server.

Table 53. System configuration properties

	<pre>enrole.system.listenPort</pre>
	<p>Do not modify this property key and value.</p> <p>Specifies the TCP (non-secure communication) listening port value.</p> <p>This value is set during IBM Security Identity Manager installation.</p> <p>Example (default):</p> <pre>enrole.system.listenPort=80</pre>
	<pre>enrole.system.SSLlistenPort</pre>
	<p>Do not modify this property key and value.</p> <p>Specifies the Secure Sockets Layer (SSL) listening port value.</p> <p>This value is set during IBM Security Identity Manager installation.</p> <p>Example (default):</p> <pre>enrole.system.SSLlistenPort=443</pre>

XML and DTD properties

XML and DTD properties are no longer used.

These properties are no longer used.

Table 54. XML and DTD properties	
enrole.dtd.uri	
	Not used.

Challenge response encoding properties

Challenge response encoding properties determine whether a response is encoded as case sensitive or insensitive.

Table 55 on page 285 defines the properties used to encode a response as case sensitive or insensitive.

Table 55. Challenge response encoding properties	
enrole.challengeresponse.responseConvertCase	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies how CR responses are encoded before they are stored in the directory. Valid values are:</p> <ul style="list-style-type: none">• lower – Encode the CR as lowercase.• upper – Encode the CR as uppercase.• none – Do not encode the CR. Retain the case-sensitive response as is. <p>Example (default):</p> <pre>enrole.challengeresponse.responseConvertCase=lower</pre>

Workflow properties

Workflow properties are used to configure the core IBM Security Identity Manager workflow engine.

Table 56 on page 286 defines the properties used to configure the core IBM Security Identity Manager workflow engine.

Note: If you begin your upgrade to Version 5.0 from Tivoli Identity Manager Version 4.5.x, and then to Version 4.6, the workflow notification properties are not modified during the upgrade. To have notification template customization available in IBM Tivoli Identity Manager Version 4.6 following an upgrade, you must modify the values of these properties. You must modify them to the new Template notification factories (prefixed with Template).

For example, the `enrole.workflow.notification.activitytimeout` property for Tivoli Identity Manager Version 4.5.x is shown in the following example (on a single line).

```
enrole.workflow.notification.activitytimeout=  
com.ibm.itim.workflow.notification.ActivityTimeoutNotification
```

If you upgrade Tivoli Identity Manager Version 4.6 to Version 5.0, the change occurs automatically. It assumes either of the following conditions:

- Version 4.6 was the starting point for upgrade
- You made the manual change to the `enrole.workflow.notification.activitytimeout` property before you upgrade from Version 4.5.x

Table 56. Workflow configuration properties	
Workflow configuration	
<code>enrole.workflow.lrucache.size</code>	
	<p>Specifies the size of the cache used to temporarily use and access workflow objects. Do not change it unless directed by IBM support. Making this value too large can result in out of memory conditions oIBM Security Identity Manager Server.</p> <p>Example (default, commented out):</p> <pre>## enrole.workflow.lrucache.size=number_of_entries</pre> <p>where the default value of <i>number_of_entries</i> is 2000.</p>
<code>enrole.workflow.notifyoption</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the behavior of workflow email notifications. Values are:</p> <ul style="list-style-type: none"> • 0 (NOTIFY_NONE) – Security Identity Manager does not send email notifications when the workflow process completes. • 1 (NOTIFY_REQUESTER) – A process completion notification is sent to the requester when the workflow process completes. Account email notifications are then sent to the requestee for the following account requests: <ul style="list-style-type: none"> New Account New Password Change Account Deprovision Account Suspend Account Restore Account <p>For example, when the workflow process completes for a new account request, a process completion notification is sent to the requester. A new account notification is then sent to the requestee.</p> <p>Example (default):</p> <pre>enrole.workflow.notifyoption=1</pre>
<code>enrole.workflow.notifypassword</code>	

Table 56. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the type of email notification in a password transaction (caused when a user password is changed or automatically generated). Values are:</p> <ul style="list-style-type: none"> • true – email notification of a password change can be sent to a user. The actual notification mechanism and whether to include the actual password in the email is dictated by the configuration of the <code>enrole.workflow.notification.newpassword</code> property value. • false – email notification of a password change is sent to a user. The email contains a URL where the user can obtain the password. The URL prompts the user for the shared secret. <p>Example (default):</p> <pre>enrole.workflow.notifypassword=true</pre>
<pre>enrole.workflow.notifyaccountsonwarning</pre>	
	<p>Specifies whether account email notifications are sent when the account operation results in a warning. Values are:</p> <ul style="list-style-type: none"> • true – Sends account email notifications. • false – Does not send account email notifications. <p>Example (default):</p> <pre>enrole.workflow.notifyaccountsonwarning=false</pre>
<pre>enrole.workflow.maxretry</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the number of times an attempt is made to start a workflow that initially failed. See also <code>enrole.workflow.retrydelay</code>.</p> <p>Example (default):</p> <pre>enrole.workflow.maxretry=2</pre>
<pre>enrole.workflow.retrydelay</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the time delay [in milliseconds] between successive attempts to start a workflow application that initially failed. See also <code>enrole.workflow.maxretry</code>.</p> <p>Example (default):</p> <pre>enrole.workflow.retrydelay=60000</pre>
<pre>enrole.workflow.skipapprovalforrequester</pre>	

Table 56. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>For a workflow activity that requires approval, this property specifies whether to skip the approval for other approvers if the requester is also an approver. Values are:</p> <ul style="list-style-type: none"> • true – Skips approval for other approvers if the requester is also an approver. • false – Forces an approval check from other required approvers of the activity, <i>except</i> the requester (if the requester is also an approver). If the requester is a single approver as a result of participant resolution, then the approval is skipped even when value is set to false. <p>Example (default):</p> <pre>enrole.workflow.skipapprovalforrequester=false</pre>
<pre>enrole.workflow.disablerequesteeapproval</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>For a workflow activity that requires approval, this property specifies whether to disable the requestee approval if the requestee is also an approver. Values are:</p> <ul style="list-style-type: none"> • true – Disables the requestee approval if the requestee is also an approver. • false – Sends an approval check to the requestee and other resolved participants if the requestee is also an approver. <p>The default value is false.</p> <p>Example (default):</p> <pre>enrole.workflow.disablerequesteeapproval=false</pre> <p>For more information, see <i>Planning > Workflow planning > Workflow participants > Disable requestee or requester approval</i> on the <i>IBM Security Identity Manager documentation</i>.</p>
<pre>enrole.workflow.disablerequesterapproval</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>IBM Security Identity Manager considers this property value only when the <code>enrole.workflow.skipapprovalforrequester</code> property value is set to false.</p> <p>For a workflow activity that requires approval, this property specifies whether to disable the requester approval if the requester is an approver. Values are:</p> <ul style="list-style-type: none"> • true – A value set to false for the <code>enrole.workflow.skipapprovalforrequester</code> property disables automatic approval if the requester is a lone approver. • false – Works according to the value that you set for the <code>enrole.workflow.skipapprovalforrequester</code> property. <p>Example (default):</p> <pre>enrole.workflow.disablerequesterapproval=false</pre> <p>For more information, see <i>Planning > Workflow planning > Workflow participants > Disable requestee or requester approval</i> on the <i>IBM Security Identity Manager documentation</i>.</p>
<pre>enrole.workflow.skipfornoncompliantaccount</pre>	

Table 56. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether to engage the entitlement workflow that is associated with the account. Specifies when a system account modification is triggered as a result of a policy enforcement action. Values are:</p> <ul style="list-style-type: none"> • true – Skips this action. • false – Does not skip this action. <p>Example (default):</p> <pre>enrole.workflow.skipfornoncompliantaccount=true</pre>
<pre>enrole.workflow.distribution</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether workflow requests use the IBM Security Identity Manager shared queues, which allow for workload distribution. Values are:</p> <ul style="list-style-type: none"> • true – Workflow requests are eligible for distribution. • false – Workflow requests are not eligible for distribution. <p>Example (default):</p> <pre>enrole.workflow.distribution=true</pre>
<pre>enrole.workflow.async_completion_enabled</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether the system uses asynchronous completion checking for some system workflows, which can decrease database lock contention and improve performance. Values are:</p> <ul style="list-style-type: none"> • true – Uses asynchronous completion checking. • false – Does not use asynchronous completion checking. <p>Example (default):</p> <pre>enrole.workflow.async_completion_enabled=true</pre>
<pre>enrole.workflow.async_completion_interval_sec</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the interval in seconds that the system checks to see whether certain system workflows are complete. Only applicable when <code>enrole.workflow.async_completion_enabled=true</code>.</p> <p>Example (default):</p> <pre>enrole.workflow.async_completion_interval_sec=30</pre>
<pre>enrole.workflow.notification.activitytimeout</pre>	

Table 56. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates the workflow activity timeout notification.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.activitytimeout= com.ibm.itim.workflow.notification.TemplateActivityTimeoutNotification</pre>
<pre>enrole.workflow.notification.processtimeout</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates the workflow process timeout notification.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.processtimeout=com.ibm.itim.workflow. notification.TemplateProcessTimeoutNotification</pre>
<pre>enrole.workflow.notification.processcomplete</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates the notification for when a workflow process is completed.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.processcomplete=com.ibm.itim.workflow. notification.TemplateProcessCompleteNotification</pre>
<pre>enrole.workflow.notification.pendingwork</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates the notification for when a workflow process is completed for manual activities (Approvals and Requests for Information).</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.pendingwork=com.ibm.itim.workflow. notification.TemplatePendingWorkNotification</pre>
<pre>enrole.workflow.notification.newaccount</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates the notification for when a workflow process is completed for a new account.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.newaccount=com.ibm.itim.workflow. notification.TemplateNewAccountNotification</pre>
<pre>enrole.workflow.notification.newpassword</pre>	

Table 56. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates a notification when a user changes a password. This property is used only when the value for the property is <code>true</code>.</p> <pre>enrole.workflow.notifypassword=true</pre> <p>This property responds to the following three-password change scenarios:</p> <ul style="list-style-type: none"> • When a user changes the password for the account • When the administrator forces a password change on the account • When a user is successfully identified through the password challenge/response feature, and challenge/response is configured. <p>Valid classes include:</p> <ul style="list-style-type: none"> • NewPasswordNotification Email notification that includes the password (in ASCII text) is sent to a user (default). • EmptyNotificationFactory Suppresses email notification. The preferred method for suppressing any notification is through the Workflow Notification GUI. • PasswordChangeNotificationFactory Email notification that does not include the password is sent to a user. Message body says: "Process completed". <p>The <code>EmptyNotificationFactory</code> and <code>PasswordChangeNotificationFactory</code> classes are in the <code>examples.jar</code> package in the <code>examples</code> directory.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.newpassword=com.ibm.itim.workflow.notification.TemplateNewPasswordNotification</pre>
	<pre>enrole.workflow.notification.deprovision</pre>
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates deprovisioning notification.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.deprovision=com.ibm.itim.workflow.notification.TemplateDeprovisionNotification</pre>
	<pre>enrole.workflow.notification.workorder</pre>
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates work order notifications.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.workorder=com.ibm.itim.workflow.notification.TemplateWorkOrderNotification</pre>
	<pre>enrole.workflow.notification.changeaccount</pre>

Table 56. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates account change notifications.</p> <p>Example (default, as a single line):</p> <pre>enrole.workflow.notification.changeaccount= com.ibm.itim.workflow.notification.TemplateChangeAccountNotification</pre>
<pre>enrole.workflow.notification.restoreaccount</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates account restoration notifications.</p> <p>Example (as a single line):</p> <pre>enrole.workflow.notification.restoreaccount= com.ibm.itim.workflow.notification.TempateRestoreAccountNotification</pre>
<pre>enrole.workflow.notification.suspendaccount</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates account suspension notifications.</p> <p>Example (as a single line):</p> <pre>enrole.workflow.notification.suspendaccount= com.ibm.itim.workflow.notification.TemplateSuspendAccountNotification</pre>

Lifecycle rule properties

Lifecycle rule properties define values such as the partition size used for lifecycle rules.

Table 57 on page 292 defines the properties used to configure lifecycle rules.

Table 57. Lifecycle rule properties

<pre>enrole.lifecyclerule.partition.size</pre>	
	<p>Do not change this value unless requested by IBM support. Specifies the size of the data partitions for processing lifecycle rules. This parameter determines how much data is processed in a single step.</p> <p>Example (default):</p> <pre>enrole.lifecyclerule.partition.size=100</pre>

Application client request properties

Application client request properties define the properties used to configure the lifetime, or timeout, value for the authentication token used to allow third-party communication with IBM Security Identity Manager Server.

Table 58 on page 293 defines the properties used to configure the lifetime, or timeout, value for the authentication token used by the IBM Security Identity Manager application API to allow third-party applications to communicate with the IBM Security Identity Manager Server.

<i>Table 58. Application client request properties</i>	
<code>authTokenTimeout</code>	
	<p>Specifies timeout value in hours for the authentication token that is used for communication between third-party applications (with the IBM Security Identity Manager application API) and the IBM Security Identity Manager Server.</p> <p>A value of -1 indicates that there is no timeout for the authentication token.</p> <p>Example (default):</p> <pre>authTokenTimeout=48</pre>

Reverse password synchronization properties

Reverse password synchronization properties are used to configure reverse password synchronization.

Table 59 on page 293 defines the properties used to configure reverse password synchronization.

<i>Table 59. Reverse password synchronization properties</i>	
<code>reversePasswordSynch.bypassPwdValidationOnOrphanAccount</code>	
	<p>Specifies whether to bypass the password validation on the orphan account when the request is submitted from the agent. Valid values are:</p> <ul style="list-style-type: none">• true – Bypass password validation.• false – Validate passwords. <p>Example (default):</p> <pre>reversePasswordSynch.bypassPwdValidationOnOrphanAccount=false</pre>
<code>enrole.passwordsynch.module.sendMail</code>	

Table 59. Reverse password synchronization properties (continued)

	<p>Specifies whether to enable or disable email notifications when password synchronization is triggered by the reverse password synchronization agent, not from the IBM Security Identity Manager graphical user interface. Valid values are:</p> <ul style="list-style-type: none"> • true – Enable email notifications. • false – Disable email notifications. <p>Example (default):</p> <pre>enrole.passwordsynch.module.sendMail=false</pre>
--	---

Post office properties

Post office properties are used to configure the post office for email collection.

Table 60 on page 294 defines the properties for testing post office configuration.

Table 60. Post office properties

<pre>enrole.postoffice.test.subject1 enrole.postoffice.test.textbody1 enrole.postoffice.test.xhtmlbody1</pre>	
	<p>Specifies the contents of the emails that are used when you test the post office configuration. It is one of three emails to which the template is applied.</p> <p>Example (default):</p> <pre>enrole.postoffice.test.subject1=This is subject 1 enrole.postoffice.test.textbody1=This is the text body 1 enrole.postoffice.test.xhtmlbody1=This is the html body 1</pre>
<pre>enrole.postoffice.test.subject2 enrole.postoffice.test.textbody2 enrole.postoffice.test.xhtmlbody2</pre>	
	<p>Specifies the contents of the emails that are used when you test the post office configuration. It is one of three emails to which the template is applied.</p> <p>Example (default):</p> <pre>enrole.postoffice.test.subject2=This is subject 2 enrole.postoffice.test.textbody2=This is the text body 2 enrole.postoffice.test.xhtmlbody2=This is the html body 2</pre>
<pre>enrole.postoffice.test.subject3 enrole.postoffice.test.textbody3 enrole.postoffice.test.xhtmlbody3</pre>	

Table 60. Post office properties (continued)

	<p>Specifies the contents of the emails that are used when you test the post office configuration. It is one of three emails to which the template is applied.</p> <p>Example (default):</p> <pre>enrole.postoffice.test.subject3=This is subject 3 enrole.postoffice.test.textbody3=This is the text body 3 enrole.postoffice.test.xhtmlbody3=This is the html body 3</pre>
<pre>enrole.postoffice.test.topic</pre>	
	<p>Specifies the topic of the email that is used when you test the post office configuration. The three test emails, whose content is defined by the preceding properties, all have this topic. The post office function gathers and stores emails by topic and locale, It then aggregates and sends them as one email on a configured interval, such as once a day or once a week. This method prevents flooding the recipient with many individual emails for a type of event. The topic data usually indicates the type of event. It is also made available to the programming environment that is activated when the gathered emails are aggregated into one summarizing email. In this way, the topic under which all of these emails were gathered can be prominently displayed in the aggregate email that is sent.</p> <p>Example (default):</p> <pre>enrole.postoffice.test.topic=topic1</pre>
<pre>enrole.postoffice.test.locale</pre>	
	<p>Specifies the locale for the language that is used in an email.</p> <p>Example (default):</p> <pre>enrole.postoffice.test.locale=en_US</pre>

Database resource bundle properties

Database resource bundle properties determine the refresh interval for the database resource bundle.

Table 61 on page 295 defines the properties used to determine the refresh interval for the database resource bundle.

Table 61. Database resource bundle properties

<pre>enrole.databaseresourcebundle.refreshInterval</pre>	
	<p>Specifies how many minutes to wait before DatabaseResourceBundle is checked for changes and reloaded.</p> <p>Example (default):</p> <pre>enrole.databaseresourcebundle.refreshInterval=5</pre>

Database cleanup properties

Database cleanup properties define the parameters to clean up session information in the database.

Table 62 on page 296 defines the parameters for the policy analysis scavenger thread to clean up session information in the database.

<i>Table 62. Database cleanup properties</i>	
<code>provisioning.policy.preview.cleanup.interval</code>	
	Specifies the interval in minutes that the scavenger thread scans the database. Example: <pre>provisioning.policy.preview.cleanup.interval=30</pre>
<code>provisioning.policy.analysis.idle.timeout</code>	
	Represents the expired time setting for a policy analysis session. The scavenger thread cleans up the staged data of a policy analysis session if the session ends at an interval that is greater than the timeout value. The timeout value might be 120 minutes. Example: <pre>provisioning.policy.analysis.idle.timeout=120</pre>

Create password check box properties

Create password check box properties define the default check box properties to create a password.

Table 63 on page 296 defines the default create password check box properties.

<i>Table 63. Create password check box default properties</i>	
<code>enrole.CreatePassword</code>	
	Specifies whether a password is created automatically. Valid values are: <ul style="list-style-type: none">• true – Create a password.• false – Do not create a password. The user must type in the password. Example (default): <pre>enrole.CreatePassword=true</pre>

Access catalog properties

The `com.ibm.itim.accesscatalog.groupIntersectionJoin.enabled` enables support for searching group access when requesting access in the Identity Service Center when Intersection

Join directive is used for the group attribute. The `com.ibm.itim.accesscatalog.customJoin.enabled` enables support for searching group access when requesting access in the Identity Service Center when Custom Join directive is used for the group attribute.

<i>Table 64. Access catalog properties</i>	
<code>com.ibm.itim.accesscatalog.groupIntersectionJoin.enabled</code>	
	<p>Do not change this property value unless you are a qualified administrator.</p> <p>Enables support for searching group access when requesting access in the Identity Service Center in the case where Intersection Join directive is used for the group attribute.</p> <p>Values include:</p> <ul style="list-style-type: none"> • true • false <p>The default is false.</p> <p>Example (default):</p> <pre>com.ibm.itim.accesscatalog.groupIntersectionJoin.enabled=false</pre>
<code>com.ibm.itim.accesscatalog.customJoin.enabled</code>	
	<p>Do not change this property value unless you are a qualified administrator.</p> <p>Enables support for searching group access when requesting access in the Identity Service Center in the case where Custom Join directive is used for the group attribute.</p> <p>Values include:</p> <ul style="list-style-type: none"> • true • false <p>The default is false.</p> <p>Example (default):</p> <pre>com.ibm.itim.accesscatalog.customJoin.enabled=false</pre>

Identity feed properties

Identity feed properties define a default identity feed action, such as whether to suspend an account.

Table 65 on page 297 defines the default identity feed properties.

<i>Table 65. Default identity feed properties</i>
<code>enrole.suspend.accounts.identity.feed</code>

Table 65. Default identity feed properties (continued)

	<p>Specifies whether all of a user's accounts are suspended when the person is suspended during an identity feed. Valid values are:</p> <ul style="list-style-type: none"> • true – Suspend all accounts of a suspended user. • false – Do not suspend all accounts of a suspended user. <p>Example (default):</p> <pre>enrole.suspend.accounts.identity.feed=true</pre>
--	--

Upgrade properties

Upgrade properties define values for the upgrade of a specific release of IBM Security Identity Manager.

Table 66 on page 298 defines the product upgrade properties.

Table 66. Default upgrade properties

<code>minUpgradeVersion</code>	
	<p>Specifies the minimum version that the upgrade supports for a specific release of IBM Security Identity Manager.</p> <p>Example (default):</p> <pre>minUpgradeVersion=5.0</pre>
<code>file.merge.list</code>	
	<p>Specifies which properties files are merged during the upgrade of IBM Security Identity Manager.</p> <p>Example (default):</p> <pre>file.merge.list=enRole \ enRoleLDAPConnection \ enRoleDatabase \ enRoleLogging \ enRoleMail \ ui \ CustomLabels \ CustomLabels_en \ enRoleAuthentication \ adhocreporting \ enroleworkflow \ enroleAuditing \ SelfServiceScreenText \ SelfServiceScreenText_en \ SelfServiceHelp \ SelfServiceUI \ SelfServiceHomePage\ scriptframework\ encryptionKey\ KMIPServer</pre> <p>Back up these files with <code>backupPropertyFiles.sh</code> or <code>backupPropertyFiles.cmd</code>.</p>

Multiple password-synch agent properties

Multiple password-synch agent properties are used to configure the IBM Security Identity Manager Server to support multiple password-synchronization agents.

Table 67 on page 299 defines the properties used to configure the support for multiple password-synch agents.

<i>Table 67. Multiple password-synch agent properties</i>	
<code>enrole.passwordsynch.enabledonresource</code>	
	<p>Specifies whether to enable or disable the support for multiple password-synch agents. Valid values are:</p> <ul style="list-style-type: none">• true – Enable the support for multiple password-synch agents• false – Disable the support for multiple password-synch agents <p>Example (default):</p> <pre>enrole.passwordsynch.enabledonresource=false</pre>
<code>enrole.passwordsynch.toleranceperiod</code>	
	<p>Specifies the maximum time duration, in <i>seconds</i>, between a password change request sent from the IBM Security Identity Manager Server to the password synch resource, and receiving a reverse password synch request from the plug-in installed on the password synch resource.</p> <p>Example (default):</p> <pre>enrole.passwordsynch.toleranceperiod=60</pre>
<code>enrole.PasswordSynchStoreMonitor.heartbeat</code>	
	<p>Specifies the password synch transaction monitor heartbeat, in <i>hours</i>.</p> <p>Example (default):</p> <pre>enrole.PasswordSynchStoreMonitor.heartbeat=1</pre>

Concurrency properties

Account concurrency properties determine how to resolve multiple provisioning requests for the same account ID.

<i>Table 68. Account concurrency properties</i>
<code>account.provision.concurrency.resolution</code>

Table 68. Account concurrency properties (continued)

	<p>Specifies which conflict resolution method is used when a concurrency issue occurs.</p> <p>Select from the following values:</p> <ul style="list-style-type: none">• 0 - Change the concurrent account add operations to account modify operations.• 1 - Add the account with a newly generated account user ID• 2 - No operation override. Fail the account provisioning. <p>Example (default):</p> <pre>account.provision.concurrency.resolution=0</pre>
--	---

Required field properties

These properties are used to configure whether fields in the user interface are required to be completed by the user.

Table 69 on page 300 defines the properties that are used to determine whether a field in the user interface is a required field.

Table 69. Required field properties

	<pre>enrole.justificationRequired</pre>
	<p>Specifies whether the Justification field is a required field.</p> <p>By default, the Justification field is not displayed in the user interface. Setting this property to true causes the Justification property to be displayed. It also sets the field as required to be completed by the user.</p> <p>Example (default):</p> <pre>enrole.justificationRequired=false</pre>

Index

A

access control
API [4](#)
AccessRequestBatch object, JavaScript extension [158](#)
AccessRequestBatch.getAccessDeprovisioningStatusList object, JavaScript extension [161](#)
AccessRequestBatch.getAccessProvisioningStatusList object, JavaScript extension [161](#)
AccessRequestBatch.getAccessUpdateStatusList object, JavaScript extension [162](#)
AccessRequestBatch.getSubmittedAccessDeprovisioningList object, JavaScript extension [160](#)
AccessRequestBatch.getSubmittedAccessProvisioningList object, JavaScript extension [159](#)
AccessRequestBatch.getSubmittedAccessUpdateList object, JavaScript extension [160](#)
account
object, JavaScript extension [71](#)
Account.getAndDecryptPassword object
JavaScript extension [72](#)
Account.setAndEncryptPassword object
JavaScript extension [72](#)
AccountModelExtension, JavaScript extensions [58](#)
AccountSearch object, JavaScript extension [73](#)
AccountSearch.searchByOwner object
JavaScript extension [73](#)
AccountSearch.searchById object, JavaScript extension [74](#)
AccountSearch.searchByURI object, JavaScript extension [75](#)
activity object, JavaScript extension [75](#)
Activity.auditEvent object, JavaScript extension [77](#)
Activity.description object, JavaScript extension [77](#)
Activity.duedate object, JavaScript extension [77](#)
Activity.getSubProcesses(), JavaScript extension [78](#)
Activity.guid object, JavaScript extension [78](#)
Activity.id object, JavaScript extension [78](#)
Activity.index object, JavaScript extension [79](#)
Activity.name object, JavaScript extension [79](#)
Activity.participant object, JavaScript extension [79](#)
Activity.resultDetail object, JavaScript extension [79](#)
Activity.resultSummary object, JavaScript extension [80](#)
Activity.setResult object, JavaScript extension [80](#)
Activity.started object, JavaScript extension [80](#)
Activity.state object, JavaScript extension [81](#)
Activity.subtype object, JavaScript extension [81](#)
Activity.type object, JavaScript extension [81](#)
adhocreporting.properties [180](#)
APIs
access control [4](#)
authentication [5](#)
data services [3](#), [6](#)
group [4](#)
IBM Directory Integration API [6](#)
JavaScript [6](#)
mail [6](#)
overview [3](#)
password rules [7](#)

APIs (*continued*)
policy analysis [7](#)
reconciliation [5](#)
self registration [4](#)
service provider [7](#)
single sign-on [8](#)
web services API [8](#)
workflow [11](#)

APIsgroup
recertification policy [4](#)
application client request configuration [293](#)
application extension methods [1](#)
application server information [261](#)
AttributeChangeOperation object, JavaScript extension [82](#)
AttributeChangeOperation.attr object, JavaScript extension [82](#)
AttributeChangeOperation.op object, JavaScript extension [82](#)
AttributeChangeOperation.values, JavaScript extension [83](#)
AttributesExtension, JavaScript extensions [56](#)
authentication
API [5](#)
authentication properties
enRoleAuthentication.properties [192](#)

C

cache information [269](#)
challenge response encoding information [285](#)
concurrency
enrole properties [299](#)
ConfigErrorMessages.properties, not configurable [178](#)
ConfigLabels.properties, not configurable [178](#)
ConfigMessages.properties, not configurable [178](#)
constructor
JavaScript migration, example [67](#)
ContainerSearch object, JavaScript extension [83](#)
ContainerSearch.searchByFilter object, JavaScript extension [83](#)
ContainerSearch.searchByURI object, JavaScript extension [84](#)
content tags
dynamic tags [31](#)
examples [31](#), [36](#)
Context object, JavaScript extension [84](#)
Context.getAccountParameter object, JavaScript extension [86](#)
Context.getActivityResult object, JavaScript extension [86](#)
Context.getActivityResultById object, JavaScript extension [86](#)
Context.getLoopCount object, JavaScript extension [87](#)
Context.getLoopCountById object, JavaScript extension [87](#)
Context.getProcessType object, JavaScript extension [87](#)
Context.getRequestee object, JavaScript extension [88](#)
Context.getService object, JavaScript extension [88](#)
control type
SubForm

- control type (*continued*)
 - SubForm (*continued*)
 - contextual parameters [171](#)
 - parameter names [172](#)
 - writing [173](#)
- create password checkbox information [296](#)
- credential
 - shared access module [89](#)
- Credential.getAccessMode() [90](#)
- Credential.isNotifyOnly() object, JavaScript extension [91](#)
- Credential.isPasswordViewable() object, JavaScript extension [91](#)
- Credential.isResetPasswordAtCheckin() object, JavaScript extension [92](#)
- CustomForms.properties, not configurable [178](#)
- customization
 - date range [17](#)
- CustomLabels.properties
 - supplemental properties [187](#)

D

- data services
 - API [3](#)
- database cleanup information [296](#)
- database resource bundle [295](#)
- DataBaseFunctions.conf [188](#)
- dataservices attributes
 - recertification [15](#)
- date range
 - customization [17](#)
- default notification templates
 - manual service [36](#)
- default recertification templates
 - recertification default messages [38](#)
- default workflow templates
 - workflow default messages [43](#)
- DelegateExtension, JavaScript extensions [57](#)
- dictionary
 - password policy [13](#)
- DirectoryObject object, JavaScript extension [93](#)
- DirectoryObject.addProperty object, JavaScript extension [94](#)
- DirectoryObject.dn object, JavaScript extension [94](#)
- DirectoryObject.getChanges object, JavaScript extension [95](#)
- DirectoryObject.getProperty object, JavaScript extension [95](#)
- DirectoryObject.getPropertyAsDate
 - object [96](#)
- DirectoryObject.getPropertyAsString
 - object [96](#)
- DirectoryObject.getPropertyNames object, JavaScript extension [97](#)
- DirectoryObject.name object, JavaScript extension [97](#)
- DirectoryObject.profileName object, JavaScript extension [97](#)
- DirectoryObject.setProperty, JavaScript extension [99](#)
- Dsml2RootDSE.properties, not configurable [178](#)
- Dsml2Schema.properties, not configurable [178](#)
- dynamic tags
 - content tags
 - examples [31](#)

E

- EmailContext object, JavaScript extension [99](#)
- EmailContextExtension, JavaScript extensions [57](#)
- encryption information [275](#)
- enrole
 - concurrency [299](#)
- Enrole object, JavaScript extension [101](#)
- Enrole.generatePassword object, JavaScript extension [102](#)
- Enrole.getAttributeValue object, JavaScript extension [103](#)
- Enrole.getAttributeValues object, JavaScript extension [103](#)
- Enrole.localize object, JavaScript extension [103](#)
- Enrole.log object, JavaScript extension [104](#)
- Enrole.logError object, JavaScript extension [104](#)
- Enrole.loginInfo object, JavaScript extension [105](#)
- Enrole.logWarning object, JavaScript extension [105](#)
- enRole.properties file
 - application client request configuration [293](#)
 - application server information [261](#)
 - cache information [269](#)
 - challenge response encoding information [285](#)
 - create password checkbox [296](#)
 - database cleanup [296](#)
 - database resource bundle [295](#)
 - encryption information [275](#)
 - identity feed [297](#)
 - LDAP connection pool information [270](#)
 - LDAP server information [264](#)
 - life cycle rule [292](#)
 - mail services configuration [272](#)
 - messaging information [273](#)
 - organization name [263](#)
 - password synchronization [299](#)
 - password transaction monitor settings [277](#)
 - person profile [268](#)
 - post office [294](#)
 - product name [278](#)
 - reconciliation information [278](#)
 - required fields [300](#)
 - reverse password synchronization [293](#)
 - scheduling information [282](#)
 - search strategy and LDAP control configuration [265](#)
 - shared secret hashing [283](#)
 - system configuration program [284](#)
 - tenant information, default [263](#)
 - upgrade [298](#)
 - WebSphere-specific configuration [255](#)
 - workflow configuration information [285](#)
 - XML and DTD information [285](#)
- Enrole.toGeneralizedTime object, JavaScript extension [106](#)
- Enrole.toMilliseconds object, JavaScript extension [106](#)
- Enrole.traceMax object, JavaScript extension [107](#)
- Enrole.traceMid object, JavaScript extension [107](#)
- Enrole.traceMin object, JavaScript extension [108](#)
- enRole2ldif.properties, deprecated [178](#)
- enroleAuditing.properties [189](#)
- enRoleAuthentication.properties
 - authentication properties [192](#)
- enRoleDatabase.properties [194](#)
- enRoleEntityHiddenAttributes, do not modify [178](#)
- EnroleExtension, JavaScript extensions [57](#)
- enRoleFonts.properties, not configurable [178](#)
- enRoleHelp.properties, not configurable [178](#)
- enRoleHiddenAttributes.properties, not configurable [178](#)

- enRoleHiddenSearchAttributes.properties, not configurable [178](#)
- enRoleLDAPConnection.properties [197](#)
- enRoleLogging.properties [201](#)
- enRoleMail.properties [214](#)
- enrolepolicies.properties [218](#)
- enroleStartup.properties [223](#)
- enroleStartup.properties, not configurable [178](#)
- enRoleUnchangedAttributes.properties, not configurable [178](#)
- enRoleValidateAttributes.properties, not configurable [178](#)
- enroleworkflow.properties [224](#)
- entitlement parameters [165](#)
- entitlementHiddenAttributes.properties, not configurable [178](#)
- Error object, JavaScript extension [108](#)
- Error.getErrorCode object, JavaScript extension [110](#)
- Error.getMessage object, JavaScript extension [109](#)
- Error.setErrorCode object, JavaScript extension [109](#)
- Error.setMessage object, JavaScript extension [109](#)
- examples
 - mail templates [36](#)
- expressHiddenAttributes.properties, not configurable [178](#)
- ExtendedPerson.getOwnershipType(), JavaScript extension [111](#)
- ExtendedPerson.setOwnershipType(), JavaScript extension [111](#)
- extensions
 - JavaScript
 - AccountModelExtension [58](#)
 - AttributesExtension [56](#)
 - DelegateExtension [57](#)
 - EmailContextExtension [57](#)
 - EnroleExtension [57](#)
 - IdentityPolicyExtension [57](#)
 - LoopCountExtension [58](#)
 - Model [58](#)
 - OrganizationModelExtension [59](#)
 - PersonModelExtension [59](#)
 - PersonPlacementRules Extension [59](#)
 - PostOfficeExtension [60](#)
 - ProvisioningPolicyExtension [60](#)
 - registering [62](#)
 - ReminderExtension [60](#)
 - RoleModelExtension [59](#)
 - ServiceExtension [60](#)
 - ServiceModelExtension [59](#)
 - SubjectExtension [61](#)
 - WorkflowExtension [61](#)
 - migrating
 - constructor [67](#)
 - example [64](#)
 - FESI [64](#)
 - script conversion [66](#)
 - scriptframework.properties [63](#)

F

- FESI
 - fesi.jar [68](#)
 - migrating
 - example [64](#)
- fesi.jar
 - FESI [68](#)

- fesixtensions.properties [62](#), [225](#)
- function differences, FESI and IBM JSEngine
 - JavaScript extensions [64](#)

G

- getRoleName()
 - RoleAssignmentAttribute [148](#)

H

- helpmappings.properties [227](#)
- HighContrastBigFontTheme.properties, not configurable [178](#)
- HighContrastTheme.properties, not configurable [178](#)

I

- ibmSchemaSyntax.properties, not configurable [178](#)
- identity feed information [297](#)
- IdentityPolicy object, JavaScript extension [112](#)
- IdentityPolicy.getNextCount object, JavaScript extension [112](#)
- IdentityPolicy.userIDExists object, JavaScript extension [113](#)
- IdentityPolicyExtension, JavaScript extensions [57](#)
- iplanetSchemaSyntax.properties, not configurable [178](#)
- itiminstaller.properties, not configurable [178](#)

J

- Javascript extension
 - RoleAssignmentAttribute.getName() [147](#)
 - RoleAssignmentAttribute.getRoleDN [148](#)
 - RoleAssignmentObject.getAssignedRoleDN() [150](#)
- JavaScript extension object
 - AccessRequestBatch [158](#)
 - AccessRequestBatch.getAccessDeprovisioningStatusList [161](#)
 - AccessRequestBatch.getAccessProvisioningStatusList [161](#)
 - AccessRequestBatch.getAccessUpdateStatusList [162](#)
 - AccessRequestBatch.getSubmittedAccessDeprovisioningList [160](#)
 - AccessRequestBatch.getSubmittedAccessProvisioningList [159](#)
 - AccessRequestBatch.getSubmittedAccessUpdateList [160](#)
 - account [71](#)
 - AccountSearch [73](#)
 - AccountSearch.searchByUid [74](#)
 - AccountSearch.searchByURI [75](#)
 - activity [75](#)
 - Activity.auditEvent [77](#)
 - Activity.description [77](#)
 - Activity.duedate [77](#)
 - Activity.getSubProcesses() [78](#)
 - Activity.guid [78](#)
 - Activity.id [78](#)
 - Activity.index [79](#)
 - Activity.name [79](#)
 - Activity.participant [79](#)
 - Activity.resultDetail [79](#)
 - Activity.resultSummary [80](#)
 - Activity.setResult [80](#)
 - Activity.started [80](#)

JavaScript extension (*continued*)object (*continued*)

[Activity.state](#) [81](#)
[Activity.subtype](#) [81](#)
[Activity.type](#) [81](#)
[AttributeChangeOperation](#) [82](#)
[AttributeChangeOperation.attr](#) [82](#)
[AttributeChangeOperation.op](#) [82](#)
[ContainerSearch](#) [83](#)
[ContainerSearch.searchByFilter](#) [83](#)
[ContainerSearch.searchByURI](#) [84](#)
[Context](#) [84](#)
[Context.getAccountParameter](#) [86](#)
[Context.getActivityResult](#) [86](#)
[Context.getActivityResultById](#) [86](#)
[Context.getLoopCount](#) [87](#)
[Context.getLoopCountById](#) [87](#)
[Context.getProcessType](#) [87](#)
[Context.getRequestee](#) [88](#)
[Context.getService](#) [88](#)
[Credential.getCheckoutDuration\(\)](#) [90](#)
[Credential.getNotificationRecipient\(\)](#) [90](#)
[Credential.getNotifyOption\(\)](#) [90](#)
[Credential.isCheckoutSearchEnable\(\)](#) [91](#)
[Credential.isNotifyOnly\(\)](#) [91](#)
[Credential.isPasswordViewable\(\)](#) [91](#)
[Credential.isResetPasswordAtCheckin\(\)](#) [92](#)
[DirectoryObject](#) [93](#)
[DirectoryObject.getPropertyNames](#) [97](#)
[DirectoryObject.addProperty](#) [94](#)
[DirectoryObject.dn](#) [94](#)
[DirectoryObject.getChanges](#) [95](#)
[DirectoryObject.getProperty](#) [95](#)
[DirectoryObject.name](#) [97](#)
[DirectoryObject.profileName](#) [97](#)
[EmailContext](#) [99](#)
[Enrole](#) [101](#)
[Enrole.generatePassword](#) [102](#)
[Enrole.getAttributeValue](#) [103](#)
[Enrole.getAttributeValues](#) [103](#)
[Enrole.localize](#) [103](#)
[Enrole.log](#) [104](#)
[Enrole.logError](#) [104](#)
[Enrole.loginfo](#) [105](#)
[Enrole.logWarning](#) [105](#)
[Enrole.toGeneralizedTime](#) [106](#)
[Enrole.toMilliseconds](#) [106](#)
[Enrole.traceMax](#) [107](#)
[Enrole.traceMid](#) [107](#)
[Enrole.traceMin](#) [108](#)
[Error](#) [108](#)
[Error.getErrorCode](#) [110](#)
[Error.getMessage](#) [109](#)
[Error.setErrorCode](#) [109](#)
[Error.setMessage](#) [109](#)
[ExtendedPerson.getOwnershipType\(\)](#) [111](#)
[ExtendedPerson.setOwnershipType\(\)](#) [111](#)
[IdentityPolicy](#) [112](#)
[IdentityPolicy.getNextCount](#) [112](#)
[IdentityPolicy.userIDExists](#) [113](#)
[PackagedApprovalDocument](#) [113](#)
[PackagedApprovalItem](#) [115](#)
[Participant](#) [116](#)
[Participant.implementation](#) [117](#)

JavaScript extension (*continued*)object (*continued*)

[Participant.name](#) [117](#)
[Participant.type](#) [117](#)
[ParticipantType](#) [118](#)
[Person](#) [119](#)
[Person.getAllAssignmentAttributes\(\)](#) [121](#)
[Person.getAndDecryptPersonPassword\(\)](#) [122](#)
[Person.getAndDecryptSynchPassword\(\)](#) [121](#)
[Person.getNewRoles](#) [124](#)
[Person.getRemovedRoles](#) [124, 125](#)
[Person.getRoleAssignmentData](#) [123](#)
[Person.getRoleAssignmentData\(\)](#) [122](#)
[Person.getRoles](#) [123](#)
[Person.isInRole](#) [125](#)
[Person.removeRole](#) [126](#)
[Person.removeRoleAssignmentData\(\)](#) [126](#)
[Person.updateRoleAssignmentData\(\)](#) [127](#)
[PersonSearch](#) [127](#)
[PersonSearch.searchByFilter](#) [128](#)
[PersonSearch.searchByURI](#) [128](#)
[PostOffice](#) [129](#)
[PostOffice.getAllEmailMessages\(\)](#) [129](#)
[PostOffice.getEmailAddress](#) [130](#)
[PostOffice.getPersonByEmailAddress](#) [130](#)
[PostOffice.getTopic](#) [130](#)
[Process](#) [130](#)
[Process.auditEvent](#) [132](#)
[Process.comment](#) [132](#)
[Process.description](#) [133](#)
[Process.getActivity](#) [133](#)
[Process.getParent](#) [133](#)
[Process.getRootProcess\(\)](#) [134](#)
[Process.getRootRequesterName\(\)](#) [134](#)
[Process.getSubProcesses\(\)](#) [135](#)
[Process.guid](#) [134](#)
[Process.id](#) [135](#)
[Process.name](#) [135](#)
[Process.parentId](#) [136](#)
[Process.requesteeDN](#) [136](#)
[Process.requesteeName](#) [136](#)
[Process.requestorDN](#) [136](#)
[Process.requestorId](#) [137](#)
[Process.requestorName](#) [137](#)
[Process.requestorType](#) [137](#)
[Process.resultDetail](#) [138](#)
[Process.resultSummary](#) [138](#)
[Process.setRequesteeData](#) [138](#)
[Process.setResult](#) [139](#)
[Process.setSubjectData](#) [139](#)
[Process.started](#) [139](#)
[Process.state](#) [140](#)
[Process.subject](#) [140](#)
[Process.type](#) [140](#)
[ProcessData](#) [141](#)
[ProcessData.get](#) [141](#)
[ProcessData.set](#) [141](#)
[RecertificationWorkflow](#) [142](#)
[Reminder](#) [142](#)
[Role](#) [143](#)
[Role.getAscendantRoles](#) [144](#)
[Role.getAssignmentAttributes](#) [144](#)
[Role.getChildRoles](#) [145](#)
[Role.getDecendantRoles](#) [145](#)

JavaScript extension (*continued*)

object (*continued*)

- Role.getOwner [146](#)
- Role.getParentRoles [146](#)
- Role.setAssignmentAttributes [147](#)
- RoleSearch [153](#)
- RoleSearch.searchByName [153](#)
- RoleSearch.searchByURI [154](#)
- service [155](#)
- ServiceSearch [155](#)
- useraccess [158](#)

objects [69](#)

- RoleAssignment.addProperty object [150](#)
- RoleAssignmentAttribute [147](#)
- RoleAssignmentObject.getChanges() [151](#)
- RoleAssignmentObject.getDefinedRoleDN() [150](#)
- RoleAssignmentObject.getProperty object [152](#)
- RoleAssignmentObject.getPropertyNames object [152](#)
- RoleAssignmentObject.removeProperty object [152](#)
- RoleAssignmentObject.setProperty object [153](#)
- SeparationOfDutyRuleViolation object [154](#)
- ServiceSearch.searchByFilter object [156](#)
- ServiceSearch.searchByName object [156](#)
- ServiceSearch.searchByURI object [157](#)
- ServiceSearch.searchForClosestToPerson object [157](#)

JavaScript extensions

- AttributesExtension [56](#)
- DelegateExtension [57](#)
- EmailContextExtension [57](#)
- EnroleExtension [57](#)
- fesixtensions.properties [62](#)
- function differences, FESI and IBM JSEngine [64](#)
- IdentityPolicyExtension [57](#)
- LoopCountExtension [58](#)
- migrating
 - FESI [64](#)
- Model
 - AccountModelExtension [58](#)
 - OrganizationModelExtension [59](#)
 - PersonModelExtension [59](#)
 - RoleModelExtension [59](#)
 - ServiceModelExtension [59](#)
- overview [55](#)
- packaged extensions [56](#)
- PersonPlacementRulesExtension [59](#)
- PostOfficeExtension [60](#)
- ProvisioningPolicyExtension [60](#)
- registering [62](#)
- ReminderExtension [60](#)
- scriptframework.properties [62](#), [63](#)
- ServiceExtension [60](#)
- SubjectExtension [61](#)
- WorkflowExtension [61](#)

JavaScript functions [165](#)

JavaScript objects

- relevant data [61](#)
- service selection policy [169](#)

L

- Labels.properties, not configurable [178](#)
- LDAP connection pool information [270](#)
- LDAP server information [264](#)
- life cycle rule [292](#)

Log4j [201](#)

LoopCountExtension, JavaScript extensions [58](#)

M

mail services configuration [272](#)

mail templates

- examples [36](#)

manual service

- default notification templates [36](#)

Messages.properties, not configurable [178](#)

messaging information [273](#)

methods

- RoleAssignmentObject [149](#)

migrating

- JavaScript
 - constructor example [67](#)
 - FESI [64](#)
 - FESI example [64](#)
 - script example [66](#)

Model, JavaScript extensions [58](#)

modifiable property files

- property files [175](#)

N

null types [165](#)

O

object

- Context.isAccountDataChanged object, JavaScript extension [88](#)
- delegate JavaScript extension [92](#)
- DirectoryObject.getPropertyAsDate [96](#)
- DirectoryObject.getPropertyAsString [96](#)
- DirectoryObject.removeProperty , JavaScript extension [98](#)
- DirectoryObject.removeProperty(name,value) , JavaScript extension [98](#)
- DirectoryObject.setProperty object, JavaScript extension [99](#)
- JavaScript extension
 - AccessRequestBatch [158](#)
 - AccessRequestBatch.getAccessdeProvisioningStatusList [161](#)
 - AccessRequestBatch.getAccessProvisioningStatusList [161](#)
 - AccessRequestBatch.getAccessUpdateStatusList [162](#)
 - AccessRequestBatch.getSubmittedAccessDeprovisioningList [160](#)
 - AccessRequestBatch.getSubmittedAccessProvisioningList [159](#)
 - AccessRequestBatch.getSubmittedAccessUpdateList [160](#)
- account [71](#)
- AccountSearch [73](#)
- AccountSearch.searchByUid [74](#)
- AccountSearch.searchByURI [75](#)
- activity [75](#)
- Activity.auditEvent [77](#)
- Activity.description [77](#)
- Activity.duedate [77](#)
- Activity.getSubProcesses() [78](#)
- Activity.guid [78](#)
- Activity.id [78](#)
- Activity.index [79](#)
- Activity.name [79](#)

object (continued)

JavaScript extension (continued)

[Activity.participant](#) 79
[Activity.resultDetail](#) 79
[Activity.resultSummary](#) 80
[Activity.setResult](#) 80
[Activity.started](#) 80
[Activity.state](#) 81
[Activity.subtype](#) 81
[Activity.type](#) 81
[AttributeChangeOperation](#) 82
[AttributeChangeOperation.attr](#) 82
[AttributeChangeOperation.op](#) 82
[ContainerSearch](#) 83
[ContainerSearch.searchByFilter](#) 83
[ContainerSearch.searchByURI](#) 84
[Context](#) 84
[Context.getAccountParameter](#) 86
[Context.getActivityResult](#) 86
[Context.getActivityResultById](#) 86
[Context.getLoopCount](#) 87
[Context.getLoopCountById](#) 87
[Context.getProcessType](#) 87
[Context.getRequestee](#) 88
[Context.getService](#) 88
[Credential.getCheckoutDuration\(\)](#) 90
[Credential.getNotificationRecipient\(\)](#) 90
[Credential.getNotifyOption\(\)](#) 90
[Credential.isCheckoutSearchEnable\(\)](#) 91
[Credential.isNotifyOnly\(\)](#) 91
[Credential.isPasswordViewable\(\)](#) 91
[Credential.isResetPasswordAtCheckin\(\)](#) 92
[DirectoryObject](#) 93
[DirectoryObject.getPropertyNames](#) 97
[DirectoryObject.addProperty](#) 94
[DirectoryObject.dn](#) 94
[DirectoryObject.getChanges](#) 95
[DirectoryObject.getProperty](#) 95
[DirectoryObject.name](#) 97
[DirectoryObject.profileName](#) 97
[EmailContext](#) 99
[Enrole](#) 101
[Enrole.generatePassword](#) 102
[Enrole.getAttributeValue](#) 103
[Enrole.getAttributeValues](#) 103
[Enrole.localize](#) 103
[Enrole.log](#) 104
[Enrole.logError](#) 104
[Enrole.loginInfo](#) 105
[Enrole.logWarning](#) 105
[Enrole.toGeneralizedTime](#) 106
[Enrole.toMilliseconds](#) 106
[Enrole.traceMax](#) 107
[Enrole.traceMid](#) 107
[Enrole.traceMin](#) 108
[Error](#) 108
[Error.getErrorCode](#) 110
[Error.getMessage](#) 109
[Error.setErrorCode](#) 109
[Error.setMessage](#) 109
[ExtendedPerson.getOwnershipType\(\)](#) 111
[ExtendedPerson.setOwnershipType\(\)](#) 111
[IdentityPolicy](#) 112
[IdentityPolicy.getNextCount](#) 112

object (continued)

JavaScript extension (continued)

[IdentityPolicy.userIDExists](#) 113
[Oerson.isInRole](#) 125
[PackagedApprovalDocument](#) 113
[PackagedApprovalItem](#) 115
[Participant](#) 116
[Participant.implementation](#) 117
[Participant.name](#) 117
[Participant.type](#) 117
[ParticipantType](#) 118
[Person](#) 119
[Person.getAllAssignmentAttributes\(\)](#) 121
[Person.getAndDecryptPersonPassword\(\)](#) 122
[Person.getAndDecryptSynchPassword\(\)](#) 121
[Person.getNewRoles](#) 124
[Person.getRemovedRoles](#) 124, 125
[Person.getRoleAssignmentData](#) 123
[Person.getRoleAssignmentData\(\)](#) 122
[Person.getRoles](#) 123
[Person.removeRole](#) 126
[Person.removeRoleAssignmentData\(\)](#) 126
[Person.updateRoleAssignmentData\(\)](#) 127
[PersonSearch](#) 127
[PersonSearch.searchByFilter](#) 128
[PersonSearch.searchByURI](#) 128
[PostOffice](#) 129
[PostOffice.getAllEmailMessages\(\)](#) 129
[PostOffice.getEmailAddress](#) 130
[PostOffice.getPersonByEmailAddress](#) 130
[PostOffice.getTopic](#) 130
[Process](#) 130
[Process.auditEvent](#) 132
[Process.comment](#) 132
[Process.description](#) 133
[Process.getActivity](#) 133
[Process.getParent](#) 133
[Process.getRootProcess\(\)](#) 134
[Process.getRootRequesterName\(\)](#) 134
[Process.getSubProcesses\(\)](#) 135
[Process.guid](#) 134
[Process.id](#) 135
[Process.name](#) 135
[Process.parentId](#) 136
[Process.requesteeDN](#) 136
[Process.requesteeName](#) 136
[Process.requestorDN](#) 136
[Process.requestorId](#) 137
[Process.requestorName](#) 137
[Process.requestorType](#) 137
[Process.resultDetail](#) 138
[Process.resultSummary](#) 138
[Process.setRequesteeData](#) 138
[Process.setResult](#) 139
[Process.setSubjectData](#) 139
[Process.started](#) 139
[Process.state](#) 140
[Process.subject](#) 140
[Process.type](#) 140
[ProcessData](#) 141
[ProcessData.get](#) 141
[ProcessData.set](#) 141
[RecertificationWorkflow](#) 142
[Reminder](#) 142

object (*continued*)

JavaScript extension (*continued*)

- Role [143](#)
- Role.getAscendantRoles [144](#)
- Role.getAssignmentAttributes [144](#)
- Role.getChildRoles [145](#)
- Role.getDecendantRoles [145](#)
- Role.getOwner [146](#)
- Role.getParentRoles [146](#)
- Role.setAssignmentAttributes [147](#)
- RoleSearch [153](#)
- RoleSearch.searchByName [153](#)
- RoleSearch.searchByURI [154](#)
- service [155](#)
- ServiceSearch [155](#)
- useraccess [158](#)

Objects

- AccountSearch.searchByUidAndService object
JavaScript extension [74](#)

OrganizationModelExtension, JavaScript extensions [59](#)
overview

- JavaScript extensions [55](#)

P

packaged extensions

- JavaScript extensions [56](#)

PackagedApprovalDocument, JavaScript extension [113](#)

PackagedApprovalItem, JavaScript extension [115](#)

Participant object, JavaScript extension [116](#)

Participant.implementation object, JavaScript extension [117](#)

Participant.name object, JavaScript extension [117](#)

Participant.type object, JavaScript extension [117](#)

ParticipantType object, JavaScript extension [118](#)

password policy

- dictionary [13](#)

password transaction monitor settings [277](#)

passwordrules.properties, not configurable [178](#)

Person object, JavaScript extension [119](#)

person profile [268](#)

Person.getAllAssignmentAttributes(), JavaScript extension [121](#), [122](#)

Person.getAndDecryptPersonPassword(), JavaScript extension [122](#)

Person.getAndDecryptSynchPassword(), JavaScript extension [121](#)

Person.getNewRoles object, JavaScript extension [124](#)

Person.getRemovedRoles object, JavaScript extension [124](#), [125](#)

Person.getRoleAssignmentData, JavaScript extension [123](#)

Person.getRoles object, JavaScript extension [123](#)

Person.isInRole object, JavaScript extension [125](#)

Person.removeRoleAssignmentData(), JavaScript extension [126](#)

Person.removeRoles object, JavaScript extension [126](#)

Person.updateRoleAssignmentData(), JavaScript extension [127](#)

PersonModelExtension, JavaScript extensions [59](#)

PersonPlacementRulesExtension, JavaScript extensions [59](#)

PersonSearch object, JavaScript extension [127](#)

PersonSearch.searchByFilter object, JavaScript extension [128](#)

PersonSearch.searchByURI object, JavaScript extension [128](#)

platformcontext.properties, not configurable [178](#)

post office information [294](#)

PostOffice object, JavaScript extension [129](#)

PostOffice.getAllEmailMessages(), JavaScript extension [129](#)
PostOffice.getEmailAddress object, JavaScript extension [130](#)

PostOffice.getPersonByEmailAddress object, JavaScript extension [130](#)

PostOffice.getTopic object, JavaScript extension [130](#)

PostOfficeExtension, JavaScript extensions [60](#)

Process object, JavaScript extension [130](#)

Process.auditEvent object, JavaScript extension [132](#)

Process.comment object, JavaScript extension [132](#)

Process.description object, JavaScript extension [133](#)

Process.getActivity object, JavaScript extension [133](#)

Process.getParent object, JavaScript extension [133](#)

Process.getRootProcess(), JavaScript extension [134](#)

Process.getRootRequesterName(), JavaScript extension [134](#)

Process.getSubProcesses(), JavaScript extension [135](#)

Process.guid object, JavaScript extension [134](#)

Process.id object, JavaScript extension [135](#)

Process.name object, JavaScript extension [135](#)

Process.parentId object, JavaScript extension [136](#)

Process.requesteeDN object, JavaScript extension [136](#)

Process.requesteeName object, JavaScript extension [136](#)

Process.requestorDN object, JavaScript extension [136](#)

Process.requestorId object, JavaScript extension [137](#)

Process.requestorName object, JavaScript extension [137](#)

Process.requestorType object, JavaScript extension [137](#)

Process.resultDetail object, JavaScript extension [138](#)

Process.resultSummary object, JavaScript extension [138](#)

Process.setRequesteeData object, JavaScript extension [138](#)

Process.setResult object, JavaScript extension [139](#)

Process.setSubjectData object, JavaScript extension [139](#)

Process.started object, JavaScript extension [139](#)

Process.state object, JavaScript extension [140](#)

Process.subject object, JavaScript extension [140](#)

Process.type object, JavaScript extension [140](#)

ProcessData object, JavaScript extension [141](#)

ProcessData.get object, JavaScript extension [141](#)

ProcessData.set object, JavaScript extension [141](#)

product name [278](#)

properties files

- additional, not configurable [178](#)

- adhocreporting.properties [180](#)

- DataBaseFunctions.conf [188](#)

- enroleAuditing.properties [189](#)

- enRoleDatabase.properties [194](#)

- enRoleLDAPConnection.properties [197](#)

- enRoleLogging.properties [201](#)

- enRoleMail.properties [214](#)

- enrolepolicies.properties [218](#)

- enroleStartup.properties [223](#)

- enroleworkflow.properties [224](#)

- fesieextensions.properties [225](#)

- helpmappings.properties [227](#)

- reportingLabels.properties [228](#)

- reporttabledeny.properties [228](#)

- rest.properties [229](#)

- scriptframework.properties [231](#)

- SelfServiceHelp.properties [233](#)

- SelfServiceHomePage [233](#)

- SelfServiceScreenText [234](#)

- SelfServiceUI.properties [234](#)

- supplemental properties [175](#)

- properties files (*continued*)
 - system properties [175](#)
 - ui.properties [237](#)
- Properties.properties, not configurable [178](#)
- property files
 - modifiable property files [175](#)
- provisioning policies
 - constant [165](#)
 - JavaScript [165](#)
 - null types [165](#)
 - parameter
 - scenarios [163](#)
 - parameters [165](#)
 - regular expressions [168](#)
- provisioning policy
 - group [4](#)
- ProvisioningPolicyExtension, JavaScript extensions [60](#)

R

- recertification default messages
 - default recertification templates [38](#)
- RecertificationWorkflow object, JavaScript extension [142](#)
- reconciliation information [278](#)
- registering application extensions [2](#)
- registering, JavaScript extensions [62](#)
- regular expressions [168](#)
- relevant data JavaScript objects [61](#)
- Reminder object, JavaScript extension [142](#)
- ReminderExtension, JavaScript extensions [60](#)
- reportingLabels.properties [228](#)
- reporttabledeny.properties [228](#)
- required fields
 - configuring [300](#)
- rest.properties [229](#)
- reverse password synchronization [293](#)
- Role object, JavaScript extension [143](#)
- Role.getAscendantRoles object, JavaScript extension [144](#)
- Role.getAssignmentAttributes object, JavaScript extension [144](#)
- Role.getChildRoles object, JavaScript extension [145](#)
- Role.getDecendantRoles object, JavaScript extension [145](#)
- Role.getOwner object, JavaScript extension [146](#)
- Role.getParentRoles object, JavaScript extension [146](#)
- Role.setAssignmentAttributes object, JavaScript extension [147](#)
- RoleAssignment.addProperty object
 - JavaScript extension [150](#)
- RoleAssignmentAttribute
 - getRoleName() [148](#)
- RoleAssignmentAttribute object, JavaScript extension [147](#)
- RoleAssignmentAttribute.getName()
 - JavaScript extension [147](#)
- RoleAssignmentAttribute.getRoleDN
 - JavaScript extension [148](#)
- RoleAssignmentObject
 - methods [149](#)
- RoleAssignmentObject.getAssignedRoleDN()
 - JavaScript extension [150](#)
- RoleAssignmentObject.getChanges()
 - JavaScript extension [151](#)
- RoleAssignmentObject.getDefinedRoleDN()
 - JavaScript extension [150](#)
- RoleAssignmentObject.getProperty object

- RoleAssignmentObject.getProperty object (*continued*)
 - JavaScript extension [152](#)
- RoleAssignmentObject.getPropertyNames object
 - JavaScript extension [152](#)
- RoleAssignmentObject.removeProperty object
 - JavaScript extension [152](#)
- RoleAssignmentObject.setProperty object
 - JavaScript extension [153](#)
- RoleModelExtension, JavaScript extensions [59](#)
- RoleSearch object, JavaScript extension [153](#)
- RoleSearch.searchByName object, JavaScript extension [153](#)
- RoleSearch.searchByURI object, JavaScript extension [154](#)

S

- scheduling information [282](#)
- script
 - service selection policy [169](#)
- scriptframework.properties
 - JavaScript
 - configuring [63](#)
- search strategy and LDAP control configuration [265](#)
- SelfServiceHelp.properties [233](#)
- SelfServiceHomePage.properties [233](#)
- SelfServiceScreenText.properties [234](#)
- SelfServiceUI.properties [234](#)
- SeparationOfDutyRuleViolation object
 - JavaScript extension [154](#)
- service
 - service selection policy Javascript [169](#)
- service object, JavaScript extension [155](#)
- service selection policy
 - JavaScript objects [169](#)
 - script [169](#)
- ServiceExtension, JavaScript extensions [60](#)
- ServiceModelExtension, JavaScript extensions [59](#)
- ServiceSearch object, JavaScript extension [155](#)
- ServiceSearch.searchByFilter object
 - JavaScript extension [156](#)
- ServiceSearch.searchByName object
 - JavaScript extension [156](#)
- ServiceSearch.searchByURI object
 - JavaScript extension [157](#)
- ServiceSearch.searchForClosestToPerson object
 - JavaScript extension [157](#)
- shared access module
 - credential [89](#)
- shared secret hashing [283](#)
- SubForm control type
 - contextual parameters [171](#)
 - parameter names [172](#)
 - writing [173](#)
- subform.properties, not configurable [178](#)
- SubjectExtension, JavaScript extensions [61](#)
- supplemental properties
 - additional, not configurable
 - ConfigLabels.properties [178](#)
 - CustomForms.properties [178](#)
 - Dsml2RootDSE.properties [178](#)
 - Dsml2Schema.properties [178](#)
 - enRole2ldif.properties [178](#)
 - enRoleFonts.properties [178](#)
 - enRoleHelp.properties [178](#)
 - itiminstaller.properties [178](#)

- supplemental properties (*continued*)
 - additional, not configurable (*continued*)
 - Labels.properties [178](#)
 - Messages.properties [178](#)
 - passwordrules.properties [178](#)
 - platformcontext.properties [178](#)
 - Properties.properties [178](#)
 - subform.properties [178](#)
 - tenant.properties [178](#)
 - tmsMessages.properties [178](#)
 - adhocreporting.properties [180](#)
 - CustomLabels.properties [187](#)
 - DataBaseFunctions.conf [188](#)
 - enroleAuditing.properties [189](#)
 - enRoleDatabase.properties [194](#)
 - enRoleLDAPConnection. properties [197](#)
 - enRoleLogging.properties [201](#)
 - enRoleMail.properties [214](#)
 - enrolepolicies.properties [218](#)
 - enroleStartup.properties [223](#)
 - enroleworkflow.properties [224](#)
 - fesiextensions.properties [225](#)
 - helpmappings.properties [227](#)
 - properties files [175](#)
 - reportingLabels.properties [228](#)
 - reporttabledeny.properties [228](#)
 - rest.properties [229](#)
 - scriptframework.properties [231](#)
 - SelfServiceHelp.properties [233](#)
 - SelfServiceHomePage [233](#)
 - SelfServiceScreenText [234](#)
 - SelfServiceUI.properties [234](#)
 - ui.properties [237](#)
- system configuration program [284](#)
- system properties
 - access catalog properties files [296](#)
 - application client request configuration [293](#)
 - application server information [261](#)
 - cache information [269](#)
 - challenge response encoding information [285](#)
 - create password checkbox [296](#)
 - database cleanup [296](#)
 - database resource bundle [295](#)
 - encryption information [275](#)
 - enRole.properties file [255](#)
 - identity feed [297](#)
 - LDAP connection pool information [270](#)
 - LDAP server information [264](#)
 - life cycle rule [292](#)
 - mail services configuration [272](#)
 - messaging information [273](#)
 - organization name [263](#)
 - password synchronization [299](#)
 - password transaction monitor settings [277](#)
 - person profile [268](#)
 - post office [294](#)
 - product name [278](#)
 - properties files [175](#)
 - reconciliation information [278](#)
 - remote services properties files [259](#)
 - required fields [300](#)
 - reverse password synchronization [293](#)
 - scheduling information [282](#)
 - search strategy and LDAP control configuration [265](#)

- system properties (*continued*)
 - shared secret hashing [283](#)
 - system configuration program [284](#)
 - tenant information, default [263](#)
 - understanding properties files [255](#)
 - upgrade [298](#)
 - web services properties files [260](#)
 - WebSphere-specific configuration [255](#)
 - workflow configuration information [285](#)
 - XML and DTD information [285](#)

T

- tenant information, default [263](#)
- tenant.properties, not configurable [178](#)
- tmsMessages.properties, not configurable [178](#)
- TungstenTheme.properties, not configurable [178](#)

U

- ui.properties [237](#)
- UIConfig.properties
 - descriptions [247](#)
 - properties [247](#)
- upgrade information [298](#)
- useraccess object, JavaScript extension [158](#)

W

- WebSphere-specific configuration [255](#)
- workflow
 - application extensions [1](#)
 - workflowApplication interface [1](#)
 - workflow configuration information [285](#)
 - workflow default messages
 - default workflow templates [43](#)
 - workflow extensions
 - intro [19](#)
 - policy enforcement [19](#)
 - recertification [19](#)
 - wait [22](#)
- WorkflowExtension, JavaScript extensions [61](#)
- workflows
 - application extension
 - methods [1](#)
 - registering [2](#)
 - JavaScript objects
 - relevant data [61](#)

X

- XML and DTD information [285](#)

