

Vertica® Analytic Database 5.0

# Getting Started Guide

Copyright© 2006-2011 Vertica, An HP Company

Date of Publication: June 20, 2011



CONFIDENTIAL

# Contents

<b>Technical Support</b>	<b>1</b>
--------------------------	----------

---

<b>About the Documentation</b>	<b>2</b>
--------------------------------	----------

---

Where to Find the Vertica Documentation .....	2
Reading the Online Documentation .....	2
Printing Full Books .....	4
Suggested Reading Paths .....	4
Where to Find Additional Information .....	6
Typographical Conventions.....	7

<b>Overview to Getting Started</b>	<b>9</b>
------------------------------------	----------

---

<b>Example Databases</b>	<b>11</b>
--------------------------	-----------

---

ClickStream Example Database.....	13
ClickStream_Fact.....	14
Customer_Dimension.....	15
CreditCard_Dimension.....	15
Date_Dimension.....	15
IPAddress_Dimension .....	16
Page_Dimension .....	16
Session_Dimension .....	17
UserAgent_Dimension.....	17
clickstream_query_01.sql.....	17
clickstream_query_02.sql.....	18
clickstream_query_03.sql.....	18
clickstream_query_04.sql.....	19
clickstream_query_05.sql.....	20
clickstream_query_06.sql.....	20
Credit History Example Database .....	22
CreditHistory_Fact.....	23
AccountType_Dimension.....	23
Customer_Dimension.....	23
Date_Dimension.....	24
Institution_Dimension.....	25
MortgageType_Dimension.....	25
credithistory_query_01.sql.....	25
credithistory_query_02.sql.....	26
credithistory_query_03.sql.....	27
credithistory_query_04.sql.....	27
credithistory_query_05.sql.....	28
credithistory_query_06.sql.....	29
Retail Sales Example Database.....	31
Retail_Sales_Fact.....	32
Date_Dimension.....	32
Product_Dimension .....	33

Promotion_Dimension .....	34
Store_Dimension .....	34
retail_query_01.sql .....	35
retail_query_02.sql .....	36
retail_query_03.sql .....	37
retail_query_04.sql .....	38
retail_query_05.sql .....	39
retail_query_06.sql .....	40
retail_query_07.sql .....	41
retail_query_08.sql .....	42
Stock Exchange Example Database .....	44
StockTransaction_Fact .....	45
Date_Dimension .....	46
Exchange_Dimension .....	47
Settlement_Dimension .....	48
Split_Dimension .....	49
Stock Dimension .....	50
Trader_Dimension .....	51
stock_query_01 .....	51
stock_query_02 .....	51
stock_query_03 .....	52
stock_query_04 .....	53
stock_query_05 .....	54
stock_query_06 .....	55
Telecom Example Database .....	57
Billing_Fact .....	58
Call_Termination_Dimension .....	58
Customer_Details_Dimension .....	59
Date_Dimension .....	59
Equipment_Dimension .....	60
Feature_Dimension .....	60
Numbering_Plan_Dimension .....	60
Rate_Plan_Dimension .....	60
telecom_query_01.sql .....	61
telecom_query_02.sql .....	61
telecom_query_03.sql .....	62
telecom_query_04.sql .....	63
telecom_query_05.sql .....	63
telecom_query_06.sql .....	64
VMart Example Database .....	66
Public Schema .....	67
Store Schema .....	73
Online_Sales Schema .....	76
vmart_query_01.sql .....	78
vmart_query_02.sql .....	78
vmart_query_03.sql .....	79
vmart_query_04.sql .....	80
vmart_query_05.sql .....	80
vmart_query_06.sql .....	81
vmart_query_07.sql .....	82
vmart_query_08.sql .....	82
vmart_query_09.sql .....	83

<b>Installing the Example Database</b>	<b>84</b>
<hr/>	
<b>Tutorial: Setting up an Example Database</b>	<b>87</b>
<hr/>	
Step 1: Set Up the Example Environment.....	88
Step 2: Create the Example Database.....	89
Step 3: Define the Database Schema.....	91
Step 4: Load the Data.....	92
Step 5: Create a Comprehensive Design.....	93
Step 6: Connect to the Database and Run a Simple Query.....	100
Step 7: Test the Optimized Design.....	100
Step 8: (Optional) Generate Custom Data Files.....	102
<hr/>	
<b>Running Simple Queries</b>	<b>104</b>
<hr/>	
<b>Cleanup Procedure</b>	<b>105</b>
<hr/>	
<b>Using the Graphical User Interface</b>	<b>106</b>
<hr/>	
<b>Notes for Remote Terminal Users</b>	<b>107</b>
<hr/>	
<b>Index</b>	<b>109</b>
<hr/>	
<b>Copyright Notice</b>	<b>111</b>
<hr/>	

# Technical Support

---

To submit problem reports, questions, comments, and suggestions, use the Technical Support page on the Vertica Web site.

---

## Notes:

- You must be a registered user in order to access the ***MyVertica Portal*** ***<http://myvertica.vertica.com/v-zone/overview>***.
  - If you are not a registered user, you can request access at the ***Technical Support Web page*** ***<http://www.vertica.com/support>***.
- 

Before you report a problem, run the Diagnostics Utility described in the Troubleshooting Guide and attach the resulting `.zip` file to your ticket.

# About the Documentation

---

This section describes how to access and print Vertica documentation. It also includes *suggested reading paths* (page 4).

## Where to Find the Vertica Documentation

You can read or download the Vertica documentation for the current release of Vertica® Analytic Database from the *Product Documentation Page* [http://www.vertica.com/v-zone/product\\_documentation](http://www.vertica.com/v-zone/product_documentation). You must be a registered user to access this page.

The documentation is available as a compressed tarball (.tar) or a zip archive (.zip) file. When you extract the file on the database server system or locally on the client, contents are placed in a /vertica50\_doc/ directory.

---

### Notes:

- The documentation on the Vertica Web site is updated each time a new release is issued.
  - A more recent version of the product documentation might be available online. To check for critical product or document information added after the product release, see the Vertica Product Documentation downloads site. You can download the PDF version or browse books online
  - If you are using an older version of the software, refer to the documentation on your database server or client systems.
- 

See Installing Vertica Documentation in the Installation Guide.

## Reading the Online Documentation

### Reading the HTML documentation files

The Vertica documentation files are provided in HTML browser format for platform independence. The HTML files require only a browser that displays frames properly with JavaScript enabled. The HTML files do not require a Web (HTTP) server.

The Vertica documentation is supported on the following browsers:

- Mozilla FireFox
- Internet Explorer
- Apple Safari
- Opera
- Google Chrome (server-side installations only)

The instructions that follow assume you have installed the documentation on a client or server machine.

### Mozilla Firefox

- 1 Open a browser window.
- 2 Choose one of the following methods to access the documentation:
  - Select **File > Open File**, navigate to `..\HTML-WEBHELP\index.htm`, and click **Open**.
  - OR drag and drop `index.htm` into a browser window.
  - OR press **CTRL+O**, navigate to `index.htm`, and click **Open**.

### Internet Explorer

Use one of the following methods:

- 1 Open a browser window.
- 2 Choose one of the following methods to access the documentation:
  - Select **File > Open > Browse**, navigate to `..\HTML-WEBHELP\index.htm`, click **Open**, and click **OK**.
  - OR drag and drop `index.htm` into the browser window.
  - OR press **CTRL+O**, Browse to the file, click **Open**, and click **OK**.

**Note:** If a message warns you that Internet Explorer has restricted the web page from running scripts or ActiveX controls, right-click anywhere within the message and select **Allow Blocked Content**.

### Apple Safari

- 1 Open a browser window.
- 2 Choose one of the following methods to access the documentation:
  - Select **File > Open File**, navigate to `..\HTML-WEBHELP\index.htm`, and click **Open**.
  - OR drag and drop `index.htm` into the browser window.
  - OR press **CTRL+O**, navigate to `index.htm`, and click **Open**.

### Opera

- 1 Open a browser window.
- 2 Position your cursor in the title bar and right click > **Customize > Appearance**, click the **Toolbar** tab and select **Main Bar**.
- 3 Choose one of the following methods to access the documentation:
  - Open a browser window and click **Open**, navigate to `..\HTML-WEBHELP\index.htm`, and click **Open**.
  - OR drag and drop `index.htm` into the browser window.
  - OR press **CTRL+O**, navigate to `index.htm`, and click **Open**.

### Google Chrome

Google does not support access to client-side installations of the documentation. You'll have to point to the documentation installed on a server system.

- 1 Open a browser window.
- 2 Choose one of the following methods to access the documentation:
  - In the address bar, type the location of the `index.htm` file on the server. For example:  
<file://<servername>//vertica50 doc//HTML/Master/index.htm>
  - OR drag and drop `index.htm` into the browser window.
  - OR press **CTRL+O**, navigate to `index.htm`, and click **Open**.

## Notes

The `.tar` or `.zip` file you download contains a complete documentation set.

The documentation page of the **Downloads Web site** [http://www.vertica.com/v-zone/download\\_vertica](http://www.vertica.com/v-zone/download_vertica) is updated as new versions of Vertica are released. When the version you download is no longer the most recent release, refer only to the documentation included in your RPM.

The Vertica documentation contains links to Web sites of other companies or organizations that Vertica does not own or control. If you find broken links, please let us know.

Report any script, image rendering, or text formatting problems to **Technical Support** (on page 1).

## Printing Full Books

Vertica also publishes books as Adobe Acrobat™ PDF. The books are designed to be printed on standard 8½ x 11 paper using full duplex (two-sided) printing.

**Note:** Vertica manuals are topic driven and not meant to be read in a linear fashion. Therefore, the PDFs do not resemble the format of typical books.

Open and print the PDF documents using Acrobat Acrobat Reader. You can download the latest version of the free Reader from the **Adobe Web site** (<http://www.adobe.com/products/acrobat/readstep2.html>).

The following list provides links to the PDFs.

- Concepts Guide
- Installation Guide
- Getting Started Guide
- Administrator's Guide
- Programmer's Guide
- SQL Reference Manual
- Troubleshooting Guide

## Suggested Reading Paths

This section provides a suggested reading path for various users. Vertica recommends that you read the manuals listed under All Users first.

## **All Users**

- **New Features** — Release-specific information, including new features and behavior changes to the product and documentation
- **Concepts Guide** — Basic concepts critical to understanding Vertica
- **Getting Started Guide** — A tutorial that takes you through the process of configuring a Vertica database and running example queries
- **Troubleshooting Guide** — General troubleshooting information

## **System Administrators**

- **New Features** — Release-specific information, including new features and behavior changes to the product and documentation
- **Installation Guide** — Platform configuration and software installation

## **Database Administrators**

- **Installation Guide** — Platform configuration and software installation
- **Administrator's Guide** — Database configuration, loading, security, and maintenance

## **Application Developers**

- **Programmer's Guide** — Connecting to a database, queries, transactions, and so on
- **SQL Reference Manual** — SQL and Vertica-specific language information

## Where to Find Additional Information

Visit the *Vertica Web site* (<http://www.vertica.com>) to keep up to date with:

- Downloads
- Frequently Asked Questions (FAQs)
- Discussion forums
- News, tips, and techniques
- Training

## Typographical Conventions

The following are the typographical and syntax conventions used in the Vertica documentation.

Typographical Convention	Description
<b>Bold</b>	Indicates areas of emphasis, such as a special menu command.
<b>Button</b>	Indicates the word is a button on the window or screen.
Code	SQL and program code displays in a monospaced (fixed-width) font.
Database objects	Names of database objects, such as tables, are shown in san-serif type.
<i>Emphasis</i>	Indicates emphasis and the titles of other documents or system files.
monospace	Indicates literal interactive or programmatic input/output.
<i>monospace italics</i>	Indicates user-supplied information in interactive or programmatic input/output.
UPPERCASE	Indicates the name of a SQL command or keyword. SQL keywords are case insensitive; <code>SELECT</code> is the same as <code>Select</code> , which is the same as <code>select</code> .
<b>User input</b>	Text entered by the user is shown in bold san serif type.
↵	indicates the Return/Enter key; implicit on all user input that includes text
Right-angle bracket >	Indicates a flow of events, usually from a drop-down menu.
Click	Indicates that the reader clicks options, such as menu command buttons, radio buttons, and mouse selections; for example, "Click OK to proceed."
Press	Indicates that the reader perform some action on the keyboard; for example, "Press Enter."
Syntax Convention	Description
Text without brackets/braces	Indicates content you type as shown.
< <i>Text inside angle brackets</i> >	Placeholder for which you must supply a value. The variable is usually shown in italics. See Placeholders below.
[ Text inside brackets ]	Indicates optional items; for example, <code>CREATE TABLE [schema_name.]table_name</code> The brackets indicate that the <code>schema_name</code> is optional. Do not type the square brackets.
{ Text inside braces }	Indicates a set of options from which you choose one; for example: <code>QUOTES { ON   OFF }</code> indicates that exactly one of ON or OFF must

	be provided. You do not type the braces: QUOTES ON
Backslash \	Continuation character used to indicate text that is too long to fit on a single line.
Ellipses . . .	Indicate a repetition of the previous parameter. For example, <code>option[. . .]</code> means that you can enter multiple, comma-separated options.  Note: Showing an ellipses in code examples might also mean that part of the text has been omitted for readability, such as in multi-row result sets.
<i>Indentation</i>	Is an attempt to maximize readability; SQL is a free-form language.
<i>Placeholders</i>	Items that must be replaced with appropriate identifiers or expressions are shown in italics.
Vertical bar	Is a separator for mutually exclusive items. For example: [ASC   DESC]  Choose one or neither. You do not type the square brackets.

# Overview to Getting Started

---

This guide serves as a tutorial, walking you through the process of configuring a Vertica database and running example queries.

Before you start, Vertica recommends that you read the Concepts Guide to gain a quick understanding of unfamiliar concepts.

---

## Prerequisites

All example databases described in this guide (including the one-step example) share the following prerequisites:

- You have installed Vertica on a cluster of hosts, as described in the Installation Guide.
  - You have downloaded and installed the documentation, as described in ***Where to Find the Vertica Documentation*** (page 2).
  - You are logged in to the server as the Database Administrator user; for example, `dbadmin`.
  - You access to your database either by an SSH client or through the terminal utility in your Linux Console, such as `vsql`.
- 

## User Interfaces

By following this tutorial, you use the following user interfaces:

- The Linux command line (shell) interface
- The Vertica Administration Tools (see the Administrator's Guide for details)
- The `vsql` client interface (see the Programmer's Guide for details)

## Example Databases

Vertica provides several simplified versions of databases that might actually be used in real-world applications. Detailed descriptions of each are provided in ***Example Databases*** (page 11).

You can use these databases as examples for learning purposes or as templates for actual databases. Even if your business has nothing to do with any of the sample schemas, the tutorial is useful because the techniques are the same, regardless of the type of data warehouse you use.

If you installed the product RPM, the example databases are located in `/opt/vertica/examples` on the host.

## One-step Example Database

Vertica provides a one-step installation script that lets you create an example database and start using it immediately. The scripts are located in `/opt/vertica/sbin` and are called:

- `install_example` — Creates a database on the default port (5433), generates data, creates the schema and a default superprojection, and loads the data.
- `delete_example` — Drops the database

---

## Notes

- Before you can install the example, you must accept the EULA (one time only) using the Administration Tools.
  - For a more advanced but equally-simple example using the Vertica databases, see the ***Tutorial*** (page 87) in the Getting Started Guide.
- 

## Tutorial

The Tutorial describes how to configure a Vertica database that you'll use to run sample queries. It assumes that you have already installed Vertica on a cluster of hosts, as described in the Installation Guide. You can copy the example databases to non-cluster hosts for reference purposes, but you must perform the tasks in the Tutorial on the Administration Host.

## Example Queries

Each example database includes several queries that are intended to represent queries that might be used in a real business. Once you're comfortable running the example queries, you'll probably want to write your own. Instructions are provided in ***Running Simple Queries*** (page 104).

## Cleanup Procedure

When you have finished with the tutorial, you can restore your host machines to their original state. Instructions are provided in ***Cleanup Procedure*** (page 105).

# Example Databases

---

Vertica provides several example databases that you can use in the tutorial:

- **ClickStream Example Database** (page 13)
- **Credit History Example Database** (page 22)
- **Retail Sales Example Database** (page 31)
- **Stock Exchange Example Database** (page 44)
- **Telecom Example Database** (page 57)
- **VMart Example Database** (page 66)

You can perform this tutorial using any or all of the example databases. The actual data returned from your queries will differ from the data published within this guide because the sample data generator program generates a new set of data for each of your example databases.

**Caution:** Although you can define multiple example databases within a single Vertica installation, Vertica strongly recommends that you start only one example database at a time to avoid unpredictable results.

## Example Database File Locations

The example databases are installed in:

```
/opt/vertica/examples/ClickStream_Schema  
/opt/vertica/examples/CreditHistory_Schema  
/opt/vertica/examples/Retail_Schema  
/opt/vertica/examples/Stock_Schema  
/opt/vertica/examples/Telecom_Schema  
/opt/vertica/examples/VMart_Schema
```

## Example Database File Descriptions

Each example database has an identical set of files except for the file name prefix and the number of query files. In each of the names in the list below, replace *example* with the prefix string that corresponds to one of the example databases:

```
clickstream  
credithistory  
retail  
stock  
telecom  
vmart
```

<code>example_count_data.sql</code>	SQL script that does a COUNT(*) of each table; can be used to verify load.
<code>example_define_schema.sql</code>	SQL script that defines the logical schema: tables and referential integrity constraints.
<code>example_gen.cpp</code>	Data generator source code (C++).
<code>example_gen</code>	Data generator executable file.


## Getting Started Guide

---

<code>example_load_data.sql</code>	SQL script that loads the generated sample data.
<code>example_queries.sql</code>	SQL script contain concatenated queries for use as a training set for the Database Designer.
<code>example_query_01.sql</code>	SQL scripts containing individual queries.
<code>example_schema_drop.sql</code>	SQL script that drops the schema.
README	Text file containing instructions for using the data generator.
Time.txt	Text file containing pre-computed data for date dimension tables.

## ClickStream Example Database

The ClickStream Example Database is a simple star schema that represents a record of the clicks made by a user on a web site. This data can be analyzed and used, for example, for business/marketing purposes or the detection of malicious activities on the web site. Each table is described in a separate section.



The ClickStream schema is focused towards discovering interesting and useful information from Web content and usage. This schema can be used for

- Marketing promotions
- Click Fraud Detection
- Improving Web site design and performance etc.

The data in the ClickStream schema is populated from parsing Web Server logs, users browsing activities and habits etc. This data can be used for tracking malicious and fraudulent activities in real time. The schema is focused towards recognizing patterns either by using statistical models, by manual off-line analysis or by SQL queries.

The schema is intended to answer following queries for fraud detection or other purposes

- 1 Number of users accessing web server from a given server IP per day? This helps us analyze whether any particular server is clogging the network or is involved in malicious attack.
- 2 Which client IP is generating excessively large hits?
- 3 Which customer (Client\_IP) address is downloading huge amount of Data?
- 4 Which customer is coming from more then one client IP?
- 5 Which customer is creating large number of sessions per day?
- 6 On which page do users stay for maximum duration?

Table Name	Default Number of Rows
<b>ClickStream_Fact</b> (on page 14)	5000000
<b>Customer_Dimension</b> (on page 15)	5000
<b>Session_Dimension</b> (on page 17)	50000
<b>UserAgent_Dimension</b> (on page 17)	500
<b>IPAddress_Dimension</b> (on page 16)	1000
<b>Page_Dimension</b> (on page 16)	5000
<b>CreditCard_Dimension</b> (on page 15)	5000

## ClickStream\_Fact

Each row in the fact table represents a summary of the user clicks done during browser session.

Field Name	Data Type	Description/Example
Date_Key	INTEGER	Date Key
Session_Key	INTEGER	Foreign Key, references Session_Dimension table
Customer_Key	INTEGER	Foreign Key, references Customer_Dimension Table
ClientIP_Key	INTEGER	Client IP Address, Foreign Key, references IPAddress_Dimension Table
ServerIP_Key	INTEGER	WebServer IP Address Foreign Key, references IPAddress_Dimension Table
UserAgent_ID	INTEGER	Foreign Key, references UserAgent_Dimension table
Page_Id	INTEGER	Foreign Key, references Page_Dimension table
Referrer_Page_id	INTEGER	Referring Page id
CreditCard_ID	INTEGER	Foreign Key, references CreditCard_Dimension Table
Num_Errors	INTEGER	Number of Errors encountered while browsing

KBytes_Downloaded	INTEGER	Amount of Data downloaded at client machine
Browsing_Time_Per_Page	INTEGER	Browsing time in minutes

## Customer\_Dimension

This table describes the user demographic information. Data in this table is populated from parsing strings from web logs of server.

Field Name	Data Type	Description/Example
Customer_Key	INTEGER	Primary key
Name	VARCHAR	Name of customer
E-mail_ID	VARCHAR	Unique mail id of customer
Sex	CHAR	Sex of the customer
Age	INTEGER	Age of customer
Annual_income	INTEGER	Annual income of the customer; for example, 50000 (\$50000)
City	VARCHAR	Home city of customer
State	VARCHAR	Home state of customer
Country	VARCHAR	Home country of customer

## CreditCard\_Dimension

This table describes the all domain pages.

Field Name	Data Type	Description/Example
Card_Key	INTEGER	PrimaryKey
CardHolder_Name	VARCHAR	Varchar
Card_Type	VARCHAR	MasterCard/Visa/Amex
Card_Expiration_Date	DATE	Date

## Date\_Dimension

Contains data for dates.

Field Name	Data Type	Description/Example
Date_Key	INTEGER	Primary key
Date_Val	DATE	Date in 'mm/dd/yyyy' format
Date_Description	VARCHAR	Description of the date; for example, January 1, 2000
Day_Num_In_Fiscal_Month	INTEGER	The day number in the month (1-31); for example, 21 for 21 <sup>st</sup> of any month.
Calendar_Year_Month	INTEGER	Calendar month of the date (1-12); for example, 9 for September
Calendar_Year	INTEGER	Calendar year of the date; for example, 2001

## IPAddress\_Dimension

This table describes the customer demographic information. Data in this table is populated from parsing strings from web logs of server.

Field Name	Data Type	Description/Example
IPAddress_Key	INTEGER	Primary key
IPAddress_Val	VARCHAR	IP Address value in dotted decimal; for example, 172.16.0.1
City	VARCHAR	City part of IP address
State	VARCHAR	State part of IP address
Country	VARCHAR	Country part of IP address

## Page\_Dimension

This table describes each page's domain relationships.

Field Name	Data Type	Description/Example
Page_Key	INTEGER	Primary key
Page_Name	VARCHAR	Page description and name
Page_Sub_Domain	VARCHAR	Page sub domain
Page_Domain	VARCHAR	Page domain

## Session\_Dimension

This table details user browsing session information.

Field Name	Data Type	Description/Example
Session_Key	INTEGER	Primary key
Session_Start_Time	VARCHAR	Session start time
Session_End_Time	VARCHAR	Session end time
Duration	INTEGER	Duration of the session in minutes
Server_IP	VARCHAR	IP address of server
Client_IP	VARCHAR	IP address of client

## UserAgent\_Dimension

This table describes user agent types for all machine types.

Field Name	Data Type	Description/Example
UserAgent_Key	INTEGER	Primary key
Browser_Type	VARCHAR	Mozilla
Browser_Version	VARCHAR	4.7
Operating_System	VARCHAR	WinNT/Linux
Operating_System_Version	VARCHAR	4.0/5.0 etc
Agent Language	VARCHAR	English/French etc

## clickstream\_query\_01.sql

### Query

```
-- Customer hitting the web server the most
-- number of times in a day

SELECT    Date_Val,
          Customer_Name,
          COUNT(*) AS Hits
FROM      ClickStream_Fact A,
          Customer_Dimension B,
          Date_Dimension C
WHERE     A.Customer_Key = B.Customer_Key
          AND A.Date_Key = C.Date_Key
GROUP BY Date_Val, Customer_Name
```

```
ORDER BY Hits DESC;
```

### Example

Date_Val	Customer_Name	Hits
2000-11-19	Michael	321
2000-03-03	Michael	320
2000-12-20	Sophie	317
2000-12-03	Sophie	314
2000-07-02	Sophie	313
2000-05-17	Michael	311

## clickstream\_query\_02.sql

### Query

```
-- Client IP hitting the server the most
-- number of times in a day

SELECT  Date_Val,
        IPAddress_Val,
        City,
        COUNT(*) AS Hits
FROM    ClickStream_Fact A,
        IPAddress_Dimension B,
        Date_Dimension C
WHERE   A.ClientIP_Key = B.IPAddress_Key
        AND A.Date_Key = C.Date_Key
GROUP BY Date_Val, IPAddress_Val, City
ORDER BY Hits DESC;
```

### Example

Date_Val	IPAddress_Val	City	Hits
2000-08-06	172.16.2.15	Noida	11
2000-10-19	172.16.1.3	Tokyo	10
2000-06-05	172.16.2.4	Paris	10
2000-07-05	172.16.1.6	London	10
2000-07-29	172.16.1.6	London	10
2000-01-19	172.16.2.15	Noida	10
2000-02-10	172.16.0.4	Detroit	10

## clickstream\_query\_03.sql

### Query

```
-- Page with the maximum number of hits
-- and total browsing time

SELECT  Date_Val,
```

```

        Page_Name,
        SUM(Browsing_Time) AS Browsing_Time,
        COUNT(*) AS Hits
FROM    ClickStream_Fact A,
        Page_Dimension B,
        Date_Dimension C
WHERE   A.Date_Key = C.Date_Key
        AND A.Page_Key = B.Page_Key
GROUP BY Date_Val, Page_Name
ORDER BY Browsing_Time DESC,
        Hits DESC;

```

### Example

Date_Val	Page_Name	Browsing_Time	Hits
2000-06-06	<a href="http://www.Geocities.Yahoo.com/page72.html">http://www.Geocities.Yahoo.com/page72.html</a>	90	16
2000-11-19	<a href="http://www.Jewellery.Rediff.com/page23.html">http://www.Jewellery.Rediff.com/page23.html</a>	87	11
2000-03-16	<a href="http://www.MP3-Players.Rediff.com/page34.html">http://www.MP3-Players.Rediff.com/page34.html</a>	81	14
2000-05-04	<a href="http://www.Cricket.Rediff.com/page90.html">http://www.Cricket.Rediff.com/page90.html</a>	80	13
2000-04-27	<a href="http://www.Laptops.Rediff.com/page69.html">http://www.Laptops.Rediff.com/page69.html</a>	79	11
2000-01-20	<a href="http://www.Mobiles.Rediff.com/page97.html">http://www.Mobiles.Rediff.com/page97.html</a>	75	12

## clickstream\_query\_04.sql

### Query

```
-- Customers creating more than 5 sessions per day
```

```

SELECT   Date_Val,
        Customer_Name,
        SUM(Duration),
        COUNT(*) AS Count_Session
FROM     ClickStream_Fact A,
        Date_Dimension B,
        Session_Dimension C,
        Customer_Dimension D
WHERE    A.Date_Key = B.Date_Key
        AND A.Customer_Key = D.Customer_Key
        AND A.Session_Key = C.Session_Key
GROUP BY Date_Val, Customer_Name, Duration
HAVING  COUNT(*) > 5
ORDER BY Duration DESC;

```

### Example

Date_Val	Customer_Name	SUM	Count_Session
2000-06-29	Matthew	1320	11
2000-07-08	Hannah	1200	10
2000-07-11	Hannah	960	8
2000-07-12	Hannah	840	7
2000-07-13	Hannah	1800	15
2000-07-15	Hannah	1920	16

## clickstream\_query\_05.sql

### Query

```
-- Customers coming from more than one IP address

SELECT    Date_Val,
          Customer_Name,
          COUNT(ClientIP_Key) AS Client_IPS
FROM      ClickStream_Fact A,
          Date_Dimension B,
          Customer_Dimension C
WHERE     A.Date_Key = B.Date_Key
          AND A.Customer_Key = C.Customer_Key
          AND A.Date_Key > 100
          AND A.Date_Key < 105
GROUP BY Date_Val, Customer_Name
HAVING    COUNT(ClientIP_Key) > 10
ORDER BY Client_IPs DESC;
```

### Example

Date_Val	Customer_Name	Client_IPS
2000-04-11	Sophie	308
2000-04-11	Michael	307
2000-04-11	Samuel	224
2000-04-11	Hannah	222
2000-04-11	Emily	214
2000-04-13	Sophie	213

## clickstream\_query\_06.sql

### Query

```
-- Pages visited by the maximum number of
-- IP addresses for a given month

SELECT    Page_Name,
          count(DISTINCT ipaddress_val) AS IP_Address_Count
FROM      ClickStream_Fact A,
          Page_Dimension B,
          IPAddress_Dimension C,
          Date_Dimension D
WHERE     A.Page_Key = B.Page_Key
          AND A.ClientIP_Key = C.IPAddress_Key
          AND A.Date_Key = D.Date_Key
          AND D.Calendar_Year = 2004
          AND D.Calendar_Month_Number_In_Year = 2
GROUP BY Page_Name
ORDER BY IP_Address_Count DESC;
```

**Example**

page_name	ip_address_count
<a href="http://www.Geocities.Yahoo.com/page2.html">http://www.Geocities.Yahoo.com/page2.html</a>	46
<a href="http://www.Geocities.Yahoo.com/page67.html">http://www.Geocities.Yahoo.com/page67.html</a>	45
<a href="http://www.Auctions.Rediff.com/page32.html">http://www.Auctions.Rediff.com/page32.html</a>	44
<a href="http://www.Books.Amazon.com/page90.html">http://www.Books.Amazon.com/page90.html</a>	44
<a href="http://www.Games.Yahoo.com/page33.html">http://www.Games.Yahoo.com/page33.html</a>	43
<a href="http://www.Messenger.Rediff.com/page17.html">http://www.Messenger.Rediff.com/page17.html</a>	43
<a href="http://www.Yellow-Pages.Yahoo.com/page60.html">http://www.Yellow-Pages.Yahoo.com/page60.html</a>	42
<a href="http://www.Groups.Yahoo.com/page73.html">http://www.Groups.Yahoo.com/page73.html</a>	41
<a href="http://www.Electronics.Amazon.com/page16.html">http://www.Electronics.Amazon.com/page16.html</a>	41
<a href="http://www.Real-Estate.Yahoo.com/page50.html">http://www.Real-Estate.Yahoo.com/page50.html</a>	41
<a href="http://www.Games.Yahoo.com/page61.html">http://www.Games.Yahoo.com/page61.html</a>	41
<a href="http://www.Jewellery&amp;Watches.Amazon.com/page6.html">http://www.Jewellery&amp;Watches.Amazon.com/page6.html</a>	41
<a href="http://www.Tools&amp;Automotive.Amazon.com/page79.html">http://www.Tools&amp;Automotive.Amazon.com/page79.html</a>	40
<a href="http://www.Home&amp;Garden.Amazon.com/page8.html">http://www.Home&amp;Garden.Amazon.com/page8.html</a>	40
<a href="http://www.Aparel&amp;Accessories.Amazon.com/page63.html">http://www.Aparel&amp;Accessories.Amazon.com/page63.html</a>	40
<a href="http://www.Maps.Yahoo.com/page66.html">http://www.Maps.Yahoo.com/page66.html</a>	39
<a href="http://www.Jobs.Rediff.com/page6.html">http://www.Jobs.Rediff.com/page6.html</a>	39
...	

## Credit History Example Database

The Credit History database is a simple star schema that represents customer credit history.




Table Name	Default Number of Rows
<b>CreditHistory_Fact</b> (on page 23)	5000000
<b>Customer_Dimension</b> (on page 23)	5000
<b>Institution_Dimension</b> (on page 25)	100
<b>AccountType_Dimension</b> (on page 23)	50
<b>MortgageType_Dimension</b> (on page 25)	1000

## CreditHistory\_Fact

Each row in the fact table represents a credit transaction performed by an individual.

Field Name	Data Type	Description
Date_Key	INTEGER	Foreign Key reference Date table
Customer_Key	INTEGER	Foreign Key reference Customer table
Institution_Key	INTEGER	Foreign Key reference Institution table
Account_Key	INTEGER	Foreign Key reference AccountType Table
Mortgage_Key	INTEGER	Foreign Key reference MortgageType Table
Days_Overdue	INTEGER	This field represents the number of days credit is overdue. 99999 represents bad debt.
Outstanding_Amount	FLOAT	Outstanding amount for a credit transaction

## AccountType\_Dimension

This table describes the type of accounts that can be offered by financial institutions

Field Name	Data Type	Description/Example
Account_Key	INTEGER	Primary key
Account_Type	VARCHAR	Type of account checking/current/loan
Account_Desc	VARCHAR	Brief description of account type
Account_Limit	INTEGER	If loan account then sanctioned credit limit

## Customer\_Dimension

This table describes details of customers whose credit history is maintained by the company.

Field Name	Data Type	Description/Example
Customer_Key	INTEGER	Primary key
Customer_FirstName	VARCHAR	Customer first name
Customer_LastName	VARCHAR	Customer last name
Current_Employer	VARCHAR	Current employer
SSN	VARCHAR	Social security number
HomePhone	VARCHAR	Home phone
Age	VARCHAR	Customer age

Sex	VARCHAR	Customer sex
City	VARCHAR	Customer city
State	INTEGER	Customer state
Zip	VARCHAR	Zip code

## Date Dimension

Contains data for dates.

Field Name	Data Type	Description/Example
Date_Key	INTEGER	Primary Key
Date_val	DATE	Date In 'mm/dd/yyyy' format
Full_date_description	VARCHAR(18)	Description of the date; for example, January 1, 2000
Day_of_week	VARCHAR(9)	Calendar year of the date; for example, 2001
Day_number_in_calendar_month	INTEGER	Calendar month of the date (1-12); for example, for September
Day_number_in_calendar_year	INTEGER	The day number in the month (1-31); for example, 21 for 21 <sup>st</sup> of any month.
Day_number_in_fiscal_month	INTEGER	
Day_number_in_fiscal_year	INTEGER	
Last_day_in_week_indicator	INTEGER	
Last_day_in_month_indicator	INTEGER	
Calendar_week_number_in_year	INTEGER	
Calendar_month_name	VARCHAR(9)	
Calendar_month_number_in_year	INTEGER	
Calendar_year_month	CHAR(7)	
Calendar_quarter	INTEGER	
Calendar_year_quarter	CHAR(7)	
Calendar_half_year	INTEGER	
Calendar_year	INTEGER	
Holiday_indicator	VARCHAR(10)	
Weekday_indicator	CHAR(7)	

## Institution\_Dimension

This table describes all the banking and financial institutions in the country.

Field Name	Data Type	Description/Example
Institution_Key	INTEGER	Primary key
Institution_Name	VARCHAR	Bank/credit lending institutions
Address	VARCHAR	Address of institution
City	VARCHAR	City of institution
State	VARCHAR	State of institution
Zip	VARCHAR	Zip code

## MortgageType\_Dimension

This table describes types of mortgages.

Field Name	Data Type	Description/Example
Mortgage_Key	INTEGER	Primary key
Mortgage_Type	VARCHAR	Car/home/personal mortgage
Mortgage_Amount	INTEGER	Mortgage Amount, such as \$1000, \$10000, and so on
Mortgage_Tenure	INTEGER	Mortgage tenure in months, such as 12, 24, 36, and so on
Mortgage_Interest	DOUBLE	Applicable interest rate.
Mortgage_EMI	DOUBLE	Amount payable monthly as installments

## credithistory\_query\_01.sql

### Query

```
-- Overdue statistics for 2001 by state
-- a. Avg Overdue (Amount and Days)
-- b. Max Overdue (Amount and Days)
-- c. Min Overdue (Amount and Days)

SELECT  State,
        MAX(Days_Overdue) AS Max_Days,
        MIN(Days_Overdue) AS Min_Days,
        AVG(Days_Overdue) AS Avg_Days,
        MAX(Outstanding_Amount) AS Max_Amount,
```

## Getting Started Guide

---

```
        MIN(Outstanding_Amount) AS Min_Amount,
        AVG(Outstanding_Amount) AS Avg_Amount,
        COUNT(*) AS Overdue_Recs
FROM    CreditHistory_Fact A,
        Customer_Dimension B,
        Date_Dimension C
WHERE   A.Date_Key = C.Date_Key
        AND A.Customer_Key = B.Customer_Key
        AND C.Calendar_Year = 2001
GROUP BY State
ORDER BY Avg_Amount DESC,
         Avg_Days DESC;
```

### Example

State	Max_Days	Min_Days	Avg_Days	Max_Amount	Min_Amount	Avg_Amount	Overdue_Recs
IL	999	0	498.137946406459	15000.3	500.67	7785.36343702016	20189
NY	999	0	500.163568584688	15000.11	500.02	7750.80704536809	39433
CA	999	0	499.313933330031	15000.51	500.73	7733.53519366982	40378

## credithistory\_query\_02.sql

### Query

```
-- Overdue statistics for 2001 by Institution
-- a. Avg Overdue (Amount and Days)
-- b. Max Overdue (Amount and Days)
-- c. Min Overdue (Amount and Days)

SELECT  Institution_Name,
        MAX(Days_Overdue) AS Max_Days,
        MIN(Days_Overdue) AS Min_Days,
        AVG(Days_Overdue) AS Avg_Days,
        MAX(Outstanding_Amount) AS Max_Amount,
        MIN(Outstanding_Amount) AS Min_Amount,
        AVG(Outstanding_Amount) AS Avg_Amount,
        COUNT(*) AS Overdue_Recs
FROM    CreditHistory_Fact A,
        Institution_Dimension B,
        Date_Dimension C
WHERE   A.Date_Key = C.Date_Key
        AND A.Institution_Key = B.Institution_Key
        AND C.Calendar_Year = 2000
GROUP BY Institution_Name
ORDER BY Avg_Amount DESC;
```

### Example

Institution_Name	Max_Days	Min_Days	Avg_Days	Max_Amount	Min_Amount	Avg_Amount	Overdue_Recs
------------------	----------	----------	----------	------------	------------	------------	--------------

INSTT#98	997	0	506.386450381679	14986.93	511.55
8034.51529580153	1048				
INSTT#57	999	2	494.70480081716	15000.01	508.57
8023.94215526047	979				
INSTT#83	999	0	508.528806584362	14994.48	502.39
8019.49127572016	972				
INSTT#56	999	3	516.19877675841	14979.93	511.46
7998.86175331295	981				
INSTT#45	997	1	498.116596638655	14994.69	507.47
7985.12201680672	952				
INSTT#66	998	0	488.579420579421	14990.66	501.3
7973.51433566434	1001				
INSTT#84	998	0	505.276302851524	14985.32	504.76
7964.23406096362	1017				
INSTT#90	996	1	510.30303030303	14990.34	536.82
7951.99204301075	1023				
INSTT#44	998	0	484.883883883884	14970.27	525.28
7945.75424424424	999				
INSTT#69	999	2	507.625502008032	14986.1	509.98
7936.75596385542	996				
INSTT#93	998	0	502.520669291339	15000.51	502.02
7936.17729330709	1016				
INSTT#73	998	0	491.066198595787	14993.14	559.45
7924.45994984955	997				

## credithistory\_query\_03.sql

### Query

```
-- Overdue mortgage statistics by year with mortgage type
```

```
SELECT Mortgage_Type,
       AVG(Days_Overdue) AS Avg_Days,
       AVG(Outstanding_Amount) AS Avg_Amount,
       COUNT(*) AS Overdue_Recs
FROM   CreditHistory_Fact A,
       Mortgage_Dimension B,
       Date_Dimension C
WHERE  A.Mortgage_Key = B.Mortgage_Key
       AND A.Date_Key = C.Date_Key
GROUP BY Calendar_Year, Mortgage_Type
ORDER BY Calendar_Year,
         Mortgage_Type;
```

### Example

Mortgage_Type	Avg_Days	Avg_Amount	Overdue_Recs
Car	499.179450730653	7758.45090843616	105522
Home	499.670780499164	7742.27507610237	94478

(2 rows)

## credithistory\_query\_04.sql

### Query

```
-- Overdue mortgage statistics by year with tenure
```

```
SELECT Mortgage_Type,
```

## Getting Started Guide

---

```
        Mortgage_Tenure,
        AVG(Days_Overdue) AS Avg_Days,
        AVG(Outstanding_Amount) AS Avg_Amount,
        COUNT(*) AS Record_Count
FROM    CreditHistory_Fact A,
        Mortgage_Dimension B,
        Date_Dimension C
WHERE   A.Mortgage_Key = B.Mortgage_Key
        AND A.Date_Key = C.Date_Key
GROUP BY Calendar_Year, Mortgage_Type, Mortgage_Tenure
ORDER BY Calendar_Year,
        Mortgage_Type,
        Mortgage_Tenure;
```

### Example

Mortgage_Type	Mortgage_Tenure	Avg_Days	Avg_Amount	Record_Count
Car	12	498.664561695056	7745.60994349813	24070
Car	24	502.332021237642	7753.32524533138	21848
Car	36	500.580798992262	7793.29573420911	22228
Car	48	498.262124831239	7730.3517000727	19258
Car	60	495.317695109836	7768.80918644442	18118
Home	60	500.719860896445	7858.66575637558	20704
Home	96	500.386262760763	7710.50094429649	18024
Home	120	496.92023054755	7751.82940172911	17350
Home	180	498.150733659404	7721.11076144953	17992
Home	240	501.653077224618	7662.79473049784	20408

(10 rows)

## credithistory\_query\_05.sql

### Query

```
-- Overdue mortgage statistics by year with account type

SELECT  Account_Type,
        AVG(Days_Overdue) AS Avg_Days,
        AVG(Outstanding_Amount) AS Avg_Amount,
        COUNT(*) AS Record_Count
FROM    CreditHistory_Fact A,
        AccountType_Dimension B,
        Date_Dimension C
WHERE   A.AccountType_Key = B.AccountType_Key
        AND A.Date_Key = C.Date_Key
GROUP BY Calendar_Year, Account_Type
ORDER BY Calendar_Year,
        Account_Type;
```

### Example

Account_Type	Avg_Days	Avg_Amount	Record_Count
Checking	500.261721483555	7741.41345971209	40012
Current	501.090460467923	7785.66681471225	28167
Saving	496.856415574621	7731.76984318532	31821

## credithistory\_query\_06.sql

### Query

```
-- Overdue statistics for 2001 by Customer age group
-- (in 5-year intervals)
-- a. Avg Overdue (Amount and Days)
-- b. Max Overdue (Amount and Days)
-- c. Min Overdue (Amount and Days)

SELECT  (Age - MOD(age, 5)) AS Age_Group,
        COUNT(DISTINCT A.Customer_Key) AS Num_Customers,
        MAX(Days_Overdue) AS Max_Days,
        MIN(Days_Overdue) AS Min_Days,
        AVG(Days_Overdue) AS Avg_Days,
        MAX(Outstanding_Amount) AS Max_Amount,
        MIN(Outstanding_Amount) AS Min_Amount,
        AVG(Outstanding_Amount) AS Avg_Amount,
        COUNT(*) AS Overdue_Recs
FROM    CreditHistory_Fact A,
        Institution_Dimension B,
        Date_Dimension C,
        Customer_Dimension D
WHERE   A.Date_Key = C.Date_Key
        AND A.Institution_Key = B.Institution_Key
        AND A.Customer_Key = D.Customer_Key
        AND C.Calendar_Year = 2001
GROUP BY (Age - MOD(age, 5))
ORDER BY (Age - MOD(age, 5));
```

### Example

age_group	num_customers	max_days	min_days	avg_days	max_amount	min_amount
avg_amount	overdue_recs					
15	222	999	0	497.936727480296	15000.93	500.23
7766.68663241784	45549					
20	628	999	0	501.106663765097	15001	500.01
7771.59768322634	128666					
25	507	999	0	499.240936955664	15000.96	500.03
7766.86130486666	103911					
30	585	999	0	500.578115364744	15000.98	500.03
7747.69135839403	120002					
35	582	999	0	499.998786631186	15000.98	500.15
7740.60186540811	119502					
40	596	999	0	500.107618470409	15000.9	500.06
7766.74586684467	122098					
45	583	999	0	499.767012348991	15000.92	500
7745.33969399988	119281					
50	586	999	0	498.041474731711	15000.97	500.03
7748.55477013954	119181					
55	583	999	0	498.440118960102	15000.9	500.07
7743.21703075921	119704					
60	128	999	0	499.436279703345	15000.92	500.14
7794.25127364916	26428					

(10 rows)



## Retail Sales Example Database

The Retail Sales Example Database is based on a fictional retail grocery chain store. It a simple star schema that represents individual line items on POS (Point of Sale) transactions. Each tuple in the fact table represents an item purchased from a store. Each table is described in a separate section.




Table Name	Default Number of Rows
<b>Retail_Sales_Fact</b> (on page 32)	5000000
<b>Product Dimension</b> (on page 70)	60000
<b>Store Dimension</b> (on page 34)	250

<b>Promotion_Dimension</b> (on page 71)	1000
---	------

## Retail\_Sales\_Fact

The Retail\_Sales\_Fact table describes individual items purchased from a grocery store. The generated data file contains data for five million items purchased by default.

Column Name	Data Type
Date_Key	INTEGER
Product_key	INTEGER
Store_key	INTEGER
Promotion_key	INTEGER
Pos_transaction_number	INTEGER
Sales_quantity	INTEGER
Sales_dollar_amount	INTEGER
Cost_dollar_amount	INTEGER
Gross_profit_dollar_amount	INTEGER

## Date\_Dimension

The Date Dimension table contains data for 1,828 dates for the years 2000-2004. It is generated from a file containing correct date/time data.

Column Name	Data Type	Description/Example
Date_Key	INTEGER	1
Date	DATE	01/01/2000
Full_date_description	VARCHAR(18)	January 1, 2000
Day_of_week	VARCHAR(9)	Sunday
Day_number_in_calendar_month	INTEGER	1
Day_number_in_calendar_year	INTEGER	1
Day_number_in_fiscal_month	INTEGER	1
Day_number_in_fiscal_year	INTEGER	1
Last_day_in_week_indicator	INTEGER	1
Last_day_in_month_indicator	INTEGER	0

Calendar_week_number_in_year	INTEGER	52
Calendar_month_name	VARCHAR(9)	January
Calendar_month_number_in_year	INTEGER	1
Calendar_year_month	CHAR(7)	2000-1
Calendar_quarter	INTEGER	1
Calendar_year_quarter	CHAR(7)	2000-q1
Calendar_half_year	INTEGER	1
Calendar_year	INTEGER	2000
Holiday_indicator	VARCHAR(10)	Holiday
Weekday_indicator	CHAR(7)	Weekend
Selling_season	VARCHAR(32)	Valentines Day

## Product Dimension

The Product Dimension table describes all products sold by the grocery chain since its beginning. Typically, individual stores only carry a subset of the products. The generated data file contains data for 60,000 products by default.

Column Name	Data Type	Description/Example
Product_Key	INTEGER	1
Product_description	VARCHAR(128)	Seafood Product 1
Sku_number	CHAR(32)	Sku-#1
Category_description	CHAR(32)	Food
Department_description	CHAR(32)	Seafood
Package_type_description	CHAR(32)	Box
Package_size	CHAR(32)	18 Oz
Fat_content	INTEGER	89
Diet_type	CHAR(32)	South Beach
Weight	INTEGER	50
Weight_units_of_measure	CHAR(32)	Gram
Shelf_width	INTEGER	2
Shelf_height	INTEGER	4
Shelf_depth	INTEGER	4

## Promotion\_Dimension

The Promotion Dimension describes every promotion (announced temporary price reduction) ever done by the grocery chain. The generated data file contains data for one thousand promotions by default.

Column Name	Data Type	Description/Example
Promotion_Key	INTEGER	1
Product_description	VARCHAR(128)	Seafood Product 1
Promotion_name	VARCHAR(128)	July 4th Liquidation Promotion
Price_reduction_type	VARCHAR(32)	20 Cents Off
Promotion_media_type	VARCHAR(32)	Magazine
Ad_type	VARCHAR(32)	1 Minute
Display_type	VARCHAR(32)	Pos
Coupon_type	VARCHAR(32)	Register Receipt
Ad_media_name	VARCHAR(32)	Other
Display_provider	VARCHAR(128)	Corporate
Promotion_cost	INTEGER	492
Promotion_begin_date	DATE	3-6-2001
Promotion_end_date	DATE	3-15-2001

## Store\_Dimension

The Store Dimension table describes all the stores in the chain. The generated data file contains data for 250 stores by default.

Column Name	Data Type	Example
Store_Key	INTEGER	1
Store_name	VARCHAR(64)	Store1
Store_name	VARCHAR(64)	Store1
Store_number	INTEGER	1
Store_street_address	VARCHAR(256)	3, Main St
Store_city	VARCHAR(64)	Concord
Store_state	CHAR(2)	Ca
Store_region	VARCHAR(64)	West
Floor_plan_type	VARCHAR(32)	Plan1
Photo_processing_type	VARCHAR(32)	Premium
Financial_service_type	VARCHAR(32)	None
Selling_square_footage	INTEGER	100
Total_square_footage	INTEGER	2000
First_open_date	DATE	3-1-2004
Last_remodel_date	DATE	null

## retail\_query\_01.sql

This query joins the fact table (five million rows) with one dimension table (1,828 rows).

### Query

```
-- The best day of the week in gross profit
-- for each year of operation.

SELECT  Calendar_Year,
        Day_Of_Week,
        SUM(Gross_Profit_Dollar_Amount) AS Profit
FROM    Retail_Sales_Fact,
        Date_Dimension
WHERE   Retail_Sales_Fact.Date_Key = Date_Dimension.Date_Key
GROUP BY Calendar_Year, Day_Of_Week
ORDER BY Calendar_Year,
        Profit DESC;
```

### Example

```
Retail_Single_Node=> \i retail_query_01.sql
calendar_year | day_of_week | profit
-----+-----+-----
2000 | Sunday      | 24610107
2000 | Tuesday     | 24389067
2000 | Thursday    | 23973851
2000 | Friday      | 23392757
```

```
2000 | Saturday | 22134302
2000 | Wednesday | 21427790
2000 | Monday | 20650172
2001 | Thursday | 24057786
2001 | Sunday | 22808366
2001 | Friday | 22262470
2001 | Tuesday | 21207805
2001 | Wednesday | 20648615
2001 | Saturday | 20522518
2001 | Monday | 16566382
2002 | Saturday | 23068736
2002 | Wednesday | 22749773
2002 | Monday | 22728810
2002 | Sunday | 20862246
2002 | Friday | 20825621
2002 | Tuesday | 20034320
2002 | Thursday | 18856255
2003 | Friday | 24563166
2003 | Tuesday | 22913972
2003 | Wednesday | 22255964
2003 | Thursday | 21596220
2003 | Saturday | 21039048
2003 | Monday | 20685036
2003 | Sunday | 20529061
2004 | Friday | 23675620
2004 | Saturday | 22815560
2004 | Wednesday | 21332928
2004 | Tuesday | 21303355
2004 | Sunday | 21190484
2004 | Monday | 20863037
2004 | Thursday | 20419213
```

(35 rows)

### retail\_query\_02.sql

This query joins five million rows of fact table data with three dimension tables (1,828 rows, 250 rows, and 1,000 rows).

#### Query

```
-- Promotion Profits by Year, Month, and Region

SELECT  Calendar_Year,
        Calendar_Month_Name,
        Store_Region,
        Promotion_Name,
        SUM(Gross_Profit_Dollar_Amount) AS Profit
FROM    Retail_Sales_Fact POS_Fact,
        Date_Dimension Date_Dim,
        Store_Dimension Store_Dim,
        Promotion_Dimension Prom_Dim
WHERE   POS_Fact.Date_Key = Date_Dim.Date_Key
        AND POS_Fact.Store_Key = Store_Dim.Store_Key
        AND POS_Fact.Promotion_Key = Prom_Dim.Promotion_Key
GROUP BY Calendar_Year,
         Calendar_Month_Name,
         Promotion_Name,
         Store_Region
HAVING  SUM(Gross_Profit_Dollar_Amount) >= 4500
ORDER BY Profit DESC;
```

**Example**

```
Retail_Single_Node=> \a
Output_format is unaligned.
Retail_Single_Node=> \i retail_query_02.sql
calendar_year | calendar_month_name | store_region | promotion_name | profit
-----+-----+-----+-----+-----
--
2000           | January              | West         | Summer Cool Sale | 97451
2000           | October              | West         | July 4th Discount Sale | 96588
2003           | March                | West         | Thanksgiving Super Sellathon | 96169
2000           | January              | West         | Thanksgiving Super Sellathon | 95184
2000           | October              | West         | Thanksgiving Super Sellathon | 95134
2000           | January              | West         | July 4th Super Sale | 94871
2000           | December             | West         | Summer Liquidation Promotion | 94343
2000           | January              | West         | Summer Liquidation Promotion | 94014
2000           | January              | West         | July 4th Cool Sellathon | 92744
2004           | January              | West         | Summer Cool Sale | 92659
2004           | January              | West         | Thanksgiving Super Sellathon | 92310
2000           | October              | West         | Summer Liquidation Promotion | 91872
2001           | August               | West         | Thanksgiving Super Sellathon | 91837
2001           | May                  | West         | Thanksgiving Super Sellathon | 91389
2004           | January              | West         | Summer Liquidation Promotion | 90615
2000           | December             | West         | Thanksgiving Super Sellathon | 90423
2004           | January              | West         | July 4th Discount Sellathon | 90282
2003           | December             | West         | Thanksgiving Super Sellathon | 89181
2004           | December             | West         | Thanksgiving Super Sellathon | 88236
(20 rows)
Retail_Single_Node=>
```

**retail\_query\_03.sql**

This query joins five million rows of fact table data with four dimension tables.

**Query**

```
-- Most Profitable Seafood Products in the East in 2003

SELECT  Product_Description,
        SUM(Gross_Profit_Dollar_Amount) AS Profit
FROM    Retail_Sales_Fact,
        Product_Dimension,
        Store_Dimension,
        Date_Dimension
WHERE   Retail_Sales_Fact.Product_Key = Product_Dimension.Product_Key
        AND Retail_Sales_Fact.Store_Key = Store_Dimension.Store_Key
        AND Retail_Sales_Fact.Date_Key = Date_Dimension.Date_Key
        AND Department_Description = 'Seafood'
        AND Store_Region = 'East'
        AND Calendar_Year = 2003
GROUP BY Store_Region,
         Product_Description
ORDER BY Store_Region,
         Profit DESC;
```

**Example**

```
Retail_Single_Node=> \i retail_query_03.sql
```

```
-----+-----
product_description | profit
-----+-----
```

## Getting Started Guide

---

Seafood Product	10370		2432
Seafood Product	47983		2331
Seafood Product	43929		2095
Seafood Product	6474		2008
Seafood Product	18213		1976
Seafood Product	53224		1935
Seafood Product	57425		1896
Seafood Product	10608		1888
Seafood Product	2989		1869
Seafood Product	258		1812
Seafood Product	25835		1809
Seafood Product	40207		1794
Seafood Product	16271		1794
Seafood Product	1429		1791
Seafood Product	58142		1777
Seafood Product	33695		1772
Seafood Product	20455		1765
Seafood Product	12616		1757
Seafood Product	57498		1750
Seafood Product	29837		1748
Seafood Product	53700		1745
Seafood Product	31991		1733
Seafood Product	16584		1731
Seafood Product	19347		1724
Seafood Product	25424		1719
Seafood Product	49094		1694
Seafood Product	57111		1683
Seafood Product	53686		1681
Seafood Product	32016		1680
Seafood Product	48506		1676
Seafood Product	12294		1669
Seafood Product	21983		1667
Seafood Product	30662		1666
Seafood Product	30073		1663
Seafood Product	27621		1662
Seafood Product	37650		1650
Seafood Product	37755		1645
Seafood Product	32757		1644
Seafood Product	21454		1636
Seafood Product	50994		1632
Seafood Product	32028		1630
Seafood Product	41263		1626
Seafood Product	6438		1606
Seafood Product	57315		1605
Seafood Product	11539		1605
Seafood Product	51685		1603
Seafood Product	34664		1600
Seafood Product	5798		1591

## retail\_query\_04.sql

### Query

```
-- Query 04
-- Report: Maximum sales_dollar_amount according to department

SELECT  a12.department_description AS department_description,
        a12.category_description AS category_description,
        sum(a11.sales_dollar_amount) AS total_sales_dollar_amount,
        max(a11.sales_dollar_amount) AS max_sales_dollar_amount
FROM    retail_sales_fact a11,
        product_dimension a12
WHERE   a11.product_key = a12.product_key
GROUP BY a12.department_description,
```

```

        a12.category_description
ORDER BY a12.department_description;

```

### Example

department_description	category_description	total_sales_dollar_amount	max_sales_dollar_amount
Bakery	Food	116489955	600
Canned Goods	Food	115699108	600
Cleaning supplies	Non-food	113700725	600
Dairy	Food	117254596	600
Frozen Goods	Food	116859512	600
Gifts	Misc	115800323	600
Liquor	Non-food	118948581	600
Meat	Food	119924642	600
Medical	Medical	115532701	600
Pharmacy	Medical	119401892	600
Photography	Misc	113603404	600
Produce	Food	113376462	600
Seafood	Food	119005848	600

(13 rows)

## retail\_query\_05.sql

### Query

```

-- Query 05
-- Top 5 Stores in a quarter on the basis of gross profit --

SELECT  a12.calendar_year_quarter AS calendar_year_quarter,
        a11.store_key AS store_key,
        max(a13.store_name) AS store_name,
        sum(a11.sales_quantity) AS total_sales_quantity,
        sum(a11.sales_dollar_amount) AS total_sales_dollar_amount,
        sum(a11.cost_dollar_amount) AS total_cost_dollar_amount,
        sum(a11.gross_profit_dollar_amount) AS total_gross_profit

FROM    retail_sales_fact a11,
        date_dimension a12,
        store_dimension a13

WHERE   a11.date_key = a12.date_key
        AND a11.store_key = a13.store_key
        AND a12.calendar_year_quarter = '2004-Q4'

GROUP BY a12.calendar_year_quarter,
         a11.store_key

ORDER BY total_gross_profit DESC

LIMIT  5;

```

### Example

```

calendar_year_quarter | store_key | store_name | total_sales_quantity | total_sales_dollar_amount |
total_cost_dollar_amount | total_gross_profit
-----+-----+-----+-----+-----+-----
2004-Q4                |      247 | Store247 |                    5844 |                    333410
|                    164461 |          |          168949
2004-Q4                |      239 | Store239 |                    5772 |                    328880
|                    162774 |          |          166106
2004-Q4                |      234 | Store234 |                    5828 |                    332649
|                    166579 |          |          166070
2004-Q4                |      168 | Store168 |                    5995 |                    325382
|                    159744 |          |          165638
2004-Q4                |       15 | Store15  |                    5864 |                    324643
|                    159716 |          |          164927
(5 rows)

```

### retail\_query\_06.sql

#### Query

```

-- Query 06
-- Region & state wise profit per unit --

SELECT    a12.store_region AS store_region,
          a12.store_state AS store_state,
          sum(a11.gross_profit_dollar_amount) AS
total_gross_profit_dollar_amount,
          sum(a11.sales_quantity) AS total_sales_quantity,
          ROUND((sum(a11.gross_profit_dollar_amount)::float /
sum(a11.sales_quantity)), 2)
          AS avg_profit_per_unit
FROM      retail_sales_fact a11,
          store_dimension a12
WHERE     a11.store_key = a12.store_key
GROUP BY a12.store_region,
          a12.store_state
ORDER BY a12.store_region,
          a12.store_state;

```

### Example

```

store_region | store_state | total_gross_profit_dollar_amount | total_sales_quantity |
avg_profit_per_unit
-----+-----+-----+-----+-----+-----
East        | CT          | 27419268 | 988967 |
27.73
East        | DC          | 6083983  | 219193 |
27.76
East        | MA          | 24425494 | 877070 |
27.85
East        | MD          | 18224018 | 657368 |
27.72
East        | MI          | 12192531 | 440660 |
27.67
East        | NC          | 9225154  | 332518 |
27.74
East        | NH          | 12227838 | 442973 |

```

27.6				
East	NJ		9153991	329633
27.77				
East	NY		3021472	108867
27.75				
East	PA		18426900	663897
27.76				
East	SC		12200472	439344
27.77				
East	TN		27424332	989000
27.73				
East	VA		12220511	439039
27.83				
MidWest	IA		3077406	111375
27.63				
MidWest	IL		36419633	1310671
27.79				
MidWest	IN		27569070	993308
27.75				
MidWest	MI		45764788	1653583
27.68				
MidWest	OH		6150916	219351
28.04				
MidWest	SD		12162880	437176
27.82				
MidWest	WI		12146497	437395
27.77				
NorthWest	OR		6090896	220814
27.58				
NorthWest	WA		3104690	110723
28.04				
South	FL		24266821	877191
27.66				
South	GA		24364400	880309
27.68				
South	LA		6080205	220558
27.57				
South	MS		3044063	110011
27.67				
South	TX		70301249	2536343
27.72				
SouthWest	AZ		15291817	551088
27.75				
SouthWest	CO		33598118	1208581
27.8				
SouthWest	KS		6109911	221061
27.64				
SouthWest	NV		12207238	439893
27.75				
West	CA		201597518	7262311
27.76				
West	UT		21366333	769336
27.77				
(33 rows)				

## retail\_query\_07.sql

### Query

```
-- Query 07
-- Listing of sales quantity of all products with id less than 100 --
```

```
SELECT  a11.product_key AS product_key,
        max(a12.product_description) AS product_description,
        max(a12.package_size) AS package_size,
        max(a12.weight_units_of_measure) AS weight_units_of_measure,
        sum(a11.sales_quantity) AS total_sales_quantity
FROM    retail_sales_fact a11, product_dimension a12
WHERE   a11.product_key = a12.product_key
        AND a11.product_key < 100
GROUP BY a11.product_key
ORDER BY a11.product_key;
```

### Example

product_key	product_description	package_size	weight_units_of_measure	total_sales_quantity
1	Seafood Product 1	Other	gram	487
2	Seafood Product 2	18 oz	gram	491
3	Seafood Product 3	1 liter	ounce	408
4	Medical Product 4	Other	pound	561
5	Seafood Product 5	1 gallon	pound	540
6	Meat Product 6	Economy	gram	576
7	Medical Product 7	Other	pound	465
8	Photography Product 8	Other	pound	504

## retail\_query\_08.sql

### Query

```
-- Query 08
-- Quarterly and monthly sales for promotional schemes --

SELECT  a13.calendar_year_quarter AS calendar_year_quarter,
        a13.calendar_month_name AS calendar_month_name,
        a12.ad_type AS ad_type,
        sum(a11.sales_dollar_amount) AS total_sales_dollar_amount,
        sum(a11.sales_quantity) AS total_sales_quantity
FROM    retail_sales_fact a11,
        promotion_dimension a12,
        date_dimension a13
WHERE   a11.promotion_key = a12.promotion_key
        AND a11.date_key = a13.date_key
GROUP BY a13.calendar_year_quarter,
        a13.calendar_month_name,
        a13.calendar_month_number_in_year,
        a12.ad_type
ORDER BY a13.calendar_year_quarter,
        a13.calendar_month_number_in_year,
        a12.ad_type;
```


### Example

calendar_year_quarter	calendar_month_name	ad_type	total_sales_dollar_amount
-----------------------	---------------------	---------	---------------------------

total_sales_quantity			
Period	Month	Frequency	Quantity
2000-Q1	January	1 minute	7858712
142398			
2000-Q1	January	30 seconds	7805195
140665			
2000-Q1	January	Fullpage	8622042
156397			
2000-Q1	January	Halfpage	7710140
139833			
2000-Q1	February	1 minute	5712781
103815			
2000-Q1	February	30 seconds	5674174
103718			
2000-Q1	February	Fullpage	6327306
114023			
2000-Q1	February	Halfpage	5623861
101407			
2000-Q1	March	1 minute	6174128
112232			
2000-Q1	March	30 seconds	6274003
113892			
2000-Q1	March	Fullpage	6890512
124231			
2000-Q1	March	Halfpage	6064541
110426			
2000-Q2	April	1 minute	5990593
108544			
2000-Q2	April	30 seconds	5976581
107663			
2000-Q2	April	Fullpage	6548556
118904			
2000-Q2	April	Halfpage	5834707
105976			
2000-Q2	May	1 minute	6496888
117450			
2000-Q2	May	30 seconds	6386322
116323			
2000-Q2	May	Fullpage	7106788
129226			
2000-Q2	May	Halfpage	6332820
115019			
2000-Q2	June	1 minute	6435020
116730			
2000-Q2	June	30 seconds	6451742
117210			
2000-Q2	June	Fullpage	7143086
128928			
2000-Q2	June	Halfpage	6262982
114252			
2000-Q3	July	1 minute	6558197
119295			
2000-Q3	July	30 seconds	6497357
117877			
2000-Q3	July	Fullpage	7284518
131812			
...			

## Stock Exchange Example Database

The Stock Exchange schema is a simple star schema that represents summary of trades done during the day by various business such as banks, insurance companies, retail investors, mutual funds, and so on. It is commonly known as a "tick store." Each table is described in a separate section.



## StockTransaction\_Fact

Each record in the fact table represents summary of stocks traded in a day.

Field Name	Data Type	Description
Date_key	INTEGER	Date Key
Exchange_Key	INTEGER	Foreign Key, references Exchange table
Settlement_Key	INTEGER	Foreign Key, references Settlement table
Trader_Key	INTEGER	Foreign Key, references Trader Table
Stock_Key	INTEGER	Foreign Key, references Stock Dimension table
Previous_Close	FLOAT	Previous close of the Script
Open_Price	FLOAT	Opening price of Script for the given day
High_Price	FLOAT	High price of Script for the given day
Low_Price	FLOAT	Low price of Script for the given day
Close_Price	FLOAT	Closing price of Script for the given day
Total_Traded_Quantity	FLOAT	Total traded quantity of the Script for the given day
Total_Deliverable Qty	FLOAT	Total Deliverable quantity Script for the given day
Total_Turnover	FLOAT	Total value of transactions for the given day
artificial_segmentation_column	INTEGER	Generated values for load-balancing nodes

## Date\_Dimension

The Date Dimension table contains data for dates.

Field Name	Data Type	Description
Date_Key	INTEGER	Primary Key
Date	DATE	
Full_date_description	VARCHAR(18)	
Day_of_week	VARCHAR(9)	
Day_number_in_calendar_month	INTEGER	
Day_number_in_calendar_year	INTEGER	
Day_number_in_fiscal_month	INTEGER	
Day_number_in_fiscal_year	INTEGER	
Last_day_in_week_indicator	INTEGER	
Last_day_in_month_indicator	INTEGER	
Calendar_week_number_in_year	INTEGER	
Calendar_month_name	VARCHAR(9)	
Calendar_month_number_in_year	INTEGER	
Calendar_year_month	CHAR(7)	
Calendar_quarter	INTEGER	
Calendar_year_quarter	CHAR(7)	
Calendar_half_year	INTEGER	
Calendar_year	INTEGER	
Holiday_indicator	VARCHAR(10)	
Weekday_indicator	CHAR(7)	

## Exchange\_Dimension

This table describes the stock exchanges included in the fact table.

Field Name	Data Type	Description
Exchange_Key	INTEGER	Primary Key
Exchange_Name	VARCHAR	Complete Exchange name
Exchange_City	VARCHAR	City where exchange is located
Exchange_Country	VARCHAR	Country where exchange is located
Local_Currency	VARCHAR	Local currency of where exchange is located

## Settlement\_Dimension

This table describes the types of settlements.

Field Name	Data Type	Description
Settlement_Key	INTEGER	Primary Key
Settlement_Description	VARCHAR	Exchange specific Settlement Number in which all transactions of specific period have to be settled
Settlement_Start_Date	DATE	Settlement Start Date
Settlement_End_Date	DATE	Settlement End Date

## Split\_Dimension

This tables contains stock split dates and factors.

Field Name	Data Type	Description
Split_Id	INTEGER	Primary Key
EntryDate	DATE	Date the split is announced.
SplitDate	DATE	Date the split is actually effective.
SplitFactor	FLOAT	The split factor expressed as a decimal value. For example, a 2 for 1 split is expressed as 0.5 and a 4 for 3 is expressed as 0.75.

## Stock Dimension

Describes all publicly traded stocks in stock exchanges.

Field Name	Data Type	Description
Stock_Key	INTEGER	Primary Key
Split_Key	INTEGER	Foreign Key references Split_Dimension Table
Stock_Name	VARCHAR	Publicly traded stock name
Stock_Symbol	VARCHAR	Symbol of traded security
Stock_Type	VARCHAR	Equity/Bond
Industry_Type	VARCHAR	Chemical/Computers/Steel
SP_Rating	VARCHAR	S&P Rating, 'AAA', AA, A B+, B etc.
Company_Name	VARCHAR	Complete name of company
Registered_Address	VARCHAR	Complete address where the company is registered
Registered_City	VARCHAR	City where company is registered
Registered_State	VARCHAR	State where company is registered
Postal_Code	VARCHAR	Postal code
Registered_Country	VARCHAR	Country where company is registered
FaceValue	INTEGER	Issue Price of stock in country where company is located; for example, \$1, \$5

## Trader\_Dimension

This table describes the institutions that trade stocks.

Field Name	Data Type	Description
Trader_Key	INTEGER	Primary Key
TraderName	VARCHAR	Name of institution.
TraderType	VARCHAR	Type of trader (broker, bank, insurance company, etc.)

## stock\_query\_01

### Query

```

--- QUERY #1
--- Stocks that gained between 70% and 75% on a given day
SELECT B.Stock_Name,
       MIN(A.Close_Price),
       MAX(A.Close_Price)
FROM   StockTransaction_Fact A,
       Stock_Dimension B
WHERE  A.Date_Key > 50
       AND A.Date_Key < 53
       AND A.Stock_Key = B.Stock_Key
       AND ((A.close_Price - A.Previous_Close) * 100) / A.Previous_Close > 70
       AND ((A.close_Price - A.Previous_Close) * 100) / A.Previous_Close < 75
GROUP BY B.Stock_Name
ORDER BY B.Stock_Name;

```

### Example

```

  stock_name | min | max
-----+-----+-----
STOCK_NAME#229 | 70.42 | 70.42
STOCK_NAME#50  | 70.12 | 70.12
(2 rows)

```

## stock\_query\_02

### Query

```

--- QUERY #2
--- Total traded quantity and value of stock in a
--- given settlement period

```

## Getting Started Guide

---

```
SELECT Settlement_Description,
       Stock_Name,
       SUM(Total_Traded_Quantity) AS Total_Traded_Qty,
       SUM(Total_Turnover)       AS Total_Trade_value
FROM   StockTransaction_Fact A,
       Settlement_Dimension B,
       Stock_Dimension C,
       Date_Dimension D
WHERE  A.Settlement_Key = B.Settlement_Key
      AND A.Stock_Key = C.Stock_Key
      AND A.Date_Key = D.Date_Key
      AND B.Settlement_Description = '2000010'
      AND D.Calendar_Month_Number_in_Year = 1
      AND D.Calendar_Year = 2004
GROUP BY Settlement_Description,
         Stock_Name
ORDER BY Settlement_Description,
         Stock_Name;
```

### Example

settlement_description	stock_name	total_traded_qty	total_trade_value
2000010	STOCK_NAME#1	1319	14927.65
2000010	STOCK_NAME#100	913	8832.14
2000010	STOCK_NAME#101	1236	23758.96
2000010	STOCK_NAME#102	42	12155.77
2000010	STOCK_NAME#103	828	12645.93
2000010	STOCK_NAME#104	1891	16389.46
2000010	STOCK_NAME#105	384	9297.98
2000010	STOCK_NAME#106	999	5227.98
2000010	STOCK_NAME#107	161	9753.48
2000010	STOCK_NAME#108	570	10918.92
2000010	STOCK_NAME#109	460	8521.47
2000010	STOCK_NAME#110	1088	20814.29
2000010	STOCK_NAME#111	854	35174.67
2000010	STOCK_NAME#112	325	10343.32
2000010	STOCK_NAME#114	1967	27991.93
2000010	STOCK_NAME#115	986	24233.03

...

## stock\_query\_03

### Query

```
--- QUERY #3
--- Stocks with maximum traded quantity and value in a
--- given week of the year
SELECT Day_Number_in_Calendar_Month,
       C.Stock_Name,
       SUM(Total_Traded_Quantity) AS Total_Traded_Qty,
       SUM(Total_Turnover)       AS Total_Trade_value
FROM   StockTransaction_Fact A,
       Date_Dimension B,
       Stock_Dimension C
WHERE  A.Date_Key = B.Date_Key
      AND A.Stock_Key = C.Stock_Key
```

```

        AND B.Calendar_Week_Number_in_Year = 7
GROUP BY Day_Number_in_Calendar_Month,
         Stock_Name
ORDER BY Day_Number_in_Calendar_Month,
         Total_Traded_Qty DESC;

```

### Example

day_number_in_calendar_month	stock_name	total_traded_qty	total_trade_value
9	STOCK_NAME#88	14060	263374.23
9	STOCK_NAME#84	11695	147378.71
9	STOCK_NAME#35	11571	188538.46
9	STOCK_NAME#139	11448	187385
9	STOCK_NAME#225	11225	196794.57
9	STOCK_NAME#247	11215	154407.54
9	STOCK_NAME#37	11142	160855.92
9	STOCK_NAME#237	11020	215696.29
9	STOCK_NAME#70	10965	177607.71
9	STOCK_NAME#114	10806	146490.98
9	STOCK_NAME#49	10641	184186.92
9	STOCK_NAME#272	10410	207722.41
9	STOCK_NAME#61	10324	152053.87
9	STOCK_NAME#18	10155	179153.75
9	STOCK_NAME#113	9993	177771.6

## stock\_query\_04

### Query

```

--- Query 04
--- Types of traders who have a maximum turnover in a given week
SELECT TraderType,
       SUM(Total_Traded_Quantity) AS Total_Traded_Quantity,
       SUM(Total_Deliverable_Qty) AS Total_Deliverable_Qty,
       SUM(Total_Deliverable_Qty)
       / SUM(Total_Traded_Quantity) AS Delivery_Trade_Ratio
FROM   StockTransaction_Fact A,
       Date_Dimension B,
       Trader_Dimension C
WHERE  A.Date_Key = B.Date_Key
       AND A.Trader_Key = C.Trader_Key
       AND B.Calendar_Week_Number_in_Year = 9
GROUP BY TraderType
ORDER BY Delivery_Trade_Ratio;

```

### Example

tradertype	total_traded_quantity	total_deliverable_qty	delivery_trade_ratio
Retail-Investor	8909895	26430691	2.966
Stock-Broker	9715181	28858933	2.97
Insurance-Company	8740296	26128178	2.989
Others	11123241	33559823	3.017
Bank	10993831	33219510	3.022

(5 rows)

## stock\_query\_05

### Query

```
--- Query 05
--- Exchange that has a maximum turnover in a year

SELECT Calendar_Year,
       Exchange_Name,
       SUM(Total_Traded_Quantity) AS Total_Traded_Quantity,
       SUM(Total_Turnover) AS Total_Trade_value
FROM   StockTransaction_Fact A,
       Date_Dimension B,
       Exchange_Dimension C
WHERE  A.Date_Key = B.Date_Key
      AND A.Exchange_Key = C.Exchange_Key
GROUP BY Calendar_Year,
         Exchange_Name
ORDER BY Total_Trade_value DESC,
         Total_Traded_Quantity;
```

### Example

calendar_year	exchange_name	total_traded_quantity	total_trade_value
2000	SHSE	140598876	2804225676.41
2000	LSE	70490890	1407294711.73
2000	NYSE	69888940	1403007907.5
2000	TSE	70013693	1402097341.09
2000	BSE	69828761	1396841233.24
2000	MSE	69536068	1391241795.02
2001	SHSE	144673882	2901380718.8
2001	BSE	72325862	1450172021.31
2001	LSE	72255304	1446701214.62
2001	TSE	72053573	1444195757.99
2001	NYSE	72086902	1442130576.81
2001	MSE	71951644	1440488299.91
2002	SHSE	146419985	2929077855.41
2002	LSE	73391671	1472145875.43
2002	MSE	73491704	1470316584.75
2002	NYSE	73413826	1468898162.55
2002	TSE	73131808	1466021941.78
2002	BSE	72713813	1458532063.79
2003	SHSE	141327981	2833415190.98
2003	MSE	70796425	1414284020.43
2003	TSE	70275688	1412779754.15
2003	NYSE	70483411	1412075549.07
2003	LSE	70573600	1411885663.35
2003	BSE	70085099	1405457706.97
2004	SHSE	141762728	2832792072.94
2004	NYSE	70852202	1420409267.29
2004	BSE	70645192	1418096154.21
2004	TSE	70803574	1416000504.84
2004	LSE	70644325	1413213041.39

2004 | MSE | 70485707 | 1409461236.42  
 (30 rows)

## stock\_query\_06

### Query

```

--- Query 06
--- Get the closing price of a set of 10 stocks for a 10-year period
--- and weekly aggregates.
SELECT Calendar_Year,
       Calendar_Year_Month,
       Calendar_Week_Number_in_Year,
       Stock_name,
       MIN(Close_Price),
       MAX(Close_Price),
       AVG(Close_Price)
FROM   StockTransaction_fact A,
       Date_Dimension B,
       Stock_Dimension C
WHERE  A.stock_key = C.stock_key
      AND A.date_key = B.date_key
      AND Calendar_Year >= 1900
      AND Calendar_Year <= 2007
GROUP BY Calendar_Year,
         Calendar_Year_Month,
         Calendar_Week_Number_in_Year,
         Stock_name
ORDER BY Stock_name,
         Calendar_Year,
         Calendar_Year_Month,
         Calendar_Week_Number_in_Year;

```

### Example

stock_name	calendar_year	calendar_year_month	week_number	min_close_price	max_close_price	avg_close_price
STOCK_NAME#1	2000	2000-1	1	40.14	69.8	53.37
STOCK_NAME#1	2000	2000-1	2	40.08	70.53	53.95
STOCK_NAME#1	2000	2000-1	3	42.08	70.52	56.54
STOCK_NAME#1	2000	2000-1	4	40.07	70.35	55.33
STOCK_NAME#1	2000	2000-1	5	42.75	67.86	56.61
STOCK_NAME#1	2000	2000-2	5	40.2	70.65	53.92
STOCK_NAME#1	2000	2000-2	6	40.13	69.26	55.86
STOCK_NAME#1	2000	2000-2	7	40.25	71	55.58
STOCK_NAME#1	2000	2000-2	8	40.52	70.88	56.67
STOCK_NAME#1	2000	2000-3	9	40.23	70.71	54.71
STOCK_NAME#1	2000	2000-2	9	40.85		

## Getting Started Guide

---

69.86	55.23						
STOCK_NAME#1		2000	2000-3		10	40.28	
70.73	56.48						
STOCK_NAME#1		2000	2000-3		11	40.06	
70.14	55.82						
STOCK_NAME#1		2000	2000-3		12	40.26	
70.91	57.74						
...							

## Telecom Example Database

The Telecom schema is a simple star schema that represents a summary of the calls made by the customers of a fictional cell phone service provider. Each table is described in a separate section.




Table Name	Default Number of Rows
<b>Billing_Fact</b> (on page 58)	5000000
<b>Customer_Details_Dimension</b> (on page 59)	50000
<b>Rate_Plan_Dimension</b> (on page 60)	500
<b>Numbering_Plan_Dimension</b> (on page 60)	500
<b>Equipment_Dimension</b> (on page 60)	200
<b>Feature_Dimension</b> (on page 60)	20
<b>Call_Termination_Dimension</b> (on page 58)	20

## Billing\_Fact

Each tuple in the fact table represents a summary of the CDR records generated at the switch for each customer.

Field Name	Data Type	Description/Example
Date_Key	INTEGER	Call Date. Foreign Key, references Date table key
Plan_Key	INTEGER	Foreign Key, references Rate_Plan table key
Calling_Number_key	INTEGER	Calling party number. Foreign Key, references Number table key
Called_Number_Key	INTEGER	Called party location. Foreign Key, references Number table key
Cust_Key	INTEGER	Calling Party customer id who is billed for the call and services. Foreign Key, references Customer_Details table key
Feature_key	INTEGER	Foreign Key, references Feature table key
Termination_key	INTEGER	Call Termination Type; for example, normal or abnormal
Equipment_Key	INTEGER	Type of Equipment
Roaming_Flag	BOOL	Whether this call is made/received while roaming
Call_Duration	TIMESTAMP	Duration of the call
Number_of_Calls	INTEGER	Total number of calls made during the day
Total_Minutes	INTEGER	Total number of minutes of calls made that day
Total_Roaming_Minutes	INTEGER	Total number of roaming minutes used
Total_Long_Distance_Minutes	INTEGER	Total number of long distance calls made.
Total_Call_Cost	FLOAT	Total cost of all the call
Total_Roaming_Cost	FLOAT	Total roaming charges
Total_Long_Distance_Cost	FLOAT	Total Long Distance charges
Service_tax	FLOAT	Service tax
Surcharge	FLOAT	Surcharge

## Call\_Termination\_Dimension

This table describes all possible reasons for which a call can be terminated.

Field Name	Data Type	Description/Example
Termination_key	INTEGER	Primary Key
Termination_type	VARCHAR	ITAU Termination Type (normal, service failure, equipment failure, etc.)
Termination_Description	VARCHAR	ITAU Termination Description

## Customer\_Details\_Dimension

This table describes the customers of the service provider.

Field Name	Data Type	Description/Example
Cust_Key	INTEGER	Primary Key
Cust_Name	VARCHAR	Customer/Subscriber Name
Cust_Age	INTEGER	Age of the customer
Cust_Sex	CHAR	Male/Female (M/F)
Cust_City	VARCHAR	City of the customer
Cust_State	VARCHAR	State of the customer
Cust_Zip	VARCHAR	Zip/postal code of the customer

## Date\_Dimension

This table contains data for dates.

Field Name	Data Type	Description/Example
Date_Key	INTEGER	Primary Key
Date_val	DATE	Date in 'mm/dd/yyyy' format
Date_Description	VARCHAR	Description of the date; for example, January 1, 2000
Calendar_Year	INTEGER	Calendar year of the date; for example, 2001
Calendar_Year_Month	INTEGER	Calendar month of the date (1-12); for example, 9 for September
Day_Num_in_Fiscal_Month	INTEGER	The day number in the month (1-31); for example, 21 for 21 <sup>st</sup> of any month.

## Equipment\_Dimension

This table describes type of equipment (handsets) used by customers of the service provider.

Field Name	Data Type	Description/Example
Equipment_Key	INTEGER	Primary Key
Equipment_type	VARCHAR	Landline/mobile/WLL/blackberry/wireless card
Manufacturer	VARCHAR	Nokia/Sony-Ericsson/Motorola
Model Number	INTEGER	Phone model number

## Feature\_Dimension

This table describes every feature offered by the service provider.

Field Name	Data Type	Description/Example
Feature_Key	INTEGER	Primary Key
Feature_type	VARCHAR	SMS/MMS/Call Forwarding/Call Waiting/
Feature_rate	VARCHAR	Feature cost per invocation

## Numbering\_Plan\_Dimension

This table describes the types of numbering plans. This is used to distinguish between originating and terminating destination calls.

Field Name	Data Type	Description/Example
Number_Key	INTEGER	Primary Key
Country_Code	VARCHAR	Country code part of the phone number.
Area_Code	VARCHAR	3 Digit Area Code of the Phone
State	VARCHAR	State Code of the Numbering Plan.
Phone_Type	VARCHAR	Type of the phone fixed/GSM/CDMA

## Rate\_Plan\_Dimension

This table describes all the rate plans offered by the service provider.

Field Name	Data Type	Description/Example
Plan_Key	INTEGER	Primary Key
Plan_Name	VARCHAR	Common/Business Name of the rate plan say 'Freedom25'
Plan_Description	VARCHAR	Description of the rate plan
Plan_Min_Rental	FLOAT	Minimum monthly rental for this rate plan say 24.99 (USD)
Plan_Currency	VARCHAR	Plan Currency (USD)
Plan_Pulse_Rate_sec	INTEGER	Pulse rate available in the plan say 30 sec pulse or 60 sec pulse
Toll_rate	FLOAT	Call charges for the plan

## telecom\_query\_01.sql

### Query

```
-- Best month of the year in terms of
-- minutes of usage for each year of operation.

SELECT  Calendar_Year,
        Calendar_Year_Month,
        SUM(Total_Minutes) AS Total_Minutes
FROM    Billing_Fact,
        Date_Dimension
WHERE   Billing_Fact.Date_Key = Date_Dimension.Date_Key
GROUP BY Calendar_Year,Calendar_Year_Month
ORDER BY Calendar_Year,
        Calendar_Year_Month;
```

### Example

```
Calendar_Year | Calendar_Year_Month | Total_Minutes
-----+-----+-----
      2000 |           1 |          1451
      2000 |           2 |          1616
      2000 |           3 |          1397
      2000 |           4 |          1334
      2000 |           5 |          1076
```

(17 rows)

## telecom\_query\_02.sql

### Query

```
-- Best rate plan in use

SELECT  Calendar_Year,
        Calendar_Year_Month,
        Plan_Name,
```

## Getting Started Guide

---

```
SUM(Number_Of_Calls) AS Calls,
SUM(Total_Minutes) AS Total_Minutes
FROM Billing_Fact Bill_Fact,
Date_Dimension Date_Dim,
Rate_Plan_Dimension Rate_Dim
WHERE Bill_Fact.Date_Key = Date_Dim.Date_Key
AND Bill_Fact.Plan_Key = Rate_Dim.Plan_Key
GROUP BY Calendar_Year, Calendar_Year_Month, Plan_Name
HAVING SUM(Number_Of_Calls) >= 10
ORDER BY Calls;
```

### Example

Calendar_Year	Calendar_Year_Month	Plan_Name	Calls	Total_Minutes
2000	12	Freedom_40	10	18
2000	9	Youth_45	10	48
2000	2	Freedom_30	10	49
2000	6	Flexi_40	10	35
2000	1	Flexi_30	10	36
2000	9	Youth_30	10	81
2000	6	Youth_25	10	55
2000	10	Executive_40	10	42

(319 rows)

## telecom\_query\_03.sql

### Query

```
-- Customer using the most roaming minutes in 2000

SELECT Cust_Name,
Calendar_Year,
SUM(Total_Roaming_minutes) AS TOTAL_ROAMING
FROM Billing_Fact Bill_Fact,
Date_Dimension Date_Dim,
Customer_Details_Dimension Cust_Dim
WHERE Bill_Fact.Cust_Key = Cust_Dim.Cust_Key
AND Bill_Fact.Date_Key = Date_Dim.Date_Key
AND Date_Dim.Calendar_Year = 2000
AND Bill_Fact.Roaming_Flag = 1
GROUP BY Cust_Name, Calendar_Year
ORDER BY Cust_Name,
TOTAL_ROAMING DESC;
```

### Example

Cust_Name	Calendar_Year	Total_Roaming
(null)	2000	361
Abigail	2000	323
Andrew	2000	216
Anthony	2000	384
AshleyJack	2000	378
Ava	2000	243

(29 rows)

**telecom\_query\_04.sql****Query**

```
-- Total service tax and surcharge paid to government in 2000

SELECT  Calendar_Year,
        Calendar_Year_Month,
        SUM(Service_Tax) AS SERVICE_TAX,
        SUM(SURCHARGE) AS SURCHARGE
FROM    Billing_Fact Bill_Fact,
        Date_Dimension Date_Dim
WHERE   Bill_Fact.Date_Key = Date_Dim.Date_Key
        AND Date_Dim.Calendar_Year = 2000
GROUP BY Calendar_Year,Calendar_Year_Month
ORDER BY Calendar_Year,
        Calendar_Year_Month DESC;
```

**Example**

Calendar_Year	Calendar_Year_Month	Service_Tax	Surcharge
2000	12	67.405	6.7405
2000	11	45.615	4.5615
2000	10	49.315	4.9315
2000	9	63.495	6.3495
2000	8	62.53	6.253

(12 rows)

**telecom\_query\_05.sql****Query**

```
-- Total number of calls with abnormal termination code

SELECT  Calendar_Year,
        Termination_Description,
        SUM(Number_Of_Calls) AS CALL_COUNT
FROM    Billing_Fact Bill_Fact,
        Date_Dimension Date_Dim,
        Call_Termination_Dimension Term_Dim
WHERE   Bill_Fact.Date_Key = Date_Dim.Date_Key
        AND Bill_Fact.Termination_Key = Term_Dim.Termination_Key
        AND Term_Dim.Termination_Type = 'Abnormal'
GROUP BY Calendar_Year, Termination_Description
ORDER BY Calendar_Year,
        CALL_COUNT;
```

**Example**

Calendar_Year	Termination_Description	Call_Count
2000	Abnormal Call Termination	2010
2001	Abnormal Call Termination	873

(2 rows)

## telecom\_query\_06.sql

### Query

```
-- Show average phone usage by customer age group
-- (5-year intervals) for a given month
SELECT calendar_year_month,
       (cust_age - MOD(cust_age, 5)) AS age_group,
       count(DISTINCT A.cust_key) AS num_customers,
       ROUND(AVG(number_of_calls)) AS avg_num_calls,
       ROUND(AVG(calls_duration)) AS avg_call_duration,
       ROUND(AVG(total_minutes)) AS avg_total_mins
FROM   Billing_Fact A,
       Date_Dimension B,
       Customer_Details_Dimension C
WHERE  A.date_key = B.date_key
       AND A.cust_key = C.cust_key
       AND calendar_year_month = '2004-8'
GROUP BY calendar_year_month,
         (cust_age - MOD(cust_age, 5))
ORDER BY (cust_age - MOD(cust_age, 5));
```

### Example

calendar_year_month	age_group	num_customers	avg_num_calls	avg_call_duration	avg_total_mins
2004-8	24	10	2871	8	25
2004-8	24	15	2903	7	25
2004-8	25	20	2790	7	24
2004-8	25	25	2787	8	25
2004-8	25	30	2768	7	24
2004-8	24	35	2843	7	25
2004-8	25	40	2873	8	25
2004-8	24	45	2856	8	24
2004-8	25	50	2926	8	24
2004-8	24	55	2809	8	25
2004-8	24	60	2836	7	25
2004-8	24	65	2855	7	24
2004-8	25	70	2772	7	24
2004-8	25	75	2798	8	24
2004-8	25	80	572	7	25

(15 rows)



## VMart Example Database

The VMart Example Database is based on a fictional department store chain that has an online store front in addition to traditional brick and mortar stores. This database contains the following schemas:


- **Public Schema** (page 67)
- **Store Schema** (page 73)
- **Online\_Sales Schema** (page 76)

Each schema is described in a separate section.

**Note:** The example VMart queries in subsequent sections are for illustrative purposes only. Your results could differ slightly from those listed in this guide.

## Public Schema

The Public schema is a snowflake schema. The following graphic illustrates the Public schema and its relationships with tables in the Online\_Sales and Store schemas.



### inventory\_fact

This table contains information about each product in inventory.

Column Name	Data Type	NULLs
Date_key	INTEGER	No

Product_key	INTEGER	No
Product_version	INTEGER	No
Warehouse_key	INTEGER	No
Qty_in_stock	INTEGER	No

### customer\_dimension

This table contains information about all the retail chain's customers.

Column Name	Data Type	NULLs
Customer_key	INTEGER	No
Customer_type	VARCHAR(16)	Yes
Customer_name	VARCHAR(256)	Yes
Customer_gender	VARCHAR(8)	Yes
Title	VARCHAR(8)	Yes
Household_id	INTEGER	Yes
Customer_address	VARCHAR(256)	Yes
Customer_city	VARCHAR(64)	Yes
Customer_state	CHAR(2)	Yes
Customer_region	VARCHAR(64)	Yes
Marital_status	VARCHAR(32)	Yes
Customer_age	INTEGER	Yes
Number_of_children	INTEGER	Yes
Annual_income	INTEGER	Yes
Occupation	VARCHAR(64)	Yes
Largest_bill_amount	INTEGER	Yes
Store_membership_card	INTEGER	Yes
Customer_since	DATE	Yes
Deal_stage	VARCHAR(32)	Yes
Deal_size	INTEGER	Yes
Last_deal_update	DATE	Yes

**date\_dimension**

This table contains information about dates. It is generated from a file containing correct date/time data.

Column Name	Data Type	NULLs
Date_key	INTEGER	No
Date	DATE	Yes
Full_date_description	VARCHAR(18)	Yes
Day_of_week	VARCHAR(9)	Yes
Day_number_in_calendar_month	INTEGER	Yes
Day_number_in_calendar_year	INTEGER	Yes
Day_number_in_fiscal_month	INTEGER	Yes
Day_number_in_fiscal_year	INTEGER	Yes
Last_day_in_week_indicator	INTEGER	Yes
Last_day_in_month_indicator	INTEGER	Yes
Calendar_week_number_in_year	INTEGER	Yes
Calendar_month_name	VARCHAR(9)	Yes
Calendar_month_number_in_year	INTEGER	Yes
Calendar_year_month	CHAR(7)	Yes
Calendar_quarter	INTEGER	Yes
Calendar_year_quarter	CHAR(7)	Yes
Calendar_half_year	INTEGER	Yes
Calendar_year	INTEGER	Yes
Holiday_indicator	VARCHAR(10)	Yes
Weekday_indicator	CHAR(7)	Yes
Selling_season	VARCHAR(32)	Yes

**employee\_dimension**

This table contains information about all the people who work for the retail chain.

Column Name	Data Type	NULLs
Employee_key	INTEGER	No
Employee_gender	VARCHAR(8)	Yes
Employee_title	VARCHAR(8)	Yes

## Getting Started Guide

---

Employee_first_name	VARCHAR(64)	Yes
Employee_middle_initial	VARCHAR(8)	Yes
Employee_last_name	VARCHAR(64)	Yes
Employee_age	INTEGER	Yes
Hire_date	DATE	Yes
Employee_street_address	VARCHAR(256)	Yes
Employee_city	VARCHAR(64)	Yes
Employee_state	CHAR(2)	Yes
Employee_region	CHAR(32)	Yes
Job_title	VARCHAR(64)	Yes
Reports_to	INTEGER	Yes
Salaried_flag	INTEGER	Yes
Annual_salary	INTEGER	Yes
Hourly_rate	FLOAT	Yes
Vacation_days	INTEGER	Yes

### product\_dimension

The product\_dimension table describes all products sold by the department store chain.

Column Name	Data Type	NULLs
Product_key	INTEGER	No
Product_version	INTEGER	No
Product_description	VARCHAR(128)	Yes
Sku_number	CHAR(32)	Yes
Category_description	CHAR(32)	Yes
Department_description	CHAR(32)	Yes
Package_type_description	CHAR(32)	Yes
Package_size	CHAR(32)	Yes
Fat_content	INTEGER	Yes
Diet_type	CHAR(32)	Yes
Weight	INTEGER	Yes
Weight_units_of_measure	CHAR(32)	Yes
Shelf_width	INTEGER	Yes

Shelf_height	INTEGER	Yes
Shelf_depth	INTEGER	Yes
Product_price	INTEGER	Yes
Product_cost	INTEGER	Yes
Lowest_competitor_price	INTEGER	Yes
Highest_competitor_price	INTEGER	Yes
Average_competitor_price	INTEGER	Yes
Discontinued_flag	INTEGER	Yes

### promotion\_dimension

The promotion\_dimension describes every promotion ever done by the retail chain.

Column Name	Data Type	NULLs
Promotion_key	INTEGER	No
Promotion_name	VARCHAR(128)	Yes
Price_reduction_type	VARCHAR(32)	Yes
Promotion_media_type	VARCHAR(32)	Yes
Ad_type	VARCHAR(32)	Yes
Display_type	VARCHAR(32)	Yes
Coupon_type	VARCHAR(32)	Yes
Ad_media_name	VARCHAR(32)	Yes
Display_provider	VARCHAR(128)	Yes
Promotion_cost	INTEGER	Yes
Promotion_begin_date	DATE	Yes
Promotion_end_date	DATE	Yes

### shipping\_dimension

This table contains information about the shipping companies that the retail chain uses.

Column Name	Data Type	NULLs
Shipping_key	INTEGER	No
Ship_type	CHAR(30)	Yes
Ship_mode	CHAR(10)	Yes

Ship_carrier	CHAR(20)	Yes
--------------	----------	-----

### vendor\_dimension

This table contains information about each vendor that provides products sold through the retail chain.

Column Name	Data Type	NULLs
Vendor_key	INTEGER	No
Vendor_name	VARCHAR(64)	Yes
Vendor_address	VARCHAR(64)	Yes
Vendor_city	VARCHAR(64)	Yes
Vendor_state	CHAR(2)	Yes
Vendor_region	VARCHAR(32)	Yes
Deal_size	INTEGER	Yes
Last_deal_update	DATE	Yes


### warehouse\_dimension

This table provides information about each of the chain's warehouses.

Column Name	Data Type	NULLs
Warehouse_key	INTEGER	No
Warehouse_name	VARCHAR(20)	Yes
Warehouse_address	VARCHAR(256)	Yes
Warehouse_city	VARCHAR(60)	Yes
Warehouse_state	CHAR(2)	Yes
Warehouse_region	VARCHAR(32)	Yes

## Store Schema

The Store schema is a snowflake schema that contains information about the retail chain's brick and mortar stores. The following graphic illustrates the Store schema and its relationship with tables in the Public schema.



### store\_orders\_fact

This table contains information about all orders made at the company's brick and mortar stores.

Column Name	Data Type	NULLs
Product_key	INTEGER	No
Product_version	INTEGER	No
Store_key	INTEGER	No

## Getting Started Guide

---

Vendor_key	INTEGER	No
Employee_key	INTEGER	No
Order_number	INTEGER	No
Date_ordered	DATE	Yes
Date_shipped	DATE	Yes
Expected_delivery_date	DATE	Yes
Date_delivered	DATE	Yes
Quantity_ordered	INTEGER	Yes
Quantity_delivered	INTEGER	Yes
Shipper_name	VARCHAR(32)	Yes
Unit_price	INTEGER	Yes
Shipping_cost	INTEGER	Yes
Total_order_cost	INTEGER	Yes
Quantity_in_stock	INTEGER	Yes
Reorder_level	INTEGER	Yes
Overstock_ceiling	INTEGER	Yes

### store\_sales\_fact

This table contains information about all sales made at the company's brick and mortar stores.

Column Name	Data Type	NULLs
Date_key	INTEGER	No
Product_key	INTEGER	No
Product_version	INTEGER	No
Store_key	INTEGER	No
Promotion_key	INTEGER	No
Customer_key	INTEGER	No
Employee_key	INTEGER	No
Pos_transaction_number	INTEGER	No
Sales_quantity	INTEGER	Yes
Sales_dollar_amount	INTEGER	Yes
Cost_dollar_amount	INTEGER	Yes
Gross_profit_dollar_amount	INTEGER	Yes

Transaction_type	VARCHAR(16)	Yes
Transaction_time	TIME	Yes
Tender_type	VARCHAR(8)	Yes


### store\_dimension

This table contains information about each brick and mortar store within the retail chain.

Column Name	Data Type	NULLs
Store_key	INTEGER	No
Store_name	VARCHAR(64)	Yes
Store_number	INTEGER	Yes
Store_address	VARCHAR(256)	Yes
Store_city	VARCHAR(64)	Yes
Store_state	CHAR(2)	Yes
Store_region	VARCHAR(64)	Yes
Floor_plan_type	VARCHAR(32)	Yes
Photo_processing_type	VARCHAR(32)	Yes
Financial_service_type	VARCHAR(32)	Yes
Selling_square_footage	INTEGER	Yes
Total_square_footage	INTEGER	Yes
First_open_date	DATE	Yes
Last_remodel_date	DATE	Yes
Number_of_employees	INTEGER	Yes
Annual_shrinkage	INTEGER	Yes
Foot_traffic	INTEGER	Yes
Monthly_rent_cost	INTEGER	Yes

## Online\_Sales Schema

The Online\_Sales schema is a snowflake schema. The following graphic illustrates the Online\_Sales schema and its relationship with tables in the Public schema.



### online\_sales\_fact

The online\_sales\_fact table describes all the items purchased through the online store front.

Column Name	Data Type	NULLS
Sale_date_key	INTEGER	No
Ship_date_key	INTEGER	No
Product_key	INTEGER	No
Product_version	INTEGER	No

Customer_key	INTEGER	No
Call_center_key	INTEGER	No
Online_page_key	INTEGER	No
Shipping_key	INTEGER	No
Warehouse_key	INTEGER	No
Promotion_key	INTEGER	No
Pos_transaction_number	INTEGER	No
Sales_quantity	INTEGER	Yes
Sales_dollar_amount	FLOAT	Yes
Ship_dollar_amount	FLOAT	Yes
Net_dollar_amount	FLOAT	Yes
Cost_dollar_amount	FLOAT	Yes
Gross_profit_dollar_amount	FLOAT	Yes
Transaction_type	VARCHAR(16)	Yes

### call\_center\_dimension

The call\_center\_dimension table describes all the chain's call centers.

Column Name	Data Type	NULLs
Call_center_key	INTEGER	No
Cc_closed_date	DATE	Yes
Cc_open_date	DATE	Yes
Cc_name	VARCHAR(50)	Yes
Cc_class	VARCHAR(50)	Yes
Cc_employees	INTEGER	Yes
Cc_hours	CHAR(20)	Yes
Cc_manager	VARCHAR(40)	Yes
Cc_address	VARCHAR(256)	Yes
Cc_city	VARCHAR(64)	Yes
Cc_state	CHAR(2)	Yes
Cc_region	VARCHAR(64)	Yes

## online\_page\_dimension

The online\_page\_dimension table describes all the pages in the online store front.

Column Name	Data Type	NULLs
Online_page_key	INTEGER	No
Start_date	DATE	Yes
End_date	DATE	Yes
Page_number	INTEGER	Yes
Page_description	VARCHAR(100)	Yes
Page_type	VARCHAR(100)	Yes

## vmart\_query\_01.sql

### Query

```
-- vmart_query_01.sql
-- FROM clause subquery
-- Return the values for five products with the
-- lowest-fat content in the Dairy department
```

```
SELECT fat_content
FROM (
  SELECT DISTINCT fat_content
  FROM product_dimension
  WHERE department_description
  IN ('Dairy') ) AS food
ORDER BY fat_content
LIMIT 5
```

### Example

```
fat_content
-----
      80
      81
      82
      83
      84
(5 rows)
```

## vmart\_query\_02.sql

### Query

```
-- vmart_query_02.sql
```

```
-- WHERE clause subquery
-- Asks for all orders placed by stores located in Massachusetts
-- and by vendors located elsewhere before March 1, 2003:
```

```
SELECT order_number, date_ordered
FROM store.store_orders_fact orders
WHERE orders.store_key IN (
  SELECT store_key
  FROM store.store_dimension
  WHERE store_state = 'MA')
  AND orders.vendor_key NOT IN (
  SELECT vendor_key
  FROM public.vendor_dimension
  WHERE vendor_state = 'MA')
  AND date_ordered < '2003-03-01';
```

### Example

order_number	date_ordered
1584	2003-01-05
39396	2003-02-05
83738	2003-01-04
8898	2003-02-05
69712	2003-01-06
74866	2003-01-03
75397	2003-02-06
60069	2003-01-10
85854	2003-01-03
21982	2003-02-03
47766	2003-02-07
31284	2003-02-03
28005	2003-01-09
79963	2003-02-01
19515	2003-02-05

(15 rows)

## vmart\_query\_03.sql

### Query

```
-- vmart_query_03.sql
-- Noncorrelated subquery
-- Requests female and male customers with the maximum
-- annual income from customers
```

```
SELECT customer_name, annual_income
FROM public.customer_dimension
WHERE (customer_gender, annual_income) IN (
  SELECT customer_gender, MAX(annual_income)
  FROM public.customer_dimension
  GROUP BY customer_gender);
```

### Example

customer_name	annual_income
Meghan U. Miller	999960
Michael T. Jackson	999981

(2 rows)

### vmart\_query\_04.sql

#### Query

```
-- vmart_query_04.sql
-- IN predicate
-- Find all products supplied by stores in Massachusetts

SELECT DISTINCT s.product_key, p.product_description
FROM store.store_sales_fact s, public.product_dimension p
WHERE s.product_key = p.product_key
AND s.product_version = p.product_version AND s.store_key IN (
    SELECT store_key
    FROM store.store_dimension
    WHERE store_state = 'MA')
ORDER BY s.product_key;
```

#### Example

product_key	product_description
1	Brand #1 butter
1	Brand #2 bagels
2	Brand #3 lamb
2	Brand #4 brandy
2	Brand #5 golf clubs
2	Brand #6 chicken noodle soup
3	Brand #10 ground beef
3	Brand #11 vanilla ice cream
3	Brand #7 canned chicken broth
3	Brand #8 halibut
3	Brand #9 camera case
4	Brand #12 rash ointment
4	Brand #13 low fat milk
4	Brand #14 chocolate chip cookies
4	Brand #15 silver polishing cream

(15 rows)

### vmart\_query\_05.sql

#### Query

```
-- vmart_query_05.sql
-- EXISTS predicate
-- Get a list of all the orders placed by all stores on
-- January 2, 2003 for the vendors with records in the
-- vendor_dimension table

SELECT store_key, order_number, date_ordered
```

```

FROM store.store_orders_fact
WHERE EXISTS (
  SELECT 1
  FROM public.vendor_dimension
  WHERE public.vendor_dimension.vendor_key =
store.store_orders_fact.vendor_key)
  AND date_ordered = '2003-01-02';

```

### Example

store_key	order_number	date_ordered
213	148816	2003-01-02
111	184148	2003-01-02
89	279732	2003-01-02
115	3677	2003-01-02
212	117057	2003-01-02
65	198323	2003-01-02
238	246942	2003-01-02
140	257554	2003-01-02
43	79699	2003-01-02
219	240925	2003-01-02
249	4789	2003-01-02
12	234175	2003-01-02
119	176211	2003-01-02
107	249378	2003-01-02
228	251959	2003-01-02

(15 rows)

## vmart\_query\_06.sql

### Query

```

-- vmart_query_06.sql
-- EXISTS predicate
-- Orders placed by the vendor who got the best deal
-- on January 4, 2004

SELECT store_key, order_number, date_ordered
FROM store.store_orders_fact ord, public.vendor_dimension vd
WHERE ord.vendor_key = vd.vendor_key
AND vd.deal_size IN (
  SELECT MAX(deal_size)
  FROM public.vendor_dimension)
AND date_ordered = '2004-01-04';

```

### Example

store_key	order_number	date_ordered
168	51386	2004-01-04
88	73316	2004-01-04
241	68520	2004-01-04

(3 rows)

## vmart\_query\_07.sql

### Query

```
-- vmart_query_07.sql
-- Multicolumn subquery
-- Which products have the highest cost,
-- grouped by category and department

SELECT product_description, sku_number, department_description
FROM public.product_dimension
WHERE (category_description, department_description, product_cost) IN (
    SELECT category_description, department_description,
    MAX(product_cost) FROM product_dimension
    GROUP BY category_description, department_description);
```

### Example

product_description	sku_number	department_description
Brand #7979 cheddar cheese	SKU-#7979	Dairy
Brand #2197 sushi	SKU-#2197	Seafood
Brand #28902 strawberries	SKU-#28902	Produce
Brand #54595 sliced turkey	SKU-#54595	Meat
Brand #26127 chocolate chip cookies	SKU-#26127	Bakery
Brand #32608 chocolate ice cream	SKU-#32608	Frozen Goods
Brand #27213 shrimp	SKU-#27213	Seafood
Brand #12533 canned green beans	SKU-#12533	Canned Goods
Brand #3957 canned tuna	SKU-#3957	Canned Goods
Brand #22103 cod	SKU-#22103	Seafood

(10 rows)

## vmart\_query\_08.sql

### Query

```
-- vmart_query_08.sql
-- Using pre-join projections to answer subqueries
-- between online_sales_fact and online_page_dimension

SELECT page_description, page_type, start_date, end_date
FROM online_sales.online_sales_fact f, online_sales.online_page_dimension d
WHERE f.online_page_key = d.online_page_key
AND page_number IN
    (SELECT MAX(page_number)
    FROM online_sales.online_page_dimension)
AND page_type = 'monthly' AND start_date = '2003-06-02';
```

### Example

page_description	page_type	start_date	end_date
Online Page Description #1	monthly	2003-06-02	2003-06-11

```

Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
Online Page Description #1 | monthly | 2003-06-02 | 2003-06-11
(12 rows)

```

## vmart\_query\_09.sql

### Query

```

-- vmart_query_09.sql
-- Equi join
-- Joins online_sales_fact table and the call_center_dimension
-- table with the ON clause

SELECT sales_quantity, sales_dollar_amount, transaction_type, cc_name
FROM online_sales.online_sales_fact
INNER JOIN online_sales.call_center_dimension
ON (online_sales.online_sales_fact.call_center_key
    = online_sales.call_center_dimension.call_center_key
    AND sale_date_key = 156)
ORDER BY sales_dollar_amount DESC;

```

### Example

sales_quantity	sales_dollar_amount	transaction_type	cc_name
7	513	purchase	Southeastern
3	439	purchase	Southwest
10	425	purchase	North Midwest
5	364	purchase	North Midwest
7	320	purchase	Pacific Northwest
2	314	purchase	Pacific Northwest
9	299	purchase	California
9	265	purchase	Central Midwest
9	247	purchase	Southwest
6	221	purchase	Central Midwest
1	198	purchase	Central Midwest
5	177	purchase	Central Midwest
7	131	purchase	Southwest
10	110	purchase	North Midwest
2	-329	return	Other

(15 rows)

# Installing the Example Database

---

Vertica provides a one-step installation script that lets you create an example database and start using it immediately. The scripts are located in `/opt/vertica/sbin` and are called:

- `install_example` — Creates a database on the default port (5433), generates data, creates the schema and a default superprojection, and loads the data.
  - `delete_example` — Drops the database
- 

## Notes

- Before you can install the example, you must accept the EULA (one time only) using the Administration Tools.
  - For a more advanced but equally-simple example using the Vertica databases, see the [Tutorial](#) (page 87) in the Getting Started Guide.
- 

## Installing the Example Database

- 1 In a terminal window, log in as the DBA user:

```
# su dbadmin
```

- 2 Change to the `/example` directory and run the install script:

```
$ /opt/vertica/sbin/install_example <example_name>
```

where `<example_name>` is one of the following: ClickStream, CreditHistory, Retail, Stock, TickStore, Telecom, VMart.


**Note:** If you have not already done so, you must accept the EULA (one time only) using the Administration Tools. You'll do that in **Step 2** (page 89) of the Tutorial.

- 3 Connect to the database:

```
$ /opt/vertica/bin/vsql
```

Alternatively connect to the database using the Administration Tools and select **Connect to Database** from the Main Menu:

```
$ admintools
```



- 4 Run a simple query. For example, to count all the records in the `store_sales_fact` table:  
=> `SELECT COUNT(1) FROM store.store_sales_fact;`

The example database log files, `ExampleDelete.txt` and `ExampleInstall.txt`, are written to `/opt/vertica/examples/log`.

### Example Database Scripts

Each of the example directories contains query script files that you can use. While you can create your own queries, Vertica provides scripts to get you started quickly. All SQL scripts used by the `install_example` installation script are available for review in the following folders. You can use the scripts as templates for your own applications.

- `/opt/vertica/examples/ClickStream_Schema`
- `/opt/vertica/examples/CreditHistory_Schema`
- `/opt/vertica/examples/Retail_Schema`
- `/opt/vertica/examples/Stock_Schema`
- `/opt/vertica/examples/TickStore_Schema`
- `/opt/vertica/examples/Telecom_Schema`
- `/opt/vertica/examples/VMart_Schema`

The following table describes the scripts available, where *{identifier}* is the name of the example database:

Script Name	Description
<code>{identifier}_count_data.sql</code>	Counts rows of all example database tables
<code>{identifier}_define_schema.sql</code>	Defines the schema for each table
<code>{identifier}_gen</code>	Is the sample data generator
<code>{identifier}_load_data.sql</code>	Loads data to the corresponding tables using COPY DIRECT
<code>{identifier}_queries.sql</code>	Contains all sample queries

{identifier}_schema_drop.sql	Drops all example database tables
{identifier}_query_##.sql	Are the individual queries; for example query #1 through “n”

**Note:** The number of example databases you create is limited only by the disk space available on your system.

### Deleting the One-Step Example Database

To remove an example database:

- 1 Log in as the DBA user; for example:

```
# su dbadmin
```

- 2 Run the `delete_example` script:

```
$ /opt/vertica/sbin/delete_example <example_name>
```

where *<example\_name>* is the name of the example database you provided to the install script.

---

# Tutorial: Setting up an Example Database

---

## Prerequisites

Before you proceed, Vertica must be installed on one host or a cluster of hosts, as described in the Installation Guide. Vertica recommends a minimum of three hosts in the cluster.

## Audience

This tutorial targets anyone who wants to learn how to create and run a Vertica database. No special database knowledge is required at this point, though a rudimentary knowledge of basic SQL commands could be useful when you begin to run queries.

## Objectives

You'll follow the simple steps below to create a fully-functioning, comprehensive design using one of the schemas described in *Example Databases* (page 11).

- 1 **Set up the example environment** (page 88)
- 2 **Create the example database** (page 89)
- 3 **Define the database schema** (page 91)
- 4 **Load the data** (page 92)
- 5 **Create a comprehensive design** (page 93)
- 6 **Connect to the database and run a simple query** (page 100)
- 7 **Test the design** (page 100)
- 8 **(Optional) Generate custom data files** (page 102)

It's that easy! The whole process takes about 15 minutes, and when you are finished, you can proceed directly to *Running Simple Queries* (page 104).

## Notes

- Although the **VMart database** (page 66) is used throughout this tutorial, the steps are the same for all of the **example databases** (page 11). If you choose a different database, replace VMart with Clickstream, Credit History, Retail Sales, Stock Exchange, or Telecom in each example provided.
- This tutorial uses a Vertica-provided query, but you can follow the same set of procedures later, when you create your own design and use your own queries file.
- If, in the future, you have a query that you want to optimize, you can create an enhanced (incremental) design with additional projections to be tuned specifically for the query you provide. See *Creating a Query-specific Design Using the Database Designer* in the Administrator's Guide.
- For additional information about managing your designs, see *Designing a Physical Schema* in the Administrator's Guide.

## Step 1: Set Up the Example Environment

In this procedure, you set up the example Vmart database environment.

- 1 Stop all databases running on the same host on which you plan to install your example database.

- 2 Choose the **example database** (page 11) that you want to use.

**Note:** All procedures in this tutorial use the **Vmart example database** (page 66).

- 3 Log in to a terminal using the database administrator account that was created during product installation.

The default account name is `dbadmin`.

- 4 Create a directory for the example files on the Administration Host:

```
$ mkdir examples
```

Do not use the default data directory `/home/dbadmin`.

- 5 Copy the files to the sample directory.

If you installed the product rpm on a database server, the example databases are located in `/opt/vertica/examples` on the host.

- 6 Set your current directory to the example database directory your created:

```
$ cd examples
```

**Note:** Do not change directories while following this tutorial. Some of the steps depend on being set to a specific directory.

- 7 Run the sample data generator program:

```
$ ./vmart_gen
```

Let the program run with the default parameters, which you can review in the README file.

**Note:** If you want to generate a smaller data set, see **Step 8: (Optional) Generate Custom Data Files** (page 102) for a list of parameters you can include in the sample generator program.

```
Using default parameters
datadirectory = ./
numfiles = 1
seed = 20177
null = ''
timefile = Time.txt
numfactsalesrows = 5000000
numfactorderrows = 300000
numprodkeys = 60000
numstorekeys = 250
numpromokeys = 1000
numvendkeys = 50
numcustkeys = 50000
numempkeys = 10000
numwarehousekeys = 100
numshippingkeys = 100
numonlinepagekeys = 1000
numcallcenterkeys = 200
numfactonlinesalesrows = 5000000
numinventoryfactrows = 300000
gen_load_script = false
Data Generated successfully !
```

If the `vmart_gen` executable does not work correctly, recompile it, as follows, and run the sample data generator script again. For example:

1. `$ g++ vmart_gen.cpp -o vmart_gen`
2. `$ chmod +x vmart_gen`
3. `$ ./vmart_gen`

(This example uses the GNU C++ compiler, which is a **free download** (<http://gcc.gnu.org/>). You can use any other C++ compiler.)

**Tip:** If you are using VMware, the fact table load could fail. Specify a smaller fact table size, such as 1000000 (1M) rows, as described in **Step 8: (Optional) Generate Custom Data Files** (page 102). The maximum size of a bulk load depends on the system resources and cannot be determined accurately.

## Step 2: Create the Example Database


In this procedure, you create the example database.

- 1 Run the Administration Tools.


```
$ /opt/vertica/bin/admintools
```

**Note:** See the **Administration Tools Keystrokes** (see "**Using the Graphical User Interface**" on page 106) for a quick reference. If you are using a remote terminal application, such as PuTTY or a Cygwin bash shell, see **Notes for Remote Terminal Users** (page 107).

- 2 Accept the license agreement (once only).
- 3 Specify the location of your license key file (once only).
- 4 From the Administration Tools Main Menu, click **Configuration Menu** and click **OK**.
- 5 Click **Create Database** and click **OK**.




- 6 Name the database **vmartdb** and click **OK**.



- 7 Click **OK** to bypass the password, and click **Yes** to confirm.

**Note:** There is no need for a database superuser password in this tutorial. When you create a production database, however, always specify a superuser password. Otherwise, the database is permanently set to trust authentication (no passwords).


- 8 Select the hosts you want to include in the database cluster and click **OK**. This example creates the `vmartdb` database on a 4-host cluster.



- 9 Click **OK** to select the default paths for the data and catalog directories.

- Catalog and data paths must contain only alphanumeric characters and cannot have leading space characters. Failure to comply with these restrictions could result in database creation failure.
- When you create a production database, you'll likely specify other locations than the default. See Prepare Disk Storage Locations in the Administrator's Guide for more information.

- 10 Click **Yes** to create the database.



During database creation, Vertica automatically creates a set of node definitions based on the database name and the names of the hosts you selected and returns a success message.

- 11 Click **OK** to close the message.

### Step 3: Define the Database Schema

Now that you have created a database, define the schema.

- 1 On the Administration Tools Configuration Menu, click **Main Menu** and click **OK**.
- 2 Click **Connect to Database** and click **OK**.

You'll see the following prompt:

```

Welcome to the vsql, Vertica_Database v5.0.x interactive terminal.
Type: \h for help with SQL commands
      \? for help with vsql commands
      \g or terminate with semicolon to execute query
      \q to quit
vmartdb=>

```

- 3 To create the logical schema, run the SQL schema definition script using the \i meta-command in vsql:

```
vmartdb=> \i vmart_define_schema.sql
```

A series of CREATE TABLE and ALTER TABLE statement scrolls on the terminal window:

```
vmartdb=> \i vmart_define_schema.sql
CREATE SCHEMA
CREATE SCHEMA
CREATE TABLE
ALTER TABLE
CREATE TABLE
CREATE TABLE
ALTER TABLE
CREATE TABLE
ALTER TABLE
CREATE TABLE
CREATE TABLE
CREATE TABLE
ALTER TABLE
vmartdb=>
```

The `vmart_define_schema.sql` file creates the tables and referential integrity constraints that make up the logical schema.

## Step 4: Load the Data

In this brief step, you'll load data into the schema you created in the previous step. Vertica automatically creates a superprojection for each table into which data is loaded.

- 1 Load data into the VMart database using the `vmart_load_data.sql` script.

```
vmartdb=> \i vmart_load_data.sql
```

```

      200
(1 row)

Rows Loaded
-----
      5000000
(1 row)

Rows Loaded
-----
      300000
(1 row)

Rows Loaded
-----
      5000000
(1 row)

Rows Loaded
-----
      300000
(1 row)

vmartdb=> █
```

**Note:** It could take several minutes to load the default five-million row fact table on a typical hardware cluster. You can check the load by examining the `vertica.log` file, as described in Monitoring the Log Files in the Administrator's Guide.

## Step 5: Create a Comprehensive Design

This procedure guides you through creating a comprehensive design and assumes you have already performed the following prerequisite steps:

- 1 **Set up the example environment** (page 88)
- 2 **Created the example database** (page 89)
- 3 **Defined the database schema** (page 91)
- 4 **Loaded the data** (page 92)

**Note:** Remember you can always create an incremental design later; for example, if you have a query that you want to optimize. See Creating a Query-specific Design Using the Database Designer in the Administrator's Guide.

- 1 Type `\q` to exit the vsql session and return to the Main Menu in the Administration Tools. Alternatively, restart the Administrative Tools:  


```
$ /opt/vertica/bin/admintools
```
- 2 From the **Main Menu**, click **Configuration Menu** and click **OK**.
- 3 From the **Configuration Menu**, click **Run Database Designer**, and click **OK**.

- 4 Select **vmartdb** as the database and click **OK**.  
If you are asked to enter the password for the database, click **OK** to bypass. No password was assigned in **Step 2: Create the Example Database** (page 89), so you do not need to enter one now.


- 5 Click **OK** to accept the default directory for storing Database Designer output and log files.  
**Note this location.**

**Note:** If you choose to not deploy your design now, the Database Designer saves the SQL script to implement the design in this directory where you can review and manually deploy it later.

- 6 In the **Database Designer** window, enter a name for the design (this example uses **vmart\_design**) and click **OK**.




- 7 In the **Design Type** window, click **Comprehensive** to create a complete initial design, and click **OK**.



- 8 Select the schemas for your design, and click **OK**.

If you include a schema that contains tables without data, the Administration Tools returns a message notifying you that designing for tables without data could be suboptimal. You can choose to continue, but Vertica recommends that you click Cancel and deselect the schemas that contain empty tables before you proceed.

**Note:** In this example, the Vmart design is a multi-schema database, so be sure to select all three options: public, store, and online\_sales



- 9 In the **Design Options** window, accept the default of all three options described below and click **OK**.

Generally, you want to accept the default of enabling all three because the Database Designer is best positioned to generate a new comprehensive design and create a complete set of projections for the tables in the selected schema. The three options are:

- *Optimize with queries:* Efficiency of the design is substantially improved if the Database Designer can access sample queries.


Supplying the Database Designer with queries is especially important if you want to optimize the database design for query performance.

- *Update statistics:* Accurate statistics help the Database Designer choose the best strategy for data compression. If you select this option, the database statistics are updated to maximize design quality.

Note that updating statistics takes time and resources, so if the current statistics are up to date, this step is unnecessary. When in doubt, update statistics.


- *Deploy design:* The new design will be automatically deployed, which means that during deployment, new projections are added, some existing projections might be retained, and any unnecessary existing projections are removed. Any new projections are refreshed so that they are populated with data.

**Note:** For large databases, a full design session could take a long time, yet it is best to allow this process to complete uninterrupted. If the session must be canceled, use CTRL+C.




- 10** If you selected the **Optimize with queries** option, you are prompted for the location of the the query file. Type the full path to the file containing the queries that will be run on your database. In this example it is:

/examples/VMart\_Schema/vmart\_queries.sql



- 11** Choose the **K-safety value** you want. In this example, it is 1. Click **OK**.


**Note:** There will be no K-safe form if you are creating a comprehensive design on a single node. In that case, you can skip this step.



- 12** Choose the Database Designer's priority for the design (in this procedure choose **Balanced**) and click **OK**.

The options are:

- *Balanced* query/load performance tells the Database Designer to create a design that is balanced between database size and query performance.
- *Query* load performance creates a design focused on faster query performance, which might recommend additional projections. These projections could result in a larger database storage size.
- *Load* performance is optimized for loads, minimizing size of the database, potentially at the expense of query performance.



- 13** When the informational message displays, click **Proceed**.

The Database Designer:

- Sets up the design session
- Examines table data
- Loads queries from the query file you provided
- Creates the design
- Deploys the design or saves a SQL file containing the design, depending on what you selected for the Deploy design option in step 9.

You can watch the progress on the terminal window. The following image is just an example and might not match exactly what you see:

```
Creating design...
[ 6%] Analyzing data statistics... Completed 1 of 15 tables. Analyzing p
[ 13%] Analyzing data statistics... Completed 2 of 15 tables. Analyzing p
[ 13%] Analyzing data statistics... Completed 2 of 15 tables. Analyzing p
[ 26%] Analyzing data statistics... Completed 4 of 15 tables. Analyzing p
[ 40%] Analyzing data statistics... Completed 6 of 15 tables. Analyzing p
[ 66%] Analyzing data statistics... Completed 10 of 15 tables. Analyzing
[ 73%] Analyzing data statistics... Completed 11 of 15 tables. Analyzing
[ 93%] Analyzing data statistics... Completed 14 of 15 tables. Analyzing
[100%] Analyzing data statistics... Completed 15 of 15 tables. Analyzing
[100%] Analyzing data statistics... Completed 15 of 15 tables.

[ 0%] Optimizing for query performance... Completed 0 of 9 queries. Sett
[ 0%] Optimizing for query performance... Completed 0 of 9 queries. Sett
[ 0%] Optimizing for query performance... Completed 0 of 9 queries. Choc
[ 0%] Optimizing for query performance... Completed 0 of 9 queries. Choc
[ 66%] Optimizing for query performance... Completed 6 of 9 queries. Choc
[100%] Optimizing for query performance... Completed 9 of 9 queries.

[ 0%] Optimizing storage footprint... Completed 0 of 15 tables. Optimizi
[ 6%] Optimizing storage footprint... Completed 1 of 15 tables. Optimizi
[ 6%] Optimizing storage footprint... Completed 1 of 15 tables. Optimizi
[ 26%] Optimizing storage footprint... Completed 4 of 15 tables. Optimizi
[ 46%] Optimizing storage footprint... Completed 7 of 15 tables. Optimizi
[ 60%] Optimizing storage footprint... Completed 9 of 15 tables. Optimizi
[ 66%] Optimizing storage footprint... Completed 10 of 15 tables. Optimiz
[ 66%] Optimizing storage footprint... Completed 10 of 15 tables. Optimiz
[ 66%] Optimizing storage footprint... Completed 10 of 15 tables. Optimiz
[ 73%] Optimizing storage footprint... Completed 11 of 15 tables. Optimiz
[ 73%] Optimizing storage footprint... Completed 11 of 15 tables. Optimiz
[ 93%] Optimizing storage footprint... Completed 14 of 15 tables. Optimiz
[ 93%] Optimizing storage footprint... Completed 14 of 15 tables. Optimiz
[ 93%] Optimizing storage footprint... Completed 14 of 15 tables. Optimiz
[ 93%] Optimizing storage footprint... Completed 14 of 15 tables. Optimiz
[ 93%] Optimizing storage footprint... Completed 14 of 15 tables. Optimiz
[ 93%] Optimizing storage footprint... Completed 14 of 15 tables. Optimiz
[100%] Optimizing storage footprint... Completed 15 of 15 tables.

[100%] All done...

Query optimization results...
9 queries FULLY OPTIMIZED BY NEW PROJECTIONS

Deploying design...
Adding 32 new projections
Dropping 56 unnecessary existing projections

[100%] Deploying/Dropping projections... Completed 88 of 88 projections.

Completed 88 of 88 projections.

Database Designer finished.
```

- 14 When the Database Designer finishes, press **Enter** to return to the Administration Tools menu.

**Note:** The Database Designer creates a backup of the current design of your database before deploying the new design. This backup is stored in the output directory you entered in step 5, and is named `design_name_projection_backup_nnnnnnnnnn.sql`

## Step 6: Connect to the Database and Run a Simple Query

Proceeding directly from Step 5:

- 1 Click **Main Menu** and click **OK**.
- 2 Click **Connect to Database** and click **OK**.

The vsql welcome prompt displays:

```
Welcome to vsql, the Vertica Analytic Database v4.0.11-20100427010202
interactive terminal.
```

```
Type:  \h for help with SQL commands
        \? for help with vsql commands
        \g or terminate with semicolon to execute query
        \q to quit
```

```
vmartdb=>
```

- 3 Use the `\i` meta-command to execute the Vertica-provided example query script:

```
vmartdb=> \i vmart_query_03.sql
```

Your results will be similar to:

```
customer_name | annual_income
-----+-----
Emily G. Vogel |          999998
James M. McNulty |          999979
(2 rows)
```

See the following list for the example queries that Vertica supplies:

- **Clickstream Example Database** (page 13)
- **Credit History Example Database** (page 22)
- **Retail Sales Example Database** (page 31)
- **Stock Exchange Example Database** (page 44)
- **Telecom Example Database** (page 57)
- **VMart Example Database** (page 66)

### See Also

**Running Simple Queries** (page 104)

Creating a Query-specific Design Using the Database Designer in the Administrator's Guide

## Step 7: Test the Optimized Design

Check query execution times to test your optimized design:

- 1 Use the `vsq! \timing` meta-command to enable the display of query execution time in milliseconds.

Execute a SQL sample query script to test your schema and load scripts for errors.

**Note:** Include a sample of queries your users are likely to run against the database. If you don't have any real queries, just write simple SQL that collects counts on each of your tables. Alternatively, you can skip this step.

- 2 Execute several ad hoc queries
  1. Run Administration Tools and select Connect to Database.
  2. Use the `\i` meta-command to execute the query script; for example:

```
vmartdb=> \i vmart_query_01.sql
```

Once the database has been optimized, it should run queries efficiently. However, you might discover additional queries that you want to optimize. If this is the case, modify and update the design.

See [Modifying Designs and Creating a Query-specific Design Using the Database Designer](#) in the Administrator's Guide.

## Step 8: (Optional) Generate Custom Data Files

Each example database provided with Vertica includes a sample data generator program that produces output files whose names correspond to the tables in the logical schema. Each data generator has a similar set of input parameters that allow you to specify the number of rows of data to generate for any subset of the tables. To see a detailed list of the parameters for any example database, examine the README file in the example database directory.

**Tip:** You can repeat the tutorial using custom data files to test larger data sizes.

### Syntax

```
./example_gen [ --files files ]
               [ --seed seed ]
               [ --time_file path ]
               [ --fact_table_name rows ]
               [ --dimension_table_name rows ] ...
```

### Parameters

<code>example_gen</code>	Where <i>example</i> is one of the following: clickstream credithistory retail stock telecom vmart
<code>files files</code>	Splits the fact table data into the specified number of files. By default, the data generator produces a single, unnumbered fact table data file. If you specify a value of two (2) or more, the data generator numbers the files by appending an underscore character ( <code>_</code> ) and three digits to the file name, starting at <code>_001</code> . For example: <pre>./retail_gen --files 3</pre> produces: Retail_Sales_Fact_001.tbl Retail_Sales_Fact_002.tbl Retail_Sales_Fact_003.tbl Default: 1
<code>seed seed</code>	Is the seed for the pseudo-random number generator. If you use the same seed each time you run the data generator, you get the same data files (excluding external factors); for example, <code>seed 9999</code> . Default: 20177
<code>time_file path</code>	Is the pathname of the pre-computed time data input file used to generate the <b>Date Dimension</b> (see " <b>Date Dimension</b> " on page 32) table. Default: <code>./Time.txt</code>

	This Vertica-supplied file is provided for each example database and the date range may vary; for example 2000-2004 or 2003-2007.
<i>fact_table_name rows</i>	Is the name of the fact table in <i>example</i> followed by the number of rows of data to generate for the fact table. Default: 5,000,000 (five million)
<i>dimension_table_name rows</i>	Is the name of a dimension table in <i>example</i> (other than the Date_Dimension table) followed by the number of rows of data to generate for that dimension table.

## Notes

- The number of rows in Date\_Dimension tables is determined by the time data input file supplied with the example database.
- If you are using multiple fact table data files, make sure that your fact table load script(s) contain the correct file names as described in Using Load Scripts.

## Examples

```
./vmart_gen
./vmart_gen --files 3
/home/dbadmin/Vmart_Schema/examples/vmart_gen \
--seed 9999
--time_file /home/dbadmin/Vmart_Schema/examples/Time.txt \
--inventory_fact 100000 \
--customer_dimension 500 \
--date_dimension 500 \
--employee_dimension 50 \
--product_dimension 500 \
--promotion_dimension 500 \
--shipping_dimension 500 \
--vendor_dimension 500 \
--warehouse_dimension 500 \

--promotion_dimension 100
```

# Running Simple Queries

---

Each example database includes example SQL queries that represent the kinds of queries you might use in a production database. If you copy the query files to a client system, you can connect to the example database and execute the queries using any of the methods described in the Programmer's Guide.

To run an example query using `vsq` on a cluster host:

**1** Run Administration Tools and select Connect to Database.

```
Welcome to the vsq, Vertica_Database v5.0.x interactive terminal.
Type:  \h for help with SQL commands
        \? for help with vsq commands
        \g or terminate with semicolon to execute query
        \q to quit
vmartdb=>
```

**2** Use the `\i` meta-command to execute the query script:

```
vmartdb=> \i vmart_query_01.sql
```

See the following list for the example queries that Vertica supplies:

- **Clickstream Example Database** (page 13)
- **Credit History Example Database** (page 22)
- **Retail Sales Example Database** (page 31)
- **Stock Exchange Example Database** (page 44)
- **Telecom Example Database** (page 57)
- **VMart Example Database** (page 66)

# Cleanup Procedure

---

If you want to clean up your host and start over from scratch, use the following steps.

## Drop the database

- 1 In a terminal window, log in to the database administrator account that was created by the installation script. The default account name is `dbadmin`.
- 2 Run the Administration Tools.  

```
$ /opt/vertica/bin/admintools
```
- 3 If necessary, stop any running database (Main Men **Stop Database**).
- 4 Click **Configuration Menu** and click **OK**.
- 5 Click **Drop Database** and click **OK**.
- 6 In the **Select database to drop** window, select the database you want to drop and click **OK**.
- 7 Click **Yes** to confirm.
- 8 In the next window type `yes` (lowercase) to confirm and click **OK**.

## Uninstall Vertica

- 1 Perform the steps in Uninstalling Vertica in the Installation Guide.

## Other

- 1 Optionally remove the `dbadmin` account on all cluster hosts.
- 2 Remove any example database directories you created.

See Also

For complete descriptions of each Admin Tools dialog, refer to the Administration Tools Reference in the Administrator's Guide.

# Using the Graphical User Interface

---

This is only a quick reference. It is not a complete guide to keystroke usage. See Using the Administration Tools in the Administrator's Guide for full details.

<b>Return</b>	Run selected command.
<b>Tab</b>	Move cursor from OK to Cancel to Help to menu or to OK...
<b>Up/Down Arrow</b>	Move cursor up and down in menu, window, or help file.
<b>Space</b>	Select item in list.
<b>Character</b>	Select corresponding command from menu.

## Notes for Remote Terminal Users

---

The appearance of the graphical interface depends on the color and font settings used by your terminal window. The screen captures in this document were made using the default color and font settings in a PuTTY terminal application running on Windows XP.

**Note:** If you are using a remote terminal application, such as PuTTY or a Cygwin bash shell, make sure your window is at least 81 characters wide and 23 characters high

If you are using PuTTY, you can make the Administration Tools look like the screen captures in this document:

- 1 In a PuTTY window, right click the title area and select Change Settings.
- 2 Create or load a saved session.
- 3 In the Category dialog, click Window > Appearance.
- 4 In the Font settings, click the Change... button.
- 5 Select Font: Courier New: Regular Size: 10
- 6 Click Apply.

Repeat these steps for each existing session that you use to run the Administration Tools.

You can also change the translation to support UTF-8:

- 1 In a PuTTY window, right click the title area and select Change Settings.
- 2 Create or load a saved session.
- 3 In the Category dialog, click Window > Translation.
- 4 In the "Received data assumed to be in which character set" drop-down menu, select UTF-8.
- 5 Click Apply.



# Index

---

## A

About the Documentation • 2  
AccountType\_Dimension • 22, 23  
Acrobat • 6  
Adobe Acrobat • 6

## B

Billing\_Fact • 58, 59  
Bold text • 7  
Braces • 7  
Brackets • 7

## C

call\_center\_dimension • 78  
Call\_Termination\_Dimension • 58, 60  
Cleanup Procedure • 10, 107  
ClickStream Example Database • 11, 13, 102, 106  
ClickStream\_Fact • 14  
clickstream\_query\_01.sql • 17  
clickstream\_query\_02.sql • 18  
clickstream\_query\_03.sql • 19  
clickstream\_query\_04.sql • 19  
clickstream\_query\_05.sql • 20  
clickstream\_query\_06.sql • 20  
Colored bold text • 7  
Copyright Notice • 113  
Credit History Example Database • 11, 22, 102, 106  
CreditCard\_Dimension • 14, 15  
CreditHistory\_Fact • 22, 23  
credithistory\_query\_01.sql • 25  
credithistory\_query\_02.sql • 26  
credithistory\_query\_03.sql • 27  
credithistory\_query\_04.sql • 28  
credithistory\_query\_05.sql • 28  
credithistory\_query\_06.sql • 29  
Customer\_Details\_Dimension • 58, 60  
customer\_dimension • 69  
Customer\_Dimension • 14, 15, 22, 23

## D

date\_dimension • 70  
Date\_Dimension • 16, 24, 32, 47, 60, 104  
Documentation • 6

## E

Ellipses • 7  
employee\_dimension • 70  
Equipment\_Dimension • 58, 61  
Example Databases • 9, 11, 89, 90  
Exchange\_Dimension • 48

## F

Feature\_Dimension • 58, 61

## H

HTML • 6

## I

Indentation • 7  
Installing the Example Database • 86  
Institution\_Dimension • 22, 25  
inventory\_fact • 68  
IPAddress\_Dimension • 14, 16  
Italic text • 7

## M

Monospace text • 7  
MortgageType\_Dimension • 22, 25

## N

Notes for Remote Terminal Users • 91, 109  
Numbering\_Plan\_Dimension • 58, 61

## O

online\_page\_dimension • 79  
Online\_Sales Schema • 67, 77  
online\_sales\_fact • 77  
Overview to Getting Started • 9

## P

Page\_Dimension • 14, 16  
PDF • 6  
Printing Full Books • 4  
product\_dimension • 31, 71  
Product\_Dimension • 33  
promotion\_dimension • 32, 72  
Promotion\_Dimension • 34  
Public Schema • 67, 68

## R

Rate\_Plan\_Dimension • 58, 62  
Reading the Online Documentation • 2  
Retail Sales Example Database • 11, 31, 102, 106

- retail\_query\_01.sql • 35
- retail\_query\_02.sql • 36
- retail\_query\_03.sql • 37
- retail\_query\_04.sql • 38
- retail\_query\_05.sql • 39
- retail\_query\_06.sql • 40
- retail\_query\_07.sql • 42
- retail\_query\_08.sql • 42
- Retail\_Sales\_Fact • 31, 32
- Running Simple Queries • 10, 89, 102, 106
- S**
- Session\_Dimension • 14, 17
- Settlement\_Dimension • 49
- Shell script • 7
- shipping\_dimension • 72
- Split\_Dimension • 50
- Step 1
  - Set Up the Example Environment • 89, 90, 95
- Step 2
  - Create the Example Database • 86, 89, 91, 95, 96
- Step 3
  - Define the Database Schema • 89, 93, 95
- Step 4
  - Load the Data • 89, 94, 95
- Step 5
  - Create a Comprehensive Design • 89, 95
- Step 6
  - Connect to the Database and Run a Simple Query • 89, 102
- Step 7
  - Test the Optimized Design • 89, 103
- Step 8
  - (Optional) Generate Custom Data Files • 89, 90, 91, 104
- Stock Dimension • 51
- Stock Exchange Example Database • 11, 45, 102, 106
- stock\_query\_01 • 52
- stock\_query\_02 • 53
- stock\_query\_03 • 53
- stock\_query\_04 • 54
- stock\_query\_05 • 55
- stock\_query\_06 • 56
- StockTransaction\_Fact • 46
- Store Schema • 67, 74
- store\_dimension • 76
- Store\_Dimension • 31, 34

- store\_orders\_fact • 74
- store\_sales\_fact • 75
- Suggested Reading Paths • 2, 5
- Support • 1
- Syntax conventions • 7

## T

- Technical Support • 1, 4
- Telecom Example Database • 11, 58, 102, 106
- telecom\_query\_01.sql • 62
- telecom\_query\_02.sql • 63
- telecom\_query\_03.sql • 63
- telecom\_query\_04.sql • 64
- telecom\_query\_05.sql • 64
- telecom\_query\_06.sql • 65
- Trader\_Dimension • 52
- Tutorial
  - Setting up an Example Database • 10, 86, 89
- Typographical Conventions • 7

## U

- Uppercase text • 7
- UserAgent\_Dimension • 14, 17
- Using the Graphical User Interface • 91, 108

## V

- vendor\_dimension • 73
- Vertical line • 7
- VMart Example Database • 11, 67, 89, 90, 102, 106
- vmart\_query\_01.sql • 79
- vmart\_query\_02.sql • 80
- vmart\_query\_03.sql • 80
- vmart\_query\_04.sql • 81
- vmart\_query\_05.sql • 82
- vmart\_query\_06.sql • 82
- vmart\_query\_07.sql • 83
- vmart\_query\_08.sql • 83
- vmart\_query\_09.sql • 84

## W

- warehouse\_dimension • 73
- Where to Find Additional Information • 6
- Where to Find the Vertica Documentation • 2, 9

# Copyright Notice

---

Copyright© 2006-2011 Vertica, An HP Company, and its licensors. All rights reserved.

Vertica, An HP Company 8 Federal Street Billerica, MA 01821 Phone: (978) 600-1000 Fax: (978) 600-1001 E-Mail: <a href="mailto:info@vertica.com">info@vertica.com</a> Web site: <a href="http://www.vertica.com">http://www.vertica.com</a> ( <a href="http://www.vertica.com">http://www.vertica.com</a> )
---

The software described in this copyright notice is furnished under a license and may be used or copied only in accordance with the terms of such license. Vertica, An HP Company software contains proprietary information, as well as trade secrets of Vertica, An HP Company, and is protected under international copyright law. Reproduction, adaptation, or translation, in whole or in part, by any means — graphic, electronic or mechanical, including photocopying, recording, taping, or storage in an information retrieval system — of any part of this work covered by copyright is prohibited without prior written permission of the copyright owner, except as allowed under the copyright laws.

This product or products depicted herein may be protected by one or more U.S. or international patents or pending patents.

## Trademarks

Vertica™, the Vertica® Analytic Database™, and FlexStore™ are trademarks of Vertica, An HP Company. Adobe®, Acrobat®, and Acrobat® Reader® are registered trademarks of Adobe Systems Incorporated.

AMD™ is a trademark of Advanced Micro Devices, Inc., in the United States and other countries.

DataDirect® and DataDirect Connect® are registered trademarks of Progress Software Corporation in the U.S. and other countries.

Fedora™ is a trademark of Red Hat, Inc.

Intel® is a registered trademark of Intel.

Linux® is a registered trademark of Linus Torvalds.

Microsoft® is a registered trademark of Microsoft Corporation.

Novell® is a registered trademark and SUSE™ is a trademark of Novell, Inc., in the United States and other countries.

Oracle® is a registered trademark of Oracle Corporation.

Red Hat® is a registered trademark of Red Hat, Inc.

VMware® is a registered trademark or trademark of VMware, Inc., in the United States and/or other jurisdictions.

Other products mentioned may be trademarks or registered trademarks of their respective companies.

## Open Source Software Acknowledgments

Vertica makes no representations or warranties regarding any third party software. All third-party software is provided or recommended by Vertica on an AS IS basis.

This product includes cryptographic software written by Eric Young ([eay@cryptsoft.com](mailto:eay@cryptsoft.com)).

## ASMJIT

Copyright (c) 2008-2010, Petr Kobalíček <[kobalicek.petr@gmail.com](mailto:kobalicek.petr@gmail.com)>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## Boost

Boost Software License - Version 1.38 - February 8th, 2009

Permission is hereby granted, free of charge, to any person or organization obtaining a copy of the software and accompanying documentation covered by this license (the "Software") to use, reproduce, display, distribute, execute, and transmit the Software, and to prepare derivative works of the Software, and to permit third-parties to whom the Software is furnished to do so, all subject to the following:

The copyright notices in the Software and this entire statement, including the above license grant, this restriction and the following disclaimer, must be included in all copies of the Software, in whole or in part, and all derivative works of the Software, unless such copies or derivative works are solely in the form of machine-executable object code generated by a source language processor.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## **bzip2**

This file is a part of bzip2 and/or libbzip2, a program and library for lossless, block-sorting data compression.

Copyright © 1996-2005 Julian R Seward. All rights reserved.

- 1 Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
- 2 Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- 3 The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
- 4 Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
- 5 The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, Cambridge, UK.

[jseward@bzip.org](mailto:jseward@bzip.org) <<mailto:jseward@bzip.org>>

bzip2/libbzip2 version 1.0 of 21 March 2000

This program is based on (at least) the work of:

Mike Burrows

David Wheeler

Peter Fenwick

Alistair Moffat

Radioed Neal

Ian H. Witten

Robert Sedgewick

Jon L. Bentley

## **Daemonize**

Copyright © 2003-2007 Brian M. Clapper.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of the clapper.org nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

### **Ganglia Open Source License**

Copyright © 2001 by Matt Massie and The Regents of the University of California.  
All rights reserved.

Permission to use, copy, modify, and distribute this software and its documentation for any purpose, without fee, and without written agreement is hereby granted, provided that the above copyright notice and the following two paragraphs appear in all copies of this software.

IN NO EVENT SHALL THE UNIVERSITY OF CALIFORNIA BE LIABLE TO ANY PARTY FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF THIS SOFTWARE AND ITS DOCUMENTATION, EVEN IF THE UNIVERSITY OF CALIFORNIA HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

THE UNIVERSITY OF CALIFORNIA SPECIFICALLY DISCLAIMS ANY WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE SOFTWARE PROVIDED HEREUNDER IS ON AN "AS IS" BASIS, AND THE UNIVERSITY OF CALIFORNIA HAS NO OBLIGATION TO PROVIDE MAINTENANCE, SUPPORT, UPDATES, ENHANCEMENTS, OR MODIFICATIONS.

### **ICU (International Components for Unicode) License - ICU 1.8.1 and later**

COPYRIGHT AND PERMISSION NOTICE

Copyright © 1995-2009 International Business Machines Corporation and others  
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, provided that the above copyright notice(s) and this permission notice appear in all copies of the Software and that both the above copyright notice(s) and this permission notice appear in supporting documentation.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization of the copyright holder.

All trademarks and registered trademarks mentioned herein are the property of their respective owners.

### **jQuery**

Copyright © 2009 John Resig, <http://jquery.com/>

All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

### **Keepalived Vertica IPVS (IP Virtual Server) Load Balancer**

Copyright © 2007 Free Software Foundation, Inc.

<http://fsf.org/>

The keepalived software contained in the `VerticaIPVSLoadBalancer-5.0.x-0.RHEL5.x86_64.rpm` software package is licensed under the GNU General Public License ("GPL"). You are entitled to receive the source code for such software. For no less than three years from the date you obtained this software package, you may download a copy of the source code for the software in this package licensed under the GPL at no charge by visiting <http://www.vertica.com/licenses/keepalived-1.1.17.tar.gz> **<http://www.vertica.com/licenses/keepalived-1.1.17.tar.gz>**. You may download this source code so that it remains separate from other software on your computer system.

### Lighttpd Open Source License

Copyright © 2004, Jan Kneschke, incremental  
All rights reserved.

- 1 Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
- 2 Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- 3 Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- 4 Neither the name of the 'incremental' nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

### MersenneTwister.h

Copyright © 1997 - 2002, Makoto Matsumoto and Takuji Nishimura,  
Copyright © 2000 - 2009, Richard J. Wagner  
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- 1 Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- 2 Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

- 3 The names of its contributors may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

### **MIT Kerberos**

Copyright © 1985-2007 by the Massachusetts Institute of Technology.

Export of software employing encryption from the United States of America may require a specific license from the United States Government. It is the responsibility of any person or organization contemplating export to obtain such a license before exporting.

WITHIN THAT CONSTRAINT, permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of M.I.T. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. Furthermore if you modify this software you must label your software as modified software and not distribute it in such a fashion that it might be confused with the original MIT software. M.I.T. makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

Individual source code files are copyright MIT, Cygnus Support, Novell, OpenVision Technologies, Oracle, Red Hat, Sun Microsystems, FundsXpress, and others.

Project Athena, Athena, Athena MUSE, Discuss, Hesiod, Kerberos, Moira, and Zephyr are trademarks of the Massachusetts Institute of Technology (MIT). No commercial use of these trademarks may be made without prior written permission of MIT.

"Commercial use" means use of a name in a product or other for-profit manner. It does NOT prevent a commercial firm from referring to the MIT trademarks in order to convey information (although in doing so, recognition of their trademark status should be given).

Portions of src/lib/crypto have the following copyright:

Copyright © 1998 by the FundsXpress, INC.

All rights reserved.

Export of this software from the United States of America may require a specific license from the United States Government. It is the responsibility of any person or organization contemplating export to obtain such a license before exporting.

WITHIN THAT CONSTRAINT, permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Funds Xpress. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. FundsXpress makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

THIS SOFTWARE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The implementation of the AES encryption algorithm in `src/lib/crypto/aes` has the following copyright:

Copyright © 2001, Dr Brian Gladman <[brg@gladman.uk.net](mailto:brg@gladman.uk.net)>, Worcester, UK.  
All rights reserved.

### LICENSE TERMS

The free distribution and use of this software in both source and binary form is allowed (with or without changes) provided that:

- 1 Distributions of this source code include the above copyright notice, this list of conditions and the following disclaimer.
- 2 Distributions in binary form include the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other associated materials.
- 3 The copyright holder's name is not used to endorse products built using this software without specific written permission.

### DISCLAIMER

This software is provided 'as is' with no explicit or implied warranties in respect of any properties, including, but not limited to, correctness and fitness for purpose.

The implementations of GSSAPI mechglue in GSSAPI-SPNEGO in `src/lib/gssapi`, including the following files:

- `lib/gssapi/generic/gssapi_err_generic.et`
- `lib/gssapi/mechglue/g_accept_sec_context.c`
- `lib/gssapi/mechglue/g_acquire_cred.c`
- `lib/gssapi/mechglue/g_canon_name.c`
- `lib/gssapi/mechglue/g_compare_name.c`
- `lib/gssapi/mechglue/g_context_time.c`
- `lib/gssapi/mechglue/g_delete_sec_context.c`
- `lib/gssapi/mechglue/g_dsp_name.c`
- `lib/gssapi/mechglue/g_dsp_status.c`
- `lib/gssapi/mechglue/g_dup_name.c`
- `lib/gssapi/mechglue/g_exp_sec_context.c`
- `lib/gssapi/mechglue/g_export_name.c`
- `lib/gssapi/mechglue/g_glue.c`
- `lib/gssapi/mechglue/g_imp_name.c`

- lib/gssapi/mechglue/g\_imp\_sec\_context.c
- lib/gssapi/mechglue/g\_init\_sec\_context.c
- lib/gssapi/mechglue/g\_initialize.c
- lib/gssapi/mechglue/g\_inquire\_context.c
- lib/gssapi/mechglue/g\_inquire\_cred.c
- lib/gssapi/mechglue/g\_inquire\_names.c
- lib/gssapi/mechglue/g\_process\_context.c
- lib/gssapi/mechglue/g\_rel\_buffer.c
- lib/gssapi/mechglue/g\_rel\_cred.c
- lib/gssapi/mechglue/g\_rel\_name.c
- lib/gssapi/mechglue/g\_rel\_oid\_set.c
- lib/gssapi/mechglue/g\_seal.c
- lib/gssapi/mechglue/g\_sign.c
- lib/gssapi/mechglue/g\_store\_cred.c
- lib/gssapi/mechglue/g\_unseal.c
- lib/gssapi/mechglue/g\_userok.c
- lib/gssapi/mechglue/g\_utils.c
- lib/gssapi/mechglue/g\_verify.c
- lib/gssapi/mechglue/gssd\_pname\_to\_uid.c
- lib/gssapi/mechglue/mglueP.h
- lib/gssapi/mechglue/oid\_ops.c
- lib/gssapi/spnego/gssapiP\_spnego.h
- lib/gssapi/spnego/spnego\_mech.c

are subject to the following license:

Copyright © 2004 Sun Microsystems, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

### **Npgsql-.Net Data Provider for Postgresql**

Copyright © 2002-2008, The Npgsql Development Team

Permission to use, copy, modify, and distribute this software and its documentation for any purpose, without fee, and without a written agreement is hereby granted, provided that the above copyright notice and this paragraph and the following two paragraphs appear in all copies.

IN NO EVENT SHALL THE NPGSQL DEVELOPMENT TEAM BE LIABLE TO ANY PARTY FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS, ARISING OUT OF THE USE OF THIS SOFTWARE AND ITS DOCUMENTATION, EVEN IF THE NPGSQL DEVELOPMENT TEAM HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

THE NPGSQL DEVELOPMENT TEAM SPECIFICALLY DISCLAIMS ANY WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE SOFTWARE PROVIDED HEREUNDER IS ON AN "AS IS" BASIS, AND THE NPGSQL DEVELOPMENT TEAM HAS NO OBLIGATIONS TO PROVIDE MAINTENANCE, SUPPORT, UPDATES, ENHANCEMENTS, OR MODIFICATIONS.

## Open LDAP

The OpenLDAP Public License  
Version 2.8, 17 August 2003

Redistribution and use of this software and associated documentation ("Software"), with or without modification, are permitted provided that the following conditions are met:

- 1 Redistributions in source form must retain copyright statements and notices,
- 2 Redistributions in binary form must reproduce applicable copyright statements and notices, this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution, and
- 3 Redistributions must contain a verbatim copy of this document.

The OpenLDAP Foundation may revise this license from time to time. Each revision is distinguished by a version number. You may use this Software under terms of this license revision or under the terms of any subsequent revision of the license.

THIS SOFTWARE IS PROVIDED BY THE OPENLDAP FOUNDATION AND ITS CONTRIBUTORS ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OPENLDAP FOUNDATION, ITS CONTRIBUTORS, OR THE AUTHOR(S) OR OWNER(S) OF THE SOFTWARE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The names of the authors and copyright holders must not be used in advertising or otherwise to promote the sale, use or other dealing in this Software without specific, written prior permission. Title to copyright in this Software shall at all times remain with copyright holders.

OpenLDAP is a registered trademark of the OpenLDAP Foundation.

Copyright 1999-2003 The OpenLDAP Foundation, Redwood City, California, USA. All Rights Reserved. Permission to copy and distribute verbatim copies of this document is granted.

## Open SSL

OpenSSL License

Copyright © 1998-2008 The OpenSSL Project. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- 1 Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- 2 Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- 3 All advertising materials mentioning features or use of this software must display the following acknowledgment: "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)"
- 4 The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact [openssl-core@openssl.org](mailto:openssl-core@openssl.org).
- 5 Products derived from this software may not be called "OpenSSL" nor may "OpenSSL" appear in their names without prior written permission of the OpenSSL Project.
- 6 Redistributions of any form whatsoever must retain the following acknowledgment: "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>)"

THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

## PCRE LICENCE

PCRE is a library of functions to support regular expressions whose syntax and semantics are as close as possible to those of the Perl 5 language.

Release 8 of PCRE is distributed under the terms of the "BSD" licence, as specified below. The documentation for PCRE, supplied in the "doc" directory, is distributed under the same terms as the software itself.

The basic library functions are written in C and are freestanding. Also included in the distribution is a set of C++ wrapper functions.

## THE BASIC LIBRARY FUNCTIONS

Written by: Philip Hazel

Email local part: ph10  
Email domain: cam.ac.uk  
University of Cambridge Computing Service,  
Cambridge, England.  
Copyright (c) 1997-2010 University of Cambridge  
All rights reserved.

#### THE C++ WRAPPER FUNCTIONS

Contributed by: Google Inc.  
Copyright (c) 2007-2010, Google Inc.  
All rights reserved.

#### THE "BSD" LICENCE

- Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of the University of Cambridge nor the name of Google Inc. nor the names of their contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

End

#### **Perl Artistic License**

Copyright © August 15, 1997

##### Preamble

The intent of this document is to state the conditions under which a Package may be copied, such that the Copyright Holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

## Definitions

"Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection of files created through textual modification.

"Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder as specified below.

"Copyright Holder" is whoever is named in the copyright or copyrights for the package.

"You" is you, if you're thinking about copying or distributing this Package.

"Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)

"Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

- 1 You may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.
- 2 You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.
- 3 You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when you changed that file, and provided that you do at least ONE of the following:
- 4 place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as uunet.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.
  1. use the modified Package only within your corporation or organization.
  2. rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide a separate manual page for each non-standard executable that clearly documents how it differs from the Standard Version.
  3. make other distribution arrangements with the Copyright Holder.
- 5 You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:
  1. distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.
  2. accompany the distribution with the machine-readable source of the Package with your modifications.
  3. give non-standard executables non-standard names, and clearly document the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.
  4. make other distribution arrangements with the Copyright Holder.

- 6 You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that you do not advertise this Package as a product of your own. You may embed this Package's interpreter within an executable of yours (by linking); this shall be construed as a mere form of aggregation, provided that the complete Standard Version of the interpreter is so embedded.
- 7 The scripts and library files supplied as input to or produced as output from the programs of this Package do not automatically fall under the copyright of this Package, but belong to whomever generated them, and may be sold commercially, and may be aggregated with this Package. If such scripts or library files are aggregated with this Package via the so-called "undump" or "unexec" methods of producing a binary executable image, then distribution of such an image shall neither be construed as a distribution of this Package nor shall it fall under the restrictions of Paragraphs 3 and 4, provided that you do not represent such an executable image as a Standard Version of this Package.
- 8 C subroutines (or comparably compiled subroutines in other languages) supplied by you and linked into this Package in order to emulate subroutines and variables of the language defined by this Package shall not be considered part of this Package, but are the equivalent of input as in Paragraph 6, provided these subroutines do not change the language in any way that would cause it to fail the regression tests for the language.
- 9 Aggregation of this Package with a commercial distribution is always permitted provided that the use of this Package is embedded; that is, when no overt attempt is made to make this Package's interfaces visible to the end user of the commercial distribution. Such use shall not be construed as a distribution of this Package.
- 10 The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

### **Pexpect**

Copyright © 2010 Noah Spurrier

Credits: Noah Spurrier, Richard Holden, Marco Molteni, Kimberley Burchett, Robert Stone, Hartmut Goebel, Chad Schroeder, Erick Tryzelaar, Dave Kirby, Ids vander Molen, George Todd, Noel Taylor, Nicolas D. Cesar, Alexander Gattin, Geoffrey Marshall, Francisco Lourenco, Glen Mabey, Karthik Gurusamy, Fernando Perez, Corey Minyard, Jon Cohen, Guillaume Chazarain, Andrew Ryan, Nick Craig-Wood, Andrew Stone, Jorgen Grahn (Let me know if I forgot anyone.)

Free, open source, and all that good stuff.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## PHP License

The PHP License, version 3.01

Copyright © 1999 - 2009 The PHP Group. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted provided that the following conditions are met:

- 1 Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- 2 Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- 3 The name "PHP" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact [group@php.net](mailto:group@php.net).
- 4 Products derived from this software may not be called "PHP", nor may "PHP" appear in their name, without prior written permission from [group@php.net](mailto:group@php.net). You may indicate that your software works in conjunction with PHP by saying "Foo for PHP" instead of calling it "PHP Foo" or "phpfoo"
- 5 The PHP Group may publish revised and/or new versions of the license from time to time. Each version will be given a distinguishing version number.
  - Once covered code has been published under a particular version of the license, you may always continue to use it under the terms of that version. You may also choose to use such covered code under the terms of any subsequent version of the license published by the PHP Group. No one other than the PHP Group has the right to modify the terms applicable to covered code created under this License.
- 6 Redistributions of any form whatsoever must retain the following acknowledgment:

"This product includes PHP software, freely available from <<http://www.php.net/software/>>".

THIS SOFTWARE IS PROVIDED BY THE PHP DEVELOPMENT TEAM ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE PHP DEVELOPMENT TEAM OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This software consists of voluntary contributions made by many individuals on behalf of the PHP Group.

The PHP Group can be contacted via Email at [group@php.net](mailto:group@php.net).

For more information on the PHP Group and the PHP project, please see <<http://www.php.net>>.

PHP includes the Zend Engine, freely available at <<http://www.zend.com>>.

### **PostgreSQL**

This product uses the PostgreSQL Database Management System (formerly known as Postgres, then as Postgres95)

Portions Copyright © 1996-2005, The PostgreSQL Global Development Group

Portions Copyright © 1994, The Regents of the University of California

Permission to use, copy, modify, and distribute this software and its documentation for any purpose, without fee, and without a written agreement is hereby granted, provided that the above copyright notice and this paragraph and the following two paragraphs appear in all copies.

IN NO EVENT SHALL THE UNIVERSITY OF CALIFORNIA BE LIABLE TO ANY PARTY FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS, ARISING OUT OF THE USE OF THIS SOFTWARE AND ITS DOCUMENTATION, EVEN IF THE UNIVERSITY OF CALIFORNIA HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

THE UNIVERSITY OF CALIFORNIA SPECIFICALLY DISCLAIMS ANY WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE SOFTWARE PROVIDED HEREUNDER IS ON AN "AS IS" BASIS, AND THE UNIVERSITY OF CALIFORNIA HAS NO OBLIGATIONS TO PROVIDE MAINTENANCE, SUPPORT, UPDATES, ENHANCEMENTS, OR MODIFICATIONS.

### **Psqlodbc**

The client drivers for Vertica Analytic Database use psqlodbc library, the Postgresql ODBC driver.

License:

This package is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This package is distributed in the hope that it is useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this package; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

The complete source code of the library and complete text of the GNU Lesser General Public License can be obtained by contacting Vertica support.

## Python 2.7

This is the official license for the Python 2.7 release:

### A. HISTORY OF THE SOFTWARE

Python was created in the early 1990s by Guido van Rossum at Stichting Mathematisch Centrum (CWI, see <http://www.cwi.nl>) in the Netherlands as a successor of a language called ABC. Guido remains Python's principal author, although it includes many contributions from others.

In 1995, Guido continued his work on Python at the Corporation for National Research Initiatives (CNRI, see <http://www.cnri.reston.va.us>) in Reston, Virginia where he released several versions of the software.

In May 2000, Guido and the Python core development team moved to BeOpen.com to form the BeOpen PythonLabs team. In October of the same year, the PythonLabs team moved to Digital Creations (now Zope Corporation, see <http://www.zope.com>). In 2001, the Python Software Foundation (PSF, see <http://www.python.org/psf/>) was formed, a non-profit organization created specifically to own Python-related Intellectual Property. Zope Corporation is a sponsoring member of the PSF.

All Python releases are Open Source (see <http://www.opensource.org> for the Open Source Definition). Historically, most, but not all, Python releases have also been GPL-compatible; the table below summarizes the various releases.

Release	Derived from	Year	Owner	GPL-compatible? (1)
0.9.0 thru 1.2		1991-1995	CWI	yes
1.3 thru 1.5.2	1.2	1995-1999	CNRI	yes
1.6	1.5.2	2000	CNRI	no
2.0	1.6	2000	BeOpen.com	no
1.6.1	1.6	2001	CNRI	yes (2)
2.1	2.0+1.6.1	2001	PSF	no
2.0.1	2.0+1.6.1	2001	PSF	yes
2.1.1	2.1+2.0.1	2001	PSF	yes
2.2	2.1.1	2001	PSF	yes
2.1.2	2.1.1	2002	PSF	yes
2.1.3	2.1.2	2002	PSF	yes
2.2.1	2.2	2002	PSF	yes
2.2.2	2.2.1	2002	PSF	yes
2.2.3	2.2.2	2003	PSF	yes
2.3	2.2.2	2002-2003	PSF	yes
2.3.1	2.3	2002-2003	PSF	yes
2.3.2	2.3.1	2002-2003	PSF	yes
2.3.3	2.3.2	2002-2003	PSF	yes
2.3.4	2.3.3	2004	PSF	yes
2.3.5	2.3.4	2005	PSF	yes
2.4	2.3	2004	PSF	yes
2.4.1	2.4	2005	PSF	yes
2.4.2	2.4.1	2005	PSF	yes
2.4.3	2.4.2	2006	PSF	yes
2.5	2.4	2006	PSF	yes
2.7	2.6	2010	PSF	yes

Footnotes:

- 1 GPL-compatible doesn't mean that we're distributing Python under the GPL. All Python licenses, unlike the GPL, let you distribute a modified version without making your changes open source. The GPL-compatible licenses make it possible to combine Python with other software that is released under the GPL; the others don't.
- 2 According to Richard Stallman, 1.6.1 is not GPL-compatible, because its license has a choice of law clause. According to CNRI, however, Stallman's lawyer has told CNRI's lawyer that 1.6.1 is "not incompatible" with the GPL.

Thanks to the many outside volunteers who have worked under Guido's direction to make these releases possible.

## **B. TERMS AND CONDITIONS FOR ACCESSING OR OTHERWISE USING PYTHON**

### **PYTHON SOFTWARE FOUNDATION LICENSE VERSION 2**

-----

- 1 This LICENSE AGREEMENT is between the Python Software Foundation ("PSF"), and the Individual or Organization ("Licensee") accessing and otherwise using this software ("Python") in source or binary form and its associated documentation.
- 2 Subject to the terms and conditions of this License Agreement, PSF hereby grants Licensee a nonexclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use Python alone or in any derivative version, provided, however, that PSF's License Agreement and PSF's notice of copyright, i.e., "Copyright (c) 2001, 2002, 2003, 2004, 2005, 2006 Python Software Foundation; All Rights Reserved" are retained in Python alone or in any derivative version prepared by Licensee.
- 3 In the event Licensee prepares a derivative work that is based on or incorporates Python or any part thereof, and wants to make the derivative work available to others as provided herein, then Licensee hereby agrees to include in any such work a brief summary of the changes made to Python.
- 4 PSF is making Python available to Licensee on an "AS IS" basis. PSF MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, PSF MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF PYTHON WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
- 5 PSF SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
- 6 This License Agreement will automatically terminate upon a material breach of its terms and conditions.
- 7 Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between PSF and Licensee. This License Agreement does not grant permission to use PSF trademarks or trade name in a trademark sense to endorse or promote products or services of Licensee, or any third party.
- 8 By copying, installing or otherwise using Python, Licensee agrees to be bound by the terms and conditions of this License Agreement.

---

## BEOPEN.COM LICENSE AGREEMENT FOR PYTHON 2.0

-----

### BEOPEN PYTHON OPEN SOURCE LICENSE AGREEMENT VERSION 1

- 1 This LICENSE AGREEMENT is between BeOpen.com ("BeOpen"), having an office at 160 Saratoga Avenue, Santa Clara, CA 95051, and the Individual or Organization ("Licensee") accessing and otherwise using this software in source or binary form and its associated documentation ("the Software").
- 2 Subject to the terms and conditions of this BeOpen Python License Agreement, BeOpen hereby grants Licensee a non-exclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use the Software alone or in any derivative version, provided, however, that the BeOpen Python License is retained in the Software, alone or in any derivative version prepared by Licensee.
- 3 BeOpen is making the Software available to Licensee on an "AS IS" basis. BEOPEN MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, BEOPEN MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
- 4 BEOPEN SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF THE SOFTWARE FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF USING, MODIFYING OR DISTRIBUTING THE SOFTWARE, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF
- 5 This License Agreement will automatically terminate upon a material breach of its terms and conditions.
- 6 This License Agreement shall be governed by and interpreted in all respects by the law of the State of California, excluding conflict of law provisions. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between BeOpen and Licensee. This License Agreement does not grant permission to use BeOpen trademarks or trade names in a trademark sense to endorse or promote products or services of Licensee, or any third party. As an exception, the "BeOpen Python" logos available at <http://www.pythonlabs.com/logos.html> may be used according to the permissions granted on that web page.
- 7 By copying, installing or otherwise using the software, Licensee agrees to be bound by the terms and conditions of this License Agreement.

## CNRI LICENSE AGREEMENT FOR PYTHON 1.6.1

-----

- 1 This LICENSE AGREEMENT is between the Corporation for National Research Initiatives, having an office at 1895 Preston White Drive, Reston, VA 20191 ("CNRI"), and the Individual or Organization ("Licensee") accessing and otherwise using Python 1.6.1 software in source or binary form and its associated documentation.

- 2 Subject to the terms and conditions of this License Agreement, CNRI hereby grants Licensee a nonexclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use Python 1.6.1 alone or in any derivative version, provided, however, that CNRI's License Agreement and CNRI's notice of copyright, i.e., "Copyright (c) 1995-2001 Corporation for National Research Initiatives; All Rights Reserved" are retained in Python 1.6.1 alone or in any derivative version prepared by Licensee. Alternately, in lieu of CNRI's License Agreement, Licensee may substitute the following text (omitting the quotes): "Python 1.6.1 is made available subject to the terms and conditions in CNRI's License Agreement. This Agreement together with Python 1.6.1 may be located on the Internet using the following unique, persistent identifier (known as a handle): 1895.22/1013. This Agreement may also be obtained from a proxy server on the Internet using the following URL: <http://hdl.handle.net/1895.22/1013>".
- 3 In the event Licensee prepares a derivative work that is based on or incorporates Python 1.6.1 or any part thereof, and wants to make the derivative work available to others as provided herein, then Licensee hereby agrees to include in any such work a brief summary of the changes made to Python 1.6.1.
- 4 CNRI is making Python 1.6.1 available to Licensee on an "AS IS" basis. CNRI MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, CNRI MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF PYTHON 1.6.1 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
- 5 CNRI SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 1.6.1 FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 1.6.1, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
- 6 This License Agreement will automatically terminate upon a material breach of its terms and conditions.
- 7 This License Agreement shall be governed by the federal intellectual property law of the United States, including without limitation the federal copyright law, and, to the extent such U.S. federal law does not apply, by the law of the Commonwealth of Virginia, excluding Virginia's conflict of law provisions. Notwithstanding the foregoing, with regard to derivative works based on Python 1.6.1 that incorporate non-separable material that was previously distributed under the GNU General Public License (GPL), the law of the Commonwealth of Virginia shall govern this License Agreement only as to issues arising under or with respect to Paragraphs 4, 5, and 7 of this License Agreement. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between CNRI and Licensee. This License Agreement does not grant permission to use CNRI trademarks or trade name in a trademark sense to endorse or promote products or services of Licensee, or any third party.
- 8 By clicking on the "ACCEPT" button where indicated, or by copying, installing or otherwise using Python 1.6.1, Licensee agrees to be bound by the terms and conditions of this License Agreement.

ACCEPT

**CWI LICENSE AGREEMENT FOR PYTHON 0.9.0 THROUGH 1.2**

-----

Copyright (c) 1991 - 1995, Stichting Mathematisch Centrum Amsterdam, The Netherlands. All rights reserved.

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Stichting Mathematisch Centrum or CWI not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

STICHTING MATHEMATISCH CENTRUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL STICHTING MATHEMATISCH CENTRUM BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### Python Dialog

The Administration Tools part of this product uses Python Dialog, a Python module for doing console-mode user interaction.

Upstream Author:

Peter Astrand <[peter@cendio.se](mailto:peter@cendio.se)>

Robb Shecter <[robb@acm.org](mailto:robb@acm.org)>

Sultanbek Tezadov

Florent Rougon <[flo@via.ecp.fr](mailto:flo@via.ecp.fr)>

Copyright © 2000 Robb Shecter, Sultanbek Tezadov

Copyright © 2002, 2003, 2004 Florent Rougon

License:

This package is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This package is distributed in the hope that it is useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this package; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

The complete source code of the Python dialog package and complete text of the GNU Lesser General Public License can be found on the Vertica Systems Web site at

<http://www.vertica.com/licenses/pythondialog-2.7.tar.bz2>

<http://www.vertica.com/licenses/pythondialog-2.7.tar.bz2>

## Rsync

### COPYRIGHT

-----

Rsync was originally written by Andrew Tridgell and is currently maintained by Wayne Davison. It has been improved by many developers from around the world.

Rsync may be used, modified and redistributed only under the terms of the GNU General Public License, found in the file COPYING in this distribution, or at:

<http://www.fsf.org/licenses/gpl.html>

The following GNU General Public License applies **only to the version of rsync** distributed with Vertica.

### GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

#### Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

## GNU GENERAL PUBLIC LICENSE

### TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

#### NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

#### END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

## RRDTool Open Source License

Note: rrdtool is a dependency of using the ganglia-web third-party tool. RRDTool allows the graphs displayed by ganglia-web to be produced.

RRDTOOL - Round Robin Database Tool

A tool for fast logging of numerical data graphical display of this data.

Copyright © 1998-2008 Tobias Oetiker

All rights reserved.

## GNU GPL License

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA

## FLOSS License Exception

(Adapted from <http://www.mysql.com/company/legal/licensing/foss-exception.html>)

I want specified Free/Libre and Open Source Software ("FLOSS") applications to be able to use specified GPL-licensed RRDtool libraries (the "Program") despite the fact that not all FLOSS licenses are compatible with version 2 of the GNU General Public License (the "GPL").

As a special exception to the terms and conditions of version 2.0 of the GPL:

You are free to distribute a Derivative Work that is formed entirely from the Program and one or more works (each, a "FLOSS Work") licensed under one or more of the licenses listed below, as long as:

- 1 You obey the GPL in all respects for the Program and the Derivative Work, except for identifiable sections of the Derivative Work which are not derived from the Program, and which can reasonably be considered independent and separate works in themselves
- 2 All identifiable sections of the Derivative Work which are not derived from the Program, and which can reasonably be considered independent and separate works in themselves
  - are distributed subject to one of the FLOSS licenses listed below, and
  - the object code or executable form of those sections are accompanied by the complete corresponding machine-readable source code for those sections on the same medium and under the same FLOSS license as the corresponding object code or executable forms of those sections.
- 3 Any works which are aggregated with the Program or with a Derivative Work on a volume of a storage or distribution medium in accordance with the GPL, can reasonably be considered independent and separate works in themselves which are not derivatives of either the Program, a Derivative Work or a FLOSS Work.

If the above conditions are not met, then the Program may only be copied, modified, distributed or used under the terms and conditions of the GPL.

#### FLOSS License List

License name	Version(s)/Copyright Date
Academic Free License	2.0
Apache Software License	1.0/1.1/2.0
Apple Public Source License	2.0
Artistic license	From Perl 5.8.0
BSD license	"July 22 1999"
Common Public License	1.0
GNU Library or "Lesser" General Public License (LGPL)	2.0/2.1
IBM Public License, Version	1.0
Jabber Open Source License	1.0
MIT License (As listed in file MIT-License.txt)	-
Mozilla Public License (MPL)	1.0/1.1
Open Software License	2.0
OpenSSL license (with original SSLeay license)	"2003" ("1998")
PHP License	3.0
Python license (CNRI Python License)	-
Python Software Foundation License	2.1.1
Sleepycat License	"1999"
W3C License	"2001"
X11 License	"2001"
Zlib/libpng License	-
Zope Public License	2.0/2.1

#### Spread

This product uses software developed by Spread Concepts LLC for use in the Spread toolkit. For more information about Spread see <http://www.spread.org> (<http://www.spread.org>).

Copyright © 1993-2006 Spread Concepts LLC.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- 1 Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer and request.
- 2 Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer and request in the documentation and/or other materials provided with the distribution.
- 3 All advertising materials (including web pages) mentioning features or use of this software, or software that uses this software, must display the following acknowledgment: "This product uses software developed by Spread Concepts LLC for use in the Spread toolkit. For more information about Spread see <http://www.spread.org>"

- 4 The names "Spread" or "Spread toolkit" must not be used to endorse or promote products derived from this software without prior written permission.
- 5 Redistributions of any form whatsoever must retain the following acknowledgment:
- 6 "This product uses software developed by Spread Concepts LLC for use in the Spread toolkit. For more information about Spread, see <http://www.spread.org>"
- 7 This license shall be governed by and construed and enforced in accordance with the laws of the State of Maryland, without reference to its conflicts of law provisions. The exclusive jurisdiction and venue for all legal actions relating to this license shall be in courts of competent subject matter jurisdiction located in the State of Maryland.

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, SPREAD IS PROVIDED UNDER THIS LICENSE ON AN AS IS BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES THAT SPREAD IS FREE OF DEFECTS, MERCHANTABILITY, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT. ALL WARRANTIES ARE DISCLAIMED AND THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE CODE IS WITH YOU. SHOULD ANY CODE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE COPYRIGHT HOLDER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY CODE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, IN NO EVENT SHALL THE COPYRIGHT HOLDER OR ANY OTHER CONTRIBUTOR BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT, OR CONSEQUENTIAL DAMAGES FOR LOSS OF PROFITS, REVENUE, OR FOR LOSS OF INFORMATION OR ANY OTHER LOSS.

YOU EXPRESSLY AGREE TO FOREVER INDEMNIFY, DEFEND AND HOLD HARMLESS THE COPYRIGHT HOLDERS AND CONTRIBUTORS OF SPREAD AGAINST ALL CLAIMS, DEMANDS, SUITS OR OTHER ACTIONS ARISING DIRECTLY OR INDIRECTLY FROM YOUR ACCEPTANCE AND USE OF SPREAD.

Although NOT REQUIRED, we at Spread Concepts would appreciate it if active users of Spread put a link on their web site to Spread's web site when possible. We also encourage users to let us know who they are, how they are using Spread, and any comments they have through either e-mail ([spread@spread.org](mailto:spread@spread.org)) or our web site at (<http://www.spread.org/comments>).

## **SNMP**

Various copyrights apply to this package, listed in various separate parts below. Please make sure that you read all the parts. Up until 2001, the project was based at UC Davis, and the first part covers all code written during this time. From 2001 onwards, the project has been based at SourceForge, and Networks Associates Technology, Inc hold the copyright on behalf of the wider Net-SNMP community, covering all derivative work done since then. An additional copyright section has been added as Part 3 below also under a BSD license for the work contributed by Cambridge Broadband Ltd. to the project since 2001. An additional copyright section has been added as Part 4 below also under a BSD license for the work contributed by Sun Microsystems, Inc. to the project since 2003.

Code has been contributed to this project by many people over the years it has been in development, and a full list of contributors can be found in the README file under the THANKS section.

**Part 1: CMU/UCD copyright notice: (BSD like)**

Copyright © 1989, 1991, 1992 by Carnegie Mellon University  
Derivative Work - 1996, 1998-2000  
Copyright © 1996, 1998-2000 The Regents of the University of California  
All Rights Reserved

Permission to use, copy, modify and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appears in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of CMU and The Regents of the University of California not be used in advertising or publicity pertaining to distribution of the software without specific written permission.

CMU AND THE REGENTS OF THE UNIVERSITY OF CALIFORNIA DISCLAIM ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL CMU OR THE REGENTS OF THE UNIVERSITY OF CALIFORNIA BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM THE LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

**Part 2: Networks Associates Technology, Inc copyright notice (BSD)**

Copyright © 2001-2003, Networks Associates Technology, Inc  
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of the Networks Associates Technology, Inc nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

**Part 3: Cambridge Broadband Ltd. copyright notice (BSD)**

Portions of this code are copyright (c) 2001-2003, Cambridge Broadband Ltd.  
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- The name of Cambridge Broadband Ltd. may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

**Part 4: Sun Microsystems, Inc. copyright notice (BSD)**

Copyright © 2003 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara,  
California 95054, U.S.A. All rights reserved.

Use is subject to license terms below.

This distribution may include materials developed by third parties.

Sun, Sun Microsystems, the Sun logo and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of the Sun Microsystems, Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

**Part 5: Sparta, Inc copyright notice (BSD)**

Copyright © 2003-2006, Sparta, Inc  
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of Sparta, Inc nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

**Part 6: Cisco/BUPTNIC copyright notice (BSD)**

Copyright © 2004, Cisco, Inc and Information Network Center of Beijing University of Posts and Telecommunications.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of Cisco, Inc, Beijing University of Posts and Telecommunications, nor the names of their contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

**Part 7: Fabasoft R&D Software GmbH & Co KG copyright notice (BSD)**

Copyright © Fabasoft R&D Software GmbH & Co KG, 2003

[oss@fabasoft.com](mailto:oss@fabasoft.com)

Author: Bernhard Penz

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- The name of Fabasoft R&D Software GmbH & Co KG or any of its subsidiaries, brand or product names may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER BE

LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

### **Tecla Command-line Editing**

Copyright © 2000 by Martin C. Shepherd.

All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, provided that the above copyright notice(s) and this permission notice appear in all copies of the Software and that both the above copyright notice(s) and this permission notice appear in supporting documentation.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization of the copyright holder.

### **Webmin Open Source License**

Copyright © Jamie Cameron

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- 1** Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- 2** Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- 3** Neither the name of the developer nor the names of contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE DEVELOPER ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE DEVELOPER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

### **xerces**

NOTICE file corresponding to section 4(d) of the Apache License, Version 2.0, in this case for the Apache Xerces distribution.

This product includes software developed by The Apache Software Foundation (<http://www.apache.org/>).

Portions of this software were originally based on the following:

Software copyright © 1999, IBM Corporation., <http://www.ibm.com>.

### **zlib**

This is used by the project to load zipped files directly by COPY command. [www.zlib.net/](http://www.zlib.net/)

zlib.h -- interface of the 'zlib' general purpose compression library version 1.2.3, July 18th, 2005

Copyright © 1995-2005 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

- 1** The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
- 2** Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
- 3** This notice may not be removed or altered from any source distribution.

Jean-loup Gailly [jloup@gzip.org](mailto:jloup@gzip.org)

Mark Adler [madler@alumni.caltech.edu](mailto:madler@alumni.caltech.edu)