

Front Line Customer Care Installation and Configuration Guide

Table of Content

1	Database Installation.....	3
1.1	Create the database Instance	3
1.2	Create the database schema	4
2	Tivoli Common Reporting (TCR) Installation	6
2.1	Deploying Dashboard and reports.....	6
2.2	Web Application Installation	8
2.2.1	Installation Steps.....	8
2.2.2	Post-Install Steps	9
3	Setting up Cognos report services for report parallel execution	15
	APPENDIX A: Accessing Dashboard and Reports Manually	16
	APPENDIX B: Updating dashboard with customer logos.....	16
	APPENDIX C: Updating dashboard granularity	17
	APPENDIX D: Applying Access Control to users.....	18
	APPENDIX E: Uninstall Steps	20

1 Database Installation

Note: These steps should be performed on the server where the Oracle 11g database is installed as the user oracle

Deploy the Front Line Customer Care installation (FLCC) package (customer_care_x.x.zip) to a known location on the database server by executing the following commands:

```
$ cp customer_care_x.x.zip <target_directory>
$ unzip customer_care_x.x.zip
$ cd <target_directory>/install
$ chmod +x install_database.ksh
```

1.1 Create the database Instance

The database creation utilizes Oracle database templates. Bundled with the FLCC installation package is a sample template that can be used for small deployments.

If a specific database size is required for the deployment a template file should be created and placed in the directory below

```
<target_directory>/db/instance
```

The following tablespaces must be defined within the template file for FLCC to function correctly

```
REF_INDX
REFERENCE
SYSLOG_INDX
SYSLOG
TRANS_INDX
TRANSACTION
```

Execute the following steps to create the FLCC database

```
$ cd <target_directory>/install
$ ./install_database.ksh -create_database
```

During the installation procedure the user will be prompted for the following information:

```
Enter FLCC Home (/home/oracle/flcc):
```

Enter the installation directory for First Line Customer Care or accept the default.

```
Enter Oracle Home (/appl/oracle/product/11.2.0/db_1):
```

Enter the installation directory for Oracle or accept the default.

```
Enter Oracle SID (ccdb):
```

Enter the SID for the database to be created or accept the default

```
Enter Oracle password for user 'sys':
```

Enter the Oracle password for the sys user. Contact your Oracle administrator if this is not available.

```
Enter Oracle password for user 'system':
```

Enter the Oracle password for the system user. Contact your Oracle administrator if this is not available.

```
Enter Oracle password for user 'etlserver':
```

Enter a password for the Oracle etlserver user that is to be created. This user will be the primary user for both data loading and retrieval

```
Enter the database template name (flcc_small):
```

Enter the name of the Oracle template file (excluding the .dbt extension). Note this file must be present in the <target_directory>/db/instance folder.

The creation of the Oracle database may take some time depending on the size of the database defined.

The location of a log file will be indicated at the end of the installation procedure containing any errors which may have been encountered.

1.2 Create the database schema

Execute the following steps to create the FLCC schema

```
$ cd <target_directory>/install
```

```
$ ./install_database.ksh -install_schema
```

During the installation procedure the user will be prompted for the following information:

```
Enter FLCC Home (/export/home/flcc):
```

Enter the installation directory for First Line Customer Care or accept the default.

Enter Oracle Home (/appl/oracle/product/11.2.0/db_1):

Enter the installation directory for Oracle or accept the default.

Enter Oracle SID (ccdb):

Enter the SID for the database created previously

Enter Oracle password for user 'sys':

Enter the Oracle password for the sys user. Contact your Oracle administrator if this is not available.

Enter Oracle password for user 'system':

Enter the Oracle password for the system user. Contact your Oracle administrator if this is not available.

Enter Oracle password for user 'etlserver':

Enter a password for the Oracle etlserver user that is to be created. This user will be the primary user for both data loading and retrieval

Enter the database template name (flcc_small):

Enter the name of the Oracle template file (excluding the .dbt extension).

Note: this file must be present in the <target_directory>/db/instance folder.

2 Tivoli Common Reporting (TCR) Installation

Note: The steps outlined in the TCR installation procedure should be carried out on the server where the TCR platform is to be installed.

Details about how to install Cognos can be found in the documentation folder of the Tivoli Common Reporting Setup files. You will also find details about the hardware and software supported by TCR.

Pre-requisite #1: Install Oracle Client on the server before performing the TCR installation

Pre-requisite #2: Ensure that the following Oracle variables have been set up before performing the TCR installation:

- ORACLE_HOME
 - LIBPATH
-

Pre-requisite #3: The only supported web browsers for accessing TCR are Microsoft Internet Explorer 7 and Mozilla Firefox 3.6

2.1 Deploying Dashboard and reports

Note: Unless otherwise specified, the procedures in this section must be performed on the designated reports server only.

Copying Content into the Tivoli Common Reporting Server

1. Copy the *flcc_dashboard.zip* file from the reports folder of the Front Line Customer Care installation package into the Cognos “*deployment*” folder:

```
$TIVOLI_COMMON_REPORTING_PATH/tipv2Components/TCRComponent/cognos/deployment
```

Creating Database Connection

1. Open a browser windows and launch Tivoli Integrated Portal by default:
`https://server:16311/ibm/console/logon.jsp`
2. Login in into the system with an user with administration privileges
3. Open the “*Reporting>Common Reporting*” tab
4. Expand the menu “*Launch*” and choose “*Administration*”
5. Select the “*Configuration*” tab
6. Create a new “*Data Source Connection*” pointing to the Front Line Customer Care Database.
 - a. Details about how to create and configure a new Data Source Connection can be found in the *IBM Cognos Business Intelligence Administration and Security Guide 8.4.1*

http://publib.boulder.ibm.com/infocenter/c8bi/v8r4m0/index.jsp?topic=/com.ibm.swg.im.cognos.ug_cra.8.4.1.doc/ug_cra.html

Chapter: *Data Management*

Section: *Data Sources and Connections > Create a Data Source*

- i. Data Source Connection name: ***FLCC_DB***
- ii. Data Source Connection type: ***Oracle***
- iii. SQL*Net Connect String: ***tnsname*** of the Oracle database
- iv. User ID and password: ***user schema*** for the Oracle database

Deploying Content

1. Open a browser windows and launch Tivoli Integrated Portal by default:
`https://server:16311/ibm/console/logon.jsp`
2. Login in into the system with an user with administration privileges
3. Open the “*Reporting>Common Reporting*” tab
4. Expand the menu “*Launch*” and choose “*Administration*”
5. Select the “*Configuration*” tab
6. Go to Content Administration and import the content of the *flcc_dashboard.zip* using the “*New Import Wizard*”.
 - a. Details about how to import and deploy IBM Cognos 8 content can be found in the *IBM Cognos Business Intelligence Administration and Security Guide 8.4.1*

http://publib.boulder.ibm.com/infocenter/c8bi/v8r4m0/index.jsp?topic=/com.ibm.swg.im.cognos.ug_cra.8.4.1.doc/ug_cra.html

Chapter: *Content Administration in IBM Cognos Connection*

Section: *Deployment>Deploying IBM Cognos 8 Entries>Import to a Target Environment*

- b. Select the following entries available in the package:
 - i. First Line Customer Care
 - ii. Second Line Customer Care

2.2 Web Application Installation

Note: Execute the following steps as the same user used to install TCR

The following pre-requisites must be followed prior to installing the Customer Care application

- Tivoli Common Reporting (TCR) v2.1 must have been installed on the target AIX server.
- The installer must know the name of the Tivoli Integrated Portal (TIP) profile being used <TIP_Profile>
- The installer must know the name of the TIP administrator user <TIP_User>
- The installer must know the password for the TIP administrator user <TIP_Passwd>
- The environment variable TIP_HOME must be set to the root of the Tivoli Integrated Portal

e.g.

```
$ export TIP_HOME=/opt/IBM/tivoli/tip
```

2.2.1 Installation Steps

Note: The following steps must be performed on the server where TCR 2.1 is installed. The operating system user used must be that which was used during the install of TCR 2.1

Place the Customer Care 1.1 installation package (customer_care_SQM1.4.X.X) in the <target directory>. Once completed, execute the following commands

```
$ cd <target directory>/install
$ chmod +x install_dashboard.ksh
```



```
$ ./install_dashboard.ksh -profile <TIP_Profile> -user <TIP_User> -passwd  
<TIP_Passwd> -mode install
```

You will be prompted to enter role names for the first line, second line and VIP user profiles. Enter three user defined names.

Note: that these names will later be configured within the Tivoli Integrated Portal user management.

Errors encountered during the installation can be seen in the log files located at the following directory:

```
$TIP_HOME/logs/customer_care
```

2.2.2 Post-Install Steps

Note: The following steps must be performed on the server where TCR 2.1 is installed. The operating system user used must be that which was used during the install of TCR 2.1

Edit the file `$TIP_HOME/bin/startflcc.sh` and replace all occurrences of `$TIP_HOME` with the fully qualified path.


Also replace the default value for the `security.log.dir` property with a path to a directory where the security audit logs are to be kept.

Restart the Tivoli Integrated Portal with the following commands:


```
$ cd $TIP_HOME/bin  
$ ./stopServer.sh server1  
$ ./startflcc.sh server1
```

Create the three user roles defined earlier in the installation. Log into the Tivoli Integrated Portal with the user name and password used when invoking the `install_dashboard.ksh` script.

Select “Users and Group” “Role Management” as shown below



Select “New” and you will be prompted to enter a role name. Enter the role name for the First Line users as defined earlier. Select “Save”



Repeat the steps above to create the Second Line and VIP User Roles. When complete all roles should be visible within Role Management

Front Line Customer Care application users can now be added to the appropriate role.

Note: that users added to the “First Line” role will not have access to location information within the dashboard view. “Second Line” users will have full access to the dashboard view. Note that VIP users (those assigned to the VIP user role) must also be assigned to either a First Line or Second Line user role.

To assign users select “Users and Groups” “User Roles” from within the Tivoli Integrated Portal.

Role Management | **User Roles** | — Select Action —

User Roles

Use this page to manage roles for users. You can search users and add/remove roles for a selected user.

Available Users

Assign roles to a selected user:

First name: Last name:

User ID: E-mail:

Number of results to display: 20

User ID	First Name	Last Name	Roles	E-mail
None				

Total: 0

Enter the search criteria for the user you wish to assign to a role and select “Search”

User Roles

Use this page to manage roles for users. You can search users and add/remove roles for a selected user.

Available Users

Assign roles to a selected user.

First name: Last name:

User ID: E-mail:

Number of results to display:

User ID	First Name	Last Name	Roles
romahony1	Richard	OMahony	operator,suppressmonitor,users,administrator,allAuthenticatedPortalUsers,chartCreator,chartAdministr

Select the user from the list returned and a list of roles will be returned

User Roles


User Roles > romahony1 Related Tasks ▾

Available Roles

Select	Roles
<input checked="" type="checkbox"/>	allAuthenticatedPortalUsers
<input checked="" type="checkbox"/>	chartAdministrator
<input checked="" type="checkbox"/>	chartCreator
<input checked="" type="checkbox"/>	chartViewer
<input checked="" type="checkbox"/>	configurator
<input type="checkbox"/>	FirstLineRole
<input checked="" type="checkbox"/>	iscadmins
<input checked="" type="checkbox"/>	monitor
<input checked="" type="checkbox"/>	operator
<input type="checkbox"/>	SecondLineRole
<input checked="" type="checkbox"/>	suppressmonitor

Total: 14 Selected: 12

Select the appropriate role for this user (either first line or second line role). Note that selecting both roles will result in full dashboard access for the user. Select “Save”. Note that all FLCC application users must also have the ‘tcrPortalOperator’ and ‘users’ roles assigned.




Repeat these steps for each of the application users.

Note: Changes to user roles will not take affect until a user re-opens the web browser.

FLCC users operating in an Internet Explorer environment should disable browser caching with the following browser update:

Select Tools/Internet, click the general tab.

Under the Browsing history section select Settings ensure that the option “Every time I visit a webpage” is selected as shown below.



3 **Setting up Cognos report services for report parallel execution**

Login into the TIP UI as a user with administration privileges

1. Open the “Reporting/Common Reporting” tab
2. Expand the menu “Launch” and choose “Administration”
3. Details about how to setup IBM Cognos 8 services for parallel execution can be found in the *IBM Cognos Business Intelligence Administration and Security Guide 8.4.1*

http://publib.boulder.ibm.com/infocenter/c8bi/v8r4m0/index.jsp?topic=/com.ibm.swg.im.cognos.ug_cra.8.4.1.doc/ug_cra.html

Chapter: *System Administration*

Section: *Server Administration>>Set Parameters for Concurrent Query Execution*

Note: Parameter selection will vary depending on the Tivoli Common Reporting server specifications

APPENDIX A: Accessing Dashboard and Reports Manually

1. Open a browser windows and launch Tivoli Integrated Portal by default:

https://server:16311/ibm/console/logon.jsp

2. Login in into the system with an user with administration privileges
3. Open the “Reporting>Common Reporting>Public Folders” tab
4. Open the “First Line Customer Care” package
5. Select any of the following files and fill the prompts:

a. CEM Dashboard - Cause and Actions

i. Prompts: Service and Reason

b. CEM Dashboard – Data

i. Prompts: IMSI and Time Range

c. CEM Dashboard – Voice

i. Prompts: IMSI and Time Range

APPENDIX B: Updating dashboard with customer logos

The following steps outline the procedure to alter the default logos on the FLCC dashboard:

1. Copy the new logo into the following folders

a. \$TIVOLI_COMMON_REPORTING_PATH/tipv2/profiles/TIPProfile/installedApps/TIPCell/IBM Cognos 8.ear/p2pd.war/tivoli/tcr_common/images

b. \$TIVOLI_COMMON_REPORTING_PATH/tipv2Components/TCRComponent/cognos/webcontent/tivoli/tcr_common/images

2. Edit and Update all the dashboard logos changing the path (all dashboard files for all services must be updated)

a. From: ../tivoli/tcr_common/images/tivoli.gif

b. To: ../tivoli/tcr_common/images/new_logo.ext

APPENDIX C: Updating dashboard granularity

The following steps detail the changes needed in the FLCC dashboard when the granularity of the underlying datasources are changed:

1. The dashboard END TIME column is defined as 15 minutes later than the transaction DATETIME recorder in the database.
2. If the granularity of the sources changes to lower values (5minutes, 1 minute...) then the TCR First Line Customer Care model has to be updated accordingly as follows:
 - a. Launch IBM Cognos 8 Framework Manager
 - b. Open “First Line Customer Care v1.x” Metadata Model
 - c. Update the following objects:
 - i. FLCC Model > VOICE > Transactions > ENDTIME
 1. The default value is adding 15 minutes (DATETIME +1/96)
 2. Example for 5 minutes (DATETIME +1/288)
 3. Example for 1 minutes (DATETIME +1/1440)
 - ii. FLCC Model > SMS > Transactions > ENDTIME
 1. The default value is adding 15 minutes (DATETIME +1/96)
 2. Example for 5 minutes (DATETIME +1/288)
 3. Example for 1 minutes (DATETIME +1/1440)
 - iii. FLCC Model > MMS > Transactions > ENDTIME
 1. The default value is adding 15 minutes (DATETIME +1/96)
 2. Example for 5 minutes (DATETIME +1/288)
 3. Example for 1 minutes (DATETIME +1/1440)
 - iv. FLCC Model > DATA > Transactions > ENDTIME
 1. The default value is adding 15 minutes (DATETIME +1/96)
 2. Example for 5 minutes (DATETIME +1/288)
 3. Example for 1 minutes (DATETIME +1/1440)
 - d. Save the model
 - e. Publish the First Line Customer Care Package

APPENDIX D: Applying Access Control to users

TIP User Group and Roles

1. Open a browser windows and launch Tivoli Integrated Portal by default:
<https://server:16311/ibm/console/logon.jsp>
2. Login in into the system with an user with administration privileges
3. Create two different TIP user groups. As an example consider the following names
 - a. First Line Group (users that belong to this group will have to be added to this group afterwards)
 - b. Second Line Group (users that belong to this group will have to be added to this group afterwards)
4. The following TIP roles will have to be assigned to both groups above
 - a. users
 - b. tcrPortalOperator

TCR Cognos Access Control

Details about how to administer IBM Cognos 8 security can be found in the *IBM Cognos 8 Administration and Security Guide 8.4.1*

http://publib.boulder.ibm.com/infocenter/c8bi/v8r4m0/index.jsp?topic=/com.ibm.swg.im.cognos.ug_cra.8.4.1.doc/ug_cra.html

Chapter: *Security Administration*

1. Open a browser windows and launch Tivoli Integrated Portal by default:
<https://server:16311/ibm/console/logon.jsp>
2. Login in into the system with an user with administration privileges
3. Open the “*Reporting>Common Reporting*” tab
4. Expand the menu “*Launch*” and choose “*Administration*”
5. Select the “*Security*” tab

- a. Remove the group “Everyone” as a member of the following role:
 - i. System Administrators
6. Expand the menu “*Launch*” and choose “*Connection*”
7. Edit the properties of the “First Line Customer Care” package:
 - a. Override the parent group privileges
 - b. Grant the following privileges to the “First Line Group” user Group created earlier:
 - i. Read
 - ii. Execute
 - c. Deny all the privileges to the “Second Line Group” user Group created earlier:
8. Edit the properties of the “Second Line Customer Care” package:
 - a. Override the parent group privileges
 - b. Grant the following privileges to the “Second Line Group” user Group created earlier:
 - i. Read
 - ii. Execute
 - c. Deny all the privileges to the “First Line Group” user Group created earlier.

How to disable editing capabilities to First Line and Second Line Users

Details about how to administer IBM Cognos 8 security can be found in the *IBM Cognos 8 Administration and Security Guide 8.4.1*

http://publib.boulder.ibm.com/infocenter/c8bi/v8r4m0/index.jsp?topic=/com.ibm.swg.im.cognos.ug_cra.8.4.1.doc/ug_cra.html

Chapter: *Security Administration*

1. Open a browser windows and launch Tivoli Integrated Portal by default:
https://server:16311/ibm/console/logon.jsp
2. Login in into the system with an user with administration privileges
3. Open the “*Reporting>Common Reporting*” tab
4. Expand the menu “*Launch*” and choose “*Administration*”

5. Select the “*Security*” tab
 - a. Remove the group “Everyone” as a member of the following roles:
 - i. Authors
 - ii. Express Authors
 - iii. Directory Administrators
 - iv. Report Administrators

APPENDIX E: Uninstall Steps

To uninstall the Front Line Customer Care Web Application execute the following steps as the user used to install TCR

```
$ cd <target_directory>/install
```

Where target <target_directory> is the location to which the Front Line Customer Care installation package was extracted to

```
$ ./install_dashboard.ksh -profile <TIP_Profile> -user <TIP_User> -passwd  
<TIP_Passwd> -mode remove
```

To uninstall the Front Line Customer Care database instance execute the following steps as the user `oracle`

```
$ export ORACLE_SID=ccdb
```

Substitute the appropriate database name for **ccdb**:

```
$ sqlplus /nolog
```

Enter the password for the sys user when prompted:

```
SQL> connect / as sysdba
```

```
SQL> shutdown immediate;
```

```
SQL> exit
```

Remove the database:

```
$ORACLE_HOME/bin/dbca -silent -deleteDatabase -sourceDB cddb -
sysDBAUserName sys -sysDBAPassword <sys DBA user password>
```

Substitute the appropriate database name for **ccdb**:

To remove the FLCC dashboard reports log into the TIP UI as a user with administration privileges. Navigate through “Reporting/Common Reporting”. Select the “First Line Customer Care” and “Second Line Customer Care” reports and click on delete.



The firstline, secondline and VIP user roles can be deleted by navigating to “Users and Group/Role Management”, selecting the groups to delete and clicking the delete button



Notices

IBM may not offer the products, services, or features discussed in this document in all countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk NY 10504-1785
U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
1623-14, Shimotsuruma, Yamato-shi
Kanagawa 242-8502 Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
5300 Cork Airport Business Park
Kinsale Road
Cork
Ireland.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

If you are viewing this information softcopy, the photographs and color illustrations may not appear.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at “Copyright and trademark information” at www.ibm.com/legal/copytrade.shtml.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Java and all Java-based trademarks and logos are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.



Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other company, product or service names may be trademarks or service marks of others.

IBM®

Printed in the Republic of Ireland