

IBM® Tivoli® Workload Scheduler, Connector and Tivoli
Plus



Fix Pack 07 for Version 8.2.0

Version 8.2.0

IBM® Tivoli® Workload Scheduler, Connector and Tivoli
Plus



Fix Pack 07 for Version 8.2.0

Version 8.2.0

Note

Before using this information and the product it supports, read the information in Chapter 3, "Notices," on page 43.

Second Edition (April 2005)

This edition applies to fix pack 7 (PTF U800780) for version 8, release 2, modification level 0 of Tivoli Workload Scheduler, Connector and Tivoli Plus Fix Pack 07 for Version 8.2.0

© Copyright International Business Machines Corporation 2004, 2005. All rights reserved.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Chapter 1. Tivoli Workload Scheduler, Connector and Tivoli Plus Fix Pack 07 for Version 8.2.0 1

About this release	1
Architecture(s)	2
Fix pack structure	2
Patch Contents in CD_1 and CD_2	2
Patch Contents in CD_1	2
Patch Contents in CD_2	3
New Features in Tivoli Workload Scheduler 8.2 Fix Pack 07	3
New Features in Tivoli Workload Scheduler 8.2 Fix Pack 04	5
New Features in Tivoli Workload Scheduler 8.2 Fix Pack 03	6
Product fix history	6
APARs and Defects Fixed in Tivoli Workload Scheduler, Connector and Tivoli Plus Module Fix Pack 07 for Version 8.2.0	7
Defects on 8.2.0-TIV-TWS-FP0007	8
APARs Reported for 8.1	9
APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 06 for Version 8.2.0	9
Internal Defects for Version 8.2	11
APARs reported for 8.1	11
APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 05 for Version 8.2.0	11
Internal Defects for version 8.2	12
APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 05 for Version 8.1	13
APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 04 for Version 8.2.0	13
Internal Defects for Version 8.2	14
APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 04 for Version 8.1	15
APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 03 for Version 8.2.0	16
APARs reported for version 8.2.	17
APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 03 for Version 8.1	18
APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 02 for Version 8.2.0	19
Internal Defects for Version 8.2	20
APARs fixed in Tivoli Workload Scheduler and Connector Fix Pack 02 for Version 8.1	20
APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 01 for Version 8.2.0	22
Internal Defects for Version 8.2	22
APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 01 for Version 8.1	24
APARs Fixed on Installation for Tivoli Workload Scheduler 8.2 GA.	26
Limitations	27
Known Defects and Limitations for the Scheduler	27
Known Defects and Limitations for Tivoli Workload Scheduler Connector	29
Known Defects and Limitations for the Scheduler in E2E Environment	29
Installation	30
Applying the Fix Pack.	30
Windows	30
UNIX (IRIX, OSF, DYNIX, LINUX_PPC).	30
UNIX (AIX, HP-UX, Solaris Operating Environment, LINUX I386, LINUX S390) - Graphical Installation	31
UNIX (AIX, HP-UX, Solaris Operating Environment) - Alternate Installation.	31
Additional Installation Instructions	31
New Installation Methods on Tier 1 Platforms.	31
Installation Log Files	33
Product Uninstall on Tier 1	34
Tivoli Workload Scheduler Connector.	34
Tivoli Workload Scheduler Plus Module.	35
Documentation notes	35
New information contained in this Fix pack	36
Documentation problems and corrections	36
New Option for the evtsize Command	37

Autotrace level 3.1.5	37
Chapter 2. Contacting IBM Software Support	41
Chapter 3. Notices	43
Trademarks	44

Chapter 1. Tivoli Workload Scheduler, Connector and Tivoli Plus Fix Pack 07 for Version 8.2.0

Date 1 April 2005

Fix Pack
8.2.0-TIV-TWS-FP0007

PTF Number
U800780

Product
Tivoli Workload Scheduler Version 8.2 and IBM Tivoli Workload Scheduler Warehouse Enablement Fix Pack 1

General Description
Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector and Tivoli Plus Module Fix Pack 07 for Version 8.2.0 and Tivoli Workload Scheduler Warehouse Enablement Pack Fix Pack 01

This readme file provides important information about Fix Pack 7 (PTF U800780) for Tivoli Workload Scheduler, Connector and Tivoli Plus Fix Pack 07 for Version 8.2.0. This readme file is the most current information for the fix pack and takes precedence over all other documentation for Tivoli Workload Scheduler, Connector and Tivoli Plus Fix Pack 07 for Version 8.2.0.

Refer to 8.2.0.TIV_WEP-FP001.readme that is contained in CD_2 directory for information regarding 8.2.0-TIV-TWS_WEP-FP0001.

Review this section thoroughly before installing or using this fix pack.

About this release

This section includes the following topics:

- “Architecture(s)” on page 2
- “Fix pack structure” on page 2
- “New Features in Tivoli Workload Scheduler 8.2 Fix Pack 07” on page 3
- “New Features in Tivoli Workload Scheduler 8.2 Fix Pack 04” on page 5
- “New Features in Tivoli Workload Scheduler 8.2 Fix Pack 03” on page 6
- “Product fix history” on page 6
- “Limitations” on page 27
- “Installation” on page 30
- “Documentation notes” on page 35

Architecture(s)

AIX, HP-UX, Solaris Operating Environment, WIN32 (Intel), LINUX (Intel, S390, PPC), IRIX, OSF, DYNIX

Fix pack structure

Patch Contents in CD_1 and CD_2

The fix pack image is structured in two CDs. This section lists their contents.

Patch Contents in CD_1:

- 8.2.0-TIV-TWS-FP0007.README (this file)
- AIX:
 - CLI
 - bin
 - catalog
 - codeset
 - FP_TWS_AIX.SPB
 - SETUP.bin
 - twspatch
- HPUX:
 - CLI
 - bin
 - catalog
 - codeset
 - FP_TWS_HP.SPB
 - SETUP.bin
 - twspatch
- GA_fixes
 - APAR IY48550
 - APAR IY49101
 - APAR IY52229
 - APAR IY54084
 - APAR IY63808
- RESPONSE_FILE
- SOLARIS:
 - CLI
 - bin
 - catalog
 - codeset
 - FP_TWS_SOLARIS.SPB
 - SETUP.bin
 - twspatch
- WINDOWS:
 - FP_TWS_WINDOWS.SPB
 - SETUP.exe
- TWSD_CONN

- TWSPLUS
- SETUP.JAR
- media.inf

Patch Contents in CD_2:

- Add-On
- DYNIX:
 - MAESTRO.TAR
- IRIX:
 - MAESTRO.TAR
- LINUX_I386:
 - CLI
 - bin
 - Catalog
 - Codeset
 - FP_TWS_LINUX_I386.SPB
 - SETUP.bin
 - twspatch
- LINUX_PPC:
 - MAESTRO.TAR
- LINUX_S390:
 - CLI
 - bin
 - Catalog
 - Codeset
 - FP_TWS_LINUX_S390.SPB
 - SETUP.bin
 - twspatch
- OSF:
 - MAESTRO.TAR
- RESPONSE_FILE
- TWSD_LCONN (Linux only)
- TWSPLUS
- SETUP.JAR
- media.inf
- 8.2.0-TIV-TWS_WEP-FP0001

New Features in Tivoli Workload Scheduler 8.2 Fix Pack 07

Described below are new features in Tivoli Workload Scheduler 8.2 Fix Pack 7

APAR IY64108: Tivoli Workload Scheduler 8.2 - Magent Support On Linux Platform.

Tivoli Workload Scheduler 8.2 fix pack 7 contains the support for Magent component on Linux Platform. The supported Linux platforms for this feature are as follows:

- RHEL 2.1

- (IA32)
- RHAS 2.1
- RHAS 3.0

APAR IY63410: In IBM Tivoli Workload Scheduler 8.2 Fix pack 6, the default date format for stdist job output is shown in the following example: Fri 15/10/04 11:05:24 AM GMT.

A new variable called UNISON_DATE_FORMAT was introduced to allow you to specify a 4 digit year format on job outputs.

UNISON_DATE_FORMAT = "%a %x %X %Z" will produce:

Fri 15/10/04 11:05:24 AM GMT 2004

The default (2 digit year) stdlist output display is obtained with the following variable setting:

UNISON_DATE_FORMAT="%a %x %X %Z".

This variable must be set locally on every workstation for which you want to display the 4 digit year format. This will affect the way the year is displayed in the job output display (stdlist).

Feature IY65271: introduces a new option in the BmEvents.conf file which will allow you to reduce network events traffic for schedules. The new parameter is called "CHSCHEM". It can be set to HIGH or LOW. Default value is HIGH.

If it is set to HIGH, the behavior of batchman related to schedule events sending is the actual one of TWS 8.2: an event will be sent, according to the filters established by the parameter settings in the BmEvents.conf file, for any schedule status transaction.

If the parameter is set to LOW, only the initial status transactions of the schedule will be tracked by an event: HOLD->READY->EXEC. For all the lifetime of the jobs into the schedule, no update of the schedule status will be reported by events, until the schedule reaches its final status. At this point an event will track the final status for the schedule. If the schedule has more than one final status, for each final status an event will be sent: for example, a schedule completed in ABEND status because of a job that abends. The event 151 (schedule abended) is sent. The job is rerun and completes successfully. The schedule assumes the SUCC status and the event 154 (schedule completed) is sent.

Particular behaviors have critical events like 152 (schedule stuck), 161 (schedule is cancel pending), 155 (until expired time with suppress onuntil option), 164 (until time expired with continue onuntil option), 165 (until time expired with cancel onuntil option), 163 (schedule is late): they are not initial, neither final statuses, however they cause an event sent (operator needs to be alert regardless by those events).

The policy used to filter the initial events (153 schedule started, 156 schedule submitted, 158 schedule ready, 159 schedule hold) is the same used in TWS 7.0 for the event 153: they are generated only when the schedule started date is still 0. As a consequence, event 153 is issued only once in the schedule life (even if this schedule is carried forward through several days). Events 158 and 159, instead,

could be generated more than once between the instant at which the schedule is created until the time it starts: a dependency is added to a schedule which resolved its dependencies. Its status changes from HOLD->READY->HOLD before it starts the first time, so the events 159, 158, 159 are generated.

The following table shows a list of schedule events supported by TWS 8.2 release; in the "chsched low" column "yes" states that the specified event is filtered by the CHSCHED parameter set to low, after the actual schedule started date is set:

Event Number	Description	CHSCHED Low
151	schedule abended	no
152	schedule is stuck	no
153	schedule started	yes
154	schedule ended	no
155	until time expired onuntil = suppr	no
156	schedule submitted	yes
157	schedule cancelled	no
158	schedule ready	yes
159	schedule hold	yes
160	schedule extrn	yes
161	schedule is cancel pending	no
162	schedule properties changed	yes
163	schedule is late	no
164	until time expired	no
165	onuntil = continue	no

New Features in Tivoli Workload Scheduler 8.2 Fix Pack 04

Described below are new features in Tivoli Workload Scheduler 8.2 Fix Pack 4

Tivoli Workload Scheduler 8.2 - Fault Tolerance Switch

Tivoli Workload Scheduler 8.2 fix pack contains the new "Fault Tolerance Switch" feature. Details can be found in the "IBM Tivoli Workload Scheduler 8.2 - Fault Tolerance Switch" document in this package.

Notes for the "Fault Tolerance Switch":

1. To activate this feature, add the following line into the <install dir>/mozart/globalopts file on the master domain manager: enable switch fault tolerance = yes
By default the feature is not active.
2. When the feature is active, the operation of Full Status agents will be different from that of previous releases. Refer to the "IBM Tivoli Workload Scheduler 8.2 - Fault Tolerance Switch" document.
3. Note that the installation of this fix pack replaces the NetConf file under the <install dir>/network directory.

4. The messages introduced with the feature are only available in English (LANG = C)
5. Remember that the feature can be activated only when the code of all the instances has been aligned to this version.

New Features in Tivoli Workload Scheduler 8.2 Fix Pack 03

Shown below are new Features in Tivoli Workload Scheduler 8.2 Fix Pack 3

- Internal CMVC Defect 169058
Symptoms: E2E alignment with Tracker Agents.

Note:

This defect is the implementation on Tivoli Workload Scheduler distributed of the changes needed to support the NP, UN, and EX commands in the E2E environment. Tivoli Workload Scheduler for z/OS 8.2.0 customers using the E2E feature that installs APAR PQ84233 to use the nop, un-nop and execute commands, (previously unsupported for operations defined on Fault-tolerant workstations) also need to install the Tivoli Workload Scheduler 8.2.0 Fix Pack 3 on all FTAs.

Internal CMVC Defect 168083

Symptoms: E2E: Re-use of deleted dependencies position.

Note: This defect is the implementation on Tivoli Workload Scheduler distributed of the changes needed to support the new feature introduced in an end-to-End environment by APAR PQ76474: End-to-End job can have 40 dependencies reusing the deleted dependency position.

The code fix for internal defect 168083 only applies to Tivoli Workload Scheduler networks working in end-to-end environments (that is, where the master domain manager is a z/OS host).

A dependency is a condition that must be satisfied before a job (or operation) is launched. When Tivoli Workload Scheduler works in end-to-end configurations, only followers (successor/predecessor) and time dependencies are allowed. The maximum number of follower dependencies allowed for an operation (job) is 40. Using either ISPF or the Job Scheduling Console, users can add or remove predecessors/successors of a certain operation running on a fault-tolerant workstation.

The problem fixed by this patch occurs when the operation (job) already has 40 dependencies. If a user first deletes a number of dependencies to make room for new ones (keeping the number within the allowed limit) and then tries to add new dependencies, Tivoli Workload Scheduler will log on stdlist that the limit of 40 dependencies has been reached and that the new ones cannot be inserted.

Product fix history

Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector Fix Pack 07 for Version 8.2.0 supersedes all the fixes released previously for the product. The following section includes all the APARs and defects shipped for Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector Fix Pack 07 for Version 8.2.0.

This section lists the APARs and defects fixed in Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector Fix Pack 07 for Version 8.2.0. It is divided into the following sub-sections:

- “APARs and Defects Fixed in Tivoli Workload Scheduler, Connector and Tivoli Plus Module Fix Pack 07 for Version 8.2.0” on page 7

- “Defects on 8.2.0-TIV-TWS-FP0007” on page 8
- “APARs Reported for 8.1” on page 9
- “APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 06 for Version 8.2.0” on page 9
- “APARs reported for 8.1” on page 11
- “APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 05 for Version 8.2.0” on page 11
- “APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 05 for Version 8.1” on page 13
- “APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 04 for Version 8.2.0” on page 13
- “APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 04 for Version 8.1” on page 15
- “APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 03 for Version 8.2.0” on page 16
- “APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 03 for Version 8.1” on page 18
- “APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 02 for Version 8.2.0” on page 19
- “APARs fixed in Tivoli Workload Scheduler and Connector Fix Pack 02 for Version 8.1” on page 20
- “APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 01 for Version 8.2.0” on page 22
- “APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 01 for Version 8.1” on page 24
- “APARs Fixed on Installation for Tivoli Workload Scheduler 8.2 GA” on page 26

APARs and Defects Fixed in Tivoli Workload Scheduler, Connector and Tivoli Plus Module Fix Pack 07 for Version 8.2.0

This section lists the APARs and defects fixed in Tivoli Workload Scheduler, Connector and Tivoli Plus Module Fix Pack 07 for Version 8.2.0

- APAR IY62216
Symptoms: AWSBDW301E Experienced error 3.0 reading courier error
- APAR IY63410
Symptoms: TWS STDLIST date format year written as two digit instead of four
- APAR IY63447
Symptoms: TWSREGISTRY.DAT includes a wrong entry for LINUX S390
- APAR IY63541
Symptoms: Mailman timeout following stops symphony message should be configured
- APAR IY63701
Symptoms: SRC/LIB/SYMACCS.C:2082 SYM_I_2_E() unexpected symphony record
- APAR IY63852
Symptoms: R11XTR -MDOES not show entries for day light saving time
- APAR IY64031
Symptoms: Composer message, such as AWSBCZ025W and AWSBCZ024W are garbled
- APAR IY64283
Symptoms: Problems linking 8.2 FP04 windows FTAS - writer appears to stay up
- APAR IY64331
Symptoms: ONUNTIL cancel action performed FTER job has started

- APAR IY64367
Symptoms: "CONMAN KILL JOBID" command returns a negative return code on unix
- APAR IY65271
Symptoms: Since 8.1, the event 153 is sent every time the status changes.
- APAR IY65401
Symptoms: "AWSBCV137W an event loss was likely detected at start of replay protocol"
- APAR IY65592
Symptoms: The REPTR -POST -DETAIL path to source file create a error
- APAR IY65629
Symptoms: 8.2.0-TWS-FP04 for ITWS Plus Module fails on AIX in interconnected TMR
- APAR IY66374
Symptoms: Error message AWSBCT301E returned when using the delete utility.
- APAR IY66445
Symptoms: REP7.CMD ON W2K uses any available path for the sort command.
- APAR IY66490
Symptoms: SYNC_GATEWAYS.SH use a wrong default user (TWUSER)
- APAR IY66492
Symptoms: TWS 8.2.0 running REPTR -POST the pid gives only 6 figures: 168363
- APAR IY66600
Symptoms: Add warning message into STDLIST file when job status in inconsistent.
- APAR IY66763
Symptoms: JBXTRACT command always returns a not null code on UNIX.
- APAR IY66841
Symptoms: CONMAN dumps when specific domain users submit jobs.
- APAR IY66999
Symptoms: Job scriptname field contained a non existent path/filename can cause TWS to crash.
- APAR IY67167
Symptoms: BATCHMAN on terminates by SIGSEGV when writing an event to log.
- APAR IY67603
Symptoms: Report 9B gives a wrong total in estimated run time for schedule
- APAR IY68132
Symptoms: Cannot start tws service on windows NT 4.0 after applying 8.2.0-TIV-TWS-FP0006.

Defects on 8.2.0-TIV-TWS-FP0007

- Internal CMVC Defect 169728
Symptoms: Cancel pend on schedules does not work
- Internal CMVC Defect 171815
Symptoms: BDMFT: warning messages appear during replay protocol Mm server.

- Internal CMVC Defect 173089
Symptoms: Unexpected Symphony record type on stdlist of tier2 platform
- Internal CMVC Defect 174492
Symptoms: TWS E2E Server ABEND878
- Internal CMVC Defect 175405
Symptoms: E2E - wrong management of continuation character in centralized security
- Internal CMVC Defect 175643
Symptoms: E2E - move writer process above 16M line
- Internal CMVC Defect 175719
Symptoms: Missing check on composer add job causes JSC error
- Internal CMVC Defect 175995
Symptoms: conman sbs AT=2300 after TWS 8.2 fix pack 4 got a trap on Windows
- Internal CMVC Defect 176479
Symptoms: iRIX: sequence GA->FP6->FP7 has caused wrong link C->C in POSIX
- Internal CMVC Defect 176690
Symptoms: Add/replace/disp jobs using parameters does not work
- Internal CMVC Defect 176830
Symptoms: DB lists of JS are not shown defining a JS on a domain.

APARs Reported for 8.1

This section lists the APARs Reported for 8.1.

- APAR IY64049
Symptoms: CONMAN CS <SCHEDULE>: PEND not working correctly
- APAR IY64454
Symptoms: Unable to use parameter in TWS security file.
- APAR IY64470
Symptoms: Jobs not running on FTA even though there is a new symphony record.
- APAR IY64480
Symptoms: Schedulr returns AWS22090035 if MASTSKED contains a job stream.
- APAR IY65726
Symptoms: USERJOBS JOBSTREAM can be cancelled.
- APAR IY66709
Symptoms: /VAR/TMP/SCHED.<PID>.P File is not removed when submitted a job stream from JSC, if SCRIPTNAME OR DOCCOMAND is very long.
- APAR IY67122
Symptoms: STAGEMAN ERROR AWS22030080I error: referenced record position

APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 06 for Version 8.2.0

This section lists the APARs and defects fixed in Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector Fix Pack 06.

- APAR IY58635
Symptoms: TWS 8.2.0 Fix pack Installer doesn't create all installation log files
- APAR IY58730

- Symptoms: Different output of "conman sc" on Master and FTA
- APAR IY59076
 - Symptoms: TWS 8.2 scheduling performance affected by CCLog default settings
- APAR IY59330
 - Symptoms: Centralized security error even when security file has been uploaded to the FTA
- APAR IY59483
 - Symptoms: composer/jsc allow OPENS file dependency definition with path greater than 120 characters
- APAR IY60008
 - Symptoms: AWSBCV067E Error reading PO Box, mailman goes down although "No Error" message is reported
- APAR IY60078
 - Symptoms: Error reading PO Box, when mailman is sending POBOx messages and writer is interrupted
- APAR IY60555
 - Symptoms: tws_launch_archiver.pl script capitalization problem
- APAR IY60567
 - Symptoms: FTA can not be stopped, after switchmgr has been performed while the FTA was down
- APAR IY61052
 - Symptoms: "conman submit" with nocheck option returns an error
- APAR IY61233
 - Symptoms: Mailman on FTA loops when linked from BDM after Jnextday and switchmngmr
- APAR IY61264
 - Symptoms: Deadline of submitted job is not include in audit files
- APAR IY61375
 - Symptoms: Netman service can cause other Windows 2003 localsystem service not work properly
- APAR IY61396
 - Symptoms: Issuing conman "start ;demgr" command from the MDM generates error StartUp not found
- APAR IY61478
 - Symptoms: First link attempt after new plan build fails for all workstation
- APAR IY62171
 - Symptoms: Rep11 is producing incorrectly formatted output
- APAR IY62798
 - Symptoms: tws_launch_archiver.pl execution rejects some schedules with a planned date between 00.00.00 and 00.10.00
- APAR IY63416
 - Symptoms: UNISON_JOB environment variable erroneously changed
- APAR IY63446
 - Symptoms: Conman sj +state=SUCC,FENCE get only all jobs in FENCE state
- APAR IY63711
 - Symptoms: preinstall script on AIX detects TWS process active, although they are down

- APAR IY64593
Symptoms: Job description with DBCS is garbled after FP05,if composer "modify" is performed

Internal Defects for Version 8.2

- Internal CMVC Defect 169827
Symptoms: rep11 return wrong output on window
- Internal CMVC Defect 175453
Symptoms: This defect is to change the message AWSBHV080E added with apar IY61734
- Internal CMVC Defect 175517
Symptoms: Modify job or sched with user different that twsuser does not work
- Internal CMVC Defect 175532
Symptoms: After adding a file dependencies with JSC, qualifiers values are in brackets
- Internal CMVC Defect 175363
Symptoms: Incorrect msg on MODIFY CPU when not authorized

APARs reported for 8.1

Listed below are Apars reported for version 8.1

- APAR IY58243
Symptoms: The "Dependencies Status" is "not released", although it is cancelled
- APAR IY58973
Symptoms: AWS11130005 error is received when "composer validate" is issued by not the TWS user
- APAR IY59057
Symptoms: stdlist message not correct when communication between mailman and writer is interrupted
- APAR IY59058
Symptoms: Event 252 sent when actually the link was not dropped
- APAR IY61734
Symptoms: stageman memory fault reading symnew with missing dependencies
- APAR IY63093
Symptoms: recovery option of "CONTINUE AFTER RECOVERY" does not work properly

APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 05 for Version 8.2.0

This section lists the APARs and defects fixed in Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector Fix Pack 05

- APAR IY53815
Symptoms: Composer add/replace/modifyerror AWSBIA226W references incorrect line input file
- APAR IY54648
Symptoms: TWS 8.2 Standard Agent "AT" job execution not dependable if SA and host are in different time zones
- APAR IY55859
Symptoms: XREF -FILE does not show file name
- APAR IY55951

Symptoms: Estimated duration time becomes 01:00 if resubmit a job stream which has a duration time of 00:01.

- APAR IY56599
Symptoms: CLAGENT failing on AIX 5.2
- APAR IY56654
Symptoms: Setup EventServer for TWS task fails to finish on Linux system
- APAR IY56655
Symptoms: Configuring TME or NON TME TEC adaptor on Linux endpoint fails
- APAR IY57113
Symptoms: magent does not work properly if snmpv3 is being used and it was not migrated properly
- APAR IY57542
Symptoms: conman sp displays garbled DBCS character at the line break point
- APAR IY57601
Symptoms: AWSBDW063E Error: MDM is not in cpu table "AWSBDW063E Error: OPCMASTER is not in cpu table".
- APAR IY58104
Symptoms: There are orphaned TWS job objects when running TBSM discovery
- APAR IY58232
Symptoms: X-Agent hosted by Std Agent CPU Limit is Ignored
- APAR IY58360
Symptoms: switchmgr does not work if backup dm (BMDM) is in around 16th p
- APAR IY54959
Symptoms: maestro.info is empty in version directory on Windows Platform
- APAR IY56317
Symptoms: showexec did not works fine
- APAR IY50278
Symptoms: abended recovery jobs status shows as exec/running indefinitely
- APAR IY58655
Symptoms: launching jobs from JSC 1.3 (fp03) with bad security settings.
- APAR IY58566
Symptoms: AWSBCW048E AND AWSBCW049E ISSUED IN STDLIST TWSMERGE LOG
- APAR IY58975
Symptoms: TWS should be able launch centralized XA (R3BATCH) jobs
- APAR IY59425
Symptoms: TWS kills processes and does not restore during patch install

Internal Defects for version 8.2

Listed below are Internal defects for version 8.2

- Internal CMVC Defect 157236
Symptoms: Mailman dies if LINK with SSL
- Internal CMVC Defect 171631
Symptoms: User Mod by Composer is not possible to do
- Internal CMVC Defect 171774
Symptoms: Open SSL 0.9.7 Security Flaw

- Internal CMVC Defect 172062
Symptoms: switchmgr does not work correctly if 16 FTA in environment
- Internal CMVC Defect 172140
Symptoms: composer replace resources fails on LINUX
- Internal CMVC Defect 172637
Symptoms: performance improvement for job definition in db
- Internal CMVC Defect 173172
Symptoms: IY41442 porting
- Internal CMVC Defect 173210
Symptoms: E2E: Heap memory corruption
- Internal CMVC Defect 173502
Symptoms: APAR IY41632 was not erroneously ported into release 8.2

APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 05 for Version 8.1

Listed below are Apars reported for version 8.1

- APAR IY55835
Symptoms: Dependency prompt is created after JNEXTDAY for a follows
- APAR IY55706
Symptoms: CONMAN H SHOWRESOURCES does not work
- APAR IY57199
Symptoms: Reporter dies with SIGSEGV due to memory corruption
- APAR IY58174
Symptoms: JOBMON fails to create tmp file at start up time if multiple TW
- APAR IY58454
Symptoms: Internetwork dependencies prompt dependencies prompt for a CF schedule gets truncated
- APAR IY58834
Symptoms: composer create says 'unable to open' file despite the file being

APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 04 for Version 8.2.0

This section lists the APARs and defects fixed in Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector Fix Pack 04 for Version 8.2.0.

- APAR IY54585
Symptoms: maestro_plan on Linux terminates with signal 11 when ad-hoc submission is done from JSC
- APAR IY52481
Symptoms: Job stdlist incorrectly reported for domain user/local user on windows 2003
- APAR IY52420
Symptoms: Domain User jobs will go to ABEND status when FP01 or FP02 is installed
- APAR IY53016
Symptoms: reporter command displays garbled DBCS characters
- APAR IY53227
Symptoms: Ad-hoc jobstream stays on hold when MASTER and FTA have different timezone

- APAR IY53266
Symptoms: The event 122 is not logged to event.log for job which runs on FTA
- APAR IY53017
Symptoms: Composer AWSBIA151W warning: deadline time occurs before AT time
- APAR IY54586
Symptoms: Headers of reports 9d and 10b do not line up with the data
- APAR IY53230
Symptoms: Event 51 is lost in event.log at Jnextday time if FTA has serverId defined
- APAR IY53228
Symptoms: When Master and FTA have different timezone setting conman sj does not display the actual start time correctly
- APAR IY54694
Symptoms: Batchman dies when job stream until time is reached and when the on until cont is used in the definition
- APAR IY53386
Symptoms: Wrong routing table record causes large numbers of TWS 8.2 RD message entries in MERGE.log
- APAR IY54975
Symptoms: Job log cannot be retrieved when workstation cpu name is 16 characters
- APAR IY54578
Symptoms: JSC 1.2 GJS1052 & AWS22230003 Unable to create an ID/handle message is unclear
- APAR IY55175
Symptoms: Mailman server memory corruption on W2K TWS Master
- APAR IY55606
Symptoms: TWS 8.2 Plus Module will not install on TMR after MN has been created
- APAR IY54342
Symptoms: Batchup service is not started after a conman start
- APAR IY56056
Symptoms: TWS events are not sent to TEC server after applying TEC fix pack02 or fix pack05
- APAR IY57077
Symptoms: New "Fault Tolerance Switch" feature

Internal Defects for Version 8.2

Listed below are Internal Defects for version 8.2

- Internal CMVC Defect 169936
Symptoms: conman "stop ;progressive" does not work in TWS 8.2 FP03
- Internal CMVC Defect 167318
Symptoms: Remove Copyright String from jobmanrc
- Internal CMVC Defect 167060
Symptoms: Uninstallation of TWS82 does not remove the Fix Pack's SPB on HP
- Internal CMVC Defect 160931

- Symptoms: batchman goes down if you list more than 43 events
- Internal CMVC Defect 168717
Symptoms: Submit ad hoc: job submitted after an error message
- Internal CMVC Defect 170663
Symptoms: Conman sbj core dump on Solaris and job stays on ADD.

APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 04 for Version 8.1

Listed below are Apars reported for version 8.1

- APAR IY51927
Symptoms: JSC hangs when trying to obtain 'Status of All Files'
- APAR IY52337
Symptoms: Standard Agent (SA) Job Abend and PID J0 when executed during Jnextday
- APAR IY53520
Symptoms: Schedule with job that has +1 days, scheduled to launch on day when DST changes the time, shows the incorrect launch time.
- APAR IY47219
Symptoms: engine hangs when listing or setting alternate plan with many entries in the schedlog directory
- APAR IY52339
Symptoms: composer and conman ctreate tmp files
- APAR IY53831
Symptoms: use of symbolic link or mounted file system for schedlog produces schedlog file that is 512 bytes
- APAR IY49695
Symptoms: TWS connector programs abend with SIGSEGV if no security is present when a list is loaded in JSC
- APAR IY51314
Symptoms: cancelled jobs still in exec allows rerun action from jsc and conman
- APAR IY52253
Symptoms: jsc filter on login fails to retrieve more than 250 records
- APAR IY49599
Symptoms: job stream containing an external dependency are not submitted correctly by conman
- APAR IY50186
Symptoms: The job description of JOB1 is moved to JOB2's within the job stream definition after modifying the JOB2
- APAR IY55455
Symptoms: fdopen fails in JOBMON because reached FOPEN_MAX number of streams
- APAR IY56810
Symptoms: datecalc did not work with date as gg-monthname-year
- APAR IY55456
Symptoms: Jobmon.exe has handle leaks with TWS 8.1

APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 03 for Version 8.2.0

This section lists the APARs and defects fixed in Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector Fix Pack 03 for Version 8.2.0.

- APAR IY48125
Symptoms: TWSUSER is not displayed in many commands STDOUT (JOB INFO, COMPO SER, CONMAN...)
- APAR IY48550
Symptoms: The migration to Tivoli Workload Scheduler 8.2 is not working when the perversion is installed in the root of your own file system.
- APAR IY48597
Symptoms: Writer periodically shows in conman sc, not just other FTAs
- APAR IY50927
Symptoms: Parms cannot used from Conman with Tivoli Workload Scheduler 8.1 and 8.2
- APAR IY51011
Symptoms: Tivoli Workload Scheduler 8.2 permission's of the "at" binary are incorrectly set at install, limiting the usability.
- APAR IY51657
Symptoms: Joblog on FTA can not be browsed only when 1. DM is on Solaris. 2. FTA belongs to DB. and 3. FTA has behindfirewall=yes
- APAR IY51745
Symptoms: Build removes script names in 8.2
- APAR IY52199
Symptoms: When alternate plan is set, job dependencies are not shown
- APAR IY52229
Symptoms: Tivoli Workload Scheduler 8.2 will not install on Windows 2000, NT or XP Systems When USERID Contains "-" Character
- APAR IY52257
Symptoms: Missing entries in conman "sc;info" output on FTA's
- APAR IY52616
Symptoms: STDLIST/LOGS directory have permissions 700
- APAR IY52693
Symptoms: Can not retrieve joblog from MDM/PDM when Tivoli Workload Scheduler 8.2 Standard Agent has "Behind Firewall" enabled.
- APAR IY52707
Symptoms: Silent install of Tivoli Workload Scheduler FP02 failed due to missing of option "-silent"
- APAR IY53203
Symptoms: Submitting a job stream from JSC causes "maestro_plan" to go down on Linux when the time zone is enabled.
- APAR IY53248
Symptoms: Unable to adhoc submit jobs with JSC when user has tight security settings.
- APAR IY53443
Symptoms: User Info Field contains garbage with TWS 8.2 FP-02 StreamLogon fix in place.
- APAR IY53568

Symptoms: DATECALC fails and return code exit 1 for 'pic YYYYMMDDHHTT'
DATECALC: AWSDED022E Calendar name "days pic yyyymmddtt too long.

APARs reported for version 8.2

Listed below are APARs reported for version 8.2

- Internal CMVC Defect 143387
Symptoms: Defect to upload zip files of TWSA for z/OS and for Oracle.
- Internal CMVC Defect 152309
Symptoms: Limit 0 not honored on Tivoli Workload Scheduler 8.1 UNIX CPUS after .MSG, symphony.
- Internal CMVC Defect 155552
Symptoms: Can not specify a workstation class when creating a new job.
- Internal CMVC Defect 167044
Symptoms: Abend 0C4 in DNTOP (MKTIME C Routine).
- Internal CMVC Defect 168291
Symptoms: CT-CDL: Alternate install enabling on Linux.
- Internal CMVC Defect 168340
Symptoms: Outbound no fallback phase in replay when runno mismatch.
- Internal CMVC Defect 168372
Symptoms: The short id is replicated from the GUI.
- Internal CMVC Defect 168558
Symptoms: Porting TWS_DEV TWS_820.
- Internal CMVC Defect 168667
Symptoms: Defect for Tivoli Workload Scheduler 8.2 fix pack 3.
- Internal CMVC Defect 168700
Symptoms: Composer core dump when I use ignore keyword.
- Internal CMVC Defect 168865
Symptoms: platform OSF need to add a lib for cclog.
- Internal CMVC Defect 168886
Symptoms: FTA operations run after 00:00.
- Internal CMVC Defect 169004
Symptoms: sbd from FTA does not work after IY49599
- Internal CMVC Defect 169091
Symptoms: The twspatch script does not update the patch number correctly.
- Internal CMVC Defect 169093
Symptoms: Solaris dwnldr crash with signal 10 "bus Error".
- Internal CMVC Defect 169097
Symptoms: APAR PQ84233 - E2E alignment to Tracker Agents.
- Internal CMVC Defect 169103
Symptoms: customize.sh -reset_perm go in errors.
- Internal CMVC Defect 169242
Symptoms: BDMFT: kill of a job defined on fta win32 does not work
- Internal CMVC Defect 169289
Symptoms: Change on Tivoli Workload Scheduler distributed side when there are plus FTA.
- Internal CMVC Defect 169295

Symptoms: PTR 944 on APAR PQ84233

- Internal CMVC Defect 169297

Symptoms: Update from Tivoli Workload Scheduler 8.1 to Tivoli Workload Scheduler 8.2 fails on Linux platform

- Internal CMVC Defect 169666

Symptoms: Batchmanabend after a "sbd fta#pwd" with TZ enabled

APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 03 for Version 8.1

Listed below are Apars reported for version 8.1

- APAR IY31441

Symptoms: Limit 0 not honored on Tivoli Workload Scheduler 8.1 UNIX CPUA after .MSG, symphony, sinfonia, jobtable removed.

- APAR IY44883

Symptoms: Tivoli Workload Scheduler patch readmes need further NT patch requirements information.

- APAR IY46358

Symptoms: Large numbers of "The description for Event ID (10006) in Source (Maestro) cannot be found" messages in NT & W2K Application Logs

- APAR IY47866

Symptoms: When alternate plan is set, job dependencies are not shown.

- APAR IY48409

Symptoms: Tivoli Workload Scheduler 8.1 directory permissions fail security compliance.

- APAR IY49100

Symptoms: Validate and compiler allow jobs to be submitted for ignored FTA.

- APAR IY50193

Symptoms: Jobs are randomly kept in READY state when submitted.

- APAR IY50614

Symptoms: rxtrct hangs when schedule contains a 127+ character comment ending in a period ".".

- APAR IY50678

Symptoms: Tivoli Workload Scheduler 8.1 Receives DR WATSON error when JOBMON is looking up account name with PeopleSoft extended agent.

- APAR IY50680

Symptoms: Tivoli Workload Scheduler jobs remain in INTRO+ STATE on the PS X-AGENT.

- APAR IY50725

Symptoms: Unable to adhoc submit jobs with Job Scheduling Console when user has tight security settings.

- APAR IY50814

Symptoms: invalid handles in the jobmon code.

- APAR IY51097

Symptoms: schedulr command does not select schedule due to the order of "ON" keywords.

- APAR IY51363

Symptoms: Calendar DB corrupts when multiple "composer replace" are run simultaneously.

- APAR IY51658
Symptoms: Domain names greater than eight (8) characters cause problems with linking and unlinking subordinate FTAs.
- APAR IY51701
Symptoms: COMPOSER AWS22080148 WARNING: UNTIL time occurs before AT time Incorrect Warning for Time zones.
- APAR IY51712
Symptoms: Conman 'show schedules' command not properly sorting output.
- APAR IY52222
Symptoms: High CPU usage by CONMAN when doing show jobs @#@.
- APAR IY52241
Symptoms: Getting "AWS22020072 NO QUALIFIED ENTRIES" Error message when trying to display jobs using +STATE=ABEND or +STATE=HOLD
- APAR IY52476
Symptoms: Every jobs with AT times behavior should be changed back to the way it historically worked.
- APAR IY53201
Symptoms: After applying patch 8.1-TWS-FP09, JSC does not show jobstream/schedule descriptions even though composer does.

APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 02 for Version 8.2.0

This section lists the APARs and defects fixed in Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector Fix Pack 02 for Version 8.2.0.

- APAR IY46920
Symptoms: Tivoli Workload Scheduler 8.2 Composer did not save the right job definition true.
- APAR IY48535
Symptoms: Plus module for Tivoli Workload Scheduler 8.2 fails to install on Solaris 2.9.
- APAR IY48660
Symptoms: The Tivoli Workload Scheduler 8.2 "trapJobAbend" trap has a carriage return coded.
- APAR IY49672
Symptoms: Failed Tivoli Workload Scheduler job creates joblog.
- APAR IY50011
Symptoms: Tivoli Workload Scheduler 8.2 Fix Pack FP01 does not update patch.info or update version.info to state fix pack level.
- APAR IY50123
Symptoms: unable to submit jobstream defined for a cpu class in 8.2.
- APAR IY50146
Symptoms: Tivoli Workload Scheduler 8.2 NT4 FTAs does not work after applying FP-01.
- APAR IY50278
Symptoms: Abended recovery jobs status shows as exec/running indefinitely.
- APAR IY50833
Symptoms: Tivoli Workload Scheduler Plus Module FP01 fails to install on managed node.

Internal Defects for Version 8.2

Listed below are Internal Defects for version 8.2

- Internal CMVC Defect 159230
Symptoms: TOS error occurred with W2K and NT FTAs.
- Internal CMVC Defect 162604
Symptoms: Wrong date in the version.info.
- Internal CMVC Defect 165804
Symptoms: tws_env.sh does not work on tier 2.
- Internal CMVC Defect 165955
Symptoms: jobstdl does not work fine on AIX when put the flags -num.
- Internal CMVC Defect 167026
Symptoms: Connector def.to complete IY49870.
- Internal CMVC Defect 167089
Symptoms: SSL netman default port must be 31113.
- Internal CMVC Defect 167349
Symptoms: Tier 2 customize script writes a bad patch_id into patch.info.
- Internal CMVC Defect 167777
Failed Tivoli Workload Scheduler job creates joblog in STDLIST directory.

APARs fixed in Tivoli Workload Scheduler and Connector Fix Pack 02 for Version 8.1

Listed below are APARs reported for version 8.1

- APAR IY35151
Symptoms: Numerous directory permissions are world-writable, which is a security flaw.
- APAR IY35486
Symptoms: Improve error reporting of NT/W2K domain errors.
- APAR IY40719
Symptoms: 'Version -A' command does not return correct patch information.
- APAR IY41341
Symptoms: Performance issues for Tivoli Workload Scheduler with the AUTOTRACE feature.
- APAR IY42981
Symptoms: Validate error on opens.
- APAR IY45818
Symptoms: Limit of 0 not honored on Standard Agent.
- APAR IY45913
Symptoms: TWS SCHED on Master stays READY even if its job on FTA goes SUCC.
- APAR IY46139
Symptoms: Bogus opens dependency OPENS FTA#" causes Jobman to abend on A.
- APAR IY46140
Symptoms: Tivoli Workload Scheduler- Process goes down after delete of resource with 2 parallel.
- APAR IY46202
Symptoms: The variable \$UNISON_HOST is set every time to the master WKS.

- APAR IY46411
Symptoms: REP11 reports incorrect planned date.
- APAR IY46414
Symptoms: Cannot define an NT-user beginning with a numerical character from composer.
- APAR IY46787
Symptoms: Cancel job stream - resource not released - opens dep placed on job stream during exec of job.
- APAR IY46970
Symptoms: Composer create CMD do not use the UMASK setting.
- APAR IY47381
Symptoms: After applying fix pack 7 - conman SJ (SHOWJOB) error on symphony and JSC properties empty for job.
- APAR IY47889
Symptoms: JSC cannot save jobstream. Reason : AWS22220027 error finding object '\$MASTER'.
- APAR IY48072
Symptoms: Schedules with run cycles containing workdays offsets and free days features no not run on the right day.
- APAR IY48076
Symptoms: Tivoli Workload Scheduler with FP06 on W2K does not run all the possible jobs defined on XA, even if the CPU limit is not reached.
- APAR IY48325
Symptoms: Jobs with open dependencies launch even though Batchman shows.
- APAR IY49003
Symptoms: X-Agent hosted by \$MASTER is shown as unlinked from JSC.
- APAR IY49150
Symptoms: DBCS users GECOS field gets garbled in Tivoli Workload Scheduler job output.
- APAR IY49379
Symptoms: R11XTR core dump when run REP11
- APAR IY49420
Symptoms: Tivoli Workload Scheduler Plus Module 8.1 - DM Monitor - STDLIST space used does not work on Windows platform - DU.EXE permission problems.
- APAR IY49577
Symptoms: CARRYFORWARD schedules causing corrupt symphony file messages in high demand environment.
- APAR IY49672
Symptoms: Failed Tivoli Workload Scheduler job creates joblog.
- APAR IY49876
Symptoms: Jobinfo not working correctly in 8.1 - rstrt_flag, job_name, re_t.
- APAR IY50126
Symptoms: Plus module for Tivoli Workload Scheduler 8.2 fails to install on Solaris 2.9.

APARs and Defects Fixed in Tivoli Workload Scheduler and Connector Fix Pack 01 for Version 8.2.0

This section lists the APARs and defects fixed in Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector Fix Pack 01 for Version 8.2.0.

- APAR IY46794
Symptoms: Adding Time zone to Tivoli Workload Scheduler 8.2 CPU Definition prevents JSC 1.2 from opening CPU Definitions.
- APAR IY47285
Symptoms: VERSION.INFO is empty after installing 8.2.
- APAR IY48050
Symptoms: RMSTDLIST does not work properly.
- APAR IY48230
Symptoms: WINDOWS Tivoli Workload Scheduler 8.2 FTA not resolving file dependencies.

Internal Defects for Version 8.2

Listed below are Internal Defects for version 8.2

- Internal CMVC Defect 162765
Symptoms: oserv failure when submitting a job with more than one file dep.
- Internal CMVC Defect 163852
Symptoms: Avoid core dumps on mm print mailbox = yes.
- Internal CMVC Defect 164003
Symptoms: setthe default stdlist width to 0 on localopts.
- Internal CMVC Defect 165981
Symptoms: complete porting for defect 162765.
- Internal CMVC Defect 152308
Symptoms: Days offset is not logged in STDLIST when adding a dependency.
- Internal CMVC Defect 155370
Symptoms: Audit log file is logged in UTF-8 locale.
- Internal CMVC Defect 155371
Symptoms: Defect to complete fix for IY47563.
- Internal CMVC Defect 155558
Symptoms: Incorrect stdlist sj output.
- Internal CMVC Defect 157227
Symptoms: Switchmgr on DM loops.
- Internal CMVC Defect 157841
Symptoms: wmaeutil.sh <TWS object instance name -dbinfo "*" does not work.
- Internal CMVC Defect 159757
Symptoms: Switchmgr has no effect if backup was not started in a Tivoli Workload Scheduler Environment.
- Internal CMVC Defect 159782
Symptoms: Wrong error messages when actions are not allowed on a job.
- Internal CMVC Defect 159791
Symptoms: Display access to prompt, parms, resource in the security.
- Internal CMVC Defect 160047
Symptoms: There is no synchronization between batchup and mailman on WNT.
- Internal CMVC Defect 160128

- Symptoms: elapsed time displayed with negative values.
- Internal CMVC Defect 160234
Symptoms: alignment with Tivoli Workload Scheduler for z/OS GA PTF.
- Internal CMVC Defect 160687
Symptoms: DIVT: Need to support tecad_win logfile adapter.
- Internal CMVC Defect 160851
Symptoms: submit job loses recovery options radio buttons.
- Internal CMVC Defect 160913
Symptoms: DIVT: TEC message parsing fails for some of Tivoli Workload Scheduler events on W2K.
- Internal CMVC Defect 162065
Symptoms: Jobs abend on Solaris after installing fix pack 7.
- Internal CMVC Defect 162067
Symptoms: Problems with calendars having dates greater than 01/18/20038.
- Internal CMVC Defect 162145
Symptoms: Submitting a job in a different cpu.
- Internal CMVC Defect 162150
Symptoms: oserv failure when adding a file dependency to a job.
- Internal CMVC Defect 162181
Symptoms: rmstdlist does not work correctly.
- Internal CMVC Defect 162182
Symptoms: jobstdl does not work correctly.
- Internal CMVC Defect 162275
Symptoms: Writer process abends when calling issuemsgtobuf.
- Internal CMVC Defect 162718
Symptoms: FTA becomes unavailable after conman command adddep.
- Internal CMVC Defect 162720
Symptoms: ESP-GS: Batchman Core on e2e + NetView.
- Internal CMVC Defect 162787
Symptoms: wrong error message when NT user is found.
- Internal CMVC Defect 163595
Symptoms: File missed integration for APAR IY43352 (defect 161854).
- Internal CMVC Defect 164351
Symptoms: enabling log on console on UNIX platform.
- Internal CMVC Defect 164688
Symptoms: LINUX Platform: spb file is not found.
- Internal CMVC Defect 164837
Symptoms: For complete porting of IY30687.
- Internal CMVC Defect 164980
Symptoms: DIVT: Some commands do not work stating incorrect syntax on Win.
- Internal CMVC Defect 165048
Symptoms: DIVT: Audit log file record using UTF-8 when JSC is used.
- Internal CMVC Defect 165090
Symptoms: DIVT: Windows Tivoli Workload Scheduler service does not start after system reboot.

- Internal CMVC Defect 165135
Symptoms: IY47987: Job suspended TEC event must not be sent if UNTIL exp.
- Internal CMVC Defect 165142
Symptoms: Rollback on Windows fails if Tivoli Workload Scheduler services are not started.
- Internal CMVC Defect 165200
Symptoms: Confirming a job, the wrong job is being confirmed "SUCC".
- Internal CMVC Defect 165241
Symptoms: DIVT: Job cancel event not sent to TEC.
- Internal CMVC Defect 165245
Symptoms: JOBMAN abends on Solaris Operating Environment.
- Internal CMVC Defect 165444
Symptoms: TWSPlus 8.2 event 111: wrong mapping with maestro.

APARs Fixed in Tivoli Workload Scheduler and Connector Fix Pack 01 for Version 8.1

Listed below are Apars reported for version 8.1

- APAR IY30687
Symptoms: Cannot perform a KILL command on child-process by Tivoli Workload Scheduler (W2K).
- APAR IY31085
Symptoms: Days offset is not logged in STDLIST when adding a dependency.
- APAR IY32174
Symptoms: Compiler stops with error if a recovery job is missing.
- APAR IY32257
Symptoms: Number of successful jobs field is incorrect for carried forward jobstream.
- APAR IY32693
Symptoms: TWS/NETVIEW: The positional variable \$12 for the trap 101 UTTRAPJOBABEND is displayed in HEX instead of in decimal.
- APAR IY34233
Symptoms: EVTSIZE on INTERCOM.MSG is reset to default at JNEXTDAY
- APAR IY35020
Symptoms: JSC ADHOC submission of jobstreams containing OPENS WITH ends with "UNABLE TO SUBMIT".
- APAR IY35151
Symptoms: Numerous directory permissions are word-writable, which is a security flow.
- APAR IY36997
Symptoms: VIA command line is impossible to create schedules that contain jobs with different workstation classes - this breaks JNEXTDAY.
- APAR IY37706
Symptoms: TWD DB/PLAN audit files are writable by every user.
- APAR IY37999
Symptoms: Compiler fails to add a dummy job in fail state during JNEXTDAY.
- APAR IY38037

- Symptoms: Unable to create a job that logs on as a user that is greater than 8 characters.
- APAR IY38040
Symptoms: Incorrect error message ****ERROR**(23) AWS22080023 JOB XXXXXX** not found in job master instead of access denied error.
 - APAR IY38156
Symptoms: JOBSTD and MORESTD commands do not produce any output for any user other than the maestro user.
 - APAR IY38216
Symptoms: When confirming a job, the wrong job is being confirmed "SUCC" in JSC 1.2.
 - APAR IY38798
Symptoms: FILEAID does not display correctly records with RECNUM > 65535.
 - APAR IY38884
Symptoms: Tivoli Workload Scheduler 8.1 - Event 107 not generated.
 - APAR IY39073
Symptoms: Conman SC does not show the L flag for XA hosted by \$MASTER.
 - APAR IY39603
Symptoms: New event needed in EVENT.LOG.
 - APAR IY40463
Symptoms: The "DATECALC SCHEDDATE" command is no longer reporting the original production date on carryforward schedules.
 - APAR IY40825
Symptoms: Recovery Job inheriting "interactive" job definition from parent.
 - APAR IY40910
Symptoms: Cannot run any Tivoli tasks on certain TME EPS after installing.
 - APAR IY41035
Symptoms: Sched with name of 16 characters and jobname of 12 char in a cpuclass does not work.
 - APAR IY41433
Symptoms: Tivoli Workload Scheduler cannot create calendars past year 2038.
 - APAR IY41442
Symptoms: Event 101-119 missing parameter.
 - APAR IY41485
Symptoms: WS distributed is to send different instance IDS for all the jobs except for jobs rerun.
 - APAR IY41586
Symptoms: Conman SS (SHOW SCHEDULES) does not show correct status.
 - APAR IY41632
Symptoms: New parameter needed into TEC events
 - APAR IY41774
Symptoms Conman SC does not show the L flag for XA hosted by \$MASTER.
 - APAR IY41863
Symptoms: Composer VERIFY does not receive hard return errors in dependencies.
 - APAR IY41868

- Symptoms: Every job w/file dependency can run too quickly.
- APAR IY42465
Symptoms: Jobtable is created with wrong run number after recovery.
- APAR IY42468
Symptoms: Some characters are garbled when viewing job stdlist, due to corrupted packets sent by SCRIBNER, related to apar IY38683.
- APAR IY42607
Symptoms: Netman (and other processes) handle leak.
- APAR IY42731
Symptoms: Kill corrupting jobtable.
- APAR IY42797
Symptoms: Batchman abended with AWS21000301E experienced error 3.0 reading courier in ../../SRC/JOBMAN/COURIER.C:READ_COURIER.
- APAR IY42981
Symptoms: Validate error on opens dependency.
- APAR IY43246
Symptoms: Composer create jobs - format incorrect in output file
- APAR IY43302
Symptoms: JOBSTD L script returned the error 0403-027 the parameter list I.
- APAR IY43352
Symptoms: Optimization needed for locking mechanism on jobtable.
- APAR IY43491
Symptoms: JSC LINK/UNLINK status wrong for FTA when host is unlinked.
- APAR IY43608
Symptoms: Conman "SJ +STATE=FENCE" does not properly select the jobs in fence state.
- APAR IY44102
Symptoms: Stageman attempts to use a record number (32768) in Symphony file.
- APAR IY44297
Symptoms: EVTSIZE -SHOW command output.
- APAR IY44471
Symptoms: JSConsole does not update Job status correctly if the job status is changed from CLI.
- APAR IY44845
Symptoms: AWS2201003E too many jobs for BATCHMAN since APAR IY38717.
- APAR IY45955
Symptoms: Parent of switched domain manager makes error in computing rout.
- APAR IY46100
Symptoms: Cannot define non local resources dependencies from JSC1.2
- APAR IY46724
Symptoms: CONFIRM SUCC for job via JSC is not working for FTA'S.
- APAR IY47563
Symptoms: Symphony decompression problem - follow up to IY36118.

APARs Fixed on Installation for Tivoli Workload Scheduler 8.2 GA

This section lists the APARs fixed in Tivoli Workload Scheduler 8.2 GA.

Note: See Readme file in the tar/zip files that are contained in the following directory: GA Fixes in CD 1

- APAR IY52229
Symptoms: Tivoli Workload Scheduler 8.2 does not install on Windows 2000, NT, or XP Systems when USERID contains "-" character
- APAR IY48550
Symptoms: The migration to Tivoli Workload Scheduler 8.2 is not working when the perversion is installed in the root of own filesystem.
- APAR IY54084
Symptoms: Tivoli has provided a CLI install action for all other tier I platforms except for LINUX. Customer needs same capability.
- APAR IY49101
Symptoms: twsinst -update moves /usr/bin during 8.2 upgrades from prior release.
Note: APAR IY49101 - AIX, HP, SOLARIS Platforms. The Alternate Installation changed when migrating to a Tivoli Workload Scheduler 8.2 version from a previous Tivoli Workload Scheduler version (7.0 or 8.1). You can use the new version of the Alternate Install script file performing the following steps:
 - Copy locally the Tivoli Workload Scheduler 8.2 CD contents for the specific Platform.
 - Write the twsinst script in the OS specific directory.
 - Run the twsinst script with the -update option. See *Tivoli Workload Scheduler 8.2 Planning and Installation Guide* for more details.
- APAR IY63808
Symptoms: A Windows service with a display name very long causes the Configuration Manager to hang

Limitations

This section describes all limitations applying to Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector Fix Pack 06. It contains the following sub-sections:

- "Known Defects and Limitations for the Scheduler"
- "Known Defects and Limitations for Tivoli Workload Scheduler Connector" on page 29
- "Known Defects and Limitations for the Scheduler in E2E Environment" on page 29
- "Installation" on page 30

Known Defects and Limitations for the Scheduler

The following Defects and limitations apply to the Scheduler:

The following are known open problems:

- In the *Tivoli Workload Scheduler Reference Guide* correct the following example of the **makecal** command:

```
makecal -e -i24  
makecal -r 3 -s "30 MAY 1999"-i30
```

as follows:

```
makecal -e -i 24  
makecal -r 3 -s "30 MAY 1999" -i 30
```

A blank space is required between the -i and the digits.

- Defect 165116 - dj command does not work on Windows.
- Defect 165022 - Documentation error in Tivoli Workload Scheduler 8.2 *Reference Guide*.
- Defects 165444 and 166007 - Event=118 and Event type=111 cause PARSING ERROR in TEC server.
- Defect 169695 - DIVT: Fix packs cannot be uninstalled by uninstaller.bin on AIX
- Defect 171749 - CMD.EXE permissions must be mod. to exec jobs in w2k3 Act.Dir. When you want to exec a job in a w2k3 active the directory environment with a w2k3 Domain User, you must add the "cmd.exe" exec permissions to that user, carry out the following steps:
 1. go in \windows\system32
 2. right click on cmd.exe -> properties
 3. click on "Security"
 4. in the "Group or User Names" click "Add" button
 5. Add the Domain User you want to exec the TWS jobs
 6. click OK, Apply and OK
- Defect 172269 - Netconf file installed with root ownership in TWS8.2 FP04. The Netconf file is installed generally under network dir with twsuser ownership. FP04 substituted this file because there are two new entries but the ownership is assign to root user. Workaround: set the ownership of Netconf file.

If you install 8.2-TWS-FPx on the product General Availability (GA) Version. If you uninstall the Tivoli Workload Scheduler 8.2 successfully, and the fix pack entry is not correctly unregistered, the following problem occurs: If you try to install the small scenario again, after the installation of Tivoli Workload Scheduler 8.2 GA for the same user, the 8.2-TWS-FPx fix pack will look like it is already installed. As a result you will not be able to install it. To workaround this problem :

1. Commit the fix pack by running the setup program or the twspatch script and running a commit action on the fix pack.
2. Repair the fix pack by running the setup program or the twspatch script and running a repair action.

The fix pack will be installed in the commit state.

Defect 169571 – DIVT: Applying the fix pack changes the TIME format from JST to UTC.

Workaround:

The time format was changed from JST to UTC by applying Tivoli Workload Scheduler Fix Packs. Tivoli Workload Scheduler 8.2 Fix Pack Installer starts netman automatically using the "UTC" timezone and the local "C" and all descendant processes will run under the netman environment. The workaround to this problem is to stop and restart the Tivoli Workload Scheduler netman process after the fix pack installation ends.

Defect 169384 – Uninstall using "twsinst" fails because of incorrect package name saved in the TWSRegistry.dat file on LINUX_S90(64 bit). Workaround: After the installation of Tivoli Workload Scheduler 8.2, perform the following steps:

1. Open /etc/TWS/TWSRegistry.dat file
2. Replace the line:


```
/Tivoli/Workload/Scheduler/"TWSUSER"_DN_Package_Name=TWS_LINUX_I386_"TWSUSER".8.2
```

with:

```
/Tivoli/Workload/Scheduler/"TWSUSER"_DN_Package_Name=TWS_LINUX_S390_"TWSUSER".8.2
```

3. Before you install again using the same TWSUSER, remove from the file /etc/TWS/TWSRegistry.dat the remaining line:

```
/Tivoli/Workload/Scheduler/"TWSUSER"_DN_Package_Name=TWS_LINUX_S390_"TWSUSER".8.2
```

Defect 169600: DIVT: Segmentation fault for jbxtract on Solaris9

Defect 169572: DIVT: console display nothing for job after applying FP03.

Defect 170905: The event 165 is not logged into the MASTER's event.log for job which runs on FTA

Defect 173580 - CrScrE2e: different behavior WNT and LINUX for failing job Centralized scripts too long on win platform cause TWS jobs go to failed status.

Known Defects and Limitations for Tivoli Workload Scheduler Connector

Configuration The following Defects limitations apply to the Tivoli Workload Scheduler Connector:

- TMR Server where Connector 8.2 and patch 2 are installed
- Managed Node without Tivoli Workload Scheduler Connector

In this scenario of a TMR Server that has already installed the Tivoli Workload Scheduler Connector 8.2.0 GA + fix pack 1 or greater, when the user tries to install the Tivoli Workload Scheduler Connector 8.2.0 GA on a Managed Node that is connected to this TMR an error occurs. The installation error is like: "The revision levels of the installation and media do not match: "8.2.02 <-> 8.2.00"

This was due to an incorrect revision level of Tivoli Workload Scheduler 8.2.0 Connector GA and there is a workaround to bypass this problem and to be able to install on the Managed Node.

Copy onto your local Machine (where the Managed Node is installed) all the images of the Tivoli Workload Scheduler Connector 8.2.0 GA and then edit the TWS_CONN.ind file to change the revision level from 8.2.00 to 8.2.02.

If you have installed on the TMR Server the Tivoli Workload Scheduler Connector 8.2.0 GA and fix pack 2, the revision level must be 8.2.02. Otherwise, if you had on the TMR Server the Tivoli Workload Scheduler 8.2.0 Connector fix pack 1, the revision level to set is 8.2.01.

In this way the installation of the Tivoli Workload Scheduler Connector 8.2.0 GA is allowed.

Defect 165405 - Audit plan log file record uses UTF-8 when JSC is used.

Known Defects and Limitations for the Scheduler in E2E Environment

The following Defects and limitations apply to the Scheduler in the E2E Environment:

- APAR - PQ93878: E2E - Error executing a centralized script with VARSUB and continuation character.

The execution of a centralized script in a E2E environment can fail if the variable substitution is used in a line with the continuation character, in this case the script content is incorrectly parsed.

Installation

This section describes how to install Tivoli Workload Scheduler and Tivoli Workload Scheduler Connector Fix Pack 06. It is divided into the following sections:

- “Windows”
- “UNIX (IRIX, OSF, DYNIX, LINUX_PPC)”
- “UNIX (AIX, HP-UX, Solaris Operating Environment, LINUX I386, LINUX S390) - Graphical Installation” on page 31
- “UNIX (AIX, HP-UX, Solaris Operating Environment) - Alternate Installation” on page 31
- “Additional Installation Instructions” on page 31
- “Installation Log Files” on page 33
- “Product Uninstall on Tier 1” on page 34
- “Tivoli Workload Scheduler Connector” on page 34
- “Tivoli Workload Scheduler Plus Module” on page 35

Applying the Fix Pack

Note: If the product was originally installed using the ISMP method, the fix pack should also be installed by this method. If another method is used to patch, you may experience various errors and a bad state of registry. Read “Additional Installation Instructions” on page 31 before installing the fix pack.

Windows: While installing the fix pack on Windows 2000, you are recommended to keep Services snap-in and all other handles to the Tivoli Workload Scheduler services closed (see Microsoft Windows bug Q287516 for more information).

To apply the fix pack on Windows NT and on Windows 2000 follow the steps below:

1. Download the WINDOWS directory on your system.
2. Unlink the host on which you are installing the patch from the IBM Tivoli Workload Scheduler network and shut down IBM Tivoli Workload Scheduler. Use the following commands:

```
conman "unlink @!@; noask"
conman "stop @!@; wait"
conman "shut;wait"shutdown
```

If you had jobs scheduled on the computer, make sure they have completed; otherwise some processes, such as jobmon or joblnch could still be active.
3. Run SETUP.exe to install the fix pack and follow the instructions on the screen. When required, select the instance of the Tivoli Workload Scheduler on which you are installing the patch.

UNIX (IRIX, OSF, DYNIX, LINUX_PPC): Follow these steps to apply the fix pack:

1. Download the operating system-specific MAESTRO.TAR file to the Tivoli Workload Scheduler home directory and untar it with the following command:

```
tar xvf MAESTRO.TAR
```

This creates the following two files:

- maestro.tar.Z
 - customize
2. You may have to set the **execute** bit on the **customize** script. Use this command:

```
chmod 755 customize
```
 3. Unlink the host on which you are installing the patch from the IBM Tivoli Workload Scheduler network and shut down IBM Tivoli Workload Scheduler. Use the following commands:

```
conman "unlink @!@; noask"  
conman "stop @!@; wait"  
conman "shut; wait"
```
 4. Run the **customize** script with the **-update** option. Use the following command:

```
customize -update -uname <tw_s_user>
```

UNIX (AIX, HP-UX, Solaris Operating Environment, LINUX I386, LINUX S390) - Graphical Installation: Follow these steps to apply the fix pack:

1. Download the operating system-specific directory, SETUP.jar and media.inf files on your system.
2. Unlink the host on which you are installing the patch from the IBM Tivoli Workload Scheduler network and shut down IBM Tivoli Workload Scheduler. Use the following commands:

```
conman "unlink @!@; noask"  
conman "stop @!@; wait"  
conman "shut; wait"
```
3. Run SETUP.bin to install the fix pack and follow the instructions on the screen. When required, select the instance of the Tivoli Workload Scheduler on which you are installing the fix pack.

UNIX (AIX, HP-UX, Solaris Operating Environment) - Alternate Installation:

1. On the patch CD, go to the directory named according to your operating system.
2. Unlink the host you are installing the patch on from the IBM Tivoli Workload Scheduler network and shut down IBM Tivoli Workload Scheduler. Use the following commands:

```
conman "unlink @!@; noask"  
conman "stop @!@; wait"  
conman "shut; wait"
```
3. Run the twspatch script, use the following option:

```
./twspatch -install -uname <tw_s_user>.
```

Additional Installation Instructions

New Installation Methods on Tier 1 Platforms: When you use the graphical installation or the command line installation you can perform the following actions:

- Apply the fix pack in "undoable" mode (this means that it is possible to roll back the modified files).
- Roll back an undoable fix pack.
- Commit an undoable fix pack (this means that it will not be possible to roll back the fix pack).

- Repair an already committed fix pack. This action allows you to restore an existing Tivoli Workload Scheduler instance to the current committed level when a problem arises with a binary.

Depending on the fix pack installation state, you can perform the action as shown below:

Initial state	Action	Final State
-	apply	IU
IU	commit	IC
IU	roll back	-
IC	repair	IC

where:

- IU = installed undoable
- IC = installed and committed

If you have a Tivoli Workload Scheduler fix pack installed in "undoable mode" (IU state) on your machine and you are applying a more recent Tivoli Workload Scheduler fix pack on it, all the changes that you have made when installing the previous Tivoli Workload Scheduler fix pack will be committed before applying the newer ones. Therefore, if you undo the fix pack you last installed, you will restore the previous fix pack changes. These changes are permanent. The setup program discovers all the Tivoli Workload Scheduler 8.2 instances existing on the machine. After selecting one of these, it is possible to specify the required action.

The table below shows the actions that are performed on your installed fix packs when patching a Tivoli Workload Scheduler 8.2 instance:

Initial state	Action	Final State
FP01=IU FP01=IC	apply FP02	FP01=IC+FP02=IU
FP01=IC+FP02=IU FP02=IU	commit FP02	FP02=IC
FP01=IC+FP02=IU FP02=IU	roll back FP02	FP01=IC

An alternative way to use the graphical installation is the silent installation. The silent installation requires the response file customization. A template of the response file is available on both CDs, in the RESPONSE_FILE directory.

You can use the silent installation by launching the SETUP.bin (SETUP.exe on Windows Systems) program as follows:

```
./SETUP.bin -options/opt/tws/FP02/patchInstall.txt -silent
```

where patchInstall.txt is a customized response file.

On AIX, HP-UX, Solaris Operating Environment, Linux_IX86, and Linux_S390 platforms you can install the fix pack using the twspatch script file. The synopsis of twspatch is:

- ./twspatch -{install | undo | commit | repair} -uname <TWS user>

The fix pack installation is recorded in the TWSRegistry.dat file adding the following lines:

```
product_dir=/home/root/.swdis/work
working_dir=/home/root/.swdis/backup
trace_level=0
trace_size=1000000
sen_timeout=300
autopack_dir=/home/root/.swdis/autopack
staging_dir=/home/root/.swdis/service
user_file_variables=/home/root/.swdis/swdis.var
import_libraries=spd,libecimp
```

where:

- \$(SWD-OS-NAME) depends on the platform where you are installing.
- \$(tws_user) is the Tivoli Workload Scheduler instance owner.
- \$(patch_id) is the fix pack number.

On Tier 2 Platforms, the existing customize script is available for installation. For more details about the new installation technologies refer to the *"Planning and Installation Guide"*.

Installation Log Files: To check the installation status look in the following log files:

```
/tmp/FP_TWS_<platform>_<TWS user>^8.2.0.01.log (%TEMP% on windows)
/tmp/TWSImp.log (%TEMP% on windows)
/tmp/TWSinstall.log (%TEMP% on windows)
```

Space Needed to Back Up Copy Creation: On AIX, HP-UX, Solaris Operating Environment, LINUX-I386, LINUX-S390 and Windows platforms the fix pack installation is SPB Technology based (as for Tivoli Workload Scheduler 8.2 GA installation). Every time you install a Tivoli Workload Scheduler 8.2 fix pack it is installed in "undoable mode".

"Undoable" means that a backup copy of the existing binaries is created automatically before replacing them with the newer ones. This installation mode allows the modifications introduced by the installed fix pack to be rolled back until you commit them.

You should commit the fix pack after checking the installation. By default, on UNIX Systems the CM/SPB working directory is set to the home directory of the installing user and for Tivoli Workload Scheduler installation the installing user is root. This is a CM4.2 configuration based on the /etc/Tivoli/swdis.ini file on UNIX Systems (%WINDIR%/swdis.ini on Windows systems). It stores the following information (needed by CM4.2 to run): product_dir=/home/root/.swdis/work working_dir=/home/root/.swdis/backup trace_level=0 trace_size=1000000 sen_timeout=300 autopack_dir=/home/root/.swdis/autopack staging_dir=/home/root/.swdis/service user_file_variables=/home/root/.swdis/swdis.var import_libraries=spd,libecimp where the root home directory is /home/root.

So, for every Tivoli Workload Scheduler 8.2 installation that you patch, you will find:

- A backup copy under the /home/root/.swdis/backup directory. Every backup copy will be removed when committing the fix pack for a specific Tivoli Workload Scheduler 8.2 installation.

- An entry in the CM 4.2 catalog. The CM `wlssp` command displays a list of all the products installed with the help of Configuration Manager.

The space requirements for creating the backup copy are shown in the following table:

Platform	Space (Mb)
Windows	10
Unix	25

Before installing a fix pack check the `/home/root` capability. If there is not enough space you need to change the CM 4.2 configuration by performing the following steps:

1. Open the `swdis.ini` file and replace the path `/home/root` by setting a path with the required capability for all path variables defined in the `swdis.ini` file.
2. Move the already existing `.swdis` directory from `/home/root` to `/<new_path>` to save the existing information.

Product Uninstall on Tier 1: Using the ISMP setup program (AIX, Solaris Operating Environment, HP-UX, LINUX, Windows): Run the Tivoli Workload Scheduler 8.2 GA ISMP uninstaller program to uninstall the Tivoli Workload Scheduler 8.2 instance and the related installed fix pack. See Tivoli Workload Scheduler 8.2 *Installation and Planning Guide* for more details about the ISMP uninstaller program.

Using alternate installation (AIX, Solaris Operating Environment, HP-UX, LINUX_I386 and LINUX_S390): Run the following two steps to uninstall the Tivoli Workload Scheduler:

1. Uninstall the current fix pack as follows:
`<TWS home>/twspatch -remove -uname <TWS user>`
2. Uninstall Tivoli Workload Scheduler as follows:
`<TWS home>/twsinst -uninst -uname <TWS user>`

Note: The `twspatch -remove` command can only be used to uninstall the fix pack.

Both uninstall methods need a Tivoli Configuration Manager update before you run them. Starting from this fix pack a new tool is available for copying the needed software from the TWS 8.2 FPx images to the TWSHome path. You will find the script named "copyCMcli" under all Tier 1 directories. The following is the copyCMcli script synopsis:

```
copyCMcli <source path> <target path>
```

Where:

`<source path>` -- path in which is contained the IBM Configuration Manager CLI directory (AIX, Solaris Operating Environment, HP-UX, LINUX_I386 and LINUX_S390).

`<target path>` -- IBM Tivoli Workload Scheduler installation path

Tivoli Workload Scheduler Connector: It is required that both the Tivoli Workload Scheduler master workstation and the connector be at the same level.

Therefore, when you install this fix pack on the connector, make sure that you also install the fix pack for the Tivoli Workload Scheduler engine on the master workstation.

To install this fix pack, you must have the General Availability version of the connector for IBM Tivoli Workload Scheduler 8.2, with or without the previous fix pack.

To install the fix pack, follow these steps on the workstation that runs the connector:

1. Insert the CD of the fix pack.
2. Open the Tivoli desktop and click on Desktop -> Install->Install Patch....
3. Select the installation path in the file browser of Select Media.
4. Follow the instructions listed in the Tivoli Job Scheduling Console User's Guide to complete installation.

Tivoli Workload Scheduler Plus Module

To apply the fix pack successfully on the Plus Module, you must have the install_product and super authorization roles. Carry out the following steps:

1. Using the Tivoli desktop, select the Install -> Install Patch... option from the Desktop menu to display the Install Patch dialog.
2. Press the Select Media... button to display the File Browser dialog.
3. Enter the path to the directory containing the patch in the Path Name: field.
4. Press the Set Media & Close button to return to the Install Patch dialog. The patch install list now contains the name of the patch. Select the patch by clicking on it.
5. Select the clients where you want to install this patch.
6. Press the Install button to install the patch."

The TWSPPlus installation has been written to be supported only in C/en LANG. Before installing TWSPPlus perform the following steps to set the framework locale to C:

1. LANG=C
2. export LANG
3. LC_ALL=C
4. export LC_ALL
5. locale=C
6. export locale
7. wsetlang -o
8. Restart the oserv
9. Start the TWSPPlus installation

Documentation notes

This section contains new information and documentation corrections contained in this fix pack. It is divided in the following sub-sections:

- "New information contained in this Fix pack" on page 36
- "Documentation problems and corrections" on page 36
- "New Option for the evtsize Command" on page 37
- "**Autotrace level 3.1.5**" on page 37

New information contained in this Fix pack

The Section below contains new information in this Fix Pack:

APAR IY63410: In IBM Tivoli Workload Scheduler 8.2 Fix pack 6, the default date format for stdlist job output is shown in the following example: Fri 15/10/04 11:05:24 AM GMT.

A new variable called UNISON_DATE_FORMAT was introduced to allow you to specify a 4 digit year format on job outputs.

UNISON_DATE_FORMAT = "%a %x %X %Z" will produce:

Fri 15/10/04 11:05:24 AM GMT 2004

The default (2 digit year) stdlist output display is obtained with the following variable setting:

UNISON_DATE_FORMAT="%a %x %X %Z".

This variable must be set locally on every workstation for which you want to display the 4 digit year format. This will affect the way the year is displayed in the job output display (stdlist).

Documentation problems and corrections

APAR - IY52481 – Microsoft answers to the ticket problem number SRQ040419601863 that the cmd.exe on Windows 2003 Enterprise Edition does not have rights to execute/read for a normal user, but it has these grants for the built-in group INTERACTIVE.

Changes for the user: The user has to check for the correct cmd.exe rights, and choose one of the following options:

1. Directly, by adding the rights for its streamlogon user;
2. Creating a group TWS_GROUP (in this case he can set the logon as batch and logon on locally for more facility use) and he can sets the righth read/execute for the group TWS_GROUP for the cmd.exe, then he can add its stream logon user in the TWS_GROUP he needs to create a new stream logon users.
3. By adding the rights read/exec for the group USERS (for default, belong to this group all domain user and local user) for the cmd.exe executable.
4. Add the rights read/exec for the group BATCH for the cmd.exe executable.

APAR IY53228: The time when a jobstream starts to correspond to the time when the first job of the jobstream started. After this APAR when the timezone feature is enabled the time when a jobstream started is always displayed in the timezone of the CPU for which the jobstream is defined.

APAR IY53815: If you define a job using more than two parameters for a FTA cpu, you get two or more warning messages, only the first warning shows the line content where the warning occurs. The others message shows only the lines number where the warning occurs but don't show the line contents.

APAR IY52476 : Every job with AT times behavior should be changed back to the way it worked before.

APAR IY52475: is a DOC APAR raised to explain how Tivoli Workload Scheduler works with the EVERY option. If the every option is used with the AT dependency

the product is designed to launch jobs at specific points in time. The following example launches the job testjob1 every 15 minutes, "testjob1 at 1800 every 15"

The job is launched at 1800, 1815, 1830 and so on. If one rerun is delayed (for a dependency or for any other reason) the product realigns to the AT time so in this case it is possible that one or two iterations do not respect the EVERY rate. For example, if the above job is submitted adhoc at 1833 the reruns occur at 1833, 1834, 1845 and so on.

In the example above, the job started at 1833, the start time is set to 1800 and it starts at 1833 the next rerun will have the start time set to 1830 (the start time of the previous job + three every rate) and it starts at 1834, the next rerun will have the start time set to 1845, it will start at 1845.

To calculate the number of iterations that do not respect the every rate in a job, you have to consider two time values.

- The start time: this is the expected start time of the job, it is displayed by conman when the job has not started to run. It is set to the AT time specified for the job or to the time when the rerun should be launched.
- The time started: this is the actual start time of the job, it is displayed by conman when the job has run.

To calculate the number of iterations that do not respect the every rate you have to consider the last run of the job.

When Tivoli Workload Scheduler creates a new "rerun job" it sets the "expected" start time of the job, this value is calculated by adding to the start_time of the previous job as many "every rate" as possible but without exceeding the current.

If the EVERY option is used without the AT dependency the rerun jobs will be scheduled always respecting the EVERY rate specified, starting from the time when the job actually started.

If the EVERY option is used with the AT dependency there could be some interactions that do not respect the EVERY rate. For all other cases the every rate is always respected

New Option for the evtsize Command: The format for the evtsize command has a new option. Instead of:

```
evtsize {-V | -U | <filename><newsiz> }
```

the syntax is now:

```
evtsize {-V | -U | -show <filename><newsiz> | }
```

to allow for queries on the current file maximum size and current queue length.

Autotrace level 3.1.5: This fix pack uses Autotrace level 3.1.5. The new level is used to fix APAR IY37113. As a consequence, before you run any of the Autotrace commands (contained in the <TWS home>/trace directory), you must set the environment variables as follows:

```
ATTRACELIB=/usr/Tivoli/TWS/TKG/3.1.5/lib
```

- For AIX:
LIBPATH=\$ATTRACELIB:\$LIBPATH; export LIBPATH
- For HP-UX:

```
LIBPATH=$ATTRACELIB:$LIBPATH; export LIBPATH (32bit)
SHLIB_PATH=$ATTRACELIB:$SHLIB_PATH; export SHLIB_PATH (64 bit)
```

- For Solaris Operating Environment:

```
LD_LIBRARY_PATH=$ATTRACELIB:$LD_LIBRARY_PATH;export LD_LIBRARY_PATH
```

Defect 175350: "On page 88 of IBM Tivoli Workload Scheduler: Administration and Troubleshooting, version 8.2, (Revised December 2004), the following should be inserted in the section 'Jnextday problems' (before the section 'Problems running jobs'):

After running Jnextday you notice that a remote workstation does not immediately initialize. The following message is seen:

```
16:26:44 ... WRITER:+++++
16:26:44 ... WRITER:+ AWSBCW037E Mailman still active, cannot initialize this cpu.
16:26:44 ... WRITER:+ +++++
16:26:44 ... WRITER:AWSBCW039E Error processing write to mailbox, total cpu 0
```

Cause and solution

If a remote mailman is still active on the remote workstation, Jnextday cannot download the Symphony file and initialize the next days activities for this cpu the first time. Instead, the master's mailman issues a **stop** command to the workstation. The workstation reacts in the normal way to the **stop** command, completing those activities it should complete and stopping those activities it can stop. After the interval determined in the localopts parameter *mm retrylink*, the domain manager tries again to initialize the workstation. When it finds that the **stop** command has been implemented, it commences to initialize the workstation, downloading the Symphony file and starting the workstation its activities.

Defect 176162: "On page 85 of IBM Tivoli Workload Scheduler: Administration and Troubleshooting, version 8.2, (Revised December 2004), the following should be inserted in the section 'Tivoli Management Framework problems' (before the section 'Composer problems'):

During an installation, an error message is displayed or logged, indicating that the Tivoli Management Region server has not been found. However, you know that the server has been successfully installed, and that you had correctly identified the host name of the server to the installation. The problem normally occurs when you are installing the Connector, but it might also occur in other Tivoli Management Framework discovery situations.

Cause and solution

The cause of this problem is that the Tivoli Management Region server is registered on your domain name server with a different name than its host name. This can occur on any operating system, but might particularly occur on HP-UX, where host names are limited to 8 characters. For example, if your enterprise has a standard for host name creation that exceeds 8 characters, the HP-UX computers will have actual host names of 8 characters, but the network administrator will have set up the domain name server so that it maps the longer standard host names to the actual host names.

The default name of the Tivoli Management Region Server is *<host_name>_region*; if the default has been used, the discovery process takes the host name part of this from the domain name server and uses it to verify the presence of the Tivoli

Management Region server. However, if the domain name server host name is different from the actual host name, it cannot make a match.

To resolve this problem there are two possible solutions:

- Install the Connector manually. This installation allows you to identify the Tivoli Management Region Server unequivocally using its real host name.
- Change the *<host_name>* part of the Tivoli Management Region server's name to reflect the actual host name. However, this might require you to uninstall and reinstall it, rendering this solution impractical.

Defect 176148:

When performing any type of installation on any operating system, you might receive the following error:

```
Error writing file = There may not be enough temporary disk space.  
Try using -is:tempdir to use a temporary directory on a partition  
with more disk space.
```

Note in particular the absence of an error code, which differentiates this message from a very similar message, with error code 28, that indicates that you are not logged on as root (see page 46).

Cause and solution

Normally this error means what it says; the solution is as follows.

First, try to redirect the installation to use a different temporary directory, by adding the `-is:tempdir .<temp_dir_path>` variable to the installation command.

If this does not work, you must use one of these two methods to give more space to the `swdis` directory:

- Either:

Create a new version in a different file system. The procedure is as follows:

In, command

In

1. Delete or rename both the work and the backup subdirectories and recreate the directories in a file system with more space in it.
2. Link the new directories to the `.swdis` directory using the `In -s` command.

- Or:

Create a new backup directory in a file system with more space in it, and modify the `/etc/Tivoli/swdis.ini` file to point to it.

However, you must pay attention to modify the correct section of the `swdis.ini` file, as follows:

- If you are making a local silent ISMP installation that uses the disconnected command line (**wdinstsp**), you should modify the value of the `backup_dir` key in the `[#MOBILE]` section.
- If you are making a remote installation using Tivoli Configuration Manager, you must identify the section relative to the endpoint chosen as the target (for example, `[lab133080_aix]`), and modify the `backup_dir` key in that section.

Defect 177524: twsclean script file fails on W2000.

To resolve this problem, uninstall the TWS Connector 82 (FP x) correctly by carrying out the following steps:

- Search for the following file: twsclean under the Tivoli Folder that is where the Tivoli framework was installed
- Open the file twsclean file
- In the twsclean file look for the following:

```
If [ "$INTERP" = "w32-ix86" ]; then
    TEMPDIR="$DBDIR"/tmp
```

else:

```
    TEMPDIR="$DBDIR"/tmp
fi
LOGDIR=$TEMPDIR
```

- Delete the section above because the variable substitution does not work correctly
- Replace the section above with the following:
TEMPDIR=<Path> (for example TEMPDIR=C:\tmp)
LOGDIR=\$TEMPDIR
- Save the file twsclean and exit
- Launch the following command in a Tivoli environment console:
wuninst TWSConnector <Managed Node> -rmfiles

Chapter 2. Contacting IBM Software Support

Before contacting IBM[®] Software Support with a problem, refer to the IBM Software Support site by accessing the following Web address:

<http://www.ibm.com/software/support>

To access Tivoli[®] support, click the Tivoli support link at the bottom right of the page.

If you want to contact IBM Software Support, see the *IBM Software Support Guide* at the following Web site:

<http://techsupport.services.ibm.com/guides/handbook.html>

The guide provides information about how to contact IBM Software Support, depending on the severity of your problem, and the following information:

- Registration and eligibility.
- Telephone numbers, depending on the country in which you are located.
- Information you must have before contacting IBM Software Support.

Chapter 3. Notices

This information was developed for products and services offered in the U.S.A. IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785 U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

IBM World Trade Asia Corporation
Licensing
2-31 Roppongi 3-chome, Minato-ku
Tokyo 106, Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement might not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
2Z4A/101
11400 Burnet Road
Austin, TX 78758 U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurement may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

If you are viewing this information in softcopy form, the photographs and color illustrations might not display.

Trademarks

IBM, the IBM logo, AIX®, Tivoli, the Tivoli logo, and z/OS are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both.

Microsoft, Windows, and Windows NT are registered trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries



Java™ and all Java-based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.

Linux™ is a trademark of Linus Torvalds in the United States, other countries, or both.

Other company, product, and service names may be trademarks or service marks of others.



Program Number: