

Enterprise beans -- table of contents

Development

4.3: Developing enterprise beans

4.3.4: Developing enterprise beans for use with the Connector Architecture

Writing Enterprise Beans

About this book

An introduction to enterprise beans

An architectural overview of the EJB programming environment

WebSphere Programming Model Extensions

More-advanced programming concepts for enterprise beans

Enabling transactions and security in enterprise beans

Developing enterprise beans

Developing EJB clients

Developing servlets that use enterprise beans

Tools for developing and deploying enterprise beans in the EJB server (AE) environment

Appendix A. Changes for version 1.1 of the EJB specification

Appendix B. Example code provided with WebSphere Application Server

Appendix D. Extensions to the EJB Specification

Administration

6.6.4: Administering EJB containers (overview)

6.6.4.0: EJB container properties

6.6.4.1: Administering enterprise bean containers with the Java administrative console

6.6.4.1.1: Configuring new EJB containers with the Java administrative console

6.6.5: Administering EJB modules (overview)

6.6.5.0: EJB module properties

6.6.5.0.1: Assembly properties for entity beans

6.6.5.0.2: Assembly properties for CMP fields

6.6.5.0.3: Assembly properties for method extensions

6.6.5.0.4: Assembly properties for session beans

6.6.5.0.5: Assembly properties for security roles

6.6.5.0.6: Assembly properties for method permissions

6.6.5.0.7: Assembly properties for container transactions

6.6.5.0aa: Assembly properties for EJB modules

6.6.5.1: Administering EJB modules with the Java administrative console

6.6.5.1.1: Installing EJB modules with the Java administrative console

6.6.5.1.2: Viewing deployment descriptors of EJB modules with the Java administrative console

6.6.5.1.3: Showing the status of EJB modules with the Java administrative console

6.6.5.1.4: Exporting table DDLs of EJB modules with the Java administrative console

6.6.5.1.5: Moving EJB modules to other application servers with the Java administrative console

6.6.5.5: Administering EJB modules with Application Assembly Tool

6.6.5.5.1: Creating an EJB module

4.3: Developing enterprise beans

Enterprise applications are applications that typically use enterprise beans. To develop enterprise applications, you must:

1. [Develop any session or entity beans your application will use](#)
2. [Create the deployment descriptor and the EJB JAR file.](#)
3. [Deploy the enterprise beans.](#)

Enterprise applications support both [transactions and security](#).

Writing Enterprise Beans is a programming guide for developing, packaging, and deploying enterprise beans in IBM WebSphere Application Server. It discusses both the Advanced Edition and Enterprise Edition of the product.

Format
PDF
HTML

4.3.4: Developing enterprise beans for use with the Connector Architecture (J2C)

It is assumed that you know how to create enterprise beans. This topic contains additional hints and tips which will help prepare your beans for successful deployment.

For information on the concepts behind EJB programming in WebSphere, see the following sources:

- Writing Enterprise Beans in WebSphere, especially the topics [An architectural overview of the EJB programming environment](#) and [An introduction to enterprise beans](#).
- The VisualAge for Java help topics under **Concepts > EJB Development Environment**.



Developing enterprise beans

The Connector Architecture (technology preview) runtime is tuned to support the EAB Session Beans that are produced by VisualAge for Java version 3.5.3 and later. You use the Enterprise Access Builder (EAB) feature of VisualAge for Java to create Session Beans that interact with non-relational backend systems such as CICS and IMS. VisualAge for Java also automatically generates significant parts of the enterprise bean code, and contains integrated tools for packaging and testing enterprise beans. For more information on using VisualAge for Java to develop enterprise beans, refer to the appropriate topics under the VisualAge for Java help topic **Tasks > Developing EJB components**.

Although use of VisualAge for Java is strongly recommended, it is not compulsory. For more information on developing enterprise beans without using VisualAge for Java, see [Tools for developing and deploying enterprise beans in the EJB server \(AE\) environment](#), especially the subtopic [Developing and deploying enterprise beans with EJB server \(AE\) tools](#).

Exporting enterprise beans from VisualAge for Java

To export your enterprise bean package from VisualAge for Java as a JAR file, complete the following steps:

1. In the Workbench, click the **EJB** tab. The EJB page appears.
2. In the Enterprise Beans pane, select your EJB Group or an individual bean.
3. From the pop-up menu for your EJB Group or bean, select **Export > EJB JAR....** The Export to an EJB JAR File wizard opens.
4. Type the name and full path for your exported .jar file in the **JAR file** field.
5. In the section **What do you want to include in the JAR file?**, complete the following steps:
 - a. Confirm that the checkboxes are enabled for **beans** and **.class**.
 - b. Confirm that the checkbox is cleared for **.java** and **.resource**.
 The reasons for not exporting .java and .resource files are that the .resource files are usually not necessary, and if you export the .java files then the WebSphere deployment step will attempt to re-compile these files and you will need additional .jar files on your classpath for the EAB runtime and resource adapter classes.
 - c. For **.class**, complete the following steps.
 To make your exported .jar file much smaller and quicker to process, you should only export those classes that are required to support your bean. This includes your bean, home, and remote interface, plus any utility or helper classes that might be contained in another project. The easiest way to get all of these utility and helper classes is to use **Select referenced types and resources** to pre-select *all* of the referenced classes that your EJB uses, then to deselect the projects that are

not required in the WebSphere environment.

- i. Click **Select referenced types and resources**.
- ii. Click the .class **Details** button.
- iii. Clear the checkboxes for the following Projects:
 - Connector CICS Beta
 - IBM Common Connector Framework
 - IBM Common Connector Framework 2
 - Connector Architecture (J2C)
 - IBM Enterprise Access Builder Library
 - IBM Java Record Library
 - Java Authentication and Authorization
- iv. Click **OK**.

6. Click **Finish**.

Your exported EJB jar file is now ready for [deployment in WebSphere](#).

- [0.42: Introducing the Connector Architecture \(J2C\)](#)
- [6.6.42: Administering J2C related administrative objects \(overview\)](#)
- [6.6.42.6: Installing the Connector Architecture \(J2C\)](#)

About this book

This document focuses on the development of enterprise beans written to the Sun Microsystems Enterprise JavaBeans^(TM) specification in the WebSphere^(TM) Application Server programming environment. It also discusses development of EJB clients that can access enterprise beans.

Who should read this book

This document is written for developers and system architects who want an introduction to programming enterprise beans and EJB clients in WebSphere Application Server. It is assumed that programmers are familiar with the concepts of object-oriented programming, distributed programming, and Web-based programming. Knowledge of the Sun Microsystems Java^(TM) programming language is also assumed.

Document organization

This document is organized as follows:

- [An architectural overview of the EJB programming environment](#) provides a high-level introduction to the EJB server environment in WebSphere Application Server.
 - [An introduction to enterprise beans](#) explains the main concepts associated with enterprise beans.
 - [Tools for developing and deploying enterprise beans](#) explains how to set up and use the tools used in developing and deploying enterprise beans.
 - [Developing enterprise beans](#) explains how to develop entity beans with container-managed persistence (CMP) and session beans. It also provides information on how to package enterprise beans for later deployment.
 - [Enabling transactions and security in enterprise beans](#) explains how to enable transactions in enterprise beans by using the appropriate deployment descriptor attributes.
 - [Developing EJB clients](#) explains the basic code required by an EJB client to use an enterprise bean. This chapter covers generic issues relevant to enterprise beans, Java applications, and Java servlets that use enterprise beans.
 - [Developing servlets that use enterprise beans](#) discusses the basic code required in a servlet that accesses an enterprise bean.
 - [More-advanced programming concepts for enterprise beans](#) explains how to develop a simple entity bean with bean-managed persistence and discusses the basic code required of an enterprise bean that manages its own transactions.
 - [Appendix A, Changes for version 1.1 of the EJB specification](#) describes features that are new or have changed in version 1.1 of the EJB specification and discusses migration issues for enterprise beans written to version 1.0 of the EJB specification.
 - [Appendix B, Example code provided with WebSphere Application Server](#) describes the major example used throughout this book and the additional examples that are delivered with the various editions of WebSphere Application Server.
 - [Appendix C, Extensions to the EJB Specification](#) describes the extensions to the EJB Specification that are specific to WebSphere Application Server. Use of these extensions is supported in VisualAge for Java only.
-

Related information

For further information on the topics discussed in this manual, see the following documents:

- [Getting Started with WebSphere Application Server](#)
 - [Building Business Solutions with WebSphere](#)
-

How to send your comments

Your feedback is important in helping to provide the most accurate and highest quality information. If you have any comments about this book, send your comments by e-mail to wasdoc@us.ibm.com. Be sure to include the name of the book, the document number of the book, the edition and version of WebSphere Application Server, and, if applicable, the specific location of the information you are commenting on (for example, a page number or table number).

An introduction to enterprise beans

This chapter looks at the characteristics and purpose of enterprise beans. It describes the two basic types of enterprise beans and their life cycles, and it provides an example of how enterprise beans can be combined to create distributed, three-tiered applications.

Bean basics

An enterprise bean is a Java component that can be combined with other enterprise beans and other Java components to create a distributed, three-tiered application. There are two types of enterprise beans:

- An *entity* bean encapsulates permanent data, which is stored in a data source such as a database or a file system, and associated methods to manipulate that data. In most cases, an entity bean must be accessed in some transactional manner. Instances of an entity bean are unique and they can be accessed by multiple users.

For example, the information about a bank account can be encapsulated in an entity bean. An account entity bean might contain an account ID, an account type (checking or savings), and a balance variable and methods to manipulate these variables.

- A *session* bean encapsulates ephemeral (nonpermanent) data associated with a particular EJB client. Unlike the data in an entity bean, the data in a session bean is not stored in a permanent data source, and no harm is caused if this data is lost. However, a session bean can update data in an underlying database, usually by accessing an entity bean. A session bean can also participate in a transaction.

When created, instances of a session bean are identical, though some session beans can store semipermanent data that makes them unique at certain points in their life cycle. A session bean is always associated with a single client; attempts to make concurrent calls result in an exception being thrown.

For example, the task associated with transferring funds between two bank accounts can be encapsulated in a session bean. Such a transfer session bean can find two instances of an account entity bean (by using the account IDs), and then subtract a specified amount from one account and add the same amount to the other account.

Entity beans

This section discusses the basics of entity beans.

Basic components of an entity bean


Every entity bean must have the following components, which are illustrated in [Figure 3](#):

- *Bean class*--This class encapsulates the data for the entity bean and contains the developer-implemented business methods that access the data. It also contains the methods used by the container to manage the life cycle of an entity bean instance. EJB clients (whether they are other enterprise beans or user components such as servlets) *never* access objects of this class directly; instead, they use the container-generated classes associated with the home and remote interfaces to manipulate the entity bean instance.
- *Home interface*--This interface defines the methods used by the client to create, find, and remove instances of the entity bean. This interface is implemented by the container during deployment in a class known generically as the *EJB home class*; instances are referred to as *EJB home objects*.
- *Remote interface*--Once the client has used the home interface to gain access to an entity bean, it uses this interface to invoke indirectly the business methods implemented in the bean class. This interface is

implemented by the container during deployment in a class known generically as the *EJB object class*; instances are referred to as *EJB objects*.

- *Primary key* -- One or more variables that uniquely identify a specific entity bean instance. A primary key that consists of a single variable of a primitive Java data type can be specified at deployment. A *primary key class* is used to encapsulate primary keys that consist of multiple variables or more complex Java data types. The primary key class also contains methods to create primary key objects and manipulate those objects.

Figure 3. The components of an entity bean



Data persistence

Entity beans encapsulate and manipulate *persistent* (or permanent) business data. For example, at a bank, entity beans can be used to model customer profiles, checking and savings accounts, car loans, mortgages, and customer transaction histories.

To ensure that this important data is not lost, the entity bean stores its data in a data source such as a database. When the data in an enterprise bean instance is changed, the data in the data source is synchronized with the bean data. Of course, this synchronization takes place within the context of the appropriate type of transaction, so that if a router goes down or a server fails, permanent changes are not lost. When you design an entity bean, you must decide whether you want the enterprise bean to handle this data synchronization or whether you want the container to handle it. An enterprise bean that handles its own data synchronization is said to implement *bean-managed persistence* (BMP), while an enterprise bean whose data synchronization is handled by the container is said to implement *container-managed persistence* (CMP).

Unless you have a good reason for implementing BMP, it is recommended that you design your entity beans to

use CMP. The code for an enterprise bean with CMP is easier to write and does not depend on any particular data storage product, making it more portable between EJB servers. However, you must use entity beans with BMP if you want to use a data source that is not supported by the EJB server.

Session beans

This section discusses the basics of session beans.


Basic components of a session bean

Every session bean must have the following components, which are illustrated in [Figure 4](#):

- *Bean class*--This class encapsulates the data associated with the session bean and contains the developer-implemented business methods that access this data. It also contains the methods used by the container to manage the life cycle of an session bean instance. EJB clients (whether they are other enterprise beans or user applications) *never* access objects of this class directly; instead, they use the container-generated classes associated with the home and remote interfaces to manipulate the session bean.
- *Home interface*--This interface defines the methods used by the client to create and remove instances of the session bean. This interface is implemented by the container during deployment in a class known generically as the *EJB home class*; instances are referred to as *EJB home object*.
- *Remote interface*--After the client has used the home interface to gain access to an session bean, it uses this interface to invoke indirectly the business methods implemented in the bean class. This interface is implemented by the container during deployment in a class known generically as the *EJB object class*; instances are referred to as *EJB objects*.

Unlike an entity bean, a session bean does not have a primary key class. A session bean does not require a primary key class because you do not need to search for specific instances of session beans.

Figure 4. The components of a session bean



Stateless versus stateful session beans

Session beans encapsulate data and methods associated with a user session, task, or ephemeral object. By definition, the data in a session bean instance is ephemeral; if it is lost, no real harm is done. For example, at a bank, session beans can represent a funds transfer, the creation of a customer profile or new account, and a withdrawal or deposit. If information about a fund transfer is already typed (but not yet committed), and a server fails, the balances of the bank accounts remains the same. Only the transfer data is lost, which can always be retyped.

The manner in which a session bean is designed determines whether its data is shorter lived or longer lived:

- If a session bean needs to maintain specific data across methods, it is referred to as a *stateful* session bean. When a session bean maintains data across methods, it is said to have a *conversational state*. A Web-based shopping cart is a classic use of a stateful session bean. As the shopping cart user adds items to and subtracts items from the shopping cart, the underlying session bean instance must maintain a record of the contents of the cart. After a particular EJB client begins using an instance of a stateful session bean, the client must continue to use that instance as long as the specific state of that instance is required. If the session bean instance is lost before the contents of the shopping cart are committed to an order, the shopper must load a new shopping cart.
- If a session bean does not need to maintain specific data across methods, it is referred to as a *stateless* session bean. The example Transfer session bean developed in [Developing session beans](#) provides an example of a stateless session bean. For stateless session beans, a client can use any instance to invoke any of the session bean's methods because all instances are the same.

Creating an EJB module

The last step in the development of an enterprise bean is the creation of an EJB module. An EJB module consists of the following:

- One or more deployable enterprise beans.
- A deployment descriptor, stored in an Extensible Markup Language (XML) file. This file contains information about the structure and external dependencies of the beans in the module, and application assembly information describing how the beans are to be used in an application.

The EJB module can be created by using the tools within an integrated development environment (IDE) like IBM's VisualAge for Java Enterprise Edition or by using the tools contained in WebSphere. For more information, see [Tools for developing and deploying enterprise beans](#).

The EJB module

The *EJB module* is used to assemble enterprise beans into a single deployable unit; this file uses the standard Java archive file format. The EJB module can contain individual enterprise beans or multiple enterprise beans. For more information, see [Creating an EJB module and deployment descriptor](#).

The deployment descriptor

The EJB module contains one or more deployable enterprise beans and one *deployment descriptor*. The deployment descriptor contains attribute and environment settings for each bean in the module, and it defines how the container invokes functionality for all beans in the module. The deployment descriptor attributes can be set for the entire enterprise bean or for the individual methods in the bean. The container uses the definition of the bean-level attribute unless a method-level attribute is defined, in which case the latter is used. The deployment descriptor contains the following information about entity and session beans. These attributes can be set on the bean only; they cannot be set on a specific method of the bean.

- The bean's name, class, home interfaces, remote interfaces, and bean type (entity or session).
- *Primary key class* attribute--Identifies the primary key class for the bean. For more information, see [Writing the primary key class \(entity with CMP\)](#) or [Writing or selecting the primary key class \(entity with BMP\)](#).
- *Persistence management*. Specifies whether persistence management is performed by the enterprise bean or by the container.
- *Container-managed fields* attribute--Lists those persistent variables in the bean class that the container must synchronize with fields in a corresponding data source to ensure that this data is persistent and consistent. For more information, see [Defining variables](#).
- *Reentrant* attribute--Specifies whether an enterprise bean can invoke methods on itself or call another bean that invokes a method on the calling bean. Only entity beans can be reentrant. For more information, see [Using threads and reentrancy in enterprise beans](#).
- *State management* attribute--Defines the conversational state of the session bean. This attribute must be set to either STATEFUL or STATELESS. For more information on the meaning of these conversational states, see [Stateless versus stateful session beans](#).
- *Timeout* attribute--Defines the idle timeout value in seconds associated with this session bean. (This attribute is an extension to the standard deployment descriptor.)
- References to external resources, such as resource connection factories, to the homes of other enterprise beans, and to security roles.

The deployment descriptor contains the following application assembly information:

- A display name and icons for identifying the module.
- The location of class files needed for a client program to access the beans in the module.

- *Security roles*-- Define a logical grouping of principals. Access to operations (such as EJB methods) is controlled by granting access to a role.
- *Method permissions*--Define a mapping between one or more security roles and one or more methods that a member of the role can invoke. This value is set per method.
- *Transaction* attributes--Define the transactional manner in which the container invokes a method for enterprise beans that require container-managed transaction demarcation. This value is set per method. The values for this attribute are described in [Enabling transactions and security in enterprise beans](#).
- *Transaction isolation level* attribute--Defines the degree to which transactions are isolated from each other by the container. This value is set per method. The values for this attribute are described in [Enabling transactions and security in enterprise beans](#). (This attribute is an extension to the standard deployment descriptor.)
- *RunAsMode* and *RunAsIdentity* attributes--The *RunAsMode* attribute defines the identity used to invoke the method. If a specific identity is required, the *RunAsIdentity* attribute is used to specify that identity. This value is set per bean. The values for the *RunAsMode* attribute are described in [Enabling transactions and security in enterprise beans](#). (This attribute is an extension to the standard deployment descriptor.)

The following binding attribute is stored in the repository (it is not part of the deployment descriptor):

- *JNDI home name* attribute--Defines the Java Naming and Directory Interface (JNDI) home name that is used to locate instances of an EJB home object. This value is set per bean. The values for this repository attribute are described in [Creating and getting a reference to a bean's EJB object](#).


Deploying an EJB module

When you deploy an EJB module, the deployment tool creates or incorporates the following elements:

- The container-implemented *EJBObject* and *EJBHome* classes (hereafter referred to as the EJB object and EJB home classes) from the enterprise bean's home and remote interfaces (and the persister and finder classes for entity beans with CMP).
- The stub and skeleton files required for remote method invocation (RMI).

[Figure 5](#) shows a simplified version of a deployed entity bean.

Figure 5. The major components of a deployed entity bean




You can deploy an EJB module with a variety of different tools. For more information, see [Tools for developing and deploying enterprise beans](#).

Developing EJB applications

To create EJB applications, create the enterprise beans and EJB clients that encapsulate your business data and functionality and then combine them appropriately. [Figure 6](#) provides a conceptual illustration of how EJB applications are created by combining one or more session beans, one or more entity beans, or both. Although individual entity beans and session beans can be used directly in an EJB client, session beans are designed to be associated with clients and entity beans are designed to store persistent data, so most EJB applications contain session beans that, in turn, access entity beans.

Figure 6. Conceptual view of EJB applications



This section provides an example of the ways in which enterprise beans can be combined to create EJB applications.

An example: enterprise beans for a bank

If you develop EJB applications for the banking industry, you can develop the following entity beans to encapsulate your business data and associated methods:

- Account bean--An entity bean that contains information about customer checking and savings accounts.
- CarLoan bean--An entity bean that contains information about an automobile loan.
- Customer bean--An entity bean that contains information about a customer, including information on accounts held and loans taken out by the customer.
- CustomerHistory bean--An entity bean that contains a record of customer transactions for specified accounts.
- Mortgage bean--An entity bean that contains information about a home or commercial mortgage.

An EJB client can directly access entity beans or session beans; however, the EJB Specification suggests that EJB clients use session beans to in turn access entity beans, especially in more complex applications. Therefore, as an EJB developer for the banking industry, you can create the following session beans to represent client tasks:

- LoanApprover bean--A session bean that allows a loan to be approved by using instances of the CarLoan bean, the Mortgage bean, or both.
- CarLoanCreator bean--A session bean that creates a new instance of a CarLoan bean.
- MortgageCreator bean--A session bean that creates a new instance of a Mortgage bean.
- Deposit bean--A session bean that credits a specified amount to an existing instance of an Account bean.
- StatementGenerator bean--A session bean that generates a statement summarizing the activities associated with a customer's accounts by using the appropriate instances of the Customer and CustomerHistory entity beans.
- Payment bean--A session bean that credits a payment to a customer's loan by using instances of the CarLoan bean, the Mortgage bean, or both.
- NewAccount bean--A session bean that creates a new instance of an Account bean.

- NewCustomer bean--A session bean that creates a new instance of a Customer bean.
- LoanReviewer bean--A session bean that accesses information about a customer's outstanding loans (instances of the CarLoan bean, the Mortgage bean, or both).
- Transfer bean--A session bean that transfers a specified amount between two existing instances of an Account bean.
- Withdraw bean--A session bean that debits a specified amount from an existing instance of an Account bean.

This example is simplified by necessity. Nevertheless, by using this set of enterprise beans, you can create a variety of EJB applications for different types of users by combining the appropriate beans within that application. One or more EJB clients can then be built to access the application.

Using the banking beans to develop EJB banking applications

When using beans built to the Sun Microsystems JavaBeans^(TM) Specification (as opposed to the EJB Specification), you combine predefined components such as buttons and text fields to create GUI applications. When using enterprise beans, you combine predefined components such as the banking beans to create three-tiered applications.

For example, you can use the banking enterprise beans to create the following EJB applications:

- Home Banking application--An Internet application that allows a customer to transfer funds between accounts (with the Transfer bean), to make payments on a loan by using funds in an existing account (with the Payment bean), to apply for a car loan or home mortgage (with the CarLoanCreator bean or the MortgageCreator bean).
- Teller application--An intranet application that allows a teller to create new customer accounts (with the NewCustomer bean and the NewAccount bean), transfer funds between accounts (with the Transfer bean), and record customer deposits and withdrawals (with the Withdraw bean and the Deposit bean).
- Loan Officer application--An intranet application that allows a loan officer to create and approve car loans and home mortgages (with the CarLoanCreator, MortgageCreator, LoanReviewer, and LoanApprover beans).
- Statement Generator application--A batch application that prints monthly customer statements related to account activity (with the StatementGenerator bean).

These examples represent only a subset of the possible EJB applications that can be created with the banking beans.

Life cycles of enterprise bean instances

After an enterprise bean is deployed into a container, clients can create and use instances of that bean as required. Within the container, instances of an enterprise bean go through a defined life cycle. The events in an enterprise bean's life cycle are derived from actions initiated by either the EJB client or the container in the EJB server. You must understand this life cycle because for some enterprise beans, you must write some of the code to handle the different events in the enterprise bean's life cycle.

The methods mentioned in this section are discussed in greater detail in [Developing enterprise beans](#).

Session bean life cycle

This section describes the life cycle of a session bean instance. Differences between stateful and stateless session beans are noted.

Creation state

A session bean's life cycle begins when a client invokes a create method defined in the bean's home interface. In response to this method invocation, the container does the following:

1. Creates a new memory object for the session bean instance.
2. Invokes the session bean's `setSessionContext` method. (This method passes the session bean instance a reference to a session context interface that can be used by the instance to obtain container services and get information about the caller of a client-invoked method.)
3. Invokes the session bean's `ejbCreate` method corresponding to the create method called by the EJB client.

Ready state

After a session bean instance is created, it moves to the ready state of its life cycle. In this state, EJB clients can invoke the bean's business methods defined in the remote interface. The actions of the container at this state are determined by whether a method is invoked transactionally or nontransactionally:

- *Transactional method invocations*--When a client invokes a transactional business method, the session bean instance is associated with a transaction. After a bean instance is associated with a transaction, it remains associated until that transaction completes. (Furthermore, an error results if an EJB client attempts to invoke another method on the same bean instance if invoking that method causes the container to associate the bean instance with another transaction or with no transaction.)

The container then invokes the following methods:

1. The `afterBegin` method, if that method is implemented by the bean class.
2. The business method in the bean class that corresponds to the business method defined in the bean's remote interface and called by the EJB client.
3. The bean instance's `beforeCompletion` method, if that method is implemented by the bean class and if a commit is requested prior to the container's attempt to commit the transaction.

The transaction service then attempts to commit the transaction, resulting either in a commit or a roll back. When the transaction completes, the container invokes the bean's `afterCompletion` method, passing the completion status of the transaction (either commit or rollback).

If a rollback occurs, a stateful session bean can roll back its conversational state to the values contained in the bean instance prior to beginning the transaction. Stateless session beans do not maintain a conversational state, so they do not need to be concerned about rollbacks.

- *Nontransactional method invocations*--When a client invokes a nontransactional business method, the container simply invokes the corresponding method in the bean class.

Pooled state

The container has a sophisticated algorithm for managing which enterprise bean instances are retained in memory. When a container determines that a stateful session bean instance is no longer required in memory, it invokes the bean instance's `ejbPassivate` method and moves the bean instance into a reserve pool. A stateful session bean instance cannot be passivated when it is associated with a transaction.

If a client invokes a method on a passivated instance of a stateful session bean, the container activates the instance by restoring the instance's state and then invoking the bean instance's `ejbActivate` method. When this method returns, the bean instance is again in the ready state.

Because every stateless session bean instance of a particular type is the same as every other instance of that

type, stateless session bean instances are not passivated or activated. These instances exist in a ready state at all times until their removal.

Removal state

A session bean's life cycle ends when an EJB client or the container invokes a remove method defined in the bean's home interface and remote interface. In response to this method invocation, the container calls the bean instance's `ejbRemove` method.

If you attempt to remove a bean instance while it is associated with a transaction, the `javax.ejb.RemoveException` is thrown. After a bean instance is removed, any attempt to invoke a method on that instance causes the `java.rmi.NoSuchObjectException` to be thrown.

A container can implicitly call a remove method on an instance after the lifetime of the EJB object has expired. The lifetime of a session EJB object is set in the deployment descriptor with the *timeout* attribute.

For more information on the remove methods, see [Removing a bean's EJB object](#).

Entity bean life cycle

This section describes the life cycle of entity bean instances. Differences between entity beans with CMP and BMP are noted.

Creation State

An entity bean instance's life cycle begins when the container creates that instance. After creating a new entity bean instance, the container invokes the instance's `setEntityContext` method. This method passes the bean instance a reference to an entity context interface that can be used by the instance to obtain container services and get information about the caller of a client-invoked method.

Pooled State

After an entity bean instance is created, it is placed in a pool of available instances of the specified entity bean class. While the instance is in this pool, it is not associated with a specific EJB object. Every instance of the same enterprise bean class in this pool is identical. While an instance is in this pooled state, the container can use it to invoke any of the bean's finder methods.

Ready State

When a client needs to work with a specific entity bean instance, the container picks an instance from the pool and associates it with the EJB object initialized by the client. An entity bean instance is moved from the pooled to the ready state if there are no available instances in the ready state.

There are two events that cause an entity bean instance to be moved from the pooled state to the ready state:

- When a client invokes the create method in the bean's home interface to create a new and unique entity of the entity bean class (and a new record in the data source). As a result of this method invocation, the container calls the bean instance's `ejbCreate` and `ejbPostCreate` methods, and the new EJB object is associated with the bean instance.
- When a client invokes a finder method to manipulate an existing instance of the entity bean class (associated with an existing record in the data source). In this case, the container calls the bean instance's `ejbActivate` method to associate the bean instance with the existing EJB object.

When an entity bean instance is in the ready state, the container can invoke the instance's `ejbLoad` and `ejbStore`

methods to synchronize the data in the instance with the corresponding data in the data source. In addition, the client can invoke the bean instance's business methods when the instance is in this state. All interactions required to handle an entity bean instance's business methods in the appropriate transactional (or nontransactional) manner are handled by the container.

When a container determines that an entity bean instance in the ready state is no longer required, it moves the instance to the pooled state. This transition to the pooled state results from either of the following events:

- When the container invokes the `ejbPassivate` method.
- When the EJB client invokes a remove method on the EJB object or on the EJB home object. When one of these methods is called, the underlying entity is removed permanently from the data source.

Removal State

An entity bean instance's life cycle ends when the container invokes the `unsetEntityContext` method on an entity bean instance in the pooled state. Do not confuse the removal of an entity bean instance with the removal of the underlying entity whose data is stored in the data source. The former simply removes an uninitialized object; the latter removes data from the data source.

For more information on the remove methods, see [Removing a bean's EJB object](#).


An architectural overview of the EJB programming environment

The World Wide Web (the Web) has transformed the way in which businesses work with their customers. At first, it was good enough just to have a Web home page. Then, businesses began to deploy active Web sites that allowed customers to order products and services. Today, businesses not only need to use the Web in all of these ways, they need to integrate their Web-based systems with their other business systems. The IBM^(R) WebSphere Application Server, and specifically the support for enterprise beans, provides the model and the tools to accomplish this integration.

Components of the EJB environment

IBM's implementation of the Sun Microsystems Enterprise JavaBeans (EJB) Specification enables users of the WebSphere Application Server to integrate their Web-based systems with their other business systems. A major part of this implementation is the WebSphere EJB server and its associated components, which are illustrated in [Figure 1](#).

Figure 1. The components of the EJB environment



The WebSphere EJB server environment contains the following components, which are discussed in more detail in the specified sections:

- **EJB server**--A WebSphere EJB server contains and runs one or more *enterprise beans*, which encapsulate the business logic and data used and shared by EJB clients. The enterprise beans installed in an EJB server do not communicate directly with the server; instead, an *EJB container* provides an interface between the enterprise beans and the EJB server, providing many low-level services such as threading, support for transactions, and management of data storage and retrieval. For more information,

see [The EJB server](#).

- *Data source*--There are two types of enterprise beans: session beans, which encapsulate short-lived, client-specific tasks and objects, and entity beans, which encapsulate permanent or *persistent* data. The EJB server stores and retrieves this persistent data in a data source, which can be a database, another application, or even a file. For more information, see [The data source](#).
- *EJB clients*--There are two general types of EJB clients:
 - *HTTP-based clients* that interact with the EJB server by using either Java servlets or JavaServer Pages^(TM) (JSP) by way of the Hypertext Transfer Protocol (HTTP).
 - *Java applications* that interact directly with the EJB server by using Java remote method invocation over the Internet Inter-ORB Protocol (RMI/IIOP).

For more information, see [The EJB clients](#).

- The *administration interface*--The administrative interface allows you to manage the EJB server environment. For more information, see [The administration interface](#).
-

The EJB server

The EJB server is the application server tier of WebSphere Application Server's three-tier architecture. The EJB server has three components: the EJB server runtime, the EJB containers, and the enterprise beans. EJB containers insulate the enterprise beans from the underlying EJB server and provide a standard application programming interface (API) between the beans and the container. The EJB Specification defines this API. Together, the EJB server and container components provide or give access to the following services for the enterprise beans that are deployed into it:

- A tool that deploys enterprise beans. When a bean is deployed, the deployment tool creates several classes that implement the interfaces that make up the predeployed bean. In addition, the deployment tool generates Java ORB, stub, and skeleton classes that enable remote method invocation. For entity beans, the tool also generates persister and finder classes to handle interaction between the bean and the data source that stores the bean's persistent data. Before an enterprise bean can be deployed, the developer must create an *EJB module* and associated *deployment descriptor*. The deployment descriptor provides information about each enterprise bean in the module and instructions for the container on how to handle the beans. For more information on deployment, see [Deploying an EJB module](#).
- A security service that handles authentication and authorization for principals that need to access resources in an EJB server environment. For more information, see [The security service](#).
- A workload management service that ensures that resources are used efficiently. For more information, see [The workload management service](#).
- A persistence service that handles interaction between an entity bean and its data source to ensure that persistent data is properly managed. For more information, see [The persistence service](#).
- A naming service that exports a bean's name, as defined in the deployment descriptor, into the name space. The EJB server uses the Java Naming and Directory Interface^(TM) (JNDI) to implement a naming service. For more information, see [The naming service](#).
- A transaction service that implements the transactional attributes in a bean's deployment descriptor. For more information, see [The transaction service](#).

The security service

When enterprise computing was handled solely by a few powerful mainframes located at a centralized site, ensuring that only authorized users obtained access to computing services and information was a fairly

straightforward task. In distributed computing systems where users, application servers, and resource managers can be spread out across the world, securing computing resources has become a much more complicated task. Nevertheless, the underlying issues are basically the same.

Authentication and authorization

A good security service provides two main functions: authentication and authorization.

Authentication takes place when a *principal* (a user or a computer process) initially attempts to gain access to a computing resource. At that point, the security service challenges the principal to prove that the principal is who it claims to be. Human users typically prove who they are by entering a user ID and password; a process normally presents an encrypted key. If the password or key is valid, the security service gives the user a *token* or *ticket* that identifies the principal and indicates that the principal has been authenticated. After a principal is authenticated, it can then attempt to use any of the resources within the boundaries of the computing system protected by the security service; however, a principal can use a particular computing resource only if it has been authorized to do so. *Authorization* takes place when an authenticated principal requests the use of a resource and the security service determines if the user has been granted permission to use that resource. Typically, authorization is handled by associating access control lists (ACLs) with resources that define which principal (or groups of principals) are authorized to use the resource. If the principal is authorized, it gains access to the resource.

In a distributed computing environment, principals and resources must be mutually suspicious of each other's identity until both have proven that they are who they say they are. This is necessary because principals can attempt to falsify an identity to get access to a resource, and a resource can be a trojan horse, attempting to get valuable information from the principal. To solve this problem, the security service contains a security server that acts as a *trusted third party*, authenticating principals and resources so that these entities can prove their identities to each other. This security protocol is known as *mutual authentication*.

Using the security server

The security service does *not* use the *access control* and *run-as identity* security attributes defined in the deployment descriptor. However, it does use the *run-as mode* attribute as the basis for mapping a user identity to a user security context. For more information on this attribute, see [The deployment descriptor](#).

The main component of the security service is an EJB server that contains security enterprise beans. When system administrators administer the security service, they manipulate the security beans in the security EJB server.

Once an EJB client is authenticated, it can attempt to invoke methods on the enterprise beans that it manipulates. A method is successfully invoked if the principal associated with the method invocation has the required permissions to invoke the method. These permissions can be set at the application level (an administrator-defined set of Web and object resources) and at the method group level (an administrator-defined set of Java interface/method pairs). An application can contain multiple method groups.

In general, the principal under which a method is invoked is associated with that invocation across multiple Web servers and EJB servers (this association is known as *delegation*). Delegating the method invocations in this way ensures that the user of an EJB client needs to authenticate only once. HTTP cookies are used to propagate a user's authentication information across multiple Web servers. These cookies have a lifetime equal to the life of the browser session, and a logout method is provided to destroy these cookies when the user is finished.

For information on administering security, see the WebSphere InfoCenter and the online help available with the WebSphere Administrative Console.

The workload management service

The workload management service improves the scalability of the EJB server environment by grouping multiple EJB servers into *server groups*. Clients then access these server groups as if they are a single EJB server, and the workload management service ensures that the workload is evenly distributed across the EJB servers in the server groups. An EJB server can belong to only one server group. The creation of server groups is an administrative task that is handled from within the WebSphere Administrative Console. For more information on workload management, consult the WebSphere InfoCenter and the online help for the appropriate administrative interface.

The persistence service

There are two types of enterprise beans: session beans and entity beans. Session beans encapsulate temporary data associated with a particular client. Entity beans encapsulate permanent data that is stored in a data source. For more information, see [An introduction to enterprise beans](#).

The persistence service ensures that the data associated with entity beans is properly synchronized with their corresponding data in the data source. To accomplish this task, the persistence service works with the transaction service to insert, update, extract, and remove data from the data source at the appropriate times.

There are two types of entity beans: those with container-managed persistence (CMP) and those with bean-managed persistence (BMP). In entity beans with CMP, the persistence service handles nearly all of the tasks required to manage persistent data. In entity beans with BMP, the bean itself handles most of the tasks required to manage persistent data.

The persistence service uses the following components to accomplish its task:

- The Java Database Connectivity (JDBCTM) API, which gives entity beans a common interface to relational databases.
- Java transaction support, which is discussed in [Using transactions in the EJB server environment](#). The EJB server ensures that persistent data is always handled within the appropriate transactional context.

The naming service

In an object-oriented distributed computing environment, clients must have a mechanism to locate and identify objects so that the clients, objects, and resources appear to be on the same machine. A naming service provides this mechanism. In the EJB server environment, JNDI is used to mask the actual naming service and provide a common interface to the naming service.

JNDI provides naming and directory functionality to Java applications, but the API is independent of any specific implementation of a naming and directory service. This implementation independence ensures that different naming and directory services can be used by accessing them by way of the JNDI API. Therefore, Java applications can use many existing naming and directory services such as the Lightweight Directory Access Protocol (LDAP), the Domain Name Service (DNS), or the DCE Cell Directory Service (CDS).

JNDI was designed for Java applications by using Java's object model. Using JNDI, Java applications can store and retrieve named objects of any Java object type. JNDI also provides methods for executing standard directory operations, such as associating attributes with objects and searching for objects by using their attributes.

In the EJB server environment, the deployment descriptor is used to specify the JNDI name for an enterprise bean. When an EJB server is started, it registers these names with JNDI.

The transaction service

A *transaction* is a set of operations that transforms data from one consistent state to another. This set of

operations is an indivisible unit of work, and in some contexts, a transaction is referred to as a *logical unit of work* (LUW). A transaction is a tool for distributed systems programming that simplifies failure scenarios. Transactions provide the *ACID properties*:


- *Atomicity*: A transaction's changes are atomic: either all operations that are part of the transaction happen or none happen.
- *Consistency*: A transaction moves data between consistent states.
- *Isolation*: Even though transactions can run (or be executed) concurrently, no transaction sees another's work in progress. The transactions appear to run serially.
- *Durability*: After a transaction completes successfully, its changes survive subsequent failures.

As an example, consider a transaction that transfers money from one account to another. Such a transfer involves money being deducted from one account and deposited in the other. Withdrawing the money from one account and depositing it in the other account are two parts of an *atomic* transaction: if both cannot be completed, neither must happen. If multiple requests are processed against an account at the same time, they must be *isolated* so that only a single transaction can affect the account at one time. If the bank's central computer fails just after the transfer, the correct balance must still be shown when the system becomes available again: the change must be *durable*. Note that *consistency* is a function of the application; if money is to be transferred from one account to another, the application must subtract the same amount of money from one account that it adds to the other account. Transactions can be completed in one of two ways: they can commit or roll back. A successful transaction is said to *commit*. An unsuccessful transaction is said to *roll back*. Any data modifications made by a rolled back transaction must be completely undone. In the money-transfer example, if money is withdrawn from one account but a failure prevents the money from being deposited in the other account, any changes made to the first account must be completely undone. The next time any source queries the account balance, the correct balance must be shown.

Distributed transactions and the two-phase commit process

A *distributed transaction* is one that runs in multiple processes, often on several machines. Each process participates in the transaction. This is illustrated in [Figure 2](#), where each oval indicates work being done on a different machine, and each arrow indicates a remote method invocation (RMI).

Figure 2. Example of a distributed transaction



Distributed transactions, like local transactions, must adhere to the ACID properties. However, maintaining these properties is greatly complicated for distributed transactions because a failure can occur in any process, and in the event of such a failure, each process must undo any work already done on behalf of the transaction.

A distributed transaction processing system maintains the ACID properties in distributed transactions by using two features:

- *Recoverable processes*: Recoverable processes are those that can restore earlier states if a failure occurs.
- *A commit protocol*: A commit protocol enables multiple processes to coordinate the committing or rolling back (aborting) of a transaction. The most common commit protocol, and the one used by the EJB server, is the two-phase commit protocol.

Transaction state information must be stored by all recoverable processes. However, only processes that manage application data (such as resource managers) must store descriptions of changes to data. Not all processes involved in a distributed transaction need to be recoverable. In general, clients are not recoverable because they do not interact directly with a resource manager. Processes that are not recoverable are referred to as *ephemeral* processes. The *two-phase commit protocol*, as the name implies, involves two phases: a prepare phase and a resolution phase. In each transaction, one process acts as the coordinator. The *coordinator* oversees the activities of the other participants in the transaction to ensure a consistent outcome. In the *prepare phase*, the coordinator sends a message to each process in the transaction, asking each process to prepare to commit. When a process prepares, it guarantees that it can commit the transaction and makes a permanent record of its work. After guaranteeing that it can commit, it can no longer unilaterally decide to roll back the transaction. If a process cannot prepare (that is, if it cannot guarantee that it can commit the transaction), it must roll back the transaction. In the *resolution phase*, the coordinator tallies the responses. If all participants are prepared to commit, the transaction commits; otherwise, the transaction is rolled back. In either case, the coordinator informs all participants of the result. In the case of a commit, the participants acknowledge that they have committed.

Using transactions in the EJB server environment

The enterprise bean transaction model corresponds in most respects to the OMG OTS version 1.1. An enterprise bean instance that is transaction enabled corresponds to an object of the OTS TransactionalObject interface. However, the enterprise bean transaction model does not support transaction nesting.

In the EJB server environment, transactions are handled by three main components of the transaction service:

- A transaction manager interface that enables the EJB server to control transaction boundaries within its enterprise beans based on the transactional attributes specified for the beans.
- An interface (UserTransaction) that allows an enterprise bean or an EJB client to manage transactions. The container makes this interface available to enterprise beans and EJB clients by way of the name service.
- Coordination by way of the X/Open XA interface that enables a transactional resource manager (such as a database) to participate in a transaction controlled by an external transaction manager.

For most purposes, the enterprise bean developers can delegate the tasks involved in managing a transaction to the container. The developer performs this delegation by setting the deployment descriptor attributes for transactions. These attributes and their values are described in [Setting transactional attributes in the deployment descriptor](#).

In other cases, the enterprise bean developer will want or need to manage the transactions at the bean level or involve the EJB client in the management of transactions. For more information on this approach, see [Using bean-managed transactions](#).

The data source

Entity beans contain persistent data that must be permanently stored in a recoverable data source. Although the EJB Specification often refers to databases as the place to store persistent data associated with an entity bean, it leaves open the possibility of using other data sources, including operating system files and other applications. If you want to let the container handle the interaction between an entity bean and a data source, you must use the data sources supported by that container.

If you write the additional code required to handle the interaction between a BMP entity bean and the data source, you can use any data source that meets your needs and is compatible with the persistence service. For more information, see [Developing entity beans with BMP](#).

The EJB clients

An EJB client can take one of the following forms: it can be a Java application, a Java servlet, a Java applet-servlet combination, or a JSP file. The EJB client code required to access and manipulate enterprise beans is very similar across the different Java EJB clients. EJB client developers must consider the following issues:

- *Naming and communications*--A Java EJB client must use either HTTP or RMI to communicate with enterprise beans. Fortunately, there is very little difference in the coding required to enable communications between the EJB client and the enterprise bean, because JNDI masks the interaction between the EJB client and the name service.
 - Java applications communicate with enterprise beans by using RMI/IIOP.
 - Java servlets and JSP files communicate with enterprise beans by using HTTP. To use servlets with an EJB server, a Web server must be installed and configured on a machine in the EJB server environment. For more information, see [The Web server](#).
- *Threading*--Java clients can be either single-threaded or multithreaded depending on the tasks that the client needs to perform. Each client thread that uses a service provided by a session bean must create or find a separate instance of that bean and maintain a reference to that bean until the thread completes; multiple client threads can access the same entity bean.
- *Security* - EJB clients that access an EJB server over HTTP (for example, servlets and JSP files) encounter the following two layers of security:
 1. Universal Resource Locator (URL) security enforced by the WebSphere Application Server Security Plug-in attached to the Web server in collaboration with the security service.
 2. Enterprise bean security enforced at the server working with the security service.

When the user of an HTTP-based EJB client attempts to access an enterprise bean, the Web server (using the WebSphere Server plug-in) authenticates the user. This authentication can take the form of a request for a user ID and password or it can happen transparently in the form of a certificate exchange followed by the establishment of a Secure Sockets Layer (SSL) session.

The authentication policy is governed by an additional option: secure channel constraint. If the secure channel constraint is required, an SSL session must be established as the final phase of authentication; otherwise, SSL is optional.

- *Transactions*--Both types of Java clients can use the transaction service by way of the JTA interfaces to manage transactions. The code required for transaction management is identical in the two types of clients. For general information on transactions and the Java transaction service, see [The transaction service](#). For information on managing transactions in a Java EJB client, see [Managing transactions in an EJB client](#).

The Web server

To access the functionality in the EJB server, Java servlets and JSP files must have access to a Web server. The Web server enables communication between a Web client and the EJB server. The EJB server, Web server, and Java servlet can each reside on different machines.

For information on the Web servers supported by the EJB servers, see the Advanced Application Server *Getting Started* document.

The administration interface

The EJB server uses the WebSphere Administrative Console. For more information on this interface, consult the WebSphere InfoCenter and the online help available with the WebSphere Administrative Console. You can also administer the EJB server using the **wscp** command-line tool. For more information, see the Advanced Edition Information Center.

WebSphere Programming Model Extensions

This section discusses facilities that are provided as part of the Programming Model Extensions in WebSphere Application Server:

- The exception-chaining package, which can be used by distributed applications to capture a sequence of exceptions. For more information, see [The distributed-exception package](#).
- The command package, which can be used by distributed applications to reduce the number of remote invocations they must make. For more information, see [The command package](#).
- The localizable-text package, which can be used by distributed applications spanning locales to deliver output in a user-specified language. For more information, see [The localizable-text package](#).

The exception-chaining and command packages are available as part of WebSphere Application Server Advanced Edition and Enterprise Edition; the localizable-text package is available as part of WebSphere Application Server Advanced Edition. All three packages are general-purpose utilities, designed to provide common functions in a reusable way. Although these facilities are described in the context of enterprise beans, they are available to any WebSphere Application Server Java application. They are not restricted to use with enterprise beans.

The distributed-exception package

Distributed applications require a strategy for exception handling. As applications become more complex and are used by more participants, handling exceptions becomes problematic. To capture the information contained in every exception, methods have to rethrow every exception they catch. If every method adopts this approach, the number of exceptions can become unmanageable, and the code itself becomes less maintainable. Furthermore, if a new method introduces a new exception, all existing methods that call the new method have to be modified to handle the new exception. Trying to explicitly manage every possible exception in a complex application quickly becomes intractable.

In order to keep the number of exceptions manageable, some programmers adopt a strategy in which methods catch all exceptions in a single clause and throw one exception in response. This reduces the number of exceptions each method must recognize, but it also means that the information about the originating exception is lost. This loss of information can be desirable, for example, when you wish to hide implementation details from end users. However, this strategy can make applications much more difficult to debug.

The distributed-exception package provides a facility that allows you to build chains of exceptions. An *exception chain* encapsulates the stack of previous exceptions. With an exception chain, you can throw one exception in response to another without discarding the previous exceptions, so you can manage the number of exceptions without losing the information they carry. Exceptions that support chaining are called *distributed exceptions*.

Distributed exceptions are packaged in the `ras.jar` file, which must be included in the application's `CLASSPATH` variable.

Overview

Support for chaining distributed exceptions is provided by the `com.ibm.websphere.exception` Java package. The following classes and interfaces make up this package:

- `DistributedException`--This class provides access to the methods on the `DistributedExceptionInfo` object. It acts as the root class for exceptions in a distributed application. For more information, see [The DistributedException class](#).
- `DistributedExceptionEnabled`--This interface allows exceptions that cannot inherit from the `DistributedException` class to be used in exception chains, so that exceptions based on predefined exceptions can be captured. For more information, see [The DistributedExceptionEnabled interface](#).
- `DistributedExceptionInfo`--This class encapsulates the work necessary for distributed exceptions. An exception class that extends the `DistributedException` class automatically gets access to this class. A class that implements the `DistributedExceptionEnabled` interface must explicitly declare a `DistributedExceptionInfo` attribute. For more information, see [The DistributedExceptionInfo class](#).
- `ExceptionInstantiationException`--This class defines the exception that is thrown if an exception chain cannot be created. This exception is instantiated internally, but you can catch and re-throw it.

This section provides a general description of the interfaces and classes in the exception-chaining package.

The DistributedException class

The DistributedException class provides the root exception for exception hierarchies defined by applications. With this class, you build chains of exceptions by saving a caught exception and bundling it into the new exception to be thrown. This way, the information about the old exception is forwarded along with the new exception. The class declares six constructors; [Figure 55](#) shows the signatures for these constructors. When your exception is a subclass of the DistributedException class, you must provide corresponding constructors in your exception class.

Figure 55. Code example: Constructors for the DistributedException class

```
...
public class DistributedException extends Exception
implements DistributedExceptionEnabled
{
    // Constructors
    public DistributedException() {...}
    public DistributedException(String message) {...}
    public DistributedException(Throwable exception) {...}
    public DistributedException(String message,Throwable exception) {...}
    public DistributedException(String resourceBundleName,
                               String resourceKey,
                               Object[] formatArguments,
                               String defaultText)
    {
        {...}
    }
    public DistributedException(String resourceBundleName,
                               String resourceKey,
                               Object[] formatArguments,
                               String defaultText,
                               Throwable exception)
    {
        {...}
    }
    // Other methods
    ...
}
```

The class also provides methods for extracting exceptions from the chain and querying the chain. These methods include:

- `getMessage`--This method returns the message string associated with the current exception.
- `getPreviousException`--This method returns the preceding exception in a chain as a Throwable object. If there are no previous exceptions, it returns null.
- `getOriginalException`--This method returns the original exception in a chain as a Throwable object. If there is no prior exception, it returns null.
- `getException`--This method returns the most recent instance of the named exception from the chain as a Throwable object. If there are no instances present, it returns null.
- `getExceptionInfo`--This method returns the DistributedExceptionInfo object for the exception.
- `printStackTrace`--These methods print the stack trace for the current exception, which includes the stack traces of all previous exceptions in the chain.

Localization support

Support for localized messages is provided by two of the constructors for distributed exceptions. These constructors take arguments representing a resource bundle, a resource key, a default message, and the set of replacement strings for variables in the message. A resource bundle is a collection of resources or resource names representing information associated with a specific locale. Resource bundles are provided as either a subclass of the ResourceBundle class or in a properties file. The resource key indicates which resource in the bundle to retrieve. The default message is returned if either the name of the resource bundle or the key is null or invalid.

The DistributedExceptionEnabled interface

Use the `DistributedExceptionEnabled` interface to create distributed exceptions when your exception cannot extend the `DistributedException` class. Because Java does not permit multiple inheritance, you cannot extend multiple exception classes. If you are extending an existing exception class, for example, `javax.ejb.CreateException`, you cannot also extend the `DistributedException` class. To allow your new exception class to chain other exceptions, you must implement the `DistributedExceptionEnabled` interface instead. The `DistributedExceptionEnabled` interface declares eight methods you must implement in your exception class:

- `getMessage`--This method returns the message string associated with the current exception.
- `getPreviousException`--This method returns the preceding exception in a chain as a `Throwable` object. If there are no previous exceptions, it returns null.
- `getOriginalException`--This method returns the original exception in a chain as a `Throwable` object. If there is no prior exception, it returns null.
- `getException`--This method returns the most recent instance of the named exception from the chain as a `Throwable` object. If there are no instances present, it returns null.
- `getExceptionInfo`--This method returns the `DistributedExceptionInfo` object for the exception.
- `printStackTrace`--These methods print the stack trace for the current exception, which includes the stack traces of all previous exceptions in the chain.
- `printSuperStackTrace`--This method is used by a `DistributedExceptionInfo` object to retrieve and save the current stack trace.

When implementing the `DistributedExceptionEnabled` interface, you must declare a `DistributedExceptionInfo` attribute. This attribute provides implementations for most of these methods, so implementing them in your exception class consists of calling the corresponding methods on the `DistributedExceptionInfo` object. For more information, see [Implementing the methods from the DistributedExceptionEnabled interface](#).

The DistributedExceptionInfo class

The `DistributedExceptionInfo` class provides the functionality required for distributed exceptions. It must be used by any exception that implements the `DistributedExceptionEnabled` interface (which includes the `DistributedException` class). A `DistributedExceptionInfo` object contains the exception itself, and it provides constructors for creating exception chains and methods for retrieving the information within those chains. It also provides the underlying methods for managing chained exceptions.

Extending the DistributedException class

The `DistributedException` class provides the root exception for exception hierarchies defined by applications. The class also provides methods for extracting exceptions from the chain and querying the chain. You must provide constructors corresponding to the constructors in the `DistributedException` class (see [Figure 55](#)). The constructors can simply pass arguments to the constructor in the `DistributedException` class by using super methods, as illustrated in [Figure 56](#).

Figure 56. Code example: Constructors in an exception class that extends the `DistributedException` class

```
...
import com.ibm.websphere.exception.*;
public class MyDistributedException extends DistributedException
{
    // Constructors
    public MyDistributedException() {
        super();
    }
    public MyDistributedException(String message) {
        super(message);
    }
    public MyDistributedException(Throwable exception) {
        super(exception);
    }
    public MyDistributedException(String message, Throwable exception) {
        super(message, exception);
    }
}
```

```

    }
    public MyDistributedException(String resourceBundleName,
                                String resourceKey, Object[] formatArguments,
                                String defaultText)
    {
        super(resourceBundleName, resourceKey, formatArguments, defaultText);
    }
    public MyDistributedException(String resourceBundleName,
                                String resourceKey, Object[] formatArguments,
                                String defaultText, Throwable exception)
    {
        super(resourceBundleName, resourceKey, formatArguments, defaultText,
              exception);
    }
}

```

Implementing the DistributedExceptionEnabled interface

Use the DistributedExceptionEnabled interface to create distributed exceptions when your exception cannot extend the DistributedException class. To allow your new exception class to be chained, you must implement the DistributedExceptionEnabled interface instead. [Figure 57](#) shows the structure of an exception class that extends the existing javax.ejb.CreateException class and implements the DistributedExceptionEnabled interface. The class also declares the required DistributedExceptionInfo object.

Figure 57. Code example: The structure of an exception class that implements the DistributedExceptionEnabled interface

```

...
import javax.ejb.*;
import com.ibm.websphere.exception.*;
public class AccountCreateException extends CreateException
implements DistributedExceptionEnabled
{
    DistributedExceptionInfo exceptionInfo = null;
    // Constructors
    ...
    // Methods from the DistributedExceptionEnabled interface
    ...
}

```

Implementing the constructors for the exception class

The exception-chaining package supports six different ways of creating instances of exception classes (see [Figure 55](#)). When you write an exception class by implementing the DistributedExceptionEnabled interface, you must implement these constructors. In each one, you must use the DistributedExceptionInfo object to capture the information for chaining the exception. [Figure 58](#) shows standard implementations for the six constructors.

Figure 58. Code example: Constructors for an exception class that implements the DistributedExceptionEnabled interface

```

...
public class AccountCreateException extends CreateException
implements DistributedExceptionEnabled
{
    DistributedExceptionInfo exceptionInfo = null;
    // Constructors
    AccountCreateException() {
        super ();
        exceptionInfo = new DistributedExceptionInfo(this);
    }
    AccountCreateException(String msg) {

```



```

        super (msg);
        exceptionInfo = new DistributedExceptionInfo(this);
    }
    AccountCreateException(Throwable e) {
        super ();
        exceptionInfo = new DistributedExceptionInfo(this, e);
    }
    AccountCreateException(String msg, Throwable e) {
        super (msg);
        exceptionInfo = new DistributedExceptionInfo(this, e);
    }
    AccountCreateException(String resourceBundleName, String resourceKey,
                           Object[] formatArguments, String defaultText)
    {
        super ();
        exceptionInfo = new DistributedExceptionInfo(resourceBundleName,
                                                    resourceKey, formatArguments, defaultText, this);
    }
    AccountCreateException(String resourceBundleName, String resourceKey,
                           Object[] formatArguments, String defaultText,
                           Throwable exception)
    {
        super ();
        exceptionInfo = new DistributedExceptionInfo(resourceBundleName,
                                                    resourceKey, formatArguments, defaultText, this, exception);
    }
    // Methods from the DistributedExceptionEnabled interface
    ...
}

```

Implementing the methods from the DistributedExceptionEnabled interface

The DistributedExceptionInfo object provides implementations for most of the methods in the DistributedExceptionEnabled interface, so you can implement the required methods in your exception class by calling the corresponding methods on the DistributedExceptionInfo object. [Figure 59](#) illustrates this technique. The only two methods that do not involve calling a corresponding method on the DistributedExceptionInfo object are the getExceptionInfo method, which returns the object, and the printSuperStackTrace method, which calls the super.printStackTrace method.

Figure 59. Code example: Implementations of the methods in the DistributedExceptionEnabled interface

```

...
public class AccountCreateException extends CreateException
implements DistributedExceptionEnabled
{
    DistributedExceptionInfo exceptionInfo = null;
    // Constructors
    ...
    // Methods from the DistributedExceptionEnabled interface
    String getMessage() {
        if (exceptionInfo != null)
            return exceptionInfo.getMessage();
        else return null;
    }
    Throwable getPreviousException() {
        if (exceptionInfo != null)
            return exceptionInfo.getPreviousException();
        else return null;
    }
    Throwable getOriginalException() {
        if (exceptionInfo != null)
            return exceptionInfo.getOriginalException();
    }
}

```



```

        else return null;
    }
    Throwable getException(String exceptionClassName) {
        if (exceptionInfo != null)
            return exceptionInfo.getException(exceptionClassName);
        else return null;
    }
    DistributedExceptionInfo getExceptionInfo() {
        if (exceptionInfo != null)
            return exceptionInfo;
        else return null;
    }
    void printStackTrace() {
        if (exceptionInfo != null)
            return exceptionInfo.printStackTrace();
        else return null;
    }
    void printStackTrace(PrintWriter pw) {
        if (exceptionInfo != null)
            return exceptionInfo.printStackTrace(pw);
        else return null;
    }
    void printSuperStackTrace(PrintWriter pw)
        if (exceptionInfo != null)
            return super.printStackTrace(pw);
        else return null;
    }
}

```

Using distributed exceptions

Defining a distributed exception gives you the ability to chain exceptions together. The `DistributedExceptionInfo` class provides methods for adding information to an exception chain and for extracting information from the chain. This section illustrates the use of distributed exceptions.

Catching distributed exceptions

You can catch exceptions that extend the `DistributedException` class or implement the `DistributedExceptionEnabled` interface separately. You can also test a caught exception to see if it has implemented the `DistributedExceptionEnabled` interface. If it has, you can treat it as any other distributed exception. [Figure 60](#) shows the use of the `instanceof` method to test for exception chaining.

Figure 60. Code example: Testing for an exception that implements the `DistributedExceptionEnabled` interface

```

....
try {
    someMethod();
}
catch (Exception e) {
    ...
    if (e instanceof DistributedExceptionEnabled) {
        ...
    }
}
...

```

Adding an exception to a chain

To add an exception to a chain, you must call one of the constructors for your distributed-exception class. This captures the previous exception information and packages it with the new exception. [Figure 61](#) shows the use of the `MyDistributedException(Throwable)` constructor.

Figure 61. Code example: Adding an exception to a chain

```
void someMethod() throws MyDistributedException {
    try {
        someOtherMethod();
    }
    catch (DistributedExceptionEnabled e) {
        throw new MyDistributedException(e);
    }
    ...
}...
```

Retrieving information from a chain

Chained exceptions allow you to retrieve information about prior exceptions in the chain. For example, the `getPreviousException`, `getOriginalException`, and `getException(String)` methods allow you to retrieve specific exceptions from the chain. You can retrieve the message associated with the current exception by calling the `getMessage` method. You can also get information about the entire chain by calling one of the `printStackTrace` methods. [Figure 62](#) illustrates calling the `getPreviousException` and `getOriginalException` methods.

Figure 62. Code example: Extracting exceptions from a chain

```
...
try {
    someMethod();
}
catch (DistributedExceptionEnabled e) {
    try {
        Throwable prev = e.getPreviousException();
    }
    catch (ExceptionInstantiationException eie) {
        DistributedExceptionInfo prevExInfo = e.getPreviousExceptionInfo();
        if (prevExInfo != null) {
            String prevExName = prevExInfo.getClassName();
            String prevExMsg = prevExInfo.getClassMessage();
            ...
        }
    }
    try {
        Throwable orig = e.getOriginalException();
    }
    catch (ExceptionInstantiationException eie) {
        DistributedExceptionInfo origExInfo = null;
        DistributedExceptionInfo prevExInfo = e.getPreviousExceptionInfo();
        while (prevExInfo != null) {
            origExInfo = prevExInfo;
            prevExInfo = prevExInfo.getPreviousExceptionInfo();
        }
        if (origExInfo != null) {
            String origExName = origExInfo.getClassName();
            String origExMsg = origExInfo.getClassMessage();
            ...
        }
    }
}
...
```

Distributed applications are defined by the ability to utilize remote resources as if they were local, but this remote work affects the performance of distributed applications. Distributed applications can improve performance by using remote calls sparingly. For example, if a server does several tasks for a client, the application can run more quickly if the client bundles requests together, reducing the number of individual remote calls. The command package provides a mechanism for collecting sets of requests to be submitted as a unit.

In addition to giving you a way to reduce the number of remote invocations a client makes, the command package provides a generic way of making requests. A client instantiates the command, sets its input data, and tells it to run. The command infrastructure determines the target server and passes a copy of the command to it. The server runs the command, sets any output data, and copies it back to the client. The package provides a common way to issue a command, locally or remotely, and independently of the server's implementation. Any server (an enterprise bean, a Java Database Connectivity (JDBC) server, a servlet, and so on) can be a target of a command if the server supports Java access to its resources and provides a way to copy the command between the client's Java Virtual Machine (JVM) and its own JVM.

Overview

The command facility is implemented in the `com.ibm.websphere.command` Java package. The classes and interfaces in the command package fall into four general categories:

- Interfaces for creating commands. For more information, see [Facilities for creating commands](#).
- Classes and interfaces for implementing commands. For more information, see [Facilities for implementing commands](#).
- Classes and interfaces for determining where the command is run. For more information, see [Facilities for setting and determining targets](#).
- Classes defining package-specific exceptions. For more information, see [Exceptions in the command package](#).

This section provides a general description of the interfaces and classes in the command package.

Facilities for creating commands

The Command interface specifies the most basic aspects of a command. This interface is extended by both the TargetableCommand interface and the CompensableCommand interface, which offer additional features. To create commands for applications, you must:

- Define an interface that extends one or more of interfaces in the command package.
- Provide an implementation class for your interface.

In practice, most commands implement the TargetableCommand interface, which allows the command to be executed remotely. [Figure 63](#) shows the structure of a command interface for a targetable command.

Figure 63. Code example: The structure of an interface for a targetable command

```
...
import com.ibm.websphere.command.*;
public interface MySimpleCommand extends TargetableCommand {
    // Declare application methods here
}
```

The CompensableCommand interface allows the association of one command with another that can undo the work of the first. Compensable commands also typically implement the TargetableCommand interface. [Figure 64](#) shows the structure of a command interface for a targetable, compensable command.

Figure 64. Code example: The structure of an interface for a targetable, compensable command

```
...
import com.ibm.websphere.command.*;
public interface MyCommand extends TargetableCommand, CompensableCommand {
    // Declare application methods here
}
```

Facilities for implementing commands

Commands are implemented by extending the class `TargetableCommandImpl`, which implements the `TargetableCommand` interface. The `TargetableCommandImpl` class is an abstract class that provides some implementations for some of the methods in the `TargetableCommand` interface (for example, setting return values) and declares additional methods that the application itself must implement (for example, how to execute the command).

You implement your command interface by writing a class that extends the `TargetableCommandImpl` class and implements your command interface. This class contains the code for the methods in your interface, the methods inherited from extended interfaces (the `TargetableCommand` and `CompensableCommand` interfaces), and the required (abstract) methods in the `TargetableCommandImpl` class. You can also override the default implementations of other methods provided in the `TargetableCommandImpl` class. [Figure 65](#) shows the structure of an implementation class for the interface in [Figure 64](#).

Figure 65. Code example: The structure of an implementation class for a command interface

```
...
import java.lang.reflect.*;
import com.ibm.websphere.command.*;
public class MyCommandImpl extends TargetableCommandImpl
implements MyCommand {
    // Set instance variables here
    ...
    // Implement methods in the MyCommand interface
    ...
    // Implement methods in the CompensableCommand interface
    ...
    // Implement abstract methods in the TargetableCommandImpl class
    ...
}
```

Facilities for setting and determining targets

The object that is the target of a `TargetableCommand` must implement the `CommandTarget` interface. This object can be an actual server-side object, like an entity bean, or it can be a client-side adapter for a server. The implementor of the `CommandTarget` interface is responsible for ensuring the proper execution of a command in the desired target server environment. This typically requires the following steps:

1. Copying the command to the target server by using a server-specific protocol.
2. Running the command in the server.
3. Copying the executed command from the target server to the client by using a server-specific protocol.

Common ways to implement the `CommandTarget` interface include:

- A local target, which runs in the client's JVM.
- A client-side adapter for a server. For an example that implements the target as a client-side adapter, see [Writing a command target \(client-side adapter\)](#).
- An enterprise bean (either a session bean or an entity bean). [Figure 66](#) shows the structure of the remote interface and enterprise bean class for an entity bean that implements the `CommandTarget` interface. An enterprise bean is provided with WebSphere that can be deployed and used as a `CommandTarget`. See [Using the WebSphere EJBCommandTarget bean as a command target](#).

Figure 66. Code example: The structure of a command-target entity bean

```
...
import java.rmi.RemoteException;
import java.util.Properties;
import javax.ejb.*;
import com.ibm.websphere.command.*;
// Remote interface for the MyBean enterprise bean (also a command target)
public interface MyBean extends EJBObject, CommandTarget {
    // Declare methods for the remote interface
```

```

    ...
}
// Entity bean class for the MyBean enterprise bean (also a command target)
public class MyBeanClass implements EntityBean, CommandTarget {
    // Set instance variables here
    ...
    // Implement methods in the remote interface
    ...
    // Implement methods in the EntityBean interface
    ...
    // Implement the method in the CommandTarget interface
    ...
}

```

Since targetable commands can be run remotely in another JVM, the command package provides mechanisms for determining where to run the command. A *target policy* associates a command with a target and is specified through the TargetPolicy interface. You can design customized target policies by implementing this interface, or you can use the provided TargetPolicyDefault class. For more information, see [Targets and target policies](#).

Exceptions in the command package

The command package defines a set of exception classes. The CommandException class extends the DistributedException class and acts as the base class for the additional command-related exceptions: UnauthorizedAccessException, UnsetInputPropertiesException, and UnavailableCompensableCommandException. Applications can extend the CommandException class to define additional exceptions, as well.

Although the CommandException class extends the DistributedException class, you do not have to import the distributed-exception package, com.ibm.websphere.exception, unless you need to use the features of the DistributedException class in your application. For more information on distributed exceptions, see [The distributed-exception package](#).

Writing command interfaces

To write a command interface, you extend one or more of the three interfaces included in the command package. The base interface for all commands is the Command interface. This interface provides only the client-side interface for generic commands and declares three basic methods:

- **isReadyToCallExecute**--This method is called on the client side before the command is passed to the server for execution.
- **execute**--This method passes the command to the target and returns any data.
- **reset**--This method reverts any output properties to the values they had before the execute method was called so that the object can be reused.

The implementation class for your interface must contain implementations for the isReadyToCallExecute and reset methods. The execute method is implemented for you elsewhere; for more information, see [Implementing command interfaces](#). Most commands do not extend the Command interface directly but use one of the provided extensions: the TargetableCommand interface and the CompensableCommand interface.

The TargetableCommand interface

The TargetableCommand interface extends the Command interface and provides for remote execution of commands. Most commands will be targetable commands. The TargetableCommand interface declares several additional methods:

- **setCommandTarget**--This method allows you to specify the target object to a command.
- **setCommandTargetName**--This method allows you to specify the target by name to a command.
- **getCommandTarget**--This method returns the target object of the command.
- **getCommandTargetName**--This method returns the name of the target object of the command.
- **hasOutputProperties**--This method indicates whether or not the command has output that must be copied back to the

client. (The implementation class also provides a method, `setHasOutputProperties`, for setting the output of this method. By default, `hasOutputProperties` returns true.)

- `setOutputProperties`--This method saves output values from the command for return to the client.
- `performExecute`--This method encapsulates the application-specific work. It is called for you by the `execute` method declared in the `Command` interface.

With the exception of the `performExecute` method, which you must implement, all of these methods are implemented in the `TargetableCommandImpl` class. This class also implements the `execute` method declared in the `Command` interface.

The `CompensableCommand` interface

The `CompensableCommand` interface also extends the `Command` interface. A compensable command is one that has another command (a compensator) associated with it, so that the work of the first can be undone by the compensator. For example, a command that attempts to make an airline reservation followed by a hotel reservation can offer a compensating command that allows the user to cancel the airline reservation if the hotel reservation cannot be made.

The `CompensableCommand` interface declares one method:

- `getCompensatingCommand`--This method returns the command that can be used to undo the effects of the original command.

To create a compensable command, you write an interface that extends the `CompensableCommand` interface. Such interfaces typically extend the `TargetableCommand` interface as well. You must implement the `getCompensatingCommand` method in the implementation class for your interface. You must also implement the compensating command.

The example application

The example used throughout the remainder of this discussion uses an entity bean with container-managed persistence (CMP) called `CheckingAccountBean`, which allows a client to deposit money, withdraw money, set a balance, get a balance, and retrieve the name on the account. This entity bean also accepts commands from the client. The code examples illustrate the command-related programming. For a servlet-based example, see [Writing a command target \(client-side adapter\)](#).

[Figure 67](#) shows the interface for the `ModifyCheckingAccountCmd` command. This command is both targetable and compensable, so the interface extends both `TargetableCommand` and `CompensableCommand` interfaces.

Figure 67. Code example: The `ModifyCheckingAccountCmd` interface

```
...
import com.ibm.websphere.exception.*;
import com.ibm.websphere.command.*;
public interface ModifyCheckingAccountCmd
extends TargetableCommand, CompensableCommand {
    float getAmount();
    float getBalance();
    float getOldBalance();           // Used for compensating
    float setBalance(float amount);
    float setBalance(int amount);
    CheckingAccount getCheckingAccount();
    void setCheckingAccount(CheckingAccount newCheckingAccount);
    TargetPolicy getCmdTargetPolicy();
    ...
}
```

Implementing command interfaces

The command package provides a class, `TargetableCommandImpl`, that implements all of the methods in the `TargetableCommand` interface except the `performExecute` method. It also implements the `execute` method from the `Command` interface. To implement an application's command interface, you must write a class that extends the `TargetableCommandImpl` class and implements your command interface. [Figure 68](#) shows the structure of the

ModifyCheckingAccountCmdImpl class.

Figure 68. Code example: The structure of the ModifyCheckingAccountCmdImpl class

```
...
public class ModifyCheckingAccountCmdImpl extends TargetableCommandImpl
implements ModifyCheckingAccountCmd
{
    // Variables
    ...
    // Methods
    ...
}
```

The class must declare any variables and implement these methods:

- Any methods you defined in your command interface.
- The `isReadyToCallExecute` and `reset` methods from the `Command` interface.
- The `performExecute` method from the `TargetableCommand` interface.
- The `getCompensatingCommand` method from the `CompensableCommand` interface, if your command is compensable. You must also implement the compensating command.

You can also override the nonfinal implementations provided in the `TargetableCommandImpl` class. The most likely candidate for reimplementation is the `setOutputProperties` method, since the default implementation does not save final, transient, or static fields.

Defining instance and class variables

The `ModifyCheckingAccountCmdImpl` class declares the variables used by the methods in the class, including the remote interface of the `CheckingAccount` entity bean; the variables used to capture operations on the checking account (balances and amounts); and a compensating command. [Figure 69](#) shows the variables used by the `ModifyCheckingAccountCmd` command.

Figure 69. Code example: The variables in the ModifyCheckingAccountCmdImpl class

```
...
public class ModifyCheckingAccountCmdImpl extends TargetableCommandImpl
implements ModifyCheckingAccountCmd
{
    // Variables
    public float balance;
    public float amount;
    public float oldBalance;
    public CheckingAccount checkingAccount;
    public ModifyCheckingAccountCompensatorCmd
        modifyCheckingAccountCompensatorCmd;
    ...
}
```

Implementing command-specific methods

The `ModifyCheckingAccountCmd` interface defines several command-specific methods in addition to extending other interfaces in the command package. These command-specific methods are implemented in the `ModifyCheckingAccountCmdImpl` class.

You must provide a way to instantiate the command. The command package does not specify the mechanism, so you can choose the technique most appropriate for your application. The fastest and most efficient technique is to use constructors. The most flexible technique is to use a factory. Also, since commands are implemented internally as JavaBeans components, you can use the standard `Beans.instantiate` method. The `ModifyCheckingAccountCmd` command uses constructors.

[Figure 70](#) shows the two constructors for the command. The difference between them is that the first uses the default target

policy for determining the target of the command and the second allows you to specify a custom policy. (For more information on targets and target policies, see [Targets and target policies](#).)

Both constructors take a `CommandTarget` object as an argument and cast it to the `CheckingAccount` type. The `CheckingAccount` interface extends both the `CommandTarget` interface and the `EJBObject` (see [Figure 80](#)). The resulting `checkingAccount` object routes the command to the desired server by using the bean's remote interface. (For more information on `CommandTarget` objects, see [Writing a command target \(server\)](#).)

Figure 70. Code example: Constructors in the `ModifyCheckingAccountCmdImpl` class

```
...
public class ModifyCheckingAccountCmdImpl extends TargetableCommandImpl
implements ModifyCheckingAccountCmd
{
    // Variables
    ...
    // Constructors
    // First constructor: relies on the default target policy
    public ModifyCheckingAccountCmdImpl(CommandTarget target,
                                       float newAmount)
    {
        amount = newAmount;
        checkingAccount = (CheckingAccount)target;
        setCommandTarget(target);
    }
    // Second constructor: allows you to specify a custom target policy
    public ModifyCheckingAccountCmdImpl(CommandTarget target,
                                       float newAmount,
                                       TargetPolicy targetPolicy)
    {
        setTargetPolicy(targetPolicy);
        amount = newAmount;
        checkingAccount = (CheckingAccount)target;
        setCommandTarget(target);
    }
    ...
}
```

[Figure 71](#) shows the implementation of the command-specific methods:

- `setBalance`--This method sets the balance of the account.
- `getAmount`--This method returns the amount of a deposit or withdrawal.
- `getOldBalance`, `getBalance`--These methods capture the balance before and after an operation.
- `getCmdTargetPolicy`--This method retrieves the current target policy.
- `setCheckingAccount`, `getCheckingAccount`--These methods set and retrieve the current checking account.

Figure 71. Code example: Command-specific methods in the `ModifyCheckingAccountCmdImpl` class

```
...
public class ModifyCheckingAccountCmdImpl extends TargetableCommandImpl
implements ModifyCheckingAccountCmd
{
    // Variables
    ...
    // Constructors
    ...
    // Methods in ModifyCheckingAccountCmd interface
    public float getAmount() {
        return amount;
    }
    public float getBalance() {
```



```

        return balance;
    }
    public float getOldBalance() {
        return oldBalance;
    }
    public float setBalance(float amount) {
        balance = balance + amount;
        return balance;
    }
    public float setBalance(int amount) {
        balance += amount ;
        return balance;
    }
    public TargetPolicy getCmdTargetPolicy() {
        return getTargetPolicy();
    }
    public void setCheckingAccount(CheckingAccount newCheckingAccount) {
        if (checkingAccount == null) {
            checkingAccount = newCheckingAccount;
        }
        else
            System.out.println("Incorrect Checking Account (" +
                newCheckingAccount + ") specified");
    }
    public CheckingAccount getCheckingAccount() {
        return checkingAccount;
    }
    ...
}

```

The ModifyCheckingAccountCmd command operates on a checking account. Because commands are implemented as JavaBeans components, you manage input and output properties of commands using the standard JavaBeans techniques. For example, initialize input properties with set methods (like setCheckingAccount) and retrieve output properties with get methods (like getCheckingAccount). The get methods do not work until after the command's execute method has been called.

Implementing methods from the Command interface

The Command interface declares two methods, isReadyToCallExecute and reset, that must be implemented by the application programmer. [Figure 72](#) shows the implementations for the ModifyCheckingAccountCmd command. The implementation of the isReadyToCallExecute method ensures that the checkingAccount variable is set. The reset method sets all of the variables back to starting values.

Figure 72. Code example: Methods from the Command interface in the ModifyCheckingAccountCmdImpl class

```

...
public class ModifyCheckingAccountCmdImpl extends TargetableCommandImpl
implements ModifyCheckingAccountCmd
{
    ...
    // Methods from the Command interface
    public boolean isReadyToCallExecute() {
        if (checkingAccount != null)
            return true;
        else
            return false;
    }
    public void reset() {
        amount = 0;
        balance = 0;
        oldBalance = 0;
    }
}

```

```

        checkingAccount = null;
        targetPolicy = new TargetPolicyDefault();
    }
    ...
}

```

Implementing methods from the TargetableCommand interface

The TargetableCommand interface declares one method, performExecute, that must be implemented by the application programmer. [Figure 73](#) shows the implementation for the ModifyCheckingAccountCmd command. The implementation of the performExecute method does the following:

- Saves the current balance (so the command can be undone by a compensator command)
- Calculates the new balance
- Sets the current balance to the new balance
- Ensures that the hasOutputProperties method returns true so that the values are returned to the client

In addition, the ModifyCheckingAccountCmdImpl class overrides the default implementation of the setOutputProperties method.

Figure 73. Code example: Methods from the TargetableCommand interface in the ModifyCheckingAccountCmdImpl class

```

...
public class ModifyCheckingAccountCmdImpl extends TargetableCommandImpl
implements ModifyCheckingAccountCmd
{
    ...
    // Method from the TargetableCommand interface
    public void performExecute() throws Exception {
        CheckingAccount checkingAccount = getCheckingAccount();
        oldBalance = checkingAccount.getBalance();
        balance = oldBalance+amount;
        checkingAccount.setBalance(balance);
        setHasOutputProperties(true);
    }
    public void setOutputProperties(TargetableCommand fromCommand) {
        try {
            if (fromCommand != null) {
                ModifyCheckingAccountCmd modifyCheckingAccountCmd =
                    (ModifyCheckingAccountCmd) fromCommand;
                this.oldBalance = modifyCheckingAccountCmd.getOldBalance();
                this.balance = modifyCheckingAccountCmd.getBalance();
                this.checkingAccount =
                    modifyCheckingAccountCmd.getCheckingAccount();
                this.amount = modifyCheckingAccountCmd.getAmount();
            }
        }
        catch (Exception ex) {
            System.out.println("Error in setOutputProperties.");
        }
    }
    ...
}

```

Implementing the CompensableCommand interface

The CompensableCommand interface declares one method, getCompensatingCommand, that must be implemented by the application programmer. [Figure 74](#) shows the implementation for the ModifyCheckingAccountCmd command. The implementation simply returns an instance of the ModifyCheckingAccountCompensatorCmd command associated with the

current command.

Figure 74. Code example: Method from the CompensableCommand interface in the ModifyCheckingAccountCmdImpl class

```
...
public class ModifyCheckingAccountCmdImpl extends TargetableCommandImpl
implements ModifyCheckingAccountCmd
{
    ...
    // Method from CompensableCommand interface
    public Command getCompensatingCommand() throws CommandException {
        modifyCheckingAccountCompensatorCmd =
            new ModifyCheckingAccountCompensatorCmd(this);
        return (Command)modifyCheckingAccountCompensatorCmd;
    }
}
```

Writing the compensating command

An application that uses a compensable command requires two separate commands: the primary command (declared as a `CompensableCommand`) and the compensating command. In the example application, the primary command is declared in the `ModifyCheckingAccountCmd` interface and implemented in the `ModifyCheckingAccountCmdImpl` class. Because this command is also a compensable command, there is a second command associated with it that is designed to undo its work. When you create a compensable command, you also have to write the compensating command.

Writing a compensating command can require exactly the same steps as writing the original command: writing the interface and providing an implementation class. In some cases, it may be simpler. For example, the command to compensate for the `ModifyCheckingAccountCmd` does not require any methods beyond those defined for the original command, so it does not need an interface. The compensating command, called `ModifyCheckingAccountCompensatorCmd`, simply needs to be implemented in a class that extends the `TargetableCommandImpl` class. This class must:

- Provide a way to instantiate the command; the example uses a constructor
- Implement the three required methods:
 - `isReadyToCallExecute` and `reset`--both from the `Command` interface
 - `performExecute`--from the `TargetableCommand` interface

Figure 75 shows the structure of the implementation class, its variables (references to the original command and to the relevant checking account), and the constructor. The constructor simply instantiates the references to the primary command and account.

Figure 75. Code example: Variables and constructor in the ModifyCheckingAccountCompensatorCmd class

```
...
public class ModifyCheckingAccountCompensatorCmd extends TargetableCommandImpl
{
    public ModifyCheckingAccountCmdImpl modifyCheckingAccountCmdImpl;
    public CheckingAccount checkingAccount;

    public ModifyCheckingAccountCompensatorCmd(
        ModifyCheckingAccountCmdImpl originalCmd)
    {
        // Get an instance of the original command
        modifyCheckingAccountCmdImpl = originalCmd;
        // Get the relevant account
        checkingAccount = originalCmd.getCheckingAccount();
    }
    // Methods from the Command and Targetable Command interfaces
    ....
}
```

Figure 76 shows the implementation of the inherited methods. The implementation of the `isReadyToCallExecute` method ensures that the `checkingAccount` variable has been instantiated.

The `performExecute` method verifies that the actual checking-account balance is consistent with what the original command returns. If so, it replaces the current balance with the previously stored balance by using the `ModifyCheckingAccountCmd` command. Finally, it saves the most-recent balances in case the compensating command needs to be undone. The `reset` method has no work to do.

Figure 76. Code example: Methods in `ModifyCheckingAccountCompensatorCmd` class

```
...
public class ModifyCheckingAccountCompensatorCmd extends TargetableCommandImpl
{
    // Variables and constructor
    ....
    // Methods from the Command and TargetableCommand interfaces
    public boolean isReadyToCallExecute() {
        if (checkingAccount != null)
            return true;
        else
            return false;
    }
    public void performExecute() throws CommandException
    {
        try {
            ModifyCheckingAccountCmdImpl originalCmd =
                modifyCheckingAccountCmdImpl;
            // Retrieve the checking account modified by the original command
            CheckingAccount checkingAccount = originalCmd.getCheckingAccount();
            if (modifyCheckingAccountCmdImpl.balance ==
                checkingAccount.getBalance()) {
                // Reset the values on the original command
                checkingAccount.setBalance(originalCmd.oldBalance);
                float temp = modifyCheckingAccountCmdImpl.balance;
                originalCmd.balance = originalCmd.oldBalance;
                originalCmd.oldBalance = temp;
            }
            else {
                // Balances are inconsistent, so we cannot compensate
                throw new CommandException(
                    "Object modified since this command ran.");
            }
        }
        catch (Exception e) {
            System.out.println(e.getMessage());
        }
    }
    public void reset() {}
}
```

Using a command

To use a command, the client creates an instance of the command and calls the command's `execute` method. Depending on the command, calling other methods can be necessary. The specifics will vary with the application.

In the example application, the server is the `CheckingAccountBean`, an entity enterprise bean. In order to use this enterprise bean, the client gets a reference to the bean's home interface. The client then uses the reference to the home interface and one of the bean's finder methods to obtain a reference to the bean's remote interface. If there is no appropriate bean, the client can create one using a `create` method on the home interface. All of this work is standard enterprise bean programming covered elsewhere in this document.

Figure 77 illustrates the use of the `ModifyCheckingAccountCmd` command. This work takes place after an appropriate `CheckingAccount` bean has been found or created. The code instantiates a command, setting the input values by using one of the constructors defined for the command. The null argument indicates that the command should look up the server using the default target policy, and 1000 is the amount the command attempts to add to the balance of the checking account. (For more information on how the command package uses defaults to determine the target of a command, see [The default target policy](#).) After the command is instantiated, the code calls the `setCheckingAccount` method to identify the account to be modified. Finally, the `execute` method on the command is called.

Figure 77. Code example: Using the `ModifyCheckingAccountCmd` command

```
{
    ...
    CheckingAccount checkingAccount
    ...
    try {
        ModifyCheckingAccountCmd cmd =
            new ModifyCheckingAccountCmdImpl(null, 1000);
        cmd.setCheckingAccount(checkingAccount);
        cmd.execute();
    }
    catch (Exception e) {
        System.out.println(e.getMessage());
    }
    ...
}
```

Using a compensating command

To use a compensating command, you must retrieve the compensator associated with the primary command and call its `execute` method. Figure 78 shows the code used to run the original command and to give the user the option of undoing the work by running the compensating command.

Figure 78. Code example: Using the `ModifyCheckingAccountCompensator` command

```
{
    ...
    CheckingAccount checkingAccount
    ....
    try {
        ModifyCheckingAccountCmd cmd =
            new ModifyCheckingAccountCmdImpl(null, 1000);
        cmd.setCheckingAccount(checkingAccount);
        cmd.execute();
        ...
        System.out.println("Would you like to undo this work? Enter Y or N");
        try {
            // Retrieve and validate user's response
            ...
        }
        ...
        if (answer.equalsIgnoreCase(Y)) {
            Command compensatingCommand = cmd.getCompensatingCommand();
            compensatingCommand.execute();
        }
    }
    catch (Exception e) {
        System.out.println(e.getMessage());
    }
    ...
}
```

Using the WebSphere EJBCCommandTarget bean as a command target

WebSphere ships a CommandTarget enterprise bean to allow administrators to execute a command in a designated server without providing their own implementation of CommandTarget. The EJBCCommandTarget class, along with the EJBCCommandTarget bean (CommandServerSessionBean), are located in the EJBCCommandTarget.jar file in the lib directory under the WebSphere installation directory. This is a deployed jar file. You can use this JAR file in a new application or add it into an existing application.

The EJBCCommandTarget class serves as a wrapper for a CommandTarget bean. CommandServerSessionBean is the WebSphere implementation of this CommandTarget bean. A command developer can set this EJBCCommandTarget object into the Command. [Figure 79](#) shows an example.

Figure 79. Code example: Using an EJBCCommandTarget bean

```
EJBCCommandTarget target = new EJBCCommandTarget();

MyCommand cmd = new MyCommandImpl(Arguments...);
cmd.setCommandTarget(target);
cmd.execute();
```

In this example, the client creates a MyCommand object. It is then executed in the application server. When the execute method is performed, the target (EJBCCommandTarget) looks up the CommandServerSessionHome from the InitialContext and executes the executeCommand method on the CommandServerSessionBean. The EJBCCommandTarget object ensures that there is only one CommandServerSessionBean per object to avoid extra naming lookup.

An EJBCCommandTarget object can be created using four different constructors:

- EJBCCommandTarget("MyNamingServerName", "PortNumber", "JNDIName")
- EJBCCommandTarget(InitialContext, "JNDIName")
- EJBCCommandTarget("JNDIName")
- EJBCCommandTarget()

The first constructor allows the application to specify the naming server name and the port. The JNDI name of the CommandServerSessionBean can also be specified. The EJBCCommandTarget constructs a provider URL of "iiop://MyNamingServerName:PortNumber" and looks up the CommandServerSessionBean with the given JNDI name. If null values are passed in for any of the parameters the WebSphere defaults for server and port and a default JNDI name of CommandServerSession are used.

The second constructor allows the application to specify its own initial context. The EJBCCommandTarget object then uses this initial context to look up the CommandServerSession bean with the specified JNDI name.

The third constructor allows the application to set up the naming server (the provider URL) in property files.

The default constructor uses the default values for the provider URL and default JNDI name for the CommandServerSession bean (CommandServerSession).

You do not need to use the EJBCCommandTarget class. You can instead create your own custom target policy that uses the EJBCCommandTarget bean (CommandServerSessionBean). The EJBCCommandTarget object is a convenience class and attempts to address most usage scenarios

Writing a command target (server)

In order to accept commands, a server must implement the CommandTarget interface and its single method, executeCommand.

The example application implements the CommandTarget interface in an enterprise bean. (For a servlet-based example, see [Writing a command target \(client-side adapter\)](#).) The target enterprise bean can be a session bean or an entity bean. You can write a target enterprise bean that forwards commands to a specific server, such as another entity bean. In this case, all commands directed at a specific target go through the target enterprise bean. You can also write a target enterprise bean that does the work of the command locally.

Make an enterprise bean the target of a command by:

- Extending the `CommandTarget` interface when you define the bean's remote interface, which must also extend the `EJBObject` interface
- Implementing the `CommandTarget` interface when you implement the bean class, which must also implement either the `SessionBean` or `EntityBean` interface

The target of the example application is an enterprise bean called `CheckingAccountBean`. This bean's remote interface, `CheckingAccount`, extends the `CommandTarget` interface in addition to the `EJBObject` interface. The methods declared in the remote interface are independent of those used by the command. The `executeCommand` is declared in neither the bean's home nor remote interfaces. [Figure 80](#) shows the `CheckingAccount` interface.

Figure 80. Code example: The remote interface for the `CheckingAccount` entity bean, also a command target

```
...
import com.ibm.websphere.command.*;
import javax.ejb.EJBObject;
import java.rmi.RemoteException;
public interface CheckingAccount extends CommandTarget, EJBObject {
    float deposit (float amount) throws RemoteException;
    float deposit (int amount) throws RemoteException;
    String getAccountName() throws RemoteException;
    float getBalance() throws RemoteException;
    float setBalance(float amount) throws RemoteException;
    float withdrawal (float amount) throws RemoteException, Exception;
    float withdrawal (int amount) throws RemoteException, Exception;
}
```

The enterprise bean class, `CheckingAccountBean`, implements the `EntityBean` interface as well as the `CommandTarget` interface. The class contains the business logic for the methods in the remote interface, the necessary life-cycle methods (`ejbActivate`, `ejbStore`, and so on), and the `executeCommand` declared by the `CommandTarget` interface. The `executeCommand` method is the only command-specific code in the enterprise bean class. It attempts to run the `performExecute` method on the command and throws a `CommandException` if an error occurs. If the `performExecute` method runs successfully, the `executeCommand` method uses the `hasOutputProperties` method to determine if there are output properties that must be returned. If the command has output properties, the method returns the command object to the client. [Figure 81](#) shows the relevant parts of the `CheckingAccountBean` class.

Figure 81. Code example: The bean class for the `CheckingAccount` entity bean, also a command target

```
...
public class CheckingAccountBean implements EntityBean, CommandTarget {
    // Bean variables
    ...
    // Business methods from remote interface
    ...
    // Life-cycle methods for CMP entity beans
    ...
    // Method from the CommandTarget interface
    public TargetableCommand executeCommand(TargetableCommand command)
    throws RemoteException, CommandException
    {
        try {
            command.performExecute();
        }
        catch (Exception ex) {
            if (ex instanceof RemoteException) {
                RemoteException remoteException = (RemoteException)ex;
                if (remoteException.detail != null) {
                    throw new CommandException(remoteException.detail);
                }
                throw new CommandException(ex);
            }
        }
    }
}
```



```

        if (command.hasOutputProperties()) {
            return command;
        }
        return null;
    }
}

```

Targets and target policies

A targetable command extends the `TargetableCommand` interface, which allows the client to direct a command to a particular server. The `TargetableCommand` interface (and the `TargetableCommandImpl` class) provide two ways for a client to specify a target: the `setCommandTarget` and `setCommandTargetName` methods. (These methods were introduced in [The TargetableCommand interface](#).) The `setCommandTarget` methods allows the client to set the target object directly on the command. The `setCommandTargetName` method allows the client to refer to the server by name; this approach is useful when the client is not directly aware of server objects. A targetable command also has corresponding `getCommandTarget` and `getCommandTargetName` methods.

The command package needs to be able to identify the target of a command. Because there is more than one way to specify the target and because different applications can have different requirements, the command package does not specify a selection algorithm. Instead, it provides a `TargetPolicy` interface with one method, `getCommandTarget`, and a default implementation. This allows applications to devise custom algorithms for determining the target of a command when appropriate.

The default target policy

The command package provides a default implementation of the `TargetPolicy` interface in the `TargetPolicyDefault` class. If you use this default implementation, the command determines the target by looking through an ordered sequence of four options:

1. The `CommandTarget` value
2. The `CommandTargetName` value
3. A registered mapping of a target for a specific command
4. A defined default target

If it finds no target, it returns null. The `TargetPolicyDefault` class provides methods for managing the assignment of commands with targets (`registerCommand`, `unregisterCommand`, and `listMappings`), and a method for setting a default name for the target (`setDefaultTargetName`). The default target name is `com.ibm.websphere.command.LocalTarget`, where `LocalTarget` is a class that runs the command's `performExecute` method locally. [Figure 82](#) shows the relevant variables and the methods in the `TargetPolicyDefault` class.

Figure 82. Code example: The `TargetPolicyDefault` class

```

...
public class TargetPolicyDefault implements TargetPolicy, Serializable
{
    ...
    protected String defaultTargetName = "com.ibm.websphere.command.LocalTarget";
    public CommandTarget getCommandTarget(TargetableCommand command) {
        ... }
    public Dictionary listMappings() {
        ... }
    public void registerCommand(String commandName, String targetName) {
        ... }
    public void unregisterCommand(String commandName) {
        ... }
    public void seDefaultTargetName(String defaultTargetName) {
        ... }
}

```

Setting the command target

The `ModifyCheckingAccountImpl` class provides two command constructors (see [Figure 70](#)). One of them takes a command target as an argument and implicitly uses the default target policy to locate the target. The constructor used in [Figure 77](#) passes a null target, so that the default target policy traverses its choices and eventually finds the default target name, `LocalTarget`.

The example in [Figure 83](#) uses the same constructor to set the target explicitly. This example differs from [Figure 77](#) as follows:

- The command target is set to the checking account rather than null. The default target policy starts to traverse its choices and finds the target in the first place it looks.
- It does not have to call the `setCheckingAccount` method to indicate the account on which the command should operate; the constructor uses the target variable as both the target and the account.

Figure 83. Code example: Identifying a target with `CommandTarget`

```
{
    ...
    CheckingAccount checkingAccount
    ....
    try {
        ModifyCheckingAccountCmd cmd =
            new ModifyCheckingAccountCmdImpl(checkingAccount, 1000);
        cmd.execute();
    }
    catch (Exception e) {
        System.out.println(e.getMessage());
    }
    ...
}
```

Setting the command target name

If a client needs to set the target of the command by name, it can use the command's `setCommandTargetName` method. [Figure 84](#) illustrates this technique. This example compares with [Figure 77](#) as follows:

- Both explicitly set the command target in the constructor to null.
- Both use the `setCheckingAccount` method to indicate the account on which the command should operate.
- This example sets the target name explicitly by using the `setCommandTargetName` method. When the default target policy traverses its choices, it finds a null for the first choice and a name for the second.

Figure 84. Code example: Identifying a target with `CommandTargetName`

```
{
    ...
    CheckingAccount checkingAccount
    ....
    try {
        ModifyCheckingAccountCmd cmd =
            new ModifyCheckingAccountCmdImpl(null, 1000);
        cmd.setCheckingAccount(checkingAccount);
        cmd.setCommandTargetName("com.ibm.sfc.cmd.test.CheckingAccountBean");
        cmd.execute();
    }
    catch (Exception e) {
        System.out.println(e.getMessage());
    }
    ...
}
```

Mapping the command to a target name

The default target policy also permits commands to be registered with targets. Mapping a command to a target is an administrative task that most appropriately done through a configuration tool. The WebSphere Application Server administrative console does not yet support the configuration of mappings between commands and targets. Applications that require support for the registration of commands with targets must supply the tools to manage the mappings. These tools can be visual interfaces or command-line tools.

Figure 85 shows the registration of a command with a target. The names of the command class and the target are explicit in the code, but in practice, these values would come from fields in a user interface or arguments to a command-line tool. If a program creates a command as shown in Figure 77, with a null for the target, when the default target policy traverses its choices, it finds a null for the first and second choices and a mapping for the third.

Figure 85. Code example: Mapping a command to a target in an external application

```
{
    ...
    targetPolicy.registerCommand(
        "com.ibm.sfc.cmd.test.ModifyCheckingAccountImpl",
        "com.ibm.sfc.cmd.test.CheckingAccountBean");
    ...
}
```

Customizing target policies

You can define custom target policies by implementing the `TargetPolicy` interface and providing a `getCommandTarget` method appropriate for your application. The `TargetableCommandImpl` class provides `setTargetPolicy` and `getTargetPolicy` methods for managing custom target policies.

So far, the target of all the commands has been a checking-account entity bean. Suppose that someone introduces a session enterprise bean (`MySessionBean`) that can also act as a command target. Figure 86 shows a simple custom policy that sets the target of every command to `MySessionBean`.

Figure 86. Code example: Creating a custom target policy

```
...
import java.io.*;
import java.util.*;
import java.beans.*;
import com.ibm.websphere.command.*;
public class CustomTargetPolicy implements TargetPolicy, Serializable {
    public CustomTargetPolicy {
        super();
    }
    public CommandTarget getCommandTarget(TargetableCommand command) {
        CommandTarget = null;
        try {
            target = (CommandTarget)Beans.instantiate(null,
                "com.ibm.sfc.cmd.test.MySessionBean");
        }
        catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

Since commands are implemented as JavaBeans components, using custom target policies requires importing the `java.beans` package and writing some elementary JavaBeans code. Also, your custom target-policy class must also implement the `java.io.Serializable` interface.

Using a custom target policy

The `ModifyCheckingAccountImpl` class provides two command constructors (see [Figure 70](#)). One of them implicitly uses the default target policy; the other takes a target policy object as an argument, which allows you to use a custom target policy. The example in [Figure 87](#) uses the second constructor, passing a null target and a custom target policy, so that the custom policy is used to determine the target. After the command is executed, the code uses the `reset` method to return the target policy to the default.

Figure 87. Code example: Using a custom target policy

```
{
    ...
    CheckingAccount checkingAccount
    ....
    try {
        CustomTargetPolicy customPolicy = new CustomTargetPolicy();
        ModifyCheckingAccountCmd cmd =
            new ModifyCheckingAccountCmdImpl(null, 1000, customPolicy);
        cmd.setCheckingAccount(checkingAccount);
        cmd.execute();
        cmd.reset();
    }
    catch (Exception e) {
        System.out.println(e.getMessage());
    }
}
```

Writing a command target (client-side adapter)

Commands can be used with any Java application, but the means of sending the command from the client to the server varies. The application described in [The example application](#) used enterprise beans. The example in this section shows how you can send a command to a servlet over the HTTP protocol.

In this example, the client implements the `CommandTarget` interface locally. [Figure 88](#) shows the structure of the client-side class; it implements the `CommandTarget` interface by implementing the `executeCommand` method.

Figure 88. Code example: The structure of a client-side adapter for a target

```
...
import java.io.*;
import java.rmi.*;
import com.ibm.websphere.command.*;
public class ServletCommandTarget implements CommandTarget, Serializable
{
    protected String hostName = "localhost";
    public static void main(String args[]) throws Exception
    {
        ....
    }
    public TargetableCommand executeCommand(TargetableCommand command)
        throws CommandException
    {
        ....
    }
    public static final byte[] serialize(Serializable serializable)
        throws IOException {
        ... }
    public String getHostName() {
        ... }
    public void setHostName(String hostName) {
        ... }
    private static void showHelp() {
        ... }
}
```

```
}
```

The main method in the client-side adapter constructs and initializes the CommandTarget object, as shown in [Figure 89](#).

Figure 89. Code example: Instantiating the client-side adapter

```
public static void main(String args[]) throws Exception
{
    String hostName = InetAddress.getLocalHost().getHostName();
    String fileName = "MyServletCommandTarget.ser";
    // Parse the command line
    ...
    // Create and initialize the client-side CommandTarget adapter
    ServletCommandTarget servletCommandTarget = new ServletCommandTarget();
    servletCommandTarget.setHostName(hostName);
    ...
    // Flush and close output streams
    ...
}
```

Implementing a client-side adapter

The CommandTarget interface declares one method, executeCommand, which the client implements. The executeCommand method takes a TargetableCommand object as input; it also returns a TargetableCommand. [Figure 90](#) shows the implementation of the method used in the client-side adapter. This implementation does the following:

- Serializes the command it receives
- Creates an HTTP connection to the servlet
- Creates input and output streams, to handle the command as it is sent to the server and returned
- Places the command on the output stream
- Sends the command to the server
- Retrieves the returned command from the input stream
- Returns the returned command to the caller of the executeCommand method

Figure 90. Code example: A client-side implementation of the executeCommand method

```
public TargetableCommand executeCommand(TargetableCommand command)
    throws CommandException
{
    try {
        // Serialize the command
        byte[] array = serialize(command);
        // Create a connection to the servlet
        URL url = new URL
            ("http://" + hostName +
             "/servlet/com.ibm.websphere.command.servlet.CommandServlet");
        URLConnection httpURLConnection =
            (URLConnection) url.openConnection();
        // Set the properties of the connection
        ...
        // Put the serialized command on the output stream
        OutputStream outputStream = httpURLConnection.getOutputStream();
        outputStream.write(array);
        // Create a return stream
        InputStream inputStream = httpURLConnection.getInputStream();
        // Send the command to the servlet
        httpURLConnection.connect();
        ObjectInputStream objectInputStream =
            new ObjectInputStream(inputStream);
        // Retrieve the command returned from the servlet
```

```

        Object object = objectInputStream.readObject();
        if (object instanceof CommandException) {
            throw ((CommandException) object);
        }
        // Pass the returned command back to the calling method
        return (TargetableCommand) object;
    }
    // Handle exceptions
    ....
}

```

Running the command in the servlet

The servlet that runs the command is shown in [Figure 91](#). The service method retrieves the command from the input stream and runs the performExecute method on the command. The resulting object, with any output properties that must be returned to the client, is placed on the output stream and sent back to the client.

Figure 91. Code example: Running the command in the servlet

```

...
import java.io.*;
import javax.servlet.*;
import javax.servlet.http.*;
import com.ibm.websphere.command.*;
public class CommandServlet extends HttpServlet {
    ...
    public void service(HttpServletRequest request,
                        HttpServletResponse response)
        throws ServletException, IOException
    {
        try {
            ...
            // Create input and output streams
            InputStream inputStream = request.getInputStream();
            OutputStream outputStream = response.getOutputStream();
            // Retrieve the command from the input stream
            ObjectInputStream objectInputStream =
                new ObjectInputStream(inputStream);
            TargetableCommand command = (TargetableCommand)
                objectInputStream.readObject();
            // Create the command for the return stream
            Object returnObject = command;

            // Try to run the command's performExecute method
            try {
                command.performExecute();
            }
            // Handle exceptions from the performExecute method
            ...

            // Return the command with any output properties
            ObjectOutputStream objectOutputStream =
                new ObjectOutputStream(outputStream);
            objectOutputStream.writeObject(returnObject);
            // Flush and close output streams
            ...
        }
        catch (Exception ex) {
            ex.printStackTrace();
        }
    }
}

```

```
}
```

In this example, the target invokes the `performExecute` method on the command, but this is not always necessary. In some applications, it can be preferable to implement the work of the command locally. For example, the command can be used only to send input data, so that the target retrieves the data from the command and runs a local database procedure based on the input. You must decide the appropriate way to use commands in your application.

The localizable-text package

Overview

Users of distributed applications can come from widely varying areas; they can speak different languages, represent dates and times in regionally specific ways, and use different currencies. An application intended to be used by such an audience must either force them all to use the same interface (for example, an English-based interface), or it can be written in such a way that it can be configured to the linguistic conventions of the users, so English-speaking users can use the English interface but French-speaking users can interact with the application through a French interface.

An application that can present information to users in formats that abide by the users' linguistic conventions is said to be *localizable*: the application can be configured to interact with users from different localities in linguistically appropriate ways. In a localized application, a user in one region sees error messages, output, and interface elements (like menu options) in the requested language. Additionally, other elements that are not strictly linguistic, like date and time formats and currencies, are presented in the appropriate style for users in the specified region. A user in another region sees output in the conventional language or format for that region.

Historically, the creation of localizable applications has been restricted to large corporations writing complex systems. The strategies for writing localizable code, collectively called *internationalization techniques*, have traditionally been expensive and difficult to implement, so they have been applied only to major development efforts. However, given the rise in distributed computing and in use of the World Wide Web, application developers have been pressured to make a much wider variety of applications localizable. This requires making internationalization--the techniques for writing localizable programs--much more accessible to application developers. The WebSphere localizable-text package is a set of Java classes and interfaces that can be used by WebSphere application developers to localize distributed WebSphere applications easily. Language catalogs for distributed WebSphere applications can be stored centrally, so the catalogs can be maintained and administered efficiently.

Writing localizable programs

In a nonlocalizable application, parts of the application that a user sees are unalterably coded into the application. For example, a routine that prints an error message simply prints a string, probably in English, to a file or the console. A localizable program adds a layer of abstraction into the design. Instead of going simply from error condition to output string, a localizable program represents error messages with some language-neutral information; in the simplest case, each error condition corresponds to a key. In order to print a usable error string for the user, the application looks up the key in the configured message catalog. A message catalog is a list of keys with corresponding strings. Different message catalogs provide the strings in different languages. The application looks up the key in the appropriate catalog, retrieves the corresponding error message in the desired language, and prints this string for the user.

The technique of localization can be used for far more than translating error messages. For example, by using keys to represent each element--button, label, menu item, and so forth--in a graphical user interface and by providing a message catalog containing translations of the button names, labels, and menu items, the graphical interface can be automatically translated into multiple languages. In addition, extending support to additional languages requires providing message catalogs for those languages; the application itself requires no modification.

Localization of an application is driven by two variables, the time zone and the locale. The time zone variable indicates how to compute the local time as an offset from a standard time like Greenwich Mean Time. The locale is a collection of information that indicates a geographic, political, or cultural region. It provides information on language, currency, and the conventions for presenting information like dates, and in a localizable program, the locale also indicates the message catalog from which an application retrieves messages. A time zone can cover many locales, and a single locale can span time zones. With both time zone and locale, the date, time, currency, and language for users in a specific region can be determined.

Identifying localizable text

To write a localizable application, an application developer must determine which aspects of the application need to be translatable. These are typically the parts of an application a user must read and understand. Application developers must consider the parts of an application with which all users directly interact, like the application's interface, and the parts serving more specialized purposes, like messages in log files. Good candidates for localization include:

- Elements in graphical user interfaces
 - Title bars for windows
 - Menu names, and the items on the menus (for example, "select File > Open")
 - Labels on buttons (for example, "click the OK button")
 - Instructions directing users to fill in fields (for example, "enter the account number")
 - Any other elements that users must read
- Prompts in command-line interfaces
- Output from the program
 - Responses to user input
 - Error messages
 - Text returned when exceptions are thrown
 - Other status messages (warnings, audit messages, and others)

After identifying each element of the application to be localized, application developers must assign a unique key to each element and provide a message catalog for each language to be supported. Each message catalog consists of keys and the corresponding language-specific strings. The key, therefore, is the link between the program and the message catalog; the program internally refers to localizable elements by key and uses the message catalog to generate the output seen by the user. Translated strings are generated by calling the format method on a `LocalizableTextFormatter` object, which represents a key and a resource bundle (a set of message catalogs). The locale setting of the program determines the message catalog in which to search for the key.

Creating message catalogs

After identifying each element to be localized, message catalogs must be created for each language to be supported. These catalogs, which are implemented as Java resource bundles, can be created in two ways, either as subclasses of the `ResourceBundle` class or as Java properties files. Resource bundles have a variety of uses in Java; for message catalogs, the properties-file approach is more common. If properties files are used, support for languages to be added or removed without modifying the application code, and catalogs can be prepared by people without programming expertise.

A message catalog implemented in a properties file consists of a line for each key, where a key identifies a localizable element. Each line in the file has the following structure:

```
key = String corresponding to the key
```

For example, a graphical user interface for a banking system can have a pull-down menu to be used for selecting a type of account, like savings or checking. The label for the pull-down menu and the account types on the menu are good choices for localization. There are three elements that require keys: the label for the account menu and the two items on the menu. If the keys are `accountString`, `savingsString`, and `checkingString`, the English properties file associates each with an English string.

Figure 92. Three elements in an English message catalog

```
accountString = Accounts
savingsString = Savings
checkingString = Checking
...
```

In the German properties files, each key is given a corresponding German value.

Figure 93. Three elements in a German message catalog

```
accountString = Konten
savingsString = Sparkonto
```

```
checkingString = Girokonto  
...
```

Properties files can be added for any other needed languages, as well.

Naming the properties files

To enable resolution to a specific properties file, Java specifies naming conventions for the properties files in a resource bundle: `resourceBundleName_localeID.properties`

Each file takes a fixed extension, `.properties`. The set of files making up the resource bundle is given a collective name; for a simple banking application, an obvious name, like `BankingResources`, suffices for the resource bundle. Each file is given the name of the resource bundle with a locale identifier; the specific value of the locale ID varies with the locale. These are used internally by the `Java.util.ResourceBundle` class to match files in a resource bundle to combinations of locale and time-zone settings. The details of the algorithm vary with the release of the JDK; see your Java documentation for information specific to your installation.

In the banking application, typical files in the `BankingResources` resource bundle include `BankingResources_en.properties` for the English message catalog and `BankingResources_de.properties` for the German catalog. Additionally, a default catalog, `BankingResources.properties`, is provided for use when the requested catalog cannot be found. The default catalog is often the English-language catalog.

Resource bundles containing message catalogs for use with localizable text need to be installed only on the systems where the formatting of strings is actually performed. The resource bundles are typically placed in an application's JAR file. See [WebSphere support](#) for more information.

Localization support in WebSphere and Java

The Java package `com.ibm.websphere.i18n.localizabletext` contains the classes and interfaces constituting the localizable-text package. This package makes extensive use of the internationalization and localization features of the Java language; programmers using the WebSphere localizable-text package must understand the underlying Java support, which are not documented in any detail here.

Java support

The WebSphere localizable-text package relies primarily on the following Java components:

- `java.util.Locale`
- `java.util.TimeZone`
- `java.util.ResourceBundle`
- `java.text.MessageFormat`

This list is not exhaustive. WebSphere and these Java classes can also use related Java classes, but the related classes--for example, `java.util.Calendar`--are typically special-purposes classes. This section briefly describes only the primary classes.

Locale

A `Locale` object in Java encapsulates a language and a geographic region, for example, the `java.util.Locale.US` object contains locale information for the United States. An application that specifies a locale can then take advantage of the locale-sensitive formatters built into the Java language. These formatters, in the `java.text` package, handle the presentation of numbers, currency values, dates, and times.

TimeZone

A `TimeZone` object in Java encapsulates a representation of the time and provides methods for tasks like reporting the time and accommodating seasonal time shifts. Applications use the time zone to determine the local date and time.

ResourceBundle

A resource bundle is a named collection of resources--information used by the application, for example, strings, fonts, and images--used by a specific locale. The `ResourceBundle` class allows an application to retrieve the named resource bundle appropriate to the locale. Resource bundles are used to hold the messages catalogs, as described in [Writing localizable programs](#). Resource bundles can be implemented in two ways, either as subclasses of the `ResourceBundle` class or as Java properties files.

MessageFormat

The `MessageFormat` class can be used to construct strings based on parameters. As a simple example, suppose a localized application represents a particular error condition with a numeric key. When the application reports the error condition, it uses a message formatter to convert the numeric key into a meaningful string. The message formatter constructs the output string by looking up the code (the parameter) in an appropriate resource bundle and retrieving the corresponding string from the message catalog. Additional parameters--for example, another key representing the program module--can also be used in assembling the output message.

WebSphere support

The WebSphere localizable-text package wraps the Java support and extends it for efficient and simple use in a distributed environment. The primary class used by application programmers is the `LocalizableTextFormatter` class. Objects of this class are created, typically in server programs, but clients can also create them. `LocalizableTextFormatter` objects are created for specific resource-bundle names and keys. Client programs that receive `LocalizableTextFormatter` objects call the object's `format` method. This method uses the locale of the client application to retrieve the appropriate resource bundle and assemble the locale-specific message based on the key.

For example, suppose that a WebSphere client-server application supports both French and English locales; the server is using an English locale and the client, a French locale. The server creates two resource bundles, one for English and one for French. When the client makes a request that triggers a message, the server creates a `LocalizableTextFormatter` object containing the name of the resource bundle and the key for the message, and passes the object back to the client.

When the client receives the `LocalizableTextFormatter` object, it calls the object's `format` method, which returns the message corresponding to the key from the French resource bundle. The `format` method retrieves the client's locale and, using the locale and name of the resource bundle, determines the resource bundle corresponding to the locale. (If the client has set an English locale, calling the `format` method results in the retrieval of an English message.) The formatting of the message is transparent to the client. In this simple client-server example, the resource bundles reside centrally with the server. The client machine does not have to install them. Part of what the WebSphere localizable-text package provides is the infrastructure to support centralized catalogs. WebSphere uses an enterprise bean, a stateless session bean provided with the localizable-text package, to access the message catalogs. When the client calls the `format` method on the `LocalizableTextFormatter` object, the following events occur internally:

1. The client application sets the time zone and locale values in the `LocalizableTextFormatter` object, either by passing them explicitly or through defaults.
2. A call, `LocalizableTextFormatterEJBFinder`, is made to retrieve a reference to the formatting enterprise bean.
3. Information from the `LocalizableTextFormatter` object, including the client's time zone and locale, is sent to the formatting bean.
4. The formatting bean uses the name of the resource bundle, the message key, the time zone, and the locale to assemble the language-specific message.
5. The enterprise bean returns the formatted message to the client.
6. The formatted message is inserted into the `LocalizableTextFormatter` object and returned by the `format` method.

A call to a `LocalizableTextFormatter.format` method requires at most one remote invocation, to contact the formatting enterprise bean. However, the `LocalizableTextFormatter` object can optionally cache formatted messages, eliminating the formatting call for subsequent uses. It also allows the application to set a fallback string; this means the application can still return a readable string even if it cannot access a message catalog to retrieve the language-specific string. Additionally, the resource bundles can be stored locally. The localizable-text package provides a static variable that indicates whether the bundles are stored locally (`LocalizableConfiguration.LOCAL`) or remotely (`LocalizableConfiguration.REMOTE`), but the setting of this variable applies to all applications running within a Java Virtual Machine (JVM).

The LocalizableTextFormatter class

The `LocalizableTextFormatter` class, found in the package `com.ibm.websphere.i18n.localizabletext`, is the primary programming interface for using the localizable-text package. Objects of this class contain the information needed to create language-specific strings from keys and resource bundles.

Location of message catalogs and the `ApplicationName` value

Applications written with the WebSphere localizable-text package can store message catalogs locally or remotely. In a distributed environment, the use of remote, centrally stored catalogs is appropriate. All applications can use the same catalogs, and administration and maintenance of the catalogs are simplified; each component does not need to store and maintain copies of the message catalogs. Local formatting is useful in test situations and appropriate under some circumstances. In order to support both local and remote formatting, a `LocalizableTextFormatter` object must indicate the name of the formatting application. For example, when an application formats a message by using remote, centrally stored catalogs, the message is actually formatted by a simple enterprise bean (see [WebSphere support](#) for more information). Although the localizable-text package contains the code to automate looking up the enterprise bean and issuing a call to it, the application needs to know the name of the formatting enterprise bean. Several methods in the `LocalizableTextFormatter` class use a value described as *application name*; this refers to the name of the formatting application, which is not necessarily the name of the application in which the value is set.

Caching messages

The `LocalizableTextFomatter` object can optionally cache formatted messages so that they do not have to be reformatted when needed again. By default, caching is not used, but the `LocalizableTextFormatter.setCacheSetting` method can be used to enable caching. When caching is enabled and the `LocalizableTextFormatter.format` method is called, the method determines whether the message has already been formatted. If so, the cached message is returned. If the message is not found in the cache, the message is formatted and returned to the caller, and a copy of the message is cached for future use.

If caching is disabled after messages have been cached, those messages remain in the cache until the cache is cleared by a call to the `LocalizableTextFormatter.clearCache` method. The cache can be cleared at any time. The cache within a `LocalizableTextFormatter` object is automatically cleared when any of the following methods are called on the object:

- `setResourceBundleName(String resourceBundleName)`
- `setPatternKey(String patternKey)`
- `setArguments(Object[] args)`
- `setApplicationName(String appName)`

Fallback information

Under some circumstances, it can be impossible to format a message. The localizable-text package implements a fallback strategy, making it possible to get some information even if a message cannot be correctly formatted into the desired language. The `LocalizableTextFomatter` object can optionally store a fallback value for a message string, the time zone, and the locale. These can be ignored unless the `LocalizableTextFormatter` object throws an exception.

Application-specific variables

The localizable-text package provides native support for localization based on time zone and locale, but application developers can construct messages on the basis of other values as well. The localizable-text package provides an illustrative class, `LocalizableTextDateTimeArgument`, which reports the date and time. The date and time information is localized by using the locale and time-zone values, but the class also uses additional variables to determine how the output is presented. The date and time information can be requested in a variety of styles, from the fully detailed to the terse. In this example, the construction of message strings is driven by three variables: the locale, the time zone, and the style. Applications can use any number of variables in addition to locale and time zone for constructing messages. See [Using optional arguments](#) for more information.

Writing a localizable application

To develop a WebSphere application that uses localizable text, application developers must do the following:

- Determine the parts of the application to be localized.
 - Identify the application elements to be localized and assign each a key.

- Create message catalogs for each language by associating a string with each key.

These tasks were described previously. See [Identifying localizable text](#) and [Creating message catalogs](#) for more information.

- Assemble language-specific strings from keys, resource bundles, and other arguments.
 - Create a `LocalizableTextFormatter` object.
 - Set the values within the object for the key, the name of the resource bundle, the name of the remote formatting application, and any optional arguments.
 - Call the `format` method on the `LocalizableTextObject`, which returns the assembled string.

This section describes these tasks.

Creating a `LocalizableTextFormatter` object

Server programs typically create `LocalizableTextFormatter` objects, which are sent to clients as the result of some operation; clients format the objects at the appropriate time. Less typically, clients can create `LocalizableTextFormatter` objects locally. To create a `LocalizableTextFormatter` object, applications use one of the constructors in the `LocalizableTextFormatter` class:

- `LocalizableTextFormatter()`
- `LocalizableTextFormatter(String resourceBundleName, String patternKey, String appName)`
- `LocalizableTextFormatter(String resourceBundleName, String patternKey, String appName, Object[] args)`

The `LocalizableTextFormatter` object must have values set for the name of the resource bundle, the key, the name of the formatting application, and for any optional values so the object can be formatted. The `LocalizableTextFormatter` object can be created and the values set in one step by using the constructor that takes the necessary arguments, or the object can be created and the values set in separate steps. Values are set by using methods on the `LocalizableTextFormatter` object; for setting the values manually, rather than by using a constructor, use these methods:

- `setResourceBundleName(String resourceBundleName)`
- `setPatternKey(String patternKey)`
- `setApplicationName(String appName)`
- `setArguments(Object[] args)`

Note:

When values in the array of optional arguments are set within a `LocalizableTextFormatter` object, they are copied into the object, not referenced. If an array variable holding a value is changed after the value has been copied into the `LocalizableTextFormatter` object, the value in the `LocalizableTextFormatter` object will not reflect the change unless it is also reset.

A `LocalizableTextFormatter` object also has methods that can be used to set values that cannot be set when the object is created, for example:

- To toggle the cache setting for the `LocalizableTextFormatter` object, use the `setCacheSetting(boolean setting)` method (See [Caching messages](#) for more information.)
- To clear the cache, use the `clearLocalizableTextFormatter` method
- To set fallback values, use these methods:
 - `setFallBackString`
 - `setFallBackLocale`
 - `setFallBackTimeZone`

(See [Fallback information](#) for more information.)

Each of these set methods also has a corresponding get method for retrieving the value. The `clearLocalizableTextFormatter` method unsets all values, returning the `LocalizableTextFormatter` object to a blank state. After clearing the object, reuse the object by setting new values and calling the `format` method again.

[Figure 94](#) creates a `LocalizableTextFormatter` object by using the default constructor and uses methods on the new object to set values for the key, name of the resource bundle, name of the formatting application, and fallback string on the object.

Figure 94. Code example: Creating a `LocalizableTextFormatter` object and setting values on it

```
import com.ibm.websphere.i18n.localizabletext.LocalizableException;
import com.ibm.websphere.i18n.localizabletext.LocalizableTextFormatter;
import java.util.Locale;
public void drawAccountNumberGUI(String accountType) {
    ...
    LocalizableTextFormatter ltf = new LocalizableTextFormatter();
    ltf.setPatternKey("accountNumber");
    ltf.setResourceBundleName("BankingSample.BankingResources");
    ltf.setApplicationName("BankingSample");
    ltf.setFallBackString("Enter account number: ");
    ...
}
```

Setting localization values

The application requesting a localized message can specify the locale and time zone for which the message is to be formatted, or the application can use the default values set for the JVM. For example, a graphical user interface can allow users to select the language in which to display the menus. A default value must be set, either in the environment or programmatically, so the menus can be generated when the application first starts, but users can then change the menu language to suit their needs. [Figure 95](#) illustrates how to change the locale used by the application based on the selection of a menu item.

Figure 95. Code example: Setting the locale programmatically

```
import java.awt.event.ActionListener;
import java.awt.event.ActionEvent;
...
import java.util.Locale;
public void actionPerformed(ActionEvent event) {
    String action = event.getActionCommand();
    ...
    if (action.equals("en_us")) {
        applicationLocale = new Locale("en", "US");
        ...
    }
    else if (action.equals("de_de")) {
        applicationLocale = new Locale("de", "DE");
        ...
    }
    else if (action.equals("fr_fr")) {
        applicationLocale = new Locale("fr", "FR");
        ...
    }
    ...
}
```

When an application calls a format method, it can specify no arguments, which causes the message to be formatted using the JVM's default values for locale and time zone, or a combination of locale and time zone can be specified to override the JVM's defaults. (See [Generating the localized text](#) for more information on the arguments to the format methods.)

Generating the localized text

After the `LocalizableTextFormatter` object has been created and the appropriate values set, the object can be formatted to generate the string appropriate to the locale and time zone. The format methods in the `LocalizableTextFormatter` class perform the work necessary to generate a string from a set of message keys and resource bundles, based on locale and time zone. The `LocalizableTextFormatter` class provides four format methods. Each format method returns the formatted

message string. The methods take a combination of `java.util.Locale` and `java.util.TimeZone` objects and throw `LocalizableException` objects:

- `String format();`
- `String format(locale);`
- `String format(timeZone);`
- `String format(locale, timeZone);`

The `format` method with no arguments uses the locale and time-zone values set as defaults for the JVM. The other format methods can be used to override either or both of these values.

[Figure 96](#) shows the creation of a localized string for the `LocalizableTextFormatter` object created in [Figure 94](#); formatting is based on the locale set in [Figure 95](#). If the formatting fails, the application retrieves and uses the fallback string instead of the localized string.

Figure 96. Code example: Formatting a LocalizableTextFormatter object

```
import com.ibm.websphere.i18n.localizabletext.LocalizableException;
import com.ibm.websphere.i18n.localizabletext.LocalizableTextFormatter;
import java.util.Locale;
public void drawAccountNumberGUI(String accountType) {
    ...
    LocalizableTextFormatter ltf = new LocalizableTextFormatter();
    ltf.setPatternKey("accountNumber");
    ltf.setResourceBundleName("BankingSample.BankingResources");
    ltf.setApplicationName("BankingSample");
    ltf.setFallBackString("Enter account number: ");
    try {
        msg = new Label(ltf.format(this.applicationLocale), Label.CENTER);
    }
    catch (LocalizableException le) {
        msg = new Label(ltf.getFallBackString(), Label.CENTER);
    }
    ...
}
```

Using optional arguments

The localizable-text package allows users to specify an array of optional arguments in a `LocalizableTextFormatter` object. These optional arguments can greatly enhance the kinds of localization done in WebSphere applications. This section describes two ways in which applications can use the optional arguments:

- To assemble and format complex strings with variable substrings
- To customize the formatting of strings, taking variables other than locale and time zone into account

Assembling complex strings

All of the keys discussed so far have represented flat strings; during localization, a string in the appropriate language is substituted for the key. The localizable-text package also supports substitution into the strings, which can include variables as placeholders. For example, an application that needs to report that an operation on a specified account was successful must provide a string like "The operation on account number was successful"; the variable number is to be replaced by the actual account number. Without support for creating strings with variable pieces, each possible string would need its own key, or the strings would have to be built phrase by phrase.

Both of these approaches quickly become intractable if a variable can take many values or if a string has several variable components. Instead, the localizable text package supports substitution of variables in strings with optional arguments. A string in a message catalog uses integers in braces--for example, {0} or {1}--to represent variable components. [Figure 97](#) shows an example from an English message catalog for a string with a single variable substitution. (The same key in message catalogs for other languages has a translation of this string with the variable in the appropriate location for the language.)

Figure 97. A message-catalog entry with a variable substring

successfulTransaction = The operation on account {0} was successful.

The values that are substituted into the string come from an array of optional arguments. One of the constructors for `LocalizableTextFormatter` objects takes an array of objects as an argument, and such an array of objects can be set within any `LocalizableTextFormatter` object. The array is used to hold values for variable parts of a string. When a format method is called on the object, the array is passed to the format method, which takes an element of the array and substitutes it into a placeholder with the matching index in the string. The value at index 0 in the array replaces the {0} variable in the string, the value at index 1 replaces {1}, and so forth.

Figure 98 shows the creation of a single-element argument array and the creation and use of a `LocalizableTextFormatter`. The element in the argument array is the account number entered by the user. The `LocalizableTextFormatter` is created by using a constructor that takes the array of optional arguments; this can also be set directly by using the `setArguments` method on the `LocalizableTextFormatter` object. Later in the code, the application calls the format method. The format method automatically substitutes values from the array of arguments into the string returned from the appropriate message catalog.

Figure 98. Code example: Formatting a message with a variable substring

```
public void updateAccount(String transactionType) {
    ...
    Object[] arg = { new String(this.accountNumber)};
    ...
    LocalizableTextFormatter successLTF =
        new LocalizableTextFormatter("BankingResources",
                                    "successfulTransaction",
                                    "BankingSample",
                                    arg);
    ...
    successLTF.format(this.applicationLocale);
    ...
}
```

Nesting LocalizableTextFormatter objects

The ability to substitute variables into the strings in message catalogs adds a level of flexibility to the localizable-text package, but the additional flexibility is limited, at least in an international environment, unless the substituted arguments themselves can be localized. For example, if an application needs to report that an operation on a specific account was successful, a string like "The operation on account number was successful"--where the only variable is an account number--can be translated and used in message catalogs for multiple languages. A string in which a variable is also a string, for example, "The type operation on account number was successful"--where the new type variable takes values like "deposit" and "withdrawal"--cannot be as easily translated. The values assumed by the type variable also need to be localized.

Figure 99 shows a message string in an English catalog with two variables, one of which will be localized, and the keys for two possible values. (The second variable in the string, the account number, is simply a number that must be substituted into the string; it does not need to be localized.)

Figure 99. A message-catalog entry with two variable substrings

```
sucessfulTransaction = The {0} operation on account {1} was successful.
depositOpString = deposit
withdrawOpString = withdrawal
```

To support localization of substrings, the localizable-text package allows the nesting of `LocalizableTextFormatter` objects. This is done simply by inserting a `LocalizableTextFormatter` object into the array of arguments for another `LocalizableTextFormatter`. When the format method does the variable substitution, it formats any `LocalizableTextFormatter` objects as it substitutes array elements for variables. This allows substrings to be formatted independently of the string in which they are embedded.

Figure 100 modifies the example in Figure 98 to format a message with a localizable substring. First, a `LocalizableTextFormatter` object for the localizable substring (referring to a deposit operation) is created. This object is

inserted, along with the account-number information, into the array of arguments. The array of arguments is then used in constructing the `LocalizableTextFormatter` object for the complete string; when the format method is called, the embedded `LocalizableTextFormatter` object is formatted to replace the first variable, and the account number is substituted for the second variable.

Figure 100. Code example: Formatting a message with a localizable variable substring

```
public void updateAccount(String transactionType) {
    ...
    // Successful Deposit.
    LocalizableTextFormatter opLTF =
        new LocalizableTextFormatter("BankingResources",
                                     "depositOpString", "BankingSample");
    Object[] args = {opLTF, new String(this.accountNumber)};
    LocalizableTextFormatter successLTF =
        new LocalizableTextFormatter("BankingResources",
                                     "successfulTransaction",
                                     "BankingSample",
                                     args);
    ...
    successLTF.format(this.applicationLocale);
    ...
}
```

Customizing the behavior of a format method

The array of optional arguments can contain simple values, like an account number to be substituted into a formatted string, and other `LocalizableTextFormatter` objects, representing localizable substrings to be substituted into a larger formatted string. These techniques are described in [Assembling complex strings](#). In addition, the optional-argument array can contain objects of user-defined classes.

User-defined classes used as optional arguments provide application-specific format methods, which programmers can use to perform localization on the basis of any number of values, not just locale and time zone. These user-defined classes need to be available only on the systems where they are constructed and inserted into `LocalizableTextFormatter` objects and where the actual formatting is done; client applications do not need to install these classes.

The localizable-text package provides an example of such a user-defined class in the `LocalizableTextDateTimeArgument` class. This class allows date and time information to be selectively formatted according to the style values defined in the `java.text.DateFormat` class and according to the constants defined by the `LocalizableTextDateTimeArgument` class.

The `DateFormat` styles determine how information is reported about a date. For example, when the `DateFormat.FULL` style is chosen, the twenty-second day of February in 2000 is represented in English as *Tuesday, February 22, 2000*. When the `DateFormat.SHORT` style is used, the same date is represented as *2/22/00*. The valid values are:

- `DateFormat.FULL`
- `DateFormat.LONG`
- `DateFormat.MEDIUM`
- `DateFormat.SHORT`
- `DateFormat.DEFAULT`

The `LocalizableTextDateTimeArgument` class defines constants that can be used to request only date or time information, or both, either in date-time order or in time-date order. The defined values are:

- `LocalizableTextDateTimeArgument.TIME`
- `LocalizableTextDateTimeArgument.DATE`
- `LocalizableTextDateTimeArgument.TIMEANDDATE`
- `LocalizableTextDateTimeArgument.DATEANDTIME`

An object of a user-defined class like the `LocalizableTextDateTimeArgument` class can be set in the optional-argument array of a `LocalizableTextFormatter` object, and when the `LocalizableTextFormatter` object attempts to format the

user-defined object, it calls the format method on that object. That format method, written by the application developer, can do whatever is appropriate with the application-specific values. In the case of the `LocalizableTextDateTimeArgument` class, the format method determines if date, time, or both are required, formats them according to the `DateFormat` value, and assembles them in the order requested in the `LocalizableTextDateTimeArgument` style. The date and time information are also affected by the locale and time-zone values, but the refinements in the formatting are accomplished by the `DateFormat` class and the user-defined values.

The string assembled from a user-defined class like the `LocalizableTextDateTimeArgument` class can then be substituted into a larger string, just as the return values of nested `LocalizableTextFormatter` objects can be. When writing such user-defined classes, it is helpful to think of them as specialized versions of the generic `LocalizableTextFormatter` class, and the way in which the `LocalizableTextFormatter` class is written provides a model for writing user-defined classes.

Structure of the LocalizableTextFormatter class

The `LocalizableTextFormatter` class is a general-purpose class for localizable text. It extends the `java.lang.Object` class and implements the `java.io.Serializable` interface and four localizable-text interfaces:

- LocalizableTextLTZ
- LocalizableTextL
- LocalizableTextTZ
- LocalizableText

Each of the localizable-text interfaces implemented by the `LocalizableTextFormatter` class implements the `Localizable` interface (which simply extends the `Serializable` interface) and defines a single `format` method:

- The `LocalizableTextLTZ` interface defines `format(locale, timezone)`.
- The `LocalizableTextL` defines `format(locale)`.
- The `LocalizableTextTZ` defines `format(timezone)`.
- The `LocalizableText` defines `format()`.

Because the `LocalizableTextFormatter` class implements all four of these interfaces, it must provide an implementation for each of these format methods.

Writing a user-defined class

A user-defined class must implement at least one of the localizable-text interfaces and its corresponding format method, as well as the Serializable interface. If the class implements more than one of the localizable-text interfaces and format methods, the order of evaluation of the interfaces is:

1. LocalizableTextLTZ
2. LocalizableTextL
3. LocalizableTextTZ
4. LocalizableText

For example, the `LocalizableTextDateTimeArgument` class implements only the `LocalizableTextLTZ` interface, as shown in [Figure 101](#).

Figure 101. Code example: The structure of the LocalizableTextDateTimeArgument class

[illegible]

A user-defined class must contain a constructor and an implementation of the format methods as defined in the localizable-text interfaces that the class implements. It can also contain other methods as needed. The `LocalizableTextDateTimeArgument` class contains a constructor, a single format method, an equality method, a hash-code generator, and a string-conversion method.

Figure 102. Code example: The methods in the `LocalizableTextDateTimeArgument` class

```
...
public class LocalizableTextDateTimeArgument implements LocalizableTextLTZ,
                                                         Serializable
{
    public final static int DATE = 1;
    public final static int TIME = 2;
    public final static int DATEANDTIME = 3;
    public final static int TIMEANDDATE = 4;
    private Date date = null;
    private dateTimeStyle = LocalizableTextDateTimeArgument.DATE;
    private int dateFormatStyle = DateFormat.FULL;
    ...
    public LocalizableTextDateTimeArgument(Date date, int dateTimeStyle,
                                           int dateFormatStyle)
    { ... }
    public boolean equals(Object param)
    { ... }
    public format (Locale locale, TimeZone timeZone)
        throws IllegalArgumentException
    { ... }

    public int hashCode()
    { ... }

    public String toString()
    { ... }
}
```

Each format method in the user-defined class can do whatever is appropriate for the application. In the `LocalizableTextDateTimeArgument` class, the format method (see [Figure 103](#) for the implementation) examines the setting of the date-time style set within the object, for example, `DATEANDTIME`. It then assembles the requested information in the requested order, according to the date-format value.

Figure 103. Code example: The format method in the `LocalizableTextDateTimeArgument` class

```
public format (Locale locale, TimeZone timeZone)
    throws IllegalArgumentException
{
    String returnString = null;

    switch(dateTimeStyle) {
        case LocalizableTextDateTimeArgument.DATE :
        {
            returnString = DateFormat.getDateInstance(dateFormatStyle,
                                                         locale).format(date);
            break;
        }
        case LocalizableTextDateTimeArgument.TIME :
        {
            df = DateFormat.getTimeInstance(dateFormatStyle, locale);
            df.setTimeZone(timeZone);
            returnString = df.format(date);
            break;
        }
        case LocalizableTextDateTimeArgument.DATEANDTIME :
```

```

    {
        dateString = DateFormat.getDateInstance(dateFormatStyle,
                                                  locale).format(date);
        df = DateFormat.getTimeInstance(dateFormatStyle, locale);
        df.setTimeZone(timeZone);
        timeString = df.format(date);
        returnString = dateString + " " + timeString;
        break;
    }
    case LocalizableTextDateTimeArgument.TIMEANDDATE :
    {
        dateString = DateFormat.getDateInstance(dateFormatStyle,
                                                  locale).format(date);
        df = DateFormat.getTimeInstance(dateFormatStyle, locale);
        df.setTimeZone(timeZone);
        returnString = timeString + " " + dateString;
        break;
    }
    default :
    {
        throw new IllegalArgumentException();
    }
}
return returnString;
}

```

An application can create a `LocalizableTextDateTimeArgument` object (or an object of any other user-defined class) and place it in the optional-argument array of a `LocalizableTextFormatter` object. When the `LocalizableTextFormatter` object reaches the user-defined object, it will attempt to format it by calling the object's `format` method. The returned string is then substituted for a variable as the `LocalizableTextFormatter` processes each element in the array of optional arguments.

Deploying the formatter enterprise bean

The **LocalizableTextEJBDeploy** tool is used by the application deployer to create a deployed `LocalizableText` JAR file for the `LocalizableText` service. You must deploy the enterprise bean for each server per application where the service is to be run. There may be servers for which the `LocalizableText` service does not need to be installed. The same deployed JAR file can be included in several application Enterprise Archive (EAR) files, but additional steps are required when the EAR file is deployed. The application deployer must also make sure that the application resource bundles are added to the application EAR file as files. The server's `CLASSPATH` variable must be adjusted to include the deployed location of the EAR file. This is so that the resource bundles can be located on the host and server.

Setting up the tool

Before the **LocalizableTextEJBDeploy** tool can be used, the following conditions must be met:

- A JAR file called `ltext.jar` must exist in the `lib` directory under the WebSphere installation directory.
- A working directory has to exist for the tool to use. The location is passed to the tool.

Using the LocalizableTextEJBDeploy Tool

After the prerequisites for the tool have been met, the tool can be used to deploy formatting session beans. The tool requires values for five arguments:

```

LocalizableTextEJBDeploy -a <appName>
                        -h <hostName>
                        -i <installationDir>
                        -s <serverName>
                        -w <workingDir>

```

The required arguments, which can be specified in any order, follow:

- **appName:** The name of the formatting session bean. This name is used in `LocalizableTextFormatter` objects to specify where the actual formatting takes place. If a `LocalizableTextFormatter` object specifies a name that cannot be resolved, an exception is thrown by the `format` method.
- **hostName:** The name of the machine on which the formatting session bean is deployed. This value specified here is case sensitive on all platforms.
- **installationDir:** The location at which WebSphere Application Server is installed on the machine.
- **serverName:** The name of the WebSphere Application Server. If this argument is not specified, the value `Default Server` is used.
- **workingDir:** The name of the working directory for the tool to use.

After the tool is run, a deployed JAR file is located in the working directory specified to the tool. This JAR file can be included in the application EAR or WAR file.

Special considerations when deploying a `LocalizableText` enterprise bean

When the application is being deployed onto a host and server, during the deployment process you will be asked if you want to regenerate the deployment code for the `LocalizableText` enterprise bean. Do not redeploy the bean. If the bean is redeployed, the JNDI name will be wrong.

If more than one `LocalizableText` enterprise bean is deployed with an application, there are two ways to handle the situation.

- Run the **`LocalizableTextEJBDeploy`** tool for each host/server combination. The tool generates a unique JNDI name for each enterprise bean. Otherwise, even though the bean has been deployed on multiple hosts and servers, the JNDI name is not changed, and there is only one entry in the naming service.
- During the deployment of the application, change the JNDI name for the localizable-text bean should begin with `com/ibm/websphere/i18n/localizabletext/homes/`. This should be followed by the application and host names, the server name, and by the string `LocalizableTextEJBHome`, all separated by two underscores, as follows:

```
<AppName>/<HostName>__<ServerName> __LocalizableTextEJBHome
```

More-advanced programming concepts for enterprise beans

This chapter discusses some of the more advanced programming concepts associated with developing and using enterprise beans. It includes information on developing entity beans with bean-managed persistence (BMP), writing the code required by a BMP bean to interact with a database, and developing session beans that directly participate in transactions.

Developing entity beans with BMP

In an entity bean with container-managed persistence (CMP), the container handles the interactions between the enterprise bean and the data source. In an entity bean with bean-managed persistence (BMP), the enterprise bean must contain all of the code required for the interactions between the enterprise bean and the data source. For this reason, developing an entity bean with CMP is simpler than developing an entity bean with BMP. However, you must use BMP if any of the following is true about an entity bean:

- The bean's persistent data is stored in more than one data source.
- The bean's persistent data is stored in a data source that is not supported by the EJB server that you are using.

This section examines the development of entity beans with BMP. For information on the tasks required to develop an entity bean with CMP, see [Developing entity beans with CMP](#).

Every entity bean must contain the following basic parts:

- The enterprise bean class. For more information, see [Writing the enterprise bean class \(entity with BMP\)](#).
- The enterprise bean's home interface. For more information, see [Writing the home interface \(entity with BMP\)](#).
- The enterprise bean's remote interface. For more information, see [Writing the remote interface \(entity with BMP\)](#).

In an entity bean with BMP, you can create your own primary key class or use an existing class for the primary key. For more information, see [Writing or selecting the primary key class \(entity with BMP\)](#).

Writing the enterprise bean class (entity with BMP)

In an entity bean with BMP, the bean class defines and implements the business methods of the enterprise bean, defines and implements the methods used to create instances of the enterprise bean, and implements the methods invoked by the container to move the bean through different stages in the bean's life cycle.

By convention, the enterprise bean class is named *NameBean*, where *Name* is the name you assign to the enterprise bean. The enterprise bean class for the example AccountBM enterprise bean is named AccountBMBean. Every entity bean class with BMP must meet the following requirements:

- It must be public, it must *not* be abstract, and it must implement the `javax.ejb.EntityBean` interface. For more information, see [Implementing the EntityBean interface](#).
- It must define instance variables that correspond to persistent data associated with the enterprise bean. For more information, see [Defining instance variables](#).
- It must implement the business methods used to access and manipulate the data associated with the enterprise bean. For more information, see [Implementing the business methods](#).
- It must contain code for getting connections to, interacting with, and releasing connections to the data source (or sources) used to store the persistent data. For more information, see [Using a database with a BMP entity bean](#).
- It must define and implement an `ejbCreate` method for each way in which the enterprise bean can be instantiated. It can, but is not required to, define and implement a corresponding `ejbPostCreate` method for each `ejbCreate` method. For more information, see [Implementing the ejbCreate and ejbPostCreate methods](#).
- It must implement the `ejbFindByPrimaryKey` method that takes a primary key and determines if it is valid and unique. It can also define and implement additional finder methods as required. For more information, see [Implementing the ejbFindByPrimaryKey and other ejbFind methods](#).

Note:

The enterprise bean class can implement the enterprise bean's remote interface, but this is not recommended. If the enterprise bean class implements the remote interface, it is possible to inadvertently pass the *this* variable as a method

argument.

Figure 42 shows the import statements and class declaration for the example AccountBM enterprise bean.

Figure 42. Code example: The AccountBMBean class

```
...
import java.rmi.RemoteException;
import java.util.*;
import javax.ejb.*;
import java.lang.*;
import java.sql.*;
import com.ibm.ejs.doc.account.InsufficientFundsException;
public class AccountBMBean implements EntityBean {
    ...
}
```

Defining instance variables

An entity bean class can contain both persistent and nonpersistent instance variables; however, static variables are not supported in enterprise beans unless they are also final (that is, they are constants). Persistent variables are stored in a database. Unlike the persistent variables in a CMP entity bean class, the persistent variables in a BMP entity bean class can be private.

Nonpersistent variables are *not* stored in a database and are temporary. Nonpersistent variables must be used with caution and must not be used to maintain the state of an EJB client between method invocations. This restriction is necessary because nonpersistent variables cannot be relied on to remain the same between method invocations outside of a transaction because other EJB clients can change these variables or they can be lost when the entity bean is passivated.

The AccountBMBean class contains three instance variables that represent persistent data associated with the AccountBM enterprise bean:

- *accountId*, which identifies the account ID associated with an account
- *type*, which identifies the account type as either savings (1) or checking (2)
- *balance*, which identifies the current balance of the account

The AccountBMBean class contains several nonpersistent instance variables including the following:

- *entityContext*, which identifies the entity context of each instance of an AccountBM enterprise bean. The entity context can be used to get a reference to the EJB object currently associated with the bean instance and to get the primary key object associated with that EJB object.
- *jdbcUrl*, which encapsulates the database universal resource locator (URL) used to connect to the data source. This variable must have the following format: *dbAPI:databaseType:databaseName*. For example, to specify a database named sample in an IBM DB2 database with the Java Database Connectivity (JDBC) API, the argument is *jdbc:db2:sample*.
- *driverName*, which encapsulates the database driver class required to connect to the database.
- *DBLogin*, which identifies the database user ID required to connect to the database.
- *DBPassword*, which identifies password for the specified user ID (*DBLogin*) required to connect to the database.
- *tableName*, which identifies the database table name in which the bean's persistent data is stored.
- *jdbcConn*, which encapsulates a Java Database Connectivity (JDBC) connection to a data source within a *java.sql.Connection* object.

Figure 43. Code example: The instance variables of the AccountBMBean class

```
...
public class AccountBMBean implements EntityBean {
    private EntityContext entityContext = null;
    ...
    private static final String DBURLProp = "DBURL";
    private static final String DriverNameProp = "DriverName";
    private static final String DBLoginProp = "DBLogin";
    private static final String DBPasswordProp = "DBPassword";
    private static final String TableNameProp = "TableName";
```

```

private String jdbcUrl, driverName, DBLogin, DBPassword, tableName;
private long accountId = 0;
private int type = 1;
private float balance = 0.0f;

private Connection jdbcConn = null;
...
}

```

To make the AccountBM bean more portable between databases and database drivers, the database-specific variables (*jdbcUrl*, *driverName*, *DBLogin*, *DBPassword*, and *tableName*) are set by retrieving corresponding environment variables contained in the enterprise bean. The values of these variables are retrieved by the `getEnvProps` method, which is implemented in the `AccountBMBean` class and invoked when the `setEntityContext` method is called. For more information, see [Managing database connections in the EJB server environment](#).

Although [Figure 43](#) shows database access compatible with version 1.0 of the JDBC specification, you can also perform database accesses that are compatible with version 2.0 of the JDBC specification. An administrator binds a `javax.sql.DataSource` reference (which encapsulates the information that was formerly stored in the `jdbcURL` and `driverName` variables) into the JNDI namespace. The entity bean with BMP does the following to get a `java.sql.Connection`:

```

DataSource ds = (DataSource)initialContext.lookup("java:comp/env/jdbc/MyDataSource");
Connection con = ds.getConnection();

```

where *MyDataSource* is the name the administrator assigned to the `datasource`.

Implementing the business methods

The business methods of an entity bean class define the ways in which the data encapsulated in the class can be manipulated. The business methods implemented in the enterprise bean class cannot be directly invoked by an EJB client. Instead, the EJB client invokes the corresponding methods defined in the enterprise bean's remote interface by using an EJB object associated with an instance of the enterprise bean, and the container invokes the corresponding methods in the instance of the enterprise bean.

Therefore, for every business method implemented in the enterprise bean class, a corresponding method must be defined in the enterprise bean's remote interface. The enterprise bean's remote interface is implemented by the container in the EJB object class when the enterprise bean is deployed.

There is no difference between the business methods defined in the `AccountBMBean` bean class and those defined in the CMP bean class `AccountBean` shown in [Figure 10](#).

Implementing the `ejbCreate` and `ejbPostCreate` methods

You must define and implement an `ejbCreate` method for each way in which you want a new instance of an enterprise bean to be created. For each `ejbCreate` method, you can also define a corresponding `ejbPostCreate` method. Each `ejbCreate` method must correspond to a `create` method in the EJB home interface.

Like the business methods of the bean class, the `ejbCreate` and `ejbPostCreate` methods cannot be invoked directly by the client. Instead, the client invokes the `create` method of the enterprise bean's home interface by using the EJB home object, and the container invokes the `ejbCreate` method followed by the `ejbPostCreate` method.

Unlike the method in an entity bean with CMP, the `ejbCreate` method in an entity bean with BMP must contain all of the code required to insert the bean's persistent data into the data source. This requirement means that the `ejbCreate` method must get a connection to the data source (if one is not already available to the bean instance) and insert the values of the bean's variables into the appropriate fields in the data source.

Each `ejbCreate` method in an entity bean with BMP must meet the following requirements:

- It must be public and return the bean's primary key class.
- Its arguments and return type must be valid for Java remote method invocation (RMI).
- It must contain the code required to insert the values of the persistent variables into the data source. For more information, see [Using a database with a BMP entity bean](#).

Each `ejbPostCreate` method must be public, return void, and have the same arguments as the matching `ejbCreate` method. If

necessary, both the `ejbCreate` method and the `ejbPostCreate` method can throw the `java.rmi.RemoteException` exception, the `javax.ejb.CreateException` exception, the `javax.ejb.DuplicateKeyException` exception, and any user-defined exceptions.

Figure 44 shows the two `ejbCreate` methods required by the example `AccountBMBean` bean class. No `ejbPostCreate` methods are required.

As in the `AccountBean` class, the first `ejbCreate` method calls the second `ejbCreate` method; the latter handles all of the interaction with the data source. The second method initializes the bean's instance variables and then ensures that it has a valid connection to the data source by invoking the `checkConnection` method. The method then creates, prepares, and executes an SQL INSERT call on the data source. If the INSERT call is executed correctly, and only one row is inserted into the data source, the method returns an object of the bean's primary key class.

Figure 44. Code example: The `ejbCreate` methods of the `AccountBMBean` class

```
public AccountBMKey ejbCreate(AccountBMKey key) throws CreateException,
    RemoteException {
    return ejbCreate(key, 1, 0.0f);
}
...
public AccountBMKey ejbCreate(AccountBMKey key, int type, float balance)
    throws CreateException, RemoteException
{
    accountId = key.accountId;
    this.type = type;
    this.balance = balance;
    checkConnection();
    // INSERT into database
    try {
        String sqlString = "INSERT INTO " + tableName +
            " (balance, type, accountid) VALUES (?, ?, ?)";
        PreparedStatement sqlStatement = jdbcConn.prepareStatement(sqlString);
        sqlStatement.setFloat(1, balance);
        sqlStatement.setInt(2, type);
        sqlStatement.setLong(3, accountId);
        // Execute query
        int updateResults = sqlStatement.executeUpdate();
        ...
    }
    catch (Exception e) { // Error occurred during insert
        ...
    }
    return key;
}
```

Implementing the `ejbFindByPrimaryKey` and other `ejbFind` methods

At a minimum, each entity bean with BMP must define and implement the `ejbFindByPrimaryKey` method that takes a primary key and determines if it is valid and unique for an instance of an enterprise bean; if the primary key is valid and unique, it returns the primary key. An entity bean can also define and implement other finder methods to find enterprise bean instances. All finder methods can throw the `javax.ejb.FinderException` exception to indicate an application-level error. Finder methods designed to find a single bean can also throw the `javax.ejb.ObjectNotFoundException` exception, a subclass of the `FinderException` class. Finder methods designed to return multiple beans should not use the `ObjectNotFoundException` to indicate that no suitable beans were found; instead, such methods should return empty return values. Throwing the `java.rmi.RemoteException` exception is deprecated; see [Standard application exceptions for entity beans](#) for more information.

Like the business methods of the bean class, the `ejbFind` methods cannot be invoked directly by the client. Instead, the client invokes a finder method on the enterprise bean's home interface by using the EJB home object, and the container invokes the corresponding `ejbFind` method. The container invokes an `ejbFind` method by using a generic instance of that entity bean in the pooled state.

Because the container uses an instance of an entity bean in the pooled state to invoke an `ejbFind` method, the method must do the following:

1. Get a connection to the data source (or sources).
2. Query the data source for records that match specifications of the finder method.
3. Drop the connection to the data source (or sources).

For more information on these data source tasks, see [Using a database with a BMP entity bean](#). Figure 45 shows the `ejbFindByPrimaryKey` method of the example `AccountBMBean` class. The `ejbFindByPrimaryKey` method gets a connection to its data source by calling the `makeConnection` method shown in Figure 45. It then creates and invokes an SQL SELECT statement on the data source by using the specified primary key.

If one and only one record is found, the method returns the primary key passed to it in the argument. If no records are found or multiple records are found, the method throws the `FinderException`. Before determining whether to return the primary key or throw the `FinderException`, the method drops its connection to the data source by calling the `dropConnection` method described in [Using a database with a BMP entity bean](#).

Figure 45. Code example: The `ejbFindByPrimaryKey` method of the `AccountBMBean` class

```
public AccountBMKey ejbFindByPrimaryKey (AccountBMKey key)
    throws FinderException {
    boolean wasFound = false;
    boolean foundMultiples = false;
    makeConnection();
    try {
        // SELECT from database
        String sqlString = "SELECT balance, type, accountid FROM " + tableName
            + " WHERE accountid = ?";
        PreparedStatement sqlStatement = jdbcConn.prepareStatement(sqlString);
        long keyValue = key.accountId;
        sqlStatement.setLong(1, keyValue);

        // Execute query
        ResultSet sqlResults = sqlStatement.executeQuery();

        // Advance cursor (there should be only one item)
        // wasFound will be true if there is one
        wasFound = sqlResults.next();

        // foundMultiples will be true if more than one is found.
        foundMultiples = sqlResults.next();
    }
    catch (Exception e) { // DB error
        ...
    }
    dropConnection();
    if (wasFound && !foundMultiples)
    {
        return key;
    }
    else
    {
        // Report finding no key or multiple keys
        ...
        throw(new FinderException(foundStatus));
    }
}
```

Figure 46 shows the `ejbFindLargeAccounts` method of the example `AccountBMBean` class. The `ejbFindLargeAccounts` method also gets a connection to its data source by calling the `makeConnection` method and drops the connection by using the `dropConnection` method. The SQL SELECT statement is also very similar to that used by the `ejbFindByPrimaryKey` method. (For more information on these data source tasks and methods, see [Using a database with a BMP entity bean](#).)

While the `ejbFindByPrimaryKey` method needs to return only one primary key, the `ejbFindLargeAccounts` method can be expected to return zero or more primary keys in an Enumeration object. To return an enumeration of primary keys, the

`ejbFindLargeAccounts` method does the following:

1. It uses a while loop to examine the result set (*sqlResults*) returned by the `executeQuery` method.
2. It inserts each primary key in the result set into a hash table named *resultTable* by wrapping the returned account ID in a Long object and then in an `AccountBMKey` object. (The Long object, *memberId*, is used as the hash table's index.)
3. It invokes the `elements` method on the hash table to obtain the enumeration of primary keys, which it then returns.

Figure 46. Code example: The `ejbFindLargeAccounts` method of the `AccountBMBean` class

```
public Enumeration ejbFindLargeAccounts(float amount) throws FinderException {
    makeConnection();
    Enumeration result;
    try {
        // SELECT from database
        String sqlString = "SELECT accountid FROM " + tableName
            + " WHERE balance >= ?";
        PreparedStatement sqlStatement = jdbcConn.prepareStatement(sqlString);
        sqlStatement.setFloat(1, amount);
        // Execute query
        ResultSet sqlResults = sqlStatement.executeQuery();
        // Set up Hashtable to contain list of primary keys
        Hashtable resultTable = new Hashtable();
        // Loop through result set until there are no more entries
        // Insert each primary key into the resultTable
        while(sqlResults.next() == true) {
            long acctId = sqlResults.getLong(1);
            Long memberId = new Long(acctId);
            AccountBMKey key = new AccountBMKey(acctId);
            resultTable.put(memberId, key);
        }
        // Return the resultTable as an Enumeration
        result = resultTable.elements();
        return result;
    } catch (Exception e) {
        ...
    } finally {
        dropConnection();
    }
}
```

Implementing the `EntityBean` interface

Each entity bean class must implement the methods inherited from the `javax.ejb.EntityBean` interface. The container invokes these methods to move the bean through different stages in the bean's life cycle. Unlike an entity bean with CMP, in an entity bean with BMP, these methods must contain all of the code for the required interaction with the data source (or sources) used by the bean to store its persistent data.

- `ejbActivate`--This method is invoked by the container when the container selects an entity bean instance from the instance pool and assigns that instance to a specific existing EJB object. This method must contain the code required to activate the enterprise bean instance by getting a connection to the data source and using the bean's `javax.ejb.EntityContext` class to obtain the primary key in the corresponding EJB object.

In the example `AccountBMBean` class, the `ejbActivate` method obtains the bean instance's account ID, sets the value of the *accountId* variable, and invokes the `checkConnection` method to ensure that it has a valid connection to the data source.

- `ejbLoad`--This method is invoked by the container to synchronize an entity bean's persistent variables with the corresponding data in the data source. (That is, the values of the fields in the data source are loaded into the persistent variables in the corresponding enterprise bean instance.) This method must contain the code required to load the values from the data source and assign those values to the bean's instance variables.

In the example `AccountBMBean` class, the `ejbLoad` method obtains the bean instance's account ID, sets the value of the *accountId* variable, invokes the `checkConnection` method to ensure that it has a valid connection to the data source, constructs and executes an SQL SELECT statement, and sets the values of the *type* and *balance* variables to match the

values retrieved from the data source.

- **ejbPassivate**--This method is invoked by the container to disassociate an entity bean instance from its EJB object and place the enterprise bean instance in the instance pool. This method must contain the code required to "passivate" or deactivate an enterprise bean instance. Usually, this passivation simply means dropping the connection to the data source.

In the example `AccountBMBean` class, the `ejbPassivate` method invokes the `dropConnection` method to drop the connection to the data source.

- **ejbRemove**--This method is invoked by the container when a client invokes the `remove` method inherited by the enterprise bean's home interface (from the `javax.ejb.EJBHome` interface) or remote interface (from the `javax.ejb.EJBObject` interface). This method must contain the code required to remove an enterprise bean's persistent data from the data source. This method can throw the `javax.ejb.RemoveException` exception if removal of an enterprise bean instance is not permitted. Usually, removal involves deleting the bean instance's data from the data source and then dropping the bean instance's connection to the data source.

In the example `AccountBMBean` class, the `ejbRemove` method invokes the `checkConnection` method to ensure that it has a valid connection to the data source, constructs and executes an SQL `DELETE` statement, and invokes the `dropConnection` method to drop the connection to the data source.

- **setEntityContext**--This method is invoked by the container to pass a reference to the `javax.ejb.EntityContext` interface to an enterprise bean instance. This method must contain any code required to store a reference to a context.

In the example `AccountBMBean` class, the `setEntityContext` method sets the value of the `entityContext` variable to the value passed to it by the container.

- **ejbStore**--This method is invoked by the container when the container needs to synchronize the data in the data source with the values of the persistent variables in an enterprise bean instance. (That is, the values of the variables in the enterprise bean instance are copied to the data source, overwriting the previous values.) This method must contain the code required to overwrite the data in the data source with the corresponding values in the enterprise bean instance.

In the example `AccountBMBean` class, the `ejbStore` method invokes the `checkConnection` method to ensure that it has a valid connection to the data source and constructs and executes an SQL `UPDATE` statement.

- **unsetEntityContext**--This method is invoked by the container, before an enterprise bean instance is removed, to free up any resources associated with the enterprise bean instance. This is the last method called prior to removing an enterprise bean instance.

In the example `AccountBMBean` class, the `unsetEntityContext` method sets the value of the `entityContext` variable to null.

Writing the home interface (entity with BMP)

An entity bean's home interface defines the methods used by EJB clients to create new instances of the bean, find and remove existing instances, and obtain metadata about an instance. The home interface is defined by the enterprise bean developer and implemented in the EJB home class created by the container during enterprise bean deployment. The container makes the home interface accessible to clients through the Java Naming and Directory Interface (JNDI).

By convention, the home interface is named *NameHome*, where *Name* is the name you assign to the enterprise bean. For example, the `AccountBM` enterprise bean's home interface is named `AccountBMHome`. Every home interface for an entity bean with BMP must meet the following requirements:

- It must extend the `javax.ejb.EJBHome` interface. The home interface inherits several methods from the `javax.ejb.EJBHome` interface. See [The javax.ejb.EJBHome interface](#) for information on these methods.
- Each method in the interface must be either a create method, which corresponds to an `ejbCreate` method (and possibly an `ejbPostCreate` method) in the enterprise bean class, or a finder method, which corresponds to an `ejbFind` method in the enterprise bean class. For more information, see [Defining create methods](#) and [Defining finder methods](#).
- The parameters and return value of each method defined in the home interface must be valid for Java RMI. For more information, see [The java.io.Serializable and java.rmi.Remote interfaces](#). In addition, each method's throws clause must include the `java.rmi.RemoteException` exception class.

Figure 47 shows the relevant parts of the definition of the home interface (`AccountBMHome`) for the example `AccountBM` bean. This interface defines two abstract create methods: the first creates an `AccountBM` object by using an associated `AccountBMKey` object, the second creates an `AccountBM` object by using an associated `AccountBMKey` object and

specifying an account type and an initial balance. The interface defines the required `findByPrimaryKey` method and the `findLargeAccounts` method.

Figure 47. Code example: The AccountBMHome home interface

```
...
import java.rmi.*;
import javax.ejb.*;
import java.util.*;
public interface AccountBMHome extends EJBHome {
    ...
    AccountBM create(AccountBMKey key) throws CreateException,
        RemoteException;
    ...
    AccountBM create(AccountBMKey key, int type, float amount)
        throws CreateException, RemoteException;
    ...
    AccountBM findByPrimaryKey(AccountBMKey key)
        throws FinderException, RemoteException;
    ...
    Enumeration findLargeAccounts(float amount)
        throws FinderException, RemoteException;
}
```

Defining create methods

A create method is used by a client to create an enterprise bean instance and insert the data associated with that instance into the data source. Each create method must be named `create` and it must have the same number and types of arguments as a corresponding `ejbCreate` method in the enterprise bean class. (The `ejbCreate` method can itself have a corresponding `ejbPostCreate` method.) The return types of the create method and its corresponding `ejbCreate` method are always different.

Each create method must meet the following requirements:

- It must be named `create`.
- It must return the type of the enterprise bean's remote interface. For example, the return type for the create methods in the `AccountBMHome` interface is `AccountBM` (as shown in [Figure 13](#)).
- It must have a throws clause that includes the `java.rmi.RemoteException` exception, the `javax.ejb.CreateException` exception, and all of the exceptions defined in the throws clause of the corresponding `ejbCreate` and `ejbPostCreate` methods.

Defining finder methods

A finder method is used to find one or more existing entity EJB objects. Each finder method must be named `findName`, where *Name* further describes the finder method's purpose.

At a minimum, each home interface must define the `findByPrimaryKey` method that enables a client to locate an EJB object by using the primary key only. The `findByPrimaryKey` method has one argument, an object of the bean's primary key class, and returns the type of the bean's remote interface.

Every other finder method must meet the following requirements:

- It must return the type of the enterprise bean's remote interface, the `java.util.Enumeration` interface, or the `java.util.Collection` interface (when a finder method can return more than one EJB object or an EJB collection).
- It must have a throws clause that includes the `java.rmi.RemoteException` and `javax.ejb.FinderException` exception classes.

Although every entity bean must contain only the default finder method, you can write additional ones if needed. For example, the `AccountBM` bean's home interface defines the `findLargeAccounts` method to find objects that encapsulate accounts with balances of more than a specified dollar amount, as shown in [Figure 47](#). Because this finder method can be expected to return a reference to more than one EJB object, its return type is `java.util.Enumeration`.

Unlike the implementation in an entity bean with CMP, in an entity bean with BMP, the bean developer must fully implement the `ejbFindByPrimaryKey` method that corresponds to the `findByPrimaryKey` method. In addition, the bean developer must

write each additional `ejbFind` method corresponding to the finder methods defined in the home interface. The implementation of the `ejbFind` methods in the `AccountBMBean` class is discussed in [Implementing the `ejbFindByPrimaryKey` and other `ejbFind` methods](#).

Writing the remote interface (entity with BMP)

An entity bean's remote interface provides access to the business methods available in the bean class. It also provides methods to remove an EJB object associated with a bean instance and to obtain the bean instance's home interface, object handle, and primary key. The remote interface is defined by the EJB developer and implemented in the EJB object class created by the container during enterprise bean deployment.

By convention, the remote interface is named *Name*, where *Name* is the name you assign to the enterprise bean. For example, the `AccountBM` enterprise bean's remote interface is named `AccountBM`. Every remote interface must meet the following requirements:

- It must extend the `javax.ejb.EJBObject` interface. The remote interface inherits several methods from the `javax.ejb.EJBObject` interface. See [Methods inherited from `javax.ejb.EJBObject`](#) for information on these methods.
- It must define a corresponding business method for every business method implemented in the enterprise bean class.
- The parameters and return value of each method defined in the interface must be valid for Java RMI. For more information, see [The `java.io.Serializable` and `java.rmi.Remote` interfaces](#).
- Each method's throws clause must include the `java.rmi.RemoteException` exception class.

[Figure 48](#) shows the relevant parts of the definition of the remote interface (`AccountBM`) for the example `AccountBM` enterprise bean. This interface defines four methods for displaying and manipulating the account balance that exactly match the business methods implemented in the `AccountBMBean` class. All of the business methods throw the `java.rmi.RemoteException` exception class. In addition, the subtract method must throw the user-defined exception `com.ibm.ejs.doc.account.InsufficientFundsException` because the corresponding method in the bean class throws this exception. Furthermore, any client that calls this method must either handle the exception or pass it on by throwing it.

Figure 48. Code example: The `AccountBM` remote interface

```
...
import java.rmi.*;
import javax.ejb.*;
import com.ibm.ejs.doc.account.InsufficientFundsException;
public interface AccountBM extends EJBObject {
    ...
    float add(float amount) throws RemoteException;
    ...
    float getBalance() throws RemoteException;
    ...
    void setBalance(float amount) throws RemoteException;
    ...
    float subtract(float amount) throws InsufficientFundsException,
        RemoteException;
}
```

Writing or selecting the primary key class (entity with BMP)

Every entity EJB object has a unique identity within a container that is defined by a combination of the object's home interface name and its primary key, the latter of which is assigned to the object at creation. If two EJB objects have the same identity, they are considered identical.

The primary key class is used to encapsulate an EJB object's primary key. In an entity bean (with BMP or CMP), you can write a distinct primary key class or you can use an existing class as the primary key class, as long as that class is serializable. For more information, see [The `java.io.Serializable` and `java.rmi.Remote` interfaces](#).

The example `AccountBM` bean uses a primary key class that is identical to the `AccountKey` class contained in the `Account` bean shown in [Figure 16](#), with the exception that the key class is named `AccountBMKey`.

Note:

The primary key class of an entity bean with BMP must implement the hashCode and equals method. In addition, the variables that make up the primary key must be public.

The java.lang.Long class is also a good candidate for a primary key class for the AccountBM bean.

Using a database with a BMP entity bean

In an entity bean with BMP, each ejbFind method and all of the life cycle methods (ejbActivate, ejbCreate, ejbLoad, ejbPassivate, and ejbStore) must interact with the data source (or sources) used by the bean to maintain its persistent data. To interact with a supported database, the BMP entity bean must contain the code to manage database connections and to manipulate the data in the database. The EJB server uses a set of specialized beans to encapsulate information about databases and an IBM-specific interface to JDBC to allow entity bean interaction with a connection manager. For more information, see [Managing database connections in the EJB server environment](#)

In general, there are three approaches to getting and releasing connections to databases:

- The bean can get a database connection in the setEntityContext method and release it in the unsetEntityContext method. This approach is the easiest for the enterprise bean developer to implement. However, without a connection manager, this approach is not viable because under it bean instances hold onto database connections even when they are not in use (that is, when the bean instance is passivated). Even with a connection manager, this approach does not scale well.
- The bean can get a database connection in the ejbActivate and ejbCreate methods, get and release a database connection in each ejbFind method, and release the database connection in the ejbPassivate and ejbRemove methods. This approach is somewhat more difficult to implement, but it ensures that only those bean instances that are activated have connections to the database.
- The bean can get and release a database connection in each method that requires a connection: ejbActivate, ejbCreate, ejbFind, ejbLoad, and ejbStore. This approach is more difficult to implement than the first approach, but is no more difficult than the second approach. This approach is the most efficient in terms of connection use and also the most scalable.

The example AccountBM bean, uses the second approach described in the preceding text. The AccountBMBean class contains two methods for making a connection to the DB2 database, checkConnection and makeConnection, and one method to drop connections: dropConnection. The code required to make the AccountBM bean work with the connection manager is shown in [Managing database connections in the EJB server environment](#)

The code required to manipulate data in a database is described in [Manipulating data in a database](#).

Managing database connections in the EJB server environment

In the EJB server environment, the administrator creates a specialized set of entity beans that encapsulate information about the database and the database driver. These specialized entity beans are created by using the WebSphere Administrative Console.

An entity bean that requires access to a database must use JNDI to create a reference to an EJB object associated with the right database bean instance. The entity bean can then use the IBM-specific interface (named com.ibm.db2.jdbc.app.stdebt.java.sql.DataSource) to get and release connections to the database.

The DataSource interface enables the entity bean to transparently interact with the connection manager of the EJB server. The connection manager creates a pool of database connections, which are allocated and deallocated to individual entity beans as needed.

Getting an EJB object reference to a data source bean instance

Before a BMP entity bean can get a connection to a database, the entity bean must perform a JNDI lookup on the data source entity bean associated with the database used to store the BMP entity bean's persistent data. [Figure 49](#) shows the code required to create an InitialContext object and then get an EJB object reference to a database bean instance. The JNDI name of the database bean is defined by the administrator; it is recommended that the JNDI naming convention be followed when defining this name. The value of the required database-specific variables are obtained by the getEnvProps method, which accesses the corresponding environment variables from the deployed enterprise bean.

Because the connection manager creates and drops the actual database connections and simply allocates and deallocates these

connections as required, there is no need for the BMP entity bean to load and register the database driver. Therefore, there is no need to define the *driverName* and *jdbcUrl* variables discussed in [Defining instance variables](#).

Figure 49. Code example: Getting an EJB object reference to a data source bean instance in the `setEntityContext` method (rewritten to use `DataSource`)

```
...
# import com.ibm.db2.jdbc.app.stdext.javax.sql.DataSource;
# import javax.naming.*;
...
InitialContext initContext = null;
DataSource ds = null;
...
public void setEntityContext(EntityContext ctx)
    throws EJBException {
    entityContext = ctx;
    try {
        getEnvProps();
        ds = initContext.lookup("jdbc/sample");
    } catch (NamingException e) {
        ...
    }
}
...
```

Allocating and deallocating a connection to a database

After creating an EJB object reference for the appropriate database bean instance, that object reference is used to get and release connections to the corresponding database. Unlike when using the `DriverManager` interface, when using the `DataSource` interface, the BMP entity bean does not really create and close data connections; instead, the connection manager allocates and deallocates connections as required by the entity bean. Nevertheless, a BMP entity bean must still contain code to send allocation and deallocation requests to the connection manager.

In the `AccountBMBean` class, the `checkConnection` method is called within other bean class methods that require a database connection, but for which it can be assumed that a connection already exists. This method checks to make sure that the connection is still available by checking if the *jdbcConn* variable is set to null. If the variable is null, the `makeConnection` method is invoked to get the connection (that is a connection allocation request is sent to the connection manager).

The `makeConnection` method is invoked when a database connection is required. It invokes the `getConnection` method on the data source object. The `getConnection` method is overloaded: it can take either a user ID and password or no arguments, in which case the user ID and password are implicitly set to null (this version is used in [Figure 50](#)).

Figure 50. Code example: The `checkConnection` and `makeConnection` methods of the `AccountBMBean` class (rewritten to use `DataSource`)

```
private void checkConnection() throws EJBException {
    if (jdbcConn == null) {
        makeConnection();
    }
    return;
}
...
private void makeConnection() throws EJBException {
    ...
    try {
        // Open database connection
        jdbcConn = ds.getConnection();
    } catch (Exception e) { // Could not get database connection
        ...
    }
}
```

Entity beans with BMP must also release database connections when a particular bean instance no longer requires it (that is, they must send a deallocation request to the connection manager). The `AccountBMBean` class contains a `dropConnection`

method to handle this task. To release the database connection, the `dropConnection` method does the following (as shown in [Figure 51](#)):

1. Invokes the `close` method on the connection object to tell the connection manager that the connection is no longer needed.
2. Sets the connection object reference to null.

Putting the `close` method inside a `try/catch/finally` block ensures that the connection object reference is always set to null even if the `close` method fails for some reason. Nothing is done in the `catch` block because the connection manager must clean up idle connections; this is not the job of the enterprise bean code.

Figure 51. Code example: The `dropConnection` method of the `AccountBMBean` class (rewritten to use `DataSource`)

```
private void dropConnection() {
    try {
        // Close the connection
        jdbcConn.close();
    } catch (SQLException ex) {
        // Do nothing
    } finally {
        jdbcConn = null;
    }
}
```

Manipulating data in a database

After an instance of a BMP entity bean obtains a connection to its database, it can read and write data. The `AccountBMBean` class communicates with the DB2 database by constructing and executing Java Structured Query Language (JSQL) calls by using the `java.sql.PreparedStatement` interface.

As shown in [Figure 52](#), the SQL call is created as a `String` (`sqlString`). The `String` variable is passed to the `java.sql.Connection.prepareStatement` method; and the values of each variable in the SQL call are set by using the various setter methods of the `PreparedStatement` class. (The variables are substituted for the question marks in the `sqlString` variable.) Invoking the `PreparedStatement.executeUpdate` method executes the SQL call.

Figure 52. Code example: Constructing and executing an SQL update call in an `ejbCreate` method

```
private void ejbCreate(AccountBMKey key, int type, float initialBalance)
    throws CreateException, EJBException {
    // Initialize persistent variables and check for good DB connection
    ...
    // INSERT into database
    try {
        String sqlString = "INSERT INTO " + tableName +
            " (balance, type, accountid) VALUES (?, ?, ?)";
        PreparedStatement sqlStatement = jdbcConn.prepareStatement(sqlString);
        sqlStatement.setFloat(1, balance);
        sqlStatement.setInt(2, type);
        sqlStatement.setLong(3, accountId);
        // Execute query
        int updateResults = sqlStatement.executeUpdate();
        ...
    }
    catch (Exception e) { // Error occurred during insert
        ...
    }
    ...
}
```

The `executeUpdate` method is called to insert or update data in a database; the `executeQuery` method is called to get data from a database. When data is retrieved from a database, the `executeQuery` method returns a `java.sql.ResultSet` object, which must be examined and manipulated using the methods of that class.

Note:

To improve scalability and performance, you do not need to call `PreparedStatement` for each database update. Instead, you can cache the results of the first `PreparedStatement` call.

[Figure 53](#) provides an example of how the data in a `ResultSet` is manipulated in the `ejbLoad` method of the `AccountBMBean` class.

Figure 53. Code example: Manipulating a `ResultSet` object in the `ejbLoad` method

```
public void ejbLoad () throws EJBException {
    // Get data from database
    try {
        // SELECT from database
        ...
        // Execute query
        ResultSet sqlResults = sqlStatement.executeQuery();
        // Advance cursor (there should be only one item)
        sqlResults.next();
        // Pull out results
        balance = sqlResults.getFloat(1);
        type = sqlResults.getInt(2);
    } catch (Exception e) {
        // Something happened while loading data.
        ...
    }
}
```

Using bean-managed transactions

In most situations, an enterprise bean can depend on the container to manage transactions within the bean. In these situations, all you need to do is set the appropriate transactional properties in the deployment descriptor as described in [Enabling transactions and security in enterprise beans](#).

Under certain circumstances, however, it can be necessary to have an enterprise bean participate directly in transactions. By setting the *transaction* attribute in an enterprise bean's deployment descriptor to `BeanManaged`, you indicate to the container that the bean is an active participant in transactions.

Note:

The value `BeanManaged` is not a valid value for the *transaction* deployment descriptor attribute in entity beans. In other words, entity beans cannot manage transactions.

When writing the code required by an enterprise bean to manage its own transactions, remember the following basic rules:

- An instance of a stateless session bean *cannot* reuse the same transaction context across multiple methods called by an EJB client. Therefore, it is recommended that the transaction context be a local variable to each method that requires a transaction context.
- An instance of a stateful session bean can reuse the same transaction context across multiple methods called by an EJB client. Therefore, make the transaction context an instance variable or a local method variable at your discretion. (When a transaction spans multiple methods, you can use the `javax.ejb.SessionSynchronization` interface to synchronize the conversational state with the transaction.)

[Figure 54](#) shows the standard code required to obtain an object encapsulating the transaction context. There are three basic steps involved:

1. The enterprise bean class must set the value of the `javax.ejb.SessionContext` object reference in the `setSessionContext` method.
2. A `javax.transaction.UserTransaction` object is created by calling the `getUserTransaction` method on the `SessionContext` object reference.
3. The `UserTransaction` object is used to participate in the transaction by calling transaction methods such as `begin` and `commit` as needed. If an enterprise bean begins a transaction, it must also complete that transaction either by invoking the `commit` method or the `rollback` method.

Note:

In both EJB servers, the `getUserTransaction` method of the `javax.ejb.EJBContext` interface (which is inherited

by the SessionContext interface) returns an object of type javax.transaction.UserTransaction rather than type javax.jts.UserTransaction. While this is a deviation from the 1.0 version of the EJB Specification, the 1.1 version of the EJB Specification requires that the getUserTransaction method return an object of type javax.transaction.UserTransaction and drops the requirement to return objects of type javax.jts.UserTransaction.

Figure 54. Code example: Getting an object that encapsulates a transaction context

```
...
import javax.transaction.*;
...
public class MyStatelessSessionBean implements SessionBean {
    private SessionContext mySessionCtx = null;
    ...
    public void setSessionContext(SessionContext ctx) throws EJBException {
        mySessionCtx = ctx;
    }
    ...
    public float doSomething(long arg1) throws FinderException, EJBException {
        UserTransaction userTran = mySessionCtx.getUserTransaction();
        ...
        // User userTran object to call transaction methods
        userTran.begin();
        // Do transactional work
        ...
        userTran.commit();
        ...
    }
    ...
}
```

The following methods are available with the UserTransaction interface:

- begin--Begins a transaction. This method takes no arguments and returns void.
- commit--Attempts to commit a transaction; assuming that nothing causes the transaction to be rolled back, successful completion of this method commits the transaction. This method takes no arguments and returns void.
- getStatus--Returns the status of the referenced transaction. This method takes no arguments and returns int; if no transaction is associated with the reference, STATUS_NO_TRANSACTION is returned. The following are the valid return values for this method:
 - STATUS_ACTIVE--Indicates that transaction processing is still in progress.
 - STATUS_COMMITTED--Indicates that a transaction has been committed and the effects of the transaction have been made permanent.
 - STATUS_COMMITTING--Indicates that a transaction is in the process of committing (that is, the transaction has started committing but has not completed the process).
 - STATUS_MARKED_ROLLBACK--Indicates that a transaction is marked to be rolled back.
 - STATUS_NO_TRANSACTION--Indicates that a transaction does not exist in the current transaction context.
 - STATUS_PREPARED--Indicates that a transaction has been prepared but not completed.
 - STATUS_PREPARING--Indicates that a transaction is in the process of preparing (that is, the transaction has started preparing but has not completed the process).
 - STATUS_ROLLEDBACK--Indicates that a transaction has been rolled back.
 - STATUS_ROLLING_BACK--Indicates that a transaction is in the process of rolling back (that is, the transaction has started rolling back but has not completed the process).
 - STATUS_UNKNOWN--Indicates that the status of a transaction is unknown.
- rollback--Rolls back the referenced transaction. This method takes no arguments and returns void.
- setRollbackOnly--Specifies that the only possible outcome of the transaction is rollback. This method takes no arguments and returns void.
- setTransactionTimeout--Sets the timeout (in seconds) associated with the transaction. If some transaction participant has not specifically set this value, a default timeout is used. This method takes a number of seconds (as type int) and returns void.

Enabling transactions and security in enterprise beans

This chapter examines how to enable transactions and security in enterprise beans by setting the appropriate deployment descriptor attributes:

- For transactions, a session bean can either use container-managed transactions or implement bean-managed transactions; entity beans must use container-managed transactions. To enable container-managed transactions, you must set the transaction attribute to any value *except* BeanManaged and set the transaction isolation level attribute. To enable bean-managed transactions, you must set the transaction attribute to BeanManaged and set the transaction isolation level attribute. For more information, see [Setting transactional attributes in the deployment descriptor](#).

If you want a session bean to manage its own transactions, you must write the code that explicitly demarcates the boundaries of a transaction as described in [Using bean-managed transactions](#).

If you want an EJB client to manage its own transactions, you must explicitly code that client to do so as described in [Managing transactions in an EJB client](#).

- For security, the *run-as mode* attribute is used by the EJB server environments. For information on the valid values of this attribute, see [Setting the security attribute in the deployment descriptor](#).

These attributes, like the other deployment descriptor attributes, are set by using one of the tools available. For more information, see [Tools for developing and deploying enterprise beans](#).

Setting transactional attributes in the deployment descriptor

The EJB Specification describes the creation of applications that enforce transactional consistency on the data manipulated by the enterprise beans. However, unlike other specifications that support distributed transactions, the EJB specification does not require enterprise bean and EJB client developers to write any special code to use transactions. Instead, the container manages transactions based on two deployment descriptor attributes associated with the EJB module, and the enterprise bean and EJB application developers are freed to deal with the business logic of their applications.

Enterprise bean developers can specifically design enterprise beans and EJB applications that explicitly manage transactions. For more information, see [Using bean-managed transactions](#).

Under most conditions, transaction management can be handled within the enterprise beans, freeing the EJB client developer of this task. However, EJB clients can participate in transactions if required or desired. For more information, see [Managing transactions in an EJB client](#).

Two attributes determine the way in which an enterprise bean is managed from a transactional perspective:

- The *transaction* attribute defines the transactional manner in which the container invokes a method. This attribute is part of the standard deployment descriptor. [Setting the transaction attribute](#) defines the valid values of this attribute and explains their meanings.
- The *transaction isolation level* attribute defines the manner in which transactions are isolated from each other by the container. This attribute is an extension to the standard deployment descriptor. [Setting the transaction isolation level attribute](#) defines the valid values of this attribute and explains their meanings.

Setting the transaction attribute

The transaction attribute defines the transactional manner in which the container invokes enterprise bean methods. This attribute is set for individual methods in a bean. The following are valid values for this attribute in decreasing order of transactional strictness:

BeanManaged

Notifies the container that the bean class directly handles transaction demarcation. This attribute value can be specified only for session beans and it cannot be specified for individual bean methods. For more information on designing session beans to implement this attribute value, see [Using bean-managed transactions](#).

Mandatory

Directs the container to always invoke the bean method within the transaction context associated with the client. If the client attempts to invoke the bean method without a transaction context, the container throws the `javax.jts.TransactionRequiredException` exception to the client. The transaction context is passed to any EJB object or resource accessed by an enterprise bean method.

EJB clients that access these entity beans must do so within an existing transaction. For other enterprise beans, the enterprise bean or bean method must implement the `BeanManaged` value or use the `Required` or `RequiresNew` value. For non-enterprise bean EJB clients, the client must invoke a transaction by using the `javax.transaction.UserTransaction` interface, as described in [Managing transactions in an EJB client](#).

Required

Directs the container to invoke the bean method within a transaction context. If a client invokes a bean method from within a transaction context, the container invokes the bean method within the client transaction context. If a client invokes a bean method outside of a transaction context, the container creates a new transaction context and invokes the bean method from within that context. The transaction context is passed to any enterprise bean objects or resources that are used by this bean method.

RequiresNew

Directs the container to always invoke the bean method within a new transaction context, regardless of whether the client invokes the method within or outside of a transaction context. The transaction context is passed to any enterprise bean objects or resources that are used by this bean method.

Supports

Directs the container to invoke the bean method within a transaction context if the client invokes the bean method within a transaction. If the client invokes the bean method without a transaction context, the container invokes the bean method without a transaction context. The transaction context is passed to any enterprise bean objects or resources that are used by this bean method.

NotSupported

Directs the container to invoke bean methods without a transaction context. If a client invokes a bean method from within a transaction context, the container suspends the association between the transaction and the current thread before invoking the method on the enterprise bean instance. The container then resumes the suspended association when the method invocation returns. The suspended transaction context is *not* passed to any enterprise bean objects or resources that are used by this bean method.

Never

Directs the container to invoke bean methods without a transaction context.

- If the client invokes a bean method from within a transaction context, the container throws the `java.rmi.RemoteException` exception.
- If the client invokes a bean method from outside a transaction context, the container behaves in the same way as if the `NotSupported` transaction attribute was set. The client must call the method without a transaction context.

Table 1. Effect of the enterprise bean's transaction attribute on the transaction context

Transaction attribute	Client transaction context	Bean transaction context
Mandatory	No transaction	Not allowed
	Client transaction	Client transaction
RequiresNew	No transaction	New transaction
	Client transaction	New transaction
Required	No transaction	New transaction
	Client transaction	Client transaction
Supports	No transaction	No transaction
	Client transaction	Client transaction
NotSupported	No transaction	No transaction
	Client transaction	No transaction
Never	No transaction	No transaction
	No transaction	No transaction

When setting the deployment descriptor for an entity bean, you can mark getter methods as "Read-Only" methods to improve performance. If a transaction unit of work includes no methods other than "Read-Only" designated methods, then the entity bean state synchronization does not invoke store.

Setting the transaction isolation level attribute

The transaction isolation level determines how strongly one transaction is isolated from another. This attribute is set for individual methods in a bean. However, within a transactional context, the isolation level associated with the first method invocation becomes the required isolation level for all other methods invoked within that transaction. If a method is invoked with a different isolation level from that of the first method, the `java.rmi.RemoteException` exception is thrown.

The following are valid values for this attribute, in decreasing order of isolation:

Serializable

This level prohibits all of the following types of reads:

- *Dirty reads*, where a transaction reads a database row containing uncommitted changes from a second transaction.
- *Nonrepeatable reads*, where one transaction reads a row, a second transaction changes the same row, and the first transaction rereads the row and gets a different value.
- *Phantom reads*, where one transaction reads all rows that satisfy an SQL WHERE condition, a second transaction inserts a row that also satisfies the WHERE condition, and the first transaction applies the same WHERE condition and gets the row inserted by the second transaction.

RepeatableRead

This level prohibits dirty reads and nonrepeatable reads, but it allows phantom reads.

ReadCommitted

This level prohibits dirty reads, but allows nonrepeatable reads and phantom reads.

ReadUncommitted

This level allows dirty reads, nonrepeatable reads, and phantom reads.

These isolation levels correspond to the isolation levels defined in the Java Database Connectivity (JDBC)

java.sql.Connection interface.

The container uses the transaction isolation level attribute as follows:

- Session beans and entity beans with bean-managed persistence (BMP)--For each database connection used by the bean, the container sets the transaction isolation level at the start of each transaction.
- Entity beans with container-managed persistence (CMP)--The container generates database access code that implements the specified isolation level.

None of these values permits two transactions to update the same data concurrently; one transaction must end before another can update the same data. These values determine only how locks are managed for reading data. However, risks to consistency can arise from read operations when a transaction does further work based on the values read. For example, if one transaction is updating a piece of data and a second transaction is permitted to read that data after it has been changed but before the updating transaction ends, the reading transaction can make a decision based on a change that is eventually rolled back. The second transaction risks making a decision on transient data.

Deciding which isolation level to use depends on several factors:

- The acceptable level of risk to data consistency
- The acceptable levels of concurrency and performance
- The isolation levels supported by the underlying database

The first two factors, risk to consistency and level of concurrency, are related. Decreasing the risk to consistency requires you to decrease concurrency because reducing the risk to consistency requires holding locks longer. The longer a lock is held on a piece of data, the longer concurrently running transactions must wait to access that data. The Serializable value protects data by eliminating concurrent access to it. Conversely, the ReadUncommitted value allows the highest degree of concurrency but entails the greatest risk to consistency. You need to balance these two factors appropriately for your application.

By default, most developers deploy enterprise beans with the transaction isolation level set to Serializable. This is the default value in IBM VisualAge for Java Enterprise Edition and other deployment tools. It is also the most restrictive and protected transaction isolation level incurring the most overhead. Some workloads do not require the isolation level and protection afforded by Serializable. A given application might never update the underlying data or be run with other applications that also make concurrent updates. In that case, the application would not have to be concerned with dirty, non-repeatable, or phantom reads. The ReadUncommitted isolation level would probably be sufficient.

Because the transaction isolation level is set in the EJB module's deployment descriptor, the same enterprise bean could be reused in different applications with different transaction isolation levels. The isolation level requirements should be reviewed and adjusted appropriately to increase performance.

The third factor, isolation levels supported in the database, means that although the EJB specification allows you to request one of the four levels of transaction isolation, it is possible that the database being used in the application does not support all of the levels. Also, vendors of database products implement isolation levels differently, so the precise behavior of an application can vary from database to database. You need to consider the database and the isolation levels it supports when deciding on the value for the transaction isolation attribute in deployment descriptors. Consult your database documentation for more information on supported isolation levels.

Setting the security attribute in the deployment descriptor

When an EJB client invokes a method on an enterprise bean, the user context of the client principal is encapsulated in a CORBA Current object, which contains credential properties for the principal. The Current object is passed among the participants in the method invocation as required to complete the method.

The security service uses the credential information to determine the permissions that a principal has on various resources. At appropriate points, the security service determines if the principal is authorized to use a particular resource based on the principal's permissions.

If the method invocation is authorized, the security service does the following with the principal's credential properties based on the value of the *run-as mode* attribute of the enterprise bean. If a specific identity is required, the *RunAsIdentity* attribute is used to specify that identity.

Identity of Caller

The security service makes no changes to the principal's credential properties.

Identity of EJB Server

The security service alters the principal's credential properties to match the credential properties associated with the EJB server.

Identity Assigned to Specified Role

A security principal that has been assigned to the specified role is used for the execution of the bean's methods. This association is part of the application binding where the role is associated with a user ID and password of a user who is granted that role.

Developing enterprise beans

This chapter explains the basic tasks required to develop and package the most common types of enterprise beans. Specifically, this chapter focuses on creating stateless session beans and entity beans that use container-managed persistence (CMP); in the discussion of stateless session beans, important information about stateful beans is also provided. For information on developing entity beans that use bean-managed persistence (BMP), see [Developing entity beans with BMP](#).

The information in this chapter is not exhaustive; however, it includes the information you need to develop basic enterprise beans. For information on developing more complicated enterprise beans, consult a commercially available book on enterprise bean development. The example enterprise beans discussed in this chapter and the example Java applications and servlets that use them are described in [Information about the examples described in the documentation](#).

This chapter describes the requirements for building each of the major components of an enterprise bean. If you do *not* intend to use one of the commercially available integrated development environments (IDE), such as IBM's VisualAge for Java, you must build each of these components manually (by using tools in the Java Development Kit and WebSphere). Manually developing enterprise beans is much more difficult and error-prone than developing them in an IDE. Therefore, it is strongly recommended that you choose an IDE with which you are comfortable.

Developing entity beans with CMP

In an entity bean with CMP, the container handles the interactions between the entity bean and the data source. In an entity bean with BMP, the entity bean must contain all of the code required for the interactions between the entity bean and the data source. For this reason, developing an entity bean with CMP is simpler than developing an entity bean with BMP.

This section examines the development of entity beans with CMP. While much of the information in this section also applies to entity beans with BMP, there are some major differences between the two types. For information on the tasks required to develop an entity bean with BMP, see [Developing entity beans with BMP](#).

Every entity bean must contain the following basic parts:

- The enterprise bean class. For more information, see [Writing the enterprise bean class \(entity with CMP\)](#).
- The enterprise bean's home interface. For more information, see [Writing the home interface \(entity with CMP\)](#).
- The enterprise bean's remote interface. For more information, see [Writing the remote interface \(entity with CMP\)](#).
- The enterprise bean's primary key class. For more information, see [Writing the primary key class \(entity with CMP\)](#).

Writing the enterprise bean class (entity with CMP)

In a CMP entity bean, the bean class defines and implements the business methods of the enterprise bean, defines and implements the methods used to create instances of the enterprise bean, and implements the methods used by the container to inform the instances of the enterprise bean of significant events in the instance's life cycle. Enterprise bean clients never access the bean class directly; instead, the classes that implement the home and remote interfaces are used to indirectly invoke the methods defined in the bean class.

By convention, the enterprise bean class is named *NameBean*, where *Name* is the name you assign to the enterprise bean. The enterprise bean class for the example Account enterprise bean is named AccountBean. Every entity bean class with CMP must meet the following requirements:

- It must be public, it must *not* be abstract, and it must implement the `javax.ejb.EntityBean` interface. For more information, see [Implementing the EntityBean interface](#).
- It must define instance variables that correspond to persistent data associated with the enterprise bean. For more information, see [Defining variables](#).
- It must implement the business methods used to access and manipulate the data associated with the enterprise bean. For more information, see [Implementing the business methods](#).
- It must define and implement an `ejbCreate` method for each way in which the enterprise bean can be instantiated. A corresponding `ejbPostCreate` method must be defined for each `ejbCreate` method. For more information, see [Implementing the ejbCreate and ejbPostCreate methods](#).

Note:

The enterprise bean class can implement the enterprise bean's remote interface, but this is not recommended. If the enterprise bean class implements the remote interface, it is possible to inadvertently pass the *this* variable as a method argument.

An enterprise bean class cannot implement two different interfaces if the methods in the interfaces have the same name, even if the methods have different signatures, due to the Java-IDL mapping specification. Errors can occur when the enterprise bean is

deployed.

[Figure 8](#) shows the main parts of the enterprise bean class for the example Account enterprise bean. (Emphasized code is in bold type.) The sections that follow discuss these parts in greater detail.

Figure 8. Code example: The AccountBean class

```
...
import java.util.Properties;
import javax.ejb.*;
import java.lang.*;
public class AccountBean implements EntityBean {
    // Set instance variables here
    ...
    // Implement methods here
    ...
}
```

Defining variables

An entity bean class can contain both persistent and nonpersistent instance variables; however, static variables are not supported in enterprise beans unless they are also final (that is, they are constants). Static variables are not supported because there is no way to guarantee that they remain consistent across enterprise bean instances.

Container-managed fields (which are persistent variables) are stored in a database. Container-managed fields must be public.

Nonpersistent variables are *not* stored in a database and are temporary. Nonpersistent variables must be used with caution and must not be used to maintain the state of an EJB client between method invocations. This restriction is necessary because nonpersistent variables cannot be relied on to remain the same between method invocations outside of a transaction because other EJB clients can change these variables, or they can be lost when the entity bean is passivated.

The AccountBean class contains three container-managed fields (shown in [Figure 9](#)):

- *accountId*, which identifies the account ID associated with an account
- *type*, which identifies the account type as either savings (1) or checking (2)
- *balance*, which identifies the current balance of the account

Figure 9. Code example: The variables of the AccountBean class

```
...
public class AccountBean implements EntityBean {
    private EntityContext entityContext = null;
    private ListResourceBundle bundle =
        ResourceBundle.getBundle(
            "com.ibm.ejs.doc.account.AccountResourceBundle");
    public long accountId = 0;
    public int type = 1;
    public float balance = 0.0f;
    ...
}
```

The deployment descriptor is used to identify container-managed fields in entity beans with CMP. In an entity bean with CMP, each container-managed field must be initialized by each `ejbCreate` method (see [Implementing the ejbCreate and ejbPostCreate methods](#)).

A subset of the container-managed fields is used to define the primary key class associated with each instance of an enterprise bean. As is shown in [Writing the primary key class \(entity with CMP\)](#), the *accountId* variable defines the primary key for the Account enterprise bean. The AccountBean class contains two nonpersistent variables:

- *entityContext*, which identifies the entity context of each instance of an Account enterprise bean. The entity context can be used to get a reference to the EJB object currently associated with the bean instance and to get the primary key object associated with that EJB object.
- *bundle*, which encapsulates a resource bundle class (`com.ibm.ejs.doc.account.AccountResourceBundle`) that contains locale-specific objects used by the Account bean.

Implementing the business methods

The business methods of an entity bean class define the ways in which the data encapsulated in the class can be manipulated. The business methods implemented in the enterprise bean class cannot be directly invoked by an EJB client. Instead, the EJB client invokes

the corresponding methods defined in the enterprise bean's remote interface, by using an EJB object associated with an instance of the enterprise bean, and the container invokes the corresponding methods in the instance of the enterprise bean.

Therefore, for every business method implemented in the enterprise bean class, a corresponding method must be defined in the enterprise bean's remote interface. The enterprise bean's remote interface is implemented by the container in the EJB object class when the enterprise bean is deployed.

Figure 10 shows the business methods for the AccountBean class. These methods are used to add a specified amount to an account balance and return the new balance (add), to return the current balance of an account (getBalance), to set the balance of an account (setBalance), and to subtract a specified amount from an account balance and return the new balance (subtract). The subtract method throws the user-defined exception `com.ibm.ejs.doc.account.InsufficientFundsException` if a client attempts to subtract more money from an account than is contained in the account balance. The subtract method in the Account bean's remote interface must also throw this exception as shown in Figure 15. User-defined exception classes for enterprise beans are created as are any other user-defined exception class. The message content for the `InsufficientFundsException` exception is obtained from the `AccountResourceBundle` class file by invoking the `getMessage` method on the *bundle* object.

Note:

If an enterprise bean container catches a system exception from the business method of an enterprise bean, and the method is running within a container-managed transaction, the container rolls back the transaction before passing the exception on to the client. However, if the business method is throwing an application exception, then the transaction is not rolled back (it is committed), unless the application has called `setRollbackOnly` function. In this case, the transaction is rolled back before the exception is re-thrown.

Figure 10. Code example: The business methods of the AccountBean class

```
...
public class AccountBean implements EntityBean {
    ...
    public long accountId = 0;
    public int type = 1;
    public float balance = 0.0f;
    ...
    public float add(float amount) {
        balance += amount;
        return balance;
    }
    ...
    public float getBalance() {
        return balance;
    }
    ...
    public void setBalance(float amount) {
        balance = amount;
    }
    ...
    public float subtract(float amount) throws InsufficientFundsException {
        if(balance < amount) {
            throw new InsufficientFundsException(
                bundle.getMessage("insufficientFunds"));
        }
        balance -= amount;
        return balance;
    }
    ...
}
```

Standard application exceptions for entity beans

Version 1.1 of the EJB specification defines several standard application exceptions for use by enterprise beans. All of these exceptions are subclasses of the `javax.ejb.EJBException` class. For entity beans with both container- and bean-managed persistence, the EJB specification defines the following application exceptions:

- `javax.ejb.CreateException`
- `javax.ejb.DuplicateKeyException`
- `javax.ejb.RemoveException`
- `javax.ejb.FinderException`
- `javax.ejb.ObjectNotFoundException`

Application programmers can use the generic `EJBException` class or one of the provided subclassed exceptions, or programmers can define their own exceptions by subclassing any of this family of exceptions. All of these exceptions inherit from the `javax.ejb.RuntimeException` class and do not have to be explicitly declared in throws clauses.

Each exception is discussed in more detail within the relevant section; for more information on:

- `CreateException` and `DuplicateKeyException` (a subclass of the `CreateException` class), see [Implementing the `ejbCreate` and `ejbPostCreate` methods](#).
- `javax.ejb.RemoveException`, see [Implementing the `EntityBean` interface](#).
- `FinderException` and `ObjectNotFoundException` (a subclass of the `FinderException` class), see [Defining finder methods](#).

Note:

Version 1.0 of the EJB specification used the `java.rmi.RemoteException` class to capture application-specific exceptions; the `EJBException` class and its subclasses are new in the 1.1 version of the specification. Therefore, using the `RemoteException` class is now deprecated in favor of the more precise exception classes. Older applications that use the `RemoteException` class can still run, but enterprise beans compliant with version 1.1 of the specification must use the new exception classes.

Implementing the `ejbCreate` and `ejbPostCreate` methods

You must define and implement an `ejbCreate` method for each way in which you want a new instance of an enterprise bean to be created. For each `ejbCreate` method, you must also define a corresponding `ejbPostCreate` method. Each `ejbCreate` and `ejbPostCreate` method must correspond to a create method in the home interface.

Like the business methods of the bean class, the `ejbCreate` and `ejbPostCreate` methods cannot be invoked directly by the client. Instead, the client invokes the create method of the enterprise bean's home interface by using the EJB home object, and the container invokes the `ejbCreate` method followed by the `ejbPostCreate` method. If the `ejbCreate` and `ejbPostCreate` methods are executed successfully, an EJB object is created and the persistent data associated with that object is inserted into the data source.

For an entity bean with CMP, the container handles the required interaction between the entity bean instance and the data source between calls to the `ejbCreate` and `ejbPostCreate` methods. For an entity bean with BMP, the `ejbCreate` method must contain the code to directly handle this interaction. For more information on entity beans with BMP, see [Developing entity beans with BMP](#).

Each `ejbCreate` method in an entity bean with CMP must meet the following requirements:

- It must be public and return the same type as the primary key. The actual return value must be null.
- Its arguments must be valid for Java remote method invocation (RMI). For more information, see [The `java.io.Serializable` and `java.rmi.Remote` interfaces](#).
- It must initialize the container-managed fields of the enterprise bean instance. The container extracts the values of these variables and writes them to the data source after the `ejbCreate` method returns.

Each `ejbPostCreate` method must be public, return void, and have the same arguments as the matching `ejbCreate` method. If necessary, both the `ejbCreate` method and the `ejbPostCreate` method can throw the `javax.ejb.EJBException` exception or one of the creation-related subclasses, the `CreateException` or the `DuplicateKeyException` exceptions. The `DuplicateKeyException` class is a subclass of the `CreateException` class. Throwing the `java.rmi.RemoteException` exception is deprecated; see [Standard application exceptions for entity beans](#) for more information.

[Figure 11](#) shows two sets of `ejbCreate` and `ejbPostCreate` methods required for the example `AccountBean` class. The first set of `ejbCreate` and `ejbPostCreate` methods are wrappers that call the second set of methods and set the *type* variable to 1 (corresponding to a savings account) and the *balance* variable to 0 (zero dollars).

Figure 11. Code example: The `ejbCreate` and `ejbPostCreate` methods of the `AccountBean` class

```
...
public class AccountBean implements EntityBean {
    ...
    public long accountId = 0;
    public int type = 1;
    public float balance = 0.0f;
    ...
    public Integer ejbCreate(AccountKey key) {
        ejbCreate(key, 1, 0.0f);
    }
    ...
    public Integer ejbCreate(AccountKey key, int type, float initialBalance)
    throws EJBException {
        accountId = key.accountId;
```

```

        type = type;
        balance = initialBalance;
    }
    ...
    public void ejbPostCreate(AccountKey key)
    throws EJBException {
        ejbPostCreate(key, 1, 0);
    }
    ...
    public void ejbPostCreate(AccountKey key, int type, float initialBalance) { }
    ...
}

```

Implementing the EntityBean interface

Each entity bean class must implement the methods inherited from the `javax.ejb.EntityBean` interface. The container invokes these methods to inform the bean instance of significant events in the instance's life cycle. (For more information, see [Entity bean life cycle](#).) All of these methods must be public and return void; they can throw the `javax.ejb.EJBException` exception or, in the case of the `ejbRemove` method, the `javax.ejb.RemoveException` exception. Throwing the `java.rmi.RemoteException` exception is deprecated; see [Standard application exceptions for entity beans](#) for more information.

- **ejbActivate**--This method is invoked by the container when the container selects an entity bean instance from the instance pool and assigns that instance to a specific existing EJB object. This method must contain any code that you want to execute when the enterprise bean instance is activated.
- **ejbLoad**--This method is invoked by the container to synchronize an entity bean's container-managed fields with the corresponding data in the data source. (That is, the values of the fields in the data source are loaded into the container-managed fields in the corresponding enterprise bean instance.) This method must contain any code that you want to execute when the enterprise bean instance is synchronized with associated data in the data source.
- **ejbPassivate**--This method is invoked by the container when the container disassociates an entity bean instance from its EJB object and places the enterprise bean instance in the instance pool. This method must contain any code that you want to execute when the enterprise bean instance is "passivated" or deactivated.
- **ejbRemove**--This method is invoked by the container when a client invokes the remove method inherited by the enterprise bean's home interface from the `javax.ejb.EJBHome` interface. This method must contain any code that you want to execute before an enterprise bean instance is removed from the container (and the associated data is removed from the data source). This method can throw the `javax.ejb.RemoveException` exception if removal of an enterprise bean instance is not permitted.
- **setEntityContext**--This method is invoked by the container to pass a reference to the `javax.ejb.EntityContext` interface to an enterprise bean instance. If an enterprise bean instance needs to use this context at any time during its life cycle, the enterprise bean class must contain an instance variable to store this value. This method must contain any code required to store a reference to a context.
- **ejbStore**--This method is invoked by the container when the container needs to synchronize the data in the data source with the values of the container-managed fields in an enterprise bean instance. (That is, the values of the variables in the enterprise bean instance are copied to the data source, overwriting the previous values.) This method must contain any code that you want to execute when the data in the data source is overwritten with the corresponding values in the enterprise bean instance.
- **unsetEntityContext**--This method is invoked by the container, before an enterprise bean instance is removed, to free up any resources associated with the enterprise bean instance. This is the last method called prior to removing an enterprise bean instance.

In entity beans with CMP, the container handles the required data source interaction for these methods. In entity beans with BMP, these methods must directly handle the required data source interaction. For more information on entity beans with BMP, see [More-advanced programming concepts for enterprise beans](#).

These methods have several possible uses, including the following:

- They can contain audit or debugging code.
- They can contain code for allocating and deallocating additional resources used by the bean instance (for example, an SNA connection to a mainframe).

As shown in [Figure 12](#), except for the `setEntityContext` and `unsetEntityContext` methods, all of these methods are empty in the `AccountBean` class because no additional action is required by the bean for the particular life cycle states associated with these methods. The `setEntityContext` and `unsetEntityContext` methods are used in a conventional way to set the value of the *entityContext* variable.

Figure 12. Code example: Implementing the EntityBean interface in the AccountBean class

```

...
public class AccountBean implements EntityBean {

```

```

private EntityContext entityContext = null;
...
public void ejbActivate() throws EJBException { }
...
public void ejbLoad () throws EJBException { }
...
public void ejbPassivate() throws EJBException { }
...
public void ejbRemove() throws EJBException { }
...
public void ejbStore () throws EJBException { }
...
public void setEntityContext(EntityContext ctx) throws EJBException {
    entityContext = ctx;
}
...
public void unsetEntityContext() throws EJBException {
    entityContext = null;
}
}

```

Writing the home interface (entity with CMP)

An entity bean's home interface defines the methods used by clients to create new instances of the bean, find and remove existing instances, and obtain metadata about an instance. The home interface is defined by the enterprise bean developer and implemented in the EJB home class created by the container during enterprise bean deployment.

The container makes the home interface accessible to enterprise bean clients through the Java Naming and Directory Interface (JNDI). JNDI is independent of any specific naming and directory service and allows Java-based applications to access any naming and directory service in a standard way.

By convention, the home interface is named *NameHome*, where *Name* is the name you assign to the enterprise bean. For example, the Account enterprise bean's home interface is named AccountHome. Every home interface must meet the following requirements:

- It must extend the `javax.ejb.EJBHome` interface. The home interface inherits several methods from the `javax.ejb.EJBHome` interface. See [The javax.ejb.EJBHome interface](#) for information on these methods.
- Each method in the interface must be either a create method that corresponds to a set of `ejbCreate` and `ejbPostCreate` methods in the EJB object class, or a finder method. For more information, see [Defining create methods](#) and [Defining finder methods](#).
- The parameters and return value of each method defined in the home interface must be valid for Java RMI. For more information, see [The java.io.Serializable and java.rmi.Remote interfaces](#). In addition, each method's throws clause must include the `java.rmi.RemoteException` exception class.

[Figure 13](#) shows the relevant parts of the definition of the home interface (AccountHome) for the example Account bean. This interface defines two abstract create methods: the first creates an Account object by using an associated AccountKey object, the second creates an Account object by using an associated AccountKey object and specifying an account type and an initial balance. The interface defines the required `findByPrimaryKey` method and a `findLargeAccounts` method, which returns a collection of accounts containing balances greater than a specified amount.

Figure 13. Code example: The AccountHome home interface

```

...
import java.rmi.*;
import java.util.*;
import javax.ejb.*;
public interface AccountHome extends EJBHome {
    ...
    Account create (AccountKey id) throws CreateException, RemoteException;
    ...
    Account create(AccountKey id, int type, float initialBalance)
        throws CreateException, RemoteException;
    ...
    Account findByPrimaryKey (AccountKey id)
        RemoteException, FinderException;
    ...
    Enumeration findLargeAccounts(float amount)
        throws RemoteException, FinderException;
}

```

Defining create methods

A create method is used by a client to create an enterprise bean instance and insert the data associated with that instance into the data source. Each create method must be named `create` and it must have the same number and types of arguments as a corresponding `ejbCreate` method in the enterprise bean class. (The `ejbCreate` method must itself have a corresponding `ejbPostCreate` method.)

Each create method must meet the following requirements:

- It must be named `create`.
- It must return the type of the enterprise bean's remote interface. For example, the return type for the create methods in the `AccountHome` interface is `Account` (as shown in [Figure 13](#)).
- It must have a throws clause that includes the `java.rmi.RemoteException` exception, the `javax.ejb.CreateException` exception, and all of the application exceptions defined in the throws clause of the corresponding `ejbCreate` and `ejbPostCreate` methods.

Defining finder methods

A finder method is used to find one or more existing entity EJB objects. Each finder method must be named `findName`, where *Name* further describes the finder method's purpose.

At minimum, each home interface must define the `findByPrimaryKey` method that enables a client to locate an EJB object by using the primary key only. The `findByPrimaryKey` method has one argument, an object of the bean's primary key class, and returns the type of the bean's remote interface.

Every other finder method must meet the following requirements:

- It must return the type of the enterprise bean's remote interface, the `java.util Enumeration` interface, or the `java.util Collection` interface (when a finder method can return more than one EJB object or an EJB collection).
- It must have a throws clause that includes the `java.rmi.RemoteException` and `javax.ejb.FinderException` exception classes.

While every entity bean must contain the default finder method, you can write additional finder methods if needed. For example, the `Account` bean's home interface defines the `findLargeAccounts` method to find objects that encapsulate accounts with balances of more than a specified amount, as shown in [Figure 14](#). Because this finder method can be expected to return a reference to more than one EJB object, its return type is `Enumeration`.

Figure 14. Code example: The `findLargeAccounts` method

```
Enumeration findLargeAccounts(float amount)
    throws RemoteException, FinderException;
```

Every EJB server can implement the `findByPrimaryKey` method. During enterprise bean deployment, the container generates the code required to search the database for the appropriate enterprise bean instance.

However, for each additional finder method that you define in the home interface, the enterprise bean deployer must associate finder logic with that finder method. This logic is used by the EJB server during deployment to generate the code required to implement the finder method.

The EJB Specification does not define the format of the finder logic, so the format can vary according to the EJB server you are using. For more information on creating finder logic, see [Creating finder logic in the EJB server](#).

Writing the remote interface (entity with CMP)

An entity bean's remote interface provides access to the business methods available in the bean class. It also provides methods to remove an EJB object associated with a bean instance and to obtain the bean instance's home interface, object handle, and primary key. The remote interface is defined by the enterprise bean developer and implemented in the EJB object class created by the container during enterprise bean deployment.

By convention, the remote interface is named *Name*, where *Name* is the name you assign to the enterprise bean. For example, the `Account` enterprise bean's remote interface is named `Account`. Every remote interface must meet the following requirements:

- It must extend the `javax.ejb.EJBObject` interface. The enterprise bean's remote interface inherits several methods from the `javax.ejb.EJBObject` interface. See [Methods inherited from javax.ejb.EJBObject](#) for information on these methods.
- You must define a corresponding business method for every business method implemented in the enterprise bean class.
- The parameters and return value of each method defined in the interface must be valid for Java RMI. For more information, see [The java.io.Serializable and java.rmi.Remote interfaces](#).
- Each method's throws clause must include the `java.rmi.RemoteException` exception class.

Figure 15 shows the relevant parts of the definition of the remote interface (Account) for the example Account enterprise bean. This interface defines four methods for displaying and manipulating the account balance that exactly match the business methods implemented in the AccountBean class. All of the business methods in the remote interface throw the `java.rmi.RemoteException` exception class. In addition, the `subtract` method must throw the user-defined exception `com.ibm.ejs.doc.account.InsufficientFundsException` because the corresponding method in the bean class throws this exception. Furthermore, any client that calls this method must either handle the exception or pass it on by throwing it.

Figure 15. Code example: The Account remote interface

```
...
import java.rmi.*;
import javax.ejb.*;
public interface Account extends EJBObject
{
    ...
    float add(float amount) throws RemoteException;
    ...
    float getBalance() throws RemoteException;
    ...
    void setBalance(float amount) throws RemoteException;
    ...
    float subtract(float amount) throws InsufficientFundsException,
        RemoteException;
}
```

Writing the primary key class (entity with CMP)

Within a container, every entity EJB object has a unique identity that is defined by using a combination of the object's home interface name and its primary key, the latter of which is assigned to the object at creation. If two EJB objects have the same identity, they are considered identical.

Primary keys are specified in two ways:

- Simple primary keys, which map to a single field in the entity bean class and are comprised of primitive Java data types (such as integer or long), are specified in the deployment descriptor.
- Composite primary keys, which map to multiple fields in the entity bean class (or to data structures built from the primitive Java data types), must be encapsulated in a *primary key class*. More complicated enterprise beans are likely to have composite primary keys, with multiple instance variables representing the primary key.

The primary key class is used to manage an EJB object's primary key. By convention, the primary key class is named *NameKey*, where *Name* is the name of the enterprise bean. For example, the Account enterprise bean's primary key class is named `AccountKey`. The primary key class must meet the following requirements:

- It must be public and it must be serializable. For more information, see [The java.io.Serializable and java.rmi.Remote interfaces](#).
- Its instance variables must be public, and the variable names must match a subset of the container-managed field names defined in the enterprise bean class.
- It must have a public default constructor, at a minimum.

Note:

The primary key class of a CMP entity bean must override the `equals` method and the `hashCode` method inherited from the `java.lang.Object` class.

Figure 16 shows a composite primary key class for an example enterprise bean, `Item`. In effect, this class acts as a wrapper around the string variables `productId` and `vendorId`. The `hashCode` method for the `ItemKey` class invokes the corresponding `hashCode` method in the `java.lang.String` class after creating a temporary string object by using the value of the `productId` variable. In addition to the default constructor, the `ItemKey` class also defines a constructor that sets the value of the primary key variables to the specified strings.

Figure 16. Code example: The ItemKey primary key class

```
...
import java.io.*;
// Composite primary key class
public class ItemKey implements java.io.Serializable {

    public String productId;
    public String vendorId;
    // Constructors
    public ItemKey() { };
    public ItemKey(String productId, String vendorId) {
```

```

        this.productId = productId;
        this.vendorId = vendorId;
    }

    public String getProductId() {
        return productId;
    }
    public String getVendorId() {
        return vendorId;
    }
    ...
    // EJB server-specific method
    public boolean equals(Object other) {
        if (other instanceof ItemKey) {
            return (productId.equals(((ItemKey)
                other).productId)
                && vendorId.equals(((ItemKey)
                other).vendorId));
        }
        else
            return false;
    }
    ...
    // EJB server-specific method
    public int hashCode() {
        return (new productId.hashCode());
    }
}

```

A primary key class can also be used to encapsulate a primary key that is not known ahead of time -- for instance, if the entity bean is intended to work with several persistent data stores, each of which requires a different primary key structure. The entity bean's primary key type is derived from the primary key type used by the underlying database that stores the entity objects; it does not necessarily have to be known to the enterprise bean developer.

To specify an unknown primary key, do the following:

- Declare the argument of the `findByPrimaryKey` class as `java.lang.Object`.
- Declare the return value of the `ejbCreate` method as `java.lang.Object`
- In the deployment descriptor, specify the primary key class as being of the type `java.lang.Object`.

When the primary key selection is deferred to deployment, client applications cannot use methods that rely on knowledge of the primary key type. In addition, applications cannot always depend on methods that return the type of the primary key (such as the `EntityContext.getPrimaryKey` method) because the return type is determined at deployment.

Interacting with databases

This section contains general information and tips on enterprise beans and database access.

- Although it is not necessary, it is good practice to specify the user ID and password for a data source either in the enterprise bean to be using the data source, or in the container of the bean.
- The container supports Option A and Option C caching. When Option A caching is in use, the application server hosting the enterprise bean container must be the only updater of the data in the persistent store. As such, Option A caching is incompatible with the following:
 - Workload managed servers (such as a cluster of clones)
 - Databases with data being shared among multiple applications

The default caching option is C (multiple entity bean instances, possibly in different servers, can update bean state in the database). The default caching option can be changed from Option C to Option A by selecting "exclusive persistent store" in the administrative console when creating the entity bean.

Shared database access corresponds to Option C caching. Option A and Option C caching are also known as commit option A and commit option C, respectively.

Developing session beans

In their basic makeup, session beans are similar to entity beans. However, their purposes are very different.

From a component perspective, one of the biggest differences between the two types of enterprise beans is that session beans do not have a primary key class and the session bean's home interface does not define finder methods. Session enterprise beans do not require primary keys and finder methods because session EJB objects are created, associated with a specific client, and then removed as needed, whereas entity EJB objects represent permanent data in a data source and can be uniquely identified with a primary key. Because the data for session beans is never permanently stored, the session bean class does not have methods for storing data to and loading data from a data source.

Every session bean must contain the following basic parts:

- The enterprise bean class. For more information, see [Writing the enterprise bean class \(session\)](#).
- The enterprise bean's home interface. For more information, see [Writing the home interface \(session\)](#).
- The enterprise bean's remote interface. For more information, see [Writing the remote interface \(session\)](#).

Writing the enterprise bean class (session)

A session bean class defines and implements the business methods of the enterprise bean, implements the methods used by the container during the creation of enterprise bean instances, and implements the methods used by the container to inform the enterprise bean instance of significant events in the instance's life cycle. By convention, the enterprise bean class is named *NameBean*, where *Name* is the name you assign to the enterprise bean. The enterprise bean class for the example Transfer enterprise bean is named *TransferBean*. Every session bean class must meet the following requirements:

- It must define and implement the business methods that execute the tasks associated with the enterprise bean. For more information, see [Implementing the business methods](#).
- It must define and implement an `ejbCreate` method for each way in which you want it to be able to instantiate the enterprise bean class. For more information, see [Implementing the ejbCreate methods](#).
- It must be public, it must *not* be abstract, and it must implement the `javax.ejb.SessionBean` interface. For more information, see [Implementing the SessionBean interface](#).

Note:

Version 1.0 of the EJB specification allowed the methods in the session bean class to throw the `java.rmi.RemoteException` exception to indicate a non-application exception. This practice is deprecated in version 1.1 of the specification. A session bean compliant with version 1.1 of the specification should throw the `javax.ejb.EJBException` exception (a subclass of the `java.lang.RuntimeException` class) or another `RuntimeException` exception instead. Because the `javax.ejb.EJBException` class is a subclass of the `java.lang.RuntimeException`, `EJBException` exceptions do not need to be explicitly listed in the `throws` clause of methods.

A session bean can be either stateful or stateless. In a stateless session bean, none of the methods depend on the values of variables set by any other method, except for the `ejbCreate` method, which sets the initial (identical) state of each bean instance. In a stateful enterprise bean, one or more methods depend on the values of variables set by some other method. As in entity beans, static variables are not supported in session beans unless they are also final. Stateful session beans possibly need to synchronize their conversational state with the transactional context in which they operate. For example, a stateful session bean possibly needs to reset the value of some of its variables if a transaction is rolled back or it possibly needs to change these variables if a transaction successfully completes.

If a bean needs to synchronize its conversational state with the transactional context, the bean class must implement the `javax.ejb.SessionSynchronization` interface. This interface contains methods to notify the session bean when a transaction begins, when it is about to complete, and when it has completed. The enterprise bean developer can use these methods to synchronize the state of the session enterprise bean instance with ongoing transactions.

The enterprise bean class can implement the enterprise bean's remote interface, but this is not recommended. If the enterprise bean class implements the remote interface, it is possible to inadvertently pass the *this* variable as a method argument.

[Figure 17](#) shows the main parts of the enterprise bean class for the example Transfer bean. The sections that follow discuss these parts in greater detail.

The Transfer bean is stateless. If the Transfer bean's `transferFunds` method were dependent on the value of the *balance* variable returned by the `getBalance` method, the `TransferBean` would be stateful.

Figure 17. Code example: The `TransferBean` class

```
...
import java.rmi.RemoteException;
import java.util.Properties;
import java.util.ResourceBundle;
import java.util.ListResourceBundle;
import javax.ejb.*;
import java.lang.*;
import javax.naming.*;
```



```

import com.ibm.ejs.doc.account.*;
...
public class TransferBean implements SessionBean {
    ...
    private SessionContext mySessionCtx = null;
    private InitialContext initialContext = null;
    private AccountHome accountHome = null;
    private Account fromAccount = null;
    private Account toAccount = null;
    ...
    public void ejbActivate() throws EJBException { }
    ...
    public void ejbCreate() throws EJBException {
        ...
    }
    ...
    public void ejbPassivate() throws EJBException { }
    ...
    public void ejbRemove() throws EJBException { }
    ...
    public float getBalance(long acctId) throws FinderException,
        EJBException {
        ...
    }
    ...
    public void setSessionContext(javax.ejb.SessionContext ctx)
        throws EJBException {
        ...
    }
    ...
    public void transferFunds(long fromAcctId, long toAcctId, float amount)
        throws EJBException {
        ...
    }
}

```

Implementing the business methods

The business methods of a session bean class define the ways in which an EJB client can manipulate the enterprise bean. The business methods implemented in the enterprise bean class cannot be directly invoked by an EJB client. Instead, the EJB client invokes the corresponding methods defined in the enterprise bean's remote interface, by using an EJB object associated with an instance of the enterprise bean, and the container invokes the corresponding methods in the enterprise bean instance.

Therefore, for every business method defined in the enterprise bean's remote interface, a corresponding method must be implemented in the enterprise bean class. The enterprise bean's remote interface is implemented by the container in the EJBObject class when the enterprise bean is deployed.

[Figure 18](#) shows the business methods for the TransferBean class. The getBalance method is used to get the balance for an account. It first locates the appropriate Account EJB object and then calls that object's getBalance method.

The transferFunds method is used to transfer a specified amount between two accounts (encapsulated in two Account entity EJB objects). After locating the appropriate Account EJB objects by using the findByPrimaryKey method, the transferFunds method calls the add method on one account and the subtract method on the other. Like all finder methods, findByPrimaryKey can throw both the FinderException and RemoteException exceptions. The try/catch blocks are set up around invocations of the findByPrimaryKey method to handle the entry of invalid account IDs by users. If the session bean user enters an invalid account ID, the findByPrimaryKey method cannot locate an EJB object, and the finder method throws the FinderException exception. This exception is caught and converted into a new FinderException exception containing information on the invalid account ID.

To call the findByPrimaryKey method, both business methods need to be able to access the EJB home object that implements the AccountHome interface discussed in [Writing the home interface \(entity with CMP\)](#). Obtaining the EJB home object is discussed in [Implementing the ejbCreate methods](#).

Figure 18. Code example: The business methods of the TransferBean class

```

public class TransferBean implements SessionBean {
    ...
    private Account fromAccount = null;
    private Account toAccount = null;

```

```

...
public float getBalance(long acctId) throws FinderException, EJBException {
    AccountKey key = new AccountKey(acctId);
    try {
        fromAccount = accountHome.findByPrimaryKey(key);
    } catch(FinderException ex) {
        throw new FinderException("Account " + acctId
            + " does not exist.");
    } catch(RemoteException ex) {
        throw new FinderException("Account " + acctId
            + " could not be found.");
    }
    return fromAccount.getBalance();
}
...
public void transferFunds(long fromAcctId, long toAcctId, float amount)
    throws EJBException, InsufficientFundsException, FinderException {
    AccountKey fromKey = new AccountKey(fromAcctId);
    AccountKey toKey = new AccountKey(toAcctId);
    try {
        fromAccount = accountHome.findByPrimaryKey(fromKey);
    } catch(FinderException ex) {
        throw new FinderException("Account " + fromAcctId
            + " does not exist.");
    } catch(RemoteException ex) {
        throw new FinderException("Account " + acctId
            + " could not be found.");
    }
    try {
        toAccount = accountHome.findByPrimaryKey(toKey);
    } catch(FinderException ex) {
        throw new FinderException("Account " + toAcctId
            + " does not exist.");
    } catch(RemoteException ex) {
        throw new FinderException("Account " + acctId
            + " could not be found.");
    }
    try {
        toAccount.add(amount);
        fromAccount.subtract(amount);
    } catch(InsufficientFundsException ex) {
        mySessionCtx.setRollbackOnly();
        throw new InsufficientFundsException("Insufficient funds in "
            + fromAcctId);
    }
}
}
}

```

Implementing the ejbCreate methods

You must define and implement an ejbCreate method for each way in which you want an enterprise bean to be instantiated.

Each ejbCreate method must correspond to a create method in the enterprise bean's home interface. (Note that there is no ejbPostCreate method in a session bean as there is in an entity bean.) Unlike the business methods of the enterprise bean class, the ejbCreate methods cannot be invoked directly by the client. Instead, the client invokes the create method in the bean instance's home interface, and the container invokes the ejbCreate method. If an ejbCreate method is executed successfully, an EJB object is created.

An ejbCreate method for a session bean must meet the following requirements:

- The method must be declared as public and cannot be declared as final or static.
- It must return void.
- A stateless session bean must have only one ejbCreate method, which must return void and contain no arguments. A stateful session bean can have multiple ejbCreate methods.

The throws clause can define arbitrary application exceptions. The javax.ejb.EJBException or another runtime exception can be used to indicate non-application exceptions.

An `ejbCreate` method for an entity bean must meet the following requirements:

- The method must be declared as `public` and cannot be declared as `final` or `static`.
- It must return the entity bean's primary key type.
- It must contain code to set the values of any variables needed by the EJB object.

The `throws` clause can define arbitrary application exceptions. The `javax.ejb.EJBException` or another runtime exception can be used to indicate non-application exceptions. [Figure 19](#) shows the `ejbCreate` method required by the example `TransferBean` class. The `Transfer` bean's `ejbCreate` method obtains a reference to the `Account` bean's home object. This reference is required by the `Transfer` bean's business methods. Getting a reference to an enterprise bean's home interface is a two-step process:

1. Construct an `InitialContext` object by setting the required property values. For the example `Transfer` bean, these property values are defined in the environment variables of the `Transfer` bean's deployment descriptor.
2. Use the `InitialContext` object to create and get a reference to the home object. For the example `Transfer` bean, the JNDI name of the `Account` bean is stored in an environment variable in the `Transfer` bean's deployment descriptor.

Creating the `InitialContext` object

When a container invokes the `Transfer` bean's `ejbCreate` method, the enterprise bean's *initialContext* object is constructed by creating a `Properties` variable (*env*) that requires the following values:

- The location of the name service (`javax.naming.Context.PROVIDER_URL`).
- The name of the initial context factory (`javax.naming.Context.INITIAL_CONTEXT_FACTORY`).

The values of these properties are discussed in more detail in [Creating and getting a reference to a bean's EJB object](#).

Figure 19. Code example: Creating the `InitialContext` object in the `ejbCreate` method of the `TransferBean` class

```
...
public class TransferBean implements SessionBean {
    private static final String INITIAL_NAMING_FACTORY_SYSPROP =
        javax.naming.Context.INITIAL_CONTEXT_FACTORY;
    private static final String PROVIDER_URL_SYSPROP =
        javax.naming.Context.PROVIDER_URL;

    ...
    private String nameService = null;
    ...
    private String providerURL = null;
    ...
    private InitialContext initialContext = null;
    ...
    public void ejbCreate() throws EJBException {
        // Get the initial context
        try {
            Properties env = System.getProperties();
            ...
            env.put( PROVIDER_URL_SYSPROP, getProviderUrl() );
            env.put( INITIAL_CONTEXT_FACTORY_SYSPROP, getNamingFactory() );
            initialContext = new InitialContext( env );
        } catch (Exception ex) {
            ...
        }
        ...
        // Look up the home interface using the JNDI name
        ...
    }
}
```

Although the example `Transfer` bean stores some locale specific variables in a resource bundle class, like the example `Account` bean, it also relies on the values of environment variables stored in its deployment descriptor. Each of these `InitialContext` `Properties` values is obtained from an environment variable contained in the `Transfer` bean's deployment descriptor. A private `get` method that corresponds to the property variable is used to get each of the values (`getNamingFactory` and `getProviderURL`); these methods must be written by the enterprise bean developer. The following environment variables must be set to the appropriate values in the deployment descriptor of the `Transfer` bean.

- `javax.naming.Context.INITIAL_CONTEXT_FACTORY`
- `javax.naming.Context.PROVIDER_URL`

[Figure 20](#) illustrates the relevant parts of the `getProviderURL` method that is used to get the `PROVIDER_URL` property value. The `javax.ejb.SessionContext` variable (*mySessionCtx*) is used to get the `Transfer` bean's environment in the deployment descriptor by

invoking the `getEnvironment` method. The object returned by the `getEnvironment` method can then be used to get the value of a specific environment variable by invoking the `getProperty` method.

Figure 20. Code example: The `getProviderURL` method

```
...
public class TransferBean implements SessionBean {
    private SessionContext mySessionCtx = null;
    ...
    private String getProviderURL() throws RemoteException {
        //get the provider URL property either from
        //the EJB properties or, if it isn't there
        //use "iiop://", which causes a default to the local host
        ...
        String pr = mySessionCtx.getEnvironment().getProperty(
            PROVIDER_URL_SYSPROP);
        if (pr == null)
            pr = "iiop://";
        return pr;
    }
    ...
}
```

Getting the reference to the home object

An enterprise bean is accessed by looking up the class implementing its home interface by name through JNDI. Methods on the home interface provide access to an instance of the class implementing the remote interface.

After constructing the `InitialContext` object, the `ejbCreate` method performs a JNDI lookup using the JNDI name of the `Account` enterprise bean. Like the `PROVIDER_URL` and `INITIAL_CONTEXT_FACTORY` properties, this name is also retrieved from an environment variable contained in the `Transfer` bean's deployment descriptor (by invoking a private method named `getHomeName`). The lookup method returns an object of type `java.lang.Object`.

The returned object is narrowed by using the static method `javax.rmi.PortableRemoteObject.narrow` to obtain a reference to the EJB home object for the specified enterprise bean. The parameters of the `narrow` method are the object to be narrowed and the class of the object to be created as a result of the narrowing. For a more thorough discussion of the code required to locate an enterprise bean in JNDI and then narrow it to get an EJB home object, see [Creating and getting a reference to a bean's EJB object](#).

Figure 21. Code example: Creating the `AccountHome` object in the `ejbCreate` method of the `TransferBean` class

```
...
public class TransferBean implements SessionBean {
    ...
    private String accountName = null;
    ...
    private InitialContext initialContext = null;
    ...
    public void ejbCreate() throws EJBException {
        // Get the initial context
        ...
        // Look up the home interface using the JNDI name
        try {
            java.lang.Object ejbHome = initialContext.lookup(accountName);
            accountHome = (AccountHome)javax.rmi.PortableRemoteObject.narrow(
                ejbHome, AccountHome.class);
        } catch (NamingException e) { // Error getting the home interface
            ...
        }
        ...
    }
    ...
}
```

Looking up an enterprise bean's environment naming context

The enterprise bean's environment is implemented by the container. It enables the bean's business logic to be customized without the need to access or change the bean's source code. The container provides an implementation of the JNDI naming context that stores the enterprise bean environment. Business methods access the environment by using the JNDI interfaces. The deployment descriptor

provides the environment entries that the enterprise bean expects at runtime.

Each enterprise bean defines its own environment entries, which are shared between all of its instances (that is, all instances with the same home). Environment entries are not shared between enterprise beans.

An enterprise bean's environment entries are stored directly in the environment naming context (or one of its subcontexts). To retrieve its environment naming context, an enterprise bean instance creates an `InitialContext` object by using the constructor with no arguments. It then looks up the environment naming via the `InitialContext` object under the name `java:comp/env`.

The enterprise bean in [Figure 22](#) changes an account number by looking up an environment entry to find the new account number.

Figure 22. Code example: Looking up an enterprise bean's environment naming context

```
public class AccountService implements SessionBean {
    ...
    public void changeAccountNumber(int accountNumber, ... )
        throws InvalidAccountNumberException{
        ....
        // Obtain the bean's environment naming context
        Context initialContext = new InitialContext();
        Context myEnvironment = (Context)initialContext.lookup("java:comp/env");
        ...
        // Obtain new account number from environment
        Integer newNumber = (Integer)myEnvironment.lookup("newAccountNumber");
        ...
    }
}
```

Implementing the SessionBean interface

Every session bean class must implement the methods inherited from the `javax.ejb.SessionBean` interface. The container invokes these methods to inform the enterprise bean instance of significant events in the instance's life cycle. All of these methods must be public, must return void, and can throw the `javax.ejb.EJBException`. (Throwing the `java.rmi.RemoteException` exception is deprecated; see *** for more information.)

- **ejbActivate**--This method is invoked by the container when the container selects an enterprise bean instance from the instance pool and assigns it a specific existing EJB object. This method must contain any code that you want to execute when the enterprise bean instance is activated.
- **ejbPassivate**--This method is invoked by the container when the container disassociates an enterprise bean instance from its EJB object and places the enterprise bean instance in the instance pool. This method must contain any code that you want to execute when the enterprise bean instance is passivated (deactivated).
- **ejbRemove**--This method is invoked by the container when a client invokes the remove method inherited by the enterprise bean's home interface (from the `javax.ejb.EJBHome` interface). This method must contain any code that you want to execute when an enterprise bean instance is removed from the container.
- **setSessionContext**--This method is invoked by the container to pass a reference to the `javax.ejb.SessionContext` interface to a session bean instance. If an enterprise bean instance needs to use this context at any time during its life cycle, the enterprise bean class must contain an instance variable to store this value. This method must contain any code required to store a reference to the context.

A session context can be used to get a handle to a particular instance of a stateful session bean. It can also be used to get a reference to a transaction context object, as described in [Using bean-managed transactions](#).

As shown in [Figure 23](#), except for the `setSessionContext` method, all of these methods in the `TransferBean` class are empty because no additional action is required by the bean for the particular life cycle states associated with these methods. The `setSessionContext` method is used in a conventional way to set the value of the `mySessionCtx` variable.

Figure 23. Code example: Implementing the SessionBean interface in the TransferBean class

```
...
public class TransferBean implements SessionBean {
    private SessionContext mySessionCtx = null;
    ...
    public void ejbActivate() throws EJBException { }
    ...
    public void ejbPassivate() throws EJBException { }
    ...
    public void ejbRemove() throws EJBException { }
    ...
    public void setSessionContext(SessionContext ctx) throwEJBException {
```

```

        mySessionCtx = ctx;
    }
    ...
}

```

Writing the home interface (session)

A session bean's home interface defines the methods used by clients to create and remove instances of the enterprise bean and obtain metadata about an instance. The home interface is defined by the enterprise bean developer and implemented in the EJB home class created by the container during enterprise bean deployment. The container makes the home interface accessible to clients through JNDI.

By convention, the home interface is named *NameHome*, where *Name* is the name you assign to the enterprise bean. For example, the Transfer enterprise bean's home interface is named TransferHome. Every session bean's home interface must meet the following requirements:

- It must extend the `javax.ejb.EJBHome` interface. The home interface inherits several methods from the `javax.ejb.EJBHome` interface. See [The `javax.ejb.EJBHome` interface](#) for information on these methods.
- Each method in the interface must be a create method that corresponds to a `ejbCreate` method in the enterprise bean class. For more information, see [Implementing the `ejbCreate` methods](#). Unlike entity beans, the home interface of a session bean contains no finder methods.
- The parameters and return value of each method defined in the interface must be valid for Java RMI. For more information, see [The `java.io.Serializable` and `java.rmi.Remote` interfaces](#). In addition, each method's throws clause must include the `java.rmi.RemoteException` exception class.

Figure 24 shows the relevant parts of the definition of the home interface (TransferHome) for the example Transfer bean.

Figure 24. Code example: The TransferHome home interface

```

...
import javax.ejb.*;
import java.rmi.*;
public interface TransferHome extends EJBHome {
    Transfer create() throws CreateException, RemoteException;
}

```

A create method is used by a client to create an enterprise bean instance. A stateful session bean can contain multiple create methods; however, a stateless session bean can contain only one create method with no arguments. This restriction on stateless session beans ensures that every instance of a stateless session bean is the same as every other instance of the same type. (For example, every Transfer bean instance is the same as every other Transfer bean instance.)

Each create method must be named `create` and have the same number and types of arguments as a corresponding `ejbCreate` method in the EJB object class. The return types of the create method and its corresponding `ejbCreate` method are always different. Each create method must meet the following requirements:

- It must return the type of the enterprise bean's remote interface. For example, the return type for the create method in the TransferHome interface is Transfer.
- It must have a throws clause that includes the `java.rmi.RemoteException` exception, the `javax.ejb.CreateException` exception class, and all of the exceptions defined in the throws clause of the corresponding `ejbCreate` method.

Writing the remote interface (session)

A session bean's remote interface provides access to the business methods available in the enterprise bean class. It also provides methods to remove an enterprise bean instance and to obtain the enterprise bean's home interface and handle. The remote interface is defined by the enterprise bean developer and implemented in the EJB object class created by the container during enterprise bean deployment.

By convention, the remote interface is named *Name*, where *Name* is the name you assign to the enterprise bean. For example, the Transfer enterprise bean's remote interface is named Transfer. Every remote interface must meet the following requirements:

- It must extend the `javax.ejb.EJBObject` interface. The remote interface inherits several methods from the `EJBObject` interface. See [Methods inherited from `javax.ejb.EJBObject`](#) for information on these methods.
- You must define a corresponding business method for every business method implemented in the enterprise bean class.
- The parameters and return value of each method defined in the interface must be valid for Java RMI. For more information, see [The `java.io.Serializable` and `java.rmi.Remote` interfaces](#).
- Each method's throws clause must include the `java.rmi.RemoteException` exception class.

Figure 25 shows the relevant parts of the definition of the remote interface (Transfer) for the example Transfer bean. This interface defines the methods for transferring funds between two Account bean instances and for getting the balance of an Account bean instance.

Figure 25. Code example: The Transfer remote interface

```
...
import javax.ejb.*;
import java.rmi.*;
import com.ibm.ejs.doc.account.*;
public interface Transfer extends EJBObject {
    ...
    float getBalance(long acctId) throws FinderException, RemoteException;
    ...
    void transferFunds(long fromAcctId, long toAcctId, float amount)
        throws InsufficientFundsException, RemoteException;
}
```

Implementing interfaces common to multiple types of enterprise beans

Enterprise beans must implement the interfaces described here in the appropriate enterprise bean component.

Methods inherited from javax.ejb.EJBObject

The remote interface inherits the following methods from the javax.ejb.EJBObject interface, which are implemented by the container during deployment:

- **getEJBHome**--Returns the enterprise bean's home interface.
- **getHandle**--Returns the handle for the EJB object.
- **getPrimaryKey**--Returns the EJB object's primary key. (For session beans, this cannot be used because session beans do not have a primary key.)
- **isIdentical**--Compares this EJB object with the EJB object argument to determine if they are the same.
- **remove**--Removes this EJB object.

These methods have the following syntax:

```
public abstract EJBHome getEJBHome();
public abstract Handle getHandle();
public abstract Object getPrimaryKey();
public abstract boolean isIdentical(EJBObject obj);
public abstract void remove();
```

These methods are implemented by the container in the EJB object class.

The javax.ejb.EJBHome interface

The home interface inherits two remove methods and the getEJBMetaData method from the javax.ejb.EJBHome interface. Just like the methods defined directly in the home interface, these inherited methods are also implemented in the EJB home class created by the container during deployment.

The remove methods are used to remove an existing EJB object (and its associated data in the database) either by specifying the EJB object's handle or its primary key. (The remove method that takes a *primaryKey* variable can be used only in entity beans.) The getEJBMetaData method is used to obtain metadata about the enterprise bean and is mainly intended for use by development tools.

These methods have the following syntax:

```
public abstract EJBMetaData getEJBMetaData();
public abstract void remove(Handle handle);
public abstract void remove(Object primaryKey);
```

The javax.ejb.EJBHome interface also contains a method to get a handle to the home interface. It has the following syntax:

```
public abstract HomeHandle getHomeHandle();
```

The java.io.Serializable and java.rmi.Remote interfaces

To be valid for use in a remote method invocation (RMI), a method's arguments and return value must be one of the following types:

- A primitive type; for example, an int or a long.
- An object of a class that directly or indirectly implements java.io.Serializable; for example, java.lang.Long.
- An object of a class that directly or indirectly implements java.rmi.Remote.
- An array of valid types or objects.

If you attempt to use a parameter that is not valid, the java.rmi.RemoteException exception is thrown. Note that the following atypical types are *not* valid:

- An object of a class that directly or indirectly implements both Serializable and Remote.
 - An object of a class that directly or indirectly implements Remote, but contains a method that does not throw the RemoteException or an exception that inherits from RemoteException.
-

Using threads and reentrancy in enterprise beans

An enterprise bean must not contain code to start new threads (nor can methods be defined with the keyword synchronized). Session beans can *never* be reentrant; that is, they cannot call another bean that invokes a method on the calling bean. Entity beans can be reentrant, but building reentrant entity beans is not recommended and is not documented here.

The EJB server enforces single-threaded access to all enterprise beans. Illegal callbacks result in a java.rmi.RemoteException exception being thrown to the EJB client.

Creating an EJB module for enterprise beans

There are two tasks involved in preparing an enterprise bean for deployment:

- Making the components of the bean part of the same Java package. For more information, see [Making bean components part of a Java package](#).
- Creating an EJB module and associated deployment descriptor. For more information, see [Creating an EJB module and deployment descriptor](#).

If you develop enterprise beans in an IDE, these tasks are handled from within the tool that you use. If you do not develop enterprise beans in an IDE, you must handle each of these tasks by using tools contained in the Java Software Development Kit (SDK) and WebSphere Application Server. For more information on the tools used to create an EJB module in the EJB server programming environment, see [Tools for developing and deploying enterprise beans](#).

Making bean components part of a Java package

You determine the best way to allocate your enterprise beans to Java packages. A Java package can contain one or more enterprise beans. The example Account and Transfer beans are stored in separate packages. All of the Java source files that make up the Account bean contain the following package statement:

```
package com.ibm.ejs.doc.account;
```

All of the Java source files that make up the Transfer bean contain the following package statement:

```
package com.ibm.ejs.doc.transfer;
```

Creating an EJB module and deployment descriptor

An EJB module contains one or more deployable enterprise beans. It also contains a deployment descriptor that provides information about each enterprise bean and instructions for the container on how to handle all enterprise beans in the module. The deployment descriptor is stored in an XML file.

During creation of the EJB module, you specify the files for each enterprise bean to be included in the module. These files include:

- The class files associated with each component of the enterprise bean.
- Any additional classes and files associated with the enterprise bean; for example: user-defined exception classes, properties files, and resource bundle classes.

You also specify other information about the bean, such as references to other enterprise beans, resource connection factories, and security roles. After defining the enterprise beans to be included in the module, you specify application assembly instructions that apply to the module as a whole. Both bean and module information are used to create a deployment descriptor. See [The deployment descriptor](#) for a list of deployment descriptor settings and attributes.

Developing EJB clients

An enterprise bean can be accessed by all of the following types of EJB clients in both EJB server environments:

- Java servlets. For more information about writing Java servlets that use enterprise beans, see [Developing servlets that use enterprise beans](#).
- Java Server Pages (JSP). For more information about writing JSP, consult a commercially available book.
- Java applications that use remote method invocation (RMI). For more information on writing Java applications, consult a commercially available book.
- Other enterprise beans. For example, the Transfer session bean acts as a client to the Account bean, as described in [Developing enterprise beans](#).

It is recommended that you avoid accessing EJB entity beans from client or servlet code. Instead, wrap and access EJB entity beans from EJB session beans. This improves performance in two ways:

- It reduces the number of remote method calls. When the client application accesses the entity bean directly, each getter method is a remote call. A wrapping session bean can access the entity bean locally, and collect the data in a structure, which it returns by value.
- It provides an outer transaction context for the EJB entity bean. An entity bean synchronizes its state with its underlying data store at the completion of each transaction. When the client application accesses the entity bean directly, each getter method becomes a complete transaction. A store and a load action follow each method. When the session bean wraps the entity bean to provide an outer transaction context, the entity bean synchronizes its state when the outer session bean reaches a transaction boundary.

Except for the basic programming tasks described in this chapter, creating a Java servlet, JSP, or Java application that is a client to an enterprise bean is not very different from designing standard versions of these types of Java programs. This chapter assumes that you understand the basics of writing a Java servlet, a Java application, or a JSP file.

Except where noted, all of the code described in this chapter is taken from the example Java application named TransferApplication. This Java application and the other EJB clients available with the documentation example code are explained in [Information about the examples described in the documentation](#).

To access and manipulate an enterprise bean in any of the Java-based EJB client types listed previously, the EJB client must do the following:

- Import the Java packages required for naming, remote method invocation (RMI), and enterprise bean interaction.
- Get a reference to an instance of the bean's EJB object by using the Java Naming and Directory Interface (JNDI). For more information, see [Creating and getting a reference to a bean's EJB object](#).
- Handle invalid EJB objects when using session beans. For more information, see [Handling an invalid EJB object for a session bean](#).
- Remove session EJB objects when they are no longer required or remove entity EJB objects when the associated data in the data source must be removed. For more information, see [Removing a bean's EJB object](#).

In addition, an EJB client can participate in the transactions associated with enterprise beans used by the client. For more information, see [Managing transactions in an EJB client](#).

Importing required Java packages

Although the Java packages required for any particular EJB client vary, the following packages are required by all EJB clients:

- java.rmi -- This package contains most of the classes required for remote method invocation (RMI).
- javax.rmi -- This package contains the PortableRemoteObject class required to get a reference to an EJB object.
- java.util -- This package contains various Java utility classes, such as Properties, Hashtable, and Enumeration used in a variety of ways throughout all enterprise beans and EJB clients.
- javax.ejb -- This package contains the classes and interfaces defined in the EJB specification.
- javax.naming -- The package contains the classes and interfaces defined in the Java Naming and Directory Interface (JNDI) specification and is used by clients to get references to EJB objects.

- The package or packages containing the enterprise beans with which the client interacts.

The Java client object request broker (ORB), which is automatically initialized in EJB clients, does not support dynamic download of implementation bytecode from the server to the client. As a result, all classes required by the EJB client at runtime must be available from the files and directories identified in the client's CLASSPATH environment variable. For information on the JAR files required by EJB clients, see [Setting the CLASSPATH environment variable in the EJB server environment](#). You can install needed files on your client machine by doing a WebSphere Application Server installation on the machine. Select the **Developer's Client Files** option. You also need to make sure that the ioser and ioserx executable files are accessible on your client machine; these files are normally part of the Java install. If you are using a Windows System, make sure that EJB clients can locate the ioser.dll library file at run time. [Figure 26](#) shows the import statements for the example Java application com.ibm.ejs.doc.client.TransferApplication. In addition to the required Java packages mentioned previously, the example application imports the com.ibm.ejs.doc.transfer package because the application communicates with a Transfer bean. The example application also imports the InsufficientFundsException class contained in the same package as the Account bean.

Figure 26. Code example: The import statements for the Java application TransferApplication

```
...
import java.awt.*;
import java.awt.event.*;
import java.util.*;
import java.rmi.*
...
import javax.naming.*;
import javax.ejb.*;
import javax.rmi.PortableRemoteObject;
...
import com.ibm.ejs.doc.account.InsufficientFundsException;
import com.ibm.ejs.doc.transfer.*;
...
public class TransferApplication extends Frame implements
    ActionListener, WindowListener {
    ...
}
```

Creating and getting a reference to a bean's EJB object

To invoke a bean's business methods, a client must create or find an EJB object for that bean. After the client has created or found this object, it can invoke methods on it in the standard way.

To create or find an instance of a bean's EJB object, the client must do the following:

1. Locate and create an EJB home object for that bean. For more information, see [Locating and creating an EJB home object](#).
2. Use the EJB home object to create or (for entity beans only) find an instance of the bean's EJB object. For more information, see [Creating an EJB object](#).

The TransferApplication client contains one reference to a Transfer EJB object, which the application uses to invoke all of the methods on the Transfer bean. When using session beans in Java applications, it is a good idea to make the reference to the EJB object a class-level variable rather than a variable that is local to a method. This allows your EJB client to repeatedly invoke methods on the same EJB object rather than having to create a new object each time the client invokes a session bean method. As discussed in [Threading issues](#), this approach is not recommended for servlets, which must be designed to handle multiple threads.

Locating and creating an EJB home object

JNDI is used to find the name of an EJB home object. The properties that an EJB client uses to initialize JNDI and find an EJB home object vary across EJB server implementations. To make an enterprise bean more portable between EJB server implementations, it is recommended that you externalize these properties in environment variables, properties files, or resource bundles rather than hard code them into your enterprise bean or EJB client code.

The example Transfer bean uses environment variables as discussed in [Implementing the ejbCreate methods](#). The TransferApplication uses a resource bundle contained in the com.ibm.ejs.doc.client.ClientResourceBundle.class file. To initialize a JNDI name service, an EJB client must set the appropriate values for the following JNDI properties:

javax.naming.Context.PROVIDER_URL

This property specifies the host name and port of the name server used by the EJB client. The property value must have the following format: `iiop://hostname:port`, where *hostname* is the IP address or hostname of the machine on which the name server runs and *port* is the port number on which the name server listens.

For example, the property value `iiop://bankserver.mybank.com:9019` directs an EJB client to look for a name server on the host named bankserver.mybank.com listening on port 9019. The property value `iiop://bankserver.mybank.com` directs an EJB client to look for a name server on the host named bankserver.mybank.com at port number 900. The property value `iiop:///` directs an EJB client to look for a name server on the local host listening on port 900. If not specified, this property defaults to the local host and port number 900, which is the same as specifying `iiop:///`. The port number used by the name service can be changed by using the administrative interface.

javax.naming.Context.INITIAL_CONTEXT_FACTORY

This property identifies the actual name service that the EJB client must use. This property must be set to `com.ibm.ejs.ns.jndi.CNInitialContextFactory`.

Locating an EJB home object is a two-step process:

1. Create a `javax.naming.InitialContext` object. For more information, see [Creating an InitialContext object](#).
2. Use the `InitialContext` object to create the EJB home object. For more information, see [Creating EJB home object](#).

Creating an InitialContext object

[Figure 27](#) shows the code required to create the `InitialContext` object. To create this object, construct a `java.util.Properties` object, add values to the `Properties` object, and then pass the object as the argument to the `InitialContext` constructor. In the TransferApplication, the value of each property is obtained from the resource bundle class named `com.ibm.ejs.doc.client.ClientResourceBundle`, which stores all of the locale-specific variables required by the TransferApplication. (This class also stores the variables used by the other EJB clients contained in the documentation example, described in [Information about the examples described in the documentation](#)). The resource bundle class is instantiated by calling the `ResourceBundle.getBundle` method. The values of variables within the resource bundle class are extracted by calling the `getString` method on the *bundle* object.

The `createTransfer` method of the TransferApplication can be called multiple times as explained in [Handling an invalid EJB object for a session bean](#). However, after the `InitialContext` object is created once, it remains good for the life of the client session. Therefore, the code required to create the `InitialContext` object is placed within an if statement that determines if the reference to the `InitialContext` object is null. If the reference is null, the `InitialContext` object is created; otherwise, the reference can be reused on subsequent creations of the EJB object.

Figure 27. Code example: Creating the InitialContext object

```
...
public class TransferApplication extends Frame implements ActionListener,
    WindowListener {
    ...
    private InitialContext ivjInitContext = null;
    private Transfer ivjTransfer = null;
    private ResourceBundle bundle = ResourceBundle.getBundle(
        "com.ibm.ejs.doc.client.ClientResourceBundle");
    ...
    private String nameService = null;
    private String accountName = null;
    private String providerUrl = null;
    ...
    private Transfer createTransfer() {
        TransferHome transferHome = null;
        Transfer transfer = null;
        // Get the initial context
        if (ivjInitContext == null) {
```

```

    try {
        Properties properties = new Properties();
        // Get location of name service
        properties.put(javax.naming.Context.PROVIDER_URL,
            bundle.getString("providerUrl"));
        // Get name of initial context factory
        properties.put(javax.naming.Context.INITIAL_CONTEXT_FACTORY,
            bundle.getString("nameService"));

        ...
        ivjInitContext = new InitialContext(properties);
    } catch (Exception e) { // Error getting the initial context
        ...
    }
}

...
// Look up the home interface using the JNDI name
...
// Create a new Transfer object to return
...
return transfer;
}

```

Creating EJB home object

After the `InitialContext` object (*ivjInitContext*) is created, the application uses it to create the EJB home object, as shown in [Figure 28](#). This creation is accomplished by invoking the `lookup` method, which takes the JNDI name of the enterprise bean in String form and returns a `java.lang.Object` object. The JNDI name specified in the deployment descriptor is used.

The example `TransferApplication` gets the JNDI name of the `Transfer` bean from the `ClientResourceBundle` class. After an object is returned by the `lookup` method, the static method `javax.rmi.PortableRemoteObject.narrow` is used to obtain an EJB home object for the specified enterprise bean. The `narrow` method takes two parameters: the object to be narrowed and the class of the EJB home object to be returned by the `narrow` method. The object returned by the `javax.rmi.PortableRemoteObject.narrow` method is cast to the class associated with the home interface.

Figure 28. Code example: Creating the EJBHome object

```

private Transfer createTransfer() {
    TransferHome transferHome = null;
    Transfer transfer = null;
    // Get the initial context
    ...
    // Look up the home interface using the JNDI name
    try {
        java.lang.Object homeObject = ivjInitContext.lookup(
            bundle.getString("transferName"));
        transferHome = (TransferHome)javax.rmi.PortableRemoteObject.narrow(
            homeObject, TransferHome.class);
    } catch (Exception e) { // Error getting the home interface
        ...
    }
    ...
    // Create a new Transfer object to return
    ...
    return transfer;
}

```

Creating an EJB object

After the EJB home object is created, it is used to create the EJB object. [Figure 29](#) shows the code required to create the EJB object by using the EJB home object. A `create` method is invoked to create an EJB object or (for entity beans only) a `finder` method is invoked to find an existing EJB object. Because the `Transfer` bean is a stateless session bean, the only choice is the default `create` method.

Figure 29. Code example: Creating the EJB object

```
private Transfer createTransfer() {
    TransferHome transferHome = null;
    Transfer transfer = null;
    // Get the initial context
    ...
    // Look up the home interface using the JNDI name
    ...
    // Create a new Transfer object to return
    try {
        transfer = transferHome.create();
    } catch (Exception e) { // Error creating Transfer object
        ...
    }
    ...
    return transfer;
}
```

Handling an invalid EJB object for a session bean

Because session beans are ephemeral, the client cannot depend on a session bean's EJB object to remain valid. A reference to an EJB object for a session bean can become invalid if the EJB server fails or is restarted or if the session bean times out due to inactivity. (The reference to an entity bean's EJB object is always valid until that object is removed.) Therefore, the client of a session bean must contain code to handle a situation in which the EJB object becomes invalid.

An EJB client can determine if an EJB object is valid by placing all method invocations that use the reference inside of a try/catch block that specifically catches the `java.rmi.NoSuchObjectException`, in addition to any other exceptions that the method needs to handle. The EJB client can then invoke the code to handle this exception.

You determine how to handle an invalid EJB object. The example `TransferApplication` creates a new `Transfer` EJB object if the one it is currently using becomes invalid. The code to create a new EJB object when the old one becomes invalid is the same code used to create the original EJB object and is described in [Creating and getting a reference to a bean's EJB object](#). For the example `TransferApplication` client, this code is contained in the `createTransfer` method.

[Figure 30](#) shows the code used to create the new EJB object in the `getBalance` method of the example `TransferApplication`. The `getBalance` method contains the local boolean variable `sessionGood`, which is used to specify the validity of the EJB object referenced by the variable `ivjTransfer`. The `sessionGood` variable is also used to determine when to break out of the do-while loop. The `sessionGood` variable is initialized to false because the `ivjTransfer` can reference an invalid EJB object when the `getBalance` method is called. If the `ivjTransfer` reference is valid, the `TransferApplication` invokes the `Transfer` bean's `getBalance` method and returns the balance. If the `ivjTransfer` reference is invalid, the `NoSuchObjectException` is caught, the `TransferApplication`'s `createTransfer` method is called to create a new `Transfer` EJB object reference, and the `sessionGood` variable is set to false so that the do-while loop is repeated with the new valid EJB object. To prevent an infinite loop, the `sessionGood` variable is set to true when any other exception is thrown.

Figure 30. Code example: Refreshing the EJB object reference for a session bean

```
private float getBalance(long acctId) throws NumberFormatException, RemoteException,
    FinderException {
    // Assume that the reference to the Transfer session bean is no good
    ...
    boolean sessionGood = false;
    float balance = 0.0f;
    do {
        try {
            // Attempt to get a balance for the specified account
            balance = ivjTransfer.getBalance(acctId);
            sessionGood = true;
            ...
        } catch(NoSuchObjectException ex) {
            createTransfer();
        }
    } while (!sessionGood);
}
```

```

        sessionGood = false;
    } catch (RemoteException ex) {
        // Server or connection problem
        ...
    } catch (NumberFormatException ex) {
        // Invalid account number
        ...
    } catch (FinderException ex) {
        // Invalid account number
        ...
    }
} while (!sessionGood);
return balance;
}

```

Removing a bean's EJB object

When an EJB client no longer needs a stateful session EJB object, the EJB client should remove that object. Instances of stateful session beans have affinity to specific clients. They will remain in the container until they are explicitly removed by the client, or removed by the container when they time out. Meanwhile, the container might need to passivate inactive stateful session beans to disk. This requires overhead for the container and impacts performance of the application. If the passivated session bean is subsequently required by the application, the container activates it by restoring it from disk. By explicitly removing stateful session beans when finished with them, applications can decrease the need for passivation and minimize container overhead.

You remove entity EJB objects *only* when you want to remove the information in the data source with which the entity EJB object is associated.

To remove an EJB object, invoke the remove method on the object. As discussed in [Creating and getting a reference to a bean's EJB object](#), the TransferApplication contains only one reference to a Transfer EJB object that is created when the application is initialized.

[Figure 31](#) shows how the example Transfer EJB object is removed in the TransferApplication in the killApp method. To parallel the creation of the Transfer EJB object when the TransferApplication is initialized, the application removes the final EJB object associated with *ivjTransfer* reference right before closing the application's GUI window. The killApp method closes the window by invoking the dispose method on itself.

Figure 31. Code example: Removing a session EJB object

```

...
private void killApp() {
    try {
        ivjTransfer.remove();
        this.dispose();
        System.exit(0);    } catch (Throwable ivjExc) {
        ...
    }
}

```

Managing transactions in an EJB client

In general, it is practical to design your enterprise beans so that all transaction management is handled at the enterprise bean level. In a strict three-tier, distributed application, this is not always possible or even desirable. However, because the middle tier of an EJB application can include two subcomponents--session beans and entity beans--it is much easier to design the transactional management completely within the application server tier. Of course, the resource manager tier must also be designed to support transactions.

Note:

EJB clients that access entity beans with CMP that use Host On-Demand (HOD) or the External Call Interface (ECI) for CICS or IMS applications must begin a transaction before invoking a method on these entity beans. This restriction

is required because these types of entity beans must use the Mandatory transaction attribute.

Nevertheless, it is still possible to program an EJB client (that is not an enterprise bean) to participate in transactions for those specialized situations that require it. To participate in a transaction, the EJB client must do the following:

1. Obtain a reference to the `javax.transaction.UserTransaction` interface by using JNDI as defined in the Java Transaction Application Programming Interface (JTA).
2. Use the object reference to invoke any of the following methods:
 - `begin`--Begins a transaction. This method takes no arguments and returns `void`.
 - `commit`--Attempts to commit a transaction; assuming that nothing causes the transaction to be rolled back, successful completion of this method commits the transaction. This method takes no arguments and returns `void`.
 - `getStatus`--Returns the status of the referenced transaction. This method takes no arguments and returns `int`; if no transaction is associated with the reference, `STATUS_NO_TRANSACTION` is returned. The following are the valid return values for this method:
 - `STATUS_ACTIVE`--Indicates that transaction processing is still in progress.
 - `STATUS_COMMITTED`--Indicates that a transaction has been committed and the effects of the transaction have been made permanent.
 - `STATUS_COMMITTING`--Indicates that a transaction is in the process of committing (that is, the transaction has started committing but has not completed the process).
 - `STATUS_MARKED_ROLLBACK`--Indicates that a transaction is marked to be rolled back.
 - `STATUS_NO_TRANSACTION`--Indicates that a transaction does not exist in the current transaction context.
 - `STATUS_PREPARED`--Indicates that a transaction has been prepared but not completed.
 - `STATUS_PREPARING`--Indicates that a transaction is in the process of preparing (that is, the transaction has started preparing but has not completed the process).
 - `STATUS_ROLLEDBACK`--Indicates that a transaction has been rolled back.
 - `STATUS_ROLLING_BACK`--Indicates that a transaction is in the process of rolling back (that is, the transaction has started rolling back but has not completed the process).
 - `STATUS_UNKNOWN`--Indicates that the status of a transaction is unknown.
 - `rollback`--Rolls back the referenced transaction. This method takes no arguments and returns `void`.
 - `setRollbackOnly`--Specifies that the only possible outcome of the transaction is for it to be rolled back. This method takes no arguments and returns `void`.
 - `setTransactionTimeout`--Sets the timeout (in seconds) associated with the transaction. If some transaction participant has not specifically set this value, a default timeout is used. This method takes a number of seconds (as type `int`) and returns `void`.

Figure 32 provides an example of an EJB client creating a reference to a `UserTransaction` object and then using that object to set the transaction timeout, begin a transaction, and attempt to commit the transaction. (The source code for this example is *not* available with the example code provided with this document.) Notice that the client does a simple type cast of the lookup result, rather than invoking a narrow method as required with other JNDI lookups. In both EJB server environments, the JNDI name of the `UserTransaction` interface is `java:comp/UserTransaction`.

Figure 32. Code example: Managing transactions in an EJB client

```
...
import javax.transaction.*;
...
// Use JNDI to locate the UserTransaction object
Context initialContext = new InitialContext();
UserTransaction tranContext = (
    UserTransaction)initialContext.lookup("java:comp/UserTransaction");
// Set the transaction timeout to 30 seconds
tranContext.setTransactionTimeout(30);
...
// Begin a transaction
tranContext.begin();
// Perform transaction work invoking methods on enterprise bean references
```

```
...  
// Call for the transaction to commit  
tranContext.commit();
```


Developing servlets that use enterprise beans

A servlet is a Java application that enables users to access Web server functionality. To use servlets, a Web server is required. The WebSphere Application Server plugs into a number of commonly used Web servers. The IBM HTTP Server with the Advanced Application Server. For more information, consult the Advanced Edition InfoCenter.

Java servlets can be combined with enterprise beans to create powerful EJB applications. This chapter describes how to use enterprise beans within a servlet. The example CreateAccount servlet, which uses the example Account bean, is used to illustrate the concepts discussed in this chapter. The example servlet and enterprise bean discussed in this chapter are explained in [Information about the examples described in the documentation](#).

An overview of standard servlet methods

Usually, a servlet is invoked from an HTML form on the user's browser. The first time the servlet is invoked, the servlet's init method is run to perform any initializations required at startup. For the first and all subsequent invocations of the servlet, the doGet method (or, alternatively, the doPost method) is run. Within the doGet method (or the doPost method), the servlet gets the information provided by the user on the HTML form and uses that information to perform work on the server and access server resources.

The servlet then prepares a response and sends the response back to the user. After a servlet is loaded, it can handle multiple simultaneous user requests. Multiple request threads can invoke the doGet (or doPost) method at the same time, so the servlet needs to be made thread safe.

When a servlet shuts down, the destroy method of the servlet is run in order to perform any needed shutdown processing.

Writing an HTML page that embeds a servlet

[Figure 33](#) shows the HTML file (named create.html) used to invoke the CreateAccount servlet. The HTML form is used to specify the account number for the new account, its type (checking or savings), and its initial balance. The request is passed to the doGet method of the servlet, where the servlet is identified with its full Java package name, as shown in the example.

Figure 33. Code example: Content of the create.html file used to access the CreateAccount servlet

```
<html>
<head>
<title>Create a new Account</title>
</head>
<body>
<h1 align="center">Create a new Account</h1>
<form method="get"
action="/servlet/com.ibm.ejs.doc.client.CreateAccount">
<table border align="center">
<!-- specify a new account number -->
<tr bgcolor="#cccccc">
<td align="right">Account Number:</td>
<td colspan="2"><input type="text" name="account" size="20"
maxlength="10">
</tr>
<!-- specify savings or checking account -->
...
<!-- specify account starting balance -->
...
<!-- submit information to servlet -->
...
<input type="submit" name="submit" value="Create">
...
<!-- message area -->
...
```

```
</form>
</body>
</html>
```

The HTML response from the servlet is designed to produce a display identical to create.html, enabling the user to continue creating new accounts. [Figure 34](#) shows what create.html looks like on a browser.

Figure 34. The initial form and output of the CreateAccount servlet

The screenshot shows a web browser window titled "Create a new Account - Microsoft Internet Explorer". The browser's menu bar includes File, Edit, View, Go, Favorites, and Help. The toolbar contains Back, Forward, Stop, Refresh, Home, Search, and Links buttons. The main content area displays the title "Create a new Account" in a large, bold, serif font. Below the title is a form with three rows: "Account Number:" followed by a text input field; "Type:" followed by two radio buttons labeled "savings" (which is selected) and "checking"; and "Starting Balance:" followed by a text input field. Below the form is a "Create" button. At the bottom of the form area, the text "Enter information, press 'Create'" is displayed. The browser's status bar at the bottom shows "My Computer".

Developing the servlet

This section discusses the basic code required by a servlet that interacts with an enterprise bean. [Figure 35](#) shows the basic outline of the code that makes up the CreateAccount servlet. As shown in the example, the CreateAccount servlet extends the javax.servlet.http.HttpServlet class and implements an init method and a doGet method.

Figure 35. Code example: The CreateAccount class

```
package com.ibm.ejs.doc.client;
// General enterprise bean code.
import java.rmi.RemoteException;
import javax.ejb.DuplicateKeyException;
// Enterprise bean code specific to this servlet.
import com.ibm.ejs.doc.account.AccountHome;
import com.ibm.ejs.doc.account.AccountKey;
import com.ibm.ejs.doc.account.Account;
// Servlet related.
import javax.servlet.*;
import javax.servlet.http.*;
// JNDI (naming).
import javax.naming.*; // for Context, InitialContext, NamingException
// Miscellaneous:
import java.util.*;
```

```

import java.io.*;
...
public class CreateAccount extends HttpServlet {
    // Variables
    ...
    public void init(ServletConfig config) throws ServletException {
        ...
    }
    public void doGet(HttpServletRequest req, HttpServletResponse res)
    throws ServletException, IOException {
        // --- Read and validate user input, initialize. ---
        ...
        // --- If input parameters are good, try to create account. ---
        ...
        // --- Prepare message to accompany response. ---
        ...
        // --- Prepare and send HTML response. ---
        ...
    }
}

```

The servlet's instance variables

Figure 36 shows the instance variables used in the CreateAccount servlet. The *nameService*, *accountName*, and *providerUrl* variables are used to specify the property values required during JNDI lookup. These values are obtained from the ClientResourceBundle class as described in [Creating and getting a reference to a bean's EJB object](#).

The CreateAccount class also initializes the string constants that are used to create the HTML response sent back to the user. (Only three of these variables are shown, but there are many of them). The init method in the CreateAccount servlet provides a way to read strings from a resource bundle to override these US English defaults in order to provide a response in a different national language. The instance variable *accountHome* is used by all client requests to create a new Account bean instance. The *accountHome* variable is initialized in the init method as shown in Figure 36.

Figure 36. Code example: The instance variables of the CreateAccount class

```

...
public class CreateAccount extends HttpServlet {
    // Variables for finding the home
    private String nameService = null;
    private String accountName = null;
    private String providerURL = null;
    private ResourceBundle bundle = ResourceBundle.getBundle(
        "com.ibm.ejs.doc.client.ClientResourceBundle");
    // Strings for HTML output - US English defaults shown.
    static String title = "Create a new Account";
    static String number = "Account Number:";
    static String type = "Type:";
    ...
    // Variable for accessing the enterprise bean.
    private AccountHome accountHome = null;
    ...
}

```

The servlet's init method

The init method of the CreateAccount servlet is shown in Figure 37. The init method is run once, the first time a request is processed by the servlet, after the servlet is started. Typically, the init method is used to do any one-time initializations for a servlet. For example, the default US English strings used in preparing the HTML response can be replaced with another national language. The init method is also the best place to initialize the value of references to the home interface of any enterprise beans used by the servlet. In the CreateAccount's init method, the *accountHome* variable is initialized to

reference the EJB home object of the Account bean.

As in other types of EJB clients, the properties required to do a JNDI lookup are specific to the EJB implementation. Therefore, these properties are externalized in a properties file or a resource bundle class. For more information on these properties, see [Creating and getting a reference to a bean's EJB object](#).

Note that in the CreateAccount servlet, a Hashtable object is used to store the properties required to do a JNDI lookup whereas a Properties object is used in the TransferApplication. Both of these classes are valid for storing these properties.

Figure 37. Code example: The init method of the CreateAccount servlet

```
// Variables for finding the EJB home object
private String nameService = null;
private String accountName = null;
private String providerURL = null;
private ResourceBundle bundle = ResourceBundle.getBundle(
    "com.ibm.ejs.doc.client.TransferResourceBundle");

...
public void init(ServletConfig config) throws ServletException {
    super.init(config);

    ...
    try {
        // Get NLS strings from an external resource bundle
        ...
        createTitle = bundle.getString("createTitle");
        number = bundle.getString("number");
        type = bundle.getString("type");
        ...
        //Get values for the naming factory and home name.
        nameService = bundle.getString("nameService");
        accountName = bundle.getString("accountName");
        providerURL = bundle.getString("providerURL");
    }
    catch (Exception e) {
        ...
    }
    // Get home object for access to Account enterprise bean.
    Hashtable env = new Hashtable();
    env.put(Context.INITIAL_CONTEXT_FACTORY, nameService);
    try {
        // Create the initial context.
        Context ctx = new InitialContext(env);
        // Get the home object.
        Object homeObject = ctx.lookup(accountName);
        // Get the AccountHome object.
        accountHome = (AccountHome) javax.rmi.PortableRemoteObject.narrow(
            homeObject, AccountHome.class);
    }
    // Determine cause of failure.
    catch (NamingException e) {
        ...
    }
    catch (Exception e) {
        ...
    }
}
```

Note:

Although the init method is a good place to obtain references to EJB home objects, it is not a good place to create enterprise beans or access other beans that might be protected with WebSphere security. Depending upon the authorization policy on the protected objects, creating or accessing these objects from within the init method could fail for authentication or authorization reasons because they were not accessed with the proper security credentials.

Creating or accessing protected objects should be done after the init method, in one of the servlet's doXXX methods.

The servlet's doGet method

The doGet method is invoked for every servlet request. In the CreateAccount servlet, the method does the following tasks to manage user input. These tasks are fairly standard for this method:

- Read the user input from the HTML form and decide if the input is valid--for example, whether the user entered a valid number for an initial balance.
- Perform the initializations required for each request.

Figure 38 shows the parts of the doGet method that handle user input. Note that the *req* variable is used to read the user input from the HTML form. The *req* variable is a `javax.servlet.http.HttpServletRequest` object passed as one of the arguments to the doGet method.

Figure 38. Code example: The doGet method of the CreateAccount servlet

```
public void doGet (HttpServletRequest req, HttpServletResponse res)
    throws ServletException, IOException {
    // --- Read and validate user input, initialize. ---
    // Error flags.
    boolean accountFlag = true;
    boolean balanceFlag = true;
    boolean inputFlag = false;
    boolean createFlag = true;
    boolean duplicateFlag = false;
    // Datatypes used to create new account bean.
    AccountKey key;
    int typeAcct = 0;
    String typeString = "0";
    float initialBalance = 0;
    // Read input parameters from HTML form.
    String[] accountArray = req.getParameterValues("account");
    String[] typeArray = req.getParameterValues("type");
    String[] balanceArray = req.getParameterValues("balance");
    // Convert input parameters to needed datatypes for new account.
    // (account)
    long accountLong = 0;
    ...
    key = new AccountKey(accountLong);
    // (type)
    if (typeArray[0].equals("1")) {
        typeAcct = 1;           // Savings account.
        typeString = "savings";
    }
    else if (typeArray[0].equals("2")) {
        typeAcct = 2;           // Checking account
        typeString = "checking";
    }
    // (balance)
    try {
        initialBalance = (Float.valueOf(balanceArray[0])).floatValue();
    } catch (Exception e) {
        balanceFlag = false;
    }
    ...
    // --- If input parameters are good, try to create account bean. ---
    ...
    // --- Prepare message to accompany response. ---
    ...
    // --- Prepare and send HTML response. ---
```

```

    ...
}

```

Creating an enterprise bean

If the user input is valid, the `doGet` method attempts to create a new account based on the user input as shown in [Figure 39](#). Besides the initialization of the home object reference in the `init` method, this is the only other piece of code that is specific to the use of enterprise beans in a servlet.

Figure 39. Code example: Creating an enterprise bean in the `doGet` method

```

public void doGet(HttpServletRequest req, HttpServletResponse res)
    throws ServletException, IOException {
    // --- Read and validate user input, initialize ---.
    ...
    // --- If input parameters are good, try to create account bean. ---
    if (accountFlag && balanceFlag) {
        inputFlag = true;
        try {
            // Create the bean.
            Account account = accountHome.create(key, typeAcct, initialBalance);
        }
        // Determine cause of failure.
        catch (RemoteException e) {
            ...
        }
        catch (DuplicateKeyException e) {
            ...
        }
        catch (Exception e) {
            ...
        }
    }
    // --- Prepare message to accompany response. ---
    ...
    // --- Prepare and send HTML response. ---
    ...
}

```

Determining the content of the user response

Next, the `doGet` method prepares a response message to be sent to the user. There are three possible responses:

- The user input was not valid.
- The user input was valid, but the account was not created for some reason.
- The account was created successfully. If the previous two errors do not occur, this response is prepared.

[Figure 40](#) shows the code used by the servlet to determine which response to send to the user. If no errors are encountered, then the response indicates success.

Figure 40. Code example: Determining a user response in the `doGet` method

```

public void doGet(HttpServletRequest req, HttpServletResponse res)
    throws ServletException, IOException {
    // --- Read and validate user input, initialize. ---
    ...
    // --- If input parameters are good, try to create account bean. ---
    ...
    // --- Prepare message to accompany response. ---
    ...
    String messageLine = "";
}

```

```

if (inputFlag) {
    // If you are here, the client input is good.
    if (createFlag) {
        // New account enterprise bean was created.
        messageLine = createdaccount + " " + accountArray[0] + ", " +
            createdtype + " " + typeString + ", " +
            createdbalance + " " + balanceArray[0];
    }
    else if (duplicateFlag) {
        // Account with same key already exists.
        messageLine = failureexists + " " + accountArray[0];
    }
    else {
        // Other reason for failure.
        messageLine = failureinternal + " " + accountArray[0];
    }
}
else {
    // If you are here, something was wrong with the client input.
    String separator = "";
    if (!accountFlag) {
        messageLine = failureaccount + " " + accountArray[0];
        separator = ", ";
    }
    if (!balanceFlag) {
        messageLine = messageLine + separator +
            failurebalance + " " + balanceArray[0];
    }
    // --- Prepare and send HTML response. ---
    ...
}

```

Sending the user response

With the type of response determined, the `doGet` method then prepares the full HTML response and sends it to the user's browser, incorporating the appropriate message. Relevant parts of the full HTML response are shown in [Figure 41](#). The `res` variable is used to pass the response back to the user. This variable is an `HttpServletResponse` object passed as an argument to the `doGet` method. The response code shown here mixes both display (HTML) and content in one servlet. You can separate the display and the content by using JavaServer Pages (JSP). A JSP allows the display and content to be developed and maintained separately.

Figure 41. Code example: Responding to the user in the `doGet` method

```

public void doGet(HttpServletRequest req, HttpServletResponse res)
    throws ServletException, IOException {
    // --- Read and validate user input, initialize. ---
    ...
    // --- If input parameters are good, try to create account bean. ---
    ...
    // --- Prepare message to accompany response. ---
    ...
    // --- Prepare and send HTML response. ---
    // HTML returned looks like initial HTML that invoked this servlet.
    // Message line says whether servlet was successful or not.
    res.setContentType("text/html");
    res.setHeader("Pragma", "no-cache");
    res.setHeader("Cache-control", "no-cache");
    PrintWriter out = res.getWriter();
    out.println("<html>");
    ...
    out.println("<title> " + createTitle + "</title>");
}

```

```
    ...  
    out.println( " </html>" );  
}
```

Threading issues

Except for the instance variable required to get a reference to the Account bean's home interface and to support multiple languages (which remain unchanged for all user requests), all other variables used in the CreateAccount servlet are local to the doGet method. Each request thread has its own set of local variables, so the servlet can handle simultaneous user requests.

As a result, the CreateAccount servlet is thread safe. By taking a similar approach to servlet design, you can also make your servlets thread safe.

Tools for developing and deploying enterprise beans

There are two basic approaches to developing and deploying enterprise beans:

- You can use one of the available integrated development environments (IDEs) such as IBM VisualAgeTM for Java Enterprise Edition. IDE tools automatically generate significant parts of the enterprise bean code and contain integrated tools for packaging and testing enterprise beans. VisualAge for Java is the recommended development tool. For more information on using VisualAge for Java, see [Using VisualAge for Java](#).
 - You can use the tools available in the Java Software Development Kit (SDK) and the Advanced Application Server. For more information, see [Developing and deploying enterprise beans](#).
-

Using VisualAge for Java

Before you can develop enterprise beans in VisualAge for Java, you must set up the EJB development environment. You need to perform this setup task only once. This setup procedure directs VisualAge for Java to import all of the classes and interfaces required to develop enterprise beans.

After generating an enterprise bean, you complete its development by following these general steps:

1. Implement the enterprise bean class.
2. Create the required abstract methods in the bean's home and remote interfaces by promoting the corresponding methods in the bean class to the appropriate interface.
3. For entity beans, do the following:
 - a. Create any additional finder methods in the home interface by using the appropriate menu items.
 - b. Create a finder helper interface, if required.
4. Create the EJB module and corresponding deployment descriptor.
5. Generate the deployment code for the bean.

VisualAge for Java contains a complete WebSphere Application Server run time environment and a mechanism to generate a test client to test your enterprise beans. For much more detailed information on developing enterprise beans in VisualAge for Java, refer to the VisualAge for Java documentation.

Developing and deploying enterprise beans

If you have decided to develop enterprise beans *without* an IDE, you need at minimum the following tools:

- An ASCII text editor. (You can also use a Java development tool that does not support enterprise bean development.)
- The SDK Java compiler (**javac**) and Java Archiving tool (**jar**).
- The WebSphere Application Assembly Tool and the WebSphere Administrative Console.

This section describes steps you can follow to develop enterprise beans by using these tools. The following tasks are involved in the development of enterprise beans:

1. Ensure that you have installed and configured the prerequisite software to develop, deploy, and run enterprise beans in the EJB server environment. For more information, see [Installing and configuring the software for the EJB server](#).
2. Set the CLASSPATH environment variable required by different components of the EJB server environment. For more information, see [Setting the CLASSPATH environment variable in the EJB](#)

[server environment](#).

3. Write and compile the components of the enterprise bean. For more information, see [Creating the components of an enterprise bean](#).
4. (*Entity beans with CMP only*) Create a finder helper interface for each entity bean with CMP that contains specialized finder methods (other than the `findByPrimaryKey` method). For more information, see [Creating finder logic in the EJB server](#).
5. Create an EJB module and corresponding deployment descriptor by using the Application Assembly Tool. For more information, see [Creating an EJB module](#).
6. (*Entity beans only*) Create a database schema to enable storage of the entity bean's persistent data in a database. For more information, see [Creating a database for use by entity beans](#).
7. Generate deployment code for the EJB module by using the Application Assembly Tool. For more information, see the WebSphere InfoCenter and the online help available with the Application Assembly Tool.
8. Install the EJB module into an EJB server and start the server by using the WebSphere Administrative Console.

Installing and configuring the software for the EJB server

You must ensure that you have installed and configured the following prerequisite software products before you can begin developing enterprise beans and EJB clients with the EJB server:

- WebSphere Application Server Advanced Edition
- One or more of the following databases for use by entity beans with container-managed persistence (CMP):
 - DB2
 - Oracle
 - Sybase
 - Informix
 - Microsoft SQL Server
 - InstantDB
- The Java Software Development Kit (SDK)

For information on the appropriate version numbers of these products and instructions for setting up the environment, see the WebSphere InfoCenter.

Setting the CLASSPATH environment variable in the EJB server environment

In addition to the `classes.zip` file contained in the SDK, the following WebSphere JAR files must be appended to the CLASSPATH environment variable for developing enterprise beans:

- `ejs.jar`
- `ujc.jar`
- `otherDeployedBean.jar` (if the enterprise bean uses another enterprise bean). This is the deployed JAR file containing the enterprise bean being used by this enterprise bean.

For developing and running an EJB client, the following WebSphere JAR files must be appended to the CLASSPATH environment variable:

- `ejs.jar`

- `ujc.jar`
- `servlet.jar` (required by EJB clients that are servlets)
- *otherDeployedBean.jar*. This is the deployed JAR file containing the enterprise bean being used by this EJB client.

Creating the components of an enterprise bean

If you use an ASCII text editor or a Java development tool that does not support enterprise bean development, you must create each of the components that compose the enterprise bean you are creating. You must ensure that these components match the requirements described in [Developing enterprise beans](#).

To manually develop a session bean, you must write the bean class, the bean's home interface, and the bean's remote interface. To manually develop an entity bean, you must write the bean class, the bean's primary key class, the bean's home interface, the bean's remote interface, and if necessary, the bean's finderHelper interface. After you have properly coded these components, use the Java compiler to create the corresponding Java class files. For example, because the components of the example Account bean are stored in a specific directory, the bean components can be compiled by issuing the following command:

```
C:\MYBEANS\COM\IBM\EJS\DOC\ACCOUNT> javac *.java
```

This command assumes that the CLASSPATH environment variable contains all of the packages used by the Account bean.

Creating finder logic in the EJB server

For the EJB server environment, the following finder logic is required for each finder method (other than the `findByPrimaryKey` method) contained in the home interface of an entity bean with CMP:

- The logic must be defined in a public interface named *NameBeanFinderHelper*, where *Name* is the name of the enterprise bean (for example, `AccountBeanFinderHelper`).
- The logic must be contained in a String constant named *findMethodNameWhereClause*, where *findMethodName* is the name of the finder method. The String constant can contain zero or more question marks (?) that are replaced from left to right with the value of the finder method's arguments when that method is invoked.

Note:

Encapsulating the logic in a String constant named *findMethodNameQueryString* has been deprecated.

If you define the `findLargeAccounts` method shown in [Figure 14](#), you must also create the `AccountBeanFinderHelper` interface shown in [Figure 7](#).

Figure 7. Code example: AccountBeanFinderHelper interface for the EJB server

```
...
public interface AccountBeanFinderHelper{
    String findLargeAccountsWhereClause = "balance > ?";
}
```

Creating an EJB module

The WebSphere Application Server Application Assembly Tool can be used to create an EJB module. An EJB module can contain one or more enterprise beans. The tool automatically creates the required deployment descriptor for the module based on information specified by the user.

Using the Application Assembly Tool

To create an EJB module and corresponding deployment descriptor, use the Create EJB Module wizard in the Application Assembly Tool. This wizard prompts you to specify the following information for each enterprise bean to be included in the module:

- The enterprise bean class, home interface class, and remote interface class.
- The bean type (entity or session), and associated attributes (such as persistence management type and primary key class for entity beans).
- References to another enterprise bean's home interface and to resource connection factories.
- References to security roles for the enterprise bean.
- CMP fields, if applicable.
- Transaction isolation level attributes for enterprise bean methods.

The wizard also prompts you to specify the following application assembly information for the module itself:

- General properties of the EJB module, such as the location of class files needed for a client program to access the enterprise beans in the module and the icons to be associated with the module.
- The deployable enterprise beans that the module will contain.
- Security roles used to access resources in the module.
- Transaction attributes for the enterprise bean methods.

Both bean and module information are used to create the deployment descriptor. See the WebSphere InfoCenter and the online help for details on how to use the Application Assembly Tool.

Creating a database for use by entity beans

For entity beans with *container-managed persistence (CMP)*, you must store the bean's persistent data in one of the supported databases. The Application Assembly Tool automatically generates SQL code for creating database tables for CMP entity beans. The tool names the database schema and table `ejb.beanNamebeantbl`, where *beanName* is the name of the enterprise bean (for example, `ejb.accountbeantbl`). If your CMP entity beans require complex database mappings, it is recommended that you use VisualAge for Java to generate code for the database tables. At run time, the WebSphere Administrative Console displays a prompt asking whether you want to execute the generated SQL code that creates the database table.

For entity beans with *bean-managed persistence (BMP)*, you can create the database and database table by using the database tools or use an existing database and database table. Because entity beans with BMP handle the database interaction, any database or database table name is acceptable.

For more information on creating databases and database tables, consult your database documentation and the online help for the WebSphere Administrative Console.

Appendix A. Changes for version 1.1 of the EJB specification

WebSphere Application Server supports version 1.1 of the EJB specification. This appendix describes features that are new or have changed in version 1.1 and discusses migration issues for enterprise beans written to version 1.0 of the EJB specification.

New and updated features

The following enterprise bean features are new or have changed for version 1.1.

- Environmental dependencies for enterprise beans are now specified using entries in a JNDI naming context. An instance of an enterprise bean creates a `javax.naming.InitialContext` object by invoking the constructor with no arguments specified. It looks up the environment naming context by using the `InitialContext` object under the name `java:comp/env`.
 - Primary keys are handled differently in version 1.1 of the EJB specification. Entity bean providers are not required to specify the primary key class for entity beans with container-managed persistence (CMP), enabling the deployer to select the primary key fields when the bean is deployed into a container.
 - The deployment descriptor has enhanced support for application assembly.
-

Migrating from version 1.0 to version 1.1

From the client's perspective, enterprise beans written to version 1.1 of the EJB specification appear nearly identical to enterprise beans written to version 1.0 of the specification. However, the following EJB 1.1 changes do affect clients:

- Enterprise beans written to version 1.1 of the EJB specification are registered in a different part of the JNDI namespace. For example, a client can look up the initial context of a version 1.0 enterprise bean in JNDI by using the **`initialContext.lookup`** method as follows:

```
initialContext.lookup( "com/ibm/Hello" )
```

The JNDI lookup for the equivalent version 1.1 enterprise bean is:

```
initialContext.lookup( "java:comp/env/ejb/Hello" )
```

- The `UserTransaction` object is obtained differently for enterprise beans written to version 1.1 of the EJB specification. Under version 1.0, it was obtained as:

```
initialContext.lookup( "jta/UserTransaction" )
```

Under version 1.1, it is obtained as:

```
initialContext.lookup( "java:comp/UserTransaction" )
```

- Because entity beans written to version 1.1 of the EJB specification now support primitive primary keys (instead of having to encapsulate them in a primary key class), the client needs to look up these primitive keys directly. For example, a client can look up a primitive key of the type `java.lang.Integer` as follows:

```
accountHome.findByPrimaryKey(new Integer(5))
```

Primary key classes are still supported, although their use for primitive data types is deprecated.

From the application developer's perspective, the following changes need to be made to make enterprise beans written to version 1.0 of the EJB specification compatible with version 1.1 of the specification.

- All deployment descriptors must be converted to the XML format specified in version 1.1 of the EJB specification.
- In general, enterprise beans written to version 1.0 of the EJB specification are compatible with version 1.1. However, you need to modify or recompile enterprise bean code in the following cases:
 - The return value of the `ejbCreate` method must be modified for all entity beans with CMP. The `ejbCreate` method is now required to return the same type as the primary key; the actual value returned must be null. These beans also must be recompiled. For more information, see [Implementing the `ejbCreate` and `ejbPostCreate` methods](#)
 - If the `javax.jts.UserTransaction` interface is used. This interface has been renamed to `javax.transaction.UserTransaction`. Enterprise beans that use this interface must be modified to use the new interface name. There have also been minor changes to the exceptions thrown by this interface.
 - If the `getCallerIdentity` or `isCallerInRole` methods of the `javax.ejb.EJBContext` interface are used. These methods were deprecated because the `javax.security.Identity` class is deprecated under the Java 2 platform.
 - If an entity bean uses the `UserTransaction` interface, which is not permitted under version 1.1 of the EJB specification.
 - If an entity bean whose finder methods do not define the `FinderException` in the methods' throws clauses. Under version 1.1, the finder methods of entity beans must define this exception.
 - If an entity bean uses the `UserTransaction` interface and implements the `SessionSynchronization` interface. Entity beans can neither use the `UserTransaction` interface nor implement the `SessionSynchronization` interface under version 1.1.
 - If a stateless session bean implements the `SessionSynchronization` interface. Stateless session beans should not implement the `SessionSynchronization` interface under version 1.1.
 - If an enterprise bean violates any of the new semantic restrictions defined in version 1.1 of the EJB specification.
 - Throwing the `javax.ejb.RemoteException` exception from the bean implementations is deprecated in version 1.1. This exception should be replaced by the `javax.ejb.EJBException` or a more specific exception such as the `javax.ejb.CreateException`. The `javax.ejb.EJBException` inherits from the `javax.ejb.RuntimeException` and does not need to be explicitly declared in throws clauses.

Declare the `javax.ejb.RemoteException` exception in the remote and home interfaces, as required by RMI. Throwing this exception directly by the bean implementation is deprecated. However, it can be thrown by the container due to a system exception or by mapping an exception thrown by the bean implementation.

Appendix B. Example code provided with WebSphere Application Server

This appendix contains information on the example code provided with the WebSphere Application Server.

Information about the examples described in the documentation

The example code discussed throughout this document is taken from a set of examples provided with the product. This set of examples is composed of the following main components:

- The Account entity bean, which models either a checking or savings bank account and maintains the balance in each account. An account ID is used to uniquely identify each instance of the bean class and to act as the primary key. The persistent data in this bean is container managed and consists of the following variables:
 - *accountId*--The account ID that uniquely identifies the account. This variable is of type long.
 - *type*--An integer that identifies the account as either a savings account (1) or a checking account (2). This variable is of type int.
 - *balance*--The current balance of the account. This variable is of type float.

The major components of this bean are discussed in [Developing entity beans with CMP](#).

- The AccountBM entity bean, which is nearly identical to the Account entity bean; however, the AccountBM bean implements bean-managed persistence. This bean is not used by any other enterprise bean, application, or servlet contained in the documentation example set. The major components of this bean are discussed in [Developing entity beans with BMP](#).
- The Transfer session bean, which models a funds transfer session that involves moving a specified amount between two instances of an Account bean. The bean contains two methods: the transferFunds method transfers funds between two accounts, the getBalance method retrieves the balance for a specified account. The bean is stateless. The major components of this bean are discussed in [Developing session beans](#).
- The CreateAccount servlet, which can be used to easily create new bank accounts (and corresponding Account bean instances) with the specified account ID, account type, and initial balance. Although this servlet is designed to make it easy for you to create accounts and demonstrate the other components in the example set, it also illustrates servlet interaction with an entity bean. This servlet is discussed in [Developing servlets that use enterprise beans](#).
- The TransferApplication Java application, which provides a graphical user interface that was built with the abstract windowing toolkit (AWT). The application creates an instance of the Transfer session bean, which is then manipulated to transfer funds between two selected accounts or to get the balance for a specified account. The TransferApplication code implements many of the requirements for using enterprise beans in an EJB client. The parts of this application that are relevant to interacting with an enterprise bean are discussed in [Developing EJB clients](#).
- The TransferFunds servlet, which is a servlet version of the TransferApplication Java application. This servlet is provided so that you can compare the use of enterprise beans between a Java application and a Java servlet that basically are doing the same tasks. This document does not discuss this servlet in any detail.

Note:

The example code in the documentation was written to be as simple as possible. The goal of these examples is to provide code that teaches the fundamental concepts of enterprise bean and EJB client development. It is not meant to provide an example of how a bank (or any similar company) possibly

approaches the creation of a banking application. For example, the Account bean contains a *balance* variable that has a type of float. In a real banking application, you must not use a float type to keep records of money; however, using a class like `java.math.BigDecimal` or a currency-handling class within the examples would complicate them unnecessarily. Remember this as you examine these examples.

Information about other examples

[Table 2](#) provides a summary of the enterprise bean-specific examples provided with the EJB server

Table 2. Examples available with the EJB server

Name	Bean types	EJB client types	Additional information
Hello	Stateless session	Java servlet	Very simple example of a session bean.
Increment	CMP entity	Java servlet	Very simple example of an entity bean.

Appendix C. Extensions to the EJB Specification

This appendix briefly discusses functional extensions to the EJB Specification that are available in the EJB server environments contained in WebSphere Application Server. These extensions are specific to WebSphere Application Server and use of these features is supported only with VisualAge for Java, Enterprise Edition. For information on implementing these features, consult your VisualAge for Java documentation.

Access beans

Access beans are Java components that adhere to the Sun Microsystems JavaBeans^(TM) Specification and are meant to simplify development of EJB clients. An access bean adapts an enterprise bean to the JavaBeans programming model by hiding the home and remote interfaces from the access bean user (that is, an EJB client developer).

There are three types of access beans, which are listed in ascending order of complexity:

- **Java bean wrapper**--Of the three types of access beans, a Java bean wrapper is the simplest to create. It is designed to allow either a session or entity enterprise bean to be used like a standard Java bean and it hides the enterprise bean home and remote interfaces from you. Each Java bean wrapper that you create extends the `com.ibm.ivj.ejb.access.AccessBean` class.
- **Copy helper**--A copy helper access bean has all of the characteristics of a Java bean wrapper, but it also incorporates a single copy helper object that contains a local copy of attributes from a remote entity bean. A user program can retrieve the entity bean attributes from the local copy helper object that resides in the access bean, which eliminates the need to access the attributes from the remote entity bean.
- **Rowset**--A rowset access bean has all of characteristics of both the Java bean wrapper and copy helper access beans. However, instead of a single copy helper object, it contains multiple copy helper objects. Each copy helper object corresponds to a single enterprise bean instance.

VisualAge for Java provides a SmartGuide to assist you in creating or editing access beans.

Associations between enterprise beans

In the EJB server environment, an association is a relationship that exists between two CMP entity beans. There are three types of associations: one-to-one and one-to-many. In a one-to-one association, a CMP entity bean is associated with a single instance of another CMP entity bean. For example, an Employee bean could be associated with only a single instance of a Department bean, because an employee generally belongs only to a single department.

In a one-to-many association, a CMP entity bean is associated with multiple instances of another CMP entity bean. For example, a Department bean could be associated with multiple instances of an Employee bean, because most departments are made up of multiple employees.

The Association Editor is used to create or edit associations between CMP entity beans in VisualAge for Java.

Inheritance in enterprise beans

In Java, *inheritance* is the creation of a new class from an existing class or a new interface from an existing interface. The EJB server environment permits two forms of inheritance: standard class inheritance and EJB inheritance. In standard class inheritance, the home interface, remote interface, or enterprise bean class inherits properties and methods from base classes that are not themselves enterprise bean classes or interfaces.

In enterprise bean inheritance, by comparison, an enterprise bean inherits properties (such as CMP fields and association ends), methods, and method-level control descriptor attributes from another enterprise bean that resides in the same group.

VisualAge for Java provides a SmartGuide to assist you in implementing inheritance in enterprise beans.

6.6.4: Administering EJB containers (overview)

A container configuration provides information about an enterprisebean container. The administrator can specify several properties to address basic questions about the container location and behavior.

Specifying the server in which the container will reside

Each enterprise bean container resides in a particular application server.

When the administrator adds a new container to the WebSphere administrativedomain, he or she must associate the container with a particular server (alsoknown as the container's parent).

An application server can host multiple containers.

Specifying how beans in the container will get database connections

Every container can support the two main bean types, session beans and entitybeans:

- Entity beans require database connections because they store permanent data.
- Session beans do not *require* database access, though they can obtain it indirectly (as needed) by accessing entity beans.

A data source is an administrative resource that defines a pool of database connections. Servlets and enterprise beans use data sources to obtain database connections.

When configuring a container, the administrator can specify a default data source for the container. This data source will be the default data source used by any entity beans installed in the container that use container managed persistence (CMP).

When configuring a CMP entity bean, the administrator can specify which data source the container must use for managing the persistent state of the entity bean. If the administrator specifies a data source for an individual CMP entity bean then this data source will override any data source specified on the container.

Specifying a default data source is optional if each CMP entity bean in the container has a data source specified in its configuration. If a default data source is not specified and a CMP entity bean is installed in that container without specifying a data source for that bean then it will not be possible to start that CMP entity bean.

The default data source for a container is secure. When specifying it, the administrator must provide the user ID and password for accessing the data source.

Specifying how the container will manage cached bean instances

Each container keeps a cache of bean instances for ready access. The WebSphere administrator specifies settings governing the cache size and a policy for removing unused items from the cache.

Specifying where the container will passivate beans to make room in its cache

A container can *passivate* session beans to make room in its cache. The container saves a serialized session bean to a file. It restores the bean to the cache when more room is available.

The WebSphere administrator specifies a passivation directory in which to keep the files.

6.6.4.0: EJB container properties

Key:



Applies to Java administrative console of Advanced Edition Version 4.0



Applies to Web administrative console of Advanced Single Server Edition Version 4.0



Applies to Application Client Resource Configuration Tool

Application Server



The application server of which the EJB container is a part

Default Data Source



The data source to use to connect to a JDBC-compliant database, such as DB2

Cache clean-up interval



or Clean-up Interval



The interval at which the container attempts to remove unused items from the cache to reduce the total number of items in the cache to the value of the Cache preferred limit property.

The cache manager tries to maintain some unallocated entries that can be allocated quickly, as needed. A background thread attempts to free some entries while ensuring that some unallocated entries are maintained. If the thread runs while the application server is idle, then when the application server needs to allocate new cache entries, it does not pay the performance cost of removing entries from the cache.

In general, increase this parameter as the cache size increases.

For the Advanced Single Server Edition: This value must be a positive integer specified in milliseconds.

Cache size



The number of buckets in the cache hash table

If you change this value, change the Cache absolute limit property to correspond. For example, if you change the cache size to 3000, change the cache absolute limit to 3000, unless for some reason you do not want all of the available cache to be used.

For Advanced Single Server Edition: This value must be a positive integer.

Inactive Pool Cleanup Interval



The interval at which inactive pools will be reduced to their minimum size.

For Advanced Single Server Edition: The value must be a positive integer specified in milliseconds.

Installed EJB Modules



The EJB modules that are installed in the EJB container of this server

Node



The node with which the application server is associated

Passivation Directory



The directory into which the container will save the persistent state of passivated session beans

Session beans are passivated when the container needs to reclaim space in the bean cache. At passivation time, the container serializes the bean instance to a file in the passivation directory and discards the instance from the bean cache. If, at a later time, a request arrives for the passivated bean instance, the container retrieves it from the passivation directory, deserializes it, returns it to the cache, and dispatches the request to it. If any step fails (for example, if the bean instance is no longer in the passivation directory), then the method invocation fails.

6.6.4.1: Administering enterprise bean containers with the Java administrative console

Use the Java administrative console to administer EJB container services.

Work with resources of this type by locating them in the application server properties:

1. [Locate the EJB container service among the application serverservices.](#)
2. When the application server properties are displayed in the [properties view](#), click the **Services** tabbed page.
3. Locate the EJB container service in the list of services.

6.6.4.1.1: Configuring the EJB container services of application servers with the Java administrative console

During this task, you will specify settings for the EJB container service of an existing application server.

1. [Locate the service](#). (Select it in the list of services).
2. Click **Edit Properties** to display the properties of the service.
3. Specify values for the [EJB container service properties](#).
4. When finished, click **OK**.

6.6.5: Administering EJB modules (overview)

Administration of EJB modules consists of the following:

- Creating the module, setting deployment descriptor properties, and generating code for deployment using the Application Assembly Tool
- Setting additional configuration properties using the console

Classpath considerations

An important classpath-related setting to note is the Module Visibility. This application server setting impacts the portability of applications and standalone modules from other WebSphere Application Server versions and editions. If your existing module does not run as-is when you transfer it to Version 4.0, you might need to reassemble an existing module or change the module visibility setting.

See [the information on setting classpaths](#) for a full discussion of classpath considerations. See the [applicationserver property reference](#) for information about the module visibility setting.

6.6.5.0: EJB module properties

Key:



Applies to Java administrative console of Advanced Edition Version 4.0



Applies to Web administrative console of Advanced Single Server Edition Version 4.0



Applies to Application Client Resource Configuration Tool

Application or  Application Ref 

The application installation binding within which the module-to-server installation binding is contained. This is typically the logical name of the enterprise application you configured to contain this EJB module.

Default Data Source 

The data source to use for this EJB module, unless a different one is specified

Execution State 

The state that you would like the enterprise bean module to be in, the next time the product is stopped and started again

Name  or Module Name 

An administrative name for the EJB module

Password 

The password corresponding to the specified user ID

Server 

The application server on which the EJB module is installed

URI 

A URI that, when resolved relative to the application URL, specifies the location of the module archive on a file system. The URI must match the URI of a ModuleRef URI in the deployment descriptor of an application if the module was packaged as part of a deployed application (EAR).

User ID 

The user ID for accessing the default data source

See also the other [application server properties](#).

6.6.5.0.1: Assembly properties for entity beans

EJB name (Required, String)

Specifies a logical name for the enterprise bean. This name must be unique within the EJB module. There is no relationship between this name and the JNDI name.

Display name

Specifies a short name that is intended to be displayed by GUIs.

Description

Contains text describing the entity bean.

Home Interface (Required, String)

Specifies the full name of the enterprise bean's home interface class--for example, `com.ibm.ejs.doc.account.AccountHome`.

Remote Interface (Required, String)

Specifies the full name of the enterprise bean's remote interface class--for example, `com.ibm.ejs.doc.account.Account`.

EJB class (Required, String)

Specifies the full name of the enterprise bean class--for example, `com.ibm.ejs.doc.account.AccountBean`.

Persistence

Specifies whether an entity bean manages its own persistent storage or whether storage is managed by the container. The valid values are `Bean-managed` and `Container-managed`.

Primary key field

Specifies the name of a simple primary key. Simple primary keys map to a single field in the entity bean class and are made up of primitive Java data types (such as integer or long). If exactly one CMP field is the primary key, it can be specified here.

Primary key class (Required, String)

Specifies the full name of the bean's primary key class--for example, `com.ibm.ejs.doc.account.AccountKey`. Composite primary keys map to multiple fields in the entity bean class (or to data structures built from the primitive Java data types), and must be encapsulated in a primary key class. More complicated enterprise beans are likely to have composite primary keys, with multiple instance variables representing the primary key. A subset of the container-managed fields is used to define the primary key class associated with each instance of an enterprise bean.

Reentrant

Specifies whether the entity bean is reentrant or not. If an enterprise bean is reentrant, it can invoke methods on itself or call another bean that invokes a method on the calling bean. Only entity beans can be reentrant. If an entity bean is not reentrant and a bean instance is executing a client request in a transaction context and another client using the same transaction context makes a request on the same bean instance, the EJB container throws the `java.rmi.RemoteException` exception to the second client. If a bean is reentrant, the container cannot distinguish this type of illegal loopback call from a legal concurrent call and the bean must be coded to detect illegal loopback calls.

Small icon

Specifies a JPEG or GIF file containing a small image (16x16 pixels). The image is used as an icon to represent the entity bean in a GUI.

Large icon

Specifies a JPEG or GIF file containing a large image (32x32 pixels). The image is used as an icon to

represent the entity bean in a GUI.

Inheritance root

Specifies whether or not the enterprise bean is at the root of an inheritance hierarchy.

Bean Cache -- Activate at

Specifies the point at which an enterprise bean is activated and placed in the cache. Removal from the cache and passivation is also governed by this setting. Valid values are Once and Transaction. Once indicates that the bean is activated when it is first accessed in the server process, and passivated (and removed from the cache) at the discretion of the container--for example, when the cache becomes full. Transaction indicates that the bean is activated at the start of a transaction and passivated (and removed from the cache) at the end of the transaction. The default value is Transaction.

Bean Cache -- Load at

Specifies when the bean loads its state from the database. The value of this property implies whether the container has exclusive or shared access to the database. Valid values are Activation and Transaction. Activation indicates that the bean is loaded when it is activated (Once or Transaction) and implies that the container has exclusive access to the database. Transaction indicates that the bean is loaded at the start of a transaction and implies that the container has shared access to the database. The default is Transaction.

The settings of the Activate at and Load at properties govern which commit options are used. The commit options are described in detail in the Enterprise JavaBeans specification, version 1.1.

- For Commit Option A (implies exclusive DB access), use Activate at = Once and Load at = Activation. This option reduces database I/O (avoids calls to the `ejbLoad` function) but serializes all transactions accessing the bean instance. Option A can increase memory usage by maintaining more objects in the cache, but could provide better response time if bean instances are not generally accessed concurrently by multiple transactions.
- For Commit Option B (implies shared DB access), use Activate at = Once, Load at = Transaction. Option B can increase memory usage by maintaining more objects in the cache. However, because each transaction creates its own copy of an object, there can be multiple copies of an instance in memory at any given time (one per transaction), requiring that the database be accessed at each transaction. If an enterprise bean contains a significant number of calls to the `ejbActivate` function, using Option B can be beneficial because the required object is already in the cache. Otherwise, this option does not provide significant benefit over Option A.
- For Commit Option C (implies shared DB access), use Activate at = Transaction and Load at = Transaction. This option can reduce memory usage by maintaining fewer objects in the cache, however, there can be multiple copies of an instance in memory at any given time (one per transaction). This option can reduce transaction contention for enterprise bean instances that are accessed concurrently but not updated.

Locale location

Specifies the language used when the enterprise bean retrieves and displays message catalogs: the local language of the client that invoked the bean method or the local language of the server where the bean is running. Valid values are server and caller.

Local Transactions -- Boundary

Specifies when a local transaction begins. The default behavior is that the local transaction begins when the method begins and ends when the method ends.

Local Transactions -- Unresolved action

Specifies the action the container must take if resources are uncommitted by an application in a local transaction. A local transaction context is created when a method executes in what the EJB specification refers to as an unspecified transaction context. Valid values are Rollback and Commit. The default is Rollback.

Local Relationship Roles - Name

Information is not available.

Local Relationship Roles - Source EJB Name

Information is not available.

Local Relationship Roles - is Forward

Information is not available.

Local Relationship Roles - is Navigable

Information is not available.

JNDI name

Specifies the JNDI name of the bean's home interface. This is the name under which the enterprise bean's home interface is registered and therefore is the name that must be specified when an EJB client does a lookup of the home interface.

Data Source - JNDI name

Specifies the JNDI name for the bean's data source.

Default Authorization - User ID

Specifies the default user ID for connecting to a data source.

Default Authorization - Password

Specifies the default password for connecting to a data source.

6.6.5.0.2: Assembly properties for CMP fields

Container-managed persistence (CMP) fields define the variables in the beanclass for which the container must handle persistence management.

Name (Required, String)

Specifies a subset of public variables in an enterprise bean's implementation class.

6.6.5.0.3: Assembly properties for method extensions

Method type

Specifies the type of the enterprise bean method. Valid values are Home methods, Remote methods, and All methods.

Name

Specifies the name of an enterprise bean method, or the asterisk character(*) . The asterisk is used to denote all the methods of the specified interface--for example, all methods in the remote interface.

Parameters

Contains a list of fully qualified Java type names of the method parameters. Used to identify a single method among multiple methods with an overloaded method name.

Isolation level attributes

The transaction isolation level determines how isolated one transaction is from another. This property can be set for individual methods in an enterprise bean or for all methods in the enterprise bean. An asterisk is used to indicate all methods in the bean. However, within a transactional context, the isolation level associated with the first method invocation becomes the required isolation level for all methods invoked within that transaction. If a method is invoked with a different isolation level from that of the first method, the `java.rmi.RemoteException` exception is thrown.

Isolation level

Specifies the level of transactional isolation. The valid values are as follows:

- Serializable. This level prohibits the following types of reads:
 - Dirty reads, where a transaction reads a database row containing uncommitted changes from a second transaction.
 - Nonrepeatable reads, where one transaction reads a row, a second transaction changes the same row, and the first transaction rereads the row and gets a different value.
 - Phantom reads, where one transaction reads all rows that satisfy an SQL WHERE condition, a second transaction inserts a row that also satisfies the WHERE condition, and the first transaction applies the same WHERE condition and gets the row inserted by the second transaction.
- Repeatable read. This level prohibits dirty reads and nonrepeatable reads, but it allows phantom reads.
- Read committed. This level prohibits dirty reads, but allows nonrepeatable reads and phantom reads.
- Read uncommitted. This level allows dirty reads, nonrepeatable reads, and phantom reads.

The container uses the transaction isolation level attribute as follows:

- Session beans and entity beans with bean-managed persistence (BMP)--For each database connection used by the bean, the container sets the transaction isolation level at the start of each transaction unless the bean explicitly sets the isolation level on the connection.
- Entity beans with container-managed persistence (CMP)--The container generates database access code that implements the specified isolation level.

Security Identity

Specifies that a principal's credential properties are to be handled as indicated in the Run-As mode property. Checking this box makes the Run-as Mode properties editable.

Description

Contains text describing or commenting on the security instructions.

Run-As Mode

Credential information is used by the security service to determine the permissions that a principal has on various resources. At appropriate points, the security service determines whether the principal is authorized to use a particular resource based on the principal's permissions. If the method invocation is authorized, the security service does the following with the principal's credential properties based on the value of the Run-as Mode property of the enterprise bean:

- Use Identity of Caller -- the security service makes no changes to the principal's credential properties.
- Use Identity of EJB Server -- the security service alters the principal's credential properties to match the credential properties associated with the EJB server.
- Use Identity Assigned to Specified Role -- A principal that has been assigned to the specified security role is used for the execution of the bean's methods. This association is part of the application binding where the role is associated with a user ID and password of a user who is granted that role.

Role Name

Specifies the name of a security role. If the Use Identity Assigned to Specified Role button is selected, a principal that has been granted this role will be used.

Description

Contains a description of the security role.

Access Intent - Intent type

Specifies whether the method is a read-only method or whether the method can update data (or invoke other methods that can update data, in the same transaction). The legal values are read or update (read/write).

Finder descriptor - User

Specifies that the user has provided a finder helper class in the entity bean's home interface. The class contains specialized finder methods.

Finder descriptor - EJB QL

Describes the semantics of a finder method using the EJB QL (Enterprise JavaBeans query language). EJB QL is a declarative, SQL-like language intended to be compiled to the target language of the persistent data store used by a persistence manager. The language is independent of the bean's mapping to a relational data store and is therefore portable. The EJB query specifies a search based on the persistent attributes and relationships of the bean. An EJB query contains a SELECT clause (optional), a FROM clause (required), a WHERE clause (optional), and an ORDER BY clause (optional). The SELECT clause specifies the EJB objects to return. The FROM clause specifies the collections of objects to which the query is to be applied. The WHERE clause contains search predicates over the collections. The ORDER BY clause specifies the ordering of the resulting collection.

Finder descriptor - Full select

Note: For information on restrictions, see the documentation for Deployment Tool for Enterprise JavaBeans.

Describes the semantics of the finder method using a SQL SELECT statement. The SELECT statement indicates the EJB objects to return.

Finder descriptor - Where clause

Note: For information on restrictions, see the documentation for Deployment Tool for Enterprise JavaBeans.

Describes the semantics of the finder method using a SQL WHERE clause. This clause restricts the

results that are returned by the query.

6.6.5.0.4: Assembly properties for session beans

EJB name (Required, String)

Specifies a logical name for the enterprise bean. This name must be unique within the EJB module. There is no relationship between this name and the JNDI name.

Display name

Specifies a short name that is intended to be displayed by GUIs.

Description

Contains text describing the session bean.

Home interface (Required, String)

Specifies the full package name of the enterprise bean's home interface class, for example, `com.ibm.ejs.doc.account.AccountHome`.

Remote interface (Required, String)

Specifies the full package name of the enterprise bean's remote interface class, for example, `com.ibm.ejs.doc.account.Account`.

EJB class (Required, String)

Specifies the full package name of the enterprise bean class, for example, `com.ibm.ejs.doc.account.AccountBean`.

Session type

Specifies whether the enterprise bean maintains a conversational state (is a stateful session bean) or does not (is a stateless session bean). Valid values are `stateful` and `stateless`.

Transaction type

Specifies whether the enterprise bean manages its own transactions or whether the container manages transactions on behalf of the bean. Valid values are `container` or `bean`.

Small icon

Specifies a JPEG or GIF file containing a small image (16x16 pixels). The image is used as an icon to represent the session bean in a GUI.

Large icon

Specifies a JPEG or GIF file containing a large image (32x32 pixels). The image is used as an icon to represent the session bean in a GUI.

Timeout

Specifies the idle timeout value for the enterprise bean in seconds. A zero (0) value indicates that idle bean instances time out after the maximum allowable timeout period elapses. By default, the timeout is 600 seconds or 10 minutes. This property does not apply to session beans.

Inheritance root

Specifies whether the enterprise bean is at the root of an inheritance hierarchy.

Bean Cache -- Activate at

Applies to stateful session beans only, not to stateless beans. Specifies the point at which an enterprise bean is activated and placed in the cache. Removal from the cache and passivation are also governed by this setting. Valid values are `Once` and `Transaction`. `Once` indicates that the bean is activated when it is first accessed in the server process and passivated (and removed from the cache) at the discretion of the container--for example, when the cache becomes full. `Transaction` indicates that the bean is activated at the start of a transaction and passivated (and removed from the cache) at the end of the transaction. The default value is `Once`.

Bean Cache -- Load at

This property does not apply to session beans.

Locale location

Specifies the language used when the enterprise bean retrieves and displays message catalogs: the local language of the client that invoked the bean method or the local language of the server where the bean is running. Valid values are server and caller.

Local Transactions -- Boundary

Specifies when a local transaction begins. The default behavior is that the local transaction begins when the method begins and ends when the method ends. This property is not applicable for session beans.

Local Transactions -- Unresolved action

Specifies the action the container must take if resources are uncommitted by an application in a local transaction. A local transaction context is created when a method executes in what the EJB specification refers to as an unspecified transaction context. Valid values are Rollback and Commit. The default is Rollback.

JNDI name

Specifies the JNDI name of the bean's home interface. This is the name under which the enterprise bean's home interface is registered and therefore is the name that must be specified when an EJB client does a lookup of the home interface.

6.6.5.0.5: Assembly properties for security roles

A security role is a logical grouping of principals. Access to operations (such as EJB methods) is controlled by granting access to a role.

Role name (Required, String)

Specifies the name of a security role.

Description

Contains text describing the security role.

If specifying security roles at the application level (EAR file), the following properties apply:

Role Name (Required, String)

Specifies the name of a security role that is unique to the application.

Description

Contains text describing the security role.

Binding -- Groups -- Name

Specifies user groups that are granted the security role.

Binding -- Users -- Name

Specifies users that are granted the security role.

Binding -- Special Subjects -- Name

Specifies one of two special categories of users to which roles can be granted: Everyone or All authenticated users. If the special subject Everyone is granted a role, then all users, including those who did not authenticate, are granted the role. In other words, a method on an enterprise bean or a URI is unprotected if any of the required roles for that method are granted to the special subject Everyone. In the case of All authenticated users, any user who can authenticate by using a valid user ID and password is considered to be granted that role.

6.6.5.0.6: Assembly properties for method permissions

A method permission is a mapping between one or more security roles and one or more methods that a member of the role can invoke. Assembly properties for method permissions include an optional description, a list of security role names, and a list of methods. The security roles must be defined, and the methods must be methods defined in the enterprise bean's remote or home interfaces.

Method permission name

Specifies a name for the mapping between method permissions and security roles.

Description

Contains text describing the mapping between method permissions and security roles.

Methods - Name

Specifies the name of an enterprise bean method, or the asterisk (*) character. The asterisk is used to denote all the methods of the specified interface--for example, all methods of the remote interface.

Methods - Enterprise Bean

Specifies the name of the enterprise bean that contains the method.

Methods - Type

Distinguishes between a method with the same signature that is defined in both the home and remote interface. Valid values are All methods, Remote methods, or Home methods.

Methods - Parameters

Contains a list of fully qualified Java type names of the method parameters. This property is used to identify a single method among multiple methods with an overloaded method name.

Roles -- Role Name

Specifies the security role that must be granted in order to invoke the method.

6.6.5.0.7: Assembly properties for container transactions

Container transaction properties specify how the container must manage transaction scopes for the enterprise bean's method invocations. Specify one or more methods and associate a transaction attribute with each method.

Name

Specifies a name for the mapping between a transaction attribute and one or more methods.

Description

Contains text describing the mapping.

Transaction Attribute

Specifies how the container must manage the transaction boundaries when delegating a method invocation to an enterprise bean's business method. The legal values are Never, Mandatory, Requires New, Required, Supports, Not Supported, and Bean Managed. The default is Not Supported.

- **Mandatory.** Directs the container to always invoke the bean method within the transaction context associated with the client. If the client attempts to invoke the bean method without a transaction context, the container throws the `javax.jts.TransactionRequiredException` exception to the client. The transaction context is passed to any EJB object or resource accessed by an enterprise bean method.

EJB clients that access these entity beans must do so within an existing transaction. For other enterprise beans, the enterprise bean or bean method must implement the Bean Managed value or use the Required or Requires New value. For non-enterprise bean EJB clients, the client must invoke a transaction by using the `javax.transaction.UserTransaction` interface.
- **Supports.** Directs the container to invoke the bean method within a transaction context if the client invokes the bean method within a transaction. If the client invokes the bean method without a transaction context, the container invokes the bean method without a transaction context. The transaction context is passed to any enterprise bean objects or resources that are used by this bean method.
- **Never.** Directs the container to invoke bean methods without a transaction context.
 - If the client invokes a bean method from within a transaction context, the container throws the `java.rmi.RemoteException` exception.
 - If the client invokes a bean method from outside a transaction context, the container behaves in the same way as if the Not Supported transaction attribute was set. The client must call the method without a transaction context.
- **Requires New.** Directs the container to always invoke the bean method within a new transaction context, regardless of whether the client invokes the method within or outside a transaction context. The transaction context is passed to any enterprise bean objects or resources that are used by this bean method.
- **Not Supported.** Directs the container to invoke bean methods without a transaction context. If a client invokes a bean method from within a transaction context, the container suspends the association between the transaction and the current thread before invoking the method on the enterprise bean instance. The container then resumes the suspended association when the method invocation returns. The suspended transaction context is *not* passed to any enterprise bean objects or resources that are used by this bean method.
- **Required.** Directs the container to invoke the bean method within a transaction context. If a client invokes a bean method from within a transaction context, the container invokes the bean method within the client transaction context. If a client invokes a bean method outside a transaction context, the container creates a new transaction context and invokes the bean method from within

that context. The transactioncontext is passed to any enterprise bean objects or resources that are used bythis bean method.

- Bean Managed. Notifies the container that the bean class directlyhandles transaction demarcation. This property can be specified onlyfor session beans, and it cannot be specified for individual beanmethods.

Method Elements - Name

Specifies the name of an enterprise bean method, or the asterisk character(*). The asterisk is used to denote all the methods of the specifiedinterface--for example, all methods of the remote interface.

Method Elements - Enterprise bean

Specifies which enterprise bean contains the methods indicated in the Nameproperty.

Method Elements - Type

Used to distinguish between a method with the same signature that isdefined in both the home and remote interface. Valid values are Allmethods, Remote methods, or Home methods. Use All methods if atransaction attribute applies to all methods of the bean.

Method Elements - Parameters

Contains a list of fully qualified Java type names of the methodparameters. This property is used to identify a single method amongmultiple methods with an overloaded method name.

6.6.5.0.aa: Assembly properties for EJB modules

File name (Required, String)

Specifies the file name of the EJB module, relative to the top level of the application package.

Alternative DD

Specifies the file name for an alternative deployment descriptor file to use instead of the original deployment descriptor file in the module's JAR file. This file is the postassembly version of the deployment descriptor file. (The original deployment descriptor file can be edited to resolve dependencies and security information. Directing the use of the alternative deployment descriptor allows you to keep the original deployment descriptor file intact). The value of the Alternative DD property must be the full path name of the deployment descriptor file relative to the module's root directory. By convention, the file is in the ALT-INF directory. If this property is not specified, the deployment descriptor file is read directly from the module's JAR file.

Classpath

The path containing additional classes required by the application but not contained in the module's archive file. The class loader uses this path. Specify the values relative to the root of the EAR file and separate the values with spaces. Absolute values that reference files or directories on the hard drive are ignored. To specify classes that are not in JAR files but are in the root of the EAR file, use a period and forward slash (.). Consider the following example directory structure in which the file myapp.ear contains an EJB module named myejb.jar. Additional classes reside in class1.jar and class2.zip. A class named xyz.class is not packaged in a JAR file but is in the root of the EAR file.

```
myapp.ear/myejb.jar myapp.ear/class1.jar myapp.ear/class2.zip myapp.ear/xyz.class
```

Specify class1.jar class2.zip ./ as the value of the Classpath property. (Name only the directory for class files.)

Display name

Specifies a short name that is intended to be displayed by GUIs.

EJB client JAR

Specifies the location of the JAR file containing a subset of deployed classes needed by the client.

Description

Contains text describing the module.

Small icon

Specifies a JPEG or GIF file containing a small image (16x16 pixels). The image is used as an icon to represent the module in a GUI.

Large icon

Specifies a JPEG or GIF file containing a large image (32x32 pixels). The image is used as an icon to represent the module in a GUI.

Generalizations -- Subtype

Information is not available.

Generalizations -- Supertype

Information is not available.

EJB Relationships -- Name

Information is not available.

EJB Relationships -- Source EJB name

Information is not available.

EJB Relationships -- Is forward

Information is not available.

EJB Relationships -- Is navigable

Information is not available.

Default Data Source -- JNDI name

Specifies the default JNDI name for the data source. This default is used if binding information is not specified in the deployment descriptor for an individual enterprise bean.

Default Authorization - User ID

Specifies the default user ID for connecting to an enterprise bean's data store.

Default Authorization - Password

Specifies the default password for connecting to an enterprise bean's data store.

6.6.5.1: Administering EJB modules with the Java administrative console

Work with resources of this type by locating them in the [tree view](#).

To locate modules according to their membership in enterprise applications, click:

WebSphere Administrative Domain -> Nodes -> *node_name* -> Enterprise Applications -> *application_name* -> EJB modules

To locate modules installed on a particular application server, click:

WebSphere Administrative Domain -> Nodes -> *node_name* -> Application Servers -> *application_server_name* -> Installed EJB modules

In either case, the instances of the module will be displayed in the [details view](#).

6.6.5.1.1: Installing EJB modules with the Java administrative console

Use the [application installation wizard](#) to install EJB modules onto an application server.

6.6.5.1.2: Viewing deployment descriptors of EJB modules with the Java administrative console

To view the [deployment descriptor](#) of an EJB module:

1. [Locate the EJB module instance](#).
2. Right-click your EJB module in the details view and select **View Deployment Descriptor** from the popup menu.

A window opens, providing descriptive information about the selected module's EJB JAR and its enterprise beans and assembly descriptors.

6.6.5.1.3: Showing the status of EJB modules with the Java administrative console

During this task, you will view the status (such as running or stopped) of each EJB module in an enterprise application.

1. [Locate the EJB module instances](#).
2. Right-click an instance and select **Show Status** to display the Module Status window.
3. When finished viewing status, close the window.

6.6.5.1.4: Exporting table DDLs of EJB modules with the Java administrative console

You can export the DDL for each EJB module that contains container managed persistence (CMP) entity beans. You can save the DDL files to the location of your choice.

Later, you (or a database administrator) can use the saved DDL with the database vendor product to create database tables that correspond to the EJB modules. See [Recreating database tables from the exported table DDL](#) for instructions.

The data store that the DDL schema is loaded into should be the same data store specified in the container managed entity bean data source bindings. The bindings should be those that were specified for each enterprise bean, using the Application Installation wizard.

To export a DDL:

1. [Locate the EJB module instance](#).
2. Right-click your EJB module in the details view and select **Export Table DDL** from the popup menu.
3. In the Export Table DDL dialog that opens:
 - a. From the **Node** drop-down list, select a node to which the DDL should be exported.
 - b. In the **Export directory** field, specify the target drive and directory for the DDL.
 - c. Click **OK**.

The DDL will be exported to the specified node and directory, and will have the name *enterpriseApplicationName_ejbModuleName_Table.ddl*.

6.6.5.1.5: Moving EJB modules to other application servers with the Java administrative console

You can move an EJB module from one application server to a different application server or server group. To move a module:

1. [Locate the EJB module instance](#).
2. Right-click your EJB module in the details view and select **Move** from the popup menu.
3. In the Select a target server or ServerGroup dialog that opens, specify the target application server or server group and click **OK**
4. Copy EAR files containing the module to the node that contains the destination server. If the destination is a server group, then copy the EAR file to all nodes that contain the clones of the destination server group.

6.6.5.5: Administering EJB modules with Application Assembly Tool

An EJB module is used to assemble one or more enterprise beans into a single deployable unit. The Application Assembly Tool is used to create and edit EJB modules, verify the archive files, and generate deployment code. See the related topics for links to concepts, instructions for creating an EJB module, and field help.

6.6.5.5.1: Creating an EJB module

EJB modules can be created by using the property dialog boxes or by using awizard.

- [Using the property dialog boxes](#)
 - [Using the Create EJB Module wizard](#)
-

Using the property dialog boxes

The steps for creating an EJB module are as follows:

1. Click **File->New->EJB Module**. Thenavigation pane displays a hierarchical structure used to build the contentsof the module. The icons represent the components, assembly properties,and files for the module. A property dialog box containing generalinformation about the module is displayed in the property pane.
2. By default, the archive file name and the module display name are thesame. It is recommended that you change the display name in theproperty pane.
3. By default, the temporary location of the EJB module isinstallation_directory/bin. You must specify a newfile name and location by clicking **File->Save**. You must add at least one enterprise bean to the module before savingit. This is a requirement for a valid archive file.
4. Enter values for other properties as needed. View the help for [6.6.5.0.a: Assembly properties for EJB modules](#).
5. Add enterprise beans to the module. You must add at least oneenterprise bean. First, click the icon representing the type of beanbeing added (Session Beans or Entity Beans). There are several ways ofadding beans to a module:
 - Import an existing JAR or EAR file containing enterprise beans.Right-click the icon representing the enterprise bean type and choose**Import**. Click **Browse** to browse the file systemand locate the desired JAR file. When the file is located, click**Open**. Select the JAR file in the left window. Theenterprise beans in the selected JAR file are displayed in the rightwindow. Select the beans to be added and click **Add**.The selected items are displayed in the Selected Components window.Click **OK**. The property dialog box for the enterprise bean isautomatically populated with required values. Click the plus sign(+) next to the icon representing the bean type to verify that thebeans are included in the module.
 - Use a copy-and-paste operation to copy archive files from an existingmodule.
 - Create a new enterprise bean. Right-click the icon representing theappropriate bean type and choose **New**. For entity beans,choose whether the bean has container-managed or bean-managedpersistence. In the property dialog box, browse for and select theclass files that make up the bean. By default, the root directory orarchive is the current archive. If needed, browse the file system forthe directory or archive where the class files reside. After you choosea directory or archive, its file structure is displayed. Expand thestructure and locate the files that you need. Select the file and click**OK**. In the property dialog box, click **OK**.Verify that the beans are added to the module (expand the hierarchy for thebean type in the navigation pane). If there are one or more beans,display the properties for each bean by clicking the bean in the top part ofthe property pane. The corresponding property dialog box is displayedin the bottom part of the pane.
6. Specify properties for each enterprise bean. Expand the hierarchyfor each bean type. Click a bean instance and, if needed, edit or enterproperties for that bean. View the help for [6.6.5.0.1: Assembly properties for entity beans](#) or [6.6.5.0.4: Assembly properties for session beans](#).
7. Add assembly properties for each bean. Click the plus sign(+) next to the bean instance to reveal

property groups. Click the icon representing a group of properties. If properties are already defined (for example, for an imported bean), edit the properties in the property pane. If properties are not defined, right-click the property icon and click **New**. A property dialog box is displayed. Enter values for the properties and click **OK**.

- Specify Environment Entries. View the help for [6.6.34.0.a: Assembly properties for environment entries](#).
 - Specify EJB References. View the help for [6.6.43.0.1: Assembly properties for EJB references](#).
 - Specify Resource References. View the help for [6.6.43.0.2 Assembly properties for resource references](#).
 - Specify Security Role References. View the help for [6.6.43.0.3: Assembly properties for security role references](#).
 - Specify CMP Fields. View the help for [6.6.5.0.2: Assembly properties for CMP fields](#).
 - Specify Method Extensions. View the help for [6.6.5.0.3: Assembly properties for method extensions](#).
8. Add assembly properties for the EJB module. In the navigation pane, right-click each property group's icon. Choose **New** to add new values.
- Specify Security roles. View the help for [6.6.5.0.5: Assembly properties for security roles](#).
 - Specify Method permissions. View the help for [6.6.5.0.6: Assembly properties for method permissions](#).
 - Specify Container transactions. View the help for [6.6.5.0.7: Assembly properties for container transactions](#).
9. Add files needed by the application. Right-click the Files icon in the navigation pane and choose **Add Files**. Click **Browse** to navigate to the desired directory or archive. Click **Select**. If you are adding an entire archive, select the directory that contains the archive. The directory structure is displayed in the left pane. Browse the directory structure. From the right pane, select one or more files to be added and click **Add**. If you select a directory and click **Add**, all files in the directory, including the directory, are added. These selected files are displayed in the Selected Files window. Relative path names are maintained. When the Selected Files window contains the correct set of files, click **OK**.
10. Click **File->Save** to save the archive.
-

Using the Create EJB Module wizard

Use this wizard to create an EJB module. The module can then be used as a stand-alone application, or it can become part of a J2EE application containing other modules. An EJB module consists of one or more enterprise beans. You can use existing EJB JAR files (import them), or create new ones.

During creation of the EJB module, you specify the files for each enterprise bean to be included in the module. You also specify other information about the bean, such as security roles and references to other enterprise beans and to resource connection factories. After defining the enterprise beans to be included in the module, you specify assembly properties that apply to the module as a whole. Both bean and module information are used to create a deployment descriptor.

You can specify either of the following:

- One or more EJB 1.1 JAR files, either created manually or with VisualAge for Java. The enterprise beans must conform to J2EE specifications. The JAR files can be deployed or undeployed.
- One or more EJB 1.0 JAR files. The Application Assembly Tool automatically converts the file to the

EJB 1.1 specification format, but you must specify dependent classpaths if any.

- Enterprise bean class files (not residing in a JAR file).

The wizard creates an EJB module in the file location you specify.

To create an EJB module, click the **Wizards** icon on the tool bar and then click **EJB Module**. Follow the instructions on each panel.

- [Specifying EJB module properties](#)
- [Adding files](#)
- [Specifying EJB Client JAR and classpath](#)
- [Choosing EJB module icons](#)
- [Adding enterprise beans](#)
- [Adding security roles](#)
- [Adding method permissions](#)
- [Adding container transactions](#)
- [Setting additional properties and saving the archive](#)

Specifying EJB module properties

On the **Specifying EJB Module Properties** panel:

1. Indicate the application to which this module is to be added. If a parent application is not indicated, the module is created as a stand-alone application.
2. Specify a display name for the module. The display name is used by the Application Assembly Tool to identify the module and can be used by other tools.
3. Specify a file name for the module. The file name specifies allocation on your system for the JAR file to be created.
4. Provide a short description of the module (optional).
5. Click **Next**.

Adding files

On the **Adding Files** panel, specify supplementary files (such as library and utility files) that are to be included in your EJB module. To add or remove files:

1. Click **Add**. Use the file browser to choose one or more files. First, browse for the root directory or archive where the files are located and click **Select**. If you are adding an entire archive, select the directory that contains the archive. The directory structure is displayed in the left pane. Browse the directory structure. From the right pane, select one or more files to be added and click **Add**. If you select a directory and click **Add**, all files in the directory, including the directory, are added. Relative path names are maintained. The selected files are displayed in the Selected Files window. Click **OK**. The files are displayed in a table on the wizard panel.
2. If you want to remove a file, select the file in the table and then click **Remove**.
3. Continue to add or remove files until you have the correct set of files.
4. Click **Next**.

Specifying EJB Client JAR and classpath

On the **Specifying EJB Client JAR and Classpath** panel:

1. Specify the EJB Client JAR file. This is the location of the JARfile containing deployed classes needed by a client program for accessing theenterprise beans in this module.
2. Specify the path containing additional classes required by theapplication. This path is used by the classpath loader.
3. Click **Next**.

Choosing EJB module icons

On the **Choosing EJB Module Icons** panel, specify icons for yourmodule.

1. Specify the full path name of a file containing a small icon. Theicon must be a GIF or JPEG image 16x16 pixels in size.
2. Specify a full path name of a file containing a large icon. Theicon must be a GIF or JPEG image 32x32 pixels in size.
3. Click **Next**.

Adding enterprise beans

The **Adding Enterprise Beans** panel is used to add new enterprisebeans, import existing beans, or (if you are modifying this module or make amistake) remove beans.

To add a new enterprise bean:

1. Click **New**. On the dialog box, choose a bean type(session bean, entity bean with BMP, or entity bean with CMP). Click**OK**.
2. On the **Specifying Enterprise Bean Properties** panel, enter values for the properties of the bean. Click **Browse** tolocate the root directory or archive where the bean class files reside.The files are displayed in a window. Locate and click the appropriatefile. Click **OK**. View the help for [6.6.5.0.1: Assembly properties for entity beans](#) or [6.6.5.0.4: Assembly properties for session beans](#). Click **Next**.
3. On the **Specifying Container-managed persistence (CMP) fields**panel, define the variables for which the container must manage persistencemanagement. View the help for [6.6.5.0.2: Assembly properties for CMP fields](#). Click **Next**. This panel is visibleonly for entity beans with CMP.
4. On the **Specifying Specific Enterprise Bean Type Properties**panel, enter values for the properties of the bean. View the help for [6.6.5.0.1: Assembly properties for entity beans](#) or [6.6.5.0.4: Assembly properties for session beans](#). Click **Next**.
5. On the **Choosing Enterprise Bean Icons** panel, specify icons forthe bean. Specify the full path name of a file containing a small iconand large icon. The icon must be a GIF or JPEG image (16x16 pixels or32x32 pixels in size).
6. On the **Adding Environment Entries** panel, enter values forenvironment entries. Click **Add** and enter a name and type(required). Click **OK**. The entry is displayed in thetable on the wizard panel. To remove an entry, select the entry andthen click **Remove**. View the help for [6.6.34.0.a: Assembly properties for environment entries](#). Click **Next**.
7. On the **Adding Security Role References** panel, enter values forsecurity role references. Click **Add** to enter a rolename. Click **OK**. The role name is displayed in a tableon the wizard panel. To remove a role, select the role in the table andthen click **Remove**. View the help for [6.6.43.0.3: Assembly properties for security role references](#). Click **Next**.
8. On the **Adding Resource References** panel, enter references forresource connection factories. Click

Add to add a reference. You must enter values for a name, type, and authorization mode. Click **OK**. The reference is displayed in a table on the wizard panel. To remove a reference, select the reference in the table and then click **Remove**. View the help for [6.6.43.0.2 Assembly properties for resource references](#). Click **Next**.

9. On the **Adding EJB References** panel, enter values for EJB references. Click **Add** to add a reference. You must enter a value for the name, home interface, remote interface, and type. Click **OK**. The reference is displayed in a table on the wizard panel. To remove a reference, select the reference in the table and then click **Remove**. View the help for [6.6.43.0.1: Assembly properties for EJB references](#).
10. Click **Finish**.
11. Continue to add more enterprise beans as needed.

To import an existing enterprise bean:

1. Click **Import**.
2. Browse the file system to locate the desired archive. The contents of the archive are displayed in a window. Select one or more JAR files. The enterprise beans in the JAR file are displayed in the right window. Select an enterprise bean and then click **Add**. The enterprise beans are added to the Selected Components window. Click **OK**.

To remove an enterprise bean, select the enterprise bean in the table and then click **Remove**.

Continue adding and removing enterprise beans as necessary. Click **Next**.

Adding security roles

On the **Adding Security Roles** panel:

1. Click **Add**. Type a role name and, optionally, type a description. Click **OK**. The role name is displayed in a table on the wizard panel. View the help for [6.6.5.0.5: Assembly properties for security roles](#).
2. Continue to add security roles as needed. If you need to remove a role, select the role in the table and then click **Remove**.
3. Click **Next**.

Adding method permissions

On the **Adding Method Permissions** panel, indicate which security roles are permitted to invoke which methods.

1. To add method permissions, click **Add**. Enter a name for the method permission. View the help for [6.6.5.0.6: Assembly properties for method permissions](#).
2. Click **Add** next to the table of methods. Locate the method in the JAR file, select it, and then click **OK**.
3. Click **Add** next to the table of security roles. Select the appropriate security role and click **OK**.
4. Verify the information and click **OK**. The method permission is displayed in a table on the wizard panel.
5. To add multiple method permissions, click **Add** on the wizard panel and repeat the process.
6. Continue to add and remove methods and corresponding security roles as needed. If you need to remove a method permission, select the item and then click **Remove**.
7. Click **Next**.

Adding container transactions

On the **Adding Container Transactions** panel, indicate transaction attributes for the methods of the enterprise

bean.

1. To add a container transaction, click **Add**. Enter a name and choose a transaction attribute from the menu. View the help for [6.6.5.0.7: Assembly properties for container transactions](#).
2. Click **Add** to choose which methods are to be governed by this attribute. Locate the method in the JAR file, select it, and then click **OK**.
3. Verify the information and click **OK**. The container transaction is displayed in a table on the wizard panel.
4. To add multiple container transactions, click **Add** on the wizard panel and repeat the process.
5. Continue adding or removing container transactions as needed. If you need to remove a container transaction, select the item and then click **Remove**.

Setting additional properties and saving the archive

Click **Finish** to complete the wizard. To change settings for properties, click **Back** to return to the appropriate panel. Make any needed changes, and then click **Finish**.

After you click **Finish**, the contents of the archive are displayed in an Application Assembly Tool window. Review the contents in the navigation pane. You can continue adding or modifying properties as needed. For example, you can add binding information. When you are finished editing the archive, click **File->Save** to save the archive file.