



**Installation Guide
for i5/OS**



**Installation Guide
for i5/OS**

Note:

Before using this information and the product it supports, be sure to read the general information under “Notices” on page 39.

Edition Notice

This edition of this book applies to Version 6.0.0.3 of the following editions of WebSphere Commerce and to all subsequent releases and modifications until otherwise indicated in new editions:

- IBM WebSphere Commerce Enterprise (5724-i38)
- IBM WebSphere Commerce Professional (5724-i40)
- IBM WebSphere Commerce - Express (5724-i36)

Make sure you are using the correct edition for the level of the product.

Order publications through your IBM representative or the IBM branch office serving your locality.

IBM welcomes your comments. You can send your comments by using the online IBM WebSphere Commerce documentation feedback form.

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

© Copyright International Business Machines Corporation 1996, 2007. All rights reserved.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Preface	v
About this book	v
Update history	v
Conventions used in this book	v
Path variables	v
Other variables used in this book	vi
Product editions	1
WebSphere Commerce editions supported by this fix pack	1
Prerequisites	3
Master technote	3
Apply the required maintenance.	3
Additional maintenance required when using dynamic caching	3
iSeries Program Temporary Fixes (PTFs)	3
Installing the fix pack	5
Before applying the fix pack	5
Fix pack installation overview	5
Backing up your WebSphere Application Server profile	7
Installing new components	7
Preparing the system to run the fix pack installer	7
Next step	7
Silent installation	7
Updating the WebSphere Commerce installation directory.	8
Updating the WebSphere Commerce or WebSphere Commerce Payments instance	8
Post installation steps	10
Updating the WebSphere Commerce database manually	10
Remote Web server tasks	11
Determining the APARs that are installed on your machine.	11
Precompiling JSP files	11
Uninstalling the fix pack	13
Next step	13
Silent uninstallation	13
Removing the fix pack from the WebSphere Commerce or WebSphere Commerce Payments instance	14
Removing the fix pack from the WebSphere Commerce installation directory	14

Appendix A. Troubleshooting	17
Troubleshooting general WebSphere Commerce fix pack issues	17
Error message when accessing WebSphere Commerce tools	17
Error message when applying a fix pack using the WebSphere Commerce Update Installer Version 6.1.0.5	17
Unable to find the fix pack log file	17
WebSphere Commerce pages are not accessible after applying the fix pack	17
Accessing backup files.	18
Troubleshooting the install and uninstall of the WebSphere Commerce fix pack on your installation directory	18
Error encountered when completing a silent installation	18
The installer is unable to update a .jar file on the system	18
Error encountered when attempting silent uninstall of fix pack	19
Errors encountered when uninstalling the WebSphere Commerce fix pack.	19
Troubleshooting the install and uninstall of the WebSphere Commerce fix pack on your instance	19
Error encountered when applying the fix pack on a machine that has WebSphere Application Server 6.0.2.5 or higher installed	19
The fix pack failed to update the WebSphere Commerce instance during install or uninstall	20
The updatedb script fails during the application of the fix pack	23
Error encountered when completing a silent installation	24
The installer is unable to update a .jar file on the system	24
Error encountered when attempting silent uninstall of fix pack	25
Exceptions are logged in the createInstanceANT.err.log and createInstanceANT.log files	25

Appendix B. WebSphere Commerce updates	27
---	-----------

Notices	39
Trademarks	40

Preface

About this book

This document describes the steps required to apply the IBM® WebSphere® Commerce Version 6.0.0.3 fix pack to the following editions of WebSphere Commerce:

- IBM WebSphere Commerce Enterprise
- IBM WebSphere Commerce Professional
- IBM WebSphere Commerce - Express

Note: The IBM WebSphere Commerce Version 6.0.0.3 fix pack cannot be applied to IBM WebSphere Commerce Developer.

Update history

This section provides an outline of the history of changes to this book:


Edition	Updates
First edition	• Original publication of this document

Conventions used in this book

This book uses the following highlighting conventions:

- **Boldface type** indicates commands or graphical user interface (GUI) controls such as names of fields, icons, or menu choices.
- Monospace type indicates examples of text you type exactly as shown, file names, and directory paths and names.
- *Italic type* is used to emphasize words. Italics also indicate names for which you must substitute the appropriate values for your system.

 Enterprise Indicates information that is specific to WebSphere Commerce Enterprise

 Professional Indicates information that is specific to WebSphere Commerce Professional.

 Express Indicates information that is specific to WebSphere Commerce – Express.

 i5 Indicates information that is specific to WebSphere Commerce for i5/OS® for iSeries®.

Path variables

WAS_installdir

The installation path for WebSphere Application Server. The default installation directory is:

`/QIBM/ProdData/WebSphere/AppServer/V6/edition/`

WAS_userdir

The directory for all the data that is used by WebSphere Application Server that can be modified or needs to be configured by the user:

`/QIBM/UserData/WebSphere/AppServer/V6/edition/`

WC_installdir

The installation path for WebSphere Commerce. The default installation directory is:

`/QIBM/ProdData/CommerceServer60`

WC_userdir

The directory for all the data that is used by WebSphere Commerce which can be modified or needs to be configured by the user:

`/QIBM/UserData/CommerceServer60`

WC_profiledir

The directory for the WebSphere Application Server profile that is used by a WebSphere Commerce instance. For example:

`WAS_userdir/profiles/profile_name/`

UPDI_installdir

The installation path for the WebSphere Commerce Update Installer. For example:

`/QIBM/ProdData/WebSphere/UpdateInstaller/V61/UPDI`

Other variables used in this book

cell_name

This variable represents the name of the WebSphere Application Server cell.

host_name

This variable represents the fully qualified host name of your WebSphere Commerce server (for example, server.mydomain.ibm.com is fully qualified).

instance_name

This variable represents the name of the WebSphere Commerce instance with which you are working (for example, demo).

payments_instance_name

This variable represents the name of the WebSphere Commerce Payments instance with which you are working.

profile_name

This variable represents the name of the WebSphere Application Server profile that is created for your WebSphere Commerce instance. This variable has the same name as your WebSphere Commerce instance.

Product editions

WebSphere Commerce editions supported by this fix pack

This fix pack supports WebSphere Commerce Enterprise, Version 6.0 on the following operating systems:

- AIX®
- i5/OS
- Linux® for iSeries
- Linux for pSeries®
- Linux for xSeries®
- Linux for zSeries®
- Solaris
- Windows® 2000 and Windows 2003

This fix pack supports WebSphere Commerce Professional, Version 6.0 on the following operating systems:

- AIX
- i5/OS
- Linux for xSeries
- Solaris
- Windows 2000 and Windows 2003

This fix pack supports WebSphere Commerce Express, Version 6.0 on the following operating systems:

- i5/OS
- Linux for xSeries
- Windows 2000 and Windows 2003

For the specific requirements on each of the supported operating systems, refer to the WebSphere Commerce detailed system requirements technote #1224147 page.

Prerequisites

Review and complete any of the following sections that are applicable to your WebSphere Commerce installation.

Master technote

The master technote summarizes known fix pack issues. The technote provides information on how to sign up for automatic notification of new fix packs and flashes. Refer to the WebSphere Commerce V6.0 fix pack master install technote for more information.

Apply the required maintenance

Complete the following steps:

- Apply the required iFixes: WebSphere Commerce required maintenance.
- You must apply the WC-file-permission3 iFix as listed on the WC-file-permission3 iFix page.
- (optional) Apply the PK13460: Disk Cache Enhancements fix.

Additional maintenance required when using dynamic caching

If you are using WebSphere Application Server Versions 6.0.2.9 to 6.0.2.19, and have dynamic caching enabled, you must complete the steps found in the NotSerializableException thrown when using dynacache with WebSphere Commerce technote.

iSeries Program Temporary Fixes (PTFs)

Ensure the required Program Temporary Fixes (PTFs) have been applied to the WebSphere Commerce system. Refer to PTF Tables by version for WebSphere Commerce technote #1239904.

Before applying any PTFs, view the PTF cover letters for any additional instructions.

Installing the fix pack

Before applying the fix pack

Important:

- If you are operating a clustered environment, apply the fix pack on the machine where WebSphere Commerce is installed.
- Stop the WebSphere Commerce Help Server when applying the fix pack.
- Ensure the WebSphere Commerce Configuration Manager server is stopped before applying the fix pack.
- Backup the WebSphere Commerce application and database before you apply the fix pack. The database updates included in this fix pack can not be undone. If you want to undo the database update after applying the WebSphere Commerce fix pack, you must restore your database backup. Refer to your database documentation for information on backing up your database. To backup the Commerce application, refer to the WebSphere Application Server Information Center documentation on backing up applications.
- Check the `WC_profiledir/logs/server1/SystemOut.log` to ensure that the database version is at the same level as the EAR version. Fix packs always update the database version number. If the versions are not the same, errors can occur. For example, search for a message similar to:

```
0000000a SystemOut 0 WC.SERVER: Enterprise 6.0.0.0 / Database: ENT 6.0.0.0
```

The “Enterprise 6.0.0.0” is the EAR version, the “Database: ENT 6.0.0.0” is the Database version. The EAR version is retrieved from the `WC_profiledir/installedApps/cell_name/WC_instance_name.ear/properties/version/COMMERCE.product`. The Database version is retrieved from the SITE table.

- Disable your firewall, or allow access to the WebSphere Application Server administrative server. If you have installed a firewall on your machine, it can interfere with the application of the fix pack.
- Ensure that WebSphere Commerce and WebSphere Commerce Developer are at the same fix pack level.

Fix pack installation overview

The WebSphere Commerce fix pack is installed using the WebSphere Commerce Update Installer. The Update Installer is a tool that is used to apply maintenance to WebSphere Commerce and WebSphere Commerce Payments instances.

The WebSphere Commerce Update Installer can be downloaded from the following Web site: [WebSphere Commerce Update Installer](#).

Notes:

1. During the application of maintenance, to the WebSphere Commerce instance, the Update Installer stops the WebSphere Commerce application automatically.
2. In a clustered environment, the WebSphere Commerce Update Installer stops the WebSphere Commerce application of the selected WebSphere Commerce instance.

3. Updating the WebSphere Commerce instance can take 40 minutes or more depending on the size of your application and the speed of your system.

To minimize downtime, apply the fix pack at a time that will least impact the operation of your business. If you have customized your WebSphere Commerce instance, ensure that you have followed the documented deployment procedure in the WebSphere Commerce Information Center, otherwise your customizations are removed when the fix pack is installed. For more information on customized code, refer to Customized code deployment.

Additionally, you should apply the fix pack to your non-production environment first, to ensure that you do not negatively impact your production environment.

Here is an overview of the application process:

1. Install the WebSphere Commerce Update Installer software on your machine from the following Web site. [WebSphere Commerce Update Installer](#)
2. Download the appropriate fix pack.
3. Use the Update Installer to apply the fix pack to your WebSphere Commerce installation directory. Existing WebSphere Commerce and WebSphere Commerce Payments instances are not updated automatically. If you create any new instances after updating the WebSphere Commerce product installation directory, these new instances will be at the new fix pack level.
4. For each WebSphere Commerce or WebSphere Commerce Payments instance that you have created, before applying the fix pack, you must complete the following steps:
 - a. Start your management server:
 - If WebSphere Commerce is managed by WebSphere Application Server Deployment Manager (dmgr), start the deployment manager and all node agents. Optionally, your cluster can also be started.
 - If WebSphere Commerce is not managed by WebSphere Application Server Deployment Manager (dmgr), start your WebSphere Application Server server1.
 - b. Using the Update Installer, update the WebSphere Commerce or WebSphere Commerce Payments instance. To update the instance you must know the following information:
 - The WebSphere Commerce or WebSphere Commerce Payments instance name
 - If the associated database should be updated
 - c. If you have WebSphere Application Server security enabled for your WebSphere Commerce Payments instance you must know the following information:
 - The global security user ID
 - The global security password
 - d. During the WebSphere Commerce or WebSphere Commerce Payments instance update, the Update Installer stops the WebSphere Commerce application. If the instance is part of a clustered environment, the WebSphere Application Server deployment manager ensures that all nodes in that cluster are updated with the fix pack changes. For the Deployment Manager to distribute the application to all nodes, you must ensure that you have not disabled application distribution. Distribution requires that your node agents are running.
 - e. After the Update Installer has updated the instance, you must restart the WebSphere Commerce application.

- f. To ensure that all of your instances are updated, repeat these steps for each instance that exists on your machine.

If you have installed the WebSphere Commerce remote management utilities on a separate node from your WebSphere Commerce server, ensure that you also install the fix pack on that machine. If you do not install the fix pack on that machine, you are not able to use the WebSphere Commerce Configuration Manager client.

Backing up your WebSphere Application Server profile

Before applying the fix pack to your machine, you should backup your *WC_profiledir* directory. Refer to Backing up and recovering the application serving environment.

This fix pack overwrites certain JSP files related to the WebSphere Commerce tools pages. Refer to the text file *tools_jsps_changed.txt* available on the WebSphere Commerce Version 6.0.0.3 Download Page technote #4016604 for a list of the JSP files that are overwritten.

Before you apply the fix pack, back up any files that you have customized. If you have customized any files then you must reapply your customizations after the fix pack is applied. For more information on checking back files into source control, refer to the WebSphere Commerce Developer 6.0.0.3 Update Guide.

Installing new components

If any new components are installed from the WebSphere Commerce base (6.0) CD images the you must reinstall the fix pack in order to upgrade that component to the 6.0.0.3 level. For example, if the Configuration Manager client is loaded on a node using the base CD images the fix pack must be reinstalled to the Configuration Manager client node.

Preparing the system to run the fix pack installer

1. Download and install the WebSphere Commerce Update Installer.
2. Open the WebSphere Commerce Version 6.0.0.3 Download Page technote #4016604.
3. Download the fix pack file *6.0.0-WS-WCServer-FP003.pak* and save it to the *UPDI_installdir/maintenance* directory.

Notes:

- a. It is recommended that no other maintenance files reside in the *UPDI_installdir/maintenance* directory.

Next step

Install the fix pack by completing the following section:

- “Silent installation”

Silent installation

Complete this section to silently install the WebSphere Commerce fix pack. If you have already created a WebSphere Commerce or WebSphere Commerce Payments instance, you must apply the fix pack to the WebSphere Commerce product first. After the fix pack is applied to the product, you must then apply it to your instances.

Refer to the following sections:

- “Updating the WebSphere Commerce installation directory.”
- “Updating the WebSphere Commerce or WebSphere Commerce Payments instance.”

Updating the WebSphere Commerce installation directory

This section updates the WebSphere Commerce product.

1. Ensure that your user has *SECOFR authority.
2. Download the appropriate maintenance to the *UPDI_installdir/maintenance* directory.

WebSphere Commerce Version 6.0.0.3 Download Page technote #4016604

3. Navigate to the *UPDI_installdir/responsefiles* directory and open the *install.txt* file in a text editor.
4. Edit the *install.txt* file, ensuring the following sections are edited appropriately and are not commented out:

Note: To uncomment a line, remove the “#” character from the beginning of the appropriate entry.

- The `-W maintenance.package` contains the directory name for the fix pack. For example:

```
-W maintenance.package="/QIBM/ProdData/WebSphere/UpdateInstaller/  
V61/UPDI/maintenance"
```

- The `-W product.location` contains the full path name of the WebSphere Commerce installation directory. For example:

```
-W product.location="/QIBM/ProdData/CommerceServer60"
```

Verify that the `-W update.instancename` and `-W update.db` entries do not exist or are commented out. Save the file and exit.

Note: If you have a WebSphere Commerce instance created, you must first update your WebSphere Commerce product. After you have updated the product, you must again edit the response file, and run the Update installer again.

5. Open the QShell by typing QSH at the i5/OS command prompt.
6. Run the following command from the *UPDI_installdir*:
`update -devkit14 -options UPDI_installdir/responsefiles/install.txt`
7. Refer to the log files in the following directory to verify that your installation was successful:

```
WC_installdir/logs/update
```

If problems are encountered during the update process, refer to Appendix A, “Troubleshooting,” on page 17.

If you do not have an existing WebSphere Commerce or WebSphere Commerce Payments instance then the installation of the fix pack is complete.

Updating the WebSphere Commerce or WebSphere Commerce Payments instance

This section updates a WebSphere Commerce or WebSphere Commerce Payments instance:

1. Ensure that your user has *SECOFR authority.
2. Ensure that your WebSphere Commerce administrative server is started. For example:
 - If WebSphere Commerce is managed by WebSphere Application Server Deployment Manager (dmgr), start the deployment manager and all node agents. Optionally, your cluster can also be started.
 - If WebSphere Commerce is not managed by WebSphere Application Server Deployment Manager (dmgr), start the WebSphere Application Server server1.

Note: During the application of maintenance to the WebSphere Commerce instance, the Update Installer stops the WebSphere Commerce application automatically.

3. Navigate to the `UPDI_installdir/responsefiles` directory and open the `install.txt` file in a text editor.
4. To update a WebSphere Commerce or WebSphere Commerce Payments instance:

Note: If you have an instance created, you must first update your WebSphere Commerce product. After you have updated the product, you must again edit the response file, and run the Update installer again.

- a. Update the `-W maintenance.package` entry with the directory name that contains the maintenance package.
- b. Update the `-W product.location` with the location of the WebSphere Commerce install.
- c. Complete one of the following steps if you are updating an instance:
 - If you are updating a WebSphere Commerce instance, add the following lines to the end of the `install.txt` file:


```
-W update.instancename="instance_name"
-W update.db="true"
```

Note: If you set `-W update.db="false"` you must update the database manually. Refer to “Updating the WebSphere Commerce database manually” on page 10.

- If you do not have WebSphere Application Server security enabled with your WebSphere Commerce Payments instance, add the following lines to the end of the `install.txt` file:


```
-W update.instancename="payments_instance_name"
-W update.db="true"
```

Note: If you set `-W update.db="false"` you must update the database manually. Refer to “Updating the WebSphere Commerce database manually” on page 10.

- If you have WebSphere Application Server security enabled with your WebSphere Commerce Payments instance, add the following lines to the end of the `install.txt` file:


```
-W update.instancename="payments_instance_name"
-W update.db="true"
-W update.wassecurityenable="true"
-W update.wasuserid="WAS_user"
-W update.wasuserpassword="WAS_password"
```

Note: If you set `-W update.db="false"` you must update the database manually. Refer to “Updating the WebSphere Commerce database manually.”

5. Open the QShell by typing QSH at the i5/OS command prompt.
6. Run the following command from the `UPDI_installdir`:
`update -devkit14 -options UPDI_installdir/responsefiles/install.txt`
7. Refer to the log files in the following directory to verify that your installation was successful:
`WC_installdir/logs/update`
8. Complete the following steps based on the type of instances you have configured on your machine:
 - If you have a WebSphere Commerce instance created, restart the WebSphere Commerce application from the WebSphere administrative console.
 - If you have a WebSphere Commerce Payments instance created, restart the WebSphere Commerce Payments application from the WebSphere administrative console. If your WebSphere Commerce Payments instance has security enabled:
 - a. Navigate to the `WC_installdir/payments/bin` directory.
 - b. Run the following command:
`IBMPayServer payments_instance_name payment_password`

Note: If you have additional instances created, you can update them by updating the response file, and repeating the following section:

- “Updating the WebSphere Commerce or WebSphere Commerce Payments instance” on page 8.

Post installation steps

Important:

Refer to Appendix B, “WebSphere Commerce updates,” on page 27 for information on the APARs that are included in this fix pack. If you have installed APARs that are not included in this fix pack you must reinstall them after the fix pack is installed.

Updating the WebSphere Commerce database manually

If you did not choose to update your database automatically during the application of the WebSphere Commerce fix pack, you must manually update your database.

On the machine where you have applied the fix pack, complete the steps in this section to manually update your database:

Note: Ensure that you have backed up your database.

1. From a command prompt launch the following command:

```
WC_installdir/bin/updatedb.sh instance_name
```

Where `instance_name` is the name of the instance to be updated.

2. When the update is complete, review the output displayed in the console window and ensure that you have successfully updated the database to the correct fix pack level. For example:

```
UpdateSiteTable:
[EchoNL] Updating database fixpack level ...
[eCDatabaseVersionInfo] UPDATE SITE SET EDITION='ENT', VERSION=6,
RELEASE=0, MOD=0, FIXPACK=3 WHERE COMPNAME='BASE'
[eCDatabaseVersionInfo] SELECT COUNT(*) FROM SITE
[eCDatabaseVersionInfo] SELECT * FROM SITE
[eCDatabaseVersionInfo] Columns in SITE table:
[eCDatabaseVersionInfo] COMPNAME=BASE
[eCDatabaseVersionInfo] EDITION=ENT
[eCDatabaseVersionInfo] VERSION=6
[eCDatabaseVersionInfo] RELEASE=0
[eCDatabaseVersionInfo] MOD=0
[eCDatabaseVersionInfo] FIXPACK=3
[eCDatabaseVersionInfo] Updated SITE table successfully.
[EchoNL] Completed database fixpack update.

BUILD SUCCESSFUL
```

Remote Web server tasks

You must update the Web server machine with a new Stores.war file every time that you update the static Web content inside the application. Store Publishing and Upload Logo actions are examples of when you should update the Web server machine.

The Stores.war is located in the following directory: *WC_profiledir/installedApps/cell_name/WC_instance_name.ear/Stores.war*

Ensure that the path to this file is the same on the Web server node and the WebSphere Commerce node.

Note: Remove any JSP and JAR files from the *WC_instance_name.ear* directory on the Web server. Only static-content files should be in this directory on the Web server.

Determining the APARs that are installed on your machine

To determine the APARs that are installed on your WebSphere Commerce machine, refer to the Determining what APARs are installed on WebSphere Commerce Version 6.0 technote.

Precompiling JSP files

Precompile your JSP files before launching your store. Refer to: Compiling JavaServer Page files

Uninstalling the fix pack

Uninstalling the fix pack restores the WebSphere Commerce product files to the previous level. These instructions also remove the fix pack code from those WebSphere Commerce or WebSphere Commerce Payments instances that were updated at the same time the fix pack was applied to your system. After you apply the fix pack to your system, you cannot return your database configurations to their previous states.

WebSphere Commerce instances or WebSphere Commerce Payments instances that were created after the installation of the fix pack, will remain at the current fix pack level. Following these instructions will not restore these instances to the previous level. If these instances are required to be at the previous level, contact IBM Support for further assistance.

1. Ensure that you are logged in with a user profile that has *SECOFR authority.
2. Complete one of the following steps:
 - To remove the fix pack from the WebSphere Commerce product, stop the following servers:
 - WebSphere Commerce Help server.
 - WebSphere Commerce Configuration Manager server.
 - To remove the fix pack from the WebSphere Commerce instance or the WebSphere Commerce Payments instance only, start the following servers:
 - WebSphere Commerce database server.
 - WebSphere Commerce Application Server. For example, *server1*.
 - If you have a federated environment:
 - The WebSphere Application Server nodeagents are started.
 - The WebSphere Application Server deployment manager is started.

Next step

Uninstall the fix pack by completing the following section:

- “Silent uninstallation”

Silent uninstallation

Complete this section to silently uninstall the WebSphere Commerce fix pack. If you have applied the fix pack to your WebSphere Commerce or WebSphere Commerce Payments instance, you must uninstall the fix pack from that instance before uninstalling the fix pack from the WebSphere Commerce product.

Refer to the following sections:

- “Removing the fix pack from the WebSphere Commerce or WebSphere Commerce Payments instance” on page 14.
- “Removing the fix pack from the WebSphere Commerce installation directory” on page 14.

Removing the fix pack from the WebSphere Commerce or WebSphere Commerce Payments instance

Note: If you have created your instance **after** applying the fix pack, you cannot uninstall the fix pack from that instance.

1. Ensure that you are logged in with a user profile that has *SECOFR authority.
2. Navigate to the *UPDI_installdir*/responsefiles directory and open the *uninstall.txt* file in a text editor.
3. Complete the following steps:

- To remove the fix pack from a WebSphere Commerce instance:
 - a. Update the **-W backup.package** entry with the name of the maintenance package that you want to uninstall.

Note: If the **-W backup.package** is not specified, the most recently installed fix pack is uninstalled.

- b. Update the **-W product.location** with the location of the WebSphere Commerce install.
- c. Add the following lines to the end of the *uninstall.txt* file:

```
-W update.instancename="instance_name"
```

Where *instance_name* is the name of your WebSphere Commerce instance or WebSphere Commerce Payments instance.

- To remove the fix pack from a WebSphere Commerce Payments instance when WebSphere Application Server security is enabled:
 - a. Update the **-W backup.package** entry with the name of the maintenance package that you want to uninstall.

Note: If the **-W backup.package** is not specified, the most recently installed fix pack is uninstalled.

- b. Update the **-W product.location** with the location of the WebSphere Commerce install.
- c. Add the following lines to the end of the *uninstall.txt* file:

```
-W update.instancename="payments_instance_name"  
-W update.was.security.enable="true"  
-W update.wasuserid="was_user_ID"  
-W update.wasuserpassword="was_user_password"
```

4. Open the QShell by typing QSH at the i5/OS command prompt.
5. Run the following command from *UPDI_installdir*:

```
update -devkit14 -options UPDI_installdir/responsefiles/uninstall.txt
```
6. Refer to the log files in the following directory to verify that your uninstall was successful:

```
WC_installdir/logs/update
```

Removing the fix pack from the WebSphere Commerce installation directory

Note: If you have applied the fix pack to a WebSphere Commerce or WebSphere Commerce Payments instance, you must refer to “Removing the fix pack from the WebSphere Commerce or WebSphere Commerce Payments instance” before uninstalling the fix pack from your WebSphere Commerce product.

1. Ensure that you are logged in with a user profile that has *SECOFR authority.
2. Navigate to the *UPDI_installdir*/responsefiles directory and open the *uninstall.txt* file in a text editor.
3. To remove the fix pack from the WebSphere Commerce product:
 - a. Update the **-W backup.package** entry with the name of the maintenance package that you want to uninstall.

Note: If the **-W backup.package** is not specified, the most recently installed fix pack is uninstalled.

- b. Update the **-W product.location** with the location of the WebSphere Commerce install.
- c. Ensure that the following line does not exist or is commented out of the *uninstall.txt* file:

```
-W update.instancename="instance_name"
```

Where *instance_name* is the name of your WebSphere Commerce instance or WebSphere Commerce Payments instance.

4. Open the QShell by typing QSH at the i5/OS command prompt.
5. Run the following command from *UPDI_installdir*:

```
update -devkit14 -options UPDI_installdir/responsefiles/uninstall.txt
```
6. Refer to the log files in the following directory to verify that your uninstall was successful:

```
WC_installdir/logs/update
```
7. Restart your WebSphere Commerce or WebSphere Commerce Payments instance.

Appendix A. Troubleshooting

Troubleshooting general WebSphere Commerce fix pack issues

Error message when accessing WebSphere Commerce tools

When accessing the WebSphere Commerce tools such as WebSphere Commerce Accelerator, the following message is displayed:

```
You are not authorized to view this page  
HTTP Error 403 - Forbidden
```

In the Web server's error log, you see a message similar to:

```
[Fri Jun 16 08:38:24 2006] [error] [client ip] (3401)Permission denied.:  
ZSRV_MSG064B: access to /adminconsole denied
```

This error is caused by incorrect file permissions in the WebSphere Commerce Enterprise Application EAR file. See the Page is forbidden when accessing WebSphere Commerce tools (HTTP Error 403) technote for more information.

Error message when applying a fix pack using the WebSphere Commerce Update Installer Version 6.1.0.5

You receive the following error message when using the WebSphere Commerce Update Installer to apply the maintenance:

The following APARs are installed or selected already for the current maintenance package.

This message means that the fixes or APARs that you have selected to install is included in, or superseded by, the fix pack. All of the APARS that are listed can be left unchecked when installing the fix pack.

Unable to find the fix pack log file

If the fix pack application failed, and you are unable to find the WebSphere Commerce log file in the *WC_installdir/logs/update* directory, refer to the following location:

```
UPDI_installdir/logs/tmp
```

WebSphere Commerce pages are not accessible after applying the fix pack

After applying the WebSphere Commerce Fix Pack and restarting WebSphere Commerce, some WebSphere Commerce pages will not be accessible.

The following error is displayed in the *SystemErr.log* file:

```
java.io.InvalidClassException
```

This error can be caused by a mismatch between a class file in the WebSphere Commerce EAR file and a class file stored in the Dynacache. To resolve the problem, restart the application server (for example, *server1*) that is associated with WebSphere Commerce .

Accessing backup files

The WebSphere Commerce fix pack update installer makes a backup of all the files modified during the fix pack installation.

- The backups made while installing the fix pack on the WebSphere Commerce product directory can be found in a .pak file at the following directory
`WC_installdir/properties/version/update/backup`
- The backups made while installing the fix pack on your WebSphere Commerce instance can be found in a .pak file at the following location:
`WC_userdir/instances/instance_name/properties/version/update/backup`

Troubleshooting the install and uninstall of the WebSphere Commerce fix pack on your installation directory

Error encountered when completing a silent installation

Error encountered when referring to an incorrect .pak file location

When completing a silent installation, you encounter an error message similar to:

```
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.  
UPDIMaintenanceInformationAction,  
err, No such path or directory. /QIBM/ProdData/WebSphere/UpdateInstaller/  
V61/UPDI/maintenance/maintenance.xml  
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.  
UPDIMaintenanceInformationAction,  
err, No such path or directory. /QIBM/ProdData/WebSphere/UpdateInstaller/  
V61/UPDI/maintenance/maintenance.xml  
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.  
UPDIMaintenanceInformationAction,  
err, java.io.FileNotFoundException: No such path or directory.  
  
/QIBM/ProdData/WebSphere/UpdateInstaller/V61/UPDI/maintenance/maintenance.xml  
at java.lang.Throwable.<init>(Throwable.java:195)  
at java.lang.Exception.<init>(Exception.java:41)  
at java.io.IOException.<init>(IOException.java:40)  
at java.io.FileNotFoundException.<init>(FileNotFoundException.java:46)  
at java.io.FileInputStream.open(Native Method)  
at java.io.FileInputStream.<init>(FileInputStream.java:106)  
at com.ibm.ws.install.ni.framework.io.DiskFileSystem.readEntry  
(DiskFileSystem.java:87)  
at com.ibm.ws.install.ni.framework.io.FileSystemEntry.getInputStream  
(FileSystemEntry.java:231)  
at com.ibm.ws.install.ni.framework.xml.XMLUtils.  
getSimpleXMLParserFromFileSystemEntry(XMLUtils.java:91)  
at com.ibm.ws.install.ni.ismp.actions.UPDIMaintenanceInformationAction.execute  
(UPDIMaintenanceInformationAction.java:60)  
at com.installshield.wizard.StandardWizardListener.execute  
(StandardWizardListener.java:123)  
at com.installshield.wizard.StandardWizardListener.currentBeanChanged  
(StandardWizardListener.java:106)
```

If you encounter this error edit your response file and ensure that you have the correct location for the WebSphere Commerce fix pack .pak file.

The installer is unable to update a .jar file on the system

If you receive an error message indicating that the installer is unable to update a .jar file on the system, refer to the `WC_installdir/logs/update/maintenance_name/updatetrace.log` file. Search this log file for an error message similar to:

```
Installer has pro2006.09.25 12:04:30.328 EDT java.lang.NullPointerException
at com.ibm.ws.install.ni.framework.io.ZipFileSystem.copyZipEntry
(ZipFileSystem.java:2010)
at com.ibm.ws.install.ni.framework.io.ZipFileSystem.copyZipEntry
(ZipFileSystem.java:1995)
at com.ibm.ws.install.ni.framework.io.ZipFileSystem.copyThisEntryInThisSource
ToThisZipFileWithThisName(ZipFileSystem.java:989)
at com.ibm.ws.install.ni.framework.io.ZipFileSystem.applyZipFileOperationsTo
ZipFile(ZipFileSystem.java:2112)
at com.ibm.ws.install.ni.framework.io.ZipFileSystem.performAllZipOperationsFor
ThisTargetFile(ZipFileSystem.java:88)
at com.ibm.ws.install.ni.framework.fileactions.ZipFileOperationController.
performAllZipOperations(ZipFileOperationController.java:108)
at com.ibm.commerce.install.updi.product.wc.WCUpdateComponent.execute
(WCUpdateComponent.java:119)
```

If you receive this error message, check if the path to the .pak file contains spaces. If there are spaces in the path, move the fix pack file to a path that does not contain spaces and complete the following steps:

1. Rerun the Update Installer to uninstall the fix pack from the system.
2. Reapply the fix pack to the system.

Error encountered when attempting silent uninstall of fix pack

The uninstall fails with the following message:

```
CWUPI0024E: The update operation is not permitted on FP003.pak. Either
this maintenance package is corrupted, or it has dependencies that prevent
this maintenance package from being updated.
```

If you encounter this error, edit your response file and ensure that you have the full name of the fix pack listed.

For example:

```
6.0.0-WS-WCServer-FP003.pak
```

Errors encountered when uninstalling the WebSphere Commerce fix pack.

When the uninstall of the WebSphere Commerce fix pack fails and you encounter the following error message:

```
CWUPI0010E: Cannot uninstall an installed maintenance package. No corresponding
maintenance backup package is available in the product maintenance backup directory.
```

Ensure that you have removed all dependent software, such as the WebSphere Commerce Feature Packs, from the machine and attempt to uninstall the fix pack again.

Troubleshooting the install and uninstall of the WebSphere Commerce fix pack on your instance

Error encountered when applying the fix pack on a machine that has WebSphere Application Server 6.0.2.5 or higher installed

If you have WebSphere Application Server Version 6.0.2.5 or higher installed on your machine and you are using a WebSphere Commerce Payments instance, refer to:

The fix pack failed to update the WebSphere Commerce instance during install or uninstall

Prerequisite checking fails during the application of the fix pack

Check the log files: If the prerequisite checking failed during the application of the fix pack, the following message is produced:

```
Failed to export the WebSphere Commerce instance to user_temp_dir/wcupdate directory. For more information, see the log file: "WC_installdir/logs/update/actions/install/exportear_instance_name.log".
```

If the prerequisite checking failed during uninstall, the following message is produced:

```
Failed to export the WebSphere Commerce instance to user_temp_dir/wcupdate directory. For more information, see the log file: "WC_installdir/logs/update/actions/uninstall/exportear_instance_name.log".
```

Ensure that the WebSphere Application Server Administrative server is started, and attempt the install or uninstall again.

Search for specific error codes in the log files: Search for the WASX7023E error code in the *exportear_instance_name.log* file under the stopWCApplications or stopPMAApplications target. For example:

```
stopPMAApplications:
  [wsadmin] WASX7023E: Error creating "SOAP" connection to host "localhost";
exception information: com.ibm.websphere.management.exception.
ConnectorNotAvailableException: com.ibm.websphere.management.exception.
ConnectorNotAvailableException: Failed to get a connection with IP
address associated with hostname localhost
  [wsadmin] WASX7213I: This scripting client is not connected to a server
process; please refer to the log file C:\Program Files\IBM\WebSphere\AppServer\
profiles\wpm\logs\wsadmin.traceout for additional information.
  [wsadmin] WASX8011W: AdminTask object is not available.
  [wsadmin] WASX7303I: The following options are passed to the scripting
environment and are available as argument that is stored in the argv variable:
"[wpm_Commerce_Payments_App]"
  [wsadmin] WASX7017E: Exception received while running file "C:/Program Files/
IBM/WebSphere/CommerceServer60/config/deployment/scripts/stopApps.jacl";
exception information: com.ibm.ws.scripting.ScriptingException: AdminControl
service not available
```

Ensure that the WebSphere Application Server Administrative server is started, and attempt the install or uninstall again.

Incomplete log files: If the last message in the *exportear_instance_name.log* is stopWCApplications or stopPMAApplications, check the following log file for a WSPProfileException error:

```
UPDI_installdir/logs/tmp/updatetrace.log
```

For example:

```
2006.09.25 17:04:45.984 EDT Failed to export the WebSphere
Commerce instance to C:\DOCUME~1\user\LOCALS~1\Temp\wcupdate
directory.
2006.09.25 17:04:46.015 EDT C:\WebSphere\CommerceServer60\config\
```

```
deployment\xml\exportEar.xml:55: The following error occurred while
executing this line:
C:\WebSphere\CommerceServer60\config\deployment\xml\exportEar.xml:145:
WSPprofileException profileName=wpm
```

If you experience this error message, run the following command to ensure that your profile is registered:

- `WAS_installdir/bin/wasprofile -listProfiles`

If the profile is not listed in the output of this command, contact WebSphere Commerce Support.

Problem deploying WebSphere Commerce

Problem: If the update installer fails to deploy the WebSphere Commerce instance to your WebSphere Application Server configuration this message, or one similar, is logged in the `updateLog.txt` file:

```
Install,com.ibm.ws.install.ni.ismp.actions.InstallNIFMaintenance, msg1,
Failed to deploy the WebSphere Commerce instance
```

The `updateLog.txt` file will also list one of the following log files:

- Install:
`WC_installdir/logs/update/actions/install/deployear_instance_name.log`
- Uninstall:
`WC_installdir/logs/update/actions/uninstall/deployear_instance_name.log`

If a problem with the `deployear_instance_name` task is indicated in these log files, check the following trace file for details:

```
WC_profiledir/logs/wsadmin.traceout.log
```

Cause: The `wsadmin.traceout.log` may contain messages indicating what has caused this problem. For example:

```
[wsadmin] com.ibm.websphere.management.exception.AdminException
[wsadmin] com.ibm.websphere.management.application.client.AppDeploymentException:
AppDeploymentException: [ADMA0092E: An unexpected exception occurred while
preparing task DataSourceFor10CMPBeans. Check the server machine First Failure
Data Capture tool (FFDC) for more information.]
```

These messages indicate that customizations were not correctly deployed. To correctly deploy any customizations, refer to the information in Stages of deploying customized assets to properly deploy any customized assets you have.

Solution: After you have properly deployed your customized assets, you can reapply the fix pack update. Complete these steps:

1. If the following directory exists:
`WC_userdir/instances/instance_name/properties/version/update/backup.save`

Do the following:

- Delete the following directory:
`WC_userdir/instances/instance_name/properties/version/update/backup`
- Rename the following directory:
`WC_userdir/instances/instance_name/properties/version/update/backup.save`

to the following:

- `WC_userdir/instances/instance_name/properties/version/update/backup`
- If the following directory exists:
`WC_userdir/instances/instance_name/properties/version/update/
confighistory.save`

Do the following:

 - Delete the following directory:
`WC_userdir/instances/instance_name/properties/version/update/confighistory`
 - Rename the directory:
`WC_userdir/instances/instance_name/properties/version/update/
confighistory.save`

to the following:
`WC_userdir/instances/instance_name/properties/version/update/confighistory`
 - Restart the update installer, and reapply the fix pack to your WebSphere Commerce instance.

If there is still a problem with applying or removing the fix pack, complete the following steps:

- Back up the following directory:
`WC_userdir/instances/instance_name/properties/version/update/backup`
- Open the following file:
`WC_userdir/instances/instance_name/properties/version/update/backup/
updateStatus.xml`

and remove the package sections where the **maintenancefilename** attribute refers to the maintenance you are working with. An example of a section, that should be entirely removed, is:

```
<package isprimary="true" maintenancefilename="6.0.0-WS-WCServer-FP003.pak"
  maintenancename="WebSphere Commerce 6.0.0.3" mode="uninstallupdate"
  timestamp="date time" uritoreinstall="" uritouninstall="zip:///C:/
  WebSphere/CommerceServer60/instances/demo/properties/version/update/
  backup/6.0.0-WS-WCServer-FP003.pak">
  <preuninstall/>
  <uninstall>
<package isprimary="true" maintenancefilename="6.0.0-WS-WCServer-FP003.pak"
  maintenancename="WebSphere Commerce 6.0.0.3" mode="uninstallupdate"
  timestamp="date time" uritoreinstall="" uritouninstall="zip:///C:/
  WebSphere/CommerceServer60/instances/demo/properties/version/update/
  backup/6.0.0-WS-WCServer-FP003.pak"/>
  </uninstall>
</package>
<package MaintenanceNamesOfPackagesToBeCleaned="" URIsOfPackagesToBeCleaned=""
  URIsOfPackagesToBeExecuted="zip:///C:/WebSphere/CommerceServer60/instances/
  demo/properties/version/update/backup/6.0.0-WS-WCServer-FP003.pak"
  isprimary="true" maintenancefilename="6.0.0-WS-WCServer-FP003.pak"
  maintenancename="WebSphere Commerce 6.0.0.3" mode="installupdate"
  modified="true" timestamp="date time" uritoreinstall=""
  uritouninstall="zip:///C:/WebSphere/CommerceServer60/instances/demo/
  properties/version/update/backup/6.0.0-WS-WCServer-FP003.pak">
  <preinstall/>
  <install>
<package isprimary="true" maintenancefilename="6.0.0-WS-WCServer-FP003.pak"
  maintenancename="WebSphere Commerce 6.0.0.3" mode="installupdate"
  timestamp="date time" uritoreinstall="" uritouninstall="zip:///C:/WebSphere/
  CommerceServer60/instances/demo/properties/version/update/backup/
  6.0.0-WS-WCServer-FP003.pak"/>
  </install>
</package>
```

3. Delete the following directory:
`WC_userdir/instances/instance_name/properties/version/update/backup/recovered`
4. If a problem was encountered while applying maintenance, do the following:

Note: This step is not required if a problem was encountered while uninstalling maintenance.

Remove the XML section, that refers to the maintenance you were trying to apply, in directory:

`WC_userdir/instances/instance_name/properties/version/update/backup/NIFStack.xml`

An example of this XML section is:

```
<maintenance name="WebSphere Commerce 6.0.0.3" order="0">
  <param name="features" value="commerceear;update"/>
  <param name="uritoreinstall" value=""/>
  <param name="isenablingifix" value="false"/>
  <param name="producttype" value="NA"/>
  <param name="wasinstalledasmaintenance" value="true"/>
  <param name="packagetype" value="NA"/>
  <param name="wasinstalledasprimary" value="true"/>
  <param name="uninstallablebyupdi" value="true"/>
  <param name="filename" value="6.0.0-WS-WCServer-FP003.pak"/>
  <param name="info" value="WebSphere Commerce 6.0.0.3"/>
  <param name="hasprofileupdates" value="false"/>
  <param name="supercedesapars" value=""/>
  <param name="supercedes" value=""/>
  <param name="builddate" value="2007/08/27"/>
  <param name="autouninstallable" value="false"/>
  <param name="iscopyjdkrequired" value="false"/>
  <param name="isbackuppackage" value="false"/>
  <param name="apars" value="IY79965;IY83748;LI71315;SI23474;"/>
  <param name="isofficialfix" value="true"/>
  <param name="targetsubproductids" value="wc.server.pro"/>
  <param name="targetproductids" value="wc.server.pro"/>
</maintenance>
```

5. If a problem was encountered while applying maintenance, do the following:

Note: This step is not required if a problem was encountered while uninstalling maintenance.

Delete the following file:

`WC_userdir/instances/instance_name/properties/version/update/backup/6.0.0-WCServer-FP003.pak.`

6. Restart the update installer, and reapply the fix pack to your WebSphere Commerce instance.

The updatedb script fails during the application of the fix pack

If the updatedb process fails during fix pack update, complete the following steps:

1. Review the log files in the following locations:

- `WC_userdir/instances/instance_name/logs/trace.txt`
- `WC_userdir/instances/instance_name/logs/messages.txt`

Review these error messages with your database administrator to ensure there are no data errors.

2. Navigate to the `WC_installdir/bin` directory.
3. Perform one of the following steps:

- Run the updatedb command again. Refer to “Updating the WebSphere Commerce database manually” on page 10 for more information.
 - Restore the original database and run the updatedb command. Refer to “Updating the WebSphere Commerce database manually” on page 10 for more information.
4. If this problem cannot be resolved, contact IBM WebSphere Commerce Support.

Error encountered when completing a silent installation

Error encountered when referring to an incorrect .pak file location

When completing a silent installation, you encounter an error message similar to:

```
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.
UPDIMaintenanceInformationAction,
err, No such path or directory. /QIBM/ProdData/WebSphere/UpdateInstaller/
V61/UPDI/maintenance/maintenance.xml
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.
UPDIMaintenanceInformationAction,
err, No such path or directory. /QIBM/ProdData/WebSphere/UpdateInstaller/
V61/UPDI/maintenance/maintenance.xml
(Sep 21, 2006 2:21:27 PM), Install, com.ibm.ws.install.ni.ismp.actions.
UPDIMaintenanceInformationAction,
err, java.io.FileNotFoundException: No such path or directory.

/QIBM/ProdData/WebSphere/UpdateInstaller/V61/UPDI/maintenance/maintenance.xml
at java.lang.Throwable.<init>(Throwable.java:195)
at java.lang.Exception.<init>(Exception.java:41)
at java.io.IOException.<init>(IOException.java:40)
at java.io.FileNotFoundException.<init>(FileNotFoundException.java:46)
at java.io.FileInputStream.open(Native Method)
at java.io.FileInputStream.<init>(FileInputStream.java:106)
at com.ibm.ws.install.ni.framework.io.DiskFileSystem.readEntry
(DiskFileSystem.java:87)
at com.ibm.ws.install.ni.framework.io.FileSystemEntry.getInputStream
(FileSystemEntry.java:231)
at com.ibm.ws.install.ni.framework.xml.XMLUtils.
getSimpleXMLParserFromFileSystemEntry(XMLUtils.java:91)
at com.ibm.ws.install.ni.ismp.actions.UPDIMaintenanceInformationAction.execute
(UPDIMaintenanceInformationAction.java:60)
at com.installshield.wizard.StandardWizardListener.execute
(StandardWizardListener.java:123)
at com.installshield.wizard.StandardWizardListener.currentBeanChanged
(StandardWizardListener.java:106)
```

If you encounter this error edit your response file and ensure that you are referring to the correct location for the WebSphere Commerce fix pack .pak file.

The installer is unable to update a .jar file on the system

If you receive an error message indicating that the installer is unable to update a .jar file on the system, refer to the *WC_installdir/logs/update/maintenance_name/*updatetrace.log file. Search this log file for an error message similar to:

```
Installer has pro2006.09.25 12:04:30.328 EDT java.lang.NullPointerException
at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.copyZipEntry
(ZIPFileSystem.java:2010)
at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.copyZipEntry
(ZIPFileSystem.java:1995)
at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.copyThisEntryInThisSource
ToThisZipFileWithThisName(ZIPFileSystem.java:989)
at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.applyZIPFileOperationsTo
ZIPFile(ZIPFileSystem.java:2112)
at com.ibm.ws.install.ni.framework.io.ZIPFileSystem.performAllZIPOperationsFor
```



```
ThisTargetFile(ZIPFileSystem.java:88)
at com.ibm.ws.install.ni.framework.fileactions.ZIPFileOperationController.
performAllZIPOperations(ZIPFileOperationController.java:108)
at com.ibm.commerce.install.updi.product.wc.WCUpdateComponent.execute
(WCUpdateComponent.java:119)
```

If you receive this error message, check if the path to the fix pack (maintenance) pak file contains spaces. If there are spaces in the path, move the fix pack file to a path that does not contain spaces and complete the following steps:

1. Rerun the Update Installer to uninstall the fix pack from the system.
2. Reapply the fix pack to the system.

Error encountered when attempting silent uninstall of fix pack

The uninstall fails with the following message:

```
CWUPI0024E: The update operation is not permitted on FP001.pak. Either
this maintenance package is corrupted, or it has dependencies that prevent
this maintenance package from being updated.
```

If you encounter this error, edit your response file and ensure that you have the full name of the fix pack listed.

For example:

```
6.0.0-WS-WCServer-FP003.pak
```

Exceptions are logged in the createInstanceANT.err.log and createInstanceANT.log files

When creating an authoring instance, errors similar to the following are logged in the createInstanceANT.err.log and createInstanceANT.log files

- createInstanceANT.err.log:

```
[2007.03.21 08:07:26] [sql] Failed to execute: DROP TRIGGER STAG0082
[2007.03.21 08:07:26] [sql] COM.ibm.db2.jdbc.DB2Exception: [IBM][CLI Driver]
[DB2/NT] SQL0204N "BUILD.STAG0082" is an undefined name. SQLSTATE=42704
```
- createInstanceANT.log:

```
[2007.03.21 08:07:25] RunSQLFileOnErrorContinue:
[2007.03.21 08:07:26] [sql] Executing file: D:\WebSphere\CommerceServer60\
schema\db2\fixpack2\wcs.d146740_trigger.sql
[2007.03.21 08:07:26] [sql] Failed to execute: DROP TRIGGER STAG0082
[2007.03.21 08:07:26] [sql] COM.ibm.db2.jdbc.DB2Exception: [IBM]
[CLI Driver][DB2/NT] SQL0204N "BUILD.STAG0082" is an undefined name.
SQLSTATE=42704
[2007.03.21 08:07:26] [sql] 0 of 1 SQL statements executed successfully
```

These errors are caused by the following scenarios:

- You are creating a new instance with a staging database. The staging trigger is not created and the updatedb command catches an exception in the log file.
- You have an existing instance with a staging database. The staging trigger is created and the updatedb command catches an exception in the log file.

These error messages can safely be ignored.

Appendix B. WebSphere Commerce updates

If you have installed other APARs that are not listed in this section, you will need to reinstall them after applying this fix pack.

This fix pack contains the interim fixes (APARs) for the WebSphere Commerce Sales Center client:

Interim fix #	Description
APAR#IY85624	Corrected MANIFEST_ID field not updated in ORDITEMCONF table issue.
APAR#IY85624	Corrected SalesContainerItemsPageManager customization issue.
APAR#IY86085	Corrected an issue where, after cloning order GUI is not receiving model change events.
APAR#IY86085	Corrected customer not cleared from stores view when closed issue.
APAR#IY86085	Corrected an issue where editors do not scroll when tab through fields.
APAR#IY86085	Corrected FindDialog stops search when=0, but resultSetSize not reached issue.
APAR#IY86085	Corrected inconsistency and UI issues of the Contact history view.
APAR#IY86085	Corrected prodcompeditor does not close window when clear store clicked issue.
APAR#JR22550	Corrected customer editor update button enablement.
APAR#IY91991	The uninstallation of the IBM Sales Center client through WEDM failed.
APAR#JR25581	IBM Sales Center treats milliseconds as absolute values instead of percentages.
APAR#JR24891	Corrected an issue where you cannot deselect hip as complete for single order item.

This fix pack contains the interim fixes (APARs):

Interim fix #	Description
APAR#IY79965	Corrected an error returned due to serialization problems in data misleading issue.
APAR#IY83748	Corrected an unable to delete template that is assigned to a category in WebSphere Commerce Accelerator issue.
APAR#IY83823	Corrected PricingDataBean using commitCopyHelper() issue.
APAR#IY83995	Corrected an issue where the DN should be able to handle \,.
APAR#IY84162	Performance improvement for Manage Files page of WebSphere Commerce Accelerator
APAR#IY84389	PCI enablement.
APAR#IY84484	Addressed findApplicableByOrgEntity SQL performance.
APAR#IY84567	Corrected an available languages for a store contains a "selected" entry issue.
APAR#IY85030	Corrected an issue where WebSphere Commerce Accelerator access continues to work after Sales Center logoff.
APAR#IY85033	Corrected a content sensitive help of Blocked Order report page issue.

APAR#IY85037	Corrected a contract export/import using WebSphere Commerce Accelerator issue.
APAR#IY85624	Corrected a MANIFEST_ID field not updated in ORDITEMCONF table issue.
APAR#IY85624	DataBean for partial shipment.
APAR#IY85624	Corrected a NullPointerException if setup TAXJCRULE with no FFMCenter issue.
APAR#IY85929	Corrected an issue where the promotion engine gets protected context attribute and add protected context attribute.
APAR#IY86088	Corrected an extra space in org field of custTerritoryGroup page issue.
APAR#IY86468	Corrected JavaScript™ error on Criteria page.
APAR#IY86472	Corrected a find store (store name) ignoreCaseBegin is case sensitive issue.
APAR#IY86715	Corrected a blank page issue when using search with double quotes.
APAR#IY86766	Corrected a payment methods issue in SupplyMarketplace for auction.
APAR#IY86766	Corrected a Submit a AutoBid issue.
APAR#IY86769	Corrected a duplicate category issue when browsing catalog during promotion creation.
APAR#IY87038	Corrected a valid offer does not get picked up for a pending order issue.
APAR#IY88549	Provided Web Service invocation update for OpenWebServicesComponent.
APAR#IY89093	Corrected a parameter value in log file issue.
APAR#IY89489	Enhanced security.
APAR#JR22709	Corrected an issue where the optimizer statistics are destroyed and regenerated with estimate option.
APAR#JR23657	Corrected a catalog search tool not support nonbuyable items/products issue.
APAR#JR23680	Corrected a date range message persistence in Contract Activity issue.
APAR#JR23688	Corrected an issue of not assigning shipping codes to products, only items.
APAR#JR23695	Corrected a Daily Sales issue.
APAR#JR23771	Corrected an issue where the Find Quote finds Orders as well.
APAR#JR23844	Corrected an AddressDataBean does not populate for address of status 'T' issue.
APAR#JR24147	Corrected a Requisition List requires User's Organization issue.
APAR#JR24205	Corrected a Null Pointer Exception when enabling persistent sessions issue.
APAR#JR24243	Corrected an issue where the guest shopping cart does not merge with registered user's cart.
APAR#JR24312	Corrected an issue where the session code didn't extract the storeId from the body of a post request.
APAR#JR24336	Corrected a List of Files displayed should be sorted by alphabetical order issue.
APAR#JR24385	Corrected limitation with pricing component call.
APAR#JR24681	Corrected a SSL accelerator fails when using default port # issue.

APAR#LI71252	Corrected an issue where two order cancellation emails are sent to shoppers.
APAR#LI71288	Corrected a deadlock in INVENTORY in repeated scheduled orders.
APAR#LI71315	Corrected an issue displaying sales catalog instead of the master catalog.
APAR#LI71375	Corrected a WebSphere Commerce XHTML issue.
APAR#SI23474	Store DN as uppercase to avoid multiple toUpper calls.
APAR#IY88656	Corrected an issue to allow future invalidation through the cacheivl table.
APAR#JR25039	Corrected an issue where the promotion engine was not applying the promotion offering.
APAR#IY90973	Corrected an issue where the promotion name should allow numeric characters.
APAR#JR25364	Corrected an issue where no warnings are logged when WebSphere Commerce Analyzer fails to save long promotion descriptions.
APAR#JR25363	Corrected an issue where you are unable to specify the category for the product promotion when category is too long.
APAR#IY87190	Corrected an issue where a custom contract does not display discounts correctly from the base contract.
APAR#JR24752	Corrected an issue where the campaign panel fails to load if the number of activities is large.
APAR#IY90976	Corrected an issue with the ShopcartDrivenAgendaBuilder when modifying the shopcart item to be quantity 0.
APAR#JR24465	Corrected an issue where the RememberMe functionality fails due to Null LangId.
APAR#IY86836	Corrected an issue where the ProductDisplay command is slow with 13 million rows in PRESETCEREL.
APAR#LI72077	Corrected an issue where the user experiences slow performance with GetContractUnitPrice.
APAR#JR24733	Corrected an issue where the user's member group list should be sorted.
APAR#JR24790	Corrected an issue where the length of address fields are cut short.
APAR#JR25163	Corrected an issue where Oracle does not accept "" as empty string.
APAR#JR24970	Corrected an issue where the user cannot complete a promotion for the dynamic kit.
APAR#IY90774	Corrected an issue where the Marketing > Promotions > Segment summary is not working.
APAR#JR23846	Corrected an issue where the Quotes to Order Conversion Rate report was not displaying the correct results.
APAR#IY93118	Corrected an issue where logging into the Administration Console fails after configuring the WebSphere Commerce to LDAP server.
APAR#LI72077	Improved the performance of GetContractUnitPriceCmdImpl.
APAR#JR24757	Corrected an issue where the getEntitledSubCatalogGroupsByStore throws NullPointerExceptions.
APAR#JR24537	Corrected an issue where the stardate and endate in the offer table are not updated in database.
APAR#IY90803	Corrected an issue where searching for orders using customer name does not work.
APAR#JR24495	Corrected an issue to allow DBUpdateTool to re-encrypt data custom tables.

APAR#JR25013	Corrected an issue where the user cannot find the wcsadmin user for MQ on startup after enabling LDAP.
APAR#JR24848	Corrected an issue where the price adjustment does not refresh after applying IY87190.
APAR#JR25025	Corrected an issue where the user is unable to approve a second order since the previous order is cached.
APAR#IY86843	Corrected an issue where the Account Representative drop-down lists are truncated in MSC.
APAR#JR24748	Corrected an issue where the GiftRegistryItemUpdate and GiftRegistryItemDelete do not work properly.
APAR#LI71582	Corrected an issue where the setdbenv scripts are using old loader classes.
APAR#IY91134	Corrected an issue where the Auction Notify messages do not compile due to nullpointer exceptions.
APAR#LI71714	Corrected an issue where the Add to Shopping Cart action fails for the Content click action.
APAR#JR25336	Corrected an issue where the FileTreeDataBean uses hard coded EAR path.
APAR#LI71608	Corrected an issue where the user cannot delete the Task Group from the workspace upon failed quick publish.
APAR#JR24498	Corrected an issue where specific products are not showing after assigning the Shipping Code.
APAR#JR24621	Corrected an issue that occurred when displaying the information for an Ad Copy in WebSphere Commerce Accelerator, the Category Name does not display if it includes the '&' character.
APAR#JR25378	Corrected an issue where products that are created in a hosted store do not show up when added to a web activity for an emarketing spot.
APAR#LI71594	Corrected an issue where adding an item to the wish-list fails.
APAR#LI71607	Corrected an issue with the shopping flow.
APAR#IY90929	Corrected an issue where addresses were limited 10 for shipping and billing.
APAR#JR25085	Corrected an issue where x-data/xact-error is wrongly treated as unsupported.
APAR#IY89101	Corrected an issue with performance problems with shipping/tax calculations.
APAR#JR24969	Corrected an issue with the search filter.
APAR#JR25049	Corrected an issue where the shopper cannot login to the store if a CSR is editing their order.
APAR#IY91513	Corrected an issue where fix pack 6001 install fails on a WebSphere Payments instance.
APAR#JR24814	Corrected an issue where the promotions bucket, order checkout fails with a null pointer exception.
APAR#JR24888	createPaymentsVirtualHost.sh error corrected.
APAR#IY90010	Corrected an issue where the user cannot apply the fix pack to a WebSphere Payments instance when global security is enabled.
APAR#IY91476	E-mail Activity Performance improved.
APAR#JR24552	Corrected an issue that occurs if the user has two or more web activities, only one web activity shows up.

APAR#JR24721	Corrected an issue where the DuplicateKeyException passed over in SetOrderPaymentInfoCmdImpl.
APAR#IY88772	Corrected an issue where the create scheduler command will clear trash can order.
APAR#JR25024	Corrected an issue where the discount price of item is not reflected in the database during order flow.
APAR#JR25189	Corrected an issue where the user cannot add an item to the cart if the item is added to more than one product.
APAR#JR25015	Corrected an issue where values are not deleted for automatic deposit payments.
APAR#LI71708	Corrected an issue where the feature is enabled and the required files do not get copied.
APAR#SE27271	Corrected an issue where URLUTF8Encoder.decode throws an exception while handling "%%%%".
APAR#IY91990	Synchronization issue with Order block corrected.
APAR#JR24876	Corrected an issue where a non-plugin folder that is placed under the plugins directory throws an exception.
APAR#JR25009	Corrected an issue where a WebSphere Payments instance is not set as INVALID when the plugin throws an InvalidPay exception.
APAR#JR24462	Corrected an issue where a StackOverflow exception is encountered during WebSphere Payment plug-in initialization.
APAR#JR25504	Corrected an issue where a user is remembered in a not remember case.
APAR#JR24546	Corrected an issue where a JspBatchCompiler error is logged with the SimpleCreditLine.jsp.
APAR#JR25335	Corrected an issue where a ProductSetID SAXException is logged.
APAR#JR25504	Corrected an issue with the AbstractMethodError.
APAR#JR25504	Corrected an issue where you do not need to setOwner on the AccManager..
APAR#JR25504	Added a cloudscape version of updatedbforldap*.sql script.
APAR#JR25504	Integrated changes required for UI Runtime support.
APAR#JR25504	Added ContextService interface and IdentityManager.
APAR#JR25504	Fixed the SOI example to match the most recent version.
APAR#LI71970	Corrected an issue where the ContentURLTag output is incorrect.
APAR#IY94004	WebSphere Commerce Analyzer find result customer segment page now list the search fields.
APAR#JR25504	Added a clean option to Windows start help script.
APAR#JR25504	Store publish and model changes.
APAR#JR25504	Corrected an issue where a NullPointerException is logged after a successful AjaxComponentService call.
APAR#JR25504	Corrected an issue where you cannot deploy an EJB on the Feature Pack 2 enablement script.
APAR#JR25038	Corrected an issue where you cannot handle an e-mail address with "1" or "3".
APAR#JR25517	Updated Migration documentation.
APAR#IY93384	Added "Select Distinct" in DynaCacheInvalidation to improve performance.
APAR#IY93347	Provided the ability to disable the Junk Order feature.

APAR#JR24734	Hardcoded role Ids make OAC uncustomizable.
APAR#JR25504	Added an iFeature version checker.
APAR#JR25504	Corrected an issue where the wmm.jar does not support a clustered environment.
APAR#JR25568	Fixed an error where an exception during a financial transaction does not roll back the transaction.
APAR#IY90328	Corrected an issue where a customer search for a segment needs to check for search criteria.
APAR#JR25504	Corrected an issue where the fixpack 2 database update fails on cloudscape.
APAR#LI71832	Corrected an issue where the store flow reset after a collapsed EAR is expanded.
APAR#LI72077	Corrected an issue where contracts cannot be displayed for Exclude/Include.
APAR#IY89289	Trace improvement in GetContractUnitPrice and RetrievePrice.
APAR#JR24749	A method has been added to make customization possible.
APAR#JR25931	Hide the 'Default' sales tax code and enable the "set as default" button.
APAR#JR25931	Support multiple fulfillment centers for the tax configuration user interface.
APAR#JR25548	Corrected an issue where phantom files were included in looseconfig.xml.
APAR#JR25518	Corrected an issue where the _API_BAD_INV error locks the shopping cart making it inaccessible.
APAR#JR25931	Corrected an issue where the UpdateTax01CmdImpl gives a Finder Exception.
APAR#JR25562	Corrected an issue where a script fails when it is running in a clustered environment.
APAR#IY94012	Corrected an issue where you cannot uninstall the fixpack after you have enabled LDAP.
APAR#JR26106	Corrected an issue where payment rules fail to resolve according to CorePaymentAction.
APAR#IY96015	Error page is display when updating the registry.
APAR#SE27480	Corrected an issue where creating a tickler at the transaction failed.
APAR#IY94647	Corrected an issue where the PluginAdapter does not set the expiry date..
APAR#JR25504	Add a trace component for Paymentech Plugin.
APAR#JR26117	In the memory the merchant configuration information should be plain text.
APAR#JR25504	Introduced a new WebSphere Payments plugin interface.
APAR#IY92177	Corrected an issue where you experience a bad or missing parameter: DynamicKitPricingTCId error.
APAR#LI71771	Corrected an issue where you empty the payments summary once a return is created for the order.
APAR#JR25553	Corrected an issue where large CatalogIDs prevents WebSphere Commerce Accelerator from modifying the price.
APAR#JR26161	Corrected an issue where Stageprop should report an error when 0 rows changed by I/U/D SQL.

APAR#IY92792	Corrected an issue where the KLF is not initiated when third-party code calls PaymentsConfigurator.
APAR#IY94694	Disable Multiclick when an https request is redirected to http.
APAR#IY93066	Unable to edit pending order in the WebSphere Commerce Accelerator
APAR#JR25513	Added a fix that corrects an error in the messaging composer on WebSphere Application Server 6.0.2.13 or later.
APAR#LI71819	Corrected an issue where you cannot add comments to orders in WebSphere Commerce Accelerator.
APAR#IY93739	Currency formats are appending, not refreshing.
APAR#JR26161	Do not fail on propagating a row delete, because the row is already deleted.
APAR#JR25413	Corrected an issue where the reserve payment fails on the second deposit.
APAR#JR25504	Corrected an issue where the enableFeatureForToolkit.xml fails.
APAR#IY93633	The content managed operation needs to be transaction aware.
APAR#JR25362	Corrected an issue where the Gift registry stops working after applying an APAR.
APAR#JR25318	Corrected an issue where you login as a registered customer and best price not updated.
APAR#JR25507	Fixed an issue where there was an incorrectly hardcoded a reason code in the WebSphere Payment AVS code.
APAR#JR24885	Corrected an issue where WebSphere Commerce Version 6.0 payments does not block an order as expected.
APAR#LI71827	Corrected an issue where there is no check operation performed during shopping flow.
APAR#JR25504	Corrected an issue to clear the identity token before the end of the web request.
APAR#LI71687	Updated OrderShippingModeListDataBean Javadoc.
APAR#IY86276	Corrected performance problems for contracts with many adjustments.
APAR#IY88078	Role ID is hardcoded in the StoreLanguageBean.class.
APAR#IY93284	nullPointer exception thrown when calculating ShipMode, with a shipping promotion, for an order with multiple orders.
APAR#IY93285	Error handling enhancement for ErrorDataBean.
APAR#IY93304	Corrected issues with the ApplyCalculationUsageTIKBaseCMDImpl class.
APAR#IY93769	Corrected a NullPointerException in the Unit Manager.
APAR#IY93770	In Accelerator, the order of content spots is matched to the of the INTVSCHED.PRIORITY field.
APAR#IY94001	Modified the GuestUserOrderMigrationEventListener to retain the component information for a dynamic kit during guest to guest event migration.
APAR#IY94413	Optimize performance with 'Request' type marketing experiments when the EXPRESULT table grows to large size.
APAR#IY94767	Optimize performance with 'Request' type marketing experiments when the EXPRESULT table grows to large size.
APAR#IY94869	Corrected an Accelerator dialog box message, in Simplified Chinese, after a successful image upload.
APAR#IY94895	Change to the FileProp parameter; -userid is changed to -user.

APAR#IY94955	Corrected an issue when removing customer segment from a promotion leaves CALCODEMGP intact.
APAR#IY95221	Reduced deadlocks during the execution of the ReleaseExpiredAllocation command.
APAR#IY95279	Added the call to super.reset() from AbstractECTargetableCommand.reset().
APAR#IY95698	Prevented failed orders from being processed during a deadlock.
APAR#IY95711	Corrected an issue when the inventory of a store item is being checked regardless of the TRACKINVENTORY flag being set to Yes or No.
APAR#IY95720	Corrected an issue when an authentication cookie is not created for commands that require https but use http
APAR#IY95821	Corrected multiple issues including DuplicateKeyException in BusinessServiceContext, BusinessContextNotFoundException after ActivityCleanup job is executed, BusinessContext unable to handle multiple threads with the same activity_id, and invalid cookie error after user registration.
APAR#IY96034	Corrected an issue when shipping charges are erroneously distributed between order items in an order.
APAR#IY96151	Corrected the UrlMapperImpl which violated the servlet specification by returning incorrect values for the URI.
APAR#IY97562	Staging propagation fixes.
APAR#IY97875	Modified the signature, of InterestItemCmdImpl.checkBuyable, from private to protected.
APAR#IY98054	Corrected when WebSphere Commerce scheduled jobs fail due to expired credentials.
APAR#IY98301	Changed two methods from the ReleaseExpiredAllocations command from private to public.
APAR#IY98315	Under catalog imported, retained the rename and delete images function.
APAR#IY98337	Corrected remote instance creation problem on iSeries.
APAR#IY98684	Includes fixes JR25946, JR26112, JR26463, JR26684, IY95567, and JR25950
APAR#IY98695	Corrected the signature of ProductSetPublishCmdImpl.getExpandedCatalogEntries() from private to protected.
APAR#IY99039	Added an extension point to the order command when retrieving trading id.
APAR#IY99570	Corrected the inability to create more than eleven workspaces due to a problem with the keys table not returning the right keys id.
APAR#IY99363	Corrected an issue where Index.jsp is empty after *Apply permanently* for change flow.
APAR#IZ01938	Corrected the NullPointerException on Staging copy and updated the staging copy utility to the latest version.
APAR#JR24753	Improved the performance of the StoreSearchBean SQL.
APAR#JR24991	Corrected the GetContractUnitPriceCmdImpl.reset method that needs to reset iGlobalOfferIds.
APAR#JR25583	Added function to the search bean to allow for customization.
APAR#JR25752	Corrected an issue when the campaign engine does not associate item beans to product beans.

APAR#JR25832	Corrected an issue when WebSphere Application Server Global Security, with a custom registry, is enabled and Server security is disabled.
APAR#JR25838	Corrected an issue when an espot overwrites other espots, after migration.
APAR#JR25878	Corrected a typo of "adress" in the BreadCrumbTrailDisplay.jsp.
APAR#JR25891	Corrected an issue with FFMCenterDialog.jsp and VendorNameAddress.jsp where the listing of countries is indexed incorrectly which can cause a java.lang.ArrayIndexOutOfBoundsException.
APAR#JR25918	Corrected an issue with SupplierCookieTable problem in a cloned WebSphere Application Server environment.
APAR#JR25944	Corrected an issue with the promotions UI so that categories, containing ampersands, can be entered.
APAR#JR25946	Corrected migration issues related to migrated ad copies.
APAR#JR25950	Corrected an issue with a NullPointerException that occurs on the scheduled job ScheduledContentManagedFileEARUpdateCmd when there is a record in the cmfile table with promote_fs=0 and storage_type=-1.
APAR#JR25955	Corrected an issue to display the correct store in a content spot's content.
APAR#JR26036	Corrected an issue when no error is posted when a new promotion, with a duplicate name, is created.
APAR#JR26047	Corrected an issue to retain CATALOG_ID parameters when SALESCATALOG is used.
APAR#JR26082	Corrected an issue when activating or deactivating promotions in Accelerator.
APAR#JR26112	Ensured that the struts-cfg.xml file, in the Initialization servlet, does not include entries which are customizable.
APAR#JR26172	Corrected an issue with the policy check for quick checkout orders.
APAR#JR26202	Provided an alternative to synchronize the product set information with a contract.
APAR#JR26212	Corrected an issue in Accelerator where Find Orders, by logonid, posts an SQL error if using Oracle.
APAR#JR26359	Improved the performance of the RegistryManager.refresh() on the PolGrpSubscriptionsRegistry during hosted store creation with a large number of organizations.
APAR#JR26432	Corrected an issue with a class casting problem with the InvoiceDataBean for all possible XML elements.
APAR#JR26436	Corrected an issue with NullPointerException from ErrorDataBean, due to a missing ECMMessage object.
APAR#JR26437	Corrected an issue where an invalid card number error was displayed even though a credit card was not used.
APAR#JR26463	Corrected an issue with code that assumes the loginID=nickname.
APAR#JR26501	Corrected an issue when looking for a response view to be returned to the service requestor, while WebSphere Commerce is set up to be the service provider and the WCS.SOAPINTEGRATION message mapper is enabled.
APAR#JR26553	Corrected an issue with the business-to-business store where a "Wish List" link is replaced with a "Requisition List" link.

APAR#JR26597	Corrected an issue in Accelerator to make the ordering of Content spots match that of the INVSCHED.PRIORITY field.
APAR#JR26607	Modified extension points in classes OrderCopyCmdImpl and OrderItemDisplayCmdImpl.
APAR#JR26623	Corrected a consistency issue with the Change Pages functionality.
APAR#JR26636	Corrected an issue for when the OrderShippingModeListDataBean is called multiple times, the adjustments, are cumulative.
APAR#JR26672	Ensured that the content, with a 'no click action', does not create links in the JSP.
APAR#JR26673	Corrected an issue where JSPHelper is unable to retrieve catalogId.
APAR#JR26684	Ensured that a free shipping promotion is applied on the whole order even what a free gift is also included.
APAR#JR26734	Corrected an error when modifying the tax on a product or item.
APAR#JR27148	Improved how a web path is built. The cached fragment pages will now be built with the correct URL.
APAR#JR27155	Corrected an issue where Feature Pack APARs can not be applied to features that have been enabled.
APAR#LI72065	The password reset page is cached under different URLs when a user navigates away from the password reset page instead of completing the password reset form.
APAR#LI72081	Prevented a stack overflow after deploying a contract and trying to retrieve the catalog information.
APAR#LI72092	Corrected an issue in Accelerator when an OutOfBoundIndexException is encountered when checking the summary of a Content Spot referenced by a URL.
APAR#LI72094	Enabled to show an image on a Content Spot when MIMETYPE on ATCHAST indicates the content is an image.
APAR#LI72102	Prevented an ORA-1000 error when massloading a large amount of data into an Oracle database.
APAR#LI72114	Corrected an issue where the advanced find order has a BOD exception when filling in the shipping information.
APAR#LI72130	Corrected an issue in Accelerator where you are unable to delete a jurisdiction.
APAR#LI72366	Corrected an issue when a Task Group in the WorkspaceAdmintool is selected and a ClassCastException occurs.
APAR#LI72400	Added method "String getCatalogEntryId" to the ItemCreateImpl class.
APAR#LI72401	Corrected issues with DuplicateKeyException in BusinessServiceContext, BusinessContextNotFoundException after ActivityCleanup job is started, and invalid cookie error after a user registration.
APAR#LI72419	Corrected issues with DuplicateKeyException in BusinessServiceContext, BusinessContextNotFoundException after ActivityCleanup job is started, invalid cookie error after a user registration, and BusinessContext unable to handle multiple threads with the same activity_id.
APAR#LI72467	Enabled filtering of shipping modes per item rather than on a per order basis.
APAR#SE29051	Corrected an issue where no eligible trading agreements could be found for the user.
APAR#SI25946	Corrected an issue where the WebSphere Commerce payments application can not find library QPYMWEB.

APAR#SI27143	Provided an updated version of the stagingprop utility.
--------------	---

Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

Any reference to an IBM licensed program in this publication is not intended to state or imply that only IBM's licensed program may be used. Any functionally equivalent product, program, or service that does not infringe any of IBM's intellectual property rights may be used instead of the IBM product, program, or service. Evaluation and verification of operation in conjunction with other products, except those expressly designated by IBM, is the user's responsibility.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

IBM World Trade Asia Corporation
Licensing
2-31 Roppongi 3-chome, Minato-ku
Tokyo 106, Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be

incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licenses of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Canada Ltd.
Office of the Lab Director
8200 Warden Avenue
Markham, Ontario
L6G 1C7
Canada

Such information may be available, subject to appropriate terms and conditions, including in some cases payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurement may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

Trademarks

IBM, the IBM logo and the following terms are trademarks or registered trademarks of International Business Machines Corporation in the United States or other countries or both:

- AIX

- iSeries
- pSeries
- xSeries
- zSeries
- WebSphere

Windows is a trademark of Microsoft Corporation in the United States, other countries, or both.

Linux is a trademark of Linus Torvalds in the United States, other countries, or both.

Other company, product or service names may be the trademarks or service marks of others.



Printed in USA