

IBM WebSphere Business Integration Collaborations for  
Product Information Management, Version 1.1.0  
IBM WebSphere Business Integration Collaborations for  
Retail Message Manager, Version 4.4.0



# Solution Development Guide

**Eighth Edition (July 2004)**

This edition applies to Version 4, Release 4, IBM WebSphere Business Integration Collaborations for Retail Message Manager, Version 4.4.0 (5724-H63) and IBM WebSphere Business Integration Collaboration for Product Information Management 1.1.0 (5724-H64)

This document contains proprietary information of IBM. It is provided under a license agreement and is protected by copyright law. The information contained in this publication does not include any product warranties, and any statements provided in this manual should not be interpreted as such.

Order publications through your IBM representative or the IBM branch office serving your locality or by calling 1-800-879-2755 in the United States or 1-800-IBM-4YOU in Canada.

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

---

# Contents

<b>About this book</b> . . . . .	<b>v</b>
Who should read the Solution Development Guide . . . . .	v
Definitions and terminology . . . . .	v
How the Solution development guide is organized . . . . .	vii

<b>Chapter 1. Processing a business object: an example NEW_ITEM workflow</b> . . . . .	<b>1</b>
Detailed workflow: receiving, filtering, and validating a business object . . . . .	1
Detailed workflow: processing a business object with cascaded GLNs . . . . .	5
Detailed workflow: completing the WebSphere MQ Workflow process and merging updated information into a complete business object . . . . .	6
Detailed workflow: synchronizing a business object to a back-end system . . . . .	8

<b>Chapter 2. Filtering publication requests before business processing</b> . . . . .	<b>13</b>
Filtering based on the presence of attributes required by UCCnet . . . . .	13
Filtering based on items belonging to approved supply-side trading partners. . . . .	16
Filtering based on items belonging to accepted categories . . . . .	16
Complex field filtering based on multiple attributes . . . . .	17
Filtering to eliminate processing of duplicate items . . . . .	18
Persisting or deleting an item to or from a local identifier store . . . . .	19

<b>Chapter 3. Validating an item before business processing.</b> . . . . .	<b>21</b>
Validating an item against customized business policy rules . . . . .	21
Validating an item by requiring data for specific attributes . . . . .	22
Performing simple filtering . . . . .	23
Performing complex filtering . . . . .	24
Specifying attribute names . . . . .	26
Using the RetailUtility external Java class . . . . .	26
Using the Custom Missing Attribute Logic . . . . .	28
Using a custom missing data retrieval process to collect data . . . . .	28

<b>Chapter 4. Adding customized code to the ItemValidation collaboration template</b> . . . . .	<b>31</b>
---	-----------

<b>Chapter 5. Processing business objects with cascaded GLNs</b> . . . . .	<b>33</b>
Using the GLN Cascade Grouping File . . . . .	33

<b>Chapter 6. Using a business process to review and approve an item</b> . . . . .	<b>37</b>
Printing an item before it is sent through the business review/approval process . . . . .	37
Mapping an item to the business review/approval process . . . . .	37
Using WebSphere MQ Workflow containers . . . . .	38
Returning data from the business review/approval process to an ItemCollector collaboration object . . . . .	40

<b>Chapter 7. Merging data into a complete item.</b> . . . . .	<b>41</b>
Merging static data by using the X_COPY ATTRIBUTE configuration properties. . . . .	43
Merging missing data by using the MISSING_DATA_CHILD_ATTRIBUTE configuration property . . . . .	44

<b>Chapter 8. Processing an item after the business review/approval process completes</b> . . . . .	<b>45</b>
Synchronizing an item to a back-end application other than a file system . . . . .	46
Synchronizing an item to multiple back-end applications . . . . .	46

<b>Chapter 9. Sending responses to UCCnet</b> . . . . .	<b>47</b>
---	-----------

<b>Chapter 10. Using identifier, message, and item stores</b> . . . . .	<b>51</b>
Persisting or deleting an item to or from a local identifier store . . . . .	51
Persisting, retrieving, or deleting an item to or from a local message store . . . . .	52
Persisting, retrieving, updating, or deleting an item to or from a local item store . . . . .	53
Generating data base keys . . . . .	54

<b>Chapter 11. Controlling e-mail.</b> . . . . .	<b>55</b>
Alerting email recipients of item status or processing errors . . . . .	55
Alerting of Approved item status . . . . .	56
Alerting of Accepted item status . . . . .	57
Alerting of Rejected item status. . . . .	58
Alerting of processing errors. . . . .	60
Specifying message text, subjects, and recipients in external files . . . . .	62
Specifying changing individual or multiple message recipients . . . . .	63
Using substitution variables in message and subject text . . . . .	63

<b>Chapter 12. Logging</b> . . . . .	<b>65</b>
Logging that mail is sent . . . . .	65
Logging errors . . . . .	65
Logging item status . . . . .	65
<b>Chapter 13. Tracing</b> . . . . .	<b>67</b>
<b>Chapter 14. Handling solution processing errors</b> . . . . .	<b>69</b>
Diagnosing error conditions . . . . .	69
Recovering from error conditions . . . . .	71

<b>Chapter 15. Handling data from other data sources</b> . . . . .	<b>73</b>
Extending the solution to handle a single data source other than UCCnet . . . . .	73
Extending the solution to handle multiple data sources . . . . .	73
<b>Notices</b> . . . . .	<b>75</b>
Copyright license . . . . .	77
Programming interface information . . . . .	77
Trademarks . . . . .	77

---

## About this book

This book is the Solution Development Guide for the Product Information Management for Retailers solution.

---

## Who should read the Solution Development Guide

The Solution Development Guide is for programmers who design and implement workflows using the Product Information Management for Retailers solution and who might participate in designing customizations to this solution.

The guide assumes that users are experienced programmers and that they understand the following concepts and have experience with the software associated with them:

- Developing collaboration objects, business objects, maps, and other related components
- Installing, configuring, and operating the Product Information Management for Retailers solution
- Modeling workflows using IBM® WebSphere® MQ Workflow

Programmers must also have experience with the respective operating system on which their implementation is installed.

---

## Definitions and terminology

Definitions of terminology used in the guide.

### Definitions of connector and adapter

The term *connector* used throughout refers to the runtime portion of an IBM WebSphere Business Integration Adapter. References to specific connectors are related to specific adapters, as follows:

Term	Usage
iSoftConnector	The runtime portion of an IBM WebSphere Business Integration Adapter for iSoft.
TPICConnector	The runtime portion of an IBM WebSphere Business Integration Adapter for Trading Partner Interchange.
JMSConnector	The runtime portion of an IBM WebSphere Business Integration Adapter for Java™ [tm ] Message Service (JMS).
JTextConnector	The runtime portion of an IBM WebSphere Business Integration Adapter for JText.
JTextISoftConnector	The runtime portion of an adapter based on the IBM WebSphere Business Integration Adapter for JText.
JTextTPICConnector	The runtime portion of an adapter based on the IBM WebSphere Business Integration Adapter for JText.

Term	Usage
JTextJMSConnector	The runtime portion of an adapter based on the IBM WebSphere Business Integration Adapter for JText.
WebSphereMQWorkflowConnector	The runtime portion of an IBM WebSphere Business Integration Adapter for WebSphere MQ Workflow.

The way you connect to UCCnet determines the connector that you use to communicate with it.

If you exchange messages with UCCnet using an AS2/EDIINT interface protocol, you can use a TPIConnector, an ISoftConnector, or you can use WebSphere Business Integration Connect in conjunction with a JMSConnector.

Use the TPI connector if you communicate with UCCnet through Trading Partner Interchange servers.

Use the ISoftConnector if you communicate with UCCnet through an iSoft Peer-to-Peer Agent.

Use the JMS connector if you communicate with UCCnet through WebSphere Business Integration Connect.

If you exchange messages through the UCCnet Command Line Utility (CLU) or are testing your installation, you can use either a JTextTPIConnector, a JTextISoftConnector, or a JTextJMSConnector.

Because the actual connector you use is dependent on your set up, this documentation uses “AS2 channel connector” as a general term for any of the TPIConnector, ISoftConnector, JMSConnector, JTextTPIConnector, JTextISoftConnector, and JTextJMSConnector.

### Schema and DTD terminology

The information in the following sections outlines how the Product Information Management for Retailers solution handles publication information notifications (in systems supporting the UCCnet DTD) or Catalogue Item Notifications (in systems supporting the UCCnet XSD). Because the collaboration templates within the Product Information Management for Retailers solution are schema-based, in DTD-based systems, the solution maps incoming DTD-based publication information notifications into XSD-based Catalogue Item Notifications during processing, and converts outgoing XSD-based Catalogue Item Confirmation commands into DTD-based Authorization commands at the end of solution processing. For simplicity, the solution will be discussed throughout using schema terminology only.

### Definitions of NULL and BLANK

The terms NULL and BLANK are defined as true responses when the attributes are tested using the business object methods isNull() and isBlank(), respectively. The method isNull() returns true when a value has never been set in an attribute. The

method `isBlank()` returns true when the attribute contains a zero-length string. An attribute containing a space character is not considered BLANK by the `isBlank()` method.

---

## How the Solution development guide is organized

The Solution development guide introduces the mechanics of the solution by first presenting a sample, high-level, step-by-step workflow. This section is useful for obtaining an overall, conceptual understanding of solution processing.

### **XSD and DTD workflow**

The guide illustrates how the solution handles the following:

- A Catalogue Item Notification `NEW_ITEM` in systems supporting the UCCnet XML Schema Definition. (XSD)
- A `PUB_RELEASE_NEW_ITEM` in systems supporting the UCCnet Document Type Definition (DTD).



---

## Chapter 1. Processing a business object: an example NEW\_ITEM workflow

The information in the following sections outlines the Product Information Management for Retailers solution workflow in detail. It describes at a high level how the solution handles a PUB\_RELEASE\_NEW\_ITEM flow (in systems supporting the UCCnet DTD) or a Catalogue Item Notification NEW\_ITEM flow (in systems supporting the UCCnet XSD).

### Overview

The example workflow follows an item from the point when it is retrieved from UCCnet, as it is taken through filtering, validation, and WebSphere MQ Workflow business review/approval processing, and is then synchronized to a back-end system. In the context of the Product Information Management for Retailers solution, this back-end system is a file system. Any response to the item is returned to UCCnet. The workflow is presented in four segments:

- The flow from when an item is received from UCCnet until it is sent to an ItemDispatcher collaboration object for optional handling of cascaded GLNs. See “Detailed workflow: receiving, filtering, and validating a business object.”
- The flow from when an item is received by an ItemDispatcher collaboration object until it is sent to WebSphere MQ Workflow for business review/approval processing. See “Detailed workflow: processing a business object with cascaded GLNs” on page 5.
- The flow from when an item enters the WebSphere MQ Workflow business review/approval process until the updated information within it is merged into a complete item by an ItemCollector collaboration object. See “Detailed workflow: completing the WebSphere MQ Workflow process and merging updated information into a complete business object” on page 6.
- The flow from when an item exits an ItemCollector collaboration object until it is synchronized to a back-end system. See “Detailed workflow: synchronizing a business object to a back-end system” on page 8.

If an error occurs, its cause and its location in its overall process flow must be determined. Processing must then be restarted. See Chapter 14, “Handling solution processing errors,” on page 69.

Tracing can also be enabled for all collaboration objects to record logical flaws and data processed. See Chapter 13, “Tracing,” on page 67.

---

### Detailed workflow: receiving, filtering, and validating a business object

The following outlines the solution workflow as an item is received from UCCnet, passes through preprocessing filtering and validating processes, and is sent to an ItemDispatcher collaboration object for optional processing of cascaded GLNs.

#### Workflow

1. A worklist is requested from UCCnet. The AS2 channel connector receives the worklist from the AS2 channel server (iSoft Peer-to-Peer Agent, TPI server or WebSphere Business Integration Connect). This worklist can contain one type of notification from the following list:

- One or more publication information notifications if you are supporting UCCnet DTDs
  - One or more Catalogue Item Notifications if you are supporting UCCnet XSDs
  - One or more price/pricebracket notifications if you are supporting UCCnet XSDs
- .
2. The AS2 channel connector sends the worklist to the IBM WebSphere Business Integration Data Handler for XML, which converts it into an application specific business object of the form UCCnetxxx\_envelope (if iSoft connectivity is used), UCCnetTPIxxx\_envelope (if TPI connectivity is used), or UCCnetJMSxxx\_envelope (if WebSphere Business Connect is used with JMS). This business object contains the entire UCCnet message, including each individual data instance and the commands related to it.

**Note:** In this and the following steps, the variable *xxx* specifies the XML definition type used (DTD or XSD).

3. The business object is converted to a UCCnetGBO\_envelope business object by passing through an input map of the form UCCnetxxx\_envelope\_to\_UCCnetGBO\_envelope (if iSoft connectivity is used), UCCnetTPIxxx\_envelope\_to\_UCCnetGBO\_envelope (if TPI connectivity is used) or UCCnetJMSxxx\_envelope\_to\_UCCnetGBO\_envelope (if WebSphere Business Connect is used with JMS). The DTD forms of these maps convert incoming ASBOs containing DTD-based publication information notifications into UCCnetGBO\_envelope GBOs containing XSD-based Catalogue Item Notifications for ongoing processing by the solution. The AS2 channel connector checks for subscriptions to the UCCnetGBO\_envelope business object by collaboration objects. Collaboration objects based on the UCCnetMessageReceive collaboration template subscribe to it. Therefore, a UCCnetMessageReceive collaboration object is passed the business object through its *FromAS2* port.
4. The UCCnetMessageReceive collaboration object parses the message, separating each instance of a Catalogue Item Notification or price/pricebracket notification. Because this is an example of a Catalogue Item Notification with a NEW\_ITEM command, the UCCnetMessageReceive collaboration object accommodates persisting the UCCnetGBO\_envelope business object to a local identifier store by first converting it to a UCCnetGBO\_identifier business object and then passing it with a Create verb to an IdentifierStore collaboration object through its *ToIdentifier\_Store* port.
5. The IdentifierStore collaboration object receives the business object on its *From* port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, stores the identifier in the identifier store. If the item is already found in the identifier store, it is rejected. “Persisting or deleting an item to or from a local identifier store” on page 19 describes how a business object is persisted to the identifier store. “Filtering to eliminate processing of duplicate items” on page 18 describes how a UCCnetMessageReceive collaboration object prevents duplicate items from being processed.
6. The UCCnetMessageReceive collaboration object accommodates persisting the UCCnetGBO\_envelope business object to a local message store by first converting it to a UCCnetGBO\_storable business object and then passing it with a Create verb to a MessageStore collaboration object through its *ToMessage\_Store* port.

7. The MessageStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, stores the message in the message store. The section “Persisting, retrieving, or deleting an item to or from a local message store” on page 52 describes in detail how a message is persisted to the message store.
8. The UCCnetMessageReceive collaboration object can filter the business object to ensure that it contains attributes required by UCCnet, that it came from an approved set of supply-side trading partners, that it belongs to an approved set of item categories, and that it passes a set of complex filters that are based on the interaction of multiple attributes. Information in Chapter 2, “Filtering publication requests before business processing,” on page 13 details how the collaboration object performs these functions. Based on whether the business object passes or fails this analysis, the collaboration object directs processing, as follows:
  - a. If the business object fails analysis, the collaboration object converts the UCCnetGBO\_envelope business object into a Retail\_Item business object containing the individual Catalogue Item Notification and its data. It attaches a status to the business object preconfigured in its FILTER\_FAIL\_RESPONSE property and sends it to its ToRetail\_Response port to be passed to a UCCnetMessageSend collaboration object for transmittal to UCCnet.
  - b. If the business object passes analysis, the collaboration object converts the UCCnetGBO\_envelope business object into a Retail\_Item business object containing the individual Catalogue Item Notification and its data. It attaches a status of Review to the business object and sets the command type according to the original message type received from UCCnet. It then sends this business object to its ToRetail\_Processing port to be passed to an ItemValidation collaboration object.

For the purposes of this example, assume this business object passed analysis.

9. The ItemValidation collaboration object accepts the Retail\_Item business object on its From port and executes any code added to the template to evaluate it according to customized business policy rules. The section “Validating an item against customized business policy rules” on page 21 details how the collaboration object performs this function. The business policy logic code must change the business object status to a value of either Review or Rejected, which directs further processing by the collaboration object, as follows:
  - a. If the Retail\_Item business object status is not set to Rejected by the business policy logic, the ItemValidation collaboration object continues to process it.
  - b. If the Retail\_Item business object status is set to Rejected by the business policy logic, the collaboration object aborts any further processing and returns the business object to the caller through its From port.

For the purposes of this example, assume that the Retail\_Item business object’s status was not set to Rejected by the business policy logic.

10. The ItemValidation collaboration object checks that those particular attributes of the business object that the user has specified must contain data are not NULL or BLANK. See “Definitions and terminology” on page v. Simple or complex filtering can be used to conditionally specify which attributes must contain data. The section “Validating an item by requiring data for specific attributes” on page 22 describes how the collaboration object performs this function. Based on the results of this check, the collaboration object handles the Retail\_Item business object, as follows:

- a. If all required attribute data is present, the ItemValidation collaboration object continues to process it.
  - b. If the business object is missing data for any specified Retail\_Item attribute, the collaboration object adds the attribute name to another Retail\_Item business object list attribute, which is specified in the collaboration object's CUST\_DATA\_MISS\_ATTR configuration property (by default, internals.customer\_data\_missing\_attributes) and continues to process it.
11. The ItemValidation collaboration object executes any customized code the user has added to the template for the command associated with the business object. The section Chapter 4, "Adding customized code to the ItemValidation collaboration template," on page 31 details how the collaboration object performs this function.
  12. If configured to do so, the ItemValidation collaboration object enables persistence of the business object to a local item store by sending it with a Create verb to its LocalItemStore port to be passed to an ItemStore collaboration object.
  13. The ItemStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, stores it in the item store database. The section "Persisting, retrieving, updating, or deleting an item to or from a local item store" on page 53 describes how a business object is persisted to the item store.
  14. The ItemValidation collaboration object sets the business object's status to Review. It processes the business object according to whether it is missing data for any specified Retail\_Item attribute, as follows:
    - a. If the object is missing required attribute data, the collaboration object passes it to its ToMissingData port to trigger a process for obtaining the missing data. The ToMissingData port can be connected to another collaboration object or to an asynchronous process for collecting the missing attribute values. This custom missing data retrieval process is described in the section "Using a custom missing data retrieval process to collect data" on page 28.
    - b. If all required attribute data is present, the collaboration object passes it to its To port to trigger an ItemDispatcher collaboration object.

For the purposes of this example, to be continued in the section "Detailed workflow: processing a business object with cascaded GLNs" on page 5, assume that all required data is present in the business object.

An ItemValidation collaboration object can be configured to initiate notification if errors are detected during processing. It connects through its Notify port to a Role\_Email collaboration object, which actually controls the email. See Chapter 11, "Controlling e-mail," on page 55.

An ItemValidation collaboration object can also log the business object being processed when an error occurs (in addition to the error) and when item status values are Review and Rejected. A Role\_Email collaboration object can log when errors occur and each time an email message is sent. See Chapter 12, "Logging," on page 65.

---

## Detailed workflow: processing a business object with cascaded GLNs

The following outlines the solution workflow as an item is accepted and processed by an ItemDispatcher collaboration object. Based on whether the item has any cascaded GLNs within it, one or more items are then sent to a WebSphere MQ Workflow process for review/approval.

### Workflow

1. An ItemDispatcher collaboration object is triggered by the receipt of a Retail\_Item business object on its From port.
2. The ItemDispatcher collaboration object examines the item to see if it contains cascaded GLNs and then directs processing, as follows:
  - If no cascaded GLNs exist, the collaboration object sends the item through its To port to the WebSphere MQ Workflow process, and processing by the ItemDispatcher collaboration object ends.
  - If cascaded GLNs do exist, the collaboration object continues processing the item.

For the purposes of this example, assume that cascaded GLNs do exist.

3. The ItemDispatcher collaboration object checks if a filename exists in its GLN\_CASCADE\_GROUPING\_FILE property and directs processing, as follows:
  - If this property is empty, the collaboration object uses the value of the GLN\_CASCADE\_GROUPING\_DEFAULT configuration property to guide on-going processing.
  - If a filename exists in this property, the collaboration object verifies that the file exists and parses correctly. Based on the results of this check, it guides processing, as follows:
    - If the file exists and parses correctly, the collaboration object continues processing the item.
    - If the file does not exist or does not parse correctly, the collaboration object raises an exception, sends the item to its Notify port with appropriate error attributes filled in, and processing ends.

For the purposes of this example, assume that a filename and file exist and that the file parses correctly.

4. The ItemDispatcher collaboration object checks if the RetailUtility class file specified in its UTILITY\_CLASS property exists. It then directs processing, as follows:
  - If a file exists, the collaboration object continues processing the item.
  - If a file does not exist, the collaboration object raises an exception, sends the item to its Notify port with appropriate error attributes filled in, and processing ends.

For the purposes of this example, assume that a RetailUtility class file exists.

5. The ItemDispatcher collaboration object uses the information in the file specified in its GLN\_CASCADE\_GROUPING\_FILE property to determine how to group the cascaded GLNs. See “Using the GLN Cascade Grouping File” on page 33.
6. For each cascaded GLN identified in Step 5, which will be sent to the WebSphere MQ Workflow process, the ItemDispatcher collaboration object creates one copy of the Retail\_Item business object. It removes the extra cascaded GLNs from each copy and sends each to its LocalItemStore port with a Create verb to an ItemStore collaboration object. The key used for each new

item is the concatenation of the `internals.correlationID` attribute value of the original triggering business object and the `internals.cascadedGlns.gln` attribute value of the newly created business object.

7. The ItemStore collaboration object receives each new business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, stores each in the item store database. The section describes in detail how a business object is persisted to the item store.
8. The collaboration object creates a new copy of the triggering Retail\_Item business object for each group, removing extra cascaded GLNs that do not belong in the group from each Retail\_Item.
9. The new Retail\_Item business objects are sent through the To port to the WebSphere MQ Workflow process for approval.
10. The original Retail\_Item business object is updated with the number of cascaded items sent to the WebSphere MQ Workflow process and is then sent to the LocalItemStore port with an Update verb to an ItemStore collaboration object.
11. The ItemStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, updates the item store database. See “Persisting, retrieving, updating, or deleting an item to or from a local item store” on page 53.

This workflow is continued in “Detailed workflow: completing the WebSphere MQ Workflow process and merging updated information into a complete business object.”

An ItemDispatcher collaboration object can be configured to initiate notification if errors are detected during processing. It connects through its Notify port to a Role\_Email collaboration object, which actually controls the e-mail. See Chapter 11, “Controlling e-mail,” on page 55.

An ItemDispatcher collaboration object can also log when errors occur. See Chapter 12, “Logging,” on page 65.

---

## Detailed workflow: completing the WebSphere MQ Workflow process and merging updated information into a complete business object

The following outlines the solution workflow as a business object passes through the WebSphere MQ Workflow business review/approval process and is delivered to an ItemCollector collaboration object, where the new information is merged into a complete business object.

Also, refer to the Installation guide for detailed information on creating port connections between collaboration objects and between collaboration objects and connectors.

### Workflow

1. The WebSphere MQ Workflow business review/approval process begins when an ItemDispatcher collaboration object passes a Retail\_Item to the WebSphereMQWorkflowConnector over its To port through the Retail\_Item\_to\_MQWF\_Retail\_Item map. At this point, the flow becomes asynchronous. A Retail\_Item can contain multiple GLNs.

2. The WebSphereMQWorkflowConnector builds a WebSphere MQ Workflow container and invokes a specific WebSphere MQ Workflow process. “Mapping an item to the business review/approval process” on page 37 and “Using WebSphere MQ Workflow containers” on page 38 describe how business objects are mapped into WebSphere MQ Workflow and how process definitions and containers are used in the context of the Product Information Management for Retailers solution.
3. The approver(s) responsible for approving the item set the item status to Approved, Rejected, Accepted, or Review through a customized user interface with WebSphere MQ Workflow. If an item contains multiple GLNs, the approver must set the status for each GLN in the item.
4. The WebSphere MQ Workflow process sends the container with the updated status to the WebSphereMQWorkflowConnector. At this point, the WebSphere MQ Workflow business review/approval process is complete and the flow becomes synchronous again.
5. The WebSphereMQWorkflowConnector maps the container back into a partial Retail\_Item business object by passing it through the MQWF\_Retail\_Item\_to\_Retail\_Item map and invokes an ItemCollector collaboration object. The section “Returning data from the business review/approval process to an ItemCollector collaboration object” on page 40 describes how updated information in this partial object is returned to the ItemCollector collaboration object.
6. The ItemCollector collaboration object accepts the partial Retail\_Item business object on its From port and retrieves the complete copy of the Retail\_Item that was stored by the ItemValidation collaboration object in the item store database before the review/approval process was started. It retrieves the item by sending the business object and a Retrieve verb to its local\_store port to be passed to an ItemStore collaboration object. The ItemCollector collaboration object saves the Retail\_Item internals.correlationID value, from the complete copy retrieved from the item store, for use in later processing.
7. The ItemStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, retrieves the item from the item store database and returns it to the ItemCollector collaboration object. The section “Persisting, retrieving, updating, or deleting an item to or from a local item store” on page 53 describes in detail how a business object is retrieved from the item store.
8. The collaboration object checks if the original Retail\_Item retrieved from the item store database contained cascaded GLNs. Assume for the purposes of this example flow that cascaded GLNs are present. See Merging data into a complete item.
9. The ItemCollector collaboration object loops through the GLNs, processing each one, as follows:
  - a. It retrieves the copy of the Retail\_Item that was stored by the ItemDispatcher collaboration object from the item store database by sending the business object and a Retrieve verb to its local\_store port to be passed to an ItemStore collaboration object. The key used to access the item is the concatenation of the internals.correlationID attribute value of the original triggering business object and the internals.cascadedGLns.gln attribute value for the GLN being processed.
  - b. The ItemStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, retrieves the item from the item store database and returns it to the ItemCollector collaboration object.

- c. The ItemCollector collaboration object merges the new data received from the WebSphere MQ Workflow process into the Retail\_Item business object retrieved from the item store. The section Merging data into a complete item describes in detail how the ItemCollector collaboration object merges the data into a complete item.
  - d. The ItemCollector collaboration object then handles the business object according to its status value. Assume for the purposes of this example flow that the status value of the internals.cascadedGLNs.item\_status attribute is Approved. In this case, the ItemCollector collaboration object routes the merged Retail\_Item business object to a Process\_Reviewed\_Item collaboration object via its To port.
10. The ItemCollector collaboration object calculates how many total cascaded GLNs have completed processing (i.e., they have Approved, Rejected, or Error status). If all of the cascaded GLNs from the original message that was sent to the ItemDispatcher collaboration object have completed processing, it does the following:
- a. Sets the Retail\_Item internals.lastCascadedGLN attribute to true indicating to the UCCnetMessageSend collaboration object that this is the last of the group of cascaded GLNs contained in the original Retail\_Item.
  - b. Deletes the copy of the Retail\_Item that was stored by the ItemValidation collaboration object from the item store database by sending the business object and a Delete verb to its local\_store port to be passed to an ItemStore collaboration object. The key used to access the item is the internals.correlationID attribute value of the original triggering business object.
  - c. The ItemStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, deletes the item from the item store database.

This workflow is continued in “Detailed workflow: synchronizing a business object to a back-end system.”

An ItemCollector collaboration object can be configured to initiate notification if errors are detected during processing. It connects through its email port to a Role\_Email collaboration object, which actually controls the e-mail. See Chapter 11, “Controlling e-mail,” on page 55.

An ItemCollector collaboration object can also log the business object being processed when an error occurs (in addition to the error). A Role\_Email collaboration object can log when errors occur and each time an e-mail message is sent. See Chapter 12, “Logging,” on page 65.

---

## Detailed workflow: synchronizing a business object to a back-end system

The following outlines the solution workflow as a business object passes from an ItemCollector collaboration object to a Process\_Reviewed\_Item collaboration object, which synchronizes the business object to the back-end system and initiates sending a response to UCCnet through a UCCnetMessageSend collaboration object.

### Workflow

1. An ItemCollector collaboration object sets the Retail\_Item internals.originalCorrelationID attribute to the value obtained from the

original Retail\_Item internals.correlationID attribute (the one saved by the ItemValidation collaboration object) and then passes the Retail\_Item business object to a Process\_Reviewed\_Item collaboration object, which receives it on its From port. The internals.originalCorrelationID is used by the UCCnetMessageSend collaboration object to access the original message in the message store.

2. If configured to do so, the Process\_Reviewed\_Item collaboration object enables deletion of the item from the item store by passing the business object with a Delete verb to its local\_store port to be passed to an ItemStore collaboration object.
3. The ItemStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, deletes the item from the item store. The section “Persisting, retrieving, updating, or deleting an item to or from a local item store” on page 53 describes in detail how a business object is deleted from the item store.
4. The Process\_Reviewed\_Item collaboration object directs processing according to the status of the business object. For the purposes of this example, assume that the status of the business object is Approved. See Processing an item after the business review/approval process completes. Because, in this example, the Retail\_Item business object status is Approved, the following operations occur:
  - a. The business object is routed to the JTextConnector via the Process\_Reviewed\_Item collaboration object’s Sync port. The JTextConnector writes the Retail\_Item business object to a file system. If this is successful, the item status is changed to Synchronized; if not, the item status is changed to Error.
  - b. The business object is sent to the respond\_to port to be passed to a UCCnetMessageSend collaboration object. Alternatively, the Retail\_Item can be sent to a single application other than the JTextConnector or to multiple back-end applications. See “Synchronizing an item to a back-end application other than a file system” on page 46 and “Synchronizing an item to multiple back-end applications” on page 46.
5. Optionally, the Process\_Reviewed\_Item collaboration object rewrites the Retail\_Item to the local item store by sending the business object and a Create verb to the local\_store port to be passed to an ItemStore collaboration object.
6. The ItemStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, stores the item in the item store. The section “Persisting, retrieving, updating, or deleting an item to or from a local item store” on page 53 describes how a business object is persisted to the item store.
7. The UCCnetMessageSend collaboration object receives the Retail\_Item business object on its FromRetail port. It then retrieves the layer information from the local message store by using the Retail\_Item internals.originalCorrelationID and converting the Retail\_Item to a UCCnetGBO\_storable business object and passing it with a Retrieve verb to a MessageStore collaboration object through its ToMessage\_Store port. If the Retail\_Item internals.originalCorrelationID attribute is not populated the Retail\_Item internals.correlationID attribute value is used
8. The MessageStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, retrieves the message from the message store database and returns it to the UCCnetMessageSend collaboration object.

The section “Persisting, retrieving, or deleting an item to or from a local message store” on page 52 describes how a message is retrieved from the message store.

9. The UCCnetMessageSend collaboration object extracts the Catalogue Item Notification command from the UCCnetGBO\_storable business object and handles the object according to its original command type, its status value, and the values of certain properties. For the purposes of this example, assume that the original Catalogue Item Notification was a NEW\_ITEM and the status is Approved. See Chapter 9, “Sending responses to UCCnet,” on page 47 for more information. The UCCnetMessageSend collaboration object builds a Catalogue Item Confirmation command message, composes the UCCnetGBO\_envelope business object by first converting the Retail\_Item and UCCnetGBO\_storable business objects into a UCCnetGBO\_RI\_S business object, and then passing this object through the map specified in its TOAS2\_RESPONSE\_MAP configuration property. The resulting UCCnetGBO\_envelope business object contains all of the information needed for the UCCnet Catalogue Item Confirmation message.
10. The UCCnetMessageSend collaboration object passes the UCCnetGBO\_envelope business object to the AS2 channel connector on its ToAS2\_Response port. In the connector controller portion of the connector, it is converted to an application specific business object of the form UCCnetxxx\_envelope (if iSoft connectivity is used), UCCnetTPIxxx\_envelope (if TPI connectivity is used), or UCCnetJMSxxx\_envelope (if WebSphere Business Connect is used with JMS). The UCCnetGBO\_envelope business object is converted by passing through either the UCCnetGBO\_envelope\_to\_UCCnetxxx\_envelope map (if iSoft connectivity is used), the UCCnetGBO\_envelope\_to\_UCCnetTPIxxx\_envelope map (if TPI connectivity is used), or the UCCnetGBO\_envelope\_to\_UCCnetJMSxxx\_envelope map (if WebSphere Business Connect is used with JMS). The DTD forms of these maps convert outgoing UCCnetGBO\_envelope GBOs containing XSD-based Catalogue Item Confirmation commands into ASBOs containing DTD-based Authorization commands.

**Note:** The variable *xxx* specifies the XML definition type used (DTD or XSD).

11. The UCCnetMessageSend collaboration object checks the Retail\_Item internals.lastCascadedGLN attribute to determine if the message store entry should be deleted. If the attribute is not false the UCCnetMessageSend collaboration object enables the deletion of the entry from the message store by using the Retail\_Item internals.originalCorrelationID and converting the Retail\_Item to a UCCnetGBO\_storable business object and passing it with a Delete verb to a MessageStore collaboration object through its ToMessage\_Store port. If the Retail\_Item internals.originalCorrelationID attribute is not populated the Retail\_Item internals.correlationID attribute value is used.
12. The MessageStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML, deletes the message from the message store. See “Persisting, retrieving, or deleting an item to or from a local message store” on page 52.
13. The AS2 channel connector calls the IBM WebSphere Business Integration Data Handler for XML to produce the XML message.
14. The AS2 channel connector passes this message to the iSoft Peer-to-Peer Agent, the TPI server or to WebSphere Business Integration Connect.

15. An AUTHORIZED authorization command for DTDs or SYNCHRONISED Catalogue Item Confirmation command for XSDs is sent to UCCnet.

A Process\_Reviewed\_Item collaboration object can be configured to initiate notification if an item has a status of Approved, Accepted, or Rejected or if errors are detected during processing. It connects through its mail port to a Role\_Email collaboration object, which actually controls the e-mail. See Chapter 11, "Controlling e-mail," on page 55.

A Process\_Reviewed\_Item collaboration object can also log the business object being processed when an error occurs (in addition to the error) and when item status values are Approved, Accepted, and Rejected. A Role\_Email collaboration object can log when errors occur and each time an e-mail message is sent. See Chapter 12, "Logging," on page 65.



---

## Chapter 2. Filtering publication requests before business processing

Details the preprocessing filtering performed by a `UCCnetMessageReceive` collaboration object, which ensures that items contain attributes required by UCCnet, that they are from supply-side trading partners or in categories accepted by the demand-side trading partner, that duplicate items are not processed, and that items pass a set of complex filters based on the interaction of multiple attributes.

### Purpose

Catalogue Item Notifications that arrive from UCCnet can be filtered before business processing occurs to ensure that certain attributes required by UCCnet are present, that items are from specified supply-side trading partners, that items are in categories accepted by the demand-side trading partner, or that items pass complex filters that are based on multiple attributes.

Catalogue Item Notifications with `NEW_ITEM`, `DATA_CHANGE`, `WITHDRAW`, and `DE_LIST` commands can also be checked against an existing identifier store to eliminate processing of duplicate items. All of these filtering operations are performed by a `UCCnetMessageReceive` collaboration object.

---

### Filtering based on the presence of attributes required by UCCnet

Enabling a `UCCnetMessageReceive` collaboration object to filter Catalogue Item Notifications for the presence of attributes required by UCCnet.

#### Filter rules

To enable a `UCCnetMessageReceive` collaboration object to filter Catalogue Item Notifications for the presence of attributes required by UCCnet, create an external text file and list those `UCCnetGBO_envelope` business object attributes that must be present and not contain `NULL` or `BLANK` values. Specify the path and name of this file in the `UCCnetMessageReceive` collaboration object's `REQUIRED_ATTRIBUTE_FILE` configuration property.

This external text file can contain one of the following:

- A simple list of the fully qualified attributes in the `UCCnetXSD_envelope_notification` child business object of the `UCCnetGBO_envelope` business object that must be present (one attribute per line).
- Complex filters that conditionally specify the list of attributes.

The first line of the file determines whether simple or complex filtering is performed. If the first line contains a single fully qualified business object attribute name, simple filtering is performed on the rest of the attributes listed in the file. If the first line of the file contains a separator of `FILTER` or `FIELDS`, complex filtering is assumed.

To provide complex filtering, the file must contain any number of sections, each section containing FILTER and FIELDS subsections. Filterless FIELDS subsections can also be included.

### Filter subsections

Each FILTER subsection filters on one or more business object attributes. A FILTER subsection contains the following parts:

- A fully qualified business object attribute name on a single line.
- On the next single line, a comma-delimited list of valid values for the attribute.
- If filtering on multiple attributes, on the next single line, a value of AND.
- On the next single line, another fully qualified attribute name.
- On the next single line, a comma-delimited list of valid values for that attribute. Any number

Any number of attributes can be filtered in this way.

Each FILTER subsection must be followed by a FIELDS subsection. A FIELDS subsection must contain the required attributes for the filter above it, each attribute on a separate single line. A FIELDS subsection can be followed by a FILTER subsection, another FIELDS subsection without a filter, or an optional END separator at the end of the file. If a FIELDS subsection is specified without a FILTER subsection in front of it, the list of attributes in that FIELDS subsection is always required.

The UCCnetMessageReceive collaboration object reads through the text file examining the first line. If the line contains a fully qualified business object attribute name, the collaboration object checks all attributes named in the specified file. If any of the listed attributes are missing from the business object or are present in the business object but missing data, the collaboration object logs the business object and handles it according to the value specified in its FILTER\_FAIL\_RESPONSE configuration property.

If the first line of the file contains a FILTER or FIELDS separator, the collaboration object reads the file until it finds a FILTER subsection that is satisfied by the attribute values contained in the business object being processed. The collaboration object then checks all attributes in the business object against the list of attributes included in the FIELDS subsection related to the satisfied filter.

If any of the attributes in the FIELDS subsection are missing from the business object or are present in the business object but missing data, the collaboration object logs the business object and handles it according to the value specified in its FILTER\_FAIL\_RESPONSE configuration property.

If no file is specified in the REQUIRED\_ATTRIBUTE\_FILE property, or if no attributes are indicated within the file, all items are accepted for further processing by the collaboration object.

The following file is an example that demonstrates complex filtering.

```
FILTER
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.informationProviderOfTradeItem.informationProvider.gln
0001111222333
AND
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemUnitDescriptor
```

```

CASE,PALLET
FIELDS
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.netWeight
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.grossWeight
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.height
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.width
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.depth
FILTER
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.informationProviderOfTradeItem.informationProvider.gln
00011112222333
AND
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemUnitDescriptor
BASE_UNIT_OR_EACH
FIELDS
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.netWeight
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.grossWeight
END

```

The collaboration object checks if the business object being processed has a gln attribute value of 00011112222333 and a tradeItemUnitDescriptor attribute value of CASE or PALLET. If it does not, the collaboration proceeds to the next FILTER. If it does, the collaboration object then checks if the business object being processed contains the attributes netWeight, grossWeight, height, width, and depth, and that these attributes are not NULL or BLANK. If the business object passes this filter, collaboration object processing continues. If any of the attributes in the FIELDS subsection are missing from the business object or are present in the business object but missing data, the collaboration object logs the business object and handles it according to the value specified in its FILTER\_FAIL\_RESPONSE configuration property.

The collaboration object then proceeds to the next FILTER subsection. It checks if the business object has a gln value of 00011112222333 and a tradeItemUnitDescriptor attribute value of BASE\_UNIT\_OR\_EACH. If it does, the collaboration object then checks if the business object being processed contains the attributes netWeight and grossWeight, and that these attributes are not NULL or BLANK. If the business object passes this filter, collaboration object processing continues. If any of the attributes in the FIELDS subsection are missing from the business object or are present in the business object but missing data, the collaboration object logs the business object and handles it according to the value specified in its FILTER\_FAIL\_RESPONSE configuration property.

---

## Filtering based on items belonging to approved supply-side trading partners

Enabling a UCCnetMessageReceive collaboration object to filter Catalogue Item Notifications to ensure that they come from supply-side trading partners approved by the demand-side trading partner.

### Filter rules

To enable a UCCnetMessageReceive collaboration object to filter Catalogue Item Notifications to ensure that they come from supply-side trading partners approved by the demand-side trading partner, create an external text file and list those trading partners from whom items are accepted. Specify the path and name of this file in the UCCnetMessageReceive collaboration object's `VENDOR_FILE` configuration property.

Each entry in this file must have the following structure and be followed by a line return:

```
vendorGLN,other_data,other_data,...
```

In this structure, `vendorGLN` is the GLN (assigned by UCCnet) of an accepted supply-side trading partner. This value is found in the `entityIdentification.globalLocationNumber.gln` field of the `UCCnetXSD_envelope_notification` child business object of the `UCCnetGBO_envelope` business object. The variables called `other_data` are other data entries that can be linked to the vendor GLN. The vendor GLN must be the first entry in the line. Any number of associated attributes can be appended to the line as long as they are separated by commas (`,`). Do not place a comma before the vendor GLN. The following is an example of a valid entry:

```
0001111222333,TestVendor,(111)111-1111,contact@TestVendor.com
```

The collaboration object checks the `entityIdentification.globalLocationNumber.gln` field of the `UCCnetXSD_envelope_notification` child business object. If the supply-side trading partner specified in this business object attribute is also listed in the file specified by the collaboration object's `VENDOR_FILE` property, the collaboration object processes the business object normally. If the supply-side trading partner specified in the business object attribute is not listed in this file, the collaboration object logs it and handles it according to the value specified in its `FILTER_FAIL_RESPONSE` configuration property. If no file is specified in the `VENDOR_FILE` property, all items are accepted for further processing by the collaboration object.

---

## Filtering based on items belonging to accepted categories

Enabling a UCCnetMessageReceive collaboration object to filter Catalogue Item Notifications to ensure that they belong to categories accepted by the demand-side trading partner.

### Purpose

To enable a UCCnetMessageReceive collaboration object to filter Catalogue Item Notifications to ensure that they belong to categories accepted by the demand-side trading partner, create an external text file and list those categories from which

items are accepted. Specify the path and name of this file in the UCCnetMessageReceive collaboration object's CATEGORY\_FILE configuration property.

Each line of this file must contain only one category value. Each entry can include embedded special characters, such as periods (.) and commas (,), as long as the characters are valid within the category. Do not place characters in the line other than those specified in the category. The following is an example of a valid entry:

```
0001.0001.001
```

The collaboration object checks the **notificationDetail.catalogueItemNotification.catalogueItem.tradeItem.tradeItemInformation.classificationCategoryCode.additionalClassification.additionalClassificationCategoryCode** field of the UCCnetXSD\_envelope\_notification child business object of the UCCnetGBO\_envelope business object. If the value specified in this business object attribute is also listed in the file specified in the collaboration object's CATEGORY\_FILE property, the collaboration object processes it normally. If the value listed in the business object attribute is not from a category listed in this file, the collaboration object handles it according to the value specified in its FILTER\_FAIL\_RESPONSE configuration property. If no file is specified in the CATEGORY\_FILE property, all items are accepted for further processing by the collaboration object.

---

## Complex field filtering based on multiple attributes

Enable a UCCnetMessageReceive collaboration object to filter Catalogue Item Notifications based on a complex set of field criteria.

### Filter rules

To enable a UCCnetMessageReceive collaboration object to filter Catalogue Item Notifications based on a complex set of field criteria, create an external text file that includes the complex filtering information. Specify the path and name of the file in the UCCnetMessageReceive collaboration object's COMPLEX\_FILTER\_FILE configuration property. This file can contain any number of sections on which the collaboration will filter, each section containing a fully qualified business object attribute and a comma-delimited list of valid values for the attribute. The collaboration object can search on multiple attribute name/value pairs combined with an AND separator, or on mutually exclusive groups of attribute name/value pairs separated by a NEXT separator. A file must be composed as follows:

- The first line contains a fully qualified attribute name on a single line.
- On the next single line, a comma-delimited list of valid values for the attribute.
- On the next single line, one of the following values:
  - AND - A value of AND is followed by another fully qualified attribute name on a single line followed by a comma-delimited list of valid values for it on the following single line. Any number of attributes can be checked together in this way.
  - NEXT - A value of NEXT is followed by another set of attributes and values combined with an AND separator.
  - END - A value of END signifies the end of the list of complex filters.

## Processing

The UCCnetMessageReceive collaboration object reads through the Complex Filter File until it finds an attribute name/value pair that is satisfied by the attribute name/value contained in the business object being processed. If the business object passes complex filtering, the collaboration object processes it normally. If the business object does not pass complex filtering, the collaboration handles it according to the value specified in the FILTER\_FAIL\_RESPONSE configuration property. If no file is specified in the COMPLEX\_FILTER\_FILE property, all items are accepted for further processing by the collaboration object. If an item satisfies the conditions of multiple filters, only the first filter in the file is ever considered.

```
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \  
tradeItemInformation.informationProviderOfTradeItem.informationProvider.gln  
00011112222333  
AND  
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \  
tradeItemInformation.classificationCategoryCode.additionalClassification[0]. \  
additionalClassificationCategoryCode  
0001.001.001  
NEXT  
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \  
tradeItemInformation.informationProviderOfTradeItem.informationProvider.gln  
00011112222334  
AND  
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \  
tradeItemInformation.classificationCategoryCode.additionalClassification[0]. \  
additionalClassificationCategoryCode  
0001.001.005  
END
```

The collaboration object checks if the business object being processed has a gln attribute value of 00011112222333 and an additionalClassificationCategoryCode attribute value of 0001.001.001. If it does, the business object is accepted and collaboration object processing continues.

If these first filter conditions were not satisfied, the collaboration object now proceeds to the attribute name/value following the NEXT separator. It checks if the business object has a gln value of 00011112222334 and an additionalClassificationCategoryCode attribute value of 0001.001.005. If it does, the business object is accepted and collaboration object processing continues. If it does not, the collaboration ends processing.

---

## Filtering to eliminate processing of duplicate items

A UCCnetMessageReceive collaboration object filters Catalogue Item Notifications with NEW\_ITEM, DATA\_CHANGE, WITHDRAW, or DE\_LIST commands to ensure that they are not duplicate items.

### Process flow

During normal item processing, a UCCnetMessageReceive collaboration object enables persistence of the UCCnetGBO\_envelope business object to a local identifier store by converting it to a UCCnetGBO\_identifier business object and passing it to its ToIdentifier\_Store port. This port is connected to an IdentifierStore collaboration object. The IdentifierStore collaboration object performs the actual storage operation. See “Persisting or deleting an item to or from a local identifier store” on page 19.

Before sending the object to this port, the collaboration object checks the value of its `FILTER_DUPLICATE` configuration property. If the value is true (which is the default value), the collaboration object checks if an item with identical key attribute values exists in the identifier store.

If you are processing DTDs the keys are the `gtin`, `version`, and `topic` attributes.

If you are processing XSDs, the keys are the `gtin`, `topic`, `dataRecipientGLN`, `dataSourceGLN`, `targetMarket` and `uniqueCreatorID` attributes.

If an identical item does exist, the second entry with identical information is logged as a duplicate and further processing of it ends. If an identical item does not exist, the item is added to the local identifier store and processed normally.

## Persisting or deleting an item to or from a local identifier store

Various collaboration objects used in the Product Information Management for Retailers solution can initiate the storage or deletion of a business object to or from an identifier store.

### Description

Various collaboration objects used in the Product Information Management for Retailers solution can initiate the storage or deletion of a business object to or from an identifier store, as follows:

- For a Catalogue Item Notification with a `NEW_ITEM`, `DATA_CHANGE`, `WITHDRAW`, or `DE_LIST` command, a `UCCnetMessageReceive` collaboration object initiates persisting the `UCCnetGBO_envelope` business object by sending it with a `Create` verb to its `ToIdentifier_Store` port.
- When error conditions are encountered, a `UCCnetMessageSend` collaboration object initiates deleting the `UCCnetGBO_envelope` business object by sending it with a `Delete` verb to its `ToIdentifier_Store` port.

In either case, before sending the `UCCnetGBO_envelope` business object to the port, the collaboration object first converts it to a `UCCnetGBO_identifier` business object by passing it through the map specified in its `TOIDENTIFIER_STORE_MAP` property. The `ToIdentifier_Store` port can then be bound to a persistence mechanism. In the context of the Product Information Management for Retailers solution, this mechanism is an `IdentifierStore` collaboration object.

The `IdentifierStore` collaboration object receives the business object on its `From` port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML (which are detailed per command in `IdentifierStore` collaboration template), stores or deletes the identifier. The key to this record in the identifier store is made up of the attributes `gtin`, `version`, and `topic` of the `UCCnetGBO_identifier` business object for DTD processing, and the attributes `gtin`, `topic`, `dataRecipientGLN`, `dataSourceGLN`, `targetMarket`, and `uniqueCreatorID` of the `UCCnetGBO_identifier` business object for XSD processing. The `UCCnetMessageReceive` collaboration object can also check if a duplicate item already exists in the identifier store to prevent processing of duplicate items. See the section for more information on this feature.

In either case, before sending the `UCCnetGBO_envelope` business object to the port, the collaboration object first converts it to a `UCCnetGBO_identifier` business object by passing it through the map specified in its `TOIDENTIFIER_STORE_MAP`

property. The `ToIdentifier_Store` port can then be bound to a persistence mechanism. In the context of the Product Information Management for Retailers solution, this mechanism is an `IdentifierStore` collaboration object.

The `IdentifierStore` collaboration object receives the business object on its `From` port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML (which are detailed per command in the `IdentifierStore` collaboration template), stores or deletes the identifier. The key to this record in the identifier store is made up of the attributes `gtin`, `version`, and `topic` of the `UCCnetGBO_identifier` business object for DTD processing, and the attributes `gtin`, `topic`, `dataRecipientGLN`, `dataSourceGLN`, `targetMarket`, and `uniqueCreatorID` of the `UCCnetGBO_identifier` business object for XSD processing. The `UCCnetMessageReceive` collaboration object can also check if a duplicate item already exists in the identifier store to prevent processing of duplicate items. See the section for more information on this feature.

---

## Chapter 3. Validating an item before business processing

Describes the item validation processes provided by an ItemValidation collaboration object, which include validating a Retail\_Item business object against customized business policy rules and evaluating an accepted business object against a customized list of required attribute data. It also details how to use a custom missing data retrieval process to obtain required attribute data.

### Purpose

A Retail\_Item business object created from an Catalogue Item Notification can be subjected to validation processes provided by code in the ItemValidation collaboration template. Use a collaboration object based on the ItemValidation collaboration template:

- To accept or reject a Retail\_Item business object based on customized business policy rules
- To evaluate an accepted business object based on a customized list of required attribute data.
- To direct the business object to the appropriate port based on the results of the evaluation.

After an item completes validation successfully, the collaboration object changes its status to Review and sends the item to its *To* port. This port is connected to an ItemDispatcher collaboration object.

---

### Validating an item against customized business policy rules

To accept or reject an item based on existing business policies, insert customized code into the ItemValidation collaboration template's Business Policy Processing subdiagram.

### Purpose

Enable the logic in this subdiagram to execute for specific commands attached to a Retail\_Item by specifying those commands in an ItemValidation collaboration object's BUSINESS\_POLICY\_CMDS configuration property.

The pre-existing subdiagram logic examines the value for the Retail\_Item business object's attribute named in the ItemValidation collaboration object's ITEM\_COMMAND\_ATTRIBUTE configuration property against the values specified in its BUSINESS\_POLICY\_CMDS configuration property. If the value for the attribute in the ITEM\_COMMAND\_ATTRIBUTE property is specified in the BUSINESS\_POLICY\_CMDS property, the ItemValidation collaboration object executes the customized code in the Business Policy Processing subdiagram.

The rules in the customized code must specify whether the Retail\_Item is accepted or rejected for subsequent processing by changing the value of its attribute named in the ItemValidation collaboration object's ITEM\_STATUS\_ATTRIBUTE configuration property. If the item is accepted, the code must change the value of the business object attribute to Review; if the item is rejected, it must change the value to Rejected. The pre-existing subdiagram logic uses this attribute value to determine whether to return the item to the caller or to continue processing it. If

the item is rejected, the business policy subdiagram raises an exception to abort the item processing and returns it to the main scenario, where the item rejection processing is handled.

---

## Validating an item by requiring data for specific attributes

Identifying certain Retail\_Item business object attributes for which data must exist.

A standard message from UCCnet might not contain all of the data required by an implementation. In this case, certain Retail\_Item business object attributes must be identified for which data must exist (the attributes must not be NULL or BLANK) before an item is accepted for processing. Pre-existing code in the ItemValidation template's File Missing Attribute Logic subdiagram enables this type of item validation.

To use this type of validation, do the following:

1. Create a text file that contains one of the following:
  - A simple list of the fully qualified attributes in the Retail\_Item business object that must be present (one attribute per line).
  - Complex filters that conditionally specify the list of attributes.

The first line of the file determines whether simple or complex filtering is performed. If the first line contains a single fully qualified business object attribute name, simple filtering is performed on the rest of the attributes listed in the file. If the first line of the file contains a separator of FILTER or FIELDS, complex filtering is assumed. See "Performing simple filtering" on page 23 and "Performing complex filtering" on page 24.

2. Specify the fully qualified name of this text file in the REQUIRED\_ATTRIBUTE\_FILE configuration property.
3. Enable the logic in the File Missing Attribute Logic subdiagram to execute for specific commands attached to a Retail\_Item by specifying those commands in the REQUIRED\_ATTRIBUTE\_CMDS configuration property. Pre-existing logic examines the value of the Retail\_Item business object's attribute, named in the configuration property ITEM\_COMMAND\_ATTRIBUTE, against the values specified in the REQUIRED\_ATTRIBUTE\_CMDS configuration property. If the value of the attribute named in the ITEM\_COMMAND\_ATTRIBUTE property is specified in the REQUIRED\_ATTRIBUTE\_CMDS property, the ItemValidation collaboration object executes the code.
4. Because the data collection process can be asynchronous or the tool used to perform it (such as a WebSphere MQ Workflow container) might be limited in size and not able to persist all of the attributes of a Retail\_Item business object, save a complete copy of the Retail\_Item business object in an item store before it is passed to the ToMissingData port for processing. This can be accomplished by setting the value of the ItemValidation collaboration object's RETAIN\_ITEM\_IN\_LOCAL\_STORE property to true. The collaboration object then calls an ItemStore collaboration object, which actually performs the storage operation.

**Note:** The value of the ItemValidation collaboration object's RETAIN\_ITEM\_IN\_LOCAL\_STORE property must be set to true for the Product Information Management for Retailers solution to operate properly.

## Performing simple filtering

A description and examples of simple filtering.

### Description

For simple filtering, the text file specified in the `REQUIRED_ATTRIBUTE_FILE` property must contain a list of the fully qualified attributes in the `Retail_Item` business object that must be present and not `NULL` or `BLANK`. It is composed, as follows:

- A fully qualified business object attribute name on a single line.
- On the next single line, another fully qualified attribute name.

Any number of attributes can be included in this way. The File Missing Attribute logic reads the attribute names from this file and employs an external Java(TM) class called `RetailUtility` in the Java package `com.ibm.wbi.retail.utils` to determine if the required attributes listed in the file contain data in the `Retail_Item` business object being processed. It then adds the names of any required attributes missing data to a `Retail_Item` business object attribute named in the configuration property `CUST_DATA_MISS_ATTR`. This attribute consists of a multiple cardinality array of `Retail_Missing_Attributes` business objects. If there are any names in this missing attribute child business object array, the `ItemValidation` collaboration object passes the `Retail_Item` business object to the `ToMissingData` port to start a process for obtaining the missing data.

### Examples

The following examples show how the missing attribute list is populated:

- The attribute `customer_data.vendorAddress` is included in the required attribute file. The `Retail_Item` business object that triggers the `ItemValidation` collaboration object does not contain an instance of the `customer_data` child business object attribute. Therefore, the missing attribute code does not include `customer_data.vendorAddress` in the missing attribute list.
- The attribute `customer_data.vendorAddress` is included in the required attribute file. The `Retail_Item` business object that triggers the `ItemValidation` collaboration object does contain an instance of the `customer_data` child business object attribute. The `vendorAddress` attribute is `NULL`. Therefore, the missing attribute code includes `customer_data.vendorAddress` in the missing attribute list.
- The attribute `item.catalogueItem.catalogueItemChildItemLink[].catalogueItem.tradeItem.tradeItemIdentification.gtin` is included in the required attribute file. The `Retail_Item` business object that triggers the `ItemValidation` collaboration object contains two instances of the `catalogueItemChildItemLink` business object attribute, each of which contains an instance of the `catalogueItem.tradeItem.tradeItemIdentification` child business object. In each instance, the `gtin` attribute is `NULL`. Therefore, the missing attribute code adds the following entries to the missing attribute list:

```
item.catalogueItem.catalogueItemChildItemLink[0].catalogueItem.tradeItem. \  
tradeItemIdentification.gtin  
item.catalogueItem.catalogueItemChildItemLink[1].catalogueItem.tradeItem. \  
tradeItemIdentification.gtin
```

The missing attribute code includes specific references to all required attributes that exist, but are `NULL` or `BLANK`.

- The attribute `item.catalogueItem.catalogueItemChildItemLink[].catalogueItem.tradeItem.tradeItemIdentification.gtin` is included in the required attribute file. The `Retail_Item` business object that triggers the `ItemValidation` collaboration object contains no instances of the `catalogueItemChildItemLink` business object attribute. Therefore, the missing attribute code includes no references to the `item.catalogueItem.catalogueItemChildItemLink[].catalogueItem.tradeItem.tradeItemIdentification.gtin` attribute in the missing attribute list.

## Performing complex filtering

A description and examples of complex filtering.

### Description of complex filtering

For complex filtering, the text file specified in the `REQUIRED_ATTRIBUTE_FILE` property must contain the fully qualified attributes in the `Retail_Item` business object that must be present and not `NULL` or `BLANK`, conditionally specified by complex filters.

The first line of the file must contain a separator of `FILTER` or `FIELDS`. The file can contain any number of sections, each section containing `FILTER` and `FIELDS` subsections. Filterless `FIELDS` subsections can also be included.

Each `FILTER` subsection filters on one or more business object attributes. A `FILTER` subsection contains the following:

- A fully qualified business object attribute name on a single line.
- On the next single line, a comma-delimited list of valid values for the attribute.
- If filtering on multiple attributes, on the next single line, a value of `AND`.
- On the next single line, another fully qualified attribute name.
- On the next single line, a comma-delimited list of valid values for that attribute.

Any number of attributes can be filtered in this way.

Each `FILTER` subsection must be followed by a `FIELDS` subsection. A `FIELDS` subsection must contain the required attributes for the filter above it, each attribute on a separate single line. A `FIELDS` subsection can be followed by a `FILTER` subsection, another `FIELDS` subsection without a filter, or an optional `END` separator at the end of the file. If a `FIELDS` subsection is specified without a `FILTER` subsection in front of it, the list of attributes in that `FIELDS` subsection is always required.

The collaboration object reads the file until it finds a `FILTER` subsection that is satisfied by the attribute values contained in the business object being processed. The File Missing Attribute logic employs an external Java class called `RetailUtility` in the Java package `com.ibm.wbi.retail.utils` to determine if the required attributes listed in the `FIELDS` subsection of the satisfied filter contain data in the `Retail_Item` business object being processed. See “Using the `RetailUtility` external Java class” on page 26.

If any of the attributes in the `FIELDS` subsection are missing from the business object or are present in the business object but missing data, the collaboration object adds their names to a `Retail_Item` business object attribute named in the configuration property `CUST_DATA_MISS_ATTR`. This attribute consists of a multiple cardinality array of `Retail_Missing_Attributes` business objects. If there are

any names in this missing attribute child business object array, the ItemValidation collaboration object passes the Retail\_Item business object to the ToMissingData port to start a process for obtaining the missing data.

If no file is specified in the REQUIRED\_ATTRIBUTE\_FILE property, or if no attributes are indicated within the file, all items are accepted for further processing by the collaboration object.

### Example

An example file that demonstrates complex filtering and its interpretation follow:

```
FILTER
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.informationProviderOfTradeItem.informationProvider.gln
00011112222333
AND
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemUnitDescriptor
CASE,PALLET
FIELDS
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.netWeight
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.grossWeight
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.height
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.width
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.depth
FILTER
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.informationProviderOfTradeItem.informationProvider.gln
00011112222333
AND
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemUnitDescriptor
BASE_UNIT_OR_EACH
FIELDS
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.netWeight
notificationDetail.catalogueItemNotification.catalogueItem.tradeItem. \
tradeItemInformation.tradingPartnerNeutralTradeItemInformation. \
tradeItemMeasurements.grossWeight
END
```

The collaboration object checks if the business object being processed has a gln attribute value of 00011112222333 and a tradeItemUnitDescriptor attribute value of CASE or PALLET. If it doesn't, the collaboration proceeds to the next FILTER. If it does, the collaboration object then checks if the business object being processed contains the attributes netWeight, grossWeight, height, width, and depth, and that these attributes are not NULL or BLANK. If any of the attributes in the FIELDS subsection are missing from the business object or are present in the business object but missing data, the collaboration object adds their names to a Retail\_Item business object attribute named in the configuration property CUST\_DATA\_MISS\_ATTR and handles the business object as described above.

The collaboration object then proceeds to the next FILTER subsection. It checks if the business object has a gln value of 00011112222333 and a tradeItemUnitDescriptor attribute value of BASE\_UNIT\_OR\_EACH. If it does, the collaboration object then checks if the business object being processed contains the attributes netWeight and grossWeight, and that these attributes are not NULL or BLANK. If any of the attributes in the FIELDS subsection are missing from the business object or are present in the business object but missing data, the collaboration object again adds their names to the Retail\_Item business object attribute named in the configuration property CUST\_DATA\_MISS\_ATTR and handles the business object as described above.

## Specifying attribute names

Describes the rules for specifying attribute names.

### Description

Each child in a hierarchical business object structure described by the attribute name is separated by periods. Any multiple-cardinality child business objects (BusObjArray) in the structure are represented in the element by appending front- and end-bracket symbols ([]) to the name of the child attribute. Single-cardinality child business objects must not contain brackets ([]) in the attribute name. The brackets ([]) characters are required to tell the code that parses through the child business objects in the attribute whether the object is a single business object (BusObj) or a business object array (BusObjArray).

Some example file entries corresponding to Retail\_Item business object attributes include the following:

```
customer_data.vendorAddress
item.catalogueItem.catalogueItemChildItemLink[].catalogueItem.tradeItem. \
tradeItemIdentification.gtin
```

Notice that because the catalogueItemChildItemLink business object is a multiple-cardinality business object array, the [] characters are appended to its name in the fully qualified attribute.

**Note:** If an attribute is part of a hierarchy of parent and child business objects, and any of the attribute's parent business objects does not exist in the Retail\_Item, then the missing attribute code does not include the attribute in the missing attribute list. Also, the Retail\_Item business object must contain an instance of its customer\_data child business object for the data check code to successfully check the customer\_data child business object attributes.

The ItemValidation collaboration object always converts mixed-case Strings to lowercase characters by using the command toLowerCase() before testing their values against known values, with the exception that attributes that are used by Java to reference a business object remain in mixed-case characters. An example is an attribute name that is inserted in the multiple cardinality array of Retail\_Missing\_Attributes business objects in the internals.customer\_data\_missing\_attributes attribute.

## Using the RetailUtility external Java class

Describes how to use the external RetailUtility Java class to check that required attributes exist.

## Description

A collaboration object based on the ItemValidation collaboration template checks that required attributes exist and contain data by using an external Java class called RetailUtility, located in the Java package com.ibm.wbi.retail.utils. It recursively parses each fully qualified attribute string to determine if the value of the attribute is NULL or BLANK.

## Methods in the class

The class contains the following methods:

```
public boolean checkRequiredAttribute(BusObj busObj, Vector attrs, Vector err) \
throws Exception
```

This method, `checkRequiredAttribute`, takes as input the Retail\_Item business object and two Vectors. The first Vector contains the list of fully qualified attribute names to be checked for NULL or BLANK values. On return, the second Vector contains the list of missing attributes (those containing NULL or BLANK values). The method returns true if no attribute data is missing; it returns false if any required attribute data is missing.

```
public boolean checkRequiredAttribute(BusObj busObj, String attr, Vector err) \
throws Exception
```

This method, also named `checkRequiredAttribute`, operates the same as the previous method, except it takes as input a single fully qualified attribute name.

```
public boolean checkComplexFilters(BusObj busObj, Vector complexFilters) \
throws Exception
```

`checkComplexFilters`, takes as input the Retail\_Item business object and one Vector. The Vector contains HashMaps of complexFilters to be checked. If any of the complex filters evaluate to true, then true is returned. If none of them evaluate to true, then false is returned.

```
public boolean checkComplexFilter(BusObj busObj, HashMap complexFilter) \
throws Exception
```

This method, `checkComplexFilter`, operates the same as the previous method, except that it takes as input a HashMap of a single complex filter.

## Runtime behavior

At runtime, if the collaboration object's missing attribute data check logic is enabled (the value of the Retail\_Item business object's attribute named in the configuration property `ITEM_COMMAND_ATTRIBUTE` exists in the `REQUIRED_ATTRIBUTE_CMDS` property), and the required attribute Vector contains elements, this class must be added to a directory or to a jar file contained in one of the following:

- On Windows(R) 2000 systems, the ICS CLASSPATH, which is set up during the `start_server.bat` file prior to starting the ICS
- On AIX(R) and Solaris(TM) systems, the CWCLASSES path, which is set up during the `CWSharedEnv.sh` file prior to starting the ICS.

Access to this external Java class via the ICS CLASSPATH or CWCLASSES path is also required in order to successfully compile the ItemValidation collaboration template.

## Using the Custom Missing Attribute Logic

Describes customized code for user-defined methods for identifying the required attributes of the Retail\_Item business object that are missing data.

### Description

The ItemValidation collaboration template also contains a subdiagram called Custom Missing Attribute Logic. This subdiagram holds customized code for user-defined methods for identifying the required attributes of the Retail\_Item business object that are missing data. This code can be executed instead of, or in addition to, the code in the File Missing Attribute Logic subdiagram. Before customization, the Custom Missing Attribute Logic subdiagram contains examples of the following methods to enhance the algorithm for identifying required attributes of the Retail\_Item business object that are missing data.

**Note:** These examples do not execute as long as the TEST configuration property is set to false. These examples should not be executed as part of production code.

- Add fully qualified attribute names to the Required Attribute Vector, which is processed later in the algorithm.
- Add fully qualified attribute names to the Missing Attribute Vector, which is processed later in the algorithm.
- Modify the name of the file that is normally set from the REQUIRED\_ATTRIBUTE\_FILE configuration property.
- Create and add instances of Retail\_Missing\_Attributes business objects directly to the attribute named in the CUST\_DATA\_MISS\_ATTR configuration property (by default, internals.customer\_data\_missing\_attributes).

## Using a custom missing data retrieval process to collect data

Describes collecting missing data.

### Description

The custom process used to collect missing data can be another collaboration object, a user interface, a WebSphere MQ Workflow process, or even an email function. Regardless of the method used, it must set each missing attribute value it acquires into the internals.customer\_data\_missing\_attributes.attributeValue attribute of the Retail\_Item business object. In the context of the Product Information Management for Retailers solution, it must then call an ItemCollector collaboration object, which assembles the complete Retail\_Item business object by merging the values of each missing attribute, internals.customer\_data\_missing\_attributes.attributeValue, into its proper place in a previously stored, complete Retail\_Item business object retrieved from the item store. See Merging data into a complete item for information about how the ItemCollector collaboration object merges missing information.

**Note:** If the custom missing data retrieval process is not asynchronous, or can persist a complete Retail\_Item business object, an ItemCollector collaboration object does not have to be used. The custom process can reuse code in the ItemCollector collaboration template to merge the collected data into the Retail\_Item business object and then pass the merged Retail\_Item business object to a Process\_Reviewed\_Item collaboration object. The DELETE\_FROM\_LOCAL\_STORE property of the Process\_Reviewed\_Item collaboration object would need to be set to false. It is recommended that

the custom missing data retrieval process not be connected to an ItemValidation collaboration object because of error flows. If an error occurs, the Process\_Reviewed\_Item collaboration object calls a UCCnetMessageSend collaboration object to send a response back to the original sender (UCCnet in the context of the Product Information Management for Retailers solution).



---

## Chapter 4. Adding customized code to the ItemValidation collaboration template

Information on how to add custom logic to the ItemValidation collaboration template.

### Description

The ItemValidation collaboration template contains a subdiagram called Message Type Processing that can be customized to contain any desired logic. After including code in this subdiagram, enable it to execute for specific commands attached to a Retail\_Item by specifying those commands in the ItemValidation collaboration object's MESSAGE\_TYPE\_PROCESSING\_CMDS configuration property.

The subdiagram logic examines the value for the Retail\_Item business object's attribute named in the ItemValidation collaboration object's ITEM\_COMMAND\_ATTRIBUTE configuration property against the values specified in its MESSAGE\_TYPE\_PROCESSING\_CMDS configuration property. If the value for the attribute in the ITEM\_COMMAND\_ATTRIBUTE property is specified in the MESSAGE\_TYPE\_PROCESSING\_CMDS property, the ItemValidation collaboration object executes the customized code in the Message Type Processing subdiagram.

**Note:** The code contained in the Message Type Processing subdiagram does *not* replace the code in the File Missing Attribute Logic or Custom Missing Attribute Logic subdiagrams.



---

## Chapter 5. Processing business objects with cascaded GLNs

Explains how the solution handles items containing cascaded GLNs.

### Description

The ItemDispatcher collaboration template is used to control how approval requests generated by an ItemValidation collaboration object are sent to a WebSphere MQ Workflow process. If a Retail\_Item business object that requires approval contains cascaded GLNs, the ItemDispatcher collaboration object breaks up the request for approval into multiple smaller messages, each containing one or more of the individual GLNs.

### Example

For example, assume that you are working with a single object that has a cascaded GLN containing six individual GLNs:

GLNs 1, 2, and 3 are the responsibility of approver A.

GLNs 4 and 5 are the responsibility of approver B.

GLN 6 can be ignored.

You can use the ItemDispatcher collaboration to create one copy of the Retail\_Item business object that contains only GLNs 1, 2, and 3, and a second copy that contains only GLNs 4 and 5. GLN 6 is disregarded. These two copies can then be directed to the correct approvers through WebSphere MQ Workflow. How the collaboration object handles any particular GLN is determined by a user-defined configuration file. Items without cascaded GLNs are passed through the collaboration object without processing.

**Note:** You can implement the Product Information Management for Retailers solution without using an ItemDispatcher collaboration object. However, you must use the ItemDispatcher collaboration object if cascaded GLNs will be received.

---

## Using the GLN Cascade Grouping File

The GLN Cascade Grouping File is a user-created text file, which provides information the ItemDispatcher collaboration object needs to determine how to group the GLNs for a given item in messages sent to WebSphere MQ Workflow for approval.

### Description

The GLN Cascade Grouping File can contain any number of sections, each section containing FILTER and GLN\_GROUPS subsections. A final optional “filterless” subsection, containing only a GLN\_GROUPS subsection, can also be included.

Each FILTER subsection filters on one or more Retail\_Item business object attributes. A FILTER subsection contains the following:

- A fully qualified Retail\_Item attribute on a single line.
- On the next single line, a comma-delimited list of valid values for the attribute.
- If filtering on multiple attributes, on the next single line, a value of AND.

- On the next single line, another fully qualified Retail\_Item attribute.
- On the next single line, a comma-delimited list of valid values for that attribute.

Any number of attributes can be filtered in this way.

Each FILTER subsection must be followed by a GLN\_GROUPS subsection. A GLN\_GROUPS subsection must contain at least one comma-delimited list of cascaded GLN values grouped together on a single line. Additional groups of cascaded GLNs can be defined simply by adding more lines of comma-delimited GLN lists to this subsection. A GLN\_GROUPS subsection can be followed by a FILTER subsection, another GLN\_GROUPS subsection without a filter, or an optional END separator at the end of the file.

The ItemDispatcher collaboration object reads through the GLN Cascade Grouping File specified in the GLN\_CASCADE\_GROUPING\_FILE configuration property until it finds a FILTER subsection that is satisfied by the attribute values contained in the Retail\_Item being processed. The collaboration object then groups the GLNs according to the GLN\_GROUPS subsection associated with the satisfied FILTER subsection. If an item satisfies the conditions of multiple filters, only the first filter in the file is ever considered.

### Example

```

FILTER
internals.fromGln
0001000000001,0001000000002
AND
item.catalogueItem.tradeItem.tradeItemInformation.classificationCategoryCode. \
additionalClassification[].additionalClassificationCategoryCode
0001.001.001,0001.001.002,0001.001.003
GLN_GROUPS
0005000000001,0005000000002,0005000000003
0005000000004,0005000000005,0005000000006
FILTER
internals.fromGln
0001000000005
GLN_GROUPS
0005000000001,0005000000002
0005000000003,0005000000004
0005000000005,0005000000006
GLN_GROUPS
0005000000001
0005000000002
0005000000003
0005000000004
0005000000005
0005000000006

```

If the Retail\_Item business object being processed has a fromGln attribute value of 0001000000001 or 0001000000002 and one of the following additionalClassificationCategoryCode attribute values:

```

0001.001.001
0001.001.002
0001.001.002

```

then the GLNs are grouped as follows:

#### Group 1

Contains GLNs 0005000000001, 0005000000002, and 0005000000003, if they exist.

**Group 2**

Contains GLNs 0005000000004, 0005000000005, and 0005000000006, if they exist.

Any GLNs that are not in the GLN\_GROUPS subsection are disregarded. Each group of GLNs is sent separately to WebSphere MQ Workflow for approval, so a maximum of two messages are sent.

If the first filter conditions were not satisfied, the collaboration object now checks to see if the Retail\_Item business object has a fromGln value of 0001000000005. If it does, then the GLNs are grouped as follows:

**Group 1**

Contains GLNs 0005000000001 and 0005000000002, if they exist.

**Group 2**

Contains GLNs 0005000000003 and 0005000000004, if they exist.

**Group 3**

Contains GLNs 0005000000005 and 0005000000006, if they exist.

Any GLNs that are not in the GLN\_GROUPS subsection are disregarded. Each group of GLNs is sent separately to WebSphere MQ Workflow for approval, so a maximum of three messages are sent.

If none of the preceding filters has been satisfied, the filterless GLN\_GROUPS subsection is assumed to apply. Each of the six listed GLNs will be sent to WebSphere MQ Workflow in its own message. Unlisted GLNs are disregarded, so a maximum of six messages are sent.

If no FILTER subsection is satisfied and there is no filterless GLN\_GROUPS subsection, then the behavior is determined by the value of the GLN\_CASCADE\_GROUPING\_DEFAULT property.



---

## Chapter 6. Using a business process to review and approve an item

Describes operations related to utilizing WebSphere MQ Workflow as a custom business review/approval process. The business review/approval process is used by the demand-side trading partner to review an item to determine whether to approve it or reject it.

### Description

The business review/approval process is a custom application used by the demand-side trading partner to review an item to determine whether to accept it. In the context of the Product Information Management for Retailers solution, a WebSphere MQ Workflow process represents it. The process can also be a general user interface or an automated process, such as another collaboration object, that examines specific item attributes and makes a decision based on that data. The following sections describe operations related to using WebSphere MQ Workflow as the business review/approval process

---

### Printing an item before it is sent through the business review/approval process

How to print a hard copy of an item before it is sent through the business review/approval process

To produce a hard copy of an item that arrives from UCCnet, do these steps:

1. Create a second UCCnetMessageReceive collaboration object.
2. Connect its FromAS2 port to an AS2 channel connector
3. Connect its ToRetail\_Processing port to a JTextConnector
4. Connect its ToRetail\_Response, ToMessage\_Store, and ToIdentifier\_Store ports to the PortConnector.

This second UCCnetMessageReceive collaboration object sends the item to the JTextConnector, which writes it to a file system. From the file system, the file can be printed by using any local print function.

---

### Mapping an item to the business review/approval process

Describes the start of the business review/approval process

### Description

In the context of the Product Information Management for Retailers solution, the business review/approval process begins when an ItemDispatcher collaboration object passes the Retail\_Item business object to the WebSphereMQWorkflowConnector over its To port. The WebSphereMQWorkflowConnector maps the Retail\_Item business object into a WebSphere MQ Workflow container by passing it through the Retail\_Item\_to\_MQWF\_Retail\_Item map. Examine this map in the Map Designer

tool to view how the Retail\_Item business object is mapped into the MQWF\_Retail\_Item application specific business object. At this point, the flow becomes asynchronous.

**Note:** The case of a business object's String attributes is normally not important. Product Information Management for Retailers solution collaboration objects always convert mixed-case Strings to lowercase characters by using the command `toLowerCase()` before testing their values against known values. An exception is that attributes that are used by Java to reference a business object remain in mixed-case characters. An example is an attribute name that is inserted in the multiple cardinality array of `Retail_Missing_Attributes` business objects in the `internals.customer_data_missing_attributes` attribute.

The `Retail_Item_to_MQWF_Retail_Item` map also invokes a specific WebSphere MQ Workflow process definition based on the command identified in the `internals.item_command` attribute of the `Retail_Item` business object. There are three WebSphere MQ Workflow process definitions in the Product Information Management for Retailers solution, which are located in the `Retail.fdl` file:

- `Retail_ItemCreate`
- `Retail_ItemUpdate`
- `Retail_ItemDelete`

These process definitions are determined by the relationship definitions contained in the `CMDTOWPN` file for the mapping of the `internals.item_command` attribute to `ProcessTemplateName`. They allow users to select a container attribute to be modified.

A customized solution might require a different set of WebSphere MQ Workflow processes. In this case, modify the process definitions by loading them into WebSphere MQ Workflow Buildtime. Alternatively, provide your own process definitions to match the item commands that are specified in the `Retail_Item_to_MQWF_Retail_Item` map. Customize the map's custom move code to enable different WebSphere MQ Workflow process definition routings. The custom move code includes examples of how to generate definition names by either using a relationship or by hard coding them. The name of the WebSphere MQ Queue Manager might have to be changed to match a particular implementation.

---

## Using WebSphere MQ Workflow containers

A WebSphere MQ Workflow container must contain the item data that is needed to make the business process decision.

### Purpose

It must also contain certain internal attributes from the `Retail_Item` business object so they can be returned to succeeding collaboration objects that require them. The following list includes those attributes that must be mapped into the WebSphere MQ Workflow container:

#### **internals.item\_status**

This attribute holds the item status value when there are no cascaded GLNs in the `internals.cascadedGlNs` child business object. The approver(s) responsible for approving items must set the value of this attribute to `Approved`, `Rejected`, `Accepted`, or `Review` through a customized

user interface with WebSphere MQ Workflow, so that the succeeding collaboration objects can determine the processing path for the item. If the status remains Review, the item is routed back to the ItemValidation collaboration object and then back into business review/approval processing.

#### **internals.cascadedGLNs**

This attribute is an N-cardinality child business object that holds the cascaded GLNs and the status for each GLN. When cascaded GLNs are present in the `internals.GLNs` child business object, the approvers responsible for approving items must set the value of the `internals.cascadedGLNs.item_status` attribute for each cascaded GLN to Approved, Rejected, Accepted, or Review through a customized user interface with WebSphere MQ Workflow, so that the succeeding collaboration objects can determine the processing path for the item. If the status remains Review, the item is routed back to the ItemValidation collaboration object and eventually back into business review/approval processing.

**Note:** If you are using DTD XML definitions, all GLNs, whether cascaded or not, are carried to the WebSphere MQ Workflow in this attribute.

#### **internals.item\_command**

This attribute holds the item command value.

#### **internals.correlationID**

This attribute holds the identifying key used to retrieve the item from the local item store. Even if a local item store is not used, the value for this attribute must be returned since it is used by the `UCCnetMessageReceive` and `UCCnetMessageSend` collaboration objects.

#### **internals.fromGLN**

This attribute holds the GLN of the supplier publishing the `Retail_Item`.

#### **internals.toGLN**

This attribute holds the top-level retailer GLN to which the item is being published.

#### **Other useful data to map**

Other useful data to map into the WebSphere MQ Workflow container includes the following attributes:

#### **internals.date\_processed**

This attribute holds the date that the item is processed by the approvers.

#### **internals.time\_processed**

This attribute holds the time that the item is processed by the approvers.

#### **internals.responder\_name**

This attribute holds the name of the approver or a list of approvers.

If the WebSphere MQ Workflow business process needs additional data from the `Retail_Item` business object that is not mapped into the container, a customized program that reads the local item store must be developed. For example, a collaboration template could be developed that invokes an `ItemStore` collaboration object to read the store. The custom collaboration object could pass the `Retail_Item` business object `internals.correlationID` attribute to the `ItemStore` collaboration object as the key to the item in the store. See “Persisting, retrieving, updating, or deleting an item to or from a local item store” on page 53.

---

## Returning data from the business review/approval process to an ItemCollector collaboration object

When the business review/approval process completes, the WebSphere MQ Workflow process sends the container with the updated status to the WebSphereMQWorkflowConnector.

### Purpose

At this point, the flow becomes synchronous again. The WebSphereMQWorkflowConnector maps the WebSphere MQ Workflow container back into a partial Retail\_Item business object by passing it through the MQWF\_Retail\_Item\_to\_Retail\_Item map and then invokes an ItemCollector collaboration object. Values for the following attributes must be mapped back into the Retail\_Item business object from the WebSphere MQ Workflow container:

- internals.item\_status
- internals.item\_command
- internals.correlationID
- internals.cascadedGlns[].gln
- internals.cascadedGlns[].item\_status

The data mapped back into the Retail\_Item from the WebSphere MQ Workflow container must also be matched with configuration property settings for the ItemCollector collaboration object, which determine which updated attribute values to copy back into a complete Retail\_Item business object. See “Merging static data by using the X\_COPY ATTRIBUTE configuration properties” on page 43.

---

## Chapter 7. Merging data into a complete item

Describes the operation of the an ItemCollector collaboration object, which builds a complete business object by merging partial business objects containing updated information into a complete copy of the business object retrieved from a local item store.

### Description

The Retail\_Item business object passed to an ItemCollector collaboration object might not be complete. The updated data contained in this incomplete item must be merged into the complete Retail\_Item business object that was saved in the local item store before the item was sent to business review/approval or missing data retrieval processing. The ItemCollector collaboration object retrieves the copy of the Retail\_Item that was stored by the ItemValidation collaboration object from the local item store. It retrieves the item by sending the business object and a Retrieve verb to its local\_store port to be passed to an ItemStore collaboration object, which actually retrieves the item and returns it to the ItemCollector collaboration object. See Persisting, retrieving, updating, or deleting an item to or from a local item store.

The ItemCollector collaboration object obtains the `internals.correlationID` value from the original Retail\_Item saved in the local item store and copies it to the Retail\_Item returned from the approval process. The value is copied into the `internals.originalCorrelationID` attribute of the Retail\_Item. This value can be used by the Message Manager collaborations to access a corresponding message store database entry.

The collaboration object checks if the original Retail\_Item retrieved from the item store database contains cascaded GLNs. It then directs processing, as follows:

- If the Retail\_Item does not contain cascaded GLNs, the collaboration object merges the new data received from the WebSphere MQ Workflow process into the Retail\_Item business object that was read from the item store. See “Merging static data by using the X\_COPY ATTRIBUTE configuration properties” on page 43 and “Merging missing data by using the MISSING\_DATA\_CHILD\_ATTRIBUTE configuration property” on page 44.

**Note:** If the business object had not had all required data present, causing the ItemValidation collaboration object to invoke a custom missing data retrieval process, it is at this point that this retrieval process would call an instance of an ItemCollector collaboration object to merge the retrieved data into the complete Retail\_Item business object.

The `internals.lastCascadedGLN` attribute of the merged Retail\_Item business object is set to true indicating there are no other cascaded GLN Retail\_Items to be processed and the Retail\_Item is routed to a Process\_Reviewed\_Item collaboration object via the ItemCollector collaboration object’s To port.

- If the Retail\_Item does contain cascaded GLNs, the collaboration object does the following:
  1. It loops through the GLNs, processing each one, as follows:
    - a. It retrieves the copy of the Retail\_Item that was stored by the ItemDispatcher collaboration object from the item store database by sending the business object and a Retrieve verb to its *local\_store* port to be

passed to an ItemStore collaboration object. The key used to access the item is the concatenation of the `internals.correlationID` attribute value of the original triggering business object and the `internals.cascadedGlns.gln` attribute value for the GLN being processed. The copy is returned to the ItemCollector collaboration object on its `local_store` port.

- b. The ItemCollector collaboration object merges the new data received from the WebSphere MQ Workflow process into the Retail\_Item business object retrieved from the item store. See “Merging static data by using the X\_COPY ATTRIBUTE configuration properties” on page 43 and “Merging missing data by using the MISSING\_DATA\_CHILD\_ATTRIBUTE configuration property” on page 44.

**Note:** If the business object had not had all required data present, causing the ItemValidation collaboration object to invoke a custom missing data retrieval process, it is at this point that this retrieval process would call an instance of an ItemCollector collaboration object to merge the retrieved data into the complete Retail\_Item business object.

- c. The ItemCollector collaboration object then handles the business object according to its status value, as follows:
  - If the status value of the `internals.cascadedGlns.item_status` attribute is either Approved or Rejected, the merged Retail\_Item business object is routed to a Process\_Reviewed\_Item collaboration object via the ItemCollector collaboration object’s To port. The ItemCollector collaboration object uses the original count of cascaded GLNs retrieved from the original Retail\_Item from the item store to determine if the Approved or Rejected Retail\_Item is the last item for the group of cascaded GLNs. If it is the last the `internals.lastCascadedGLN` attribute of the Retail\_Item is set to true. If it is not the last item the attribute is set to false.
  - If the status value of the `internals.cascadedGlns.item_status` attribute is Review or Accepted, the `internals.cascadedGlns` child business object is added to an array, as follows:
    - If the status is Review, it is added to an array of review cascaded GLNs.
    - If the status is Accepted, it is added to an array of accepted cascaded GLNs.

**Note:** If the cascaded GLN is not the first GLN in the respective array, the ItemCollector collaboration object deletes the copy of the Retail\_Item that was stored by the ItemDispatcher collaboration object from the item store database by sending the business object and a Delete verb to its `local_store` port to be passed to an ItemStore collaboration object, which performs the deletion. The key used to access the item is the concatenation of the `internals.correlationID` attribute value of the original triggering business object and the `internals.cascadedGlns.gln` attribute value of the newly created business object.

2. After all of the cascaded GLNs are processed, all the GLNs with a status of Review are sent as a group by copying the array of review cascaded GLNs into the `internals.cascadedGlns` attribute, to a Process\_Reviewed\_Item collaboration object via the ItemCollector collaboration object’s To port. Similarly, all GLNs with a status of Accepted are sent as a group by copying

the array of accepted cascaded GLNs into the `internals.cascadedGlns` attribute, to a `Process_Reviewed_Item` collaboration object via the `ItemCollector` collaboration object's `To` port.

3. The `ItemCollector` collaboration object calculates how many total cascaded GLNs have completed processing (that is, they have `Approved`, `Rejected`, or `Error` status). If all of the cascaded GLNs from the original message that was sent to the `ItemDispatcher` collaboration object have completed processing, it does the following:
  - a. Sets the `internals.lastCascadedGln` attribute of the `Retail_Item` to `true`.
  - b. Deletes the copy of the `Retail_Item` that was stored by the `ItemValidation` collaboration object from the item store database by sending the business object and a `Delete` verb to its `local_store` port to be passed to an `ItemStore` collaboration object, which performs the deletion. The key used to access the item is the `internals.correlationID` attribute value of the original triggering business object.

---

## Merging static data by using the `X_COPY ATTRIBUTE` configuration properties

An `ItemCollector` collaboration template can be configured with properties that indicate which attributes to copy from a triggering business object

### Description

An `ItemCollector` collaboration template can be configured with properties that indicate which attributes to copy from a triggering business object received on the `From` port into the complete item previously stored in the item store. These configuration properties are of the form `X_COPY_ATTRIBUTE` (where `X` is an integer, such as in `1_COPY_ATTRIBUTE`). Four properties with default values are supplied with the collaboration template:

- `1_COPY_ATTRIBUTE`
- `2_COPY_ATTRIBUTE`
- `3_COPY_ATTRIBUTE`
- `4_COPY_ATTRIBUTE`

Any number of configuration properties of the form `X_COPY_ATTRIBUTE` can be created to copy any number of attributes.

For each of the attributes identified in these properties, the collaboration object first verifies that the attribute exists in the `Retail_Item` business object and, if it does, copies the updated attribute value from the `Retail_Item` business object received on the `From` port to the `Retail_Item` retrieved from the local item store. If the attribute does not exist in the `Retail_Item` business object, the collaboration object generates an informational message in the log and continues processing.

When using an unmodified `Retail_Item` business object, at a minimum, set `1_COPY_ATTRIBUTE` equal to the value `internals.item_status`, so that the status of the item is copied. Remove any properties of the form `X_COPY_ATTRIBUTE` that are not used. A blank for the property value, or an invalid attribute name, cause a warning message to be logged by the collaboration object.

---

## Merging missing data by using the MISSING\_DATA\_CHILD\_ATTRIBUTE configuration property

An ItemCollector collaboration object checks if the attribute specified in its property contains a list of missing attributes.

### Description

Within a triggering Retail\_Item business object, an ItemCollector collaboration object checks if the attribute specified in its property MISSING\_DATA\_CHILD\_ATTRIBUTE (by default, the internals.customer\_data\_missing\_attributes child business object) contains a list of missing attributes.

**Note:** It is assumed that previous processing, such as that performed by an ItemValidation collaboration object, identified which attribute names were required and missing from the item and that previous processing (such as a custom collaboration object) collected the values for those missing attributes and set the values in the Retail\_Missing\_Attributes child business object of the Retail\_Item business object. See “Validating an item by requiring data for specific attributes” on page 22 and “Using a custom missing data retrieval process to collect data” on page 28.

Each Retail\_Missing\_Attributes business object contains two attributes. The first attribute contains the name of a Retail\_Item attribute that was determined during previous processing to be required and missing its data. The second attribute contains the value of the Retail\_Item attribute that was obtained through a custom missing data retrieval process prior to the ItemCollector collaboration object being invoked.

The ItemCollector collaboration object needs to reference each of the two elements of the Retail\_Missing\_Attributes child business object. This is accomplished by using two configuration properties, MISSING\_DATA\_NAME\_ATTRIBUTE and MISSING\_DATA\_VALUE\_ATTRIBUTE:

### MISSING\_DATA\_NAME\_ATTRIBUTE

This property holds the attribute name as defined in the Retail\_Missing\_Attributes child business object. By default, this value is attribute\_name. If this default value is changed, the change must be reflected in the value of the MISSING\_DATA\_NAME\_ATTRIBUTE as well.

### MISSING\_DATA\_VALUE\_ATTRIBUTE

This property holds the attribute value as defined in the Retail\_Missing\_Attributes child business object. By default, this value is attributeValue. If this default value is changed, the change must be reflected in the value of the MISSING\_DATA\_NAME\_ATTRIBUTE as well.

For each Retail\_Missing\_Attributes instance in the missing attribute array, the collaboration object first verifies that the attribute is a valid Retail\_Item attribute. If so, the attribute’s value is copied from the Retail\_Missing\_Attributes instance to its correct position in the Retail\_Item business object obtained from the local item store. If the attribute is not valid for the Retail\_Item, the collaboration object generates an informational message in the log and continues processing.

---

## Chapter 8. Processing an item after the business review/approval process completes

Details how a `Process_Reviewed_Item` collaboration object synchronizes an item to a back-end file system and calls a `UCCnetMessageSend` collaboration object to send a response to UCCnet. It also suggests ways of synchronizing an item to a customized back-end application other than a file system or to multiple back-end applications.

### Description

After the `ItemCollector` collaboration object merges data into a complete `Retail_Item` business object, it passes this `Retail_Item` to a `Process_Reviewed_Item` collaboration object. The `Process_Reviewed_Item` collaboration object receives this object on its `From` port. It then performs several tasks, as follows:

1. If the collaboration object's `DELETE_FROM_LOCAL_STORE` configuration property is set to true, it calls an `ItemStore` collaboration object to delete the item from the item store.
2. It examines the status of the item and directs processing, as follows:
  - If the item status is `Approved`, the collaboration object routes the `Retail_Item` business object to the `JTextConnector` via its `Sync` port. The `JTextConnector` writes the `Retail_Item` business object to a file system. If this is successful, the item status is changed to `Synchronised`; if not, the item status is changed to `Error`. The item is also sent to the `respond_to` port to be passed to a `UCCnetMessageSend` collaboration object. Alternatively, the `Retail_Item` can be sent to a single application other than the `JTextConnector` or to multiple back-end applications.
  - If the item status is `Rejected`, the collaboration object routes the `Retail_Item` to the `JTextConnector` via its `Sync` port. The `JTextConnector` writes the `Retail_Item` business object to a file system. If this is not successful, the item status is changed to `Error`. The item is then sent to the `respond_to` port to be passed to a `UCCnetMessageSend` collaboration object. See “Synchronizing an item to a back-end application other than a file system” on page 46 and “Synchronizing an item to multiple back-end applications” on page 46.
  - If the item status is `Accepted` or `Review`, the collaboration object routes the `Retail_Item` business object back to a `ItemValidation` collaboration object via its `reprocess` port. The `Process_Reviewed_Item` collaboration object then waits for a response. When the item is returned on the `reprocess` port from the `ItemValidation` collaboration object, the `Process_Reviewed_Item` collaboration object processes it, as follows:
    - If the status of the returned item is `Review` or `reprocess`, it indicates that the item was successfully processed by the `ItemValidation` collaboration object and sent to the WebSphere MQ Workflow business review/approval process by the `ItemDispatcher` collaboration object. If the original status for the item when it was received on the `From` port was `Accepted`, the item with `Accepted` status is sent to the `respond_to` port to be passed to a `UCCnetMessageSend` collaboration object. Otherwise, the item is not sent to the `respond_to` port. At this point, processing performed by the `Process_Reviewed_Item` collaboration object ends. When the WebSphere MQ Workflow process triggered by the `ItemDispatcher` collaboration

- object completes, the Retail\_Item will again be sent to a Process\_Reviewed\_Item collaboration object's From port.
- If the status of the returned item is Rejected or Error, the collaboration object sends the Retail\_Item to the respond\_to port to be passed to a UCCnetMessageSend collaboration object.
3. Optionally, the collaboration object calls an ItemStore collaboration object to rewrite the Retail\_Item to the local item store for back-up or future validation purposes. See "Persisting, retrieving, updating, or deleting an item to or from a local item store" on page 53.

---

## Synchronizing an item to a back-end application other than a file system

Describes synchronizing an item to a back-end application that is not a file system

### Description

In the context of the Product Information Management for Retailers solution, a Process\_Reviewed\_Item collaboration object's Sync port is connected to the JTextConnector, which writes the item to a file system. By setting the JTextConnector's BOPrefix property, the filename can be prefixed to match the requirements of any back-end application. Also, the Sync port can be attached to any other connector that supports a different back-end application, such as a legacy system. IBM WebSphere technology adapters can provide interfaces to different types of back-end systems such as databases or queue interfaces.

---

## Synchronizing an item to multiple back-end applications

Describes synchronizing to more than one back-end application.

### Description

Synchronize a Retail\_Item business object to more than one back-end application by doing one of the following:

- Modify the Process\_Reviewed\_Item collaboration template to include several Sync ports or write another custom collaboration template and attach a collaboration object based on it to a Process\_Reviewed\_Item collaboration object's Sync port. A collaboration object based on this custom collaboration template can pass the Retail\_Item business object to multiple output ports (i.e., each back-end application's connector).
- Connect a Process\_Reviewed\_Item collaboration object's Sync port to a collaboration object based on the ItemSync collaboration template. The Retail\_Item business object must be added to the list of supported business objects for a collaboration object based on this template. The advantage of using an ItemSync collaboration object is that it provides the base capabilities to do the following:
  - Convert a Create verb to an Update verb if the item currently exists in the back-end application.
  - Convert an Update verb to a Create verb if the item does not exist in the back-end application (a Process\_Reviewed\_Item collaboration object provides only the Create verb).
  - Filter the item based on its contents and not synchronize it to the back-end application.

---

## Chapter 9. Sending responses to UCCnet

Explains how a `UCCnetMessageSend` collaboration object sends response messages to UCCnet based on an item's command type, status value, and the values of particular collaboration object properties.

### Description

Response messages must be returned to UCCnet for each `NEW_ITEM`, `DATA_CHANGE`, or `NEW_ITEM` with reload request. In the Product Information Management for Retailers solution, a `Process_Reviewed_Item` collaboration object is connected through its `respond_to` port to a `UCCnetMessageSend` collaboration object, which builds and sends appropriate responses to UCCnet. Response messages must be returned to UCCnet for each `NEW_ITEM`, `DATA_CHANGE`, or `NEW_ITEM` with reload request. `Process_Reviewed_Item` collaboration objects pass `Retail_Item` business objects to `UCCnetMessageSend` collaboration objects when they have been assigned `Synchronised`, `Rejected`, `Accepted`, or `Error` status. `UCCnetMessageReceive` collaboration objects may also pass `Retail_Item` business objects with `Review` or `Error` status to `UCCnetMessageSend` collaboration objects for the purpose of sending a response to UCCnet.

When a triggering `Retail_Item` business object is received, a `UCCnetMessageSend` collaboration object first retrieves the layer information from the local message store by converting the `Retail_Item` to a `UCCnetGBO_storable` business object and passing it to its `ToMessage_Store` port. This port is bound to the appropriate persistence mechanism, such as a `MessageStore` collaboration object, which performs the retrieval. The `UCCnetMessageSend` collaboration object uses the `Retail_Item` `internals.originalCorrelationID` attribute, if it is populated, to access the proper entry in the message store. If this attribute does not contain a value, the collaboration object uses the `Retail_Item` `internals.correlationID` attribute value.

It then extracts the Catalogue Item Notification command and handles the object according to its original command type, its status value, and the values of certain properties, as follows:

- If the original command to the demand-side trading partner was a `DE_LIST`, `WITHDRAW`, or `CORRECTION`, the collaboration object stops processing.
- If the original command to the demand-side trading partner was a `NEW_ITEM`, `DATA_CHANGE`, or `NEW_ITEM` with reload, the `UCCnetMessageSend` collaboration object does the following:
  1. Checks the value of the `internals.item_status` attribute of the `Retail_Item`:
    - If the status of the `Retail_Item` is `Synchronised`, the collaboration object builds a Catalogue Item Confirmation message with a state of `Synchronised`.
    - If the status is `Rejected` and the collaboration object's `SEND_REJECT` property is set to true, it builds a Catalogue Item Confirmation message with a state of `Rejected`.
    - If the status is `Review` and the collaboration object's `SEND_REVIEW` property is set to true, it builds a Catalogue Item Confirmation message with a state of `Review`.

**Note:** A `UCCnetMessageReceive` collaboration object can initiate sending a Catalogue Item Confirmation message with a state of Review when an item is first received and sent to the business review/approval process. Since this process can be long-running, it might be necessary to send the Catalogue Item Confirmation message with a state of Review back to originator of the request. Normally, UCCnet does not want Catalogue Item Confirmation messages with a state of Review to be sent, so it is recommended that the `SEND_REVIEW` property be set to false.

- If the status is Accepted and the collaboration object's `SEND_ACCEPT` property is set to true, it builds a Catalogue Item Confirmation message with a state of Accepted.
2. Composes a `UCCnetGBO_envelope` business object by first converting the `Retail_Item` and `UCCnetGBO_storable` business objects into a `UCCnetGBO_RI_S` business object and then passing this object through the map specified in its `TOAS2_RESPONSE_MAP` configuration property. The resulting `UCCnetGBO_envelope` business object contains all of the information needed for the UCCnet Catalogue Item Confirmation message.
  3. Passes the `UCCnetGBO_envelope` business object to the AS2 channel connector on its `ToAS2_Response` port. In the connector controller portion of the connector, it is converted to an application specific business object of the form:

`UCCnetxxx_envelope` if iSoft connectivity is used.

`UCCnetTPIxxx_envelope` if TPI connectivity is used.

`UCCnetJMSxxx_envelope` if WebSphere Business Connect is used with JMS.

The `UCCnetGBO_envelope` business object is converted by passing through:

`UCCnetGBO_envelope_to_UCCnetxxx_envelope` map if iSoft connectivity is used

`UCCnetGBO_envelope_to_UCCnetTPIxxx_envelope` map if TPI connectivity is used

`UCCnetGBO_envelope_to_UCCnetJMSxxx_envelope` map if WebSphere Business Connect is used with JMS

The DTD forms of these maps convert the outgoing `UCCnetGBO_envelope` GBO containing an XSD-based Catalogue Item Confirmation command into an ASBO containing a DTD-based Authorization command.

**Note:** The variable `xxx` specifies the XML definition type used (DTD or XSD).

4. If the status of the item is Synchronized, Rejected, or Error the collaboration object checks the `Retail_Item` `internals.lastCascadedGLN` attribute. If the attribute is not false it deletes the entry from the message store corresponding to the `Retail_Item` `internals.originalCorrelationID` value by converting the business object to a `UCCnetGBO_storable` business object and passing this object to its `ToMessage_Store` port. If the status of the `Retail_Item` is Accepted or Review the message store entry is not deleted. This port is bound to the appropriate persistence mechanism, such as a `MessageStore` collaboration object, which performs the actual deletion.
- Regardless of the original command type, if the status of the item is Error, the `UCCnetMessageSend` collaboration object does the following:
    - If the value of its `FILTER_DUPLICATE` configuration property is true, it maintains the identifier store by converting the business object to a `UCCnetGBO_identifier` business object and calling an `IdentifierStore`

collaboration object to remove the entry from the identifier store. The key attributes for DTD processing are gtin, version, and topic. The key attributes for XSD processing are gtin, topic, dataRecipientGLN, dataSourceGLN, targetMarket, and uniqueCreatorID. See “Filtering to eliminate processing of duplicate items” on page 18 and “Persisting or deleting an item to or from a local identifier store” on page 19.

- Checks the Retail\_Item internal's lastCascadedGLN attribute. If the attribute is not false it calls a MessageStore collaboration object to delete the entry from the message store. See “Persisting, retrieving, or deleting an item to or from a local message store” on page 52.
- It stops further processing of the Catalogue Item Confirmation command so that no response is returned to UCCnet.



---

## Chapter 10. Using identifier, message, and item stores

Identifies how and why various collaboration objects persist, retrieve, update, and delete items to and from identifier, message, and item stores.

### Local stores

Three local stores, or database tables, are used in the Product Information Management for Retailers solution. The stage of item processing determines when these stores are accessed, by which collaboration objects, and which actions (Create, Retrieve, Delete, Update) are performed on them.

### Identifier store

The identifier store stores unique identifying information for each item, which is used by a `UCCnetMessageReceive` collaboration object to prevent duplicate Catalogue Item Notifications with `NEW_ITEM`, `DATA_CHANGE`, `WITHDRAW`, or `DE_LIST` commands from being processed. This collaboration object triggers an `IdentifierStore` collaboration object, which performs the actual Create action on the store. When error conditions are encountered, the `UCCnetMessageSend` collaboration object can also trigger an `IdentifierStore` collaboration object to delete the item from the identifier store.

### Message store

The message store holds item information that is used by `UCCnetMessageReceive` and `UCCnetMessageSend` collaboration objects to build appropriate messages to be sent back to UCCnet. These collaboration objects trigger a `MessageStore` collaboration object, which performs the actual Create, Retrieve, and Delete actions on the store.

### Item store

The item store saves a complete version of the `Retail_Item` business object. A complete version of the item might have to be stored and later merged with updated information for some of its attributes for the following reasons:

- Processes to be performed on the item are long-running, disjoint, and asynchronous, or cannot persist the entire `Retail_Item` business object.
- A complete version of the item is needed for validation or back-up.
- Complete information might be needed by business review/approval processes.

`ItemValidation`, `ItemCollector`, `ItemDispatcher`, and `Process_Reviewed_Item` collaboration objects trigger an `ItemStore` collaboration object, which performs the actual Create, Retrieve, Update, and Delete actions on the store.

---

## Persisting or deleting an item to or from a local identifier store

Various collaboration objects used in the Product Information Management for Retailers solution can initiate the storage or deletion of a business object to or from an identifier store.

## Description

Various collaboration objects used in the Product Information Management for Retailers solution can initiate the storage or deletion of a business object to or from an identifier store, as follows:

- For a Catalogue Item Notification with a NEW\_ITEM, DATA\_CHANGE, WITHDRAW, or DE\_LIST command, a UCCnetMessageReceive collaboration object initiates persisting the UCCnetGBO\_envelope business object by sending it with a Create verb to its ToIdentifier\_Store port.
- When error conditions are encountered, a UCCnetMessageSend collaboration object initiates deleting the UCCnetGBO\_envelope business object by sending it with a Delete verb to its ToIdentifier\_Store port.

In either case, before sending the UCCnetGBO\_envelope business object to the port, the collaboration object first converts it to a UCCnetGBO\_identifier business object by passing it through the map specified in its TOIDENTIFIER\_STORE\_MAP property. The ToIdentifier\_Store port can then be bound to a persistence mechanism. In the context of the Product Information Management for Retailers solution, this mechanism is an IdentifierStore collaboration object.

The IdentifierStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML (which are detailed per command in the IdentifierStore collaboration template), stores or deletes the identifier. The key to this record in the identifier store is made up of the attributes gtin, version, and topic of the UCCnetGBO\_identifier business object for DTD processing, and the attributes gtin, topic, dataRecipientGLN, dataSourceGLN, targetMarket, and uniqueCreatorID of the UCCnetGBO\_identifier business object for XSD processing. The UCCnetMessageReceive collaboration object can also check if a duplicate item already exists in the identifier store to prevent processing of duplicate items. See “Filtering to eliminate processing of duplicate items” on page 18 for more information.

---

## Persisting, retrieving, or deleting an item to or from a local message store

Various collaboration objects used in the Product Information Management for Retailers solution can initiate the storage, retrieval, or deletion of a business object to or from a message store.

### Description

- A UCCnetMessageReceive collaboration object initiates persisting a business object for use in a return message by sending it with a Create verb to its ToMessage\_Store port.
- A UCCnetMessageSend collaboration object initiates retrieving or deleting a business object by passing it with either a Retrieve or Delete verb to a MessageStore collaboration object through its ToMessage\_Store port.

In each case, before persisting, retrieving, or deleting the business object, the collaboration object first converts it to a UCCnetGBO\_storable business object. The UCCnetGBO\_storable business object is a combination of one instance of an Catalogue Item Notification, together with the message header and routing information for the worklist message in which the item was contained. The outgoing port on each collaboration object can then be bound to a persistence

mechanism. In the context of the Product Information Management for Retailers solution, this mechanism is a MessageStore collaboration object.

The MessageStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML (which are detailed per command in MessageStore collaboration template), stores, retrieves, or deletes the message. When it retrieves a message, it returns it to the calling collaboration object. The key to this record in the message store is saved in the correlationID attribute of the UCCnetGBO\_storable business object.

### Generating data base keys

A key is guaranteed to be unique for each item and for each type of command. The key for the item store is saved in the Retail\_Item business object internals.correlationID attribute. Do not modify the value of this attribute.

Entries in the item store and message store can possess identical keys since the stores are different tables within the database.

---

## Persisting, retrieving, updating, or deleting an item to or from a local item store

Various collaboration objects used in the Product Information Management for Retailers solution can initiate the storage, retrieval, updating, or deletion of a business object to or from an item store.

### Description

- ItemValidation, ItemDispatcher, and Process\_Reviewed\_Item collaboration objects initiate persisting a business object. An ItemValidation collaboration object initiates storing the item prior to its being sent to a process for obtaining missing information or for business review/approval. An ItemDispatcher collaboration object initiates storing an item with cascaded GLNs. A Process\_Reviewed\_Item collaboration object initiates storing the item after it is synchronized to a back-end system, so the item is available to be used later for validation or back-up.

To enable persisting the item in the local item store, set an ItemValidation or Process\_Reviewed\_Item collaboration object's configuration property RETAIN\_ITEM\_IN\_LOCAL\_STORE to true; an ItemDispatcher collaboration object persists by default. ItemValidation and ItemDispatcher collaboration objects then send the business object with a Create verb to their LocalItemStore ports; the ItemDispatcher collaboration object to its LocalItemStore port; and the Process\_Reviewed\_Item collaboration object, to its local\_store port.

- An ItemCollector collaboration object initiates retrieving and deleting a Retail\_Item business object. The ItemCollector collaboration object sends the item with a Retrieve or Delete verb to its local\_store port.
- An ItemDispatcher collaboration object initiates updating a Retail\_Item business object. The ItemDispatcher collaboration object sends the item with an Update verb to its LocalItemStore port.
- A Process\_Reviewed\_Item collaboration object initiates deleting a business object. To enable deletion of the business object, set a Process\_Reviewed\_Item collaboration object's configuration property DELETE\_FROM\_LOCAL\_STORE to true. It then passes the item with a Delete verb to its local\_store port.

The ItemValidation and ItemDispatcher collaboration objects' LocalItemStore ports, and the ItemCollector and Process\_Reviewed\_Item collaboration objects' local\_store ports, are all bound to a persistence mechanism. In the context of the Product Information Management for Retailers solution, this mechanism is an ItemStore collaboration object.

The ItemStore collaboration object receives the business object on its From port and, through a series of interactions with the IBM WebSphere Business Integration Data Handler for XML (which are detailed per command in ItemStore collaboration template), stores, retrieves, updates, or deletes the item. When the collaboration object retrieves an item, it returns it to the calling collaboration object. The key to this record in the item store is saved in the internals.correlationID attribute of the Retail\_Item business object.

**Note:** If the item has not been stored by another collaboration object and therefore does not have to be deleted, set the Process\_Reviewed\_Item collaboration object's property DELETE\_FROM\_LOCAL\_STORE to false.

---

## Generating data base keys

A UCCnetMessageReceive collaboration object generates keys to items in each of the stores. A key is guaranteed to be unique for each item and for each type of command. The key for the item store is saved in the Retail\_Item business object internals.correlationID attribute. Do not modify the value of this attribute.

### Generating data base keys

Data base table	Key
item store	<ul style="list-style-type: none"> <li>For systems with cascaded GLNs: messageHeader.messageIdentifier + notification.sequenceId + internals.cascadedGlNs.gln</li> <li>For systems without cascaded GLNs: messageHeader.messageIdentifier + notification.sequenceId</li> </ul>
message store	<ul style="list-style-type: none"> <li>For systems with cascaded GLNs: messageHeader.messageIdentifier + notification.sequenceId + internals.cascadedGlNs.gln</li> <li>For systems without cascaded GLNs: messageHeader.messageIdentifier + notification.sequenceId</li> </ul>
identifier store	<ul style="list-style-type: none"> <li>For systems supporting XSD XML definition: gtin, topic, dataRecipientGLN, dataSourceGLN, targetMarket, uniqueCreatorID attributes of UCCnetGBO_identifier business object</li> <li>For systems supporting DTD XML definition: gtin, version, topic attributes of UCCnetGBO_identifier business object</li> </ul>

Entries in the item store and message store can possess identical keys because the stores are different tables within the database.

---

## Chapter 11. Controlling e-mail

Details how various collaboration objects enable a Role\_Email collaboration object to alert users of item status or if errors occur during processing. It also describes how to specify message text, subjects, and recipients in external files to eliminate updating individual collaboration objects each time one of these variables changes. Specifying changing individual or multiple message recipients and how to use substitution variables in message and subject text is also covered.

### Related topics

ItemValidation, ItemCollector, ItemDispatcher, and Process\_Reviewed\_Item collaboration objects can be configured to initiate sending e-mail to alert recipients of item status or when processing errors occur. These collaboration objects link to a Role\_Email collaboration object, which actually controls sending the e-mail.

The Role\_Email collaboration object allows the contents of the Retail\_Item attributes that specify e-mail message text, subject text, and recipients to contain the names of files. These files contain the actual e-mail message text, subject text, and addresses, and can be easily modified without modifying the using collaboration objects. This feature permits messages, subjects, and recipients to be shared among multiple collaboration objects. Also, more than one recipient can be specified to receive e-mail through use of a comma-delimited list. Plus, e-mail message and subject text can be constants that contain variables. The Role\_Email collaboration object substitutes data from the processing state or business object into these variables dynamically.

---

## Alerting email recipients of item status or processing errors

ItemValidation, ItemCollector, ItemDispatcher, and Process\_Reviewed\_Item collaboration objects can initiate sending e-mail to alert recipients of item status or when processing errors occur.

### Description

You can configure the following actions:

- Alerting of Approved item status - Process\_Reviewed\_Item collaboration objects only
- Alerting of Accepted item status - Process\_Reviewed\_Item collaboration objects only
- Alerting of Rejected item status - ItemValidation and Process\_Reviewed\_Item collaboration objects only
- Alerting of processing errors - ItemValidation, ItemCollector, ItemDispatcher, and Process\_Reviewed\_Item collaboration objects

Common configuration properties control whether e-mail is sent and delineate the contents of the message text, message subject, and the mail recipients. These collaboration objects link to a Role\_Email collaboration object, which actually controls sending the e-mail through use of the sendEmail API. This collaboration object formulates the sendEmail API parameters from the triggering business object (Retail\_Item in the Product Information Management for Retailers solution) passed to it from the various collaboration objects.

## Alerting of Approved item status

Properties that can be configured to enable e-mail to be sent if an item contains a status of Approved.

### Overview

The collaboration object sends the business object to its *mail* port and the Role\_Email collaboration object receives it on its *From* port. The Role\_Email collaboration object then formulates the sendEmail API parameters from the values of the EMAIL\_ROLE\_ATTRIBUTE, EMAIL\_MSG\_ATTRIBUTE, and EMAIL\_SUBJECT\_ATTRIBUTE properties passed to it.

### SEND\_MAIL\_ON\_APPROVAL

This property controls whether the Retail\_Item is sent to the port connected to the Role\_Email collaboration object. In essence, its value of true or false controls whether e-mail is sent. This property must be configured by the user.

### APPROVED\_EMAIL\_ROLE

This property specifies the Retail\_Item attribute containing the recipients that are to receive the message. It must be configured by the user. If this property and the SEND\_MAIL\_ON\_APPROVAL property exist, and the Retail\_Item has a status of Approved, the value of APPROVED\_EMAIL\_ROLE is stored in the Retail\_Item attribute specified by the Process\_Reviewed\_Item collaboration object's EMAIL\_ROLE\_ATTRIBUTE property. By default, this Retail\_Item attribute is internals.message\_recipient\_role. To successfully use the Role\_Email collaboration object as the notifying collaboration object, the Retail\_Item attribute specified in the Process\_Reviewed\_Item collaboration object's EMAIL\_ROLE\_ATTRIBUTE property must match the Retail\_Item attribute specified in the Role\_Email collaboration object's MSG\_RECIPIENT\_ATTRIBUTE property. This Retail\_Item attribute can contain either the actual recipient or list of recipients or a filename containing this value. See "Specifying message text, subjects, and recipients in external files" on page 62 for more information on how to specify e-mail recipients by using filenames and the benefits of specifying e-mail recipients in this way.

**Note:** If the APPROVED\_EMAIL\_ROLE property does not exist, a value of unknown is set in the Retail\_Item attribute specified in the collaboration object's EMAIL\_ROLE\_ATTRIBUTE.

### APPROVED\_EMAIL\_MSG

This property specifies the Retail\_Item attribute containing the appropriate message text to be sent. If the SEND\_MAIL\_ON\_APPROVAL and APPROVED\_EMAIL\_ROLE properties exist, and the Retail\_Item has a status of Approved, the value of APPROVED\_EMAIL\_MSG is stored in the Retail\_Item attribute specified by the Process\_Reviewed\_Item collaboration object's EMAIL\_MSG\_ATTRIBUTE property. By default, this Retail\_Item attribute is internals.message\_text. To successfully use the Role\_Email collaboration object as the notifying collaboration object, the Retail\_Item attribute specified in the Process\_Reviewed\_Item collaboration object's EMAIL\_MSG\_ATTRIBUTE property must match the Retail\_Item attribute specified in the Role\_Email collaboration object's MSG\_TEXT\_ATTRIBUTE property. This Retail\_Item attribute can contain either the actual message text or a filename containing the message text. See "Specifying message text, subjects, and recipients in external files" on page 62.

## APPROVED\_EMAIL\_SUBJECT

This property specifies the `Retail_Item` attribute containing the appropriate message subject. If the `SEND_MAIL_ON_APPROVAL` and `APPROVED_EMAIL_ROLE` properties exist, and the `Retail_Item` has a status of `Approved`, the value of `APPROVED_EMAIL_SUBJECT` is stored in the `Retail_Item` attribute specified by the `Process_Reviewed_Item` collaboration object's `EMAIL_SUBJECT_ATTRIBUTE` property. By default, this `Retail_Item` attribute is `internals.message_subject`. To successfully use the `Role_Email` collaboration object as the notifying collaboration object, the `Retail_Item` attribute specified in the `Process_Reviewed_Item` collaboration object's `EMAIL_SUBJECT_ATTRIBUTE` property must match the `Retail_Item` attribute specified in the `Role_Email` collaboration object's `MSG_SUBJECT_ATTRIBUTE` property. This `Retail_Item` attribute can contain either the actual subject text or a filename containing the subject text. See "Specifying message text, subjects, and recipients in external files" on page 62.

## Alerting of Accepted item status

Properties that can be configured to enable email to be sent if an item contains a status of `Accepted`

### Overview

The collaboration object sends the business object to its *mail* port and the `Role_Email` collaboration object receives it on its *From* port. The `Role_Email` collaboration object then formulates the `sendEmail` API parameters from the values of the `EMAIL_ROLE_ATTRIBUTE`, `EMAIL_MSG_ATTRIBUTE`, and `EMAIL_SUBJECT_ATTRIBUTE` properties passed to it.

A `Process_Reviewed_Item` collaboration object contains the following properties that can be configured to enable email to be sent if an item contains a status of `Accepted`.

## SEND\_MAIL\_ON\_ACCEPTED

This property controls whether the `Retail_Item` is sent to the port connected to the `Role_Email` collaboration object. In essence, its value of `true` or `false` controls whether email is sent. This property must be configured by the user.

## ACCEPTED\_EMAIL\_ROLE

This property specifies the `Retail_Item` attribute containing the recipients that are to receive the message. It must be configured by the user. If this property and the `SEND_MAIL_ON_ACCEPTED` property exist, and the `Retail_Item` has a status of `Accepted`, the value of `ACCEPTED_EMAIL_ROLE` is stored in the `Retail_Item` attribute specified by the `Process_Reviewed_Item` collaboration object's `EMAIL_ROLE_ATTRIBUTE` property. By default, this `Retail_Item` attribute is `internals.message_recipient_role`. To successfully use the `Role_Email` collaboration object as the notifying collaboration object, the `Retail_Item` attribute specified in the `Process_Reviewed_Item` collaboration object's `EMAIL_ROLE_ATTRIBUTE` property must match the `Retail_Item` attribute specified in the `Role_Email` collaboration object's `MSG_RECIPIENT_ATTRIBUTE` property. This `Retail_Item` attribute can contain either the actual recipient or list of recipients or a filename containing this value. See "Specifying message text, subjects, and recipients in external files" on page 62.

**Note:** If the `ACCEPTED_EMAIL_ROLE` property does not exist, a value of unknown is set in the `Retail_Item` attribute specified in the collaboration object's `EMAIL_ROLE_ATTRIBUTE`.

### **ACCEPTED\_EMAIL\_MSG**

This property specifies the `Retail_Item` attribute containing the appropriate message text to be sent. If the `SEND_MAIL_ON_ACCEPTED` and `ACCEPTED_EMAIL_ROLE` properties exist, and the `Retail_Item` has a status of Accepted, the value of `ACCEPTED_EMAIL_MSG` is stored in the `Retail_Item` attribute specified by the `Process_Reviewed_Item` collaboration object's `EMAIL_MSG_ATTRIBUTE` property. By default, this `Retail_Item` attribute is `internals.message_text`. To successfully use the `Role_Email` collaboration object as the notifying collaboration object, the `Retail_Item` attribute specified in the `Process_Reviewed_Item` collaboration object's `EMAIL_MSG_ATTRIBUTE` property must match the `Retail_Item` attribute specified in the `Role_Email` collaboration object's `MSG_TEXT_ATTRIBUTE` property. This `Retail_Item` attribute can contain either the actual message text or a filename containing the message text. See "Specifying message text, subjects, and recipients in external files" on page 62.

### **ACCEPTED\_EMAIL\_SUBJECT**

This property specifies the `Retail_Item` attribute containing the appropriate message subject. If the `SEND_MAIL_ON_ACCEPTED` and `ACCEPTED_EMAIL_ROLE` properties exist, and the `Retail_Item` has a status of Accepted, the value of `ACCEPTED_EMAIL_SUBJECT` is stored in the `Retail_Item` attribute specified by the `Process_Reviewed_Item` collaboration object's `EMAIL_SUBJECT_ATTRIBUTE` property. By default, this `Retail_Item` attribute is `internals.message_subject`. To successfully use the `Role_Email` collaboration object as the notifying collaboration object, the `Retail_Item` attribute specified in the `Process_Reviewed_Item` collaboration object's `EMAIL_SUBJECT_ATTRIBUTE` property must match the `Retail_Item` attribute specified in the `Role_Email` collaboration object's `MSG_SUBJECT_ATTRIBUTE` property. This `Retail_Item` attribute can contain either the actual subject text or a filename containing the subject text. See "Specifying message text, subjects, and recipients in external files" on page 62.

## **Alerting of Rejected item status**

Properties that can be configured to enable e-mail to be sent if an item contains a status of Rejected.

### **Overview**

The `ItemValidation` collaboration object sends the object to its Notify port; the `Process_Reviewed_Item` collaboration object, to its mail port. The `Role_Email` collaboration object receives it on its From port and then formulates the `sendEmail` API parameters from the values of the `EMAIL_ROLE_ATTRIBUTE`, `EMAIL_MSG_ATTRIBUTE`, and `EMAIL_SUBJECT_ATTRIBUTE` properties passed to it.

`ItemValidation` and `Process_Reviewed_Item` collaboration objects contain the following properties that can be configured to enable e-mail to be sent if an item contains a status of Rejected

## SEND\_MAIL\_ON\_REJECTION

This property controls whether the Retail\_Item is sent to the port connected to the Role\_Email collaboration object. In essence, its value of true or false controls whether e-mail is sent. This property must be configured by the user.

## REJECT\_EMAIL\_ROLE

This property specifies the Retail\_Item attribute containing the recipients that are to receive the message. It must be configured by the user. If this property and the SEND\_MAIL\_ON\_REJECTION property exist (and, in the ItemValidation collaboration object, are not BLANK), and the Retail\_Item has a status of Rejected, the value of REJECT\_EMAIL\_ROLE is stored in the Retail\_Item attribute specified by the ItemValidation or Process\_Reviewed\_Item collaboration object's EMAIL\_ROLE\_ATTRIBUTE property. By default, this Retail\_Item attribute is internal.message\_recipient\_role. To successfully use the Role\_Email collaboration object as the notifying collaboration object, the Retail\_Item attribute specified in the ItemValidation or Process\_Reviewed\_Item collaboration object's EMAIL\_ROLE\_ATTRIBUTE property must match the Retail\_Item attribute specified in the Role\_Email collaboration object's MSG\_RECIPIENT\_ATTRIBUTE property. This Retail\_Item attribute can contain either the actual recipient or list of recipients or a filename containing this value. See "Specifying message text, subjects, and recipients in external files" on page 62.

**Note:** In the Process\_Reviewed\_Item collaboration object, if the REJECT\_EMAIL\_ROLE property does not exist, a value of unknown is set in the Retail\_Item attribute specified by the EMAIL\_ROLE\_ATTRIBUTE property. In the ItemValidation collaboration object, if the REJECT\_EMAIL\_ROLE property exists but is BLANK, no notification is executed (no default mail recipient exists).

## REJECT\_EMAIL\_MSG

This property specifies the Retail\_Item attribute containing the appropriate message text to be sent. If the SEND\_MAIL\_ON\_REJECTION and REJECT\_EMAIL\_ROLE properties exist (and, in the ItemValidation collaboration object, are not BLANK), and the Retail\_Item has a status of Rejected, the value of REJECT\_EMAIL\_MSG is stored in the Retail\_Item attribute specified by the ItemValidation or Process\_Reviewed\_Item collaboration object's EMAIL\_MSG\_ATTRIBUTE property. By default, this Retail\_Item attribute is internal.message\_text. To successfully use the Role\_Email collaboration object as the notifying collaboration object, the Retail\_Item attribute specified in the ItemValidation or Process\_Reviewed\_Item collaboration object's EMAIL\_MSG\_ATTRIBUTE property must match the Retail\_Item attribute specified in the Role\_Email collaboration object's MSG\_TEXT\_ATTRIBUTE property. This Retail\_Item attribute can contain either the actual message text or a filename containing the message text. See "Specifying message text, subjects, and recipients in external files" on page 62.

**Note:** In the ItemValidation collaboration object, if the REJECT\_EMAIL\_MSG property exists but is BLANK, a default value is placed in the Retail\_Item attribute specified by the EMAIL\_MSG\_ATTRIBUTE property.

## REJECT\_EMAIL\_SUBJECT

This property specifies the Retail\_Item attribute containing the appropriate message subject. If the SEND\_MAIL\_ON\_REJECTION and REJECT\_EMAIL\_ROLE properties exist (and, in the ItemValidation collaboration object, are not BLANK), and the Retail\_Item has a status of Rejected, the value of REJECT\_EMAIL\_SUBJECT is stored in the Retail\_Item attribute specified by the ItemValidation or Process\_Reviewed\_Item collaboration object's EMAIL\_SUBJECT\_ATTRIBUTE property. By default, this Retail\_Item attribute is internal.message\_subject. To successfully use the Role\_Email collaboration object as the notifying collaboration object, the Retail\_Item attribute specified in the ItemValidation or Process\_Reviewed\_Item collaboration object's EMAIL\_SUBJECT\_ATTRIBUTE property must match the Retail\_Item attribute specified in the Role\_Email collaboration object's MSG\_SUBJECT\_ATTRIBUTE property. This Retail\_Item attribute can contain either the actual subject text or a filename containing the subject text. See "Specifying message text, subjects, and recipients in external files" on page 62.

**Note:** In the ItemValidation collaboration object, if the REJECT\_EMAIL\_SUBJECT property exists but is BLANK, a default value is placed in the Retail\_Item attribute specified by the EMAIL\_SUBJECT\_ATTRIBUTE property.

## Alerting of processing errors

Properties that can be configured to enable email to be sent if errors are detected during processing.

### Overview

The ItemValidation and ItemDispatcher collaboration objects send the object to their *Notify* ports; the ItemCollector collaboration object, to its *email* port; the Process\_Reviewed\_Item collaboration object, to its *mail* port. The Role\_Email collaboration object receives it on its *From* port and then formulates the sendEmail API parameters from the values of the EMAIL\_ROLE\_ATTRIBUTE, EMAIL\_MSG\_ATTRIBUTE, and EMAIL\_SUBJECT\_ATTRIBUTE properties passed to it.

ItemValidation, ItemCollector, ItemDispatcher, and Process\_Reviewed\_Item collaboration objects contain the following properties that can be configured to enable email to be sent if errors are detected during processing.

### SEND\_MAIL\_ON\_ERROR

This property controls whether the Retail\_Item is sent to the port connected to the Role\_Email collaboration object. In essence, its value of true or false controls whether email is sent. This property must be configured by the user.

### ERROR\_EMAIL\_ROLE

This property specifies the Retail\_Item attribute containing the recipients that are to receive the message. It must be configured by the user. If an error occurs and this property and the SEND\_MAIL\_ON\_ERROR property exist (and, in the ItemValidation collaboration object, are not BLANK), the value of ERROR\_EMAIL\_ROLE is stored in the Retail\_Item attribute specified by the ItemValidation, ItemCollector, ItemDispatcher, or Process\_Reviewed\_Item collaboration object's EMAIL\_ROLE\_ATTRIBUTE property. By default, this

Retail\_Item attribute is `internals.message_recipient_role`. To successfully use the Role\_Email collaboration object as the notifying collaboration object, the Retail\_Item attribute specified in the ItemValidation, ItemCollector, ItemDispatcher, or Process\_Reviewed\_Item collaboration object's EMAIL\_ROLE\_ATTRIBUTE property must match the Retail\_Item attribute specified in the Role\_Email collaboration object's MSG\_RECIPIENT\_ATTRIBUTE property. This Retail\_Item attribute can contain either the actual recipient or list of recipients or a filename containing this value. See "Specifying message text, subjects, and recipients in external files" on page 62.

**Note:** In the Process\_Reviewed\_Item collaboration object, if the ERROR\_EMAIL\_ROLE property does not exist, a value of unknown is set in the Retail\_Item attribute specified by the EMAIL\_ROLE\_ATTRIBUTE property. In the ItemValidation collaboration object, if the ERROR\_EMAIL\_ROLE property exists but is BLANK, no notification is executed (no default mail recipient exists).

### E-mail error properties

The following properties

- ERROR\_EMAIL\_MSG (ItemValidation, ItemDispatcher and Process\_Reviewed\_Item collaboration objects only)
- ERROR\_RETRIEVE\_EMAIL\_MSG (ItemCollector collaboration object only)
- ERROR\_SEND\_EMAIL\_MSG (ItemCollector collaboration object only)

specify the Retail\_Item attribute containing the appropriate message text to be sent. If an error occurs and the SEND\_MAIL\_ON\_ERROR and ERROR\_EMAIL\_ROLE properties exist (and, in the ItemValidation collaboration object, are not BLANK), the value of ERROR\_EMAIL\_MSG, ERROR\_RETRIEVE\_EMAIL\_MSG, or ERROR\_SEND\_EMAIL\_MSG is stored in the Retail\_Item attribute specified by the ItemValidation, ItemCollector, ItemDispatcher, or Process\_Reviewed\_Item collaboration object's EMAIL\_MSG\_ATTRIBUTE property. By default, this Retail\_Item attribute is `internals.message_text`. To successfully use the Role\_Email collaboration object as the notifying collaboration object, the Retail\_Item attribute specified in the ItemValidation, ItemCollector, ItemDispatcher, or Process\_Reviewed\_Item collaboration object's EMAIL\_MSG\_ATTRIBUTE property must match the Retail\_Item attribute specified in the Role\_Email collaboration object's MSG\_TEXT\_ATTRIBUTE property. This Retail\_Item attribute can contain either the actual message text or a filename containing the message text. See "Specifying message text, subjects, and recipients in external files" on page 62.

**Note:** In the ItemValidation collaboration object, if the ERROR\_EMAIL\_MSG property exists but is BLANK, a default value is placed in the Retail\_Item attribute specified by the EMAIL\_MSG\_ATTRIBUTE property. In the ItemCollector collaboration object, if the ERROR\_RETRIEVE\_EMAIL\_MSG or ERROR\_SEND\_EMAIL\_MSG properties exist but are BLANK, a default value is placed in the Retail\_Item attribute specified by the EMAIL\_MSG\_ATTRIBUTE property. In the ItemDispatcher collaboration object, if the ERROR\_EMAIL\_MSG property exists but is BLANK, the exception that occurred in the collaboration object is used as the message text.

## ERROR\_EMAIL\_SUBJECT

This property specifies the Retail\_Item attribute containing the appropriate message subject. If an error occurs and the SEND\_MAIL\_ON\_ERROR and ERROR\_EMAIL\_ROLE properties exist (and, in the ItemValidation collaboration object, are not BLANK), the value of ERROR\_EMAIL\_SUBJECT is stored in the Retail\_Item attribute specified by the ItemValidation, ItemCollector, ItemDispatcher, or Process\_Reviewed\_Item collaboration object's EMAIL\_SUBJECT\_ATTRIBUTE property. By default, this Retail\_Item attribute is internal.s.message\_subject. To successfully use the Role\_Email collaboration object as the notifying collaboration object, the Retail\_Item attribute specified in the ItemValidation, ItemCollector, ItemDispatcher, or Process\_Reviewed\_Item collaboration object's EMAIL\_SUBJECT\_ATTRIBUTE property must match the Retail\_Item attribute specified in the Role\_Email collaboration object's MSG\_SUBJECT\_ATTRIBUTE property. This Retail\_Item attribute can contain either the actual subject text or a filename containing the subject text. See "Specifying message text, subjects, and recipients in external files."

**Note:** In the ItemValidation collaboration object, if the ERROR\_EMAIL\_SUBJECT property exists but is BLANK, a default value is placed in the Retail\_Item attribute specified by the EMAIL\_SUBJECT\_ATTRIBUTE property.

## QUALIFICATION\_FAILED\_EMAIL\_MSG

The QUALIFICATION\_FAILED\_EMAIL\_MSG property is used only with the Process\_Reviewed\_Item collaboration object.

Set this attribute to the appropriate message text to be sent if the status of the item returned on the Process\_Reviewed\_Item collaboration object's *reprocess* port from the ItemValidation collaboration object is Rejected.

---

## Specifying message text, subjects, and recipients in external files

A Role\_Email collaboration object allows the contents of the Retail\_Item attributes that specify email message text, subject text, and recipients to contain the names of files.

### Description

These files contain the actual email message text, subject text, and addresses, and can be easily modified without modifying the using collaboration objects. This feature permits messages, subjects, and recipients to be shared among multiple collaboration objects. A solution's messages, subjects, and recipients can all be contained in one easily modifiable directory.

The Role\_Email collaboration object uses the following configuration properties to identify the Retail\_Item attributes containing the email message text, subject text, and recipients:

### MSG\_TEXT\_ATTRIBUTE

Identifies the Retail\_Item attribute containing the message text, by default, internal.s.message\_text

### MSG\_SUBJECT\_ATTRIBUTE

Identifies the Retail\_Item attribute containing the subject text, by default, internal.s.message\_subject

## MSG\_RECIPIENT\_ATTRIBUTE

Identifies the Retail\_Item attribute containing the recipient or list of recipients, by default, `internals.message_recipient_role`

The collaboration object distinguishes whether the content of the Retail\_Item attributes are actual values or filenames through use of its configuration property `FILE_NAME_PREFIX`. If the value of the Retail\_Item attribute specified in the `MSG_TEXT_ATTRIBUTE`, `MSG_SUBJECT_ATTRIBUTE`, or `MSG_RECIPIENT_ATTRIBUTE` property is prefixed with the String specified in `FILE_NAME_PREFIX`, the Role\_Email collaboration object interprets the rest of the value as a filename. The collaboration object reads the value of the file into a String variable in preparation for further processing. Files must be identified by their fully qualified names.

For instance, if the filename containing the email recipient(s) is `c:\Email_Files\CategoryManagerRole.txt` and the value of `FILE_NAME_PREFIX` is `@`, set the value of the Retail\_Item attribute identified by the `MSG_RECIPIENT_ATTRIBUTE` property, as follows:

```
@c:\Email_Files\CategoryManagerRole.txt
```

If the values of the Retail\_Item attributes specified in the `MSG_TEXT_ATTRIBUTE`, `MSG_SUBJECT_ATTRIBUTE`, and `MSG_RECIPIENT_ATTRIBUTE` properties do not start with the String specified in `FILE_NAME_PREFIX`, the Role\_Email collaboration object obtains the email values directly from the attributes. If the Retail\_Item attributes for message text or subject text contain no values, the Role\_Email collaboration object supplies default values for them.

---

## Specifying changing individual or multiple message recipients

Using a Role\_Email collaboration to route e-mail.

### Purpose

A Role\_Email collaboration object allows all e-mail messages to be routed to an administrator or to a specific role in an organization (like a Category Manager), without the need to maintain the email recipient's fully qualified e-mail address in every collaboration object that might send e-mail. By placing the e-mail address in an external file, if the address changes, the file can be modified without having to reconfigure the using collaboration objects. More than one recipient can be specified to receive the e-mail through use of a comma-delimited list. The comma-delimited list can be specified in the business object attribute or in the external file pointed to by the attribute.

---

## Using substitution variables in message and subject text

Email message and subject text can be constants that contain variables.

A Role\_Email collaboration object substitutes data from the processing state or business object into these variables dynamically. For instance, in the message

```
An item with GTIN ${item.catalogueItem.tradeItem.itemInformation. \
tradeItemIdentification.gtin} was approved and synchronized to the back end system
```

the GTIN value represented by `${item.catalogueItem.tradeItem.itemInformation.tradeItemIdentification.gtin}`

```
${item.catalogueItem.tradeItem.itemInformation.tradeItemIdentification.gtin}
```

is filled in automatically during the generation of this message.

Variables to be substituted must be enclosed in prefix and suffix characters. The substitution variable characters are defined in the values of the Role\_Email collaboration object's configuration properties SUBSTITUTION\_VARIABLE\_PREFIX and SUBSTITUTION\_VARIABLE\_SUFFIX. In the following example, these properties are set as follows:

```
SUBSTITUTION_VARIABLE_PREFIX = ${  
SUBSTITUTION_VARIABLE_SUFFIX = }
```

As a result, the substitution variables in the email message and subject text must appear as: `${variable_name}`

**Note:** These characters might have to be changed to meet National Language requirements.

### Supported values

The supported values for *variable\_name*, along with the values that the collaboration object actually inserts in the text, are as follows:

ROOT	The entire triggering business object.
Date	The current date
getName	The name of the triggering business object
getVerb	The verb of the triggering business object
Any attribute name	The value of the named attribute from the triggering business object. If the value for <i>variable_name</i> does not match one of the specific values above, the collaboration object interprets it as the name of a business object attribute.

---

## Chapter 12. Logging

Describes the special capabilities of various collaboration objects to log errors, item status, and when mail is sent.

### Description

ItemValidation, ItemCollector, Process\_Reviewed\_Item, and Role\_Email collaboration objects can log error situations and, in some cases, item status. A Role\_Email collaboration object can also log each time an email message is sent.

---

### Logging that mail is sent

Set a Role\_Email collaboration object's configuration property LOG\_ALL\_MAIL to true to place an entry in the configured log destination each time an email message is generated.

---

### Logging errors

If error conditions are encountered during any stage of processing, actions are taken. ItemValidation, ItemCollector, and Process\_Reviewed\_Item collaboration objects do the following:

#### Description

If error conditions are encountered during any stage of processing, ItemValidation, ItemCollector, and Process\_Reviewed\_Item collaboration objects do the following:

- Set the Retail\_Item business object's attribute value named in the configuration property ITEM\_STATUS\_ATTRIBUTE to .Error
- Log the error in the configured log destination.
- Return the object to the calling collaboration object through the *From* port.

If any errors are detected when email is sent, the Role\_Email collaboration object logs them in the log destination.

**Note:** For error logging to occur in ItemCollector and Process\_Reviewed\_Item collaboration objects, tracing must be enabled. For error logging to occur in a Role\_Email collaboration object, its LOG\_ERROR configuration property must be set to true.

---

### Logging item status

The available configuration properties to log item status.

#### Description

The values of configuration properties in ItemValidation, ItemCollector, and Process\_Reviewed\_Item collaboration objects control the logging of item status. A value of true in the following properties enables the business object to be logged in the configured log destination:

**LOG\_ERROR\_ITEM**

Specifies whether the collaboration object logs the business object being processed (in addition to the error) when an error is detected during processing.

**LOG\_REVIEW\_ITEM**

(ItemValidation collaboration objects only) Specifies whether the collaboration object logs the business object being processed when the object is successfully processed. The Review item status means that the item continues to be processed for required missing attribute data review or approval.

**LOG\_APPROVED\_ITEM**

(Process\_Reviewed\_Item collaboration objects only) Specifies whether the collaboration object logs the business object being processed when the object status is Approved.

**LOG\_ACCEPTED\_ITEM**

(Process\_Reviewed\_Item collaboration objects only) Specifies whether the collaboration object logs the business object being processed when the object status is Accepted.

**LOG\_REJECTED\_ITEM**

(ItemValidation and Process\_Reviewed\_Item collaboration objects only) Specifies whether the collaboration objects log the business object being processed when the object status is Rejected.

Solution requirements dictate the type of logging that occurs, as well as when it occurs. It is recommended that the LOG\_ERROR\_ITEM property always be set to true so that any item that fails is logged for diagnostic purposes.

To log an item only after it completes the business review/approval process, set the LOG\_APPROVED\_ITEM and LOG\_REJECTED\_ITEM properties of the Process\_Reviewed\_Item collaboration object to true and the LOG\_REVIEW\_ITEM and LOG\_REJECTED\_ITEM properties of the ItemValidation collaboration object and the LOG\_ACCEPTED\_ITEM property of the Process\_Reviewed\_Item collaboration object to false.

To log an item both before and after it enters the business review/approval process, set all logging collaboration properties of ItemValidation and Process\_Reviewed\_Item collaboration objects to true.

**Planning files for logging and tracing**

Use separate files for logging and tracing. Use logging files to maintain persistent records of processed data. Use tracing files to diagnose problems and to show the flow of an item through the Product Information Management for Retailers solution. The Log Viewer tool has log and trace file filters that enable users to view the log or trace records for a particular business object or collaboration object.

---

## Chapter 13. Tracing

Outlines how to trace and identify problems that might occur in the solution workflow.

All collaboration objects based on collaboration templates included in the Product Information Management for Retailers solution provide tracing capabilities to record logical flows and data processed. Users can enable tracing for a particular collaboration object by selecting the collaboration object in the System Manager, displaying its properties, and, on the **Collaboration General Properties** tab, selecting a trace level greater than 0 from the **System trace level** field.

Enable tracing for one or more collaboration objects when a reproducible problem occurs. If a problem occurs only once during processing, leave the tracing function enabled continually so that the first occurrence of the failure is captured. However, leaving the tracing function enabled continually can degrade performance. Clear the trace file periodically to simplify viewing and filtering it.

**Note:** Use separate files for tracing and logging. Use tracing files to diagnose problems and to show the flow of an item through the Product Information Management for Retailers solution. Use logging files to maintain persistent records of processed data. The Log Viewer tool has trace and log file filters that enable users to view the trace or log records for a particular business object or collaboration object.



---

## Chapter 14. Handling solution processing errors

Provides troubleshooting tips that can be used to diagnose error conditions, identify where in the process flow errors might have occurred, and recover from error conditions.

### Description

The Product Information Management for Retailers solution is designed so that its component collaboration objects gather as much information as possible about an error situation, notify the appropriate users that an error has occurred, and then continue with item processing. Only severe system errors cause processing by a collaboration object to end as an unfinished flow. This design prevents situations in which a restarted flow might not have all of the resources available to it to reprocess the item or might initiate tasks that should not be repeated. The following examples describe some of the problems that can occur if item processing is restarted:

- If an item is approved in the business process but the synchronization fails on the back end, if the process is restarted, the item will not be found in the item store (it has already been deleted).
- If an item is synchronized to the back end but an error occurs when sending the response to UCCnet, if the process is restarted, the item will be synchronized to the back end again.

The following lists several error situations that can occur when processing an item:

- A UCCNetMessageReceive collaboration object cannot parse the incoming message into a specific item request.
- A database access failure occurs during processing by ItemValidation, ItemCollector, ItemDispatcher, or Process\_Reviewed\_Item collaboration objects.
- The business review/approval process ends in error.
- An item cannot be synchronized to the back-end system.
- A response cannot be sent back to UCCnet.

---

## Diagnosing error conditions

Some procedures to follow to determine how an item failed in processing and where in the processing flow it failed.

### Determining the problem from e-mail messages

The Product Information Management for Retailers solution uses e-mail routed to specific user IDs to alert users when errors occur during item processing. The e-mail provides basic information about the errors. E-mail messages can be configured or modified.

### Determining the problem from log or trace files

Use the log file to determine how far an item progressed through the solution flow before a problem occurred. Filter the log file to examine specific collaboration object or business object events. If the log does not provide enough information about the failure, activate tracing for one or more collaboration objects and

examine the trace file for more details. Filter the trace file to search for specific collaboration object or business object events.

### **Determining the point of failure**

The point of failure in solution processing determines the method used to restart item processing. The following sections outline check points that can help pinpoint where in item processing an error occurred.

#### **Check that the item exists in the message store**

Use database user interface methods to examine the message store. Search for a message that correlates to the item in error. Refer to the key of the message store to correlate the item.

#### **Check that the item completed validation checks**

Examine the log file for messages originating from the ItemValidation collaboration object that indicate that the item completed validation checks.

#### **Check that the item reached the business review/approval process**

Use the user interface for the business review/approval process to search for the item in question. If the item reached the business review/approval process and the business review/approval process used is WebSphere MQ Workflow, the item appears as a new task in the workflow.

#### **Check that the item completed the business review/approval process**

The log information related to the ItemCollector collaboration object indicates the state of the item as it arrives from the business review/approval process. If the error occurred in this process, the status of the item passed to the ItemCollector collaboration object is Error.

If the error resulted from the ItemCollector collaboration object not being able to read the item from the item store, information in the log or trace files can identify the failure. Remove the item from the stores and restart the item from UCCnet.

#### **Check that item synchronization to the back end occurred**

In the context of the Product Information Management for Retailers solution, the JTextConnector synchronizes the item to a back-end file system by writing it to a flat file. Examine the directory containing the item files to see if the failed item was written to a file. If it was, the item was synchronized properly and the error occurred at a later stage.

If the item was not written to a file, the error occurred prior to processing performed by the Process\_Reviewed\_Item collaboration object. Most likely, no response was sent to UCCnet.

#### **Check that a response was sent to UCCnet**

Verify that a response was sent to UCCnet by examining the logging and tracing information related to the UCCnetMessageSend collaboration object or the AS2 channel output directory.

If the response sent to UCCnet was Synchronised (for systems using the XSD XML definition) or Authorized (for systems using the DTD XML definition), the item was synchronized to the back-end system before the error occurred.

If the response sent was Rejected, most likely the item was rejected. The error might have occurred after the response was sent. Normally, a UCCnetMessageSend collaboration object is configured to *not* send responses if errors occur during item processing.

If no response was sent for the item, the item can be reprocessed.

---

## Recovering from error conditions

Removing an existing item from the process that ended in error so it can be reprocessed.

### Description

After determining the nature of the error and correcting it, the existing item must be removed from the process that ended in error so it can be reprocessed. Unless the item is to be restarted by using a test connector, the item must be removed from every store and from the business review/approval process before processing can be restarted.

### Removing an item from processing

1. Remove the item from the business review/approval process (WebSphere MQ Workflow in the context of the Product Information Management for Retailers solution) by referring to WebSphere MQ Workflow documentation that describes how to remove the instance of the WebSphere MQ Workflow process that ended in error.
2. Delete the item from the item store by finding the value of its `internals.correlationID` attribute in the log file. Use this value as the key to the item store and find and delete the `Retail_Item` record.
3. Delete the item from the message store finding the value of the `correlationID` attribute of the related `UCCnetGBO_storable` business object in the log file. Use this value as the key to the message store and find and delete the record.
4. If the original request was a `NEW_ITEM`, `DATA_CHANGE`, `WITHDRAW`, or `DE_LIST`, delete the item from the identifier store by finding in the log file the values of the `gtin`, `version`, and `topic` attributes of the related `UCCnetGBO_identifier` business object for DTD processing or the `gtin`, `topic`, `dataRecipientGLN`, `dataSourceGLN`, `targetMarket`, and `uniqueCreatorID` attributes of the related `UCCnetGBO_identifier` business object for XSD processing. Use these values as the key to the identifier store and find and delete the record.

### Restarting item processing

To restart item processing, do one of the following:

- Regenerate the message from UCCnet by obtaining the GTIN and trading partner GLN from the log entries related to the item and using the UCCnet Graphical User Interface (GUI) to request a republication of the item. This action causes a message to arrive for the item and the item is processed normally.
- Regenerate the message from the UCCnet backup area. The original message containing the failed item can be copied from the UCCnet staging directory to the connector processing directory.
- Use a test connector to restart the item from the item store if the following conditions exist:
  - The item failed in the back-end process
  - The item was synchronized
  - No message was sent to UCCnet
  - The item still exists in the item, identifier, and message stores

To use a test connector to restart the item, do the following:

1. Do not delete the item from the item store, message store, or identifier store.
2. Start a test connector and connect it to an ItemCollector collaboration object flow. This requires configuring a set of collaboration objects and connectors to imitate a normal back-end flow.
3. Create a Retail\_Item business object in the test connector and set the value of its `internals.correlationID` attribute equal to the value of the `internals.correlationID` attribute for the item found in the log.
4. Send the item. The ItemCollector collaboration object receives it and processes it normally.

---

## Chapter 15. Handling data from other data sources

Suggestions for extending the solution to handle single data sources other than UCCnet or multiple data sources.

### Other data sources

The Product Information Management for Retailers solution can be extended to handle different item sources in addition to UCCnet, including the World Wide Retail Exchange (WWRE), the Universal Data Exchange (UDEX), or a user interface. Items from various sources can differ significantly in the architecture of the data that comprises them.

---

### Extending the solution to handle a single data source other than UCCnet

Put your short description here; used for first paragraph and abstract.

#### Description

To handle data from a source other than UCCnet, do the following:

1. Replace the UCCnetMessageReceive and UCCnetMessageSend collaboration templates with custom collaboration templates that generate collaboration objects that can parse incoming messages from and produce appropriate response messages to the new data source.
2. Modify the Retail\_Item business object `item` attribute type (by default, `Retailer_item`) into a different child business object that represents the new architecture of the item data. It is recommended that this child business object closely follow the architecture of the data source (that is, UCCnet publication, WWRE item, or other source).
3. Modify all solution maps that convert Retail\_Item business objects to instead convert items with the new data architecture.
4. Configure all the configuration properties that point to attributes in the Retail\_Item business object to instead point to the appropriate attributes in the new data architecture.

---

### Extending the solution to handle multiple data sources

To handle items from multiple data sources, the front end of the solution must include collaboration objects that can parse each type of new item.

#### Description

To handle items from multiple data sources, the front end of the solution must include collaboration objects that can parse each type of new item. These collaboration objects must be based on custom collaboration templates similar to the UCCnetMessageReceive collaboration template. Each of these front-end collaboration objects must be attached to an ItemValidation collaboration object. The ItemValidation collaboration objects operate identically for each front-end parsing collaboration object, routing the different types of Retail\_Item business objects to ItemDispatcher collaboration objects. If the various data sources use the

same business review/approval process, they can use a common data container. Appropriate maps must be created that convert the different types of Retail\_Item business objects to the common data container.

When the business review/approval process completes, the common data container is sent to the WebSphere MQ Workflow queue. The existing Product Information Management for Retailers solution uses the MQWF\_Retail\_Item\_to\_Retail\_Item map to convert the WebSphere MQ Workflow container into a Retail\_Item business object. However, this map, which is used by the WebSphereMQWorkflowConnector, cannot produce different types of Retail\_Item business objects. Because the incoming Retail\_Item business objects are from different sources, the Retail\_Item business objects going to the back end are going to be different as well.

A collaboration template (similar to the ItemCollector collaboration template) must be created that develops and builds these different business objects. A collaboration object based on this custom collaboration template can possibly use the call\_map API and have a different To port for each data source producing a Retail\_Item business object.

---

## Notices

IBM may not offer the products, services, or features discussed in this document in all countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to: IBM Director of Licensing IBM Corporation North Castle Drive Armonk, NY 10504-1785 U.S.A.

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact: IBM Burlingame Laboratory Director IBM Burlingame Laboratory 577 Airport Blvd., Suite 800 Burlingame, CA 94010 U.S.A

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement, or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurement may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not necessarily tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

This information may contain examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples may include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement, or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurement may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not necessarily tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

This information may contain examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples may include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

---

## Copyright license

This information may contain sample application programs in source language, which illustrates programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs.

---

## Programming interface information

Programming interface information, if provided, is intended to help you create application software using this program.

General-use programming interfaces allow you to write application software that obtain the services of this program's tools.

However, this information may also contain diagnosis, modification, and tuning information. Diagnosis, modification and tuning information is provided to help you debug your application software.

Warning: Do not use this diagnosis, modification, and tuning information as a programming interface because it is subject to change.

---

## Trademarks

The following terms are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both:

IBM  
WebSphere

Java and all Java-based trademarks are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.







Printed in USA