



**Program Directory for  
WebSphere Process Server  
for z/OS**

Version 6 Release 2 Modification 0

Program Number 5655-N53

FMID HWPS620

for use with  
z/OS V1.7 or higher

Document Date: December 2008

G111-4299-00

**Note!**

Before using this information and the product it supports, be sure to read the general information under 7.0, "Notices" on page 43.

A form for reader's comments appears at the back of this publication. When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

© **Copyright International Business Machines Corporation 2006, 2008. All rights reserved.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

---

# Contents

<b>1.0 Introduction</b>	1
1.1 WebSphere Process Server Description	1
1.2 WebSphere Process Server FMIDs	2
<b>2.0 Program Materials</b>	3
2.1 Basic Machine-Readable Material	3
2.2 Optional Machine-Readable Material	3
2.3 Program Publications	3
2.3.1 Basic Program Publications	4
2.3.2 Optional Program Publications	5
2.4 Program Source Materials	5
2.5 Publications Useful During Installation	5
<b>3.0 Program Support</b>	6
3.1 Program Services	6
3.2 Preventive Service Planning	6
3.3 Statement of Support Procedures	7
<b>4.0 Program and Service Level Information</b>	8
4.1 Program Level Information	8
4.2 Service Level Information	8
<b>5.0 Installation Requirements and Considerations</b>	9
5.1 Driving System Requirements	9
5.1.1 Machine Requirements	9
5.1.2 Programming Requirements	9
5.2 Target System Requirements	10
5.2.1 Machine Requirements	10
5.2.2 Programming Requirements	11
5.2.2.1 Installation Requisites	11
5.2.2.2 Operational Requisites	11
5.2.2.3 Toleration/Coexistence Requisites	13
5.2.2.4 Incompatibility (Negative) Requisites	13
5.2.3 DASD Storage Requirements	13
5.3 FMIDs Deleted	19
5.4 Special Considerations	19
5.4.1 SMP/E Considerations	20
5.4.2 Selecting Driving System Mount points	21
5.4.3 Selecting Target System Mount points	21
5.4.4 Removal of WebSphere Application Server Levels	22
<b>6.0 Installation Instructions</b>	23

6.1	Installing WebSphere Application Server	23
6.1.1	SMP/E Considerations for Using the SMP/E Web Download	23
6.1.2	SMP/E Considerations for Installing WebSphere Application Server	24
6.1.3	Sample Jobs	25
6.1.4	Allocate SMP/E CSI (Optional)	26
6.1.5	Define New SMP/E TARGET and DLIB Zones (Optional)	26
6.1.6	Add Target Zones for Cross-Zone Prerequisite Checking	26
6.1.7	Perform SMP/E RECEIVE	27
6.1.8	Allocate SMP/E Target and Distribution Libraries	27
6.1.9	Allocate HFS or zFS PATHS	27
6.1.10	Create DDDEF Entries	28
6.1.11	Perform SMP/E APPLY	28
6.1.12	Perform SMP/E ACCEPT	29
6.2	Installing the WebSphere Application Server for z/OS V6.1.0 Optional Materials	29
6.2.1	Sample Jobs	30
6.2.2	Perform SMP/E RECEIVE	31
6.2.3	Define Target and Distribution Libraries	31
6.2.4	Set Up HFS Directories	32
6.2.5	Define SMP/E DDDEFs	32
6.2.6	Perform SMP/E APPLY	33
6.2.7	Perform SMP/E ACCEPT	34
6.3	Installing WebSphere Process Server	34
6.3.1	SMP/E Considerations for Using the SMP/E Web Download	34
6.3.2	SMP/E Considerations for Installing WebSphere Process Server	35
6.3.3	Sample Jobs	35
6.3.4	Create CSI Global Zone	37
6.3.5	Perform SMP/E RECEIVE	37
6.3.6	Allocate SMP/E Target and Distribution Libraries	38
6.3.7	Create the USS File System	38
6.3.8	Allocate HFS or zFS PATHS	38
6.3.9	Define Target and Distribution Zones.	39
6.3.10	Define SMP/E DDDEFs	39
6.3.11	Add Target Zones for Cross-Zone Prerequisite Checking	39
6.3.12	Perform SMP/E APPLY	39
6.3.13	Perform SMP/E ACCEPT	40
6.4	Activating WebSphere Process Server	41
6.4.1	HFS Execution	41
6.4.2	WebSphere Process Server configuration	41
6.4.3	Mount the HFS or zFS Data Set on the Target System	41
6.4.4	Activating WebSphere Process Server	42
<b>7.0</b>	<b>Notices</b>	<b>43</b>
7.1	Trademarks	44
<b>Reader's Comments</b>		<b>45</b>

---

## Figures

1.	Basic Material: Unlicensed Publications	4
2.	Basic Material: Other Unlicensed or Licensed Publications	4
3.	Publications Useful During Installation	5
4.	PSP Upgrade and Subset ID	6
5.	Component IDs	7
6.	Driving System Software Requirements	10
7.	Mandatory Installation Requisites	11
8.	Mandatory Operational Requisites	11
9.	Conditional Operational Requisites	12
10.	Total DASD Space Required by WebSphere Process Server	13
11.	Storage Requirements for SMP/E Work Data Sets	15
12.	Storage Requirements for SMP/E Data Sets	16
13.	Storage Requirements for WebSphere Process Server Target Libraries	16
14.	WebSphere Process Server HFS or zFS Paths	17
15.	Storage Requirements for WebSphere Process Server Distribution Libraries	18
16.	Sample Installation Jobs	25
17.	Sample Installation Jobs - JIWO610	30
18.	Sample Installation Jobs	35



---

## 1.0 Introduction

This Program Directory is intended for the system programmer responsible for program installation and maintenance. It contains information concerning the material and procedures associated with the installation of WebSphere Process Server for z/OS V6.2.0. This publication refers to WebSphere Process Server for z/OS V6.2.0 as WebSphere Process Server.

The Program Directory contains the following sections:

- 2.0, “Program Materials” on page 3 identifies the basic and optional program materials and documentation for WebSphere Process Server.
- 3.0, “Program Support” on page 6 describes the IBM support available for WebSphere Process Server.
- 4.0, “Program and Service Level Information” on page 8 lists the APARs (program level) and PTFs (service level) incorporated into WebSphere Process Server.
- 5.0, “Installation Requirements and Considerations” on page 9 identifies the resources and considerations required for installing and using WebSphere Process Server.
- 6.0, “Installation Instructions” on page 23 provides detailed installation instructions for WebSphere Process Server. It also describes the procedures for activating the functions of WebSphere Process Server, or refers to appropriate publications.

Before installing WebSphere Process Server, read the *CBPDO Memo To Users* and the *CBPDO Memo To Users Extension* that were supplied with this program in softcopy form as well as this Program Directory and then keep them for future reference. Section 3.2, “Preventive Service Planning” on page 6 tells you how to find any updates to the information and procedures in this Program Directory.

WebSphere Process Server is supplied in a Custom-Built Product Delivery Offering (CBPDO, 5751-CS3). The Program Directory is provided in softcopy form on the CBPDO tape which is identical to the hardcopy form provided with your order. All service and HOLDDATA for WebSphere Process Server are included on the CBPDO tape.

Do not use this Program Directory if you are installing WebSphere Process Server with a SystemPac or ServerPac. When using these offerings, use the jobs and documentation supplied with the offering. This documentation may point you to specific sections of the Program Directory as required.

---

### 1.1 WebSphere Process Server Description

WebSphere Process Server helps provide an SOA infrastructure that delivers one common model to orchestrate, mediate, connect, map and perform the underlying IT functions.

Carries out a series of services, as part of a process, with end-to-end transactional integrity, Including comprehensive support for human-related tasks, information integration from disparate applications into a process, and integration with information management systems.

Enables rapid process changes, providing business agility and enabling you to leverage resources efficiently.

Perform the mediations between the service requester and the service provider as a business process runs.

---

## 1.2 WebSphere Process Server FMIDs

WebSphere Process Server consists of the following FMIDs:

HWPS620 - WebSphere Process Server for z/OS V6.2.0

H28W610 - WebSphere Application Server for z/OS V6.1.0

JIWO610 - WebSphere Application Server for z/OS V6.1 Optional Materials

**Note!**

The Java Software Development Kit (SDK) is now shipped, installed, and serviced as part of WebSphere Application Server. There is no longer a separate FMID for the SDK. This makes the WebSphere Application Server for z/OS products independent of any other SDK installed on the same z/OS systems.



---

## 2.0 Program Materials

An IBM program is identified by a program number. The program number for WebSphere Process Server is 5655-N53.

Basic Machine-Readable Materials are materials that are supplied under the base licence and feature numbers, and are required for the use of the product. Optional Machine-Readable Materials are orderable under separate feature numbers, and are not required for the product to function.

The program announcement material describes the features supported by WebSphere Process Server. Ask your IBM representative for this information if you have not already received a copy.

---

### 2.1 Basic Machine-Readable Material

The distribution medium for this program is magnetic tape or downloadable files. It is installed using SMP/E, and is in SMP/E RELFILE format. See 6.0, "Installation Instructions" on page 23 for more information about how to install the program.

Information about the physical tape for the Basic Machine-Readable Materials for WebSphere Process Server can be found in the *CBPDO Memo To Users Extension*.

Included with this product are media kits ( LK4T-1484, LK4T-1485, LK4T-1486, LK4T-1487, LK4T-1488, LK4T-1489, and LK4T-1490) containing software that is not intended to run on z/OS. These media kits provide additional value and tool support for your production and development environments. The use of these DVDs and CDs is optional. See the Packaging topics in the WebSphere Process Server Information Center for information on using these DVDs and CDs.

---

### 2.2 Optional Machine-Readable Material

No optional machine-readable materials are provided for WebSphere Process Server.

---

### 2.3 Program Publications

The following sections identify the basic and optional publications for WebSphere Process Server. Note the main documentation distribution medium for WebSphere Process Server is the Information Center, which can be accessed from the WebSphere Process Server product documentation page at: <http://www.ibm.com/software/integration/wps/library/infocenter>

In addition to the Information Center, WebSphere Process Server product documentation is available in PDF format on the same Web site.

## 2.3.1 Basic Program Publications

Figure 1 on page 4 identifies the basic unlicensed program publications for WebSphere Process Server. You can download the program directory for WebSphere Process Server from <http://www.ibm.com/software/integration/wps/library/infocenter>.

<i>Figure 1. Basic Material: Unlicensed Publications</i>	
<b>Publication Title</b>	<b>Form Number</b>
Program Directory for WebSphere Process Server	GI11-4299-00
License Information WebSphere Process Server for z/OS	LC23-4990-04
Carefully read the WebSphere Process Server for z/OS License Information, a copy of which is provided to you with your order. This document contains the product-specific terms and conditions for WebSphere Process Server for z/OS.	

Figure 2 identifies the basic unlicensed or licensed publications that are not available in hardcopy form, but are available through the internet or other media for WebSphere Process Server.

All of the documents listed in Figure 2 are available for download at either the WebSphere Process Server Library page: <http://www-01.ibm.com/software/integration/wps/library/infocenter/> or <http://www.ibm.com/shop/publications/order>

<i>Figure 2. Basic Material: Other Unlicensed or Licensed Publications</i>		
<b>Publication Title</b>	<b>Form Number</b>	<b>How Available</b>
WebSphere Process Server for z/OS V6.2.0 Product overview	-	Library page
WebSphere Process Server for z/OS V6.2.0 Planning	-	Library page
WebSphere Process Server for z/OS V6.2.0 Installing	-	Library page
WebSphere Process Server for z/OS V6.2.0 Migrating to WebSphere Process Server	-	Library page
WebSphere Process Server for z/OS V6.2.0 Administering WebSphere Process Server	-	Library page
WebSphere Process Server for z/OS V6.2.0 Developing and deploying modules	-	Library page
WebSphere Process Server for z/OS V6.2.0 Monitoring	-	Library page
WebSphere Process Server for z/OS V6.2.0 Tuning	-	Library page
WebSphere Process Server for z/OS V6.2.0 Troubleshooting	-	Library page
Message Service Clients for C++ and .NET V1.2	SC34-6778	Library page

## 2.3.2 Optional Program Publications

There are no optional publications for WebSphere Process Server for z/OS.

---

## 2.4 Program Source Materials

No program source materials or viewable program listings are provided for WebSphere Process Server.

---

## 2.5 Publications Useful During Installation

The publications listed in Figure 3 may be useful during the installation of WebSphere Process Server. To order copies, contact your IBM representative or visit the IBM Publications Center on the World Wide Web at:

<http://www.ibm.com/shop/publications/order>

You can also access these publications online at:

[http://publibz.boulder.ibm.com/cgi-bin/bookmgr\\_OS390/](http://publibz.boulder.ibm.com/cgi-bin/bookmgr_OS390/)

<b>Publication Title</b>	<b>Form Number</b>
<i>IBM SMP/E for z/OS User's Guide</i>	SA22-7773
<i>IBM SMP/E for z/OS Commands</i>	SA22-7771
<i>IBM SMP/E for z/OS Reference</i>	SA22-7772
<i>IBM SMP/E for z/OS Messages, Codes, and Diagnosis</i>	GA22-7770
<i>z/OS MVS JCL Reference</i>	SA22-7597
<i>z/OS System Codes</i>	SA22-7626
<i>IBM Software Delivery Standard Packaging Rules for z/OS-Based Products</i>	SC23-3695

---

## 3.0 Program Support

This section describes the IBM support available for WebSphere Process Server.

---

### 3.1 Program Services

Contact your IBM representative for specific information about available program services.

---

### 3.2 Preventive Service Planning

Before installing WebSphere Process Server, it is VERY IMPORTANT that you review the current Preventive Service Planning (PSP) information. The PSP buckets maintain current lists (which have been identified since the package was created) of any recommended or required service for this package's installation. This includes software PSP information that contains HIPER, and/or required PTFs against the base release.

While there can be overlap between SW, HW, and functional PSP buckets, reviewing all that apply to this package will ensure that you identify any known service required for your installation of this package.

If you obtained WebSphere Process Server as part of a CBPDO, there is HOLDDATA included on the PDO.

If the CBPDO for WebSphere Process Server is more than two weeks old when you install it, you should contact the IBM Support Center, use S/390 SoftwareXcel to obtain the current "PSP Bucket" or obtain the current PSP from the Web at <https://techsupport.services.ibm.com/server/390.psp390>.

For program support, access the Software Support Web site at <http://www-3.ibm.com/software/support/>

PSP Buckets are identified by UPGRADEs, which specify product levels, and SUBSETs, which specify the FMIDs for a product level. The UPGRADE and SUBSET values for WebSphere Process Server are:

*Figure 4. PSP Upgrade and Subset ID*

UPGRADE	SUBSET	Description
WPSZ	HWPS620	WebSphere Process Server for z/OS

---

### 3.3 Statement of Support Procedures

Report any difficulties you have using this program to your IBM Support Center. If an APAR is required, the Support Center will advise how you should submit any needed information or documentation.

Figure 5 on page 7 identifies the component IDs (COMPID) for WebSphere Process Server.

<i>Figure 5. Component IDs</i>			
<b>FMID</b>	<b>COMPID</b>	<b>Component Name</b>	<b>RETAIN Release</b>
HWPS620	5655N5300	WebSphere Process Server for z/OS V6.2.0	620
H28W610	5655I3500	WebSphere Application Server for z/OS V6.1.0	610
JIWO610	--	WebSphere Application Server for z/OS V6.1 Optional Materials. Optional Materials delivered in this FMID will receive unique COMPIDs at the time of their delivery.	610

---

## **4.0 Program and Service Level Information**

This section identifies the program and any relevant service levels of WebSphere Process Server. The program level refers to the APAR fixes incorporated into the program. The service level refers to the PTFs incorporated into the program.

---

### **4.1 Program Level Information**

All applicable WebSphere Process Server V6.1.0 and V6.1.2 for z/OS service have been incorporated into WebSphere Process Server V6.2.0

---

### **4.2 Service Level Information**

No PTFs against this release of WebSphere Process Server have been incorporated into the product tape.

No PTFs against this release of WebSphere Process Server have been incorporated into the Web deliverable.

Over time it is HIGHLY recommended that you frequently check the WebSphere Process Server PSP bucket for HIPER and SPECIAL Attention PTFs against all FMID(s) which should be installed.

---

## 5.0 Installation Requirements and Considerations

The following sections identify the system requirements for installing and activating WebSphere Process Server. The following terminology is used:

- *Driving system*: the system used to install the program.

The program may have specific operating system or product level requirements for utilizing processes such as binder or assembly utilities during the install.

- *Target system*: the system on which the program is intended to run.

The program may have specific product level requirements such as needing access to another product's library for link-edits that may directly affect the elements during the install or for its basic or enhanced operation. These requirements may be mandatory or optional.

In many cases, the same system can be used as both a driving system and a target system. However, you may want to set up a clone of your system to use as a target system by making a separate IPL-able copy of the running system. The clone should include copies of all system libraries that SMP/E updates, copies of the SMP/E CSI data sets that describe the system libraries, and your PARMLIB and PROCLIB.

Some cases where two systems should be used include the following:

- When installing a new level of a product that is already installed, the new product will delete the old one. By installing onto a separate target system, you can test the new product while still keeping the old one in production.
- When installing a product that shares libraries or load modules with other products, the installation can disrupt the other products. Installing onto a test system or clone will allow you to assess these impacts without disrupting your production system.

---

### 5.1 Driving System Requirements

This section describes the environment of the driving system required to install WebSphere Process Server.

#### 5.1.1 Machine Requirements

The driving system can run in any hardware environment that supports the required software.

#### 5.1.2 Programming Requirements

Figure 6. Driving System Software Requirements

Program Number	Product Name and Minimum VRM/Service Level
<b>EITHER</b> 5694-A01 or 5665-G52:	
5694-A01	z/OS V1.7 or higher, and the following APARs OA11519, OA11699, or later. Also required is IBM SMP/E for z/OS with APAR IO04924 or later
5665-G52	z/OS.e V1.7 or higher, with PTFs to satisfy APARs OA11519, OA11699, or later. Also required is IBM SMP/E for z/OS with APAR IO04924 or later
5665-I56	Java 2 Technology Edition SDK 1.4 or higher

WebSphere Process Server for z/OS V6.2.0 installs in the z/OS (Z038) SREL.

**Notes:**

1. SMP/E uses the Java SDK to install WebSphere Application Server and WebSphere Process Server, you must install SDK 1.4 or higher on the driving system.

You can download a free copy of Java SDK 1.4 from:

<http://www.ibm.com/servers/eserver/zseries/software/java>

This SDK is different from the imbedded SDK mentioned in the following notes.

2. UNIX must be up in full function mode on your driving system so that the utilities are available for the Shell Script support.
3. The following installation jobs, as well as the SMP/E APPLY job, should be run under a user ID with UID(0), or with a user ID with read access to the BPX.SUPERUSER resource in the RACF facility class. This installation user ID must also have read access to the facility class resources BPX.FILEATTR.PROGCTL, BPX.FILEATTR.APF, and BPX.FILEATTR.SHARELIB.
  - BBOISMKD
  - BPZISMKD

---

## 5.2 Target System Requirements

This section describes the environment of the target system required to install and use WebSphere Process Server.

WebSphere Process Server installs in the z/OS (Z038) SREL.

### 5.2.1 Machine Requirements

The target system can run in any hardware environment that supports the required software.



## 5.2.2 Programming Requirements

**5.2.2.1 Installation Requisites:** An installation requisite is defined as a product that is required and **must** be present or one that is not required but **should** be present on the system for the successful installation of this product.

A mandatory installation requisite identifies products that are required, without exception, or this product **will not install** on your system. This includes products specified as PREs or REQs.

<i>Figure 7. Mandatory Installation Requisites</i>	
Program Number	Product Name and Minimum VRM/Service Level
Any <b>one</b> of the following:	
5694-A01	z/OS V1.7 or higher, and the following APARs OA11519, OA11699, or later. Also Required is z/OS UNIX System Services and the hierarchical file system (HFS) or zSeries file system(zFS)
5655-G52	z/OS.e V1.7 or higher, with PTFs to satisfy APARs OA11519, OA11699, or later. Also Required is z/OS UNIX System Services and the hierarchical file system (HFS) or zSeries file system(zFS)

A conditional installation requisite identifies products that are **not** required for successful install but may resolve such things as certain warning messages at installation time. They include products that are specified as IF REQs.

WebSphere Process Server has no conditional installation requisites.

**5.2.2.2 Operational Requisites:** An operational requisite is defined as a product that is required and **must** be present or a product that is not required but **should** be present on the system in order for this product to operate all or some of its functions.

A mandatory operational requisite identifies products that are required, without exception, or this product **will not operate** its basic function unless the requisite is met. This includes products specified as PREs or REQs.

<i>Figure 8. Mandatory Operational Requisites</i>	
Program Number	Product Name and Minimum VRM/Service Level
Any <b>one</b> of the following:	
5694-A01	z/OS V1.7 or higher, and the following APARs OA11519, OA11699, or later
5655-G52	z/OS.e V1.7 or higher with PTFs to satisfy APARs OA11519, OA11699, or later

A conditional operational requisite identifies products that are **not required** for the basic function but are needed at run time for this product to utilize specific functions. They may include products specified as IF REQs.

Figure 9 (Page 1 of 2). Conditional Operational Requisites

Program Number	Product Name and Minimum VRM/Service Level	Function
5694-A01 or 5655-G52	z/OS or z/OS.e V1.7 or higher with PTFs UQ88825, UA13606, UQ88986, UQ89754, UQ90946, UQ90077, UQ91768, UQ90822, UQ92626 and UA12453	Required by JDK V5 64-bit processing.
5655-N01	WebSphere Application Server V6.1.0.21	Required for 64-bit processing
5655-N01	WebSphere Application Server for z/OS V6.1 Optional Materials	Required for WebSphere Process Server for z/OS V6.2.0
5625-DB2, or 5635-DB2	DB2 for z/OS with the relevant APARs and PTFs: V8.1 or later with APARs PK00615, PQ84577, PQ87786, PQ88082, UQ86912, PK25139, and PTFs UK01566, UQ86912, UQ91762, UQ88239, UQ92168, UQ85537  V9.1 or later with APAR PK41173	Required to use Web Services UDDI and session persistence for Web container or if your application environment accesses DB2 through Java DataBase Connectivity (JDBC) or through IBM Connection/Connector for Java.  Required for Type 2 and Type 4 DB2 drivers. Additionally, APAR PK25139 provides DB2 drivers Version 2.10.4.4 and is required for Type 2 drivers for 64 bit processing on DB2 V7 and V8.
5655-K61, or 5655-N97	DB2 licensed utilities:  DB2 for z/OS V8: 5655-K61 DB2 Utilities Suite for z/OS.  DB2 for z/OS V9: 5655-N97 DB2 Utilities Suite for z/OS.	Required for use of DB2. Alternatively, you can use an equivalent licensed utility.
5655-147	CICS TS V2.3 or later	Required if your application environment uses CICS Transaction Server.
5655-M69	CICS Transaction Gateway for z/OS V6.0	Required if your application environment accesses CICS TS through the CICS Transaction Gateway (CICS TG), See <a href="http://www.ibm.com/cics/ctg">www.ibm.com/cics/ctg</a> for more information.
5655-R25	CICS Transaction Gateway for z/OS V7.0 or later	Required for 64-bit processing and also provides better performance with WebSphere Application Server V6.1 and Java V5.

Figure 9 (Page 2 of 2). Conditional Operational Requisites

Program Number	Product Name and Minimum VRM/Service Level	Function
5655-C56	IMS V8 or later	Required if your application environment accesses IMS through Java DataBase Connectivity (JDBC) or through IBM Connect/Connector for Java.
5655-J38 or 5635-A01	IMS V9 and APAR PK30868 or IMS V10 and APARs PK39061, PK49198	Required for 64-bit processing.
5655-L82	WebSphere MQ V6 with APAR PK31289 (also referred to as WebSphere MQ v6.0.2.1)	Required for 64-bit processing.
5655-R17	WebSphere Portal Enable for z/OS V6	Required for 64-bit processing.

**5.2.2.3 Toleration/Coexistence Requisites:** A toleration/coexistence requisite is defined as a product that must be present on a sharing system. These systems can be other systems in a multisystem environment (not necessarily sysplex), a shared DASD environment (such as test and production), or systems that reuse the same DASD at different time intervals.

WebSphere Process Server has no toleration/coexistence requisites.

**5.2.2.4 Incompatibility (Negative) Requisites:** A negative requisite identifies products that must *not* be installed on the same system as this product.

WebSphere Process Server has no negative requisites.

## 5.2.3 DASD Storage Requirements

WebSphere Process Server libraries can reside on all z/OS or z/OS.e supported DASD types.

Figure 10 lists the total space required for each type of library.

Figure 10 (Page 1 of 2). Total DASD Space Required by WebSphere Process Server

Library Type	Total Space Required (3390 Tracks)	Component
Target	1850	WebSphere Application Server
Target	24	WebSphere Process Server
Target	20	WebSphere Application Server for z/OS V6.1.0 Optional Materials (JIWO610)
Distribution	18555	WebSphere Application Server
Distribution	11544	WebSphere Process Server

Figure 10 (Page 2 of 2). Total DASD Space Required by WebSphere Process Server

Library Type	Total Space Required (3390 Tracks)	Component
Distribution	30	WebSphere Application Server for z/OS V6.1.0 Optional Materials (JIWO610)
HFS or zFS	28050	WebSphere Application Server
HFS or zFS	11600	WebSphere Process Server
HFS	27000	WebSphere Application Server for z/OS V6.1.0 Optional Materials (JIWO610)

**Notes:**

1. IBM recommends use of system determined block sizes for efficient DASD utilization for all non-RECFM U data sets. For RECFM U data sets, IBM recommends a block size of 32760, which is the most efficient from a performance and DASD utilization perspective.

2. Abbreviations used for the data set type are:

- U** Unique data set, allocated by this product and used only by this product. To determine the correct storage needed for this data set, this table provides all required information; no other tables (or Program Directories) need to be referenced for the data set size.
- S** Shared data set, allocated by this product and used by this product and others. To determine the correct storage needed for this data set, the storage size given in this table needs to be added to other tables (perhaps in other Program Directories). If the data set already exists, it must have enough free space to accommodate the storage size given in this table.
- E** Existing shared data set, used by this product and others. This data set is NOT allocated by this product. To determine the correct storage needed for this data set, the storage size given in this table needs to be added to other tables (perhaps in other program directories). This existing data set must have enough free space to accommodate the storage size given in this table.

If you currently have a previous release of this product installed in these libraries, the installation of this release will delete the old one and reclaim the space used by the old release and any service that had been installed. You can determine whether or not these libraries have enough space by deleting the old release with a dummy function, compressing the libraries, and comparing the space requirements with the free space in the libraries.

For more information on the names and sizes of the required data sets, please refer to 6.1.8, "Allocate SMP/E Target and Distribution Libraries" on page 27.

3. Abbreviations used for the HFS or zFS Path type are:

- N** New path, created by this product.
- X** Path created by this product, but may already exist from a previous release.
- P** Previously existing path, created by another product.

4. All target and distribution libraries listed have the following attributes:

- The default name of the data set may be changed.
  - The default block size of the data set may be changed.
  - The data set may be merged with another data set that has equivalent characteristics.
  - The data set may be either a PDS or a PDSE, unless PDSE is explicitly specified.
5. All target libraries listed have the following attributes:
- The data set may be SMS-managed.
  - It is not required for the data set to be SMS-managed.
  - It is not required for the data set to reside on the IPL volume.
  - The values in the "Member Type" column are not necessarily the actual SMP/E element types identified in the SMPMCS.
6. All target libraries listed which contain load modules have the following attributes: (See the customization instruction for details)
- Some target libraries or library members must be placed in the LPA.
  - Some target libraries or library members must be placed in the LNKLST.
  - Some target libraries must be APF-authorized.
7. All of the storage requirements quoted for WebSphere Application Server are copied from the WebSphere Application Server for z/OS V6.1.0 Program Directory (G111-2825-06).

Figure 11. Storage Requirements for SMP/E Work Data Sets

<b>Library DDNAME</b>	<b>T Y P E</b>	<b>O R G</b>	<b>R E C F M</b>	<b>L R E C L</b>	<b>No. of 3390 Trks</b>	<b>No. of DIR Blks</b>
SMPWRK1	E	PDS	FB	80	120	10
SMPWRK2	E	PDS	FB	80	30	10
SMPWRK3	E	PDS	FB	80	9500	150
SMPWRK4	E	PDS	FB	80	80	10
SMPWRK6	E	PDS	FB	80	4100	300
SYSUT1	E	SEQ	--	--	7500	0
SYSUT2	E	SEQ	--	--	30	0
SYSUT3	E	SEQ	--	--	30	0
SYSUT4	E	SEQ	--	--	30	0

If the table indicates that the SMPLTS data set must be a PDSE, but, your existing SMPLTS is a PDS, you will need to allocate a new PDSE and copy you existing SMPLTS into it and then change the SMPLTS DDDEF entry to indicate the new PDSE data set.

Figure 12. Storage Requirements for SMP/E Data Sets

Library DDNAME	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
SMPLTS	E	PDSE	U	0	6535	-
SMPMTS	E	PDS	FB	80	15	80
SMPPTS	E	PDS	FB	80	8000	80
SMPCDS	E	PDS	FB	80	15	80
SMPSTS	E	PDS	FB	80	15	80

The following figures describe the target and distribution libraries and HFS or zFS paths required to install WebSphere Process Server. The storage requirements of WebSphere Process Server must be added to the storage required by other programs having data in the same library or path.

The data in these tables should be used when determining which libraries can be merged into common data sets. In addition, because some ALIAS names may not be unique, ensure that no naming conflicts will be introduced before merging libraries.

Figure 13 (Page 1 of 2). Storage Requirements for WebSphere Process Server Target Libraries

Library DDNAME	Member Type	Target Volume	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
SBBOCLIB	Clist	TVOL1	U	PDS	FB	80	20	5
SBBODSD	DATA	TVOL2	U	PDSE	FB	80	60	-
SBBOEXEC	EXEC	TVOL1	U	PDS	VB	255	10	5
SBBOJCL	Sample	TVOL2	U	PDS	FB	80	10	5
SBBOLD2	LMOD	TVOL1	U	PDSE	U	0	10	-
SBBOLOAD	LMOD	TVOL1	U	PDSE	U	0	1467	-
SBBOLPA	LMOD	TVOL1	U	PDSE	U	0	21	-
SBBOMAC	MACRO	TVOL2	U	PDS	FB	80	10	5
SBBOMIG	LMOD	TVOL1	U	PDSE	U	0	41	-
SBBOMJPN	Message	TVOL1	U	PDS	FB	80	10	5
SBBOMLIB	Message	TVOL1	U	PDS	FB	80	10	5
SBBOMSG	Message	TVOL1	U	PDS	VB	255	10	5
SBBOPJPN	Panel	TVOL1	U	PDS	FB	80	30	10

Figure 13 (Page 2 of 2). Storage Requirements for WebSphere Process Server Target Libraries

Library DDNAME	Member Type	Target Volume	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
SBBOPLIB	Panel	TVOL1	U	PDS	FB	80	30	10
SBBOSLB2	SKEL	TVOL1	U	PDS	VB	255	14	5
SBBOSLIB	SKEL	TVOL1	U	PDS	FB	80	40	10
SBPZEXEC	EXEC	TVOL1	U	PDSE	VB	255	10	-
SBPZJCL	Sample	TVOL2	U	PDSE	FB	80	14	-
SIWOEXEC	EXEC	TVOL1	U	PDS	VB	255	10	5
SIWOJCL	Sample	TVOL2	U	PDS	FB	80	10	5

Figure 14. WebSphere Process Server HFS or zFS Paths

DDNAME	T Y P E	Path Name
SBBOBIN1	N	/usr/lpp/zWebSphere/V6R1/bin/IBM/
SBBODWN	N	/usr/lpp/zWebSphere/V6R1/downloads2/IBM/
SBBOEBCD	N	/usr/lpp/zWebSphere/V6R1/IBM/
SBBOJAR	N	/usr/lpp/zWebSphere/V6R1/IBM/
SBBOEXP1	N	/usr/lpp/zWebSphere/V6R1/lib/IBM/
SBBOANT	N	/usr/lpp/zWebSphere/V6R1/IBM/
SBBOZAR	N	/usr/lpp/zWebSphere/V6R1/IBM/
SBPZANT	N	/usr/lpp/zWPS/V6R2/IBM/
SBPZEBCD	N	/usr/lpp/zWPS/V6R2/IBM/
SGLDHCLI	P	/usr/lpp/ldapclient/IBM/
SGSKHFS	P	/usr/lpp/gskssl/IBM/
SIMWSA	P	/usr/lpp/internet/samples/API/IBM/
SIWOBIN1	N	/usr/lpp/zWebSphere_OM/V6R1/IBM/

Figure 15. Storage Requirements for WebSphere Process Server Distribution Libraries

<b>Library DDNAME</b>	<b>T Y P E</b>	<b>O R G</b>	<b>R E C F M</b>	<b>L R E C L</b>	<b>No. of 3390 Trks</b>	<b>No. of DIR Blks</b>
ABBOANT	U	PDS	VB	255	9388	550
ABBOCLIB	U	PDS	FB	80	20	10
ABBOEBCD	N	PDS	VB	31000	14	10
ABBOEXEC	U	PDS	VB	255	10	5
ABBOEXP	U	PDS	FB	80	41	5
ABBOINC	U	PDS	VB	255	15	5
ABBOJAR	U	PDS	VB	255	7000	50
ABBOJCL	U	PDS	FB	80	10	5
ABBOMJPN	U	PDS	FB	80	10	5
ABBOMAC	U	PDS	FB	80	10	5
ABBOMLIB	U	PDS	FB	80	10	5
ABBOMSG	U	PDS	VB	255	10	5
ABBOOBJ	U	PDSE	U	0	1101	-
ABBOPJPN	U	PDS	FB	80	27	10
ABBOPLIB	U	PDS	FB	80	27	10
ABBOSLB2	U	PDS	VB	255	14	5
ABBOSLIB	U	PDS	FB	80	38	10
ABBOZAR	U	PDS	VB	255	15626	10
ABPZANT	U	PDSE	VB	255	11500	-
ABPZEBCD	U	PDSE	VB	31000	20	-
ABPZEXEC	U	PDSE	VB	255	10	-
ABPZJCL	U	PDSE	FB	80	14	-
AIWOEXEC	U	PDS	VB	255	10	5
AIWOINC	U	PDS	VB	255	10	5
AIWOJCL	U	PDS	FB	80	10	5



**Notes:**

1. IBM recommends the following Distribution Library Data Set secondary allocation:
  - ABBOZAR 1000 tracks
2. WebSphere Process Server will require several thousand additional tracks (3390) for run-time data sets; the amount of space depends on the application server structure to be used, the applications to be run and the amount of data storage the applications will require.
3. WebSphere Process Server requires significantly larger amounts of HFS or zFS storage for downloadable Application Server Client code. See 6.1.8, “Allocate SMP/E Target and Distribution Libraries” on page 27 for more information.

---

## 5.3 FMIDs Deleted

Installing WebSphere Process Server may result in the deletion of other FMIDs. To see what FMIDs will be deleted, examine the ++VER statement in the product's SMPMCS.

If you do not wish to delete these FMIDs at this time, you must install WebSphere Process Server into separate SMP/E target and distribution zones.

These FMIDs will not automatically be deleted from the Global Zone. Consult the SMP/E manuals for instructions on how to do this.

---

## 5.4 Special Considerations

WebSphere Process Server is a functional successor to the following products:

- WebSphere Business Integration Server Foundation Version 5.1 (5655-L85)
- WebSphere Process Server 6.0.1 (5655-N53 )
- WebSphere Process Server 6.0.2 (5655-N53)
- WebSphere Process Server 6.1 (5655-N53)

The IBM Software Development Kit for z/OS Java 2 Technology Edition, Version 5.0, which is included as part of WebSphere Process Server, is a functional successor to various Java products from IBM, including those shipped with previous releases of WebSphere Application Server for z/OS and OS/390.

If you have previously installed any of these products, you should take the following considerations into account when installing WebSphere Process Server.

## 5.4.1 SMP/E Considerations

IBM recommends that you install WebSphere Process Server into a new set of SMP/E zones, including SMPCSI, target, distribution, and HFS or zFS data sets, to allow independent maintenance of WebSphere Application Server, z/OS, and other subsystems. This program directory provides sample jobs and instructions to create such an SMP/E environment.

If you install WebSphere Process Server into SMP/E target and distribution zones that contain a previous WebSphere Application Server release, you must completely remove the old release from the target and distribution zones **before** installing the new release. This can be done by receiving, applying, and accepting a "dummy sysmod" such as the following:

```
//SMPPTFIN DD *
++FUNCTION(DELWAS4) .
++VER(Z038) DELETE(H28W410) .
//SMPCNTL DD *
  SET BDY(GLOBAL).
  RECEIVE .
  SET BDY(WASTZN).
  APPLY S(DELWAS4) C(ALL).
  SET BDY(WASDZN).
  ACCEPT S(DELWAS4) C(ALL).
  SET BDY(WASTZN).
  UCLIN.
  DEL SYSMOD(DELWAS4).
  DEL SYSMOD(H28W410) .
  ENDUCL.
  SET BDY(WASDZN).
  UCLIN.
  DEL SYSMOD(DELWAS4).
  DEL SYSMOD(H28W410) .
  ENDUCL.
  SET BDY(GLOBAL).
  REJECT S(H28W410) .
```

This will remove the old WebSphere Application Server release from target and distribution libraries as well as from the SMPCSI; therefore, you may wish to make copies of these libraries before applying the sysmod above. When the old WebSphere Application Server release has been deleted, remove any DDDEFs for the old release from the target and distribution zones, and install the new WebSphere Application Server release with new target and distribution data sets, using the instructions in this program directory.

## 5.4.2 Selecting Driving System Mount points

During installation of WebSphere Process Server on the driving system, the target HFS or zFS file systems must be mounted at the following mount points:

- PathPrefix-/usr/lpp/zWPS/V6R2
- PathPrefix-/usr/lpp/zWebSphere/V6R1
- PathPrefix-/usr/lpp/zWebSphere\_OM/V6R1

where -PathPrefix- is an HFS or zFS path prefix such as /SERVICE or /WAS61. Use of a path prefix allows maintenance to be applied to a copy of the WebSphere Application Server HFS or zFS data sets without disturbing the production HFS or zFS data sets. For more information on the use of an HFS or zFS path prefix during product maintenance, see the UNIX System Services Planning book for your release of z/OS.

If you use a separate HFS or zFS for the downloadable Application Server Clients in WebSphere Application Server, mount it at:

- PathPrefix-/usr/lpp/zWebSphere/V6R1/downloads2

before applying maintenance.

Care must be taken that maintenance is applied to the proper HFS or zFS. Be sure to verify that the correct HFS or zFS is mounted at your service mount point(s) whenever maintenance is applied.

## 5.4.3 Selecting Target System Mount points

During customization and operation of WebSphere Process Server on the target system, the target HFS or zFS file system must be mounted at the following mount point:

- A WebSphere Process Server mount point, normally /usr/lpp/zWPS/V6R2
- A WebSphere mount point, normally /usr/lpp/zWebSphere/V6R1
- A WebSphere Optional Materials mount point, normally /usr/lpp/zWebSphere\_OM/V6R1

If you use a separate HFS or zFS for the downloadable Application Server Clients in WebSphere Application Server, mount it at:

- /usr/lpp/zWebSphere/V6R1/downloads2

on those systems from which you want to download the Application Server Client code. The files in this HFS or zFS are not required for the product to run on z/OS.

**Notes:**

1. WebSphere Process Server also uses a customization HFS or zFS for each server node; by default, the initial customization HFS or zFS is mounted at: /zWPS/V6R2. Data in this HFS or zFS is **not** compatible with releases of WebSphere Application Server prior to WebSphere Process Server Version 6.1.0. Do not attempt to reuse a customization HFS or zFS from WebSphere Application Server V3.02, V4.0, V4.0.1, V5.0, or V5.1 with WebSphere Process Server.
2. Refer to the WebSphere Information Center Reference Library for migrating Version 5 servers to Version 6.

### **5.4.4 Removal of WebSphere Application Server Levels**

WebSphere Application Server versions prior to WebSphere Application Server for z/OS V6.1.0 must be maintained until all applications have been migrated to Version 6.1.0

Refer to the WebSphere Application Server for z/OS information center for information about migrating to V6.1.0

---

## 6.0 Installation Instructions

This chapter describes the installation method and the step-by-step procedures to install and to activate the functions of WebSphere Process Server, including WebSphere Application Server for z/OS.

This release of WebSphere Process Server is installed using the SMP/E RECEIVE, APPLY and ACCEPT commands. The SMP/E dialogs may be used to accomplish the SMP/E installation steps.

WebSphere Process Server can be installed into new or existing SMP/E zones.

---

### 6.1 Installing WebSphere Application Server

Certain installation steps must be run from a user ID that is defined to UNIX Systems Services, and has the following attributes:

- UID(0) or READ access or higher to the BPX.SUPERUSER facility class.
- READ access or higher to the BPX.FILEATTR.PROGCTL and BPX.FILEATTR.APF and BPX.FILEATTR.SHARELIB facility classes.

This product is available as a Web download package, or in the customized offerings. If you are downloading this product from the Web, follow the instructions below. If you have received this product from customized offerings, go to 6.1.2, "SMP/E Considerations for Installing WebSphere Application Server" on page 24.

#### 6.1.1 SMP/E Considerations for Using the SMP/E Web Download

The SMP/E Web download package for WebSphere Application Server is packaged using the SMP/E GIMZIP function, which was introduced in SMP/E for z/OS V3.1. Although GIMZIP and GIMUNZIP are used for the packaging, the full SMP/E RECEIVE FROMNETWORK function is not available with this package. The SMP/E GIMUNZIP function is required to process the downloaded package. Refer to z/OS SMP/E Reference for information about using GIMZIP and GIMUNZIP. You need to ensure that you have met the driving system requirements as documented in Driving System Requirements.

You will need to perform the following tasks:

1. For a description of the GIMZIP and GIMUNZIP function, refer to the SMP/E Web page at:  
<http://www.ibm.com/servers/eserver/zseries/zos/smpe/>.  
Ensure that configuration requirements for using GIMUNZIP have been completed.
2. Allocate a R/W HFS or zFS directory on the z/OS system where the package will be staged. This is the repository for the download package.
3. Download the Web package. The package is available from the following Web site:  
<https://www14.software.ibm.com/webapp/ShopzSeries/ShopzSeries.jsp>.

There are two parts of the package:

a. bbo.README.txt

This file contains a sample job that performs the following tasks. It must be updated to reflect your environment. Make sure this file is transferred from the download site as a text file.

- Executes the z/OS UNIX System Services UNIX System Services pax command to extract the GIMZIP archives from the download package.
- Executes the GIMUNZIP program to expand the GIMZIP archives and places their contents in data sets that can be processed by SMP/E.
- Executes the SMP/E RECEIVE from DASD function to receive the FMID.

b. bbo.pax.Z

This pax archive file contains the SMP/E MCS and the associated RELFILES. This must be downloaded to a node that has connectivity to the target z/OS system. Transfer the file to the host using binary format.

4. Run the sample job in bsb.README.txt. This job will perform the required tasks up to and including the SMP/E RECEIVE from DASD step.
5. Complete the installation using the instructions in this program directory.

## 6.1.2 SMP/E Considerations for Installing WebSphere Application Server

IBM recommends installing WebSphere Application Server into a new set of SMP/E zones, including target, distribution, and HFS or zFS data sets. This allows separate maintenance of z/OS and WebSphere software. Sample jobs BBOCSICR and BBOZNCRT can be customized for your system and used to create a new CSI and SMP/E TARGET and DLIB zones. These jobs can be found in the product relfile IBM.H28W610.F1 and IBM.H28W610.F4, which is loaded during SMP/E processing; see Figure 16 on page 25 for a list of sample jobs.

If you choose to install WebSphere Application Server into existing SMP/E target and distribution zones, be sure to remove any previous versions of WebSphere Application Server from the zones and remove the previous version's DDDEFs **before** installing the new version. See 5.4.1, "SMP/E Considerations" on page 20 for more information.

WebSphere Application Server for z/OS V6.1.0 installation does not require a DDDEF for SYSLIB; however, SMP/E APPLY processing expects to have one. If necessary, create DDDEFs for SMPMTS and SYS1.MACLIB; and create a SYSLIB DDDEF that points to a concatenation of these two data sets. See IBM SMP/E for z/OS and OS/390 Reference for more information about the SYSLIB concatenation.

### 6.1.3 Sample Jobs

Sample jobs to allocate the target and distribution libraries, set up directories, and create DDDEF entries for the WebSphere Application Server for z/OS elements have been provided.

Figure 16 on page 25 lists the sample jobs for WebSphere Application Server.

<i>Figure 16. Sample Installation Jobs</i>			
<b>Job Name</b>	<b>Job Type</b>	<b>Description</b>	<b>RELFILE</b>
BBOCSICR	Setup	Sample job to create an SMP/E global zone	IBM.H28W610.F1
BBOZNCRT	Setup	Sample job to create SMP/E target and distribution zones	IBM.H28W610.F1
BBOXZDEF	Setup	Sample job to add additional target zone definitions for cross-zone prerequisite checking	IBM.H28W610.F1
BBOALLOC	ALLOCATE	Sample job to allocate target and distribution libraries for WebSphere Application Server	IBM.H28W610.F1
BBOISMKD	MKDIR	Sample job to invoke the supplied BBOMKDIR EXEC to create HFS paths for WebSphere Application Server	IBM.H28W610.F1
BBODDDEF	DDDEF	Sample job to define SMP/E DDDEFs for WebSphere Application Server	IBM.H28W610.F1
BBOAPPLY	APPLY	Sample job to apply base and maintenance	IBM.H28W610.F1
BBOACCEP	ACCEPT	Sample job to accept base and maintenance	IBM.H28W610.F1

You can access the sample installation jobs by performing an SMP/E RECEIVE and then copying the jobs from the RELFILES to a work data set for editing and submission. See Figure 16 to find the appropriate RELFILE data set.

Each sample job contains comments with specific instructions for customization.

You may also choose to copy the jobs from the tape or product files by submitting the jobs below. Use either the //TAPEIN or the //FILEIN DD statement, depending on your distribution medium, and comment out or delete the other statement. Add a job card and change the lowercase parameters to uppercase values to meet your site's requirements before submitting.

```
//STEP1    EXEC PGM=IEBCOPY
//SYSPRINT DD SYSOUT=*
//TAPEIN   DD DSN=IBM.H28W610.F1,UNIT=tunit,
//          VOL=SER=vo1ser,LABEL=(x,SL),
//          DISP=(OLD,KEEP)
//FILEIN   DD DSN=IBM.H28W610.F1,UNIT=SYSALLDA,DISP=SHR,
//          VOL=SER=filevol
//OUT      DD DSNAME=jc1-library-name,
//          DISP=(NEW,CATLG,DELETE),
```

```
//          VOL=SER=dasdvol,UNIT=SYSALLDA,
//          SPACE=(TRK,(30,20,5))
//SYSUT3   DD UNIT=SYSALLDA,SPACE=(CYL,(1,1))
//SYSIN    DD *
          COPY INDD=xxxxIN,OUTDD=OUT
/*
```

In the sample above, update the statements as noted below:

If using TAPEIN:

**tunit** is the unit value matching the product tape.

**volser** is the volume serial matching the product tape.

**x** is the tape file number where the data set name is on the tape.

Refer to the documentation provided by CBPDO to see where IBM.H28W610.F1 is on the tape.

If using FILEIN

**filevol** is the volume serial of the DASD device where the downloaded files reside.

OUT

**jcl-library-name** is the name of the output data set where the sample jobs will be stored.

**dasdvol** is the volume serial of the DASD device where the output data set will reside.

SYSIN

**xxxxIN** is either TAPEIN or FILEIN depending on your input DD statement.

#### 6.1.4 Allocate SMP/E CSI (Optional)

If you are using an existing CSI, do not execute this job.

If you are allocating a new SMP/E CSI data set for this install, edit and submit sample job BBOCSICR to allocate the SMP/E CSI data set for WebSphere Application Server for z/OS. Consult the instructions in the sample job for more information.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

#### 6.1.5 Define New SMP/E TARGET and DLIB Zones (Optional)

Edit and submit sample job BBOZNCRT to define new SMP/E Target and Distribution zones. Consult the instructions in the sample job for more information.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

#### 6.1.6 Add Target Zones for Cross-Zone Prerequisite Checking

Because the WebSphere Application Server component has a number of maintenance requirements for the target z/OS systems, we recommend that you add the appropriate SMP/E target zones (z/OS, DB2, CICS, and IMS) to the WebSphere Application Server SMP/E global zone. This will allow SMP/E to check each zone for maintenance required by WebSphere Application Server for z/OS.



Customize and run the BBOXZDEF job to add target zones to the global zone which will be used for the SMP/E APPLY and ACCEPT steps below.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

### 6.1.7 Perform SMP/E RECEIVE

Having obtained WebSphere Application Server as part of a CBPDO, use the RCVPDO job found in the CBPDO RIMLIB data set to RECEIVE the H28W610 FMIDs as well as any service, HOLDDATA, included on the CBPDO tape. For more information, refer to the documentation included with the CBPDO.

The CBPDO contains all non-integrated PTFs for every WebSphere Application Server for z/OS FMID. (Cumulative service is included in CBPDO orders, so there is no separate cumulative service tape.) Depending on the options selected when you ordered the CBPDO, your order may contain service for other products in your profile.

To receive service for WebSphere Application Server for z/OS select FMID H28W610.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

### 6.1.8 Allocate SMP/E Target and Distribution Libraries

Edit and submit sample job BBOALLOC to allocate the SMP/E target and distribution libraries for WebSphere Application Server. Consult the instructions in the sample job for more information.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

### 6.1.9 Allocate HFS or zFS PATHS

Customize the sample job BBOISMKD to mount the WebSphere Application Server for z/OS product HFS(s) or zFS(s) and create the target directories needed to install the WebSphere Application Server component.

#### **Important!**

- The BBOISMKD and BBODDDEF jobs use -PathPrefix- to represent a service directory on your driving system. It is assumed that you will be mounting WebSphere Application Server for z/OS data sets under a service directory that already contains the /usr and /usr/lpp directories. If you specify a -PathPrefix- directory which does not contain /usr and /usr/lpp subdirectories, you must manually create these subdirectories before running the BBOISMKD job. If -PathPrefix-/usr/lpp is not a read/write HFS or zFS, you will need to manually create some additional subdirectories as well. See the comments in the BBOISMKD job for further information.
- The BBOISMKD job will mount the product HFS or zFS and create all product directories in it.

Run the customized sample job BBOISMKD under a user ID that has certain system privileges; refer to 6.1, "Installing WebSphere Application Server" on page 23 for a summary of the privileges that you need to run the BBOISMKD successfully.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

Check the job output to verify that all directories have been created.

Verify that the product HFS or zFS is mounted at:

-PathPrefix-/usr/lpp/zWebSphere/V6R1

If you are making a second product HFS or zFS for downloads, verify that it is mounted at:

-PathPrefix-/usr/lpp/zWebSphere/V6R1/downloads2

### 6.1.10 Create DDDEF Entries

Edit and submit sample job BBODDDEF to create DDDEF entries for the SMP/E target and distribution libraries. Consult the instructions in the sample job for more information.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

### 6.1.11 Perform SMP/E APPLY

SMP/E apply processing for WebSphere Application Server for z/OS V6.1.0 uses the Java SDK JAR command to extract certain files. In order for the JAR command to run correctly, SMP/E must be running with the fix for APAR IO04924, and the user ID used to run the BBOAPPLY job must have the SDK bin directory in its Unix System Services PATH.

If BBOZNCRT was not run, set your SMPJHOME DDDEF to your Java PATH. For example:

PATH=/usr/lpp/java/IBM/J1.4/bin

Test the availability of the JAR command by logging in to the OMVS shell with the user ID that will be used to run the BBOAPPLY job and entering the command "jar"; the JAR command should print its usage information. See the z/OS UNIX System Services User's Guide for information about using /etc/profile and \$HOME/.profile scripts.

Run the SMP/E APPLY job with a user ID that has certain system privileges; refer to 6.1, "Installing WebSphere Application Server" on page 23 for a summary of the privileges that you need to run the BBOAPPLY successfully.

Customize and run the sample job BBOAPPLY to perform an SMP/E APPLY CHECK of the WebSphere Application Server base and service.

To receive the full benefit of the SMP/E Causer SYSMOD Summary Report, do *not* bypass any of the following on the APPLY CHECK: PRE, ID, REQ, and IFREQ. This is because the SMP/E root cause analysis identifies the cause only of **ERRORS** and not of **WARNINGS** (bypassed SYSMODs are treated as warnings, not errors, by SMP/E). The GROUPEXTEND operand indicates that SMP/E should APPLY all requisite SYSMODs. The requisite SYSMODs may be part of other products; review the APPLY CHECK output carefully before proceeding.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly (or a return code of 4, if any HOLDS are bypassed).

When you have resolved any problems indicated by the APPLY CHECK, remove the CHECK operand and run the job again to perform the APPLY.

**Expected Return Codes and Messages from APPLY:** You will receive a return code of 0 if this job runs correctly (or a return code of 4, if any HOLDS are bypassed).

## 6.1.12 Perform SMP/E ACCEPT

Customize and run the sample job BBOACCEP to perform an SMP/E ACCEPT CHECK of the WebSphere Application Server base and service.

To receive the full benefit of the SMP/E Causer SYSMOD Summary Report, do *not* bypass any of the following on the ACCEPT CHECK: PRE, ID, REQ, and IFREQ. This is because the SMP/E root cause analysis identifies the cause only of **ERRORS** and not of **WARNINGS** (bypassed SYSMODs are treated as warnings, not errors, by SMP/E).

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

When you have resolved any problems indicated by the ACCEPT CHECK, remove the CHECK operand and run the job again to perform the ACCEPT.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

---

## 6.2 Installing the WebSphere Application Server for z/OS V6.1.0 Optional Materials

The optional materials for WebSphere Application Server for z/OS will be shipped as service to the function SYSMOD JIWO610. Follow the instructions in section to install the function SYSMOD and prepare the optional materials HFS.

The WebSphere Application Server for z/OS optional materials must be installed into SMP/E target and distribution zones that contain the WebSphere Application Server for z/OS base product. Install the JIWO610 function SYSMOD (and its service) into the same SMP/E zones used for H28W610.

## 6.2.1 Sample Jobs

Sample jobs to allocate the target and distribution libraries, set up HFS directories, and create DDDEF entries for the WebSphere Application Server for z/OS V6.1.0 Optional Materials have been provided.

Figure 17 on page 30 lists the sample jobs for WebSphere Application Server for z/OS V6.1.0 Optional Materials.

<i>Figure 17. Sample Installation Jobs - JIWO610</i>			
<b>Job Name</b>	<b>Job Type</b>	<b>Description</b>	<b>RELFILE</b>
IWOALLOC	ALLOCATE	Sample job to add additional target zone definitions for WebSphere Application Server for z/OS V6.1.0 Optional Materials	IBM.JIWO610.F1
IWOISMKD	MKDIR	Sample job to invoke the supplied IWOMKDIR EXEC to create HFS paths for WebSphere Application Server for z/OS V6.1.0 Optional Materials	IBM.JIWO610.F1
IWODDDEF	DDDEF	Sample job to define SMP/E DDDEFs for WebSphere Application Server for z/OS V6.1.0 Optional Materials	IBM.JIWO610.F1
IWOAPPLY	APPLY	Sample job to apply base and maintenance	IBM.JIWO610.F1
IWOACCEP	ACCEPT	Sample job to accept base and maintenance	IBM.JIWO610.F1

You can access the sample installation jobs by performing an SMP/E RECEIVE and then copying the jobs from the RELFILEs to a work data set for editing and submission. See Figure 17 to find the appropriate RELFILE data set.

Each sample job contains comments with specific instructions for customization.

You may also choose to copy the jobs from the tape or product files by submitting the job below. Use either the //TAPEIN or the //FILEIN DD statement, depending on your distribution medium, and comment out or delete the other statement. Add a job card and change the lowercase parameters to uppercase values to meet your site's requirements before submitting.

```
//STEP1    EXEC PGM=IEBCOPY
//SYSPRINT DD SYSOUT=*
//TAPEIN   DD DSN=IBM.JIWO610.F1,UNIT=tunit,
//          VOL=SER=volser,LABEL=(x,SL),
//          DISP=(OLD,KEEP)
//FILEIN   DD DSN=IBM.JIWO610.F1,UNIT=SYSALLDA,DISP=SHR,
//          VOL=SER=filevol
//OUT      DD DSNAME=jc1-library-name,
//          DISP=(NEW,CATLG,DELETE),
//          VOL=SER=dasdvol,UNIT=SYSALLDA,
```

```
//          SPACE=(TRK,(30,20,5))
//SYSUT3   DD UNIT=SYSALLDA,SPACE=(CYL,(1,1))
//SYSIN    DD *
          COPY INDD=xxxxIN,OUTDD=OUT
/*
```

In the sample above, update the statements as noted below:

If using TAPEIN:

**tunit** is the unit value matching the product tape.

**volser** is the volume serial matching the product tape.

**x** is the tape file number where the data set name is on the tape.

Refer to the documentation provided by CBPDO to see where IBM.JIWO610.F1 is on the tape.

If using FILEIN

**filevol** is the volume serial of the DASD device where the downloaded files reside.

OUT

**jcl-library-name** is the name of the output data set where the sample jobs will be stored.

**dasdvol** is the volume serial of the DASD device where the output data set will reside.

SYSIN

**xxxxIN** is either TAPEIN or FILEIN depending on your input DD statement.

## 6.2.2 Perform SMP/E RECEIVE

Receive function SYSMOD and service for the WebSphere Application Server for z/OS V6.1.0 Optional Materials by running the RCVPDO job and specifying FMID **JIWO610**. See the *MVS CBPDO Memo to User Extension* included with the CBPDO.

The CBPDO contains all non-integrated PTFs for every WebSphere Application Server for z/OS V6.1.0 Optional Materials FMID. (Cumulative service is included in CBPDO orders, so there is no separate cumulative service tape.) Depending on the options selected when you ordered the CBPDO, your order may contain service for other products in your profile.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

## 6.2.3 Define Target and Distribution Libraries

Customize and run the IWOALLOC sample job to define target and distribution libraries for the WebSphere Application Server for z/OS V6.1.0 Optional Materials.

Make sure the data sets are allocated on the desired volumes.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

## 6.2.4 Set Up HFS Directories

Customize the sample job IWOISMKD to mount the WebSphere Application Server for z/OS optional materials HFS and create the HFS target directories needed to install the WebSphere Application Server for z/OS V6.1.0 Optional Materials component.

### Important!

- The IWOISMKD and IWODDDEF jobs use `-PathPrefix-` to represent a service directory on your driving system. It is assumed that you will be mounting WebSphere Application Server for z/OS V6.1.0 Optional Materials HFS data sets under a service directory that already contains the `/usr` and `/usr/lpp` directories. If you specify a `-PathPrefix-` directory which does not contain `/usr` and `usr/lpp` subdirectories, you must manually create these subdirectories before running the IWOISMKD job. If `-PathPrefix-/usr/lpp` is not a read/write HFS, you will need to manually create some additional subdirectories as well. See the comments in the IWOISMKD job for further information.
- The IWOISMKD job will mount the product HFS, create all product directories in it and create the base directory for WebSphere Application Server for z/OS V6.1.0 Optional Materials.

The customized sample job IWOISMKD must be run under a user ID with a number of system privileges; see 6.1, “Installing WebSphere Application Server” on page 23 for a summary of privileges that are needed to run IWOISMKD successfully

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

Check the job output to verify that all directories have been created.

Verify that the product HFS is mounted at

`-PathPrefix-/usr/lpp/zWebSphere_OM/V6R1`

## 6.2.5 Define SMP/E DDDEFs

Customize and run the sample job IWODDDEF to create SMP/E DDDEFs for target and distribution data sets and directories.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

## 6.2.6 Perform SMP/E APPLY

SMP/E apply processing for WebSphere Process Server uses the Java SDK JAR command to extract certain HFS files. In order for the JAR command to run correctly, SMP/E must be running with a fix for APAR IR54653, and the user ID used to run the IWOAPPLY job must have the SDK bin directory in its Unix System Services PATH. This can be accomplished in one of two ways:

1. Add an SDK bin directory containing the JAR command (such as /usr/lpp/java/IBM/J1.3/bin) to the PATH variable in /etc/profile before running the IWOAPPLY job. For example:

```
PATH=/usr/lpp/java/IBM/J1.3/bin:<rest of PATH>
```

2. Add an SDK bin directory to the PATH variable in a file named .profile in the HOME directory for the user ID used in running the IWOAPPLY job.

Test the availability of the JAR command by logging in to the OMVS shell with the user ID that will be used to run the IWOAPPLY job and entering the command "jar"; the JAR command should print its usage information. See the z/OS Unix System Services User's Guide for information about using /etc/profile and &HOME/.profile scripts.

The SMP/E apply job must be run with a user ID having a number of system privileges; see 6.1, "Installing WebSphere Application Server" on page 23 for a summary of privileges that are needed to run IWOISMKD successfully.

Customize and run the sample job IWOAPPLY to perform an SMP/E APPLY CHECK of the WebSphere Application Server for z/OS V6.1.0 Optional Materials. base and service.

To receive the full benefit of the SMP/E Cause SYSMOD Summary Report, do *not* bypass any of the following on the APPLY CHECK: PRE, ID, REQ, and IFREQ. This is because the SMP/E root cause analysis identifies the cause only of **ERRORS** and not of **WARNINGS** (bypassed SYSMODs are treated as warnings, not errors, by SMP/E).

**Note:** The GROUPEXTEND operand indicates that SMP/E should APPLY all requisite SYSMODS. The requisite SYSMODS may be part of other products; review the APPLY CHECK output carefully before proceeding.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly (or a return code of 4, if any HOLDS are bypassed).

Once you have resolved any problems indicated by the APPLY CHECK, remove the CHECK operand and run the job again to perform the APPLY.

### Expected Return Codes from APPLY:

You will receive a return code of 0 if this job runs correctly (or a return code of 4, if any HOLDS are bypassed).

## 6.2.7 Perform SMP/E ACCEPT

Customize and run the sample job IWOACCEP to perform an SMP/E ACCEPT CHECK of the WebSphere Application Server for z/OS V6.1.0 Optional Materials.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

To receive the full benefit of the SMP/E Causer SYSMOD Summary Report, do *not* bypass any of the following on the ACCEPT CHECK: PRE, ID, REQ, and IFREQ. This is because the SMP/E root cause analysis identifies the cause only of **ERRORS** and not of **WARNINGS** (bypassed SYSMODs are treated as warnings, not errors, by SMP/E).

Once you have resolved any problems indicated by the ACCEPT CHECK, remove the CHECK operand and run the job again to perform the ACCEPT.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

---

## 6.3 Installing WebSphere Process Server

All installation steps must be run from a user ID that is defined to UNIX Systems Services, and has the following attributes:

- UID(0) or READ access or higher to the BPX.SUPERUSER facility class.
- READ access or higher to the BPX.FILEATTR.PROGCTL and BPX.FILEATTR.APF and BPX.FILEATTR.SHARELIB facility classes.

This product is available as a Web download package, or in the customized offerings. If you are downloading this product from the Web, follow the instructions below. If you have received this product from customized offerings, go to 6.3.2, "SMP/E Considerations for Installing WebSphere Process Server" on page 35.

### 6.3.1 SMP/E Considerations for Using the SMP/E Web Download

The SMP/E Web download package for WebSphere Process Server is packaged using the SMP/E GIMZIP function, which was introduced in SMP/E for z/OS V3.1. Although GIMZIP and GIMUNZIP are used for the packaging, the full SMP/E RECEIVE FROMNETWORK function is not available with this package. The SMP/E GIMUNZIP function is required to process the downloaded package. Refer to z/OS SMP/E Reference for information about using GIMZIP and GIMUNZIP. You need to ensure that you have met the driving system requirements as documented in Driving System Requirements.

You will need to perform the following tasks:

1. For a description of the GIMZIP and GIMUNZIP function, refer to the SMP/E Web page at: <http://www.ibm.com/servers/eserver/zseries/zos/smpe/>.

Ensure that configuration requirements for using GIMUNZIP have been completed.



2. Allocate a R/W HFS or zFS directory on the z/OS system where the package will be staged. This is the repository for the download package.
3. Download the Web package. The package is available from the following Web site:  
<https://www14.software.ibm.com/webapp/ShopzSeries/ShopzSeries.jsp>.

There are two parts of the package:

a. bpz.README.txt

This file contains a sample job that performs the following tasks. It must be updated to reflect your environment. Make sure this file is transferred from the download site as a text file.

- Executes the z/OS UNIX System Services UNIX System Services pax command to extract the GIMZIP archives from the download package.
- Executes the GIMUNZIP program to expand the GIMZIP archives and places their contents in data sets that can be processed by SMP/E.
- Executes the SMP/E RECEIVE from DASD function to receive the FMID.

b. bpz.pax.Z

This pax archive file contains the SMP/E MCS and the associated RELFILES. This must be downloaded to a node that has connectivity to the target z/OS system. Transfer the file to the host using binary format.

4. Run the sample job in bsb.README.txt. This job will perform the required tasks up to and including the SMP/E RECEIVE from DASD step.
5. Complete the installation using the instructions in this program directory.

### 6.3.2 SMP/E Considerations for Installing WebSphere Process Server

WebSphere Process Server must be installed into the same Target and Distribution zones as WebSphere Application Server for z/OS.

### 6.3.3 Sample Jobs

Sample jobs to allocate the target and distribution libraries, set up directories, and create DDDEF entries for the WebSphere Process Server elements have been provided.

Figure 18 lists the sample jobs for WebSphere Process Server.

<i>Figure 18 (Page 1 of 2). Sample Installation Jobs</i>			
<b>Job Name</b>	<b>Job Type</b>	<b>Description</b>	<b>RELFILE</b>
BPZCSICR	Setup	Creates a new SMP/E Consolidated Software Inventory (CSI) global zone.	IBM.HWPS620.F1
BPZRECEV	RECIEVE	Performs the RECIEVE for the installation.	IBM.HWPS620.F1

Figure 18 (Page 2 of 2). Sample Installation Jobs

Job Name	Job Type	Description	RELFILE
BPZALLOC	ALLOCATE	Allocates the TARGET and DISTRIBUTION libraries.	IBM.HWPS620.F1
BPZALHFS	ALLOCATE	Allocates the HFS libraries.	IBM.HWPS620.F1
BPZALZFS	ALLOCATE	Allocates the zFS libraries.	IBM.HWPS620.F1
BPZISMKD	MKDIR	Runs the BBOMKDIR EXEC job to create file system paths for WebSphere Application Server.	IBM.HWPS620.F1
BPZZNCRT	Setup	Creates SMP/E TARGET and DISTRIBUTION zones.	IBM.HWPS620.F1
BPZZONES	Setup	Defines TARGET and DLIB zones for an already allocated CSI.	IBM.HWPS620.F1
BPZDDDEF	DDDEF	Defines SMP/E DDDEFs for WebSphere Application Server.	IBM.HWPS620.F1
BPZXZDEF	Setup	Adds additional target zone definitions for cross-zone prerequisite checking.	IBM.HWPS620.F1
BPZAPPLY	APPLY	Applies base and maintenance	IBM.HWPS620.F1
BPZACCEP	ACCEPT	Accept base and maintenance	IBM.HWPS620.F1

You can access the sample installation jobs by performing an SMP/E RECEIVE and then copying the jobs from the RELFILES to a work data set for editing and submission. See Figure 18 on page 35 to find the appropriate relfile data set.

The sample job below points to F1. You will also need to run the UNLOAD again for F4.

You might also choose to copy the jobs from the tape or product files by submitting the job below. Use either the //TAPEIN or the //FILEIN DD statement, depending on your distribution medium, and comment out or delete the other statement. Add a job card and change the lowercase parameters to uppercase values to meet your site's requirements before submitting.

```
//STEP1 EXEC PGM=IEBCOPY
//SYSPRINT DD SYSOUT=*
//TAPEIN DD DSN=IBM.HWPS620.F1,UNIT=tunit,
// VOL=SER=volser,LABEL=(x,SL),
// DISP=(OLD,KEEP)
//FILEIN DD DSN=IBM.HWPS620.F1,UNIT=SYSALLDA,DISP=SHR,
// VOL=SER=filevol
//OUT DD DSNAME=jcl-library-name,
// DISP=(NEW,CATLG,DELETE),
// VOL=SER=dasdvol,UNIT=SYSALLDA,
// SPACE=(TRK,(30,20,5))
//SYSUT3 DD UNIT=SYSALLDA,SPACE=(CYL,(1,1))
//SYSIN DD *
```

```
COPY INDD=xxxxIN,OUTDD=OUT
/*
```

In the sample above, update the statements as noted below:

If using TAPEIN:

**tunit** is the unit value matching the product tape.

**volser** is the volume serial matching the product tape.

**x** is the tape file number where the data set name is on the tape.

Refer to the documentation provided by CBPDO to see where IBM.HWPS620.F1 is on the tape.

If using FILEIN

**filevol** is the volume serial of the DASD device where the downloaded files reside.

OUT

**jcl-library-name** is the name of the output data set where the sample jobs will be stored.

**dasdvol** is the volume serial of the DASD device where the output data set will reside.

SYSDIN

**xxxxIN** is either TAPEIN or FILEIN depending on your input DD statement.

Customize each of the sample jobs listed in Figure 18 on page 35. Each sample job contains comments with specific instructions for customization.

### 6.3.4 Create CSI Global Zone

If you want to install WebSphere Process Server into a new CSI, customize and run the BPZCSICR job.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

### 6.3.5 Perform SMP/E RECEIVE

If you ordered WebSphere Process Server for z/OS V6.2.0 using CBPDO receive function SYSMOD and service by running the RCPDO job. For more information, refer to *MVS CBPDO Memo to User Extension*, which is included with the CBPDO.

The CBPDO contains all non-intergrated PTFs for every WebSphere Process Server FMID. (Cumulative service is including in CBPDO orders so there is no separate cumulative service tape). Depending on the options selected when you ordered the CBPDO, your order might contain service for other products in your profile.

If you ordered a stand-alone product tape instead of using CBPDO, customize and run the BPZRECEV job.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

### 6.3.6 Allocate SMP/E Target and Distribution Libraries

Customize and run sample job BPZALLOC to allocate the SMP/E target and distribution libraries for WebSphere Process Server. Refer to the instructions in the sample job for more information.

Make sure the data sets are allocated on the desired volumes.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

### 6.3.7 Create the USS File System

If you are installing in a zFS file system, customize and run the BPZALZFS sample job to define the file system libraries.

Otherwise, if you are installing in an HFS file system, customize and run the BPZALHFS sample job to define the file system libraries.

Run only one of these jobs.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

### 6.3.8 Allocate HFS or zFS PATHS

Customize the sample job BPZISMKD to mount the WebSphere Process Server for z/OS product file systems and create the target directories needed to install the WebSphere Process Server component.

#### Important!

The BPZISMKD and BPZDDDEF jobs use `-PathPrefix-` to represent a service directory on your driving system. It is assumed that you are mounting WebSphere Process Server HFS or zFS data sets under a service directory that already contains the `/usr` and `/usr/lpp` directories. If you specify a `-PathPrefix-` directory that does not contain `/usr` and `usr/lpp` subdirectories, you must manually create these subdirectories before running the BPZISMKD job. If `-PathPrefix-/usr/lpp` is not a read/write HFS or zFS, you must manually create some additional subdirectories as well. See the comments in the BPZISMKD job for further information.

Run the customized sample job BPZISMKD under a user ID that has certain system privileges; refer to 6.3, "Installing WebSphere Process Server" on page 34 for a summary of the privileges that you need to run the BPZISMKD successfully.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

Check the job output to verify that all directories have been created.

Verify that the product file system is mounted at:

-PathPrefix-/usr/lpp/zWPS/V6R2

### 6.3.9 Define Target and Distribution Zones.

To create a new global CSI containing data sets in target and distribution zones, customize and run the BPZZNCRT sample job.

To define new target and distribution zones on an already allocated CSI, customize and run the BPZZONES sample job.

### 6.3.10 Define SMP/E DDDEFs

Customize and run the sample job BPZDDDEF to create SMP/E DDDEFs for target and distribution data sets and directories. Make sure the call library DDDEFs point to the corresponding data sets for your z/OS target system.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

### 6.3.11 Add Target Zones for Cross-Zone Prerequisite Checking

Because the WebSphere Process Server component has a number of maintenance requirements for the target z/OS systems, add the appropriate SMP/E target zones (z/OS, DB2, CICS, and IMS) to the WebSphere Process Server SMP/E global zone. This will allow SMP/E to check each zone for maintenance required by WebSphere Process Server.

Customize and run the BPZXZDEF job to add target zones to the global zone which will be used for the SMP/E APPLY and ACCEPT steps below.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

### 6.3.12 Perform SMP/E APPLY

SMP/E apply processing for WebSphere Process Server for z/OS uses the Java SDK JAR command to extract certain files. In order for the JAR command to run correctly, SMP/E must have the fix for APAR IO04924 applied.

A new DDDEF entry named SMPJHOME in the target zone is required. The samples job (BPZZNCRT) includes a DDDEF entry to address this specific issue. For example:

```
//SMPJHOME DD PATH='/usr/lpp/java/IBM/J1.4/bin'
```

Run the SMP/E APPLY job with a user ID that has certain system privileges; refer to 6.3, "Installing WebSphere Process Server" on page 34 for a summary of the privileges that you need to run the BPZAPPLY successfully.

Customize and run the sample job BPZAPPLY to perform an SMP/E APPLY CHECK of the WebSphere Process Server base and service.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly (or a return code of 4, if any HOLDS are bypassed).

To receive the full benefit of the SMP/E Causer SYSMOD Summary Report, do *not* bypass any of the following on the APPLY CHECK: PRE, ID, REQ, and IFREQ. This is because the SMP/E root cause analysis identifies the cause only of **ERRORS** and not of **WARNINGS** (bypassed SYSMODs are treated as warnings, not errors, by SMP/E). The GROUPEXTEND operand indicates that SMP/E should APPLY all requisite SYSMODs. The requisite SYSMODs may be part of other products; review the APPLY CHECK output carefully before proceeding.

When you have resolved any problems indicated by the APPLY CHECK, remove the CHECK operand and run the job again to perform the APPLY.

**Expected Return Codes and Messages from APPLY:** You will receive a return code of 0 if this job runs correctly (or a return code of 4, if any HOLDS are bypassed).

### 6.3.13 Perform SMP/E ACCEPT

Customize and run the sample job BPZACCEP to perform an SMP/E ACCEPT CHECK of the WebSphere Process Server base and service.

If you are installing into an existing SMP/E CSI, the IEBCOPY utility needs to have at least 2M work area for the ACCEPT step. Add the following PARM to the IEBCOPY utility entry:

```
WORK=2M
```

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

To receive the full benefit of the SMP/E Causer SYSMOD Summary Report, do *not* bypass any of the following on the ACCEPT CHECK: PRE, ID, REQ, and IFREQ. This is because the SMP/E root cause analysis identifies the cause only of **ERRORS** and not of **WARNINGS** (bypassed SYSMODs are treated as warnings, not errors, by SMP/E).

The GROUPEXTEND operand indicates that SMP/E should ACCEPT all requisite SYSMODs. The requisite SYSMODs may be part of other products; review the ACCEPT CHECK output carefully before proceeding.

When you have resolved any problems indicated by the ACCEPT CHECK, remove the CHECK operand and run the job again to perform the ACCEPT.

**Expected Return Codes and Messages:** You will receive a return code of 0 if this job runs correctly.

---

## 6.4 Activating WebSphere Process Server

### 6.4.1 HFS Execution

If you choose to have the HFS or zFS in which you have installed WebSphere Process Server mounted in read-only mode during execution, then the following tasks are required to accomplish this:

If you have included a mount statement in BPXPRMxx PARMLIB member for this HFS, ensure it includes the operand MODE(READ).

To Change the HFS filesystem to read only in Unix System Services, execute the following USS commands:

1. `umount -o immediate pathname`
2. `mount -t hfs -d destdsys -f fsname -r pathname`

For a detailed explanation of the above commands, refer to the z/OS UNIX System Services Command Reference, listed in Figure 3 on page 5.

### 6.4.2 WebSphere Process Server configuration

WebSphere Process Server must be configured when SMP/E installation is complete. See the *WebSphere Process Server for z/OS installation topics* in the information center for more information on how to enable WebSphere Process Server for use, along with additional information from the WebSphere Process Server Infocenter, which is located at:

<http://publib.boulder.ibm.com/infocenter/dmndhelp/v6r2/index.jsp>

### 6.4.3 Mount the HFS or zFS Data Set on the Target System

Before proceeding with activation, copy the WebSphere Process Server , WebSphere Application Server and WebSphere Application Server for z/OS V6.1.0 Optional Materials HFS or zFS data sets from the driving system to the target system. Mount them on the target system at the target system mount point. See 5.4.3, “Selecting Target System Mount points” on page 21, for assistance in selecting the mount point. If you have selected the default mount points, you can use the following TSO commands on your target system to mount the HFS or zFS data set (if you are using zFS, replace HFS with ZFS. This must reflect what you decided at the ALLOCATE and MKDIR steps):

```
MOUNT FILESYSTEM('h1q.SBPZHFS')
MOUNTPOINT('/usr/lpp/zWPS/V6R2') TYPE(HFS) MODE(READ)

MOUNT FILESYSTEM('h1q.SBBOHFS')
MOUNTPOINT('/usr/lpp/zWebSphere/V6R1') TYPE(HFS) MODE(READ)

MOUNT FILESYSTEM('h1q.SIWOHFS')
MOUNTPOINT('/usr/lpp/zWebSphere_OM/V6R1') TYPE(HFS) MODE(READ)
```

Add these mounts to your BPXPRMxx member in parmlib to ensure that these file systems are mounted at IPL. To apply service to the WebSphere Process Server for z/OS V6.2.0 product you will need to perform the following tasks:

1. Apply Service on the driving system.
2. Copy the WebSphere Process Server for z/OS V6.2.0 file system from the driving system to the target system.
3. Stop any servers on the target system.
4. Unmount the HFS or zFS data set from the target mount point.
5. Mount the new serviced copy at the target mount point and restart the server or servers.

#### **6.4.4 Activating WebSphere Process Server**

The WebSphere Process Server for z/OS Information Center contains the step-by-step procedures to complete the installation and configuration of WebSphere Process Server.



---

## 7.0 Notices

References in this document to IBM products, programs, or services do not imply that IBM intends to make these available in all countries in which IBM operates. Any reference to an IBM product, program, or service is not intended to state or imply that only IBM's product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe on any of IBM's intellectual property rights may be used instead of the IBM product, program, or service. Evaluation and verification of operation in conjunction with other products, except those expressly designated by IBM, is the user's responsibility.

APAR numbers are provided in this document to assist in locating PTFs that may be required. Ongoing problem reporting may result in additional APARs being created. Therefore, the APAR lists in this document may not be complete. To obtain current service recommendations and to identify current product service requirements, always contact the IBM Customer Support Center or use S/390 SoftwareXcel to obtain the current "PSP Bucket".

IBM may have patents or pending patent applications covering subject matter in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to the

IBM Director of Licensing  
IBM Corporation  
North Castle Drive  
Armonk, New York 10504-1785  
USA

For online versions of this book, we authorize you to:

- Copy, modify, and print the documentation contained on the media, for use within your enterprise, provided you reproduce the copyright notice, all warning statements, and other required statements on each copy or partial copy.
- Transfer the original unaltered copy of the documentation when you transfer the related IBM product (which may be either machines you own, or programs, if the program's license terms permit a transfer). You must, at the same time, destroy all other copies of the documentation.

You are responsible for payment of any taxes, including personal property taxes, resulting from this authorization.

THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Some jurisdictions do not allow the exclusion of implied warranties, so the above exclusion may not apply to you.

Your failure to comply with the terms above terminates this authorization. Upon termination, you must destroy your machine readable documentation.

---

## 7.1 Trademarks

The following terms are trademarks of the IBM Corporation in the United States or other countries or both:

CICS	MVS/ESA	VTAM
DB2	OS/390	WebSphere
IBM	RACF	z/OS
IBMLink	RETAIN	z/VM
IMS	S/390	z/Architecture
Language Environment	SP	zSeries
MQSeries	SystemPac	

The following terms are trademarks of other companies as follows:

JAVA	Java and all Java-based trademarks and logos are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.
UNIX	UNIX is a registered trademark of The Open Group in the United States and other countries.

# Reader's Comments

## Program Directory for WebSphere Process Server for z/OS V6.2.0, December 2008

You may use this form to comment about this document, its organization, or subject matter with the understanding that IBM may use or distribute whatever information you supply in any way it believes appropriate without incurring any obligation to you.

For each of the topics below please indicate your satisfaction level by circling your choice from the rating scale. If a statement does not apply, please circle N.

RATING SCALE						
very satisfied	<----->				very dissatisfied	not applicable
1	2	3	4	5	N	

	Satisfaction					
Ease of product installation	1	2	3	4	5	N
Contents of Program Directory	1	2	3	4	5	N
Installation Verification Programs	1	2	3	4	5	N
Time to install the product	1	2	3	4	5	N
Readability and organization of Program Directory tasks	1	2	3	4	5	N
Necessity of all installation tasks	1	2	3	4	5	N
Accuracy of the definition of the installation tasks	1	2	3	4	5	N
Technical level of the installation tasks	1	2	3	4	5	N
Ease of getting the system into production after installation	1	2	3	4	5	N

How did you order this product?

- CBPDO
- CustomPac
- ServerPac
- Independent
- Other

Is this the first time your organization has installed this product?

- Yes
- No

Were the people who did the installation experienced with the installation of z/OS products?

- Yes



User Technologies Department (MP095)  
IBM United Kingdom Limited  
Hursley Park  
Winchester  
Hampshire  
S021 2JN  
United Kingdom

FAX Number: (UK) 01962 842327  
FAX Number: (Elsewhere):  
Your International Access Code +44+1962+842327

Internet e-mail: [idrcf@hursley.ibm.com](mailto:idrcf@hursley.ibm.com)



Printed in U.S.A.

G111-4299-00

