



Cisco MDS 9506, 9509, 9513, 9216i, 9222i, 9148, 9134, and 9124 for IBM System Storage™ Directors and Switches

Interoperability Matrix

Last update: August 31, 2010

© Copyright International Business Machines Corporation 1999, 2002, 2003, 2004, 2005. All rights reserved.

The information provided in this document is provide "AS IS" without warranty of any kind, including any warranty of merchantability, fitness for a particular purpose, interoperability or compatibility. IBM's products are warranted in accordance with the agreements under which they are provided.

Unless otherwise specified, the product manufacturer, supplier, or publisher of non-IBM products provides warranty, service, and support directly to you. IBM makes no representations or warranties regarding non-IBM products.

The inclusion of an IBM or non-IBM product on an interoperability list is not a guarantee that it will work with the designated IBM storage product. In addition, not all software and hardware combinations created from compatible components will necessarily function properly together. The following list includes products developed or distributed by companies other than IBM. IBM does not provide service or support for the non-IBM products listed, but does not prohibit them from being used together with IBM's storage products. During problem debug and resolution, IBM may require that hardware or software additions be removed from the IBM product to provide problem determination and resolution on the IBM-supplied hardware/ software. For support issues regarding non-IBM products, please contact the manufacturer of the product directly. IBM does not warrant either functionality or problem resolution of any non-IBM products.

This information could include technical inaccuracies or typographical errors. IBM does not assume any liability for damages caused by such errors as this information is provided for convenience only; the reader should confirm any information contained herein with the associated vendor.

Changes are periodically made to the content of the document. These changes will be incorporated in new editions of the document. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this document at anytime without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

The following terms are trademarks of the International Business Machines Corporation in the United States, other countries, or both:

AIX	Micro Channel	System p
BladeCenter	Multiprise	System Storage
e (logo)	Netfinity	System x
eServer	OS/390	System z
ESCON	OS/400	TotalStorage
ES/9000	Redbooks	VSE/ESA
FICON	RS/6000	xSeries
FlashCopy	S/390	z/OS
IBM	S/390 Parallel Enterprise Server	z/VM
IBM logo	SP	
I5/OS	System i	

Microsoft and Windows are trademarks of Microsoft Corporation in the United States, other countries, or both.

Java and all Java-based trademarks are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other company, product, or service names may be trademarks or service marks of others.

Table of Contents

ESS	Page 3
DS8000	Page 8
DS6000	Page 13
DS4000	Page 18
Tape	Page 23
NAS	Page 30

What has changed?

1. Cisco MDS NX-OS support with 4.2(7a)
2. Cisco MDS NX-OS support with 5.0(1a)
3. Cisco Fabric Manager with 5.0(1a)
4. Cisco MDS 9148 support with 5.0(1a)
5. IBM BladeCenter Qlogic 8GB IPM support with 4.2(7a)

Notes:

1. The **MDS 9506/9509/9513** Multilayer Directors and **MDS 9216i/9222i/9124/9134** Fabric Switches **latest firmware level is 4.2(7a)**. The latest *FICON* or *Intermix* fabrics **firmware level is 4.2(1b)**. SAN-OS Release notes are found http://www.cisco.com/en/US/products/ps5989/prod_release_notes_list.html
2. Installation and upgrade information:
http://www.cisco.com/en/US/products/hw/ps4159/ps4358/prod_installation_guides_list.html
3. Product datasheets:
http://www.cisco.com/en/US/products/hw/ps4159/ps4358/products_data_sheets_list.html
4. Configuration Guides:
http://www.cisco.com/en/US/products/ps5989/products_installation_and_configuration_guides_list.html
5. Maximum ISLs (physical hops): 7 (maximum 1 Longwave ISL)
6. Blade module information: http://www.cisco.com/en/US/products/ps5991/prod_models_home.html
7. Technical support on **SAN Volume Controller (SVC)** can be found at: <http://www-03.ibm.com/systems/storage/software/virtualization/svc/index.html>
8. This SAN product line can not attach to public telecom networks and is not intended to attach to public telecom networks
9. **Note - Customers that do not** require an upgrade to NX-OS 4.2(7a), but require field updates, may install SAN-OS 3.3(5). **FICON** customers that **do not** require an upgrade to NX-OS 4.2(1b), but require field updates may install **_SAN-OS 3.3(1c)**
10. The MDS 9216, 9216A and Supervisor-1 are not NX-OS compatible. SAN-OS 3.3.5 must be used.
11. Please note limited support claims on the p7 for system p

ESS Connectivity

1. Please see **IBM TotalStorage Enterprise Storage Server [Interoperability Matrix](#)** for Licensed Internal Code (LIC) level.
2. For **PPRC** FC Direct, FC-CWDM and FCIP support see table 4 of **ESS Interoperability Matrix**.

IBM [System z](#) Models

Description	Operating Systems	Additional Information
IBM TotalStorage Enterprise Storage Servers IBM 2105 Model <ul style="list-style-type: none"> • 750 • 800 • F10/F20 	IBM z/OS level 1.4.1 or later	Available ¹ Cascading: Maximum of 1 hop (Inter Switch Links) is supported. Taking the CUP off-line prior to a concurrent software update. zSeries I/O Connectivity

IBM [System z](#)

Description	Operating Systems	Additional Information
IBM TotalStorage Enterprise Storage Servers IBM 2105 Model <ul style="list-style-type: none"> • 750 • 800 • F10/F20 	UnitedLinux (FCP) SLES (FCP) RedHat EL (FCP)	Available.

¹ When the Cisco switch is to be used in a FICON/Open intermixed environment, the user should manage the fabric from the Cisco Device and Fabric Managers. Disable host port control with the following procedure.

From the switch Device Manager Window:

1. Go to FICON ->
2. Select VSANs ->
3. Find "Port Control by", then Uncheck the left hand side box labeled "Host"

The user still has the capability of using IBM's SA OS/390 application for viewing the FICON related portions of the fabric.

It is recommended that network-admin privilege be strictly controlled.

IBM [System p](#) Servers

Description	Operating Systems	Additional Information
IBM TotalStorage Enterprise Storage Servers IBM 2105 Model <ul style="list-style-type: none"> • 750 • 800 • F10/F20 	AIX 5L HACMP	Available. IBM TotalStorage Enterprise Storage Server Interoperability Matrix
	Linux <ul style="list-style-type: none"> • SuSE Linux Enterprise Server • Red Hat Enterprise Linux 	Available.

IBM [System i](#) Servers

Description	Platform/Operating Systems	Additional Information
IBM TotalStorage Enterprise Storage Servers IBM 2105 Model <ul style="list-style-type: none"> • 750 • 800 • F10/F20 	OS/400 Linux	Available. IBM TotalStorage Enterprise Storage Server Interoperability Matrix System i SAN information

IBM [System x](#) and other Intel-based Servers

Description	Operating Systems	Additional Information
IBM TotalStorage Enterprise Storage Servers IBM 2105 Model <ul style="list-style-type: none"> • 750 • 800 • F10/F20 	Microsoft Windows	Available. IBM TotalStorage Enterprise Storage Server Interoperability Matrix IBM Server Proven Interoperability matrix
	Novell Netware	Available.
	Red Hat Enterprise Linux SuSE Linux Enterprise Server (SLES) UnitedLinux	Available.

SUN Microsystems Servers

Description	Operating Systems	Additional Information
<p>IBM TotalStorage Enterprise Storage Servers</p> <p>IBM 2105 Model</p> <ul style="list-style-type: none"> • 750 • 800 • F10/F20 	Solaris	<p>Available.</p> <p>IBM TotalStorage Enterprise Storage Server Interoperability Matrix</p>

Hewlett-Packard Servers – HP- UX

Description	Operating Systems	Additional Information
<p>IBM TotalStorage Enterprise Storage Servers</p> <p>IBM 2105 Model</p> <ul style="list-style-type: none"> • 750 • 800 • F10/F20 	HP-UX	<p>Available.</p> <p>IBM TotalStorage Enterprise Storage Server Interoperability Matrix</p>

DS8000 Connectivity

Please see **IBM TotalStorage DS 8000 [Interoperability Matrix](#)**

1. For Licensed Internal Code (LIC) level.
2. For **PPRC** FC Direct, FC-CWDM and FCIP support see table 4 of DS8000 **Interoperability Matrix**.

IBM [System z](#)

Description	Operating Systems	Additional Information
IBM TotalStorage DS 8000 Series IBM Model <ul style="list-style-type: none"> • 8100 Model 921 • 8300 Model 922 • 8300 Model 9A2 • 8700 Model 941 	IBM z/OS level 1.4.1 or later	Available ² Cascading: Maximum of 1 hop (Inter Switch Links) is supported. Taking the CUP off-line prior to a concurrent software update. zSeries I/O Connectivity

IBM [System z](#)

Description	Operating Systems	Additional Information
IBM TotalStorage DS 8000 Series IBM Model <ul style="list-style-type: none"> • 8100 Model 921 • 8300 Model 922 • 8300 Model 9A2 • 8700 Model 941 	UnitedLinux (FCP) SLES (FCP) RedHat EL (FCP)	Available.

² When the Cisco switch is to be used in a FICON/Open intermixed environment, the user should manage the fabric from the Cisco Device and Fabric Managers. Disable host port control with the following procedure.

From the switch Device Manager Window:

1. Go to FICON ->
2. Select VSANs ->
3. Find "Port Control by", then Uncheck the left hand side box labeled "Host"

The user still has the capability of using IBM's SA OS/390 application for viewing the FICON related portions of the fabric.

It is recommended that network-admin privilege be strictly controlled.

IBM [System p5](#) Servers

Description	Operating Systems	Additional Information
IBM TotalStorage DS 8000 Series IBM Model <ul style="list-style-type: none"> • 8100 Model 921 • 8300 Model 922 • 8300 Model 9A2 • 8700 Model 941 	AIX HACMP	Available. IBM TotalStorage DS 8000 Interoperability Matrix
	RHELppc SUSEppc	Available.

IBM [System p6](#) Servers

Description	Operating Systems	Additional Information
IBM TotalStorage DS 8000 Series IBM Model <ul style="list-style-type: none"> • 8100 Model 921 • 8300 Model 922 • 8300 Model 9A2 • 8700 Model 941 	AIX HACMP	Available. IBM TotalStorage DS 8000 Interoperability Matrix
	RHELppc SUSEppc	Available.

IBM [System p7](#) Servers

Description	Operating Systems	Additional Information
IBM TotalStorage DS 8000 Series IBM Model <ul style="list-style-type: none"> • 8100 Model 921 • 8300 Model 922 • 8300 Model 9A2 • 8700 Model 941 	AIX 5.3 ML 12 (p7) AIX 6.1 ML 5 (p7)	Available. IBM TotalStorage DS 8000 Interoperability Matrix
	RHEL 5.5 (pLinux) (p7) SLES 11	Available.

IBM [System i](#) Servers

Description	Platform/Operating Systems	Additional Information
IBM TotalStorage DS 8000 Series IBM Model <ul style="list-style-type: none">• 8100 Model 921• 8300 Model 922• 8300 Model 9A2• 8700 Model 941	IBM System i Models OS/400 i5/OS V6R1M1	Available. IBM TotalStorage DS 8000 Interoperability Matrix System i SAN information

IBM [System x](#), and other Intel-based Servers

Description	Operating Systems	Additional Information
IBM TotalStorage DS 8000 Series IBM Model <ul style="list-style-type: none"> • 8100 Model 921 • 8300 Model 922 • 8300 Model 9A2 • 8700 Model 941 	Microsoft Windows	Available. IBM TotalStorage DS 8000 Interoperability Matrix IBM Server Proven Interoperability matrix
	Novell Netware	Available.
	Red Hat Enterprise Linux SuSE Linux Enterprise Server (SLES) UnitedLinux	Available.

SUN Microsystems Servers

Description	Operating Systems	Additional Information
<p>IBM TotalStorage DS 8000 Series</p> <p>IBM Model</p> <ul style="list-style-type: none"> • 8100 Model 921 • 8300 Model 922 • 8300 Model 9A2 • 8700 Model 941 	Solaris	<p>Available.</p> <p>IBM TotalStorage DS 8000 Interoperability Matrix</p>

Hewlett-Packard Servers – HP- UX

Description	Operating Systems	Additional Information
<p>IBM TotalStorage DS 8000 Series</p> <p>IBM Model</p> <ul style="list-style-type: none"> • 8100 Model 921 • 8300 Model 922 • 8300 Model 9A2 • 8700 Model 941 	HP-UX	<p>Available.</p> <p>IBM TotalStorage DS 8000 Interoperability Matrix</p>

DS6000 Connectivity

Please see **IBM TotalStorage DS 6000 [Interoperability Matrix](#)**

3. For Licensed Internal Code (LIC) level.

4. For **PPRC** FC Direct, FC-CWDM and FCIP support see table 4 of DS6000 **Interoperability Matrix**.

IBM [System z](#) Models

Description	Operating Systems	Additional Information
IBM TotalStorage DS 6000 Series IBM 1750 Model <ul style="list-style-type: none"> • DS 6800 	IBM z/OS level 1.4.1 or later	Available ³ Cascading: Maximum of 1 hop (Inter Switch Links) is supported. Taking the CUP off-line prior to a concurrent software update. zSeries I/O Connectivity

IBM [System z](#)

Description	Operating Systems	Additional Information
IBM TotalStorage DS 6000 Series IBM 1750 Model <ul style="list-style-type: none"> • DS 6800 	UnitedLinux (FCP)⁴	Available.

³ When the Cisco switch is to be used in a FICON/Open intermixed environment, the user should manage the fabric from the Cisco Device and Fabric Managers. Disable host port control with the following procedure.

From the switch Device Manager Window:

1. Go to FICON ->
2. Select VSANs ->
3. Find "Port Control by", then Uncheck the left hand side box labelled "Host"

The user still has the capability of using IBM's SA OS/390 application for viewing the FICON related portions of the fabric.

It is recommended that network-admin privilege be strictly controlled.

⁴ SLES 8 for IBM zSeries 32-bit and 64-bit Server

IBM [System p5](#) Servers

Description	Operating Systems	Additional Information
IBM TotalStorage DS 6000 Series IBM 1750 Model <ul style="list-style-type: none"> • DS 6800 	AIX 5L HACMP	Available. IBM TotalStorage DS 6000 Interoperability Matrix
	Linux	Available.

IBM [System p6](#) Servers

Description	Operating Systems	Additional Information
IBM TotalStorage DS 6000 Series IBM 1750 Model <ul style="list-style-type: none"> • DS 6800 	AIX 5L HACMP	Available. IBM TotalStorage DS 6000 Interoperability Matrix
	Linux	Available.

IBM [System p7](#) Servers

Description	Operating Systems	Additional Information
IBM TotalStorage DS 6000 Series IBM 1750 Model <ul style="list-style-type: none"> • DS 6800 	AIX 5.3 ML 12 (p7) AIX 6.1 ML 5 (p7)	Available. IBM TotalStorage DS 6000 Interoperability Matrix
	RHEL 5.5 (pLinux) (p7) SLES 11	Available.

IBM [System i](#) Servers

Description	Platform/Operating Systems	Additional Information
IBM TotalStorage DS 6000 Series IBM 1750 Model <ul style="list-style-type: none">• DS 6800	i5/OS V6R1M1 Linux	Available. IBM TotalStorage DS 6000 Interoperability Matrix System i SAN information

IBM [System x](#) and other Intel-based Servers

Description	Operating Systems	Additional Information
IBM TotalStorage DS 6000 Series IBM 1750 Model <ul style="list-style-type: none"> • DS 6800 	Microsoft Windows	Available. IBM TotalStorage DS 6000 Interoperability Matrix IBM Server Proven Interoperability matrix
	Novell Netware	Available.
	Red Hat Enterprise Linux SuSE Linux Enterprise Server (SLES) UnitedLinux	Available.

SUN Microsystems Servers

Description	Operating Systems	Additional Information
IBM TotalStorage DS 6000 Series IBM 1750 Model <ul style="list-style-type: none"> • DS 6800 	Solaris	Available. IBM TotalStorage DS 6000 Interoperability Matrix

Hewlett-Packard Servers – HP- UX

Description	Operating Systems	Additional Information
IBM TotalStorage DS 6000 Series IBM 1750 Model <ul style="list-style-type: none"> • DS 6800 	HP-UX	Available. IBM TotalStorage DS 6000 Interoperability Matrix

DS4000 Connectivity

For the most current supported **HACMP**, **PSSP**, **GPFS/RVSD** configurations see the important notices and Readme files posted on each DS4000 product website.

IBM [System p5](#)

Description	Operating Systems	Additional Information
IBM TotalStorage Storage Servers <ul style="list-style-type: none"> • DS4800 • DS4700 • DS4500 • DS4400 • DS4300 • Dual Controller • Turbo • DS4200 • DS4100 	AIX 5L HACMP, PSSP (see note #0 page 18)	Available. IBM TotalStorage DS 4000 Storage Interoperability matrix IBM Server Proven Interoperability matrix
	Red Hat Enterprise Linux PPC SuSE Linux Enterprise Server (SLES) PPC	Available.

IBM [System p6](#)

Description	Operating Systems	Additional Information
IBM TotalStorage Storage Servers <ul style="list-style-type: none"> • DS4800 • DS4700 • DS4500 • DS4400 • DS4300 • Dual Controller • Turbo • DS4200 • DS4100 	AIX 5L HACMP, PSSP (see note #0 page 18)	Available. IBM TotalStorage DS 4000 Storage Interoperability matrix IBM Server Proven Interoperability matrix
	Red Hat Enterprise Linux PPC SuSE Linux Enterprise Server (SLES) PPC	Available.

IBM [System p7](#)

Description	Operating Systems	Additional Information
IBM TotalStorage Storage Servers <ul style="list-style-type: none"> • DS4800 • DS4700 • DS4500 • DS4400 • DS4300 <ul style="list-style-type: none"> • Dual Controller • Turbo • DS4200 • DS4100 	AIX 5.3 ML 12 (p7) AIX 6.1 ML 5 (p7)	Available. IBM TotalStorage DS 4000 Storage Interoperability matrix IBM Server Proven Interoperability matrix
	No Linux Support	Available.

IBM [System x](#) and other Intel-based Servers

Description	Operating Systems	Additional Information
IBM TotalStorage Storage Servers <ul style="list-style-type: none"> • DS4800 • DS4700 • DS4500 • DS4400 • DS4300 <ul style="list-style-type: none"> • Dual Controller • Turbo • DS4200 • DS4100 	Microsoft Windows	Available. IBM TotalStorage DS 4000 Storage Interoperability matrix IBM Server Proven Interoperability matrix
	Novell Netware	Available.
	Red Hat Enterprise Linux	Available.
	SuSE Linux Enterprise Server (SLES) UnitedLinux	

SUN Microsystems Servers

Description	Operating Systems	Additional Information
<p>IBM TotalStorage Storage Servers</p> <ul style="list-style-type: none"> • DS4800 • DS4700 • DS4500 • DS4400 • DS4300 • Dual Controller • Turbo • DS4200 • DS4100 	Solaris	<p>Available.</p> <p>IBM TotalStorage DS 4000 Storage Interoperability matrix</p> <p>IBM Server Proven Interoperability matrix</p>

Hewlett-Packard Servers – HP- UX

Description	Operating Systems	Additional Information
<p>IBM TotalStorage Storage Servers</p> <ul style="list-style-type: none"> • DS4800 • DS4700 • DS4500 • DS4400 • DS4300 • Dual Controller • Turbo • DS4200 • DS4100 	HP-UX	<p>Available.</p> <p>IBM TotalStorage DS 4000 Storage Interoperability matrix</p> <p>IBM Server Proven Interoperability matrix</p>

DS5000 Connectivity

For the most current supported **HACMP**, **PSSP**, **GPFS/RVSD** configurations see the important notices and Readme files posted on each DS4000 product website.

IBM [System p5](#)

Description	Operating Systems	Additional Information
IBM TotalStorage Storage Servers <ul style="list-style-type: none"> • DS5100 • DS5300 	AIX HACMP, PSSP (see note #0 page 18)	Available. ADD DS5k Interop Matrix
	Linux RHELppc SUSEppc	Available.

IBM [System p6](#)

Description	Operating Systems	Additional Information
IBM TotalStorage Storage Servers <ul style="list-style-type: none"> • DS5100 • DS5300 	AIX HACMP, PSSP (see note #0 page 18)	Available. ADD DS5k Interop Matrix
	Linux RHELppc SUSEppc	Available.

IBM [System p7](#)

Description	Operating Systems	Additional Information
IBM TotalStorage Storage Servers <ul style="list-style-type: none"> • DS5100 • DS5300 	AIX 5.3 ML 12 (p7) AIX 6.1 ML 5 (p7)	Available. ADD DS5k Interop Matrix
	No Linux Support	Available.

IBM [System x](#) and other Intel-based Servers

Description	Operating Systems	Additional Information
IBM TotalStorage Storage Servers <ul style="list-style-type: none"> • DS5100 • DS5300 	Microsoft Windows	Available. IBM TotalStorage DS 4000 Storage Interoperability matrix IBM Server Proven Interoperability matrix
	Novell Netware	Available.
	Red Hat Enterprise Linux United Linux	Available.

SUN Microsystems Servers

Description	Operating Systems	Additional Information
IBM TotalStorage Storage Servers <ul style="list-style-type: none"> • DS5100 • DS5300 	Solaris	Available. IBM TotalStorage DS 4000 Storage Interoperability matrix IBM Server Proven Interoperability matrix

Hewlett-Packard Servers – HP- UX

Description	Operating Systems	Additional Information
IBM TotalStorage Storage Servers <ul style="list-style-type: none"> • DS5100 • DS5300 	HP-UX	Available. IBM TotalStorage DS 4000 Storage Interoperability matrix IBM Server Proven Interoperability matrix

IBM XIV System Storage Connectivity

Please see IBM XIV System Storage [Interoperability Matrix](#)

IBM [System z](#)

Description	Operating Systems	Additional Information
IBM System Storage XIV IBM Model <ul style="list-style-type: none"> • XIV 2810 • XIV 2812 	IBM z/OS level 1.4.1 or later	<p>Cascading: Maximum of 1 hop (Inter Switch Links) is supported.</p> <p>Taking the CUP off-line prior to a concurrent software update.</p> <p>zSeries I/O Connectivity</p>

IBM [System z](#)

Description	Operating Systems	Additional Information
IBM System Storage XIV IBM Model <ul style="list-style-type: none"> • XIV 2810 • XIV 2812 	UnitedLinux (FCP) SLES (FCP) RedHat EL (FCP)	Available.

IBM [System p5](#) Servers

Description	Operating Systems	Additional Information
IBM System Storage XIV IBM Model <ul style="list-style-type: none"> • XIV 2810 • XIV 2812 	AIX 6.1 ML2 AIX 5.3 ML 8 HACMP	Available. IBM XIV System Storage Interoperability Matrix
	Linux	Available.

IBM [System p6](#) Servers

Description	Operating Systems	Additional Information
IBM System Storage XIV IBM Model <ul style="list-style-type: none"> • XIV 2810 • XIV 2812 	AIX 5.3 ML 8 AIX 6.1 ML2 HACMP	Available. IBM XIV System Storage Interoperability Matrix
	Linux	Available.

IBM [System p7](#) Servers

Description	Operating Systems	Additional Information
IBM System Storage XIV IBM Model <ul style="list-style-type: none"> • XIV 2810 • XIV 2812 	AIX 5.3 ML 12 (p7) AIX 6.1 ML 5 (p7)	Available. IBM XIV System Storage Interoperability Matrix
	RHEL 5.5 (pLinux) (p7) SLES 11	Available.

IBM System x, and other Intel-based Servers

Description	Operating Systems	Additional Information
IBM System Storage XIV IBM Model <ul style="list-style-type: none"> • XIV 2810 • XIV 2812 	Microsoft Windows 2000 Microsoft Windows 2000 (64 bit) Microsoft Windows 2003 Microsoft Windows 2003 (64 bit)	Available. IBM XIV System Storage Interoperability Matrix IBM Server Proven Interoperability matrix
	Novell Netware	Available.
	Red Hat Enterprise Linux SuSE Linux Enterprise Server (SLES) UnitedLinux	Available.

TAPE Connectivity

IBM 9672 Enterprise G5, G6 and [System z](#)

Description	Operating Systems	Additional Information
<p>IBM TotalStorage Enterprise Tape Controller 3592 Model J70, E06</p> <p>FICON Attachment Longwave:</p> <ul style="list-style-type: none"> • FC-3434 (2 Gb) <p>Shortwave:</p> <p>FC-3435 (2 Gb)</p> <p>IBM TotalStorage Enterprise Automated Tape Library 3494</p> <p>IBM TotalStorage Virtual Tape Server 3494-B10/B20 in Standalone or Peer to Peer configurations</p> <p>IBM TotalStorage Enterprise Tape Drive Frame 3590 Model A14</p> <p>IBM TotalStorage Silo Compatible Tape Drive Frame</p>	<p>IBM 9672 Enterprise G5 or G6 and zSeries Servers</p>	<p>Available.⁵</p> <p>Cascading: Maximum of 1 hop (Inter Switch Links) is supported.</p> <p>Taking the CUP off-line prior to a concurrent software update.</p>

⁵ When the Cisco switch is to be used in a FICON/Open intermixed environment, the user should manage the fabric from the Cisco Device and Fabric Managers. Disable host port control with the following procedure.

From the switch Device Manager Window:

1. Go to FICON ->
2. Select VSANs ->
3. Find "Port Control by", then Uncheck the left hand side box labelled "Host"

The user still has the capability of using IBM's SA OS/390 application for viewing the FICON related portions of the fabric.

It is recommended that network-admin privilege be strictly controlled.

IBM [System z](#)

Description	Operating Systems	Additional Information
<p>Enterprise Tape System 3592 J1A, E06 in a 3494 or 3584 Tape Library.</p> <p>Enterprise Tape System 3590 E11/E1A and H11/H1A with Native FC Tape Drives. Standalone or in a 3494 Tape Library.</p> <p>Enterprise Tape System TS1120 (3952 E05) tape drive.</p> <p>All 3494 rules apply. i.e. ESCON/FICON owned drives cannot co-exist in the same frame as Open Systems drives.</p> <p>TS3310 Tape Library with Native Ultrium 3 drives</p> <p>TS3400 Tape Library with TS1120 tape drives</p> <p>TS3500 Tape Library with LTO 4</p> <p>Ultrium 3584 UltraScalable Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3583 Scalable Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3582 Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3581-2U IBM LTO Tape Autoloader</p> <p>Virtualization Engine TS7510 and TS7520</p>	<p>SLES 8 for IBM zSeries 32-bit and 64-bit Server</p>	<p>Available.</p> <p>zSeries Support of Fibre Channel FCP Channels</p>

IBM [System p](#) Servers

Description	Operating Systems	Additional Information
Enterprise Tape System 3592 J1A, E06 in a 3494 or 3584 Tape Library, rack mounted or Silo Compatible Frame.	AIX 5.3 ML 12 (p7) AIX 6.1 ML 5 (p7)	Available. Please review RMSS Technical Support Site.
Enterprise Tape System 3590 E11/E1A and H11/H1A with Native FC Tape Drives. Standalone or in a 3494 Tape Library or Silo Compatible Frame. Enterprise Tape System TS1120 (3952 E05) tape drive. TS3310 Tape Library with Native Ultrium 3 drives TS3400 Tape Library with TS1120 tape drives TS3500 Tape Library with LTO 4 Ultrium 3584 UltraScalable Tape Library with Native FC Ultrium 2, 3, and 4 drives Ultrium 3583 Scalable Tape Library with Native FC Ultrium 2, 3, and 4 drives Ultrium 3582 Tape Library with Native FC Ultrium 2, 3, and 4 drives Ultrium 3581-2U IBM LTO Tape Autoloader Virtualization Engine TS 7510 and TS7520		Available.

****Note- No NPIV support with Linux**

IBM [System i](#) Servers

Description	Platform/Operating Systems	Additional Information
<p>Enterprise Tape System 3592 J1A, E06 in a 3494 or 3584 Tape Library or rack mounted.</p> <p>Enterprise Tape System 3590 E11/E1A and H11/H1A with Native FC Tape Drives. Standalone or in a 3494 Tape Library.</p> <p>Enterprise Tape System TS1120 (3952 E05) tape drive.</p> <p>TS3310 Tape Library with Native Ultrium 3 drives</p> <p>TS3400 Tape Library with TS1120 tape drives</p> <p>TS3500 Tape Library with LTO 4</p> <p>Ultrium 3584 UltraScalable Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3583 Scalable Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3582 Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3581-2U IBM LTO Tape Autoloader</p> <p>Virtualization Engine TS7510 and TS7520</p>	<p>OS/400⁶ i5/OS V6R1M1</p>	<p>Available.</p> <p>System i SAN information.</p> <p>Please review RMSS Technical Support Site.</p>

⁶ Required PTF MF32002

IBM [System x](#) and other Intel-based Servers

Description	Operating Systems	Additional Information
<p>Enterprise Tape System 3592 J1A, E06 in a 3494 or 3584 Tape Library, rack mounted or Silo Compatible Frame.</p> <p>Enterprise Tape System 3590 E11/E1A and H11/H1A with Native FC Tape Drives. Standalone or in a 3494 Tape Library or Silo Compatible Frame.</p>	<p>Microsoft Windows</p>	<p>Available.</p> <p>IBM Server Proven Interoperability matrix</p> <p>Please review RMSS Technical Support Site.</p>
<p>Enterprise Tape System TS1120 (3952 E05) tape drive.</p> <p>TS3310 Tape Library with Native Ultrium 3 drives</p> <p>TS3400 Tape Library with TS1120 tape drives</p> <p>TS3500 Tape Library with LTO 4</p> <p>Ultrium 3584 UltraScalable Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3583 Scalable Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3582 Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3581-2U IBM LTO Tape Autoloader</p> <p>Virtualization Engine TS 7510 and TS7520</p>	<p>Red Hat Enterprise Linux</p> <p>SuSE Linux Enterprise Server (SLES)</p> <p>United Linux 1.0</p>	<p>Available.</p> <p>Please review RMSS Technical Support Site.</p>

SUN Microsystems Servers

Description	Operating Systems	Additional Information
<p>Enterprise Tape System 3592 J1A, C06 in a 3494 or 3584 Tape Library, rack mounted or Silo Compatible Frame.</p> <p>Enterprise Tape System 3590 E11/E1A and H11/H1A with Native FC Tape Drives. Standalone or in a 3494 Tape Library or Silo Compatible Frame.</p> <p>Enterprise Tape System TS1120 (3952 E05) tape drive.</p> <p>TS3310 Tape Library with Native Ultrium 3 drives</p> <p>TS3400 Tape Library with TS1120 tape drives</p> <p>TS3500 Tape Library with LTO 4</p> <p>Ultrium 3584 UltraScalable Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3583 Scalable Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3582 Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3581-2U IBM LTO Tape Autoloader</p> <p>Virtualization Engine TS 7510 and TS7520</p>	<p>Solaris</p>	<p>Available.</p> <p>Please review RMSS Technical Support Site.</p>

Hewlett-Packard Servers – HP- UX

Description	Operating Systems	Additional Information
<p>Enterprise Tape System 3592 J1A, C06 in a 3494 or 3584 Tape Library, rack mounted or Silo Compatible Frame.</p> <p>Enterprise Tape System 3590 E11/E1A and H11/H1A with Native FC Tape Drives. Standalone or in a 3494 Tape Library or Silo Compatible Frame.</p> <p>Enterprise Tape System TS1120 (3952 E05) tape drive.</p> <p>TS3310 Tape Library with Native Ultrium 3 drives</p> <p>TS3400 Tape Library with TS1120 tape drives</p> <p>TS3500 Tape Library with LTO 4</p> <p>Ultrium 3584 UltraScalable Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3583 Scalable Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3582 Tape Library with Native FC Ultrium 2, 3, and 4 drives</p> <p>Ultrium 3581-2U IBM LTO Tape Autoloader</p> <p>Virtualization Engine TS 7510 and TS7520</p>	<p>HP-UX</p>	<p>Available.</p> <p>Please see the readme file for any restrictions.</p> <p>Please review RMSS Technical Support Site.</p>

NETWORK ATTACHED STORAGE ([NAS](#))

Cisco MDS 9506, 9509, 9513, 9216i, 9216i, 9222i*, 9148 and 9134* for IBM System Storage Directors and Switches are interoperable with:

N series models – Supported with SAN-OS 2.1(2b) and above

NAS and N series Gateways – Supported with SAN-OS 2.1(2b) and above

*Denotes products must run SAN-OS 3.x or above

IBM eServer Blade Center ([BC](#))

Information on interoperability and Technical Support can be found at [IBM eServer Blade Center](#).

Description	Blade Switch Module Firmware	Cisco MDS 9000 SAN Family
Cisco 10/20 port FCSM*	4.2 (3)	4.2(3)
4GB Qlogic Intelligent Pass-Thru	6.5.0.21.0	4.2(3)
8GB Qlogic Intelligent Pass-Thru	7.10.1.04	4.2.5
Optical Pass-Thru Module	N/A	4.2(3)

*Notes

NPV and NPIV is supported with fw 3.2 and above

Heterogeneous SAN support

For information regarding heterogeneous SAN support please use the following:

<http://www.cisco.com/en/US/docs/switches/datacenter/mds9000/interoperability/matrix/Matrix4.html#wp299210>

Supported Distance / Extension Methods

Traffic / Application	Extension Method	Supported Distance
regular FICON traffic	FC ISLs with DWDM	300km
regular FICON traffic	CWDM FC ISLs	100km
regular FICON traffic	FCIP ISLs	300km
IBM VTS (host to VTC connection)	FC ISLs with DWDM	250km
IBM VTS (VTC to VTS connection)	FC ISLs with DWDM	250km
IBM Enterprise and LTO Tape	all	300km*
IBM XRC FICON	FC ISLs with DWDM	200km
IBM XRC FICON	CWDM FC ISLs	200km
IBM XRC FICON	FCIP ISLs	200km

* IBM 3592 drives with Control Units C06 and J70 supported up to 3000km when Cisco FICON Tape Acceleration is enabled