



## Technical Documentation for Ukraine Technical Regulation on Ecodesign Requirements for Computers and Computer Servers, Resolution No. 737

7/22/2022

The following information is based on IBM's knowledge as of the date of this document, which may be based on its records and information from third parties. This documentation applies to finished products that IBM newly puts on the market in Ukraine and other jurisdictions which require this Technical Documentation as of the above date.

<b>Product Information</b>			
<b>Machine Type(s)</b>	<b>Model(s)</b>	<b>Part Number</b>	<b>Product Type</b>
9105	41B	-	Computer server

Manufacturer's name, registered trade name and registered trade address:

**IBM**  
Marca Registrada  
© Registered Trademark of  
International Business Machines Corporation  
New Orchard Road Armonk, New York 10504

Year of manufacture

**2022**

Noise levels (declared A-weighted sound power level of the computer)

	Operating	Idle
- Typical configuration - Typical workload - 23°C (73.4°F), 500 m (1640 ft) environment	7.5	7.5
- Typical configuration - Typical workload - 23°C (73.4°F), 500 m (1640 ft) environment - Front acoustic door <sup>9</sup>	7.0	7.0
- Typical configuration - Typical workload - 25°C (77°F), 500 m (1640 ft) environment	7.9	7.9
- Typical configuration - Typical workload - 25°C (77°F), 500 m (1640 ft) environment - Front acoustic door <sup>9</sup>	7.3	7.3
- 24-core configuration - Typical workload - 23°C (73.4°F), 500 m (1640 ft) environment	8.0	7.6
- 24-core configuration - Typical workload - 23°C (73.4°F), 500 m (1640 ft) environment - Front acoustic door <sup>9</sup>	7.4	7.1




- High power PCIe adapter - Typical workload - 23°C (73.4°F), 500 m (1640 ft) environment	7.8	7.8
- High power PCIe adapter - Typical workload - 23°C (73.4°F), 500 m (1640 ft) environment - Front acoustic door?	7.3	7.4
- High power PCIe adapter - Typical workload - 25°C (77°F), 500 m (1640 ft) environment	8.0	8.0
- High power PCIe adapter - Typical workload - 25°C (77°F), 500 m (1640 ft) environment - Front acoustic door?	7.4	7.4
- Typical configuration with high power PCIe adapter - Typical workload - 40°C (104°F), 3050 m (10000 ft) environment	8.3	8.0
- Typical configuration with high power PCIe adapter - Typical workload - 40°C (104°F), 3050 m (10000 ft) environment - Front acoustic door?	7.7	7.5
- 24-core configuration - Typical workload - 40°C (104°F), 3050 m (10000 ft) environment	8.3	8.3
- 24-core configuration - Typical workload - 40°C (104°F), 3050 m (10000 ft) environment - Front acoustic door?	7.7	7.7

### Internal/external power supply efficiency

<b>ID Number</b>	SO-2021
<b>Manufacturer</b>	IBM
<b>Model Number</b>	AWF2DC1200W-E
<b>Serial Number</b>	03FP726YL30NH1C7133
<b>Year</b>	2022
<b>Type</b>	1U
<b>Test Date</b>	04/18/22

Rated Specifications	Value	Units
Input Voltage	100-127/200-240	Volts
Input Current	12/7.5	Amps
Input Frequency	50/60	Hz
Rated Output Power	1,200	Watts

Note: All measurements were taken with input voltage at 230 V nominal and 60 Hz.




Input AC Current Waveform (ITHD = 7.107%, 50% Load)

I <sub>RMS</sub>	PF	I <sub>THD</sub>	Load	Fraction of Load	Input Watts	External Fan (W)*	DC Terminal Voltage (V)/ DC Load Current (A)		Output Watts	Efficiency
							12.3V	12.3Vsb		
0.677	0.8473	42.10%	10%	Low	131.97	2.04	12.18/9.24	12.14/0.55	119.18	90.31%
1.149	0.9541	16.84%	20%	Light	252.12	2.04	12.16/18.47	12.1/1.11	238.06	94.42%
2.747	0.9778	7.11%	50%	Typical	617.67	2.04	12.13/46.16	12.04/2.78	593.29	96.05%
5.404	0.9930	4.86%	100%	Full	1234.64	8.52	12.07/92.32	11.94/5.55	1180.98	95.65%

\* Fan power is not included in the efficiency calculations



ID Number	SO-2020.1
Manufacturer	IBM
Model Number	AWF2DC1600W-I
Serial Number	02PX119YL30NH22R186
Year	2022
Type	1U
Test Date	04/18/22



Input AC Current Waveform (ITHD = 5.052%, 50% Load)

Rated Specifications	Value	Units
Input Voltage	100-127/200-240	Volts
Input Current	12/9	Amps
Input Frequency	50/60	Hz
Rated Output Power	1,600	Watts

Note: All measurements were taken with input voltage at 230 V nominal and 60 Hz.

I <sub>RMS</sub>	PF	I <sub>THD</sub>	Load	Fraction of Load	Input Watts	External Fan (W)*	DC Terminal Voltage (V)/ DC Load Current (A)		Output Watts	Efficiency
							12.3V	12.3Vsb		
0.822	0.9224	21.08%	10%	Low	174.44	1.92	12.27/12.48	12.25/0.57	160.15	91.80%
1.531	0.9597	9.13%	20%	Light	338.06	1.80	12.26/24.95	12.21/1.15	319.96	94.65%
3.643	0.9900	5.05%	50%	Typical	829.42	1.92	12.22/62.39	12.15/2.86	797.46	96.15%
7.277	0.9969	4.13%	100%	Full	1668.89	8.52	12.16/124.77	12.05/5.73	1586.12	95.04%

\* Fan power is not included in the efficiency calculations

Maximum power (watts)

**962 watts**

Idle State power (watts)

**324 watts**

Sleep mode power (watts)

**Not applicable for computer servers**

Off mode power (watts)

**36 watts**

Test parameters	Properties
Test voltage and frequency	230 V ac at 50 Hz or 60 Hz
Total harmonic distortion of the electricity supply system	The maximum harmonic content of the input voltage waveform is equal to or less than 2%. The qualification is compliant with EN 61000-3-2.
Information and documentation on the instrumentation setup and circuits that are used for electrical testing	SPEC SERT suite version 2.x. ECOVA Generalized Test Protocol for Calculating the Energy Efficiency of Internal Ac-Dc and Dc-Dc Power Supplies
Measurement methodology that is used to determine information in this document	SPEC SERT suite version 2.x. ECOVA Generalized Test Protocol for Calculating the Energy Efficiency of Internal Ac-Dc and Dc-Dc Power Supplies

IBM maintains a product environmental specification, IBM Engineering Specification 46G3772 - Baseline Environmental Requirements for Supplier Deliverables to IBM which mandates part and product compliance to relevant worldwide regulations, including EU Regulation 2019/424. The specifications are



located for supplier access at: <http://www.ibm.com/ibm/environment/products/> and <http://www-03.ibm.com/procurement/proweb.nsf/ContentDocsByTitle/United+States~Information+for+suppliers>.

Suppliers are required to certify compliance to IBM product environmental specifications by completing the IBM Product Content Declaration (PCD), located at: <http://www.ibm.com/ibm/environment/products/>. Once completed, the PCD form is submitted to IBM, loaded into product management databases and accessed for compliance review by product. IBM's Product Environmental Profile process and tool documents and reviews product compliance prior to release to the market. The documentation presented here is a result of this review and process.

In 1997, IBM became the world's first major multinational corporation to have earned a single worldwide registration to the ISO 14001 Environmental Management System (EMS) standard. The registration covers IBM's manufacturing, product design and hardware development operations across its business units worldwide. IBM was able to earn its single worldwide registration to ISO 14001 because of its longstanding global EMS. ISO 14001 EMS standard is a voluntary international standard that identifies the elements of an EMS needed for an organization to effectively manage its impact on the environment. Its objective is to integrate the EMS with overall business management processes so that environmental considerations are a standard part of business decisions. Applied to all its manufacturing and hardware development operations globally, IBM's EMS fosters common solutions, continual improvement and worldwide consistency. The result is a more effective and efficient EMS. The single registration also ensures that IBM executes the same EMS no matter where in the world it does business. Under IBM's single global registration, approximately 20 sites or registered entities are audited annually on a sampling or rolling basis by Bureau Veritas Certification North America, IBM's ISO 14001 registrar. These audits of IBM's EMS include sampling and verification of the implementation of IBM's internal requirements, monitoring and measurement as reported through the self assessment program, energy master plans, and in the Environmental Performance Database, and other tools used to provide the information for IBM's annual environmental and corporate responsibility reporting and for management review. The IBM ISO 14001 certification is located at <http://www.ibm.com/ibm/environment/iso14001/>.

More information on IBM's product stewardship program and / or environmental policies is located at: <http://www.ibm.com/ibm/environment/>

Limitations for Customers: The Product information provided in this Technical Documentation ("Documentation") is provided "AS IS", without any express or implied warranty of any kind. This information is subject to change without notice; provided, however, that IBM reserves the right, in its discretion, to issue an update or modification to this Documentation if it believes it is appropriate to do so. The contents of this Documentation do not constitute either: (1) legal advice; (2) a legal opinion; or (3) any representation, warranty, or guarantee regarding a person's ability to comply with applicable legal requirements. This Documentation in no way modifies any agreements entered into by IBM. The information here is based on IBM's knowledge as of the date of this document, which may be based on its records and information from third parties. This documentation applies to finished products that IBM newly puts on the market in the European Union and other jurisdictions which require this Declaration of Conformity as of the date above. CE Mark applies only to those new products put on the market in the EU and the European Free Trade Association jurisdictions by IBM.

The following are trademarks of International Business Machines Corporation in the United States, or other countries, or both: IBM IBM Logo.