Recyclability assessment *

Date: March 6, 2023 IBM Power Server 9105 42A

| Brand name = | IBM | | | | |
|--|-----------|-----|------------------|----------------------|----------------------|
| Model name = | 9105 42A | | Product weight = | 42.51 kg | |
| | | | | | |
| Part/Sub-Assembly | Mass (kg) | Qty | Mass/System(kg) | Recyclability rate** | Recyclable mass (kg) |
| 4U Chassis Asm. w/Integrated DASD Cage | 10.87 | 1 | 10.87 | 100% | 10.87 |
| 2.5" NVMe DASD | 0.21 | 16 | 3.35 | 92% | 3.08 |
| Nisqually FRU (w/PDB, Winthrop & BH's) | 7.00 | 1 | 7.00 | 97% | 6.79 |
| 4U Air Baffle | 0.82 | 1 | 0.82 | 97% | 0.79 |
| Power Supply | 1.07 | 4 | 4.27 | 97% | 4.14 |
| 4U Top Cover | 3.18 | 1 | 3.18 | 97% | 3.09 |
| 4U CPU Heatsink | 1.55 | 2 | 3.11 | 97% | 3.02 |
| 4U DDIMM | 0.07 | 32 | 2.33 | 97% | 2.26 |
| Blower Asm | 0.34 | 6 | 2.02 | 97% | 1.96 |
| VRM Up-Regs + Ten60 mated pair | 0.39 | 2 | 0.78 | 97% | 0.76 |
| FHHL HMS-Bono OpenCAPI | 0.39 | 3 | 1.17 | 97% | 1.14 |
| FHHL PCIe Card | 0.23 | 4 | 0.91 | 97% | 0.88 |
| FHHL Flett Card | 0.20 | 3 | 0.60 | 97% | 0.58 |
| Oculink Cables | 0.42 | 1 | 0.42 | 97% | 0.41 |
| Williwakas DASD Backplane | 0.10 | 2 | 0.20 | 97% | 0.19 |
| DCM Module | 0.24 | 2 | 0.47 | 97% | 0.46 |
| 4U PCIe Dividers | 0.04 | 10 | 0.36 | 97% | 0.35 |
| eBMC Card | 0.32 | 1 | 0.32 | 97% | 0.31 |
| LCD Assembly | 0.04 | 1 | 0.04 | 97% | 0.04 |
| 4U Front Bezel | 0.18 | 1 | 0.18 | 97% | 0.18 |
| Other, Misc. Cables | 0.11 | 1 | 0.11 | 93% | 0.10 |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| Sum *** | | • | 42.5 | 1 | 41.3 |

97.4

Recyclability rate: R _{rcy} = Symbols and definitions

 $\sum m_{(i)} x RCR_{(i)} / m_{EEE} x 100\% =$

m(i) = Mass of ith part

 $RCR_{(i)}$ = Recycling rate of the ith part in the corresponding end-of-life treatment scenario

Tatal and date

 m_{EEE} = Total product mass

* This recyclability assessment is based on the format in the International Electrotechnical Commission (EC) 5235 Standard Guidelines for end-of-life information provided by manufacturers and recycles and for recyclability rate calculation of electrical and electronic equipment. Recyclability is defined by the standard to be "ability of values product to be recycled, based on actual practices." The recyclability rate calculation equation is defined by this standard. Products were assessed based on the results of reuse, recycling, and/or disposal at IBM's Product End-of-Life Management suppliers. The 2018 results for IBM product end-of-life management are attached to the right. The IBM and the Environment 2018 Annual report is located at https://www.ibm.com/bm/environment/annual/reporting.shtml


** Assumptions - Recyclability rates projected for this product and parts are based on knowledge of the product material composition, publically available references sources for recyclability of materials (see references below) and on the overall results of IBM's product end-of-life management venders. Where there is a publically available recyclability rate for a commodity or assembly such as those in the IRC Technical Report below, that rate is used. Where there is not a publically available recyclability rate, the overall rate of 97% was chosen because that is the documented and actual recycling rates from IBM Product End of Life Management venders. The 97% is the actual recyclability of IBM products as reported from IBM PELM vendors and the available infrastructure. According to NSF/ANSI 426-2018 - Printed circuit boards busbrate material, included in printed circuit boards that will be sent to a smelter for metals recycling, shall be considered recyclable for the purpose of the calculation.

*** This POWER server is unique in content based on customer ordering. The weight will vary based on content of the server. The bill of material provided here is an example for this product and that which is used for the Installation Planning manual.

**** References: IEC/TR 62635, "Technical Report IEC/TR 62635, Guidelines for End of Life information provision from manufactures and recyclers, and for recyclability rate calculation of Electrical and Electronic Equipment." The International Electrotechnical Commission (IEC), 2012; P. Chancerel and M. Marwede, JRC Technical Reports, Feasibility study for setting-up reference values to support the calculation of recyclability / recoverability rates of electr(on)ic products August 2016; and NSF/ANSI 426 - 2018 Environmental Leadership and Corporate Social Responsibility Assessment of Servers

End of life treatment methodology - The methodology for recycling technologies and practices for this product generally follow the end-of-life treatement process as outlined by IEC/TR62635. See the process flow diagram to the right. Disassembly of the product is required to sort into recycling streams based on the infrastructure available to the dismantler. Generally circuit cards, backplanes, processors, etc. would go to a precious metal recycler. Metal covers, chasis, brackets, screws, etc to a metal simelter. Plastic parts variable to the beezel, covers, etc. would go to a plastic recycler.

The information here is based on IBM's knowledge as of the date of this document, which may be based on its records and information from third parties. This documentation applies to finished products that IBM newly puts on the market. Limitations for Customers: The Product information provided here is provided "ASI", without any express or implied warranty of any kind. This information is subject to change without notice; product information provided, however, that IBM reserves the right, in its discretion, to issue an update or modification to this Documentation if it believes it is appropriate to do so. The contents of this Documentation do not constitute either: (1) legal advice; (2) a legal opinion; or (2) any representation, warranty, or gurantee regarding a person's ability to comply with applicable legal requirements. This Documentation in no way modifies any agreements entered into ty IBM.



End-of-life treatment processes from IEC/TR 62635

Product end-of-life processing methods

47.6% Recycled

44.8% Resold

2.9% Waste-to-Energy

0.7% Landfill or Incineration

= 4% Reused

R_{rcv} = Recyclability rate