

Support Matrix for IBM System Storage DS3400

Supported OS	Supported IBM Servers	Controller Firmware	Multipath (MPIO) DSM	Host Bus Adapter (HBA)	Interconnect Fibre Switch	Other
Microsoft Windows 2003 R2 SP1 SP2 32 bit (x86) 64 bit (x64)	System x 3950* System x 3850 System x 3800 System x 3755 System x 3655 System x 3650 System x 3550 System x 3500 System x 3455 System x 3400 *All servers support PCI-x and PCI-e with the exception of System x 3950 which is PCI-x only.	Firmware Version v.06.17.xx.yy The above link supports both the firmware and NVSRAM.	MPIO Version v.01.01.35.17 MPIO Software is included in the Storage Manger Host Software package.	Qlogic System x Driver (all) storport v.9.1.2.17 PCI-x 2 Gb Bios 1.47 QLA234x PCI-x 4 Gb BIOS 1.12 QLA246x PCI-e 2Gb Bios 1.47 QLE236x PCI-e 4Gb Bios 1.12 QLE246x Emulex System x Driver (all)-v.1.20.a3-1h PCI-x - LP1100X BIOS/Firmware 5.02.a.1/2.10.a10 PCI-e - LPe1100X BIOS/Firmware 5.02.a.1/2.50.a6 Emulex BladeCenter HBA - LP1105-BC Driver 1.20A3-1h Firmware - 2.10a10 BIOS 5.02.a1 BladeCenter Driver (all) storport v.9.1.2.17 2GB HBAs Bios 1.47 IBM HS20 Fibre Channel Expansion Card IBM BladeCenter SFF Fibre Channel Expansion Card 4GB HBAs Bios 1.12 Qlogic 4Gb Standard Fibre Channel Expansion Card Qlogic 4Gb SFF Fibre Channel Expansion Card	IBM SAN fibre channel switch models: 2005-H16 FW: 5.x 2109-F16 FW: 3.x SAN 16B-2 FW: 6.x SAN 32B-3 FW: 6.x	For additional information on Storport drivers it is recommended that you search the Microsoft website for the latest Storport QFE.
	BladeCenter LS20-8850 HS21-8853 HS21-7995 HS20-8843 HS20-8832 Current server code is available via IBM Update Express. Download the most recent version here. Note: Servers can be used heterogeneously or homogeneously within a 4 node cluster.					