


System Service Information




Hot-Swap Hard Disk Drives



Orange/terracotta on a component indicates that the component can be hot-swapped. Hot-swap means that if the system, operating system, and configuration all support hot-swap capability, you can remove or install the component while the system is running.


Blue on a component indicates touch points. Touch points are where you can grip the component to remove or install it from the system, open or close a latch, and so on.

Hot-Swap Fans




ATTENTION: For proper cooling, do not leave cover off for more than 2 minutes at a time while system is running.


Hot-Swap Power Supplies



PCI Express/PCI-X Adapters



System Board



NOTE: When installing a second microprocessor, be sure to install a VRM.

Memory (Non-Mirrored)

Microprocessor #	DIMM Install Order
1	3, 6, 8, 2, 5, 7
2	11, 14, 16, 10, 13, 15

Memory (Mirrored)

Microprocessor #	DIMM Install Order
1	3&6, 2&5
2	11&14, 10&13

Red Outline is for Die Cut ONLY!

336 mm


Red Outline is for Die Cut ONLY!

MANUFACTURING NOTES:

1. Graphics shall conform to the Artwork above.
2. Ink colors to match PMS BlackC, PMS 1525C, and PMS 2718C.
3. Refer to label print part number 59Y3446 for manufacturing and material notes.

Must conform to Eng. Spec: 80X2324
Tolerances unless noted: Linear \pm 0.3

SI
metric



IBM			Art Part number 59Y3449	
EC number L79970F	Date 8/18/09	ID approval RA	Eng approval ET	
Title Label, System Service				
This document is the property of IBM. Its use is authorized only for responding to a request for quotation or for the performance of work for IBM. All questions must be referred to the IBM purchasing department.				