

IBM® BladeCenter S SAS RAID Module Interoperability Matrix

Section 1 – Hardware Options

BladeCenter Chassis	Type	Required
BladeCenter S (BC-S)	8886 / 1948	Yes

RAID Controller	Option / AAS Feature	Required
SAS RAID Module	43W3584 / 3734	Yes

Management Modules	Option / AAS Feature	Required
Advanced Management Module (AMM)	25R5778 / 3201	Yes

Battery Backup Unit (BBU) - One Per Module	Option / AAS Feature	Required
IBM BladeCenter RAID Battery Backup Module	Part of 43W3584 / NA (part of 3734)	

Note 1: 12 Disks Storage Module only support HX5, HS12, HS22, HS22V, HS23, HS23E.

Note 2: JS12, JS22, JS23, JS43, PS700/701/702, PS703/704 are supported when configured with 6 Disks Storage Module only and RSSM firmware level is 1.2.4.xxx and below.

Interoperability Matrix: SAS RAID Module – IBM BladeCenter S - Version 1.99 (12/23/2014)

TS2240 Tape Device (Connects to External SAS ports)	Optional
TS2250 Tape Device (Connects to External SAS ports)	Optional
TS2900 Tape Device (Connects to External SAS ports)	Optional
TS2230 Tape Device (Connects to External SAS ports)	Optional
TS2340 Tape Device (Connects to External SAS ports)	Optional
TS3100 Tape Device (Connects to External SAS ports)	Optional

Note: All levels in this document are minimum required levels or current levels available at the time of publication.

Interoperability Matrix: SAS RAID Module – IBM BladeCenter S - Version 1.99 (12/23/2014)

SUSE Linux Enterprise Server 11	11 – 2.6.27.42.-0.1 / 0.4.8-40.6.1; 11.1 – 2.6.32.12-0.7 / 0.4.8-40.21.1; 11.2 - 3.0.13-0.27; 11.3 - 3.0.76-0.11
Windows Server 2003 / 2008 /2012 / 2012 R2	Windows 2003: SP2; Windows 2008: SP1 / R2 SP1; Windows 2012 ; Windows 2012 R2
AIX	Refer to Note 4 above

Note: All levels in this document are minimum required levels or current levels available at the time of publication.

